



SAR TEST REPORT

Product Name: Multifunctional Tablet

Model Name: P100S

FCC ID: 2AC6AP100S

Issued For : Shenzhen Chainway Information Technology Co., Ltd
9F Building 2, Daqian Industrial Park, District 67, XingDong
Community, Xin'an Street, Bao'an District, Shenzhen,
Guangdong, China

Issued By : Shenzhen LGT Test Service Co., Ltd.
Room 205, Building 13, Zone B, Zhenxiong Industrial Park,
No.177, Renmin West Road, Jinsha, Kengzi Street,
Pingshan District, Shenzhen, Guangdong, China

Report Number: LGT24F082HA02

Sample Received Date: Aug. 16, 2024

Date of Test: Aug. 29, 2024~Oct. 23, 2024

Date of Issue: Dec. 04, 2024

Max. SAR (10g): Body: 1.096 W/kg

The test report is effective only with both signature and specialized stamp. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report only apply to the tested sample.



Table of Contents

1. General Information	5
1.1 EUT Description	5
1.2 Test Environment	7
1.3 Test Factory	7
2. Test Standards and Limits	8
3. SAR Measurement System	9
3.1 Definition of Specific Absorption Rate (SAR)	9
3.2 SAR System	9
4. Tissue Simulating Liquids	12
4.1 Simulating Liquids Parameter Check	12
5. SAR System Validation	14
5.1 Validation System	14
5.2 Validation Result	15
6. SAR Evaluation Procedures	16
7. EUT Antenna Location Sketch	17
7.1 SAR test exclusion consider table	18
8. EUT Test Position	24
8.1 Define Two Imaginary Lines on the Handset	24
8.2 Hotspot mode exposure position condition	25
9. Uncertainty	26
9.1 Measurement Uncertainty	26
9.2 System validation Uncertainty	27
10. Conducted Power Measurement	28
10.1 Test Result	28
10.2 Tune up Power	53
11. EUT and Test Setup Photo	57
11.1 EUT Photos	57
11.2 Setup Photos	60
12. SAR Result Summary	63
12.1 Body-worn and Hotspot SAR	63
12.2 Repeated SAR	68
12.3 Repeated SAR measurement	69
12.4 Simultaneous Multi-band Transmission Evaluation	70
13. Equipment List	72
Appendix A. System Validation Plots	73

**Appendix B. SAR Test Plots****91****Appendix C. Probe Calibration and Dipole Calibration Report****111****Revision History**

Rev.	Issue Date	Contents
00	Dec. 04, 2024	Initial Issue



TEST REPORT CERTIFICATION

Applicant Shenzhen Chainway Information Technology Co., Ltd
9F Building 2, Daqian Industrial Park, District 67, XingDong
Address Community, Xin'an Street, Bao'an District, Shenzhen,
Guangdong, China

Manufacture Shenzhen Chainway Information Technology Co., Ltd
9F Building 2, Daqian Industrial Park, District 67, XingDong
Address Community, Xin'an Street, Bao'an District, Shenzhen,
Guangdong, China

Product Name Multifunctional Tablet

Trademark CHAINWAY

Model Name P100S

Sample number LGT2408142-4

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
ANSI/IEEE Std. C95.1-1992 FCC 47 CFR Part 2 (2.1093) IEEE 1528: 2013	PASS

Prepared by:

Della He

Della He
Engineer

Approved by:

Vita Li

Vita Li
Manager





1. General Information

Environmental evaluation measurements of specific absorption rate (SAR) distributions in emulated human head and body tissues exposed to radio frequency (RF) radiation from wireless portable devices for compliance with the rules and regulations of the U.S. Federal Communications Commission (FCC).

1.1 EUT Description

Product Name	Multifunctional Tablet	
Trademark	CHAINWAY	
Model Name	P100S	
Series Model	N/A	
Model Difference	N/A	
Device Category	Portable	
Product stage	Production unit	
RF Exposure Environment	General Population / Uncontrolled	
Hardware Version	P100S_Hardware_version	
Software Version	P100S_Hardware_version	
Frequency Range	GSM 850: 824 ~ 849 MHz PCS 1900: 1850 ~ 1910 MHz WCDMA Band II: 1850 ~ 1910 MHz WCDMA Band IV: 1710 ~ 1755 MHz WCDMA Band V: 824 ~ 849 MHz LTE Band 2: 1850 ~ 1910 MHz LTE Band 4: 1710 ~ 1755 MHz LTE Band 5: 824 ~ 849 MHz LTE Band 7: 2500 ~ 2570 MHz LTE Band 12: 699 ~ 716 MHz LTE Band 17: 704 ~ 716 MHz LTE Band 38: 2570 ~ 2620 MHz LTE Band 40: 2305 ~ 2315 MHz / 2350 ~ 2360 MHz LTE Band 41: 2496 ~ 2690 MHz WLAN 802.11b/g/n20: 2412 MHz ~ 2462 MHz WLAN 802.11n40: 2422 MHz ~ 2452 MHz WLAN 802.11a/n20/n40/ac20/ac40/ac80: 5150 ~ 5250 MHz WLAN 802.11a/n20/n40/ac20/ac40/ac80: 5250 ~ 5350 MHz WLAN 802.11a/n20/n40/ac20/ac40/ac80: 5470 ~ 5725 MHz WLAN 802.11a/n20/n40/ac20/ac40/ac80: 5725 ~ 5850 MHz Bluetooth: 2402 ~ 2480 MHz NFC: 13.56 MHz	
Max. Reported SAR(1g): (Limit: 1.6W/kg) Test distance: 0mm	Mode	Body Worn and Hotspot (W/ kg)
	GSM 850	0.798
	PCS 1900	0.886
	WCDMA Band II	1.086
	WCDMA Band IV	0.795
	WCDMA Band V	0.894
	LTE Band 2	0.954
	LTE Band 4	0.992
	LTE Band 5	0.655
	LTE Band 7	1.095
	LTE Band 12	0.539



	LTE Band 17	0.565
	LTE Band 38	1.029
	LTE Band 40	1.003
	LTE Band 41	1.096
	2.4G WLAN	0.285
	5.2G WLAN	0.251
	5.3G WLAN	0.295
	5.6G WLAN	0.130
	5.8G WLAN	0.189
	Bluetooth	0.315
	NFC ^{Note}	0.0000002
1-g Sum SAR		1.391
Battery	Battery1: Capacity: 10000mAh Rated Voltage: 3.85V Battery2: Capacity: 78mAh Rated Voltage: 3.8V	
Description test modes	SIM 1 and SIM 2 is a chipset unit and tested as single chipset, SIM 1 is used to tested.	
Operating Mode:	GSM: GSM Voice; GPRS/EGPRS Class 12 WCDMA: RMC, HSDPA, HSUPA Release 6 LTE: QPSK, 16QAM 2.4G WLAN: 802.11b(DSSS): CCK, DQPSK, DBPSK 802.11g(OFDM): BPSK, QPSK, 16-QAM, 64-QAM 802.11n(OFDM): BPSK, QPSK, 16-QAM, 64-QAM 5G WLAN: 802.11a(OFDM): BPSK, QPSK, 16-QAM, 64-QAM 802.11n(OFDM): BPSK, QPSK, 16-QAM, 64-QAM 802.11ac (OFDM): BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM Bluetooth: GFSK + π /4DQPSK+8DPSK BLE: GFSK NFC: ASK	
Antenna Specification	GSM/WCDMA/LTE: FPC Antenna Bluetooth: FPC Antenna WLAN:FPC Antenna NFC: Coil Antenna	
Operating Mode	Maximum continuous output	
SIM Card	Support dual-SIM, dual standby, the multiple SIM card with two lines cannot trans mitting at the same time	
Hotspot Mode	Support	
DTM Mode	Not Support	
Note 1: The NFC value was Estimated.		



1.2 Test Environment

Ambient conditions in the SAR laboratory:

Items	Required
Temperature (°C)	18-25
Humidity (%RH)	30-70

1.3 Test Factory

Company Name:	Shenzhen LGT Test Service Co., Ltd.
Address:	Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China
Accreditation Certificate	FCC Registration No.: 746540
	A2LA Certificate No.: 6727.01
	IC Registration No.: CN0136



2. Test Standards and Limits

No.	Identity	Document Title
1	47 CFR Part 2	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	ANSI/IEEE Std. C95.1-1992	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz
3	IEEE Std. 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
4	FCC KDB 447498 D01 v06	Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies
5	FCC KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz
6	FCC KDB 865664 D02 v01r02	RF Exposure Reporting
7	FCC KDB 941225 D01 v03r01	SAR Measurement Procedures for 3G Devices
8	FCC KDB 941225 D05 v02r05	SAR for LTE Devices
9	FCC KDB 941225 D06 v02r01	Hotspot Mode SAR
10	FCC KDB 648474 D04 v01r03	SAR Evaluation Considerations for Wireless Handsets
11	FCC KDB 248227 D01 Wi-Fi SAR v02r02	SAR Considerations for 802.11 Devices
12	616217 D04 SAR for laptop and tablets v01r02	SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers

(A). Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body Partial-Body Hands, Wrists, Feet and Ankles

0.4 8.0 20.0

(B). Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body Partial-Body Hands, Wrists, Feet and Ankles

0.08 1.6 4.0

NOTE: Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

NOTE
GENERAL POPULATION/UNCONTROLLED EXPOSURE
PARTIAL BODY LIMIT
1.6 W/kg



3. SAR Measurement System

3.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by


$$SAR = \frac{\sigma E^2}{\rho}$$

Where: σ is the conductivity of the tissue;

ρ is the mass density of the tissue and E is the RMS electrical field strength.

3.2 SAR System

MVG SAR System Diagram:



COMOSAR is a system that is able to determine the SAR distribution inside a phantom of human being according to different standards. The COMOSAR system consists of the following items:

- Main computer to control all the system
- 6 axis robot
- Data acquisition system
- Miniature E-field probe
- Phone holder
- Head simulating tissue

The following figure shows the system.



The EUT under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The OpenSAR software computes the results to give a SAR value in a 1g or 1g mass.

3.2.1 Probe

For the measurements the Specific Dosimetric E-Field Probe SN 04/22 EPGO364 with following specifications is used

- Probe Length: 330 mm
- Length of Individual Dipoles: 2mm
- Maximum external diameter: 8 mm
- Probe Tip External Diameter: 2.5 mm
- Distance between dipole/probe extremity: 1 mm
- Dynamic range: 0.01-100 W/kg
- Probe linearity: 3%
- Axial Isotropy: < 0.10 dB
- Spherical Isotropy: < 0.10 dB
- Calibration range: 600 MHz to 6 GHz for head & body simulating liquid.
- Angle between probe axis (evaluation axis) and surface normal line: less than 30°



Figure 1-MVG COMOSAR Dosimetric E field Probe

3.2.2 Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.




Figure-SN 06/22 SAM 148



Figure-SN 06/22 ELLI 51

3.2.3 Device Holder



The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of ± 0.5 mm would produce a SAR uncertainty of ± 20 %. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.



4. Tissue Simulating Liquids

4.1 Simulating Liquids Parameter Check

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values

The uncertainty due to the liquid conductivity and permittivity arises from two different sources. The first source of error is the deviation of the liquid conductivity from its target value (max _ 5 %) and the second source of error arises from the measurement procedures used to assess conductivity. The uncertainty shall be assessed using a rectangular probability For 1 g averaging, the maximum weighting coefficient for SAR is 0,5.

IEEE SCC-34/SC-2 RECOMMENDED TISSUE DIELECTRIC PARAMETERS

The head and body tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 have been incorporated in the following table.

Frequency	ϵ_r	σ 10g S/m
300	45.3	0.87
450	43.5	0.87
750	41.9	0.89
835	41.5	0.90
900	41.5	0.97
1450	40.5	1.20
1800 to 2000	40.0	1.40
2100	39.8	1.49
2450	39.2	1.80
2600	39.0	1.96
3000	38.5	2.40
3500	37.9	2.91
4000	37.4	3.43
4500	36.8	3.94
5000	36.2	4.45
5200	36.0	4.66
5400	35.8	4.86
5600	35.5	5.07
5800	35.3	5.27



LIQUID MEASUREMENT RESULTS

Date	Ambient		Simulating Liquid		Parameters	Target	Measured	Deviation %	Limit d %
	Temp. [°C]	Humidity %	Frequency (MHz)	Temp. [°C]					
2024-09-06	23.3	41	750	23.1	Permittivity	41.90	41.39	-1.22	±5
					Conductivity	0.89	0.92	3.60	±5
2024-10-16	23.5	20.9	835	23.2	Permittivity	41.38	41.94	1.36	±5
					Conductivity	0.85	0.87	2.53	±5
2024-10-20	21.7	44	1800	21.5	Permittivity	40.00	40.56	1.40	±5
					Conductivity	1.40	1.42	1.43	±5
2024-10-18	21.8	44	1900	21.5	Permittivity	40.00	41.28	3.20	±5
					Conductivity	1.40	1.41	0.71	±5
2024-09-05	20.6	20.8	2450	20.3	Permittivity	39.20	39.79	1.51	±5
					Conductivity	1.80	1.76	-2.22	±5
2024-10-13	22.5	59	2600	22.2	Permittivity	39.00	39.39	1.00	±5
					Conductivity	1.96	1.95	-0.51	±5
2024-08-31	22.4	43	5200	22	Permittivity	36.00	36.94	2.61	±5
					Conductivity	4.66	4.64	-0.43	±5
2024-08-29	22.5	46	5600	22.2	Permittivity	35.60	36.13	1.49	±5
					Conductivity	5.06	5.12	1.19	±5
2024-10-23	22.6	46	5800	22.3	Permittivity	35.40	35.90	1.41	±5
					Conductivity	5.26	5.31	0.95	±5




5. SAR System Validation

5.1 Validation System

Each MVG system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the MVG software, enable the user to conduct the system performance check and system validation. System kit includes a dipole, and dipole device holder.

The system check verifies that the system operates within its specifications. It's performed daily or before every SAR measurement. The system check uses normal SAR measurement in the flat section of the phantom with a matched dipole at a specified distance. The system validation setup is shown as below.





5.2 Validation Result

Comparing to the original SAR value provided by MVG, the validation data should be within its specification of $\pm 10\%$.

Date	Freq.	Power	Tested Value	Normalized SAR	Target SAR	Tolerance	Limit
	(MHz)	(mW)	(W/Kg)	(W/kg)	1g(W/kg)	(%)	(%)
2024-09-06	750	100	0.824	8.24	8.27	-0.36	10
2024-10-16	835	100	0.936	9.36	9.75	-4.00	10
2024-10-20	1800	100	3.869	38.69	39.06	-0.95	10
2024-10-18	1900	100	4.086	40.86	40.85	0.02	10
2024-09-05	2450	100	5.410	54.10	54.28	-0.33	10
2024-10-13	2600	100	5.666	56.66	56.58	0.14	10
2024-08-31	5200	100	8.100	81.00	80.97	0.04	10
2024-08-29	5600	100	8.113	81.13	80.96	0.21	10
2024-10-23	5800	100	8.133	81.33	81.67	-0.42	10

Note:

1. The tolerance limit of System validation $\pm 10\%$.
2. The dipole input power (forward power) was 100 mW.
3. The results are normalized to 1 W input power.



6. SAR Evaluation Procedures

The procedure for assessing the average SAR value consists of the following steps:

The following steps are used for each test position

- Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.


➤ Area Scan & Zoom Scan

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01 quoted below.

When the 1-g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

7. EUT Antenna Location Sketch

It is a Multifunctional Tablet, support GSM/WCDMA/LTE/WLAN/BT mode.



Left side

Antenna Separation Distance(mm)					
ANT	Back Side	Left Side	Right Side	Top Side	Bottom Side
WLAN/BT	≤5	245	≤5	≤5	158
WWAN	≤5	67	140	≤5	150

Note 1: The antenna information refer the manufacturer provide report, applicable only to the tested sample identified in the report.



7.1 SAR test exclusion consider table

The WWAN/WLAN/BT SAR evaluation of Maximum power (dBm) summing tolerance.

Exposure Position	Wireless Interface	GSM850	PCS1900	WCDMA II	WCDMA IV	WCDMA V
	Calculated Frequency (MHz)	848.8	1850.2	1907.6	1752.4	846.6
	Maximum Turn-up power (dBm)	33.5	26	21	20	24.5
	Maximum rated power(mW)	2238.72	398.11	125.89	100.00	281.84
Back Side	Separation distance (mm)	≤5	≤5	≤5	≤5	≤5
	exclusion threshold(mW)	16.28	11.03	10.86	11.33	16.30
	Testing required?	YES	YES	YES	YES	YES
Left Edge	Separation distance (mm)	67	67	67	67	67
	exclusion threshold(mW)	983.32	1898.80	1952.62	1807.30	981.40
	Testing required?	YES	NO	NO	NO	NO
Right Edge	Separation distance (mm)	140	140	140	140	140
	exclusion threshold(mW)	983.32	1898.80	1952.62	1807.30	163.02
	Testing required?	YES	NO	NO	NO	YES
Top Edge	Separation distance (mm)	≤5	≤5	≤5	≤5	≤5
	exclusion threshold(mW)	16.28	11.03	10.86	11.33	16.30
	Testing required?	YES	YES	YES	YES	YES
Bottom Edge	Separation distance (mm)	150	150	150	150	150
	exclusion threshold(mW)	983.32	1898.80	1952.62	1807.30	981.40
	Testing required?	YES	NO	NO	NO	NO



Exposure Position	Wireless Interface	LTE Band 2	LTE Band 4	LTE Band 5	LTE Band 7	LTE Band 12
	Calculated Frequency (MHz)	1900	1732.5	829	2535	707.5
	Maximum Turn-up power (dBm)	20.5	20	24.5	20	21
	Maximum rated power(mW)	112.20	100.00	281.84	100.00	125.89
Back Side	Separation distance (mm)	≤5	≤5	≤5	≤5	≤5
	exclusion threshold(mW)	10.88	11.40	16.47	9.42	17.83
	Testing required?	YES	YES	YES	YES	YES
Left Edge	Separation distance (mm)	67	67	67	67	67
	exclusion threshold(mW)	1945.49	1788.71	966.11	2544.71	862.25
	Testing required?	NO	NO	NO	NO	NO
Right Edge	Separation distance (mm)	140	140	140	140	140
	exclusion threshold(mW)	1945.49	1788.71	966.11	2544.71	862.25
	Testing required?	NO	NO	NO	NO	NO
Top Edge	Separation distance (mm)	≤5	≤5	≤5	≤5	≤5
	exclusion threshold(mW)	10.88	11.40	16.47	9.42	17.83
	Testing required?	YES	YES	YES	YES	YES
Bottom Edge	Separation distance (mm)	150	150	150	150	150
	exclusion threshold(mW)	1945.49	1788.71	966.11	2544.71	862.25
	Testing required?	NO	NO	NO	NO	NO



Exposure Position	Wireless Interface	LTE Band 17	LTE Band 38	LTE Band 40	LTE Band 41
	Calculated Frequency (MHz)	709	2595	2355	2506
	Maximum Turn-up power (dBm)	24	24	13.5	24.5
	Maximum rated power(mW)	251.19	251.19	22.39	281.84
Back Side	Separation distance (mm)	≤5	≤5	≤5	≤5
	exclusion threshold(mW)	17.81	9.31	9.77	9.48
	Testing required?	YES	YES	YES	YES
Left Edge	Separation distance (mm)	67	67	67	67
	exclusion threshold(mW)	863.51	2601.62	2374.25	2517.22
	Testing required?	NO	NO	NO	NO
Right Edge	Separation distance (mm)	140	140	140	140
	exclusion threshold(mW)	863.51	2601.62	2374.25	2517.22
	Testing required?	NO	NO	NO	NO
Top Edge	Separation distance (mm)	≤5	≤5	≤5	≤5
	exclusion threshold(mW)	17.81	9.31	9.77	9.48
	Testing required?	YES	YES	YES	YES
Bottom Edge	Separation distance (mm)	150	150	150	150
	exclusion threshold(mW)	863.51	2601.62	2374.25	2517.22
	Testing required?	NO	NO	NO	NO



Exposure Position	Wireless Interface	BT	2.4G WLAN	5.2G WLAN
	Calculated Frequency (MHz)	2437	5200	2441
	Maximum Turn-up power (dBm)	14.5	13	1
	Maximum rated power(mW)	28.18	19.95	1.26
Back Side	Separation distance (mm)	≤5	≤5	≤5
	exclusion threshold(mW)	9.61	6.58	9.60
	Testing required?	YES	YES	NO
Left Edge	Separation distance (mm)	245	245	245
	exclusion threshold(mW)	2581.83	1145.78	2585.83
	Testing required?	NO	NO	NO
Right Edge	Separation distance (mm)	≤5	≤5	≤5
	exclusion threshold(mW)	9.61	6.58	9.60
	Testing required?	YES	YES	NO
Top Edge	Separation distance (mm)	≤5	≤5	≤5
	exclusion threshold(mW)	9.61	6.58	9.60
	Testing required?	YES	YES	NO
Bottom Edge	Separation distance (mm)	158	158	158
	exclusion threshold(mW)	2581.83	1145.78	2585.83
	Testing required?	NO	NO	NO



Exposure Position	Wireless Interface	5.3G WLAN	5.6G WLAN	5.8G WLAN
	Calculated Frequency (MHz)	5260	5700	5825
	Maximum Turn-up power (dBm)	12.5	13	12.5
	Maximum rated power(mW)	17.78	19.95	17.78
Back Side	Separation distance (mm)	≤5	≤5	≤5
	exclusion threshold(mW)	6.54	6.28	6.22
	Testing required?	YES	YES	YES
Left Edge	Separation distance (mm)	245	245	245
	exclusion threshold(mW)	2015.40	2012.83	2012.15
	Testing required?	NO	NO	NO
Right Edge	Separation distance (mm)	≤5	≤5	≤5
	exclusion threshold(mW)	6.54	6.28	6.22
	Testing required?	YES	YES	YES
Top Edge	Separation distance (mm)	≤5	≤5	≤5
	exclusion threshold(mW)	6.54	6.28	6.22
	Testing required?	YES	YES	YES
Bottom Edge	Separation distance (mm)	158	158	158
	exclusion threshold(mW)	1145.40	1142.83	1142.15
	Testing required?	NO	NO	NO

Note:

1. maximum power is the source-based time-average power and represents the maximum RF output power among production units.
2. per KDB 447498 D01, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
3. per KDB 447498 D01, standalone SAR test exclusion threshold is applied; if the distance of the antenna to the user is <25mm, 25mm is user to determine SAR exclusion threshold
4. per KDB 447498 D01, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distance ≤50mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$

$$f(\text{GHz}) \text{ is the RF channel transmit frequency in GHz. Power and distance are rounded to the nearest mW and mm before calculation.}$$

The result is rounded to one decimal place for comparison



For <50mm distance, we just calculate mW of the exclusion threshold value(3.0)to do compare


5. per KDB 447498 D01, at 100 MHz to 6GHz and for test separation distances >50mm, the SAR test exclusion threshold is determined according to the following
 - a)[threshold at 50mm in step 1]+(test separation distance -50mm)*(f (MHz)/150)]mW, at 100 MHz to 1500 MHz
 - b) [threshold at 50mm in step1]+(test separation distance -50mm) *10]mW at > 1500MHz and ≤ 6GHz
6. Per KDB 248227 D01, choose the highest output power channel to test SAR and determine further SAR exclusion 8.for each frequency band ,testing at higher data rates and higher order modulations is not required when the maximum average output power for each of each of these configurations is less than 1/4db higher than those measured at the lower data rate than 11b mode ,thus the SAR can be excluded.
7. Per KDB 616217 D04, SAR evaluation for the front surface of tablet display screens are generally not necessary.

8. EUT Test Position

This EUT was tested in Right Cheek, Right Titled, Left Cheek, Left Titled, Front Face and Rear Face.


8.1 Define Two Imaginary Lines on the Handset

- (1) The vertical centerline passes through two points on the front side of the handset the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the handset.
- (2) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
- (3) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.



Cheek Position

- 1) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- 2) To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost





Title Position

- (1) To position the device in the “cheek” position described above.
- (2) While maintaining the device in the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until with the ear is lost.




Body-worn Position Conditions:

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB Publication 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. When the same wireless transmission configuration is used for testing body-worn accessory and hotspot mode SAR, respectively, in voice and data mode, SAR results for the most conservative *test separation distance* configuration may be used to support both SAR conditions. When the *reported* SAR for a body-worn accessory, measured without a headset connected to the handset, is $> 1.2 \text{ W/kg}$, the highest *reported* SAR configuration for that wireless mode and frequency band should be repeated for the body-worn accessory with a headset attached to the handset.



8.2 Hotspot mode exposure position condition

For handsets that support hotspot mode operations, with wireless router capabilities and various web browsing function, the relevant hand and body exposure condition are tested according to the hotspot SAR procedures in KDB 941225. A test separation distance of 10 mm is required between the phantom and all surface and edges with a transmitting antenna located within 25 mm from that surface or edge. When form factor of a handset is smaller than 9cm x 5cm, a test separation distance of 5mm (instead of 10mm) is required for testing hotspot mode. When the separate distance required for body-worn accessory testing is larger than or equal to that tested for hotspot mode, in the same wireless mode and for the same surface of the phone, the hotspot mode SAR data may be used to support body-worn accessory SAR compliance for that particular configuration (surface).





9. Uncertainty

9.1 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in IEEE 1528: 2013. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Uncertainty Component	Tol (+/- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+/-%)	10g Ui (+/-%)	vi
Measurement System								
Probe calibration	5.8	N	1	1	1	5.8	5.8	∞
Axial Isotropy	3.5	R	$\sqrt{3}$	$\sqrt{0.5}$	$\sqrt{0.5}$	1.43	1.43	∞
Hemispherical Isotropy	5.9	R	$\sqrt{3}$	$\sqrt{0.5}$	$\sqrt{0.5}$	2.41	2.41	∞
Boundary effect	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	4.7	R	$\sqrt{3}$	1	1	2.71	2.71	∞
System detection limits	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Readout Electronics	0.5	N	1	1	1	0.50	0.50	∞
Response Time	0	R	$\sqrt{3}$	1	1	0.00	0.00	∞
Integration Time	1.4	R	$\sqrt{3}$	1	1	1.81	1.81	∞
RF ambient conditions-Noise	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient conditions-reflections	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner mechanical tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to phantom shell	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation, Interpolation and Integration Algorithms for Max, SAR	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
Test sample Related								
Test sample positioning	2.6	N	1	1	1	2.60	2.60	11
Device holder uncertainty	3	N	1	1	1	3.00	3.00	7
Output Power Variation - SAR Drift Measurement	5	R	$\sqrt{3}$	1	1	2.89	2.89	∞
SAR scaling	2	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Phantom and tissue parameters								
Phantom uncertainty (shape and thickness uncertainty)	4	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	2	N	1	1	0.84	2.00	1.68	∞
Liquid Conductivity - Measurement Uncertainty)	4	N	1	0.78	0.71	3.12	2.84	5
Liquid Permittivity - Measurement Uncertainty	5	N	1	0.23	0.26	1.15	1.30	5
Liquid Conductivity (Temperature Uncertainty)	2.5	R	$\sqrt{3}$	0.78	0.71	1.13	1.02	∞
Liquid Permittivity (Temperature Uncertainty)	2.5	R	$\sqrt{3}$	0.23	0.26	0.33	0.38	∞
Combined Standard Uncertainty		RSS				10.47	10.34	
Expanded Uncertainty (95% Confidence interval)		K				20.95	20.69	



9.2 System validation Uncertainty

Uncertainty Component	Tol (+ - %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	vi
Measurement System								
Probe calibration	5.8	N	1	1	1	5.8	5.8	∞
Axial Isotropy	3.5	R	$\sqrt{3}$	1	1	2.02	2.02	∞
Hemispherical Isotropy	5.9	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Boundary effect	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	4.7	R	$\sqrt{3}$	1	1	0.71	0.71	∞
System detection limits	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	0	N	$\sqrt{3}$	0	0	0.00	0.00	∞
Readout Electronics	0.5	N	1	1	1	0.50	0.50	∞
Response Time	0	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Integration Time	1.4	R	$\sqrt{3}$	0	0	0.00	0.00	∞
RF ambient conditions-Noise	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient conditions- reflections	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner mechanical tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to phantom shell	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation, Interpolation and Integration Algorithms for Max, SAR	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
Dipole								
Deviation of Experimental Source from Numerical Source	5	N	1	1	1	5.00	5.00	∞
Input Power and SAR Drift Measurement	0.5	R	$\sqrt{3}$	1	1	0.29	0.29	∞
Dipole Axis to Liquid Distance	2	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Phantom and Tissue Parameters								
Phantom uncertainty (shape and thickness uncertainty)	4	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	2	N	1	1	0.84	2.00	1.68	∞
Liquid Conductivity - Measurement Uncertainty)	4	N	1	0.78	0.71	3.12	2.84	5
Liquid Permittivity - Measurement Uncertainty	5	N	1	0.23	0.26	1.15	1.30	5
Liquid Conductivity (Temperature Uncertainty)	2.5	R	$\sqrt{3}$	0.78	0.71	1.13	1.02	∞
Liquid Permittivity (Temperature Uncertainty)	2.5	R	$\sqrt{3}$	0.23	0.26	0.33	0.38	∞
Combined Standard Uncertainty		RSS				10.16	10.03	
Expanded Uncertainty (95% Confidence interval)		K				20.32	20.06	



10. Conducted Power Measurement

10.1 Test Result

Burst Average Power (dBm)						
Band	GSM 850			PCS 1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.6	848.8	1850.2	1880.0	1909.8
GSM (GMSK, 1-Slot)	34.26	34.21	34.40	24.38	24.86	24.91
GPRS (GMSK, 1-Slot)	34.19	34.18	34.34	24.43	24.91	24.97
GPRS (GMSK, 2-Slot)	32.93	32.80	32.95	24.33	24.71	24.77
GPRS (GMSK, 3-Slot)	30.93	30.58	30.87	24.12	24.51	24.66
GPRS (GMSK, 4-Slot)	29.55	29.35	29.74	23.87	24.30	24.29
EGPRS (8PSK, 1-Slot)	26.52	26.87	26.70	26.77	26.15	26.13
EGPRS (8PSK, 2-Slot)	25.63	25.26	25.19	24.60	24.49	24.38
EGPRS (8PSK, 3-Slot)	22.64	22.57	22.97	22.08	22.02	21.65
EGPRS (8PSK, 4-Slot)	20.81	20.67	20.92	20.36	20.21	20.15
Remark: GPRS, CS4 coding scheme. EGPRS, MCS5 coding scheme. Multi-Slot Class 8, Support Max 4 downlink, 1 uplink, 5 working link Multi-Slot Class 10, Support Max 4 downlink, 2 uplink, 5 working link Multi-Slot Class 12, Support Max 4 downlink, 4 uplink, 5 working link						

Frame- Average Power(dBm)						
Band	GSM 850			PCS 1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.6	848.8	1850.2	1880.0	1909.8
GSM (GMSK, 1-Slot)	25.23	25.18	25.37	15.35	15.83	15.88
GPRS (GMSK, 1-Slot)	25.16	25.15	25.31	15.40	15.88	15.94
GPRS (GMSK, 2-Slot)	26.91	26.78	26.93	18.31	18.69	18.75
GPRS (GMSK, 3-Slot)	26.67	26.32	26.61	19.86	20.25	20.40
GPRS (GMSK, 4-Slot)	26.54	26.34	26.73	20.86	21.29	21.28
EGPRS (8PSK, 1-Slot)	17.49	17.84	17.67	17.74	17.12	17.10
EGPRS (8PSK, 2-Slot)	19.61	19.24	19.17	18.58	18.47	18.36
EGPRS (8PSK, 3-Slot)	18.38	18.31	18.71	17.82	17.76	17.39
EGPRS (8PSK, 4-Slot)	17.80	17.66	17.91	17.35	17.20	17.14
Remark: 1. SAR testing was performed on the maximum frame-averaged power mode. 2. The frame-averaged power is linearly proportion to the slot number configured and it is linearly scaled the maximum Burst - averaged power based on time slots. The calculated method is shown as below: Frame-averaged power = Burst averaged power (1 TX Slot) – 9.03 dB Frame-averaged power = Burst averaged power (2 TX Slots) – 6.02 dB Frame-averaged power = Burst averaged power (3 TX Slots) - 4.26 dB Frame-averaged power = Burst averaged power (4 TX Slots) – 3.01 dB						



WCDMA

Band	WCDMA Band 2			WCDMA Band 4			WCDMA Band 5		
Channel	9262	9400	9538	1312	1450	1513	4132	4182	4233
Frequency (MHz)	1852.4	1880	1907.6	1712.6	1740	1752.4	826.4	836.4	846.6
RMC 12.2Kbps	21.46	21.41	21.57	20.79	20.87	20.94	25.03	25.07	24.92
HSDPA Subtest-1	20.57	20.60	20.69	19.84	19.95	19.98	24.03	24.08	23.96
HSDPA Subtest-2	20.08	20.18	20.21	19.33	19.40	19.47	23.46	23.43	23.72
HSDPA Subtest-3	18.89	19.01	19.00	18.21	18.23	18.58	22.65	22.62	22.23
HSDPA Subtest-4	18.77	18.88	19.34	18.49	18.44	18.69	22.41	22.56	22.66
HSUPA Subtest-1	19.50	20.30	20.50	19.13	19.69	19.73	23.11	23.86	23.82
HSUPA Subtest-2	20.37	20.36	20.54	19.66	19.83	19.89	24.06	23.94	23.87
HSUPA Subtest-3	18.63	19.23	19.20	18.02	18.57	18.65	22.21	22.76	22.55
HSUPA Subtest-4	20.48	20.52	20.65	19.78	19.92	19.97	24.05	24.10	23.94
HSUPA Subtest-5	19.07	19.78	19.99	18.26	19.14	19.10	22.80	23.44	23.18

According to 3GPP 25.101 sub-clause 6.2.2, the maximum output power is allowed to be reduced by following the table.

Table 6.1A: UE maximum output power with HS-DPCCH and E-DCH

UE Transmit Channel Configuration	CM (db)	MPR (db)
For all combinations of ,DPDCH,DPCCH HS-DPDCH,E-DPDCH and E-DPCCH	$0 \leq CM \leq 3.5$	$MAX(CM-1,0)$
Note: CM=1 for $\beta_c/\beta_d=12/15$, $\beta_{hs}/\beta_c=24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.		

The device supports MPR to solve linearity issues (ACLR or SEM) due to the higher peak-to average ratios (PAR) of the HSUPA signal. This prevents saturating the full range of the TX DAC inside of device and provides a reduced power output to the RF transceiver chip according to the Cubic Metric (a function of the combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH).

When E-DPDCH channels are present the beta gains on those channels are reduced firsts to try to get the power under the allowed limit. If the beta gains are lowered as far as possible, then a hard limiting is applied at the maximum allowed level.

The SW currently recalculates the cubic metric every time the beta gains on the E-DPDCH are reduced. The cubic metric will likely get lower each time this is done .However, there is no reported reduction of maximum output power in the HSUPA mode since the device also provides a compensation for the power back-off by increasing the gain of TX_AGC in the transceiver (PA) device.

The end effect is that the DUT output power is identical to the case where there is no MPR in the device.



2.4G WLAN

2.4GWIFI				
Mode	Channel Number	Frequency (MHz)	Output Power (dBm)	Output Power (mW)
802.11b	1	2412	14.98	31.48
	6	2437	15.22	33.27
	11	2462	15.11	32.43
802.11g	1	2412	13.24	21.09
	6	2437	13.43	22.03
	11	2462	13.31	21.43
802.11 n-HT20	1	2412	12.25	16.79
	6	2437	12.10	16.22
	11	2462	12.19	16.56
802.11 n-HT40	3	2422	12.52	17.86
	6	2437	12.52	17.86
	9	2452	12.54	17.95

Bluetooth

BT				
Mode	Channel Number	Frequency (MHz)	Average Power (dBm)	Output Power (mW)
GFSK(1Mbps)	0	2402	1.61	1.45
	39	2441	1.95	1.57
	78	2480	1.74	1.49
$\pi/4$ -QPSK(2Mbps)	0	2402	0.93	1.24
	39	2441	1.25	1.33
	78	2480	1.04	1.27
8DPSK(3Mbps)	0	2402	0.93	1.24
	39	2441	1.20	1.32
	78	2480	1.06	1.28

BLE

BLE				
Mode	Channel Number	Frequency (MHz)	Average Power (dBm)	Output Power (mW)
GFSK(1Mbps)	0	2402	7.32	5.40
	19	2440	7.55	5.69
	39	2480	7.27	5.33
GFSK(2Mbps)	0	2402	7.32	5.40
	19	2440	7.53	5.66
	39	2480	7.32	5.40



WLAN (5.2Gband)

5.2G WLAN				
Mode	Channel Number	Frequency (MHz)	Output Power (dBm)	Output Power (mW)
802.11a20	36	5180	13.25	21.13
	40	5200	13.59	22.86
	48	5240	13.13	20.56
802.11 n-HT20	36	5180	12.33	17.10
	40	5200	11.98	15.78
	48	5240	12.04	16.00
802.11 n-HT40	38	5190	11.99	15.81
	46	5230	12.50	17.78
802.11ac-VHT20	36	5180	11.90	15.49
	40	5200	12.34	17.14
	48	5240	12.44	17.54
802.11ac-VHT40	38	5190	12.00	15.85
	46	5230	12.12	16.29
802.11ac-VHT80	42	5210	11.84	15.28

WLAN (5.3G band)5.3G WLAN				
Mode	Channel Number	Frequency (MHz)	Output Power (dBm)	Output Power (mW)
802.11a20	52	5260	13.20	20.89
	60	5300	12.98	19.86
	64	5320	12.99	19.91
802.11 n-HT20	52	5260	12.51	17.82
	60	5300	12.31	17.02
	64	5320	11.82	15.21
802.11 n-HT40	54	5270	12.52	17.86
	62	5310	12.23	16.71
802.11ac-VHT20	52	5260	12.44	17.54
	60	5300	12.38	17.30
	64	5320	12.38	17.30
802.11ac-VHT40	54	5270	11.98	15.78
	62	5310	11.80	15.14
802.11ac-VHT80	58	5290	11.68	14.72



WLAN (5.6G band)

5.6G WLAN				
Mode	Channel Number	Frequency (MHz)	Output Power (dBm)	Output Power (mW)
802.11a20	100	5500	12.50	17.78
	116	5580	12.94	19.68
	140	5700	13.66	23.23
802.11 n-HT20	100	5500	12.50	17.78
	116	5580	12.94	19.68
	140	5700	13.66	23.23
802.11 n-HT40	102	5510	11.29	13.46
	110	5550	11.73	14.89
	134	5670	12.18	16.52
802.11ac-VHT20	100	5500	12.12	16.29
	116	5580	12.30	16.98
	140	5700	12.48	17.70
802.11ac-VHT40	102	5510	11.11	12.91
	110	5550	11.10	12.88
	134	5670	11.98	15.78
802.11ac-VHT80	106	5530	11.09	12.85
	122	5610	11.65	14.62
	138	5690	12.50	17.78

WLAN (5.8G band)

5.8G WLAN				
Mode	Channel Number	Frequency (MHz)	Output Power (dBm)	Output Power (mW)
802.11a20	149	5745	13.46	22.18
	157	5785	13.32	21.48
	165	5825	13.48	22.28
802.11 n-HT20	149	5745	12.31	17.02
	157	5785	12.16	16.44
	165	5825	12.85	19.28
802.11 n-HT40	151	5755	12.30	16.98
	159	5795	12.77	18.92
802.11ac-VHT20	149	5745	12.27	16.87
	157	5785	12.17	16.48
	165	5825	12.30	16.98
802.11ac-VHT40	151	5755	12.21	16.63
	159	5795	12.10	16.22
802.11ac-VHT80	155	5775	12.10	16.22

NFC

Field strength(dBuV/m)	ERP(dBm)
50.38	-44.82

Note. The power of this EUT NFC is -44.82dBm (0.00003mW), this power is less than the defined low power exclusion level (Pmax: 39 mW), so NFC is exemption.



LTE Conducted Power

General Note:

1. Anritsu CMW500 base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05, 16QAM SAR testing is not required.
7. Per KDB 941225 D05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05, smaller bandwidth SAR testing is not required.



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	20.43	20.47	20.50
1.4	1	2		20.50	20.56	20.68
1.4	1	5		20.45	20.51	20.55
1.4	3	0		20.51	20.51	20.72
1.4	3	1		20.55	20.55	20.70
1.4	3	2		20.50	20.53	20.67
1.4	6	0		19.54	19.52	19.70
1.4	1	0	16-QAM	19.36	19.67	19.79
1.4	1	2		19.43	19.72	19.84
1.4	1	5		19.38	19.72	19.80
1.4	3	0		19.70	19.78	19.94
1.4	3	1		19.72	19.79	20.01
1.4	3	2		19.72	19.74	19.97
1.4	6	0		18.77	18.77	18.92
3	1	0	QPSK	20.29	20.24	20.49
3	1	7		20.41	20.40	20.58
3	1	14		20.44	20.33	20.41
3	8	0		19.50	19.52	19.75
3	8	4		19.61	19.56	19.78
3	8	7		19.56	19.59	19.71
3	15	0		19.55	19.51	19.65
3	1	0	16-QAM	19.32	19.75	19.69
3	1	7		19.37	19.92	19.82
3	1	14		19.33	19.80	19.72
3	8	0		18.50	18.59	18.78
3	8	4		18.57	18.66	18.79
3	8	7		18.61	18.61	18.71
3	15	0		18.66	18.59	18.69



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	20.55	20.53	20.72
5	1	12		20.68	20.66	20.86
5	1	24		20.61	20.68	20.70
5	12	0		19.57	19.63	19.79
5	12	6		19.66	19.71	19.90
5	12	11		19.70	19.66	19.78
5	25	0		19.63	19.63	19.77
5	1	0	16-QAM	20.15	19.97	20.16
5	1	12		20.37	20.10	20.24
5	1	24		20.27	20.05	20.15
5	12	0		18.60	18.58	18.84
5	12	6		18.71	18.67	18.91
5	12	11		18.76	18.68	18.84
5	25	0		18.64	18.69	18.81
10	1	0	QPSK	20.65	20.59	20.87
10	1	24		20.72	20.77	20.91
10	1	49		20.80	20.79	20.80
10	25	0		19.51	19.56	19.74
10	25	12		19.71	19.75	19.88
10	25	24		19.72	19.64	19.86
10	50	0		19.68	19.60	19.81
10	1	0	16-QAM	19.85	19.55	20.39
10	1	24		19.98	19.68	20.38
10	1	49		19.96	19.75	20.29
10	25	0		18.59	18.62	18.82
10	25	12		18.76	18.73	18.94
10	25	24		18.76	18.70	18.92
10	50	0		18.74	18.63	18.86



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	20.59	20.54	20.86
15	1	37		20.79	20.70	20.98
15	1	74		20.64	20.77	20.80
15	36	0		19.58	19.54	19.82
15	36	18		19.67	19.64	19.90
15	36	39		19.64	19.65	19.88
15	75	0		19.64	19.64	19.90
15	1	0	16-QAM	19.72	20.03	20.09
15	1	38		19.91	20.21	20.20
15	1	75		19.82	20.29	20.04
15	36	0		18.60	18.68	18.92
15	36	18		18.68	18.70	18.98
15	36	39		18.66	18.72	18.99
15	75	0		18.69	18.67	18.89
20	1	0	QPSK	20.50	20.51	20.73
20	1	49		20.79	20.78	21.03
20	1	99		20.53	20.76	20.77
20	50	0		19.61	19.60	19.99
20	50	24		19.77	19.71	20.04
20	50	49		19.75	19.68	20.06
20	100	0		19.65	19.62	19.96
20	1	0	16-QAM	19.90	19.82	20.02
20	1	49		20.25	20.11	20.32
20	1	99		19.93	20.11	20.05
20	50	0		18.70	18.59	19.08
20	50	24		18.88	18.70	19.11
20	50	49		18.83	18.71	19.14
20	100	0		18.68	18.67	19.03



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	20.47	20.57	20.64
1.4	1	2		20.44	20.59	20.69
1.4	1	5		20.37	20.54	20.58
1.4	3	0		20.45	20.60	20.62
1.4	3	1		20.45	20.64	20.66
1.4	3	2		20.42	20.62	20.61
1.4	6	0		19.46	19.66	19.67
1.4	1	0	16-QAM	19.59	19.46	19.80
1.4	1	2		19.63	19.51	19.82
1.4	1	5		19.60	19.47	19.80
1.4	3	0		19.75	19.81	19.88
1.4	3	1		19.79	19.86	19.93
1.4	3	2		19.74	19.85	19.87
1.4	6	0		18.67	18.89	18.93
3	1	0	QPSK	20.27	20.40	20.47
3	1	7		20.34	20.48	20.54
3	1	14		20.27	20.45	20.45
3	8	0		19.42	19.61	19.63
3	8	4		19.50	19.72	19.68
3	8	7		19.48	19.68	19.67
3	15	0		19.44	19.65	19.64
3	1	0	16-QAM	19.23	19.91	19.64
3	1	7		19.27	19.98	19.79
3	1	14		19.17	19.91	19.71
3	8	0		18.44	18.70	18.71
3	8	4		18.53	18.78	18.73
3	8	7		18.46	18.72	18.68
3	15	0		18.53	18.69	18.69



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	20.54	20.66	20.69
5	1	12		20.55	20.75	20.78
5	1	24		20.54	20.75	20.69
5	12	0		19.49	19.68	19.72
5	12	6		19.56	19.79	19.81
5	12	11		19.47	19.78	19.78
5	25	0		19.53	19.74	19.78
5	1	0	16-QAM	20.13	20.09	20.15
5	1	12		20.23	20.19	20.18
5	1	24		20.16	20.15	20.17
5	12	0		18.58	18.66	18.78
5	12	6		18.60	18.79	18.88
5	12	11		18.52	18.77	18.83
5	25	0		18.58	18.78	18.76
10	1	0	QPSK	20.51	20.49	20.74
10	1	24		20.74	20.81	20.93
10	1	49		20.71	20.73	20.78
10	25	0		19.66	19.67	19.83
10	25	12		19.74	19.82	19.88
10	25	24		19.77	19.94	19.79
10	50	0		19.67	19.79	19.77
10	1	0	16-QAM	19.77	19.90	20.02
10	1	24		20.02	20.22	20.24
10	1	49		19.97	20.11	20.10
10	25	0		18.73	18.73	18.84
10	25	12		18.80	18.97	18.88
10	25	24		18.85	19.01	18.78
10	50	0		18.76	18.85	18.82



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	20.61	20.65	20.73
15	1	37		20.68	20.85	20.82
15	1	74		20.66	20.82	20.77
15	36	0		19.53	19.64	19.77
15	36	18		19.61	19.74	19.79
15	36	39		19.59	19.90	19.68
15	75	0		19.59	19.77	19.76
15	1	0	16-QAM	19.80	19.77	20.22
15	1	38		19.90	19.97	20.32
15	1	75		19.91	19.98	20.26
15	36	0		18.65	18.67	18.80
15	36	18		18.71	18.77	18.83
15	36	39		18.74	18.83	18.77
15	75	0		18.62	18.83	18.75
20	1	0	QPSK	20.67	20.79	20.78
20	1	49		20.65	20.87	20.77
20	1	99		20.69	20.94	20.81
20	50	0		19.58	19.71	19.75
20	50	24		19.63	19.83	19.80
20	50	49		19.57	19.88	19.74
20	100	0		19.58	19.80	19.76
20	1	0	16-QAM	19.86	19.68	20.29
20	1	49		19.88	19.76	20.25
20	1	99		19.90	19.80	20.34
20	50	0		18.63	18.72	18.80
20	50	24		18.65	18.89	18.86
20	50	49		18.61	18.87	18.82
20	100	0		18.68	18.79	18.79



LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	24.85	25.05	24.87
1.4	1	2		24.98	25.15	24.97
1.4	1	5		24.89	25.07	24.85
1.4	3	0		25.01	25.12	24.86
1.4	3	1		25.02	25.13	24.88
1.4	3	2		25.03	25.10	24.86
1.4	6	0		24.09	24.15	23.94
1.4	1	0	16-QAM	24.00	23.87	23.87
1.4	1	2		24.09	23.96	23.98
1.4	1	5		24.09	23.89	23.88
1.4	3	0		24.13	24.23	24.04
1.4	3	1		24.22	24.27	24.03
1.4	3	2		24.19	24.26	23.98
1.4	6	0		23.23	23.36	23.13
3	1	0	QPSK	24.72	24.88	24.72
3	1	7		24.84	24.96	24.84
3	1	14		24.81	24.85	24.78
3	8	0		23.98	24.10	23.93
3	8	4		24.07	24.15	23.97
3	8	7		24.08	24.11	23.86
3	15	0		23.97	24.09	23.88
3	1	0	16-QAM	24.12	24.07	23.56
3	1	7		24.25	24.16	23.63
3	1	14		24.17	24.10	23.51
3	8	0		22.99	23.10	22.87
3	8	4		23.08	23.18	22.92
3	8	7		23.05	23.08	22.84
3	15	0		23.04	23.08	22.94



LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	25.00	25.14	24.96
5	1	12		25.13	25.22	24.99
5	1	24		25.19	25.14	24.86
5	12	0		24.01	24.22	23.97
5	12	6		24.22	24.19	24.04
5	12	11		24.29	24.15	23.85
5	25	0		24.12	24.17	23.94
5	1	0	16-QAM	24.43	24.47	24.22
5	1	12		24.57	24.53	24.29
5	1	24		24.62	24.44	24.19
5	12	0		23.00	23.16	22.98
5	12	6		23.16	23.16	23.07
5	12	11		23.24	23.09	22.88
5	25	0		23.11	23.25	22.94
10	1	0	QPSK	25.17	25.19	25.18
10	1	24		25.39	25.21	25.11
10	1	49		25.40	25.15	25.04
10	25	0		23.99	24.26	24.04
10	25	12		24.29	24.29	24.09
10	25	24		24.28	24.16	24.05
10	50	0		24.18	24.25	24.07
10	1	0	16-QAM	23.88	24.59	24.31
10	1	24		24.11	24.63	24.30
10	1	49		24.17	24.58	24.16
10	25	0		22.96	23.31	23.07
10	25	12		23.26	23.33	23.13
10	25	24		23.32	23.22	23.03
10	50	0		23.13	23.25	23.09



LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	20.31	20.65	20.66
5	1	12		20.40	20.75	20.77
5	1	24		20.34	20.64	20.63
5	12	0		19.31	19.70	19.68
5	12	6		19.39	19.78	19.82
5	12	11		19.36	19.70	19.78
5	25	0		19.30	19.70	19.74
5	1	0	16-QAM	19.96	20.13	20.09
5	1	12		20.11	20.22	20.24
5	1	24		19.99	20.12	20.13
5	12	0		18.44	18.77	18.88
5	12	6		18.54	18.84	18.96
5	12	11		18.46	18.76	18.90
5	25	0		18.40	18.88	18.88
10	1	0	QPSK	19.18	19.40	19.48
10	1	24		20.39	20.76	20.79
10	1	49		20.36	20.49	20.75
10	25	0		19.27	19.65	19.70
10	25	12		19.46	19.79	19.78
10	25	24		19.40	19.69	19.84
10	50	0		19.32	19.61	19.73
10	1	0	16-QAM	18.67	18.97	18.86
10	1	24		19.80	20.27	20.09
10	1	49		19.74	19.96	20.01
10	25	0		18.45	18.81	18.75
10	25	12		18.61	18.95	18.84
10	25	24		18.55	18.82	18.90
10	50	0		18.49	18.73	18.84



LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	20.26	20.66	20.56
15	1	37		20.34	20.80	20.83
15	1	74		20.28	20.61	20.77
15	36	0		19.20	19.63	19.58
15	36	18		19.31	19.69	19.69
15	36	39		19.26	19.61	19.76
15	75	0		19.25	19.69	19.69
15	1	0	16-QAM	19.83	19.91	19.68
15	1	38		19.92	20.06	19.95
15	1	75		19.89	19.88	19.90
15	36	0		18.37	18.84	18.66
15	36	18		18.46	18.90	18.73
15	36	39		18.40	18.81	18.86
15	75	0		18.38	18.74	18.79
20	1	0	QPSK	20.40	20.76	20.67
20	1	49		20.44	20.84	20.80
20	1	99		20.43	20.75	20.81
20	50	0		19.32	19.69	19.66
20	50	24		19.42	19.79	19.85
20	50	49		19.32	19.74	19.84
20	100	0		19.38	19.75	19.79
20	1	0	16-QAM	19.66	19.69	20.21
20	1	49		19.67	19.74	20.34
20	1	99		19.61	19.69	20.33
20	50	0		18.44	18.83	18.86
20	50	24		18.55	18.90	18.99
20	50	49		18.48	18.86	19.01
20	100	0		18.55	18.82	18.90



LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	21.70	21.66	21.55
1.4	1	2		21.79	21.77	21.67
1.4	1	5		21.70	21.64	21.56
1.4	3	0		21.67	21.77	21.69
1.4	3	1		21.73	21.77	21.67
1.4	3	2		21.72	21.76	21.64
1.4	6	0		20.73	20.82	20.73
1.4	1	0	16-QAM	20.81	20.89	20.46
1.4	1	2		20.90	20.93	20.54
1.4	1	5		20.86	20.89	20.45
1.4	3	0		20.88	21.03	20.86
1.4	3	1		20.92	21.08	20.87
1.4	3	2		20.92	21.06	20.83
1.4	6	0		19.93	19.96	19.90
3	1	0	QPSK	21.37	21.56	21.47
3	1	7		21.51	21.61	21.56
3	1	14		21.43	21.45	21.50
3	8	0		20.64	20.67	20.70
3	8	4		20.68	20.76	20.76
3	8	7		20.67	20.77	20.66
3	15	0		20.64	20.77	20.62
3	1	0	16-QAM	20.88	20.70	20.40
3	1	7		21.02	20.83	20.46
3	1	14		20.94	20.74	20.38
3	8	0		19.68	19.72	19.65
3	8	4		19.71	19.81	19.69
3	8	7		19.71	19.78	19.67
3	15	0		19.67	19.72	19.69



LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	21.62	21.76	21.70
5	1	12		21.82	21.81	21.79
5	1	24		21.78	21.77	21.71
5	12	0		20.70	20.71	20.82
5	12	6		20.80	20.82	20.82
5	12	11		20.65	20.90	20.69
5	25	0		20.74	20.86	20.77
5	1	0	16-QAM	20.99	21.14	21.28
5	1	12		21.20	21.21	21.40
5	1	24		21.15	21.10	21.33
5	12	0		19.68	19.78	19.88
5	12	6		19.78	19.88	19.84
5	12	11		19.65	19.93	19.76
5	25	0		19.80	19.82	19.74
10	1	0	QPSK	21.79	21.84	21.80
10	1	24		21.92	21.94	21.80
10	1	49		21.91	21.94	21.78
10	25	0		20.94	20.73	20.59
10	25	12		20.88	20.89	20.83
10	25	24		20.97	20.95	20.59
10	50	0		20.99	20.89	20.60
10	1	0	16-QAM	20.98	20.73	21.29
10	1	24		21.10	20.83	21.30
10	1	49		21.10	20.80	21.26
10	25	0		20.00	19.76	19.63
10	25	12		19.91	19.90	19.91
10	25	24		20.04	19.98	19.65
10	50	0		20.03	19.86	19.55



LTE Band 17 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.73	24.68	24.55
5	1	12		24.78	24.75	24.66
5	1	24		24.76	24.69	24.55
5	12	0		23.70	23.61	23.77
5	12	6		23.79	23.75	23.69
5	12	11		23.83	23.66	23.66
5	25	0		23.78	23.67	23.68
5	1	0	16-QAM	24.29	23.99	23.95
5	1	12		24.35	24.06	24.01
5	1	24		24.28	23.97	23.86
5	12	0		22.72	22.60	22.78
5	12	6		22.82	22.72	22.75
5	12	11		22.83	22.67	22.67
5	25	0		22.77	22.73	22.69
10	1	0	QPSK	24.80	24.75	24.79
10	1	24		24.86	24.76	24.80
10	1	49		24.83	24.71	24.72
10	25	0		23.50	23.50	23.52
10	25	12		23.74	23.69	23.72
10	25	24		23.65	23.52	23.53
10	50	0		23.65	23.58	23.55
10	1	0	16-QAM	23.66	24.18	23.93
10	1	24		23.62	24.19	23.96
10	1	49		23.66	24.14	23.86
10	25	0		22.56	22.56	22.53
10	25	12		22.76	22.78	22.76
10	25	24		22.69	22.56	22.48
10	50	0		22.62	22.52	22.56



LTE Band 38 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.17	24.23	24.10
5	1	12		24.35	24.33	24.29
5	1	24		24.21	24.18	24.12
5	12	0		23.17	23.28	23.15
5	12	6		23.23	23.34	23.19
5	12	11		23.22	23.31	23.15
5	25	0		23.26	23.31	23.19
5	1	0	16-QAM	23.47	23.56	23.70
5	1	12		23.62	23.67	23.86
5	1	24		23.49	23.55	23.74
5	12	0		22.15	22.33	22.18
5	12	6		22.26	22.38	22.23
5	12	11		22.17	22.36	22.18
5	25	0		22.33	22.33	22.18
10	1	0	QPSK	24.03	24.25	24.10
10	1	24		24.34	24.39	24.28
10	1	49		24.24	24.15	24.09
10	25	0		23.14	23.25	23.15
10	25	12		23.32	23.33	23.22
10	25	24		23.32	23.24	23.15
10	50	0		23.24	23.23	23.11
10	1	0	16-QAM	23.31	23.43	23.26
10	1	24		23.63	23.55	23.44
10	1	49		23.51	23.30	23.20
10	25	0		22.25	22.24	22.22
10	25	12		22.39	22.36	22.28
10	25	24		22.42	22.27	22.19
10	50	0		22.32	22.27	22.15



LTE Band 38 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	24.19	24.24	24.18
15	1	37		24.34	24.32	24.32
15	1	74		24.31	24.17	24.16
15	36	0		23.21	23.22	23.15
15	36	18		23.27	23.32	23.19
15	36	39		23.28	23.24	23.15
15	75	0		23.22	23.27	23.21
15	1	0	16-QAM	23.63	23.39	23.32
15	1	38		23.75	23.48	23.45
15	1	75		23.77	23.31	23.32
15	36	0		22.17	22.31	22.11
15	36	18		22.28	22.38	22.18
15	36	39		22.30	22.33	22.10
15	75	0		22.21	22.24	22.19
20	1	0	QPSK	24.27	24.38	24.27
20	1	49		24.33	24.43	24.30
20	1	99		24.30	24.33	24.22
20	50	0		23.26	23.34	23.18
20	50	24		23.37	23.36	23.25
20	50	49		23.31	23.34	23.19
20	100	0		23.31	23.37	23.24
20	1	0	16-QAM	23.74	23.52	23.13
20	1	49		23.88	23.56	23.18
20	1	99		23.84	23.44	23.13
20	50	0		22.37	22.36	22.20
20	50	24		22.42	22.44	22.28
20	50	49		22.37	22.38	22.21
20	100	0		22.36	22.41	22.20



LTE Band 40(2305-2315MHz) Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	13.79	13.76	13.74
5	1	12		13.89	13.90	13.91
5	1	24		13.80	13.84	13.84
5	12	0		12.82	12.80	12.84
5	12	6		12.83	12.88	12.91
5	12	11		12.79	12.79	12.87
5	25	0		12.79	12.83	12.86
5	1	0	16-QAM	13.40	13.10	13.15
5	1	12		13.58	13.23	13.29
5	1	24		13.48	13.14	13.25
5	12	0		11.78	11.76	11.86
5	12	6		11.83	11.80	11.94
5	12	11		11.79	11.73	11.90
5	25	0		11.79	11.84	11.89
10	1	0	QPSK	/	13.81	/
10	1	24		/	13.96	/
10	1	49		/	13.99	/
10	25	0		/	12.86	/
10	25	12		/	12.91	/
10	25	24		/	12.84	/
10	50	0		/	12.86	/
10	1	0	16-QAM	/	12.98	/
10	1	24		/	13.09	/
10	1	49		/	13.09	/
10	25	0		/	11.84	/
10	25	12		/	11.91	/
10	25	24		/	11.87	/
10	50	0		/	11.89	/



LTE Band 40(2350-2360MHz) Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	13.95	13.84	13.87
5	1	12		13.98	13.99	13.99
5	1	24		13.94	13.84	13.87
5	12	0		12.92	12.88	12.86
5	12	6		12.98	12.97	12.93
5	12	11		13.01	12.95	12.92
5	25	0		12.96	12.93	12.91
5	1	0	16-QAM	13.49	13.25	13.58
5	1	12		13.57	13.42	13.74
5	1	24		13.51	13.27	13.60
5	12	0		11.97	11.92	11.88
5	12	6		12.04	11.99	11.94
5	12	11		12.02	11.96	11.93
5	25	0		11.97	11.91	11.90
10	1	0	QPSK	/	13.91	/
10	1	24		/	14.01	/
10	1	49		/	13.91	/
10	25	0		/	12.90	/
10	25	12		/	12.97	/
10	25	24		/	12.98	/
10	50	0		/	12.96	/
10	1	0	16-QAM	/	13.29	/
10	1	24		/	13.42	/
10	1	49		/	13.30	/
10	25	0		/	11.87	/
10	25	12		/	11.93	/
10	25	24		/	11.90	/
10	50	0		/	12.02	/



LTE Band 41 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	24.75	24.21	24.54
5	1	12		24.91	24.30	24.61
5	1	24		24.84	24.17	24.49
5	12	0		23.70	23.26	23.48
5	12	6		23.80	23.30	23.51
5	12	11		23.83	23.25	23.44
5	25	0		23.79	23.28	23.45
5	1	0	16-QAM	23.97	23.57	24.01
5	1	12		24.12	23.66	24.11
5	1	24		24.08	23.54	24.02
5	12	0		22.70	22.28	22.47
5	12	6		22.81	22.37	22.50
5	12	11		22.79	22.31	22.43
5	25	0		22.85	22.28	22.46
10	1	0	QPSK	24.76	24.34	24.76
10	1	24		24.93	24.40	24.70
10	1	49		24.93	24.32	24.59
10	25	0		23.77	23.28	23.60
10	25	12		23.90	23.29	23.63
10	25	24		23.93	23.32	23.47
10	50	0		23.91	23.33	23.56
10	1	0	16-QAM	24.23	23.47	23.58
10	1	24		24.38	23.55	23.55
10	1	49		24.43	23.46	23.47
10	25	0		22.84	22.33	22.60
10	25	12		22.97	22.40	22.61
10	25	24		23.04	22.35	22.50
10	50	0		22.92	22.40	22.57



LTE Band 41 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	24.73	24.29	24.96
15	1	37		25.00	24.40	24.89
15	1	74		24.88	24.24	24.67
15	36	0		23.82	23.29	23.83
15	36	18		23.96	23.32	23.80
15	36	39		23.96	23.31	23.62
15	75	0		23.95	23.36	23.78
15	1	0	16-QAM	24.19	23.45	24.00
15	1	38		24.44	23.52	23.96
15	1	75		24.36	23.38	23.73
15	36	0		22.84	22.37	22.77
15	36	18		23.03	22.42	22.70
15	36	39		23.03	22.39	22.59
15	75	0		22.94	22.34	22.73
20	1	0	QPSK	24.68	24.19	24.93
20	1	49		25.09	24.41	24.93
20	1	99		24.78	24.14	24.60
20	50	0		23.78	23.27	23.81
20	50	24		23.99	23.38	23.78
20	50	49		23.94	23.34	23.57
20	100	0		23.87	23.28	23.68
20	1	0	16-QAM	23.83	23.49	23.94
20	1	49		24.18	23.68	23.98
20	1	99		23.92	23.42	23.67
20	50	0		22.82	22.37	22.83
20	50	24		23.05	22.49	22.77
20	50	49		23.02	22.41	22.58
20	100	0		22.89	22.31	22.70



10.2 Tune up Power

Mode	GSM850	GSM1900
GSM/PCS	33.5±1dBm	24±1dBm
GPRS (1 Slot)	33.5±1dBm	24±1dBm
GPRS (2 Slot)	32±1dBm	24±1dBm
GPRS (3 Slot)	30±1dBm	24±1dBm
GPRS (4 Slot)	29±1dBm	23.5±1dBm
EDGE (1 Slot)	26±1dBm	26±1dBm
EDGE (2 Slot)	25±1dBm	24±1dBm
EDGE (3 Slot)	22±1dBm	21.5±1dBm
EDGE (4 Slot)	20±1dBm	19.5±1dBm

Mode	WCDMA Band II	WCDMA Band V	WCDMA Band IV
RMR	21±1dBm	20±1dBm	24.5±1dBm
HSDPA Subtest-1	20±1dBm	19±1dBm	23.5±1dBm
HSDPA Subtest-2	19.5±1dBm	18.5±1dBm	23±1dBm
HSDPA Subtest-3	18.5±1dBm	18±1dBm	22±1dBm
HSDPA Subtest-4	18.5±1dBm	18±1dBm	22±1dBm
HSUPA Subtest-1	20±1dBm	19±1dBm	23±1dBm
HSUPA Subtest-2	20±1dBm	19±1dBm	23.5±1dBm
HSUPA Subtest-3	18.5±1dBm	18±1dBm	22±1dBm
HSUPA Subtest-4	20±1dBm	19±1dBm	23.5±1dBm
HSUPA Subtest-5	19±1dBm	18.5±1dBm	22.5±1dBm

Mode	NFC
NFC	-44±1dBm

Mode	BT
GFSK	1±1dBm
$\pi/4$ -DQPSK	0.5±1dBm
8DPSK	0.5±1dBm

Mode	BLE
GFSK(1Mbps)	7±1dBm
GFSK(2Mbps)	7±1dBm

Mode	2.4G WLAN
802.11b	14.5±1dBm
802.11g	12.5±1dBm
802.11n(HT20)	11.5±1dBm
802.11n(HT40)	12±1dBm



Mode	5.2G WLAN
802.11a	13±1dBm
802.11 n-HT20	11.5±1dBm
802.11 n-HT40	12±1dBm
802.11 ac-VHT20	11.5±1dBm
802.11 ac-VHT40	11.5±1dBm
802.11 ac-VHT80	11±1dBm

Mode	5.3G WLAN
802.11a	12.5±1dBm
802.11 n-HT20	12±1dBm
802.11 n-HT40	12±1dBm
802.11 ac-VHT20	11.5±1dBm
802.11 ac-VHT40	11±1dBm
802.11 ac-VHT80	11±1dBm

Mode	5.6G WLAN
802.11a	13±1dBm
802.11 n-HT20	13±1dBm
802.11 n-HT40	11.5±1dBm
802.11 ac-VHT20	11.5±1dBm
802.11 ac-VHT40	11±1dBm
802.11 ac-VHT80	11±1dBm

Mode	5.8G WLAN
802.11a	12.5±1dBm
802.11 n-HT20	12±1dBm
802.11 n-HT40	12±1dBm
802.11 ac-VHT20	11.5±1dBm
802.11 ac-VHT40	11.5±1dBm
802.11 ac-VHT80	11.5±1dBm



BW[MHz]	RB Size	Mode	Band 2	Band 4	Band 5	Band 7	Band 12
1.4	1	QPSK	20±1dBm	19.5±1dBm	24.5±1dBm	N/A	21±1dBm
1.4	3		20±1dBm	20±1dBm	24.5±1dBm	N/A	21±1dBm
1.4	6		20±1dBm	20±1dBm	24±1dBm	N/A	21±1dBm
1.4	1	16-QAM	19±1dBm	19±1dBm	23.5±1dBm	N/A	20±1dBm
1.4	3		19±1dBm	19±1dBm	23.5±1dBm	N/A	20.5±1dBm
1.4	6		19.5±1dBm	19±1dBm	23.5±1dBm	N/A	20±1dBm
3	1	QPSK	19.5±1dBm	19.5±1dBm	24±1dBm	N/A	21±1dBm
3	8		19.5±1dBm	19.5±1dBm	24±1dBm	N/A	21±1dBm
3	15		20±1dBm	20±1dBm	24±1dBm	N/A	21±1dBm
3	1	16-QAM	18.5±1dBm	18.5±1dBm	23.5±1dBm	N/A	19.5±1dBm
3	8		18±1dBm	19±1dBm	23.5±1dBm	N/A	20±1dBm
3	15		19±1dBm	19±1dBm	23±1dBm	N/A	19.5±1dBm
5	1	QPSK	20±1dBm	20±1dBm	24.5±1dBm	19.5±1dBm	21±1dBm
5	12		20±1dBm	20±1dBm	24.5±1dBm	20±1dBm	21±1dBm
5	25		20±1dBm	20±1dBm	24±1dBm	20±1dBm	21±1dBm
5	1	16-QAM	19.5±1dBm	19.5±1dBm	24±1dBm	19.5±1dBm	19.5±1dBm
5	12		19.5±1dBm	19.5±1dBm	24±1dBm	19.5±1dBm	20.5±1dBm
5	25		19.5±1dBm	19.5±1dBm	23.5±1dBm	19.5±1dBm	20.±1dBm
10	1	QPSK	20±1dBm	20±1dBm	24.5±1dBm	19.5±1dBm	21±1dBm
10	25		20±1dBm	20±1dBm	24.5±1dBm	20±1dBm	21±1dBm
10	50		20±1dBm	20±1dBm	24.5±1dBm	20±1dBm	21±1dBm
10	1	16-QAM	19±1dBm	19.5±1dBm	23.5±1dBm	19±1dBm	20.5±1dBm
10	25		19±1dBm	19.5±1dBm	24±1dBm	19.5±1dBm	20±1dBm
10	50		19.5±1dBm	19.5±1dBm	23.5±1dBm	19.5±1dBm	20.5±1dBm
15	1	QPSK	20±1dBm	20±1dBm	N/A	19.5±1dBm	N/A
15	36		20±1dBm	20±1dBm	N/A	20±1dBm	N/A
15	75		20±1dBm	20±1dBm	N/A	20±1dBm	N/A
15	1	16-QAM	19±1dBm	19±1dBm	N/A	19±1dBm	N/A
15	36		19.5±1dBm	19±1dBm	N/A	19.5±1dBm	N/A
15	75		19.5±1dBm	19.5±1dBm	N/A	19±1dBm	N/A
20	1	QPSK	20±1dBm	20±1dBm	N/A	19.5±1dBm	N/A
20	50		20±1dBm	20±1dBm	N/A	20±1dBm	N/A
20	100		20.5±1dBm	20±1dBm	N/A	20±1dBm	N/A
20	1	16-QAM	19.5±1dBm	19±1dBm	N/A	19±1dBm	N/A
20	50		19.5±1dBm	19±1dBm	N/A	19±1dBm	N/A
20	100		19.5±1dBm	19.5±1dBm	N/A	19.5±1dBm	N/A




BW[MHz]	RB Size	Mode	Band 17	Band 38	Band 40(2305-2315)	Band 40(2350-2360)	Band 41
1.4	1	QPSK	N/A	N/A	N/A	N/A	N/A
1.4	3		N/A	N/A	N/A	N/A	N/A
1.4	6		N/A	N/A	N/A	N/A	N/A
1.4	1	16-QAM	N/A	N/A	N/A	N/A	N/A
1.4	3		N/A	N/A	N/A	N/A	N/A
1.4	6		N/A	N/A	N/A	N/A	N/A
3	1	QPSK	N/A	N/A	N/A	N/A	N/A
3	8		N/A	N/A	N/A	N/A	N/A
3	15		N/A	N/A	N/A	N/A	N/A
3	1	16-QAM	N/A	N/A	N/A	N/A	N/A
3	8		N/A	N/A	N/A	N/A	N/A
3	15		N/A	N/A	N/A	N/A	N/A
5	1	QPSK	24±1dBm	23.5±1dBm	13±1dBm	13±1dBm	24±1dBm
5	12		24±1dBm	23.5±1dBm	13±1dBm	13±1dBm	23.5±1dBm
5	25		24±1dBm	23.5±1dBm	13±1dBm	13±1dBm	24±1dBm
5	1	16-QAM	23.5±1dBm	23±1dBm	13±1dBm	13±1dBm	23.5±1dBm
5	12		23.5±1dBm	23±1dBm	12.5±1dBm	12.5±1dBm	23±1dBm
5	25		23.5±1dBm	23±1dBm	12.5±1dBm	13±1dBm	23.5±1dBm
10	1	QPSK	24±1dBm	23.5±1dBm	13±1dBm	13.5±1dBm	24±1dBm
10	25		24±1dBm	23.5±1dBm	12±1dBm	12±1dBm	23.5±1dBm
10	50		24±1dBm	23.5±1dBm	12±1dBm	12±1dBm	24±1dBm
10	1	16-QAM	23±1dBm	23±1dBm	12.5±1dBm	12.5±1dBm	23.5±1dBm
10	25		23.5±1dBm	23±1dBm	11±1dBm	11.5±1dBm	23±1dBm
10	50		23±1dBm	22.5±1dBm	11±1dBm	11.5±1dBm	23±1dBm
15	1	QPSK	N/A	23.5±1dBm	N/A	N/A	24±1dBm
15	36		N/A	23.5±1dBm	N/A	N/A	23.5±1dBm
15	75		N/A	23.5±1dBm	N/A	N/A	24±1dBm
15	1	16-QAM	N/A	23±1dBm	N/A	N/A	23.5±1dBm
15	36		N/A	23.5±1dBm	N/A	N/A	23±1dBm
15	75		N/A	23.5±1dBm	N/A	N/A	23±1dBm
20	1	QPSK	N/A	23.5±1dBm	N/A	N/A	24.5±1dBm
20	50		N/A	23.5±1dBm	N/A	N/A	23.5±1dBm
20	100		N/A	23.5±1dBm	N/A	N/A	24±1dBm
20	1	16-QAM	N/A	23±1dBm	N/A	N/A	23.5±1dBm
20	50		N/A	23±1dBm	N/A	N/A	23±1dBm
20	100		N/A	22.5±1dBm	N/A	N/A	23±1dBm




11. EUT and Test Setup Photo

11.1 EUT Photos

Front side



Back side






Right Edge



Left Edge






Top Edge




Bottom Edge



11.2 Setup Photos

Body Back side (separation distance is 0mm)



Body Left side (separation distance is 0mm)



Body Right side (separation distance is 0mm)



Body Top side (separation distance is 0mm)






Body Bottom side (separation distance is 0mm)



Liquid depth (15 cm)





12. SAR Result Summary

12.1 Body-worn and Hotspot SAR

Band	Model	Test Position	Freq.	SAR (1g) (W/kg)	Power Drift (%)	Max. Turn-up Power(dBm)	Meas. Output Power(dBm)	Scaled SAR (W/Kg)	Meas. No.
GSM850	GPRS Data-4 Slot	Back Side	848.8	0.78	-0.85	34.50	34.40	0.798	1
		Left Side	848.8	0.383	-3.28	34.50	34.40	0.392	/
		Right Side	848.8	0.323	-2.35	34.50	34.40	0.331	/
		Top Side	848.8	0.209	0.05	34.50	34.40	0.214	/
		Bottom Side	848.8	0.188	-0.74	34.50	34.40	0.192	/
PCS 1900	EGPRS(8PSK, 4-Slot)	Back Side	1850.2	0.84	2.63	27.00	26.77	0.886	2
		Back Side	1880	0.654	-1.71	27.00	26.15	0.795	/
		Back Side	1909.8	0.712	3.39	27.00	26.13	0.870	/
		Left Side	1850.2	0.353	0.52	27.00	26.77	0.372	/
		Right Side	1850.2	0.292	1.91	27.00	26.77	0.308	/
		Top Side	1850.2	0.195	3.31	27.00	26.77	0.206	/
		Bottom Side	1850.2	0.171	-2.03	27.00	26.77	0.180	/
WCDMA Band II	RMC	Back Side	1852.4	0.881	-2.22	22.00	21.46	0.998	/
		Back Side	1880	0.796	1.57	22.00	21.41	0.912	/
		Back Side	1907.6	0.984	-3.78	22.00	21.57	1.086	3
		Left Side	1907.6	0.484	2.02	22.00	21.57	0.534	/
		Right Side	1907.6	0.405	-1.06	22.00	21.57	0.447	/
		Top Side	1907.6	0.266	-0.54	22.00	21.57	0.294	/
		Bottom Side	1907.6	0.239	-3.98	22.00	21.57	0.264	/
WCDMA Band IV	RMC	Back Side	1752.4	0.784	-0.73	21.00	20.94	0.795	4
		Left Side	1752.4	0.388	2.85	21.00	20.94	0.393	/
		Right Side	1752.4	0.322	0.81	21.00	20.94	0.326	/
		Top Side	1752.4	0.215	-0.78	21.00	20.94	0.218	/
		Bottom Side	1752.4	0.191	-1.65	21.00	20.94	0.194	/
WCDMA Band V	RMC	Back Side	826.4	0.723	3.89	25.50	25.03	0.806	/
		Back Side	836.4	0.81	-3.96	25.50	25.07	0.894	5
		Back Side	846.6	0.689	0.26	25.50	24.92	0.787	/
		Left Side	836.4	0.341	-0.19	25.50	25.07	0.376	/
		Right Side	836.4	0.287	-3.73	25.50	25.07	0.317	/
		Top Side	836.4	0.186	-0.93	25.50	25.07	0.205	/
		Bottom Side	836.4	0.166	3.52	25.50	25.07	0.183	/
2.4GHz WLAN	802.11b	Back Side	2437	0.267	3.10	15.50	15.22	0.285	6
		Left Side	2437	0.133	2.80	15.50	15.22	0.142	/
		Right Side	2437	0.11	-3.68	15.50	15.22	0.117	/
		Top Side	2437	0.087	0.33	15.50	15.22	0.093	/
		Bottom Side	2437	0.066	-1.50	15.50	15.22	0.070	/
BT	GFSK	Back Side	2441	0.311	0.79	2.00	1.95	0.315	7
		Left Side	2441	0.153	-0.04	2.00	1.95	0.155	/
		Right Side	2441	0.13	0.88	2.00	1.95	0.132	/
		Top Side	2441	0.083	2.68	2.00	1.95	0.084	/
		Bottom Side	2441	0.075	-2.59	2.00	1.95	0.076	/
5.2GHz WLAN	802.11a	Back Side	5200	0.228	2.46	14.00	13.59	0.251	8
		Left Side	5200	0.115	-1.97	14.00	13.59	0.126	/
		Right Side	5200	0.097	-1.05	14.00	13.59	0.107	/
		Top Side	5200	0.063	0.32	14.00	13.59	0.069	/
		Bottom Side	5200	0.058	1.28	14.00	13.59	0.064	/



5.3GHz WLAN	802.11a	Back Side	5260	0.275	-2.35	13.50	13.20	0.295	9
		Left Side	5260	0.135	-1.50	13.50	13.20	0.145	/
		Right Side	5260	0.115	1.86	13.50	13.20	0.123	/
		Top Side	5260	0.074	2.89	13.50	13.20	0.079	/
		Bottom Side	5260	0.07	3.36	13.50	13.20	0.075	/
5.6GHz WLAN	802.11a	Back Side	5700	0.12	-0.13	14.00	13.66	0.130	10
		Left Side	5700	0.06	-1.77	14.00	13.66	0.065	/
		Right Side	5700	0.051	1.05	14.00	13.66	0.055	/
		Top Side	5700	0.031	2.69	14.00	13.66	0.034	/
		Bottom Side	5700	0.032	1.41	14.00	13.66	0.035	/
5.8GHz WLAN	802.11a	Back Side	5825	0.188	-2.73	13.50	13.48	0.189	11
		Left Side	5825	0.095	3.43	13.50	13.48	0.095	/
		Right Side	5825	0.079	-1.12	13.50	13.48	0.079	/
		Top Side	5825	0.051	-3.11	13.50	13.48	0.051	/
		Bottom Side	5825	0.049	-0.66	13.50	13.48	0.049	/



Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	Result 1g (W/Kg)	Power Drift (%)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaled SAR (W/Kg)	Meas. No.
LTE Band 2	20M	QPSK	1	0	Back Side	1860	0.676	-0.21	21.50	20.79	0.796	/
			1	0	Back Side	1880	0.694	2.55	20.50	20.78	0.651	/
			1	0	Back Side	1900	0.856	3.95	21.50	21.03	0.954	12
			50	0	Back Side	1900	0.687	3.54	20.50	20.06	0.760	/
			1	0	Left Side	1900	0.343	-0.74	21.50	21.03	0.382	/
			50	0	Left Side	1900	0.343	-0.99	20.50	20.06	0.380	/
			1	0	Right Side	1900	0.396	-2.85	21.50	21.03	0.441	/
			50	0	Right Side	1900	0.376	-2.73	20.50	20.06	0.416	/
			1	0	Top Side	1900	0.652	3.05	21.50	21.03	0.727	/
			50	0	Top Side	1900	0.592	1.14	20.50	20.06	0.655	/
			1	0	Bottom Side	1900	0.338	-0.34	21.50	21.03	0.377	/
			50	0	Bottom Side	1900	0.318	2.40	20.50	20.06	0.352	/
LTE Band 4	20M	QPSK	1	0	Back Side	1720	0.786	0.10	21.00	20.69	0.844	/
			1	0	Back Side	1732.5	0.978	-2.67	21.00	20.94	0.992	13
			1	0	Back Side	1745	0.745	-0.98	21.00	20.81	0.778	/
			50	0	Back Side	1732.5	0.523	-1.75	20.00	19.88	0.538	/
			1	0	Left Side	1732.5	0.302	2.37	21.00	20.94	0.306	/
			50	0	Left Side	1732.5	0.299	-1.88	20.00	19.88	0.307	/
			1	0	Right Side	1732.5	0.346	-0.44	21.00	20.94	0.351	/
			50	0	Right Side	1732.5	0.33	0.48	20.00	19.88	0.339	/
			1	0	Top Side	1732.5	0.569	-0.97	21.00	20.94	0.577	/
			50	0	Top Side	1732.5	0.517	0.29	20.00	19.88	0.531	/
			1	0	Bottom Side	1732.5	0.292	-2.63	21.00	20.94	0.296	/
			50	0	Bottom Side	1732.5	0.278	-3.14	20.00	19.88	0.286	/
LTE Band 5	10M	QPSK	1	0	Back Side	829	0.640	2.44	25.50	25.40	0.655	14
			25	0	Back Side	829	0.579	2.11	24.50	24.29	0.608	/
			1	0	Left Side	829	0.256	0.40	25.50	25.40	0.262	/
			25	0	Left Side	829	0.259	-3.12	24.50	24.29	0.272	/
			1	0	Right Side	829	0.297	0.18	25.50	25.40	0.304	/
			25	0	Right Side	829	0.283	-1.24	24.50	24.29	0.297	/
			1	0	Top Side	829	0.488	-2.85	25.50	25.40	0.499	/
			25	0	Top Side	829	0.442	1.89	24.50	24.29	0.464	/
			1	0	Bottom Side	829	0.252	1.33	25.50	25.40	0.258	/
			25	0	Bottom Side	829	0.24	0.33	24.50	24.29	0.252	/
LTE Band 7	20M	QPSK	1	0	Back Side	2510	0.941	-2.36	21.00	20.44	1.071	/
			1	0	Back Side	2535	1.055	3.80	21.00	20.84	1.095	15
			1	0	Back Side	2560	0.924	-3.46	21.00	20.81	0.965	/
			50	0	Back Side	2560	0.649	-3.76	20.00	19.85	0.672	/
			1	0	Left Side	2535	0.373	2.28	21.00	20.84	0.387	/
			50	0	Left Side	2560	0.372	2.25	20.00	19.85	0.385	/
			1	0	Right Side	2535	0.426	-2.21	21.00	20.84	0.442	/
			50	0	Right Side	2560	0.411	1.75	20.00	19.85	0.425	/
			1	0	Top Side	2535	0.706	-3.24	21.00	20.84	0.732	/
			50	0	Top Side	2560	0.641	0.62	20.00	19.85	0.664	/
			1	0	Bottom Side	2535	0.36	2.89	21.00	20.84	0.374	/
			50	0	Bottom Side	2560	0.342	2.91	20.00	19.85	0.354	/



LTE Band 12	10M	QPSK	1	0	Back Side	707.5	0.532	-3.46	22.00	21.94	0.539	16
			25	0	Back Side	704	0.483	-1.62	21.00	20.97	0.486	/
			1	0	Left Side	707.5	0.214	0.90	22.00	21.94	0.217	/
			25	0	Left Side	704	0.216	-3.54	21.00	20.97	0.217	/
			1	0	Right Side	707.5	0.248	2.37	22.00	21.94	0.251	/
			25	0	Right Side	704	0.235	-0.36	21.00	20.97	0.237	/
			1	0	Top Side	707.5	0.405	0.30	22.00	21.94	0.411	/
			25	0	Top Side	704	0.367	2.03	21.00	20.97	0.370	/
			1	0	Bottom Side	707.5	0.211	-0.78	22.00	21.94	0.214	/
			25	0	Bottom Side	704	0.199	-3.08	21.00	20.97	0.200	/
LTE Band 17	10M	QPSK	1	0	Back Side	709	0.547	2.76	25.00	24.86	0.565	17
			25	0	Back Side	709	0.493	2.74	24.00	23.74	0.523	/
			1	0	Left Side	709	0.221	-0.31	25.00	24.86	0.228	/
			25	0	Left Side	709	0.22	0.08	24.00	23.74	0.234	/
			1	0	Right Side	709	0.254	-0.39	25.00	24.86	0.262	/
			25	0	Right Side	709	0.243	2.72	24.00	23.74	0.258	/
			1	0	Top Side	709	0.419	0.46	25.00	24.86	0.433	/
			25	0	Top Side	709	0.378	-1.98	24.00	23.74	0.401	/
			1	0	Bottom Side	709	0.214	3.90	25.00	24.86	0.221	/
			25	0	Bottom Side	709	0.203	0.48	24.00	23.74	0.216	/
LTE Band 38	20M	QPSK	1	0	Back Side	2580	0.786	1.89	25.00	24.33	0.917	/
			1	0	Back Side	2595	0.902	3.68	25.00	24.43	1.029	18
			1	0	Back Side	2610	0.812	2.87	25.00	24.30	0.954	/
			50	0	Back Side	2580	0.62	2.65	23.50	23.37	0.639	/
			1	0	Left Side	2595	0.326	-1.22	25.00	24.43	0.372	/
			50	0	Left Side	2580	0.328	1.25	23.50	23.37	0.338	/
			1	0	Right Side	2595	0.377	3.36	25.00	24.43	0.430	/
			50	0	Right Side	2580	0.36	0.27	23.50	23.37	0.371	/
			1	0	Top Side	2595	0.62	3.95	25.00	24.43	0.707	/
			50	0	Top Side	2580	0.561	-3.98	23.50	23.37	0.578	/
			1	0	Bottom Side	2595	0.317	0.98	25.00	24.43	0.361	/
			50	0	Bottom Side	2580	0.3	0.46	23.50	23.37	0.309	/
LTE Band 40	10M	QPSK	1	0	Back Side	2355	0.896	0.24	14.50	14.01	1.003	19
			50	0	Back Side	2355	0.681	-3.06	13.00	12.98	0.684	/
			1	0	Left Side	2355	0.361	1.13	14.50	14.01	0.404	/
			50	0	Left Side	2355	0.362	1.04	13.00	12.98	0.364	/
			1	0	Right Side	2355	0.412	-1.44	14.50	14.01	0.461	/
			50	0	Right Side	2355	0.397	1.04	13.00	12.98	0.399	/
			1	0	Top Side	2355	0.685	2.16	14.50	14.01	0.767	/
			50	0	Top Side	2355	0.618	-2.49	13.00	12.98	0.621	/
			1	0	Bottom Side	2355	0.352	0.81	14.50	14.01	0.394	/
			50	0	Bottom Side	2355	0.336	3.13	13.00	12.98	0.338	/



LTE Band 41	20M	QPSK	1	0	Back Side	2506	0.997	0.03	25.50	25.09	1.096	20
			1	0	Back Side	2593	0.813	-1.17	25.50	25.09	0.893	/
			1	0	Back Side	2680	0.924	3.64	25.50	25.09	1.015	/
			50	0	Back Side	2506	0.666	-0.29	24.00	23.99	0.668	/
			1	0	Left Side	2506	0.37	2.09	25.50	25.09	0.407	/
			50	0	Left Side	2506	0.372	3.98	24.00	23.99	0.373	/
			1	0	Right Side	2506	0.429	-1.16	25.50	25.09	0.471	/
			50	0	Right Side	2506	0.408	3.89	24.00	23.99	0.409	/
			1	0	Top Side	2506	0.656	-3.28	25.50	25.09	0.721	/
			50	0	Top Side	2506	0.638	3.77	24.00	23.99	0.639	/
			1	0	Bottom Side	2506	0.364	2.32	25.50	25.09	0.400	/
			50	0	Bottom Side	2506	0.345	-1.55	24.00	23.99	0.346	/

Note:

1. The test separation of all above table is 0mm.
2. Per KDB 447498 D01, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. Scaled SAR(W/kg) = Measured SAR(W/kg) *Tune-up Scaling Factor
3. When the user enables the personal Wireless router functions for the handsets, actual operations include simultaneous transmission of both the Wi-Fi transmitting frequency and thus cannot be evaluated for SAR under actual use conditions. The "Portable Hotspot" feature on the handset was NOT activated, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal.



12.2 Repeated SAR

Band	Mode	Test Position	Ch.	Result 1g (W/Kg)	Power Drift (%)	Max. Turn-up Power(dBm)	Meas. Output Power(dBm)	Scaled SAR(W/Kg)
PCS 1900	GPRS Data-4 Slot	Back Side	1850.2	0.836	1.03	27.00	26.77	0.881
		Back Side	1880	0.626	-0.56	27.00	26.15	0.762
		Back Side	1909.8	0.696	-1.69	27.00	26.13	0.851
WCDMA Band II	RMC	Back Side	1852.4	0.841	2.47	22.00	21.46	0.952
		Back Side	1880	0.763	-2.83	22.00	21.41	0.874
		Back Side	1907.6	0.945	-2.43	22.00	21.57	1.043
WCDMA Band V	RMC	Back Side	826.4	0.701	2.83	25.50	25.03	0.781
		Back Side	836.4	0.794	-1.69	25.50	25.07	0.877
		Back Side	846.6	0.682	3.27	25.50	24.92	0.779

Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	Result 1g (W/Kg)	Power Drift (%)	Max. Turn-up Power(dBm)	Meas. Output Power (dBm)	Scaled SAR (W/Kg)
LTE Band 2	20M	QPSK	1	0	Back Side	1860	0.663	3.25	21.50	20.79	0.781
			1	0	Back Side	1880	0.674	-0.36	20.50	20.78	0.632
			1	0	Back Side	1900	0.837	-1.14	21.50	21.03	0.933
LTE Band 4	20M	QPSK	1	0	Back Side	1720	0.776	-1.49	21.00	20.69	0.833
			1	0	Back Side	1732.5	0.941	-0.64	21.00	20.94	0.954
			1	0	Back Side	1745	0.741	-1.95	21.00	20.81	0.774
LTE Band 7	20M	QPSK	1	0	Back Side	2510	0.903	-2.35	21.00	20.44	1.027
			1	0	Back Side	2535	1.030	2.56	21.00	20.84	1.069
			1	0	Back Side	2560	0.910	-0.58	21.00	20.81	0.950
LTE Band 38	20M	QPSK	1	0	Back Side	2580	0.779	2.99	25.00	24.33	0.909
			1	0	Back Side	2595	0.863	-3.14	25.00	24.43	0.984
			1	0	Back Side	2610	0.796	-3.81	25.00	24.30	0.935
LTE Band 41	20M	QPSK	1	0	Back Side	2506	0.967	-3.30	25.50	25.09	1.063
			1	0	Back Side	2593	0.812	3.55	25.50	25.09	0.892
			1	0	Back Side	2680	0.881	-1.38	25.50	25.09	0.969
LTE Band 40	20M	QPSK	1	0	Back Side	2355	0.868	2.54	14.50	14.01	0.972



12.3 Repeated SAR measurement

Band	Mode	Test Position	Ch.	Original Measured SAR 1g(W/kg)	1 st Repeated SAR 1g	Ratio
PCS 1900	GPRS Data-4 Slot	Back Side	1850	0.84	0.803	1.047
		Back Side	1880	0.654	0.622	1.051
		Back Side	1910	0.712	0.708	1.005
WCDMA Band II	RMC	Back Side	1852	0.881	0.864	1.020
		Back Side	1880	0.796	0.774	1.029
		Back Side	1908	0.984	0.965	1.020
WCDMA Band V	RMC	Back Side	826.4	0.723	0.720	1.005
		Back Side	836.4	0.81	0.797	1.017
		Back Side	846.6	0.689	0.658	1.047

Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	Original Measured SAR 1g(W/kg) 1g (W/Kg)	1 st Repeated SAR 1g	Ratio
LTE Band 2	20M	QPSK	1	0	Back Side	1860	0.676	0.663	1.020
			1	0	Back Side	1880	0.694	0.674	1.030
			1	0	Back Side	1900	0.856	0.837	1.023
LTE Band 4	20M	QPSK	1	0	Back Side	1720	0.786	0.776	1.013
			1	0	Back Side	1732.5	0.978	0.941	1.039
			1	0	Back Side	1745	0.745	0.741	1.005
LTE Band 7	20M	QPSK	1	0	Back Side	2510	0.941	0.903	1.042
			1	0	Back Side	2535	1.055	1.030	1.024
			1	0	Back Side	2560	0.924	0.910	1.016
LTE Band 38	20M	QPSK	1	0	Back Side	2580	0.786	0.779	1.009
			1	0	Back Side	2595	0.902	0.863	1.045
			1	0	Back Side	2610	0.812	0.796	1.020
LTE Band 41	20M	QPSK	1	0	Back Side	2506	0.997	0.967	1.031
			1	0	Back Side	2593	0.813	0.812	1.002
			1	0	Back Side	2680	0.924	0.881	1.048
LTE Band 40	20M	QPSK	1	0	Back Side	2355	0.896	0.868	1.032

Note:

1. Per KDB 865664 D01, for each frequency band, repeated SAR measurement is required only when the measured SAR is $\geq 0.8\text{W/Kg}$.
2. Per KDB 865664 D01, if the ratio of largest to smallest SAR for the original and first repeated measurement is ≤ 1.2 and the measured SAR $< 1.45\text{W/Kg}$, only one repeated measurement is required.
3. Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is $\geq 1.45\text{W/Kg}$.
4. The ratio is the difference in percentage between original and repeated measured SAR.



12.4 Simultaneous Multi-band Transmission Evaluation

Application Simultaneous Transmission information:

Position	Simultaneous State
Body	1. GSM + 2.4GHz WLAN/5G WLAN+NFC
	2. GSM + Bluetooth+NFC
	3. WCDMA + 2.4GHz WLAN/5G WLAN+NFC
	4. WCDMA + Bluetooth+NFC
	5. LTE + 2.4GHz WLAN/5G WLAN+NFC
	6. LTE + Bluetooth+NFC

NOTE:

1. Bluetooth and WLAN can't simultaneous transmission at the same time.
2. For simultaneous transmission at head and body exposure position, 2 transmitters simultaneous transmission was the worst state.
3. If the test separation distance is <5mm, 5mm is used for excluded SAR calculation.
4. KDB 447498 / 4.3.2 (2) when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:
 - a) $(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f \text{ (GHz)}} / x] \text{ W/kg}$ for test separation distances $\leq 50 \text{ mm}$;
Where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.
 - b) 0.4W/Kg for 1-g SAR and 1.0W/Kg for 10-g SAR, when the separation distance is $>50\text{mm}$.

Estimated SAR		Maximum Turn-up Power		Antenna to user(mm)	Frequency(GHz)	Stand Alone SAR(1g) [W/kg]
		dBm	mW			
NFC	Body	-43	0.000050	5	0.01356	0.0000002



Simultaneous Mode	Position	Mode	Max. 1-g SAR	1-g Sum SAR
			(W/kg)	(W/kg)
GSM + 2.4G WLAN + NFC	Body	GSM	0.886	1.171
		NFC	0.0000002	
		2.4G WLAN	0.285	
GSM + Bluetooth+ NFC	Body	GSM	0.886	1.201
		NFC	0.0000002	
		BT	0.315	
GSM + 5G WLAN+ NFC	Body	GSM	0.886	1.181
		NFC	0.0000002	
		5G WLAN	0.295	
WCDMA + 2.4G WLAN + NFC	Body	WCDMA	1.086	1.371
		NFC	0.0000002	
		2.4G WLAN	0.285	
WCDMA + Bluetooth+ NFC	Body	WCDMA	1.086	1.401
		NFC	0.0000002	
		BT	0.315	
WCDMA + 5G WLAN+ NFC	Body	WCDMA	1.086	1.381
		NFC	0.0000002	
		5G WLAN	0.295	
LTE + 2.4G WLAN + NFC	Body	LTE	1.096	1.381
		NFC	0.0000002	
		2.4G WLAN	0.285	
LTE + Bluetooth+ NFC	Body	LTE	1.096	1.411
		NFC	0.0000002	
		BT	0.315	
LTE + 5G WLAN+ NFC	Body	LTE	1.096	1.391
		NFC	0.0000002	
		5G WLAN	0.295	

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR 1g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR-1g 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 1g is greater than the SAR limit (SAR-1g 1.6 W/kg), SAR test exclusion is determined by the SPLSR.



13. Equipment List

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
750MHz Dipole	MVG	DIP0G750	SN 06/22 DIP0G750-638	2022.02.11	2025.02.10
835MHz Dipole	MVG	DIP0G835	SN 06/22 DIP0G835-639	2022.02.11	2025.02.10
1800MHz Dipole	MVG	DIP1G800	SN 06/22 DIP1G800-640	2022.02.11	2025.02.10
1900MHz Dipole	MVG	DIP1G900	SN 06/22 DIP1G900-641	2022.02.11	2025.02.10
2450MHz Dipole	MVG	DIP2G450	SN 06/22 DIP2G450-645	2022.02.11	2025.02.10
2600MHz Dipole	MVG	DIP2G600	SN 06/22 DIP2G600-646	2022.02.11	2025.02.10
5000MHz Dipole	MVG	DIP5G000	SN 06/22 DIP5G000-653	2022.02.11	2025.02.10
E-Field Probe	MVG	EPGO364	SN 04/22 EPGO364	2024.02.07	2025.02.06
Liquid Calibration Kit	MVG	OCPG 87	SN 06/22 OCPG87	2024.02.07	2025.02.06
Antenna	MVG	ANTA 73	SN 06/22 ANTA 73	N/A	N/A
Ellipsoid Phantom	MVG	ELLI 51	SN 06/22 ELLI 51	N/A	N/A
Phantom	MVG	SAM 148	SN 06/22 SAM148	N/A	N/A
Phone holder	MVG	MSH 117	SN 06/22 MSH 117	N/A	N/A
Laptop positioner	MVG	LSH 36	SN 06/22 LSH 38	N/A	N/A
Directional coupler	SHW	SHWDCP	202203280013	N/A	N/A
Network Analyzer	ZVL	R&S	116184-HC	2024.03.25	2025.03.24
Multi Meter	DMM6500	Keithley	4527252	2024.03.15	2025.03.14
Signal Generator	Keysight	N5182B	MY59100717	2024.03.09	2025.03.08
Wireless Communication Test Set	R&S	CMW500	137737	2024.03.09	2025.03.08
Power Sensor	R&S	Z11	116184	2024.02.23	2025.02.22
Electronic Temperature hygrometer	N/A	ST-W2318	N/A	2024.03.11	2025.03.10
Temperature hygrometer	N/A	TP101	N/A	2024.03.11	2025.03.10



Appendix A. System Validation Plots

System Performance Check Data (750MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2024-09-06

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW750
Channels	Middle
Signal	CW
Frequency (MHz)	750.000
Relative permittivity	41.39
Conductivity (S/m)	0.92
Probe	SN 04/22 EPGO364
ConvF	1.68
Crest factor:	1:1




Maximum location: X=1.00, Y=2.00 ; SAR Peak: 1.52 W/kg

SAR 10g (W/Kg)	0.528
SAR 1g (W/Kg)	0.824



Z Axis Scan





System Performance Check Data (835MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2024-10-16

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW835
Channels	Middle
Signal	CW
Frequency (MHz)	835.000
Relative permittivity	41.94
Conductivity (S/m)	0.87
Probe	SN 04/22 EPGO364
ConvF	1.70
Crest factor:	1:1




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 1.32 W/kg

SAR 10g (W/Kg)	0.588
SAR 1g (W/Kg)	0.936



Z Axis Scan





System Performance Check Data (1800MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement:2023-10-20

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW1800
Channels	Middle
Signal	CW
Frequency (MHz)	1800.000
Relative permittivity	40.56
Conductivity (S/m)	1.42
Probe	SN 04/22 EPGO364
ConvF	1.91
Crest factor:	1:1




Maximum location: X=2.00, Y=2.00 ; SAR Peak: 1.88 W/kg

SAR 10g (W/Kg)	0.615
SAR 1g (W/Kg)	3.869



Z Axis Scan





System Performance Check Data (1900MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement:2024-10-18

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW1900
Channels	Middle
Signal	CW
Frequency (MHz)	1900.000
Relative permittivity	41.28
Conductivity (S/m)	1.41
Probe	SN 04/22 EPGO364
ConvF	2.24
Crest factor:	1:1




Maximum location: X=0.00, Y=0.00 ; SAR Peak: 6.84 W/kg

SAR 10g (W/Kg)	2.025
SAR 1g (W/Kg)	4.086



Z Axis Scan





System Performance Check Data (2450MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement:2024-09-05

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW2450
Channels	Middle
Signal	CW
Frequency (MHz)	2450.000
Relative permittivity	39.79
Conductivity (S/m)	1.76
Probe	SN 04/22 EPGO364
ConvF	2.30
Crest factor:	1:1




Maximum location: X=3.00, Y=0.00 ; SAR Peak: 9.55 W/kg

SAR 10g (W/Kg)	2.327
SAR 1g (W/Kg)	5.410



Z Axis Scan





System Performance Check Data (2600MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement:2024-10-13

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW2600
Channels	Middle
Signal	CW
Frequency (MHz)	2600.000
Relative permittivity	39.39
Conductivity (S/m)	1.95
Probe	SN 04/22 EPGO364
ConvF	2.35
Crest factor:	1:1




Maximum location: X=5.00, Y=0.00 ; SAR Peak: 6.19 W/kg

SAR 10g (W/Kg)	2.393
SAR 1g (W/Kg)	5.666



Z Axis Scan





System Performance Check Data (5200MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=4mm, dy=4mm

Zoom scan resolution: dx=4mm, dy=4mm, dz=2mm

Date of measurement:2024-08-31

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW5200
Channels	Middle
Signal	CW
Frequency (MHz)	5200.000
Relative permittivity	36.94
Conductivity (S/m)	4.64
Probe	SN 04/22 EPGO364
ConvF	1.98
Crest factor:	1:1




Maximum location: X=1.00, Y=0.00 ; SAR Peak: 26.81 W/kg

SAR 10g (W/Kg)	2.298
SAR 1g (W/Kg)	8.100



Z Axis Scan





System Performance Check Data (5600MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=4mm, dy=4mm

Zoom scan resolution: dx=4mm, dy=4mm, dz=2mm

Date of measurement:2024-08-29

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW5600
Channels	Middle
Signal	CW
Frequency (MHz)	5600.000
Relative permittivity	36.13
Conductivity (S/m)	5.12
Probe	SN 04/22 EPGO364
ConvF	1.86
Crest factor:	1:1




Maximum location: X=-1.00, Y=0.00 ; SAR Peak: 23.91 W/kg

SAR 10g (W/Kg)	2.334
SAR 1g (W/Kg)	8.113



Z Axis Scan





System Performance Check Data (5800MHz)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement:2024-10-23

Experimental conditions.

Phantom	Validation plane
Device Position	Dipole
Band	CW5800
Channels	Middle
Signal	CW
Frequency (MHz)	5800.000
Relative permittivity	35.90
Conductivity (S/m)	5.31
Probe	SN 04/22 EPGO364
ConvF	1.71
Crest factor:	1:1




Maximum location: X=1.00, Y=0.00 ; SAR Peak: 24.10 W/kg

SAR 10g (W/Kg)	2.353
SAR 1g (W/Kg)	8.133



Z Axis Scan






Appendix B. SAR Test Plots

Plot 1:

Test Date	2024-10-16
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7, dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	GPRS850
Signal	TDMA (GPRS)
Frequency	848.8
SAR 10g (W/Kg)	0.435
SAR 1g (W/Kg)	0.780
ConvF	1.70
Relative permittivity	41.94
Conductivity (S/m)	0.87

Maximum location: X=14.00, Y=15.00 ; SAR Peak: 1.29 W/kg






Plot 2:

Test Date	2024-10-20
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	GPRS1900
Signal	TDMA (GPRS)
Frequency	1850.2
SAR 10g (W/Kg)	0.451
SAR 1g (W/Kg)	0.840
ConvF	2.24
Relative permittivity	41.28
Conductivity (S/m)	1.41

Maximum location: X=-40.00, Y=38.00 ; SAR Peak: 1.43 W/kg






Plot 3:

Test Date	2024-10-18
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	Band 2 (1900)
Signal	WCDMA
Frequency	1907.6
SAR 10g (W/Kg)	0.517
SAR 1g (W/Kg)	0.984
ConvF	2.24
Relative permittivity	41.28
Conductivity (S/m)	1.41

Maximum location: X=2.00, Y=-16.00 ; SAR Peak: 1.71 W/kg






Plot 4:

Test Date	2024-10-20
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	Band 4 (1700)
Signal	WCDMA
Frequency	1752.4
SAR 10g (W/Kg)	0.424
SAR 1g (W/Kg)	0.784
ConvF	1.91
Relative permittivity	40.56
Conductivity (S/m)	1.42

Maximum location: X=5.00, Y=-24.00 ; SAR Peak: 1.31 W/kg






Plot 5:

Test Date	2024-10-16
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	Band 5 (850)
Signal	WCDMA
Frequency	846.6
SAR 10g (W/Kg)	0.420
SAR 1g (W/Kg)	0.810
ConvF	1.70
Relative permittivity	41.94
Conductivity (S/m)	0.87

Maximum location: X=2.00, Y=-15.00 ; SAR Peak: 1.34 W/kg






Plot 6:

Test Date	2024-09-05
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	ISM ANT 1
Signal	IEEE 802.11b
Frequency	2437
SAR 10g (W/Kg)	0.121
SAR 1g (W/Kg)	0.267
ConvF	2.30
Relative permittivity	39.79
Conductivity (S/m)	1.76

Maximum location: X=-12.00, Y=-59.00 ; SAR Peak: 0.52 W/kg






Plot 7:

Test Date	2024-09-05
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	Bluetooth
Signal	GFSK
Frequency	2441
SAR 10g (W/Kg)	0.142
SAR 1g (W/Kg)	0.311
ConvF	2.30
Relative permittivity	36.94
Conductivity (S/m)	4.64

Maximum location: X=3.00, Y=-48.00 ; SAR Peak: 0.59 W/kg






Plot 8:

Test Date	2024-10-09
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm
Phantom	Validation plane
Device Position	Back Side
Band	U-NII-1
Signal	IEEE 802.11a
Frequency	5200
SAR 10g (W/Kg)	0.084
SAR 1g (W/Kg)	0.228
ConvF	1.98
Relative permittivity	36.94
Conductivity (S/m)	4.64

Maximum location: X=-7.00, Y=-64.00 ; SAR Peak: 1.33 W/kg






Plot 9:

Test Date	2024-08-31
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm
Phantom	Validation plane
Device Position	Back Side
Band	U-NII-1
Signal	IEEE 802.11a
Frequency	5260
SAR 10g (W/Kg)	0.107
SAR 1g (W/Kg)	0.275
ConvF	1.98
Relative permittivity	36.94
Conductivity (S/m)	4.64

Maximum location: X=3.00, Y=-57.00 ; SAR Peak: 1.21 W/kg






Plot 10:

Test Date	2024-08-29
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm
Phantom	Validation plane
Device Position	Back Side
Band	U-NII-2c
Signal	IEEE 802.11a
Frequency	5700
SAR 10g (W/Kg)	0.054
SAR 1g (W/Kg)	0.120
ConvF	1.86
Relative permittivity	36.13
Conductivity (S/m)	5.12

Maximum location: X=-14.00, Y=80.00 ; SAR Peak: 0.67 W/kg






Plot 11:

Test Date	2024-10-23
Area Scan	dx=8mm dy=8mm
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm
Phantom	Validation plane
Device Position	Back Side
Band	U-NII-3
Signal	IEEE 802.11a
Frequency	5825
SAR 10g (W/Kg)	0.088
SAR 1g (W/Kg)	0.188
ConvF	1.71
Relative permittivity	35.90
Conductivity (S/m)	5.31

Maximum location: X=10.00, Y=-62.00 ; SAR Peak: 0.97 W/kg






Plot 12:

Test Date	2024-10-18
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 2
Signal	LTE FDD
Frequency	1900
SAR 10g (W/Kg)	0.436
SAR 1g (W/Kg)	0.856
ConvF	2.24
Relative permittivity	41.28
Conductivity (S/m)	1.41

Maximum location: X=-37.00, Y=43.00 ; SAR Peak: 1.47 W/kg






Plot 13:

Test Date	2024-10-20
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	ELLI
Device Position	Back Side
Band	LTE band 4
Signal	LTE FDD
Frequency	1732.5
SAR 10g (W/Kg)	0.507
SAR 1g (W/Kg)	0.978
ConvF	1.91
Relative permittivity	40.56
Conductivity (S/m)	1.42

Maximum location: X=-38.00, Y=40.00 ; SAR Peak: 1.69 W/kg






Plot 14:

Test Date	2024-10-16
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 5
Signal	LTE FDD
Frequency	829
SAR 10g (W/Kg)	0.324
SAR 1g (W/Kg)	0.640
ConvF	1.68
Relative permittivity	41.94
Conductivity (S/m)	0.87

Maximum location: X=-5.00, Y=-8.00 ; SAR Peak: 1.07 W/kg






Plot 15:

Test Date	2024-10-13
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 7
Signal	LTE FDD
Frequency	2535
SAR 10g (W/Kg)	0.507
SAR 1g (W/Kg)	1.055
ConvF	2.35
Relative permittivity	39.39
Conductivity (S/m)	1.95

Maximum location: X=-54.00, Y=64.00 ; SAR Peak: 1.79 W/kg






Plot 16:

Test Date	2024-09-06
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 12
Signal	LTE FDD
Frequency	707.5
SAR 10g (W/Kg)	0.326
SAR 1g (W/Kg)	0.532
ConvF	1.68
Relative permittivity	41.39
Conductivity (S/m)	0.92

Maximum location: X=-24.00, Y=9.00 ; SAR Peak: 0.81 W/kg






Plot 17:

Test Date	2024-09-06
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 17
Signal	LTE FDD
Frequency	709
SAR 10g (W/Kg)	0.351
SAR 1g (W/Kg)	0.547
ConvF	1.68
Relative permittivity	41.39
Conductivity (S/m)	0.92

Maximum location: X=-22.00, Y=8.00 ; SAR Peak: 0.78 W/kg






Plot 18:

Test Date	2024-10-13
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 38
Signal	LTE TDD
Frequency	2595
SAR 10g (W/Kg)	0.374
SAR 1g (W/Kg)	0.902
ConvF	2.35
Relative permittivity	39.39
Conductivity (S/m)	1.95

Maximum location: X=-22.00, Y=-11.00 ; SAR Peak: 1.70 W/kg






Plot 19:

Test Date	2024-09-05
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 40
Signal	LTE TDD
Frequency	2355
SAR 10g (W/Kg)	0.441
SAR 1g (W/Kg)	0.896
ConvF	2.30
Relative permittivity	39.79
Conductivity (S/m)	1.76

Maximum location: X=-16.00, Y=36.00 ; SAR Peak: 1.66 W/kg






Plot 20:

Test Date	2024-10-13
Area Scan	dx=8mm dy=8mm
Zoom Scan	5x5x7,dx=8mm dy=8mm dz=5mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE band 41
Signal	LTE TDD
Frequency	2506
SAR 10g (W/Kg)	0.430
SAR 1g (W/Kg)	0.997
ConvF	2.35
Relative permittivity	39.39
Conductivity (S/m)	1.95

Maximum location: X=-7.00, Y=-16.00 ; SAR Peak: 1.77 W/kg





Appendix C. Probe Calibration and Dipole Calibration Report

Refer the appendix Calibration Report.

※※※※※END OF THE REPORT※※※※※