



Tengxiang Technology.Inc

东莞市腾祥电子有限公司

Product Number: AN2450-FPC168BX

Product Name: Antenna

Specification For Approval

Date: 2024.3.26

Version: 1.0

客户名称

Customer:

九安

客户料号

Customer P/N:

腾祥料号

T X P/N:

AN2450-FPC168BX

规格描述

Description :

2.4G /5GFPC 天线 1.13mm 黑色线 L=370mm +IPEX

Tengxiang Checked By: 腾祥审核		Customer Approved By: 客户审核	
DRAWN 制 作	路婷	TESTED BY 检 测	
CHECKED BY 审 核	胡超	CHECKED BY 审 核	
Q.C.DEPT. 品 管	祁志鹏	Q.C.DEPT. 品 管	
APPROVED BY 核 准	韦佳	APPROVEDBY 核 准	



NO.53 Shatou ShaChong Road, ChangAn Town, Guangdong province, China

中国广东省东莞市长安镇沙头区沙涌路 53 号

TEL:86-769-81873082 FAX:86-769-82663788

<http://www.tenxiang.cn>



Tengxiang Technology.Inc

东莞市腾祥电子有限公司

Product Number: AN2450-FPC168BX

Product Name: Antenna

Index:

1. Specification (规格)
2. Characteristics and Reliability Test (产品特性和可靠性测试标准)
3. Antenna - S Parameter Test Data (样品测试数据)
4. Antenna - Radiation Pattern Test Data (辐射模式测试数据)
5. Mechanical and Packing Drawing (图纸包装规范)

Revision History (变更履历)

Revision	Date	Change Notification	Description
1.0	2024.3.26	初版	

Product Number: AN2450-FPC168BX

Product Name: Antenna

1. Specification

Sample Photo



A. Electrical Characteristics

Frequency 频率	2400-2500 MHz/5150-5850MHz
S.W.R. 驻波比	≤ 2.0
Antenna Gain 增益	3.39dBi / 2.95dBi
Polarization 极化方式	Linear
Impedance 阻抗	50 Ohm

B. Material & Mechanical Characteristics

Cable Type 线材规格	OD1.13mm ,Black
Connector Type 连接器规格	I-PEX

C. Environmental

Storage Temperature 存储温度	- 40°C ~ +80 °C
Operation Temperature 工作温度	- 40°C ~ +80 °C

Product Number: AN2450-FPC168BX

Product Name: Antenna



2. Characteristics and Reliability Test

Test Items 测试项目		Test Condition and Procedure 测试方法	Requirements 要求	Result 结果
1	V.S.W.R. 电压驻波比	Set DUT on Network Analyzer; make individual calibration to test 设置网络分析仪参数进行测试	Directive DUT specification 符合待测物规范	PASS
2	Insertion Loss 插入损失	Set DUT on Network Analyzer; make individual calibration to test 设置网络分析仪参数进行测试	Directive DUT specification 符合待测物规范	PASS
3	Antenna Gain 天线增益	Set DUT on Antenna Chamber; make individual calibration to test 设置天线暗室参数进行测试	Directive DUT specification 符合待测物规范	PASS
4	Solderability 可焊性	GB / T2423.28-2005 Temp: 260±5° C;Duration: 5 seconds 温度 260±5° C;持续 5 秒	Tin evenly on full 上锡均匀饱满	PASS
5	Pull Test 拉力	Holding with individual specification; force applied to axis of terminal .单独定义产品端子拉力	1. Directive DUT specification 2. Frequency Tol.≤5% 符合待测物规范;频率偏移≤5%	PASS
6	Dimension 尺寸	Inspection of dimension, color, material, package, surface process.检查尺寸,颜色,材料,包装,表面处理	Directive DUT specification 符合待测物规范	PASS
7	Salt Spray 盐雾	GB / T 2423.17-2008 Temp: 35°C; RH: ≥ 95%; NaCl solution: ≥ 5%;Time: 24H 温度 35°C; 湿度≥95%;盐水浓度≥5%; 测试 24H	1. No Visual Damage 2. Frequency Tol.≤5% 无明显外观不良;频率偏移≤5%	PASS
8	RoHS	With Reference to IEC 62321:2008 with flow chart 参考 IEC 62321 测试流程	Directive RoHS 2015/863/EU 符合 RoHS 2015/863/EU 标准	PASS

Product Number: AN2450-FPC168BX

Product Name: Antenna

3. Antenna - S Parameter Test Data



Product Number: AN2450-FPC168BX

Product Name: Antenna

4. Antenna - Radiation Pattern Test Data

Frequency ID	1	2	3	4	5	6	7	8	9	10	11
Frequency (MHz)	2400.0	2410.0	2420.0	2430.0	2440.0	2450.0	2460.0	2470.0	2480.0	2490.0	2500.0
Gain (dBi)	2.81	2.96	3.03	3.10	3.21	3.39	3.25	3.29	3.17	3.06	2.89
Efficiency (%)	44.88	46.24	44.97	44.48	45.43	46.16	45.86	44.60	45.68	44.23	43.20





12	13	14	15	16	17	18	19	20	21	22	23	24	25	26
5150.0	5200.0	5250.0	5300.0	5350.0	5400.0	5450.0	5500.0	5550.0	5600.0	5650.0	5700.0	5750.0	5800.0	5850.0
2.70	2.95	2.79	2.64	2.53	2.62	2.86	2.50	2.65	2.42	2.67	2.51	2.66	2.54	2.49
44.53	43.65	42.83	43.69	42.56	43.33	44.29	43.69	42.69	43.07	44.79	42.51	43.13	43.69	42.95

XZ





YZ

XY





2400MHz



2450MHz




2500MHz




Product Number: AN2450-FPC168BX

Product Name: Antenna


5150MHz



5550MHz



5850MHz



5. Mechanical Drawing See attached files

1		2		3		4		5		6		7		8			
HF										SIGN		DATE		DESCRIPTION		APPROVER	
RoHS2.0																	
REACH																	
CONFIDENTIAL																	
1 18.5 40.0 AN2400-FPC400185 2 370.0±5.0 3																	
Note: 1.Mark * is important dimension;"Cpk "Identify for process control(CpK≥ 1.33). 2.Tolerance:Unmarked tolerance refer to the standard tolerance please. 3.Pay attention to the direction of the connector.																	
3 CR-113-ZP-A I-PEX Cu Au Plated 1 2 CB-113BS Coaxial Cable OD1.13 Black 1 1 AN2400-FPC400185 FPC Black 1 No. Part Number Name Material Finish Q'ty Tengxiang Electronics Co., Ltd. TITLE: Antenna PART NO.: AN2450-FPC168BX CUSTOMER P/N: / APP BY CHK BY RF BY DES BY UNITS: mm SCALE: 1/1 REVISION: A Tolerance X.X ±0.5 X.XX ±0.2 X° ±1																	
1		2		3		4		5		6		7		8			

產品包裝規範


PACKING CRITERION

Date: 2024.03.26

Page: 1 of 1


Part Number : AN2450-FPC168BX	Revision : A
Name: Antenna	Customer : ALL

1 . Enter PE bag。




100pcs/ PE bag

2.PACKING。




8000pcs/Carton


3. SEALING。



SIDE



FRONT



APPROVED BY : YCX CHECKED BY : HC DESIGNED BY : SY Y