

# FCC RF EXPOSURE REPORT

**FCC ID: TE7C200**

**Project No.** : 1905C161  
**Equipment** : Pan/Tilt Home Security Wi-Fi Camera  
**Model Name** : Tapo C200  
**Series Model** : N/A  
**Applicant** : TP-Link Technologies Co., Ltd.  
**Address** : Building 24(floors1,3,4,5) and 28(floors1-4)  
Central Science and Technology Park,  
Shennan Rd, Nanshan, Shenzhen, China  
  
**According** : FCC Guidelines for Human Exposure IEEE  
C95.1 & FCC Part 2.1091

## **B T L I N C .**

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan,  
Guangdong, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000



Certificate #5123.02

**REPORT ISSUED HISTORY**

Report Version	Description	Issued Date
R00	Original Issue.	Jul. 02, 2019
R01	Changed the product name and model name.	Jul. 16, 2019
R02	Added brand name.	Jul. 22, 2019

## 1. GENERAL SUMMARY

Equipment : Pan/Tilt Home Security Wi-Fi Camera  
 Brand Name : tp-link, tapo  
 Test Model : Tapo C200  
 Series Model : N/A  
 Applicant : TP-Link Technologies Co., Ltd.  
 Manufacturer : TP-Link Technologies Co., Ltd.  
 Address : Building 24(floors1,3,4,5) and 28(floors1-4) Central Science and Technology Park, Shennan Rd, Nanshan, Shenzhen, China  
 Date of Test : Jun. 01, 2019 ~ Jun. 18, 2019  
 Test Sample : Engineering Sample No.: DG19053129  
 Standards : FCC Title 47 Part 2.1091, OET Bulletin 65 Supplement C

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FCCP-2-1905C161) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of A2LA according to the ISO/IEC 17025 quality assessment standard and technical standard(s).

## 2. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	Internal	N/A	2

### 3. TEST RESULTS

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Average Output Power (dBm)	Max. Average Output Power (mW)	Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
2	1.5849	16.94	49.4311	0.01559	1	Complies

Note: The calculated distance is 20 cm.

**End of Test Report**