

# TEST REPORT

EMI Test for FCC Certification of LM-Q720VSP Model

APPLICANT

LG Electronics USA, Inc.

REPORT NO.

HCT-EM-1906-FC011-R1

DATE OF ISSUE

June 25, 2019

**HCT Co., Ltd.**

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA  
Tel. +82 31 634 6300 Fax. +82 31 645 6401



**HCT Co., Ltd.**

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA  
Tel. +82 31 634 6300 Fax. +82 31 645 6401

# TEST REPORT

EMI Test for  
FCC Certification

REPORT NO.  
HCT-EM-1906-FC011-R1

DATE OF ISSUE  
June 25, 2019

FCC ID.  
ZNFQ720VS

Applicant LG Electronics USA, Inc.  
1000 Sylvan Avenue, Englewood Cliffs NJ 07632 United States

Product Name Multi-band GSM/CDMA/WCDMA/LTE Phone with WLAN, Bluetooth and NFC  
Model Name LM-Q720VSP  
Series Model Name Refer to the clause 1.1 Description of EUT

Date of Test June 15, 2019

Test Standard Used FCC CFR 47 PART 15 Subpart B Class B  
ANSI C63.4-2014

Test Results Refer to the present document

Manufacturer LG Electronics Inc.

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

Tested by  
Na-Eun Song

(signature)

Technical Manager  
Jeong-Hyun Choi

(signature)

## REVISION HISTORY

The revision history for this test report is shown in table.

| Revision No. | Date of Issue | Description             |
|--------------|---------------|-------------------------|
| 0            | June 17, 2019 | Initial Release         |
| 1            | June 25, 2019 | Added Series Model Name |

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4-2014. (See Test Report if any modifications were made for compliance)

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

HCT certifies that no party to application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C 862

## CONTENTS

|  |    |
|--|----|
| 1. GENERAL INFORMATION                                   | 5  |
| 1.1 Description of EUT                                   | 5  |
| 1.2 Tested System Details                                | 7  |
| 1.3 Cable Description                                    | 7  |
| 1.4 Noise Suppression Parts on Cable. (I/O Cable)        | 8  |
| 1.5 Test Facility  | 8  |
| 1.6 Calibration of Measuring Instrument                  | 8  |
| 1.7 Measurement Uncertainty                              | 9  |
| 2. DESCRIPTION OF TEST                                   | 10 |
| 2.1 Measurement of Conducted Emission                    | 10 |
| 2.2 Measurement of Radiated Emission                     | 11 |
| 2.3 Configuration of Tested System                       | 12 |
| 3. PRELIMINARY TEST                                      | 13 |
| 3.1 Conducted Emission                                   | 13 |
| 3.2 Radiated Emission                                    | 13 |
| 4. CONDUCTED EMISSION AND RADIATED EMISSION TEST SUMMARY | 14 |
| 4.1 Conducted Emission                                   | 14 |
| 4.2 Radiated Emission Below 1 GHz                        | 21 |
| 4.3 Radiated Emission Above 1 GHz                        | 23 |
| 5. CONCLUSION  | 26 |
| 6. APPENDIX A. TEST SETUP PHOTOGRAPHS                    | 27 |

## 1. GENERAL INFORMATION

### 1.1 Description of EUT

Its basic purpose is used for communications.

|                   |   |
|-------------------|---|
| FCC ID            | ZNFQ720VS   |
| Model             | LM-Q720VSP  |
| Series Model Name | LM-Q720VS, LM-Q720VSPP, LMQ720VS, LMQ720VSP, LMQ720VSPP, Q720VS, Q720VSP, Q720VSPP, LM-Q720VSPB, LMQ720VSPB, Q720VSPB   |
| EUT Type          | Multi-band GSM/CDMA/WCDMA/LTE Phone with WLAN, Bluetooth and NFC  |
| TX Frequency      | 824.70 MHz to 848.31 MHz (CDMA BC0)<br>1 851.25 MHz to 1 908.75 MHz (CDMA BC1)<br>824.2 MHz to 848.8 MHz (GSM 850)<br>1 850.2 MHz to 1 909.8 MHz (GSM 1 900)<br>1 852.4 MHz to 1 907.6 MHz (WCDMA B2)<br>826.4 MHz to 846.6 MHz (WCDMA B5)<br>1 850 MHz to 1 910 MHz (LTE B2)<br>1 710 MHz to 1 755 MHz (LTE B4)<br>824 MHz to 849 MHz (LTE B5)<br>777 MHz to 787 MHz (LTE B13)<br>1 710 MHz to 1 780 MHz (LTE B66)<br>2 402 MHz to 2 480 MHz (Bluetooth)<br>2 412 MHz to 2 462 MHz (WiFi 2.4 GHz)<br>5 180 MHz to 5 240 MHz (WiFi 5 GHz_UNII 1)<br>5 260 MHz to 5 320 MHz (WiFi 5 GHz_UNII 2A)<br>5 500 MHz to 5 720 MHz (WiFi 5 GHz_UNII 2C)<br>5 745 MHz to 5 825 MHz (WiFi 5 GHz_UNII 3)<br>13.56 MHz (NFC) |

|              |   |
|--------------|---|
| RX Frequency | 869.70 MHz to 893.31 MHz (CDMA BC0)         |
|              | 1 931.25 MHz to 1 988.75 MHz (CDMA BC1)     |
|              | 869.2 MHz to 893.8 MHz (GSM 850)            |
|              | 1 930.2 MHz to 1 989.8 MHz (GSM 1 900)      |
|              | 1 932.4 MHz to 1 987.6 MHz (WCDMA B2)       |
|              | 871.4 MHz to 891.6 MHz (WCDMA B5)           |
|              | 1 930 MHz to 1 990 MHz (LTE B2)             |
|              | 2 110 MHz to 2 155 MHz (LTE B4)             |
|              | 869 MHz to 894 MHz (LTE B5)                 |
|              | 746 MHz to 756 MHz (LTE B13)                |
|              | 2 110 MHz to 2 200 MHz (LTE B66)            |
|              | 2 402 MHz to 2 480 MHz (Bluetooth)          |
|              | 2 412 MHz to 2 462 MHz (WiFi 2.4 GHz)       |
|              | 5 180 MHz to 5 240 MHz (WiFi 5 GHz_UNII 1)  |
|              | 5 260 MHz to 5 320 MHz (WiFi 5 GHz_UNII 2A) |
|              | 5 500 MHz to 5 720 MHz (WiFi 5 GHz_UNII 2C) |
|              | 5 745 MHz to 5 825 MHz (WiFi 5 GHz_UNII 3)  |
|              | 13.56 MHz (NFC)                             |

## 1.2 Tested System Details

All equipment descriptions used in the tested system (including inserted cards) are:

| Device Type         | Model Name  | Serial Number | Manufacturer       |
|---------------------|---|---------------|--------------------|
| EUT                 | LM-Q720VSP  | -             | LG                 |
| Data Cable          | EAD64746103                                       | -             | Ningbo             |
| Earphone            | EAB64468445                                       | -             | BUJEON             |
| Notebook PC         | ProBook6560b                                      | 5CB2053MXF    | HP                 |
| Notebook PC adaptor | Series PPP009L-E                                  | -             | LITE-ON Technology |
| Gateway             | TL-WR747N   | -             | TP Link            |
| Gateway adaptor     | T090060-2H1                                       | -             | TP Link            |
| Serial mouse        | Serial 2 Button mouse                             | 02031069      | Radio Shack        |
| RJ45 cable          | -   | -             | -                  |
| Micro SD Card       | SAMSUNG EVO+ microSDXC<br>CLASS10 UHS- I (256 GB) | -             | SAMSUNG            |

## 1.3 Cable Description

| Product Name | Port          | Power Cord Shielded (Y/N) | I/O Cable Shielded (Y/N) | Length (m) |
|--------------|---------------|---------------------------|--------------------------|------------|
| EUT          | USB Type C    | Y                         | Y                        | (P,D) 1.0  |
|              | Earphone      | N/A                       | N                        | (D) 1.2    |
| Notebook PC  | RJ 45         | N/A                       | N                        | (D) 1.6    |
|              | Serial(Mouse) | N/A                       | Y                        | (D) 1.8    |
|              | DC IN         | N                         | N/A                      | (P) 1.8    |
| Gateway      | DC IN         | N                         | N/A                      | (P) 1.8    |

NOTE. The marked "(D)" means the data cable and "(P)" means the power cable.

#### 1.4 Noise Suppression Parts on Cable (I/O Cable)

| Product Name | Port          | Ferrite Bead (Y/N) | Location | Metal Hood (Y/N) | Location        |
|--------------|---------------|--------------------|----------|------------------|-----------------|
| EUT          | USB Type C    | N                  | N/A      | Y                | Both End        |
|              | Earphone      | N                  | N/A      | Y                | EUT End         |
| Notebook PC  | RJ 45         | N                  | N/A      | N                | N/A             |
|              | Serial(Mouse) | N                  | N/A      | Y                | Notebook PC End |

#### 1.5 Test Facility

Test site is located at 74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, South Korea. Those measurement facilities are constructed in conformance with the requirements of ANSI C63.4-2014. The Normalized site attenuations (30 MHz to 1 GHz) and Site validation (1 GHz to 18 GHz) were performed in accordance with the standard in ANSI C63.4-2014

| Measurement Facilities  | Designation No. |
|---|-----------------|
| Radiated Field strength measurement facility<br>3 m Semi Anechoic chamber     | KR0032          |
| Radiated Field strength measurement facility<br>10 m Semi Anechoic chamber #1 |                 |
| Radiated Field strength measurement facility<br>10 m Semi Anechoic chamber #2 |                 |

#### 1.6 Calibration of Measuring Instrument

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturers recommendations for utilizing calibration equipment, which is traceable to recognized national standards. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version : 2006).



## 1.7 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the  $U_{CISPR}$  measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

| Parameter                               | Expanded Uncertainty |
|---|----------------------|
| Conducted Emission (0.15 MHz to 30 MHz) | 1.78 dB              |
| Radiated Emissions (30 MHz to 1 GHz)    | 6.00 dB              |
| Radiated Emissions (1 GHz to 18 GHz)    | 4.78 dB              |
| Radiated Emissions (18 GHz to 40 GHz)   | 4.94 dB              |

## 2. DESCRIPTION OF TEST

### 2.1 Measurement of Conducted Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 7.3

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN).  
If the EUT is connected to the PC through USB, the AC power-line adapter of the PC is directly connected to a line impedance stabilization network (LISN).  
Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both conducted lines are measured in Quasi-Peak and Average mode, including the worst-case data points for each tested configuration.
- c. The frequency range from 150 kHz to 30 MHz was searched.

#### Conducted Emission Limits

| Frequency (MHz) | Resolution Bandwidth (kHz) | Class A           |                | Class B           |                |
|-----------------|----------------------------|-------------------|----------------|-------------------|----------------|
|                 |                            | Quasi-Peak (dBμV) | Average (dBμV) | Quasi-Peak (dBμV) | Average (dBμV) |
| 0.15 to 0.5     | 9                          | 79                | 66             | 66 to 56*         | 56 to 46*      |
| 0.5 to 5        | 9                          | 73                | 60             | 56                | 46             |
| 5 to 30         | 9                          | 73                | 60             | 60                | 50             |

NOTE. Decreases with the logarithm of the frequency.

## 2.2 Measurement of Radiated Emission

The test procedure was in accordance with ANSI C63.4-2014, Clause 8.3

- The EUT was placed on the top of a turn table 0.8 meters above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 m away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from 1 m to 4 m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 m to 4 m and the turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Quasi-Peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- The test-receiver system was set to Peak and Average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.
- Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.  
(1 GHz to 40 GHz)

### Radiated Emission Limits


| Frequency<br>(MHz) | Class A                    |  |                                     | Class B                       |  |                                     |
|--------------------|----------------------------|--|-------------------------------------|-------------------------------|--|-------------------------------------|
|                    | Antenna<br>Distance<br>(m) | Field<br>Strength<br>( $\mu\text{V/m}$ ) | Quasi-Peak<br>(dB $\mu\text{V/m}$ ) | Antenna<br>Distance<br>(m)    | Field<br>Strength<br>( $\mu\text{V/m}$ ) | Quasi-Peak<br>(dB $\mu\text{V/m}$ ) |
| 30 to 88           | 10                         | 90                                       | 39.0                                | 3                             | 100                                      | 40.0                                |
| 88 to 216          | 10                         | 150                                      | 43.5                                | 3                             | 150                                      | 43.5                                |
| 216 to 960         | 10                         | 210                                      | 46.4                                | 3                             | 200                                      | 46.0                                |
| Above 960          | 10                         | 300                                      | 49.5                                | 3                             | 500                                      | 54.0                                |
| Frequency<br>(MHz) | Antenna Distance<br>(m)    | Class A                                  |                                     | Class B                       |  |                                     |
|                    |                            | Peak<br>(dB $\mu\text{V/m}$ )            | Average<br>(dB $\mu\text{V/m}$ )    | Peak<br>(dB $\mu\text{V/m}$ ) | Average<br>(dB $\mu\text{V/m}$ )         |                                     |
| Above 1 000        | 3                          | 80                                       | 60                                  | 74                            | 54                                       |                                     |

### 2.2.1 Frequency Range of Radiated Measurements

An unintentional radiator, including a digital device, the spectrum shall be investigated from the lowest radio frequency signal generated or used in the device, without going below the lowest frequency for which a Radiated Emission limit is specified, up to the frequency shown in the following table

| Highest frequency generated or used in the device or on which the device operates or tunes (MHz) | Upper frequency of measurement range (MHz)                          |
|--|---|
| Below 1.705  | 30  |
| 1.705 to 108   | 1 000   |
| 108 to 500   | 2 000   |
| 500 to 1 000   | 5 000   |
| Above 1 000  | 5th harmonic of the highest frequency or 40 GHz, whichever is lower |
| Below 1.705  | 30  |

### 2.3 Configuration of Tested System



Non-Conductive Table

Power Line: 120 VAC, 60 Hz

### 3. PRELIMINARY TEST

#### 3.1 Conducted Emission

It was tested the following operating mode, after connecting all peripheral devices.

**Operating Modes:** Data Communication mode

#### 3.2 Radiated Emission

It was tested the following operating mode, after connecting all peripheral devices.

**Operating Modes:** Data Communication mode

## 4. CONDUCTED EMISSION AND RADIATED EMISSION TEST SUMMARY

### 4.1 Conducted Emission

#### 4.1.1 Measuring instruments

| Type  | Manufacturer    | Model Name      | Serial Number | Calibration Cycle | Calibration Date |
|---|-----------------|-----------------|---------------|-------------------|------------------|
| <input checked="" type="checkbox"/> EMI Test Receiver | Rohde & Schwarz | ESCI            | 100584        | 1 year            | 06.25.2018       |
| <input checked="" type="checkbox"/> LISN              | Rohde & Schwarz | ENV216          | 102245        | 1 year            | 12.12.2018       |
| <input checked="" type="checkbox"/> LISN              | Rohde & Schwarz | ENV216          | 100073        | 1 year            | 04.30.2019       |
| <input checked="" type="checkbox"/> Software          | Rohde & Schwarz | EMC32 VER8.54.0 | -             | -                 | -                |


#### 4.1.2 Operating Condition

The test results of conducted emission at mains ports provide the following information:

|                    |   |
|--------------------|---|
| Test Standard Used | FCC CFR 47 PART 15 Subpart B Class B<br>ANSI C63.4-2014 |
| Detector           | Quasi-Peak, CISPR-Average                               |
| Bandwidth          | 9 kHz (6 dB)  |
| Operating Mode     | Data Communication mode                                 |
| Kind of Test Site  | Shielded Room   |
| Temperature        | 22.9 °C   |
| Relative Humidity  | 43.2 %  |
| Test Date          | June 15, 2019   |

### 4.1.3 Measuring Data

Figure 1: Conducted Emission, AC Main Port, Line (L1)



## QuasiPeak Final Result, Line (L1)

| Frequency (MHz) | QuasiPeak (dBμV) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dBμV) |
|-----------------|------------------|-----------------|------|------------|-------------|--------------|
| 0.154000        | 42.4             | 9.000           | L1   | 9.6        | 23.4        | 65.8         |
| 0.158000        | 42.2             | 9.000           | L1   | 9.6        | 23.4        | 65.6         |
| 0.162000        | 42.6             | 9.000           | L1   | 9.6        | 22.7        | 65.4         |
| 0.170000        | 45.3             | 9.000           | L1   | 9.6        | 19.7        | 65.0         |
| 0.174000        | 45.4             | 9.000           | L1   | 9.6        | 19.4        | 64.8         |
| 0.180000        | 44.4             | 9.000           | L1   | 9.6        | 20.1        | 64.5         |
| 3.198000        | 29.9             | 9.000           | L1   | 9.8        | 26.1        | 56.0         |
| 3.300000        | 29.6             | 9.000           | L1   | 9.8        | 26.4        | 56.0         |
| 3.402000        | 28.5             | 9.000           | L1   | 9.8        | 27.5        | 56.0         |
| 3.444000        | 29.7             | 9.000           | L1   | 9.8        | 26.3        | 56.0         |
| 3.608000        | 27.2             | 9.000           | L1   | 9.8        | 28.8        | 56.0         |
| 3.976000        | 27.2             | 9.000           | L1   | 9.8        | 28.8        | 56.0         |
| 9.244000        | 32.8             | 9.000           | L1   | 9.9        | 27.2        | 60.0         |
| 9.352000        | 33.3             | 9.000           | L1   | 10.0       | 26.7        | 60.0         |
| 9.370000        | 33.3             | 9.000           | L1   | 10.0       | 26.7        | 60.0         |
| 9.568000        | 33.5             | 9.000           | L1   | 10.0       | 26.5        | 60.0         |
| 9.588000        | 33.3             | 9.000           | L1   | 10.0       | 26.7        | 60.0         |
| 9.732000        | 32.8             | 9.000           | L1   | 10.0       | 27.2        | 60.0         |

## Calculation Formula:

1. Conductor L1 = Hot, Conductor N = Neutral
2. Corr. = LISN Factor + Cable Loss
3. QuasiPeak or CAverage= Receiver Reading + Corr.
4. Margin = Limit – QuasiPeak or CAverage




CAverage Final Result, Line (L1)

| Frequency<br>(MHz) | CAverage<br>(dBμV) | Bandwidth<br>(kHz) | Line | Corr.<br>(dB) | Margin<br>(dB) | Limit<br>(dBμV) |
|--------------------|--------------------|--------------------|------|---------------|----------------|-----------------|
| 0.152000           | 25.6               | 9.000              | L1   | 9.6           | 30.3           | 55.9            |
| 0.158000           | 25.0               | 9.000              | L1   | 9.6           | 30.6           | 55.6            |
| 0.164000           | 27.5               | 9.000              | L1   | 9.6           | 27.7           | 55.3            |
| 0.172000           | 30.8               | 9.000              | L1   | 9.6           | 24.1           | 54.9            |
| 0.178000           | 31.1               | 9.000              | L1   | 9.6           | 23.5           | 54.6            |
| 0.182000           | 31.0               | 9.000              | L1   | 9.6           | 23.4           | 54.4            |
| 3.094000           | 22.3               | 9.000              | L1   | 9.8           | 23.7           | 46.0            |
| 3.198000           | 21.4               | 9.000              | L1   | 9.8           | 24.6           | 46.0            |
| 3.402000           | 20.0               | 9.000              | L1   | 9.8           | 26.0           | 46.0            |
| 3.608000           | 18.2               | 9.000              | L1   | 9.8           | 27.8           | 46.0            |
| 3.914000           | 17.3               | 9.000              | L1   | 9.8           | 28.7           | 46.0            |
| 3.976000           | 16.6               | 9.000              | L1   | 9.8           | 29.4           | 46.0            |
| 9.244000           | 25.2               | 9.000              | L1   | 9.9           | 24.8           | 50.0            |
| 9.352000           | 25.9               | 9.000              | L1   | 10.0          | 24.1           | 50.0            |
| 9.370000           | 26.0               | 9.000              | L1   | 10.0          | 24.0           | 50.0            |
| 9.450000           | 26.0               | 9.000              | L1   | 10.0          | 24.0           | 50.0            |
| 9.568000           | 26.1               | 9.000              | L1   | 10.0          | 23.9           | 50.0            |
| 9.732000           | 24.5               | 9.000              | L1   | 10.0          | 25.5           | 50.0            |

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

Figure 2: Conducted Emission, AC Main Port, Line (N)



## QuasiPeak Final Result, Line (N)

| Frequency<br>(MHz) | QuasiPeak<br>(dBμV) | Bandwidth<br>(kHz) | Line | Corr.<br>(dB) | Margin<br>(dB) | Limit<br>(dBμV) |
|--------------------|---------------------|--------------------|------|---------------|----------------|-----------------|
| 0.150000           | 42.9                | 9.000              | N    | 9.6           | 23.1           | 66.0            |
| 0.156000           | 42.5                | 9.000              | N    | 9.6           | 23.2           | 65.7            |
| 0.162000           | 41.8                | 9.000              | N    | 9.6           | 23.6           | 65.4            |
| 0.172000           | 46.5                | 9.000              | N    | 9.6           | 18.4           | 64.9            |
| 0.178000           | 46.0                | 9.000              | N    | 9.6           | 18.5           | 64.6            |
| 0.194000           | 43.8                | 9.000              | N    | 9.6           | 20.0           | 63.9            |
| 3.446000           | 25.4                | 9.000              | N    | 9.8           | 30.6           | 56.0            |
| 3.858000           | 26.3                | 9.000              | N    | 9.8           | 29.7           | 56.0            |
| 3.942000           | 30.6                | 9.000              | N    | 9.8           | 25.4           | 56.0            |
| 3.962000           | 27.9                | 9.000              | N    | 9.8           | 28.1           | 56.0            |
| 4.064000           | 27.7                | 9.000              | N    | 9.8           | 28.3           | 56.0            |
| 4.476000           | 28.3                | 9.000              | N    | 9.8           | 27.7           | 56.0            |
| 9.524000           | 32.3                | 9.000              | N    | 9.9           | 27.7           | 60.0            |
| 9.546000           | 32.2                | 9.000              | N    | 9.9           | 27.8           | 60.0            |
| 9.614000           | 32.4                | 9.000              | N    | 9.9           | 27.6           | 60.0            |
| 9.618000           | 32.0                | 9.000              | N    | 9.9           | 28.0           | 60.0            |
| 9.622000           | 32.2                | 9.000              | N    | 9.9           | 27.8           | 60.0            |
| 9.730000           | 32.5                | 9.000              | N    | 9.9           | 27.5           | 60.0            |

CAverage Final Result, Line (N)

| Frequency<br>(MHz) | CAverage<br>(dBμV) | Bandwidth<br>(kHz) | Line | Corr.<br>(dB) | Margin<br>(dB) | Limit<br>(dBμV) |
|--------------------|--------------------|--------------------|------|---------------|----------------|-----------------|
| 0.150000           | 25.8               | 9.000              | N    | 9.6           | 30.2           | 56.0            |
| 0.156000           | 25.4               | 9.000              | N    | 9.6           | 30.3           | 55.7            |
| 0.184000           | 30.6               | 9.000              | N    | 9.6           | 23.7           | 54.3            |
| 0.192000           | 29.7               | 9.000              | N    | 9.6           | 24.3           | 53.9            |
| 0.200000           | 25.7               | 9.000              | N    | 9.6           | 27.9           | 53.6            |
| 0.208000           | 23.4               | 9.000              | N    | 9.6           | 29.9           | 53.3            |
| 3.446000           | 15.5               | 9.000              | N    | 9.8           | 30.5           | 46.0            |
| 3.858000           | 16.6               | 9.000              | N    | 9.8           | 29.4           | 46.0            |
| 3.944000           | 17.7               | 9.000              | N    | 9.8           | 28.3           | 46.0            |
| 3.962000           | 17.8               | 9.000              | N    | 9.8           | 28.2           | 46.0            |
| 4.064000           | 19.3               | 9.000              | N    | 9.8           | 26.7           | 46.0            |
| 4.474000           | 19.6               | 9.000              | N    | 9.8           | 26.4           | 46.0            |
| 9.376000           | 23.5               | 9.000              | N    | 9.9           | 26.5           | 50.0            |
| 9.452000           | 24.2               | 9.000              | N    | 9.9           | 25.8           | 50.0            |
| 9.524000           | 24.4               | 9.000              | N    | 9.9           | 25.6           | 50.0            |
| 9.614000           | 24.4               | 9.000              | N    | 9.9           | 25.6           | 50.0            |
| 9.622000           | 24.6               | 9.000              | N    | 9.9           | 25.4           | 50.0            |
| 9.730000           | 24.4               | 9.000              | N    | 9.9           | 25.6           | 50.0            |

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

## 4.2 Radiated Emission Below 1 GHz

### 4.2.1 Measuring instruments

|                                     | Type                      | Manufacturer    | Model Name      | Serial Number             | Calibration Cycle | Calibration Date |
|-------------------------------------|---------------------------|-----------------|-----------------|---------------------------|-------------------|------------------|
| <input checked="" type="checkbox"/> | EMI test receiver         | Rohde & Schwarz | ESU40           | 100524                    | 1 year            | 05.17.2019       |
| <input checked="" type="checkbox"/> | Trilog antenna            | Schwarzbeck     | VULB 9168       | 255                       | 2 year            | 03.26.2019       |
| <input checked="" type="checkbox"/> | Antenna master            | INNCO Systems   | MA4640-XP-ET    | -                         | N/A               | -                |
| <input checked="" type="checkbox"/> | Antenna master controller | INNCO Systems   | CO3000          | CO3000/870/<br>35990515/L | N/A               | -                |
| <input checked="" type="checkbox"/> | Turn Table                | INNCO Systems   | 1060            | -                         | N/A               | -                |
| <input checked="" type="checkbox"/> | Turn table controller     | INNCO Systems   | CO2000          | CO2000/095/<br>7590304/L  | N/A               | -                |
| <input checked="" type="checkbox"/> | Software                  | Rohde & Schwarz | EMC32 VER8.40.0 | -                         | -                 | -                |

### 4.2.2 Operating Condition

The test results of radiated emission provide the following information:

|                           |   |
|---------------------------|---|
| <b>Used Test Standard</b> | FCC CFR 47 PART 15 Subpart B Class B<br>ANSI C63.4-2014 |
| <b>Detector</b>           | Quasi-Peak  |
| <b>Bandwidth</b>          | 120 kHz (6 dB)  |
| <b>Operating Mode</b>     | Data Communication mode                                 |
| <b>Kind of Test Site</b>  | 3 m semi anechoic chamber                               |
| <b>Temperature</b>        | 21.4 °C   |
| <b>Relative Humidity</b>  | 43.3 %  |
| <b>Test Date</b>          | June 15, 2019   |

### 4.2.3 Measuring Data

| Frequency<br>(MHz) | Quasi Peak<br>(dBμV/m) | Antenna<br>Height<br>(cm) | POL.<br>(H/V) | Azimuth<br>(deg) | Corr.<br>(dB) | Margin<br>(dB) | Limit<br>(dBμV/m) |
|--------------------|------------------------|---------------------------|---------------|------------------|---------------|----------------|-------------------|
| 64.752000          | 28.1                   | 100.0                     | V             | 278.0            | 18.8          | 11.9           | 40.0              |
| 265.604800         | 34.8                   | 125.2                     | H             | 131.0            | 19.3          | 11.2           | 46.0              |
| 374.999200         | 37.7                   | 100.0                     | H             | 66.0             | 22.3          | 8.3            | 46.0              |
| 600.047200         | 39.4                   | 205.8                     | V             | 222.0            | 27.4          | 6.6            | 46.0              |
| 800.032800         | 38.5                   | 174.9                     | V             | 130.0            | 30.4          | 7.5            | 46.0              |
| 999.768000         | 46.3                   | 100.0                     | H             | 264.0            | 32.3          | 7.7            | 54.0              |

#### - Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. QuasiPeak = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor + Cable Loss
4. Margin = Limit - QuasiPeak

### 4.3 Radiated Emission Above 1 GHz

#### 4.3.1 Measuring instruments

|                                     | Type                      | Manufacturer    | Model Name      | Serial Number             | Calibration Cycle | Calibration Date |
|-------------------------------------|---------------------------|-----------------|-----------------|---------------------------|-------------------|------------------|
| <input checked="" type="checkbox"/> | EMI test receiver         | Rohde & Schwarz | ESU40           | 100524                    | 1 year            | 05.17.2019       |
| <input checked="" type="checkbox"/> | Antenna master            | INNCO Systems   | MA4640-XP-ET    | -                         | N/A               | -                |
| <input checked="" type="checkbox"/> | Antenna master controller | INNCO Systems   | CO3000          | CO3000/870/<br>35990515/L | N/A               | -                |
| <input checked="" type="checkbox"/> | Turn table                | INNCO Systems   | 1060            | -                         | N/A               | -                |
| <input checked="" type="checkbox"/> | Turn table controller     | INNCO Systems   | CO2000          | CO2000/095/<br>7590304/L  | N/A               | -                |
| <input checked="" type="checkbox"/> | Horn antenna              | Schwarzbeck     | BBHA 9120D      | 01836                     | 2 year            | 07.20.2018       |
| <input checked="" type="checkbox"/> | Low Noise amplifier       | TESTEK          | TK-PA18H        | 170034-L                  | 1 year            | 03.04.2019       |
| <input checked="" type="checkbox"/> | Power Amplifier           | TK-PA1840H      | TESTEK          | 170030-L                  | 1 year            | 12.17.2018       |
| <input checked="" type="checkbox"/> | Horn Antenna              | BBHA 9170       | Schwarzbeck     | BBHA 9170<br>#786         | 2 year            | 12.05.2017       |
| <input checked="" type="checkbox"/> | Software                  | Rohde & Schwarz | EMC32 VER8.40.0 | -                         | -                 | -                |

#### 4.3.2 Operating Condition

The test results of radiated emission provide the following information:

|                               |   |
|-------------------------------|---|
| <b>Used Test Standard</b>     | FCC CFR 47 PART 15 Subpart B Class B<br>ANSI C63.4-2014                                       |
| <b>Detector</b>               | Peak mode: Peak (RBW: 1 MHz, VBW: 3 MHz)<br>CISPR-Average mode: Peak (RBW: 1 MHz, VBW: 10 Hz) |
| <b>Highest Frequency</b>      | 5 825 MHz   |
| <b>Tested Frequency Range</b> | 1 GHz to 30 GHz   |
| <b>Operation Mode</b>         | Data Communication mode   |
| <b>Kind of Test Site</b>      | 3 m semi anechoic chamber   |
| <b>Temperature</b>            | 21.4 °C   |
| <b>Relative Humidity</b>      | 43.3 %  |
| <b>Test Date</b>              | June 15, 2019   |



### 4.3.3 Measuring Data

| Frequency (MHz) | Peak (dBμV/m) | Antenna Height (cm) | POL. (H/V) | Azimuth (deg) | Corr. (dB) | Margin (dB) | Limit (dBμV/m) |
|-----------------|---------------|---------------------|------------|---------------|------------|-------------|----------------|
| 1000.690000     | 36.6          | 201.6               | H          | 226.0         | -27.8      | 37.4        | 74.0           |
| 1399.920000     | 55.3          | 321.7               | V          | 212.0         | -26.0      | 18.7        | 74.0           |
| 1996.310000     | 52.4          | 100.0               | V          | 53.0          | -25.2      | 21.6        | 74.0           |
| 2656.930000     | 49.0          | 100.0               | V          | 4.0           | -22.7      | 25.0        | 74.0           |
| 5979.065000     | 46.8          | 307.6               | V          | 111.0         | -14.7      | 27.2        | 74.0           |
| 14989.040000    | 49.6          | 100.0               | V          | 66.0          | 1.4        | 24.4        | 74.0           |

| Frequency (MHz) | CAverage (dBμV/m) | Antenna Height (cm) | POL. (H/V) | Azimuth (deg) | Corr. (dB) | Margin (dB) | Limit (dBμV/m) |
|-----------------|-------------------|---------------------|------------|---------------|------------|-------------|----------------|
| 1000.690000     | 31.4              | 201.6               | H          | 226.0         | -27.8      | 22.6        | 54.0           |
| 1399.920000     | 50.7              | 321.7               | V          | 212.0         | -26.0      | 3.3         | 54.0           |
| 1996.310000     | 27.5              | 100.0               | V          | 53.0          | -25.2      | 26.5        | 54.0           |
| 2656.930000     | 23.1              | 100.0               | V          | 4.0           | -22.7      | 30.9        | 54.0           |
| 5979.065000     | 29.8              | 307.6               | V          | 111.0         | -14.7      | 24.2        | 54.0           |
| 14989.040000    | 36.6              | 100.0               | V          | 66.0          | 1.4        | 17.4        | 54.0           |

#### - Calculation Formula:

1. POL. H = Horizontal, POL. V = Vertical
2. Peak or CAverage = Reading (Receiver Reading) + Corr.
3. Corr. (Correction Factor) = Antenna Factor+ Cable Loss –Amplifier Gain
4. Margin = Limit - Peak or CAverage

## 5. CONCLUSION

The data collected shows that the EUT Type: Multi-band GSM/CDMA/WCDMA/LTE Phone with WLAN, Bluetooth and NFC, Model: LM-Q720VSP complies with §15.107 and §15.109 of the FCC rules.

## 6. APPENDIX A. TEST SETUP PHOTO

Please refer to Appendix. A and test setup photo file no. as follows;

| File No.            | Date of Issue | Description     |
|---------------------|---------------|-----------------|
| HCT-EM-1906-FC011-P | June 17, 2019 | Initial Release |

End of report