

Technical drawing of a lens with dimensions and specifications:


- Top Dimension:** $\phi 42.5 \pm 0.5$
- Left Dimension:** $\phi 18.2 \pm 0.5$
- Model:** TAA6606
- Input:** 5V = 200mA
- HC:** 24589-TAA6606
- Ref no.:** TAA6606WT/00
- CMIIIT ID:** XXXXXXXXXX
- FCC ID:** 2AR2STAA6606
- Manufacturer:** MMD Hong Kong Holding Limited.
- Unit:** 1006, 10th Floor, C-Boss International Center, 108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
- 型号:** TAA6606
- 输入:** 5V = 200mA
- Manufacturer:** 冠捷视科技(深圳)有限公司
- Location:** Made in China





Energy Verified

S/N: LCPXYWWXXXXXX
R




标签粘贴位置

LCPXYWWXXXXXX

定量, 供应商代码, 固定用“LC”表示.

5) 测试要求: 高温测试: 将待测物放入温度为 65°C 的焗炉内, 4小时、12小时、48小时后各取出观察一次, 被测物不能出现翘起及气泡现象.

			产品型号			TAA6606XX/00					
			零件名称			铭牌标签					
			零件编号								
变 更	原 因	签名/日期	图纸编号								
标 记	签 名 / 日期		版本	比例	单位						
制 图	陈丽莹 2021/5/26		V1	/	MM	A	± 0.05	± 0.1	± 0.2	± 0.3	± 0.4
工 艺						B	± 0.1	± 0.2	± 0.3	± 0.4	± 0.5
审 核						C	± 0.2	± 0.5	± 0.7	± 1.2	± 2.0
批 准						等级	<5	5~15	15~60	60~250	>250