



FCC RF Test Report

APPLICANT : Askey Computer Corporation
EQUIPMENT : Android Player Card
BRAND NAME : ASUS
MODEL NAME : CA001
FCC ID : H8N-WHD0200
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DSS) Spread Spectrum Transmitter

The product was received on May 05, 2016 and testing was completed on Jun. 21, 2016. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Prepared by: James Huang / Manager

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China



TABLE OF CONTENTS

1	GENERAL DESCRIPTION	5
1.1	Applicant	5
1.2	Manufacturer	5
1.3	Product Feature of Equipment Under Test	5
1.4	Product Specification of Equipment Under Test	6
1.5	Modification of EUT	6
1.6	Testing Location	7
1.7	Applicable Standards	7
2	TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1	Descriptions of Test Mode	8
2.2	Test Mode	9
2.3	Connection Diagram of Test System	10
2.4	Support Unit used in test configuration and system	11
2.5	EUT Operation Test Setup	11
2.6	Measurement Results Explanation Example	12
3	TEST RESULT	13
3.1	Number of Channel Measurement	13
3.2	Hopping Channel Separation Measurement	15
3.3	Dwell Time Measurement	22
3.4	20dB and 99% Bandwidth Measurement	25
3.5	Peak Output Power Measurement	38
3.6	Conducted Band Edges Measurement	40
3.7	Conducted Spurious Emission Measurement	47
3.8	Radiated Band Edges and Spurious Emission Measurement	57
3.9	AC Conducted Emission Measurement	63
3.10	Antenna Requirements	67
4	LIST OF MEASURING EQUIPMENT	68
5	UNCERTAINTY OF EVALUATION	69
APPENDIX A. RADIATED TEST RESULTS		
APPENDIX B. SETUP PHOTOGRAPHS		



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR650502A	Rev. 01	Initial issue of report	Jul. 28, 2016

SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	RSS-247 5.1(4)	Number of Channels	$\geq 15\text{Chs}$	Pass	-
3.2	15.247(a)(1)	RSS-247 5.1(2)	Hopping Channel Separation	$\geq 2/3$ of 20dB BW	Pass	-
3.3	15.247(a)(1)	RSS-247 5.1(4)	Dwell Time of Each Channel	$\leq 0.4\text{sec}$ in 31.6sec period	Pass	-
3.4	15.247(a)(1)	RSS-247 5.1(1)	20dB Bandwidth	NA	Pass	-
3.4	-	RSS-Gen 6.6	99% Bandwidth	-	Pass	-
3.5	15.247(b)(1)	RSS-247 5.4(2)	Peak Output Power	$\leq 125\text{ mW}$	Pass	-
3.6	15.247(d)	RSS-247 5.5	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
3.7	15.247(d)	RSS-247 5.5	Conducted Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.8	15.247(d)	RSS-247 5.5	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 4.05 dB at 46.490 MHz
3.9	15.207	RSS-Gen 8.8	AC Conducted Emission	15.207(a)	Pass	Under limit 16.99 dB at 0.170 MHz
3.10	15.203 & 15.247(b)	N/A	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

Askey Computer Corporation

10F, NO.119, JIANKANG RD., ZHONGHE DIST., NEW TAIPEI CITY, TAIWAN, R.O.C.

1.2 Manufacturer

Askey Computer Corporation

10F, NO.119, JIANKANG RD., ZHONGHE DIST., NEW TAIPEI CITY, TAIWAN, R.O.C.

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Android Player Card
Brand Name	ASUS
Model Name	CA001
FCC ID	H8N-WHD0200
EUT supports Radios application	WLAN2.4GHz 802.11b/g/n HT20/HT40 Bluetooth v2.1+EDR Bluetooth v3.0+EDR Bluetooth v4.0 LE
HW Version	REV:4
SW Version	3188-BSP-AS-1-6-B-2016-06-17-1
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Maximum Output Power to Antenna	Bluetooth BR(1Mbps) : 4.04 dBm (0.0025 W) Bluetooth EDR (2Mbps) : 5.01 dBm (0.0032 W) Bluetooth EDR (3Mbps) : 5.64 dBm (0.0037 W)
99% Occupied Bandwidth	Bluetooth BR(1Mbps) : 0.868MHz Bluetooth EDR (2Mbps) : 1.160MHz Bluetooth EDR (3Mbps) : 1.144MHz
Antenna Type/Gain	Antenna A:External Antenna with gain 5.00 dBi Antenna B:External Antenna with gain 4.61 dBi
Type of Modulation	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth EDR (3Mbps) : 8-DPSK

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.			
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China			
	TEL: +86-0512-5790-0158			
	FAX: +86-0512-5790-0958			
Test Site No.	Sporton Site No.			FCC/IC Registration No.
	TH01-KS	CO01-KS	03CH03-KS	306251/4086E

Note: The test site complies with ANSI C63.4 2014 requirement.

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

Preliminary tests were performed in different data rates and recorded the RF output power in the following table:

Channel	Frequency	Bluetooth RF Output Power		
		Data Rate / Modulation		
		GFSK	$\pi/4$ -DQPSK	8-DPSK
		1Mbps	2Mbps	3Mbps
Ch00	2402MHz	4.04 dBm	5.01 dBm	5.64 dBm
Ch39	2441MHz	3.41 dBm	4.35 dBm	4.89 dBm
Ch78	2480MHz	3.39 dBm	4.28 dBm	4.79 dBm

Remark:

1. All the test data for each data rate were verified, but only the worst case was reported.
 2. The data rate was set in 3Mbps for all the test items due to the highest RF output power.
- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests, X, Y, Z in three orthogonal panels, and different data rates were conducted to determine the final configuration (X plane as worst plane) from all possible combinations, and the worst mode of radiated spurious emissions is Bluetooth 3Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.


2.2 Test Mode

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps π /4-DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted Test Cases	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz
	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz
Radiated Test Cases	Bluetooth EDR 3Mbps 8-DPSK		
	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz		
AC Conducted Emission	Mode 1 :Bluetooth Link + WLAN Link + LAN load (RJ-45) + SD Card Play Color Bar + Adapter with Test Jig + USB 1 With U disk + USB 2 With U disk + Earphone + VGA With Monitor		
Remark:			
1. For radiated test cases, the worst mode data rate 3Mbps was reported only, because this data rate has the highest RF output power at preliminary tests and no other significantly frequencies found in conducted spurious emission.			
2. For Radiated TCs, The tests were performance with test Jig with Adapter, Earphone and Antenna A.			
3. EUT with Antenna B only verified the worst mode of EUT with Antenna A.			

2.3 Connection Diagram of Test System

<Bluetooth Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Base Station	R&S	CBT	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-Link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8m
3.	Notebook	Lenovo	G480	FCC Doc	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
4.	Earphone	Lenovo	SH100	N/A	N/A	N/A
5.	LCD monitor	Dell	IN1930MWc	FCC DoC	Shielded, 1.2m	Unshielded, 1.8m
6.	(USB)Mouse	Dell	MS111-P	FCC DoC	Shielded, 1.8m	N/A
7.	Bluetooth Earphone	Nokia	BH-106	QTLBH-106	N/A	Unshielded, 0.53m
8.	Bluetooth Earphone	Nokia	BH-102	PYAHS-107W	N/A	N/A
9.	Test Jig	ASKEY	WHD0200-D6 1/B	N/A	N/A	N/A
10.	VGA Cable	N/A	N/A	N/A	N/A	N/A
11.	RJ-45 Cable	N/A	N/A	N/A	N/A	N/A
12.	Adapter	Ktec	KSAS0121200 100VU	N/A	N/A	Unshielded, 1.6 m
13.	U Disk 4GB	SanDisk	SDCZ50-004G	N/A	N/A	N/A
14.	U Disk 16GB	Kingston	DTSE9 G2	N/A	N/A	N/A
15.	SD Card	Kingston	4GB	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For Bluetooth function, the engineering test program was provided and enabled to make EUT connect with Bluetooth base station to continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 4.5 dB.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)}. \\ &= 4.5 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation;
RBW = 300kHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

3.1.4 Test Setup




3.1.5 Test Result of Number of Hopping Frequency


Test Mode :	3Mbps	Temperature :	24~25°C
Test Engineer :	Ivan Zhang	Relative Humidity :	54~55%
Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass



Number of Hopping Channel Plot on Channel 00 - 78



Date: 14.JUN.2016 05:14:38



Date: 14.JUN.2016 05:20:20

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels;
RBW = 300kHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.2.4 Test Setup




3.2.5 Test Result of Hopping Channel Separation

Test Mode :	1Mbps	Temperature :	24~25°C
Test Engineer :	Ivan Zhang	Relative Humidity :	54~55%


Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.008	0.6027	Pass
39	2441	1.008	0.5973	Pass
78	2480	1.008	0.6427	Pass

Channel Separation Plot on Channel 00 - 01




Date: 14.JUN.2016 04:42:13

Channel Separation Plot on Channel 39 - 40



Date: 14.JUN.2016 04:43:09

Channel Separation Plot on Channel 77 - 78




Date: 14.JUN.2016 04:45:01




Test Mode :	2Mbps	Temperature :	24~25°C
Test Engineer :	Ivan Zhang	Relative Humidity :	54~55%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.8480	Pass
39	2441	1.002	0.8200	Pass
78	2480	1.002	0.8200	Pass

Channel Separation Plot on Channel 00 - 01


Date: 14.JUN.2016 04:51:04

Channel Separation Plot on Channel 39 - 40



Date: 14.JUN.2016 04:51:45

Channel Separation Plot on Channel 77 - 78




Date: 14.JUN.2016 04:52:29



Test Mode :	3Mbps	Temperature :	24~25°C
Test Engineer :	Ivan Zhang	Relative Humidity :	54~55%


Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.008	0.8280	Pass
39	2441	1.002	0.8240	Pass
78	2480	1.008	0.8240	Pass

Channel Separation Plot on Channel 00 - 01

Date: 14.JUN.2016 04:53:55




Channel Separation Plot on Channel 39 - 40



Date: 14.JUN.2016 04:54:37

Channel Separation Plot on Channel 77 - 78



Date: 14.JUN.2016 04:56:03

3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW $\geq$ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Dwell Time

Test Mode :	3DH5	Temperature :	24~25℃
Test Engineer :	Ivan Zhang	Relative Humidity :	54~55%


Mode	Hopping Channel Number	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Normal	79	106.67	2.9217	0.31	0.4	Pass
AFH	20	53.33	2.9217	0.16	0.4	Pass

Remark:

1. In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels.
With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s),
Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
2. In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels.
With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s),
Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time



Package Transfer Time Plot



Date: 14 JUN 2016 03:02:53

3.4 20dB and 99% Bandwidth Measurement

3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;
RBW $\geq$ 1% of the 20 dB bandwidth; VBW $\geq$ RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;
RBW $\geq$ 1% of the 99% bandwidth; VBW $\geq$ RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
6. Measure and record the results in the test report.

3.4.4 Test Setup






3.4.5 Test Result of 20dB Bandwidth

Test Mode :	1Mbps	Temperature :	24~25°C
Test Engineer :	Ivan Zhang	Relative Humidity :	54~55%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	0.904
39	2441	0.896
78	2480	0.964


20 dB Bandwidth Plot on Channel 00



Date: 14.JUN.2016 04:56:18




20 dB Bandwidth Plot on Channel 39



Date: 14.JUN.2016 04:56:32

20 dB Bandwidth Plot on Channel 78




Date: 14.JUN.2016 04:57:00



Test Mode :	2Mbps	Temperature :	24~25°C
Test Engineer :	Ivan Zhang	Relative Humidity :	54~55%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.272
39	2441	1.230
78	2480	1.230

20 dB Bandwidth Plot on Channel 00

Date: 14.JUN.2016 04:57:15




20 dB Bandwidth Plot on Channel 39



Date: 14.JUN.2016 04:57:25

20 dB Bandwidth Plot on Channel 78




Date: 14.JUN.2016 04:57:51



Test Mode :	3Mbps	Temperature :	24~25°C
Test Engineer :	Ivan Zhang	Relative Humidity :	54~55%


Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.242
39	2441	1.236
78	2480	1.236

20 dB Bandwidth Plot on Channel 00

Date: 14.JUN.2016 04:58:05




20 dB Bandwidth Plot on Channel 39



Date: 14.JUN.2016 04:58:16

20 dB Bandwidth Plot on Channel 78




Date: 14.JUN.2016 04:58:43

3.4.6 Test Result of 99% Occupied Bandwidth

Test Mode :	1Mbps	Temperature :	24~25°C
Test Engineer :	Ivan Zhang	Relative Humidity :	54~55%


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	0.864
39	2441	0.864
78	2480	0.868

99% Occupied Bandwidth Plot on Channel 00




Date: 14.JUN.2016 05:04:33

99% Occupied Bandwidth Plot on Channel 39



Date: 14.JUN.2016 05:05:09

99% Occupied Bandwidth Plot on Channel 78




Date: 14.JUN.2016 05:30:17



Test Mode :	2Mbps	Temperature :	24~25°C
Test Engineer :	Ivan Zhang	Relative Humidity :	54~55%


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	1.156
39	2441	1.160
78	2480	1.160

99% Occupied Bandwidth Plot on Channel 00

Date: 14.JUN.2016 05:06:22




99% Occupied Bandwidth Plot on Channel 39



Date: 14.JUN.2016 05:06:58

99% Occupied Bandwidth Plot on Channel 78




Date: 14.JUN.2016 05:37:12



Test Mode :	3Mbps	Temperature :	24~25°C
Test Engineer :	Ivan Zhang	Relative Humidity :	54~55%


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	1.144
39	2441	1.136
78	2480	1.140

99% Occupied Bandwidth Plot on Channel 00

Date: 14.JUN.2016 05:33:20




99% Occupied Bandwidth Plot on Channel 39



Date: 14.JUN.2016 05:08:48

99% Occupied Bandwidth Plot on Channel 78



Date: 14.JUN.2016 05:34:21

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.5 Peak Output Power Measurement

3.5.1 Limit of Peak Output Power

Section 15.247 (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

3.5.4 Test Setup



3.5.5 Test Result of Peak Output Power

Test Mode :	1Mbps	Temperature :	24~25°C
Test Engineer :	Ivan Zhang	Relative Humidity :	54~55%

Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	4.04	20.97	Pass
39	2441	3.41	20.97	Pass
78	2480	3.39	20.97	Pass

Test Mode :	2Mbps	Temperature :	24~25°C
Test Engineer :	Ivan Zhang	Relative Humidity :	54~55%

Channel	Frequency (MHz)	RF Power (dBm)		
		$\pi/4$ -DQPSK	Max. Limits (dBm)	Pass/Fail
		2 Mbps		
00	2402	5.01	20.97	Pass
39	2441	4.35	20.97	Pass
78	2480	4.28	20.97	Pass

Test Mode :	3Mbps	Temperature :	24~25°C
Test Engineer :	Ivan Zhang	Relative Humidity :	54~55%

Channel	Frequency (MHz)	RF Power (dBm)		
		8-DPSK	Max. Limits (dBm)	Pass/Fail
		3 Mbps		
00	2402	5.64	20.97	Pass
39	2441	4.89	20.97	Pass
78	2480	4.79	20.97	Pass

3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.


3.6.4 Test Setup



3.6.5 Test Result of Conducted Band Edges


Test Mode :	1Mbps	Temperature :	24~25°C
Test Channel :	00 and 78	Relative Humidity :	54~55%
		Test Engineer :	Ivan Zhang

Low Band Edge Plot on Channel 00



Date: 14.JUN.2016 05:28:07


High Band Edge Plot on Channel 78



Date: 14.JUN.2016 05:00:28


Test Mode :	2Mbps	Temperature :	24~25℃
Test Channel :	00 and 78	Relative Humidity :	54~55%
		Test Engineer :	Ivan Zhang

Low Band Edge Plot on Channel 00



Date: 14.JUN.2016 05:01:20


High Band Edge Plot on Channel 78




Date: 14.JUN.2016 05:02:12



Test Mode :	3Mbps	Temperature :	24~25°C
Test Channel :	00 and 78	Relative Humidity :	54~55%
		Test Engineer :	Ivan Zhang

Low Band Edge Plot on Channel 00

Date: 14.JUN.2016 05:03:04


High Band Edge Plot on Channel 78

Date: 14.JUN.2016 05:03:55

3.6.6 Test Result of Conducted Hopping Mode Band Edges


Test Mode :	1Mbps	Temperature :	24~25℃
Test Engineer :	Ivan Zhang	Relative Humidity :	54~55%

1Mbps Hopping Mode Low Band Edge Plot



Date: 14.JUN.2016 05:39:30


1Mbps Hopping Mode High Band Edge Plot




Date: 14.JUN.2016 05:41:11



Test Mode :	2Mbps	Temperature :	24~25°C
Test Engineer :	Ivan Zhang	Relative Humidity :	54~55%

2Mbps Hopping Mode Low Band Edge Plot

Date: 14.JUN.2016 05:44:53


2Mbps Hopping Mode High Band Edge Plot

Date: 14.JUN.2016 05:43:01




Test Mode :	3Mbps	Temperature :	24~25°C
Test Engineer :	Ivan Zhang	Relative Humidity :	54~55%

3Mbps Hopping Mode Low Band Edge Plot



Date: 14.JUN.2016 05:51:06

3Mbps Hopping Mode High Band Edge Plot



Date: 14.JUN.2016 05:48:04

3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


3.7.4 Test Setup



3.7.5 Test Result of Conducted Spurious Emission


Test Mode :	1Mbps	Temperature :	24~25°C
Test Channel :	00	Relative Humidity :	54~55%
		Test Engineer :	Ivan Zhang

1Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 14.JUN.2016 05:52:30


1Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 14.JUN.2016 05:52:52


Test Mode :	1Mbps	Temperature :	24~25℃
Test Channel :	39	Relative Humidity :	54~55%
		Test Engineer :	Ivan Zhang

1Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 14.JUN.2016 05:53:30


1Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 14.JUN.2016 05:53:52


Test Mode :	1Mbps	Temperature :	24~25℃
Test Channel :	78	Relative Humidity :	54~55%
		Test Engineer :	Ivan Zhang

1Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 14.JUN.2016 05:54:30


1Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz




Date: 14.JUN.2016 05:54:52



Test Mode :	2Mbps	Temperature :	24~25°C
Test Channel :	00	Relative Humidity :	54~55%
		Test Engineer :	Ivan Zhang

2Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz


Date: 14.JUN.2016 05:57:50

2Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz

Date: 14.JUN.2016 05:59:02


Test Mode :	2Mbps	Temperature :	24~25℃
Test Channel :	39	Relative Humidity :	54~55%
		Test Engineer :	Ivan Zhang

2Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 14.JUN.2016 06:00:32


2Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz




Date: 14.JUN.2016 06:00:54



Test Mode :	2Mbps	Temperature :	24~25°C
Test Channel :	78	Relative Humidity :	54~55%
		Test Engineer :	Ivan Zhang

2Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz


Date: 14.JUN.2016 06:01:32

2Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz


Date: 14.JUN.2016 06:01:54



Test Mode :	3Mbps	Temperature :	24~25°C
Test Channel :	00	Relative Humidity :	54~55%
		Test Engineer :	Ivan Zhang

3Mbps CSE Plot on Ch 00 between 30MHz ~ 3 GHz


Date: 14.JUN.2016 06:03:29

3Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz


Date: 14.JUN.2016 06:03:50



Test Mode :	3Mbps	Temperature :	24~25°C
Test Channel :	39	Relative Humidity :	54~55%
		Test Engineer :	Ivan Zhang

3Mbps CSE Plot on Ch 39 between 30MHz ~ 3 GHz


Date: 14.JUN.2016 06:04:24

3Mbps CSE Plot on Ch 39 between 2 GHz ~ 25 GHz


Date: 14.JUN.2016 06:04:46



Test Mode :	3Mbps	Temperature :	24~25°C
Test Channel :	78	Relative Humidity :	54~55%
		Test Engineer :	Ivan Zhang

3Mbps CSE Plot on Ch 78 between 30MHz ~ 3 GHz

Date: 14.JUN.2016 06:08:52

3Mbps CSE Plot on Ch 78 between 2 GHz ~ 25 GHz

Date: 14.JUN.2016 06:09:14

3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.8.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz, RBW=1MHz for $f > 1$ GHz ; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement: use duty cycle correction factor method per 15.35(c).
Duty cycle = On time/100 milliseconds
On time = $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$
Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.
Average Emission Level = Peak Emission Level + $20 * \log(\text{Duty cycle})$
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.79dB) derived from $20 \log(\text{dwell time}/100\text{ms})$. This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz




3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)


The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.8.6 Duty cycle correction factor for average measurement

3DH5 on time (One Pulse) Plot on Channel 39



3DH5 on time (Count Pulses) Plot on Channel 39



Note:

1. Worst case Duty cycle = on time/100 milliseconds = $2 * 2.88 / 100 = 5.76 \%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.79 \text{ dB}$
3. 3DH5 has the highest duty cycle worst case and is reported.

Duty Cycle Correction Factor Consideration for AFH mode:

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.88 \text{ ms} \times 20 \text{ channels} = 57.6 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period. $[100\text{ms} / 57.6\text{ms}] = 2 \text{ hops}$

Thus, the maximum possible ON time:

$$2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.76 \text{ ms}/100\text{ms}) = -24.79 \text{ dB}$$

3.8.7 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix A.

3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix A.

3.9 AC Conducted Emission Measurement

3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.9.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.9.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.9.4 Test Setup



3.9.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	22~24℃
Test Engineer :	Amos Zhang	Relative Humidity :	44~46%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	Bluetooth Link + WLAN Link + LAN load (RJ-45) + SD Card Play Color Bar + Adapter with Test Jig + USB 1 With U disk + USB 2 With U disk + Earphone + VGA With Monitor		




Site : CO01-KS
Condition : FCC PART 15C LISN-L-20151024 LINE
mode : Mode 1
: SN:G2LSKW000015

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 *	0.17	48.13	-16.99	65.12	37.60	0.41	10.12	QP
2	0.17	28.43	-26.69	55.12	17.90	0.41	10.12	Average
3	0.19	44.90	-19.21	64.11	34.50	0.28	10.12	QP
4	0.19	26.30	-27.81	54.11	15.90	0.28	10.12	Average
5	0.23	39.16	-23.28	62.44	28.80	0.22	10.14	QP
6	0.23	21.96	-30.48	52.44	11.60	0.22	10.14	Average
7	0.26	37.57	-23.99	61.56	27.21	0.22	10.14	QP
8	0.26	21.67	-29.89	51.56	11.31	0.22	10.14	Average
9	0.32	32.68	-26.94	59.62	22.29	0.23	10.16	QP
10	0.32	18.68	-30.94	49.62	8.29	0.23	10.16	Average
11	0.45	33.30	-23.59	56.89	22.90	0.23	10.17	QP
12	0.45	28.00	-18.89	46.89	17.60	0.23	10.17	Average



Test Mode :	Mode 1	Temperature :	22~24℃
Test Engineer :	Amos Zhang	Relative Humidity :	44~46%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	Bluetooth Link + WLAN Link + LAN load (RJ-45) + SD Card Play Color Bar + Adapter with Test Jig + USB 1 With U disk + USB 2 With U disk + Earphone + VGA With Monitor		



Site : CO01-KS
Condition : FCC PART 15C LISN-N-20151024 NEUTRAL

mode : Mode 1
: SN:G2LSKW000015

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 *	0.16	47.61	-17.64	65.25	37.20	0.30	10.11	QP
2	0.16	27.01	-28.24	55.25	16.60	0.30	10.11	Average
3	0.23	39.95	-22.57	62.52	29.50	0.31	10.14	QP
4	0.23	21.75	-30.77	52.52	11.30	0.31	10.14	Average
5	0.31	33.36	-26.52	59.88	22.90	0.31	10.15	QP
6	0.31	20.76	-29.12	49.88	10.30	0.31	10.15	Average
7	0.40	32.09	-25.72	57.81	21.60	0.32	10.17	QP
8	0.40	21.69	-26.12	47.81	11.20	0.32	10.17	Average
9	0.45	32.09	-24.80	56.89	21.60	0.32	10.17	QP
10	0.45	24.09	-22.80	46.89	13.60	0.32	10.17	Average
11	7.73	35.72	-24.28	60.00	25.20	0.29	10.23	QP
12	7.73	29.72	-20.28	50.00	19.20	0.29	10.23	Average



3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.10.2 Antenna Anti-Replacement Construction

External Antenna connector is used.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Oct. 24, 2015	Jun. 14, 2016	Oct. 23, 2016	Conducted (TH01-KS)
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Sep. 10, 2015	Jun. 14, 2016	Sep. 09, 2016	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 20, 2016	Jun. 14, 2016	Jan. 19, 2017	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 20, 2016	Jun. 14, 2016	Jan. 19, 2017	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Oct. 24, 2015	Jun. 21, 2016	Oct. 23, 2016	Radiation (03CH03-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz~44GHz	Apr. 22, 2016	Jun. 21, 2016	Apr. 21, 2017	Radiation (03CH03-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 07, 2015	Jun. 21, 2016	Nov. 06, 2016	Radiation (03CH03-KS)
Bilog Antenna	TeseQ	CBL6112D	35406	25MHz-2GHz	Apr. 16, 2016	Jun. 21, 2016	Apr. 15, 2017	Radiation (03CH03-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1356	1GHz~18GHz	Apr. 16, 2016	Jun. 21, 2016	Apr. 15, 2017	Radiation (03CH03-KS)
SHF-EHF Horn	com-power	AH-840	101070	18GHz~40GHz	Oct. 10, 2015	Jun. 21, 2016	Oct. 09, 2016	Radiation (03CH03-KS)
Amplifier	Burgeon	BPA-530	102212	0.01MHz-3000MHz	Aug. 10, 2015	Jun. 21, 2016	Aug. 09, 2016	Radiation (03CH03-KS)
Amplifier	MITEQ	TTA1840-35-HG	1887435	18~40GHz	Aug. 27, 2015	Jun. 21, 2016	Aug. 26, 2016	Radiation (03CH03-KS)
high gain Amplifier	MITEQ	AMF-7D-0010 1800-30-10P	1889560	1GHz-18GHz	Aug. 10, 2015	Jun. 21, 2016	Aug. 09, 2016	Radiation (03CH03-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Oct. 24, 2015	Jun. 21, 2016	Oct. 23, 2016	Radiation (03CH03-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Jun. 21, 2016	NCR	Radiation (03CH03-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Jun. 21, 2016	NCR	Radiation (03CH03-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 29, 2016	May 15, 2016	Apr. 28, 2017	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 24, 2015	May 15, 2016	Oct. 23, 2016	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 24, 2015	May 15, 2016	Oct. 23, 2016	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 24, 2015	May 15, 2016	Oct. 23, 2016	Conduction (CO01-KS)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.3dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.5dB
---	-------

Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.5dB
---	-------

Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.6dB
---	-------



Appendix A. Radiated Spurious Emission

Antenna A

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BT CH00 2402MHz		2344.84	51.42	-22.58	74	56.05	26.86	5.52	37.01	100	165	P	H
		2344.84	26.63	-27.37	54	-	-	-	-	-	-	A	H
	*	2402.04	87.24	-	-	91.67	27	5.59	37.02	100	165	P	H
	*	2402.04	62.45	-	-	-	-	-	-	-	-	A	H
		2389.56	58.23	-15.77	74	62.66	27	5.59	37.02	133	192	P	V
		2389.56	33.44	-20.56	54	-	-	-	-	-	-	A	V
	*	2402.04	101.5	-	-	105.93	27	5.59	37.02	133	192	P	V
	*	2402.04	76.71	-	-	-	-	-	-	-	-	A	V
BT CH 39 2441MHz	*	2441	90.78	-	-	94.71	27.39	5.65	36.97	116	161	P	H
	*	2441	65.99	-	-	-	-	-	-	-	-	A	H
	*	2441	103.3	-	-	107.23	27.39	5.65	36.97	133	192	P	V
	*	2441	78.51	-	-	-	-	-	-	-	-	A	V
BT CH 78 2480MHz	*	2480.05	90.34	-	-	93.95	27.64	5.69	36.94	100	159	P	H
	*	2480.05	65.55	-	-	-	-	-	-	-	-	A	H
		2483.50	52.32	-21.68	74	55.93	27.64	5.69	36.94	100	159	P	H
		2483.50	27.53	-26.47	54	-	-	-	-	-	-	A	H
	*	2479.98	102.27	-	-	105.88	27.64	5.69	36.94	133	192	P	V
	*	2479.98	77.48	-	-	-	-	-	-	-	-	A	V
		2483.62	61.41	-12.59	74	65.02	27.64	5.69	36.94	133	192	P	V
		2483.62	36.62	-17.38	54	-	-	-	-	-	-	A	V
Remark	1. No other spurious found.												
	2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BT CH 00 2402MHz		4806	35.87	-38.13	74	57.41	31.48	9.1	62.12	100	0	P	H
		4806	36.53	-37.47	74	58.07	31.48	9.1	62.12	100	360	P	V
BT CH 39 2441MHz		4884	37.63	-36.37	74	58.87	31.59	9.2	62.03	100	360	P	H
		7323	40.27	-33.73	74	54.04	34.08	11.3	59.15	100	360	P	H
		4882	38.64	-35.36	74	59.88	31.59	9.2	62.03	100	360	P	V
		7320	39.72	-34.28	74	53.49	34.08	11.3	59.15	100	360	P	V
BT CH 78 2480MHz		4962	37.39	-36.61	74	58.27	31.72	9.32	61.92	100	360	P	H
		7440	40.05	-33.95	74	53.61	34.44	11.3	59.3	100	360	P	H
		4960	37.4	-36.6	74	58.28	31.72	9.32	61.92	100	360	P	V
		7440	41.42	-32.58	74	54.98	34.44	11.3	59.3	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz BT (LF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BT LF	!	36.79	35.01	-4.99	40	50.36	16.42	0.73	32.5	-	-	P	H
		90.14	30.54	-12.96	43.5	49.83	11.9	1.15	32.34	-	-	P	H
	!	224	41.34	-4.66	46	60.05	11.9	1.73	32.34	100	249	P	H
	!	320.03	40.51	-5.49	46	55.32	15.26	2.2	32.27	-	-	P	H
		480.08	32.48	-13.52	46	44.03	17.94	2.74	32.23	-	-	P	H
		595.51	29.17	-16.83	46	40.57	17.33	3.06	31.79	-	-	P	H
	!	46.49	35.95	-4.05	40	56.06	11.63	0.84	32.58	100	273	P	V
		88.2	32.93	-10.57	43.5	52.9	11.22	1.14	32.33	-	-	P	V
		147.37	19.38	-24.12	43.5	36.59	13.76	1.47	32.44	-	-	P	V
		223.03	30.37	-15.63	46	49.13	11.85	1.73	32.34	-	-	P	V
		320.03	36.62	-9.38	46	51.43	15.26	2.2	32.27	-	-	P	V
		480.08	29.88	-16.12	46	41.43	17.94	2.74	32.23	-	-	P	V
Remark	1. No other spurious found.												
	2. All results are PASS against limit line.												



Antenna B

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BT CH 78 2480MHz	*	2479.98	87.6	-	-	91.21	27.64	5.69	36.94	100	326	P	H
	*	2479.98	62.81	-	-	-	-	-	-	-	-	A	H
		2486.49	51.25	-22.75	74	54.86	27.64	5.69	36.94	100	326	P	H
		2486.49	26.46	-27.54	54	-	-	-	-	-	-	A	H
	*	2479.98	102.83	-	-	106.44	27.64	5.69	36.94	115	190	P	V
	*	2479.98	78.04	-	-	-	-	-	-	-	-	A	V
		2483.5	61.46	-12.54	74	65.07	27.64	5.69	36.94	115	190	P	V
		2483.5	36.67	-17.33	54	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

**2.4GHz 2400~2483.5MHz****BT (Harmonic @ 3m)**

BT	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BT CH 78 2480MHz		4962	37.91	-36.09	74	58.79	31.72	9.32	61.92	100	360	P	H
		7440	40.04	-33.96	74	53.6	34.44	11.3	59.3	100	360	P	H
		4960	38.39	-35.61	74	59.27	31.72	9.32	61.92	100	221	P	V
		7440	41.76	-32.24	74	55.32	34.44	11.3	59.3	100	221	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

**Note symbol**

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is Less than 6 dB under limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.