




TEST REPORT

Report No.: CHTEW20120171 Report verification : 

Project No.: SHT2012072601EW

FCC ID: 2APQ9-L7-1

Applicant's name: Shenzhen JX ROBOT Technology Co., Ltd.

Address: Area B, Floor 9th, Building 1, Yulu Seventh Industrial Zone,
Gongming Street, Guangming, Shenzhen, Guangdong, China.

Test item description: Foldable 3 axis gimbal stabilizer

Trade Mark: -

Model/Type reference: L7B

Listed Model(s): L7C, L7D

Standard: 47 CFR FCC Part 15 Subpart B

Date of receipt of test sample: Dec.22, 2020

Date of testing: Dec.22, 2020- Dec.31, 2020

Date of issue: Jan.04, 2021

Result: Pass

Compiled by
(position+printed name+signature) . : File administrators Echo Wei

Supervised by
(position+printed name+signature) . : Project Engineer Kiki Kong

Approved by
(position+printed name+signature) . : RF Manager Hans Hu

Echo Wei

Kiki Kong

Hans Hu

Testing Laboratory Name: Shenzhen Huatongwei International Inspection Co., Ltd.

Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao,
Gongming, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely corresponds to the test sample.

Contents

<u>1.</u>	<u>TEST STANDARDS AND REPORT VERSION</u>	<u>3</u>
1.1.	Test Standards	3
1.2.	Report version information	3
<u>2.</u>	<u>TEST DESCRIPTION</u>	<u>4</u>
<u>3.</u>	<u>SUMMARY.....</u>	<u>5</u>
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	EUT operation mode	5
<u>4.</u>	<u>TEST ENVIRONMENT</u>	<u>6</u>
4.1.	Testing Laboratory Information	6
4.2.	Environmental conditions	6
4.3.	Statement of the measurement uncertainty	6
4.4.	Equipments Used during the Test	7
<u>5.</u>	<u>TEST CONDITIONS AND RESULTS</u>	<u>8</u>
5.1.	Conducted Emissions Test	8
5.2.	Radiated Emissions Test	11
<u>6.</u>	<u>TEST SETUP PHOTOS OF THE EUT</u>	<u>15</u>
<u>7.</u>	<u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT</u>	<u>16</u>

1. TEST STANDARDS AND REPORT VERSION

1.1. Test Standards

The tests were performed according to following standards:

[47 CFR FCC Part 15 Subpart B](#) - Unintentional Radiators

[ANSI C63.4: 2014](#) – American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40GHz

1.2. Report version information

Revision No.	Date of issue	Description
N/A	2021-01-04	Original

2. TEST DESCRIPTION

Test Item	Section in CFR 47	Result	Test Engineer
Conducted Emissions	15.107(a)	PASS	Si Ding
Radiated Emissions	15.109(a)	PASS	Haoxin Luo

Note: The measurement uncertainty is not included in the test result.

3. **SUMMARY**

3.1. Client Information

Applicant:	Shenzhen JX ROBOT Technology Co., Ltd.
Address:	Area B, Floor 9th, Building 1, Yulv Seventh Industrial Zone, Gongming Street, Guangming, Shenzhen, Guangdong, China.
Manufacturer:	Shenzhen JX ROBOT Technology Co., Ltd.
Address:	Area B, Floor 9th, Building 1, Yulv Seventh Industrial Zone, Gongming Street, Guangming, Shenzhen, Guangdong, China.

3.2. Product Description

Name of EUT:	Foldable 3 axis gimbal stabilizer
Trade Mark:	-
Model No.:	L7B
Listed Model(s)	L7C, L7D
Power supply:	DC 3.7V
Battery Information:	2000mAh 3.7V
Hardware version:	V1.0.0.7
Software version:	V1.0.0.7

3.3. EUT operation mode

Test mode O1	Keep the EUT in Camera recording statusm,power supply by adapter.
--------------	---

4. TEST ENVIRONMENT

4.1. Testing Laboratory Information

Laboratory Name	Shenzhen Huatongwei International Inspection Co., Ltd.	
Laboratory Location	1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China	
Connect information:	Phone: 86-755-26715499 E-mail: cs@szhtw.com.cn http://www.szhtw.com.cn	
Qualifications	Type	Accreditation Number
	FCC	762235

4.2. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35°C
Relative Humidity:	30~60 %
Air Pressure:	950~1050mba

4.3. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emissions	30~1000MHz	4.90 dB	(1)
Radiated Emissions	1~18GHz	4.96 dB	(1)
Conducted Disturbance	0.15~30MHz	3.02 dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

4.4. Equipments Used during the Test

● Conducted Emission							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Shielded Room	Albatross projects	HTWE0114	N/A	N/A	2018/09/28	2023/09/27
●	EMI Test Receiver	R&S	HTWE0111	ESCI	101247	2020/10/19	2021/10/18
●	Artificial Mains	SCHWARZBECK	HTWE0113	NNLK 8121	573	2020/10/15	2021/10/14
●	Pulse Limiter	R&S	HTWE0033	ESH3-Z2	100499	2020/10/15	2021/10/14
●	RF Connection Cable	HUBER+SUHNER	HTWE0113-02	ENVIROFLEX 142	EF-NM-BNCM-2M	2020/10/15	2021/10/14
●	Test Software	R&S	N/A	ES-K1	N/A	N/A	N/A

● Radiated Emission-6th test site							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2018/09/30	2021/09/29
●	EMI Test Receiver	R&S	HTWE0099	ESCI	100900	2020/10/19	2021/10/18
●	Ultra-Broadband Antenna	SCHWARZBECK	HTWE0119	VULB9163	546	2020/04/28	2023/04/27
●	Pre-Amplifier	SCHWARZBECK	HTWE0295	BBV 9742	N/A	2020/11/13	2021/11/12
●	RF Connection Cable	HUBER+SUHNER	HTWE0062-01	N/A	N/A	2020/05/27	2021/05/26
●	RF Connection Cable	HUBER+SUHNER	HTWE0062-02	SUCOFLEX104	501184/4	2020/05/27	2021/05/26
●	Test Software	R&S	N/A	ES-K1	N/A	N/A	N/A

● Radiated emission-7th test site							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0122	SAC-3m-01	N/A	2018/09/27	2021/09/26
●	Spectrum Analyzer	R&S	HTWE0098	FSP40	100597	2020/10/20	2021/10/19
●	Horn Antenna	SCHWARZBECK	HTWE0126	9120D	1011	2020/04/01	2023/03/31
●	Broadband Pre-amplifier	SCHWARZBECK	HTWE0201	BBV 9718	9718-248	2020/05/23	2021/05/22
●	RF Connection Cable	HUBER+SUHNER	HTWE0121-01	RE-7-FH	N/A	2020/05/10	2021/05/09
●	Test Software	Audix	N/A	E3	N/A	N/A	N/A

5. TEST CONDITIONS AND RESULTS

5.1. Conducted Emissions Test


LIMIT

FCC CFR Title 47 Part 15 Subpart B Section 15.107:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup according to ANSI C63.4:2014
2. The EUT was placed on a plat form of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50ohm / 50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST MODE:


Please refer to the clause 3.3

TEST RESULTS

☒ Passed ☐ Not Applicable

Test Line:

L

**MEASUREMENT RESULT: "GM2012285027_fin"**

12/28/2020 6:10PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.168000	53.20	10.2	65	11.9	QP	L1	GND
0.433500	39.60	10.2	57	17.6	QP	L1	GND
0.546000	42.60	10.2	56	13.4	QP	L1	GND
4.704000	36.00	10.2	56	20.0	QP	L1	GND
6.769500	42.00	10.2	60	18.0	QP	L1	GND


MEASUREMENT RESULT: "GM2012285027_fin2"

12/28/2020 6:10PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.163500	38.60	10.2	55	16.7	AV	L1	GND
0.442500	33.10	10.2	47	13.9	AV	L1	GND
0.550500	33.70	10.2	46	12.3	AV	L1	GND
0.663000	31.50	10.2	46	14.5	AV	L1	GND
0.883500	28.30	10.2	46	17.7	AV	L1	GND
6.531000	33.60	10.2	50	16.4	AV	L1	GND

Test Line:

N

**MEASUREMENT RESULT: "GM2012285028_fin"**

12/28/2020 6:14PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.150000	30.80	10.2	66	35.2	QP	N	GND
0.555000	34.70	10.2	56	21.3	QP	N	GND
0.982500	35.50	10.2	56	20.5	QP	N	GND
4.996500	33.40	10.2	56	22.6	QP	N	GND
6.405000	39.70	10.2	60	20.3	QP	N	GND
21.880500	35.60	10.5	60	24.4	QP	N	GND

MEASUREMENT RESULT: "GM2012285028_fin2"

12/28/2020 6:14PM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.303000	23.10	10.2	50	27.1	AV	N	GND
0.550500	35.20	10.2	46	10.8	AV	N	GND
0.928500	29.00	10.2	46	17.0	AV	N	GND
4.438500	26.50	10.2	46	19.5	AV	N	GND
6.801000	31.60	10.2	50	18.4	AV	N	GND
20.922000	28.10	10.5	50	21.9	AV	N	GND

5.2. Radiated Emissions Test


LIMIT

FCC CFR Title 47 Part 15 Subpart B Section 15.109


Frequency	Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	Quasi-peak
88MHz-216MHz	43.50	Quasi-peak
216MHz-960MHz	46.00	Quasi-peak
960MHz-1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION

➤ 30MHz ~ 1GHz



➤ Above 1GHz



TEST PROCEDURE

1. The EUT was tested according to ANSI C63.4:2014.
2. The EUT is placed on a turn table which is 0.8 meter above ground.
3. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
4. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
5. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna.
6. Use the following spectrum analyzer settings
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Below 1GHz,
RBW=120KHz, VBW=300KHz, Sweep=auto, Detector function=peak, Trace=max hold;
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - (3) From 1GHz to 5th harmonic, RBW=1MHz, VBW=3MHz

TEST MODE:

Please refer to the clause 3.3


TEST RESULTS

☒ **Passed** ☐ **Not Applicable**

Note: Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
The emission levels of frequency above 6GHz are very lower than limit and not show in test report.


Polarization:

Horizontal

**MEASUREMENT RESULT: "GM2012286111_red"**

12/28/2020 10:43PM


Frequency MHz	Level dBuV/m	Transd dB	Limit dBuV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
121.180000	33.90	-12.9	43.5	9.6	QP	300.0	131.00	HORIZONTAL
150.280000	36.70	-14.0	43.5	6.8	QP	100.0	172.00	HORIZONTAL
212.360000	34.90	-10.5	43.5	8.6	QP	100.0	95.00	HORIZONTAL
224.000000	39.70	-9.7	46.0	6.3	QP	100.0	72.00	HORIZONTAL
262.800000	36.70	-8.2	46.0	9.3	QP	100.0	132.00	HORIZONTAL
910.760000	36.10	7.3	46.0	9.9	QP	300.0	338.00	HORIZONTAL



Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1289.73	35.12	25.98	5.39	36.33	30.16	74.00	-43.84	Peak
2	1491.17	34.86	25.93	5.75	36.81	29.73	74.00	-44.27	Peak
3	1878.92	34.14	25.72	6.54	36.98	29.42	74.00	-44.58	Peak
4	2423.30	32.68	27.61	7.78	37.34	30.73	74.00	-43.27	Peak
5	3480.11	32.94	29.02	9.43	36.59	34.80	74.00	-39.20	Peak
6	5398.09	30.77	31.69	12.12	35.31	39.27	74.00	-34.73	Peak


Polarization:

Vertical

**MEASUREMENT RESULT: "GM2012286112_red"**

12/28/2020 10:45PM

Frequency MHz	Level dBuV/m	Transd dB	Limit dBuV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
30.000000	31.50	-12.4	40.0	8.5	QP	100.0	75.00	VERTICAL
45.520000	36.20	-8.9	40.0	3.8	QP	100.0	282.00	VERTICAL
72.680000	35.10	-14.0	40.0	4.9	QP	100.0	269.00	VERTICAL
117.300000	31.40	-12.1	43.5	12.1	QP	100.0	183.00	VERTICAL
291.900000	29.00	-7.3	46.0	17.0	QP	100.0	282.00	VERTICAL
916.580000	35.40	7.5	46.0	10.6	QP	100.0	75.00	VERTICAL



Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	1313.04	35.27	26.08	5.44	36.33	30.46	74.00	-43.54	Peak
2	1937.04	35.06	25.87	6.62	36.96	30.59	74.00	-43.41	Peak
3	2239.59	33.18	28.12	7.22	37.41	31.11	74.00	-42.89	Peak
4	3153.52	33.41	28.99	8.68	37.18	33.90	74.00	-40.10	Peak
5	3430.58	33.63	28.78	9.27	36.60	35.08	74.00	-38.92	Peak
6	4971.02	30.45	31.67	11.55	35.21	38.46	74.00	-35.54	Peak

6. TEST SETUP PHOTOS OF THE EUT

Conducted Emissions (AC Mains)



Radiated Emissions





7. EXTERNAL AND INTERNAL PHOTOS OF THE EUT

Reference to the test report No.: CHTEW20120169

-----End of Report-----