

## 11 Appendix- RF Exposure Information

FCC ID: ATL- FITACTAIR

### SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v05r02.
  - (1) Clause 4.3: General SAR test reduction and exclusion guidance
    - Sub clause 4.31: Standalone SAR test exclusion considerations
      - 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance  $\leq 50$  mm are determined by:  
$$\frac{[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{(\text{GHz})}}]}{\leq 3.0 \text{ for 1-g SAR}}$$
  
$$\frac{[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{(\text{GHz})}}]}{\leq 7.5.0 \text{ for 10-g SAR}}$$

2.

Calculation:

Bluetooth Mode (BLE)						
Frequency (GHz)	Conducted Power (dBm)	Ant Gain (dBi)	TX Power (mW)	Distance (mm)	Calculation Value	Threshold Value
2.402	-3.923	0	0.405	5	0.126	3.0
2.442	-3.938	0	0.404	5	0.126	3.0
2.480	-4.435	0	0.360	5	0.113	3.0

**So standalone SAR measurements are not required.**