

RF Exposure Evaluation Report

Product : Dual Dynamic Driver Wireless Neckband Sports Earbuds
Trade mark : MINISO
Model/Type reference : TB19
Serial Number : N/A
Report Number : EED32N81116602
FCC ID : 2ART4-TB19
Date of Issue : Nov. 10, 2021
Test Standards : 47 CFR Part 1.1307
47 CFR Part 2.1093
KDB447498D01 General
RF Exposure Guidance v06
Test result : PASS

Prepared for:

Miniso Corporation
Room 2501, No. 486 Heye Square Kangwang Middle Road, Liwan District, GuangZhou, Guangdong, China

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District, Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Compiled by:

Martin Lee

Reviewed by:

Aaron Ma

Approved by:

David Wang

Date:

Nov. 10, 2021

David Wang

Check No.: 3306291021



1 Version

Version No.	Date	Description
00	Nov. 10, 2021	Original

2 Contents

	Page
1 VERSION.....	2
2 CONTENTS.....	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT.....	4
3.3 TEST LOCATION.....	5
3.4 DEVIATION FROM STANDARDS.....	5
3.5 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
3.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
4 SAR EVALUATION.....	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	6
4.1.1 Standard Requirement.....	6
4.1.2 EUT RF Exposure.....	7
PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS.....	8

3 General Information

3.1 Client Information

Applicant:	Miniso Corporation
Address of Applicant:	Room 2501, No. 486 Heye Square Kangwang Middle Road, Liwan District, GuangZhou, Guangdong, China
Manufacturer:	Dongguan Shengbang Electronic Technology Co. , Ltd.
Address of Manufacturer:	Room 101, No. 33, Shenxi Road, Houjie Town, Dongguan City, Guangdong Province
Factory:	Dongguan Shengbang Electronic Technology Co. , Ltd.
Address of Factory:	Room 101, No. 33, Shenxi Road, Houjie Town, Dongguan City, Guangdong Province

3.2 General Description of EUT

Product Name:	Dual Dynamic Driver Wireless Neckband Sports Earbuds
Mode No.:	TB19
Trade mark:	MINISO
Bluetooth Version:	V5.0
Operation Frequency:	2402MHz~2480MHz
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Product Type:	☐ Mobile ☒ Portable ☐ Fix Location
Antenna Type:	PCB antenna
Antenna Gain:	0dBi
Power Supply:	lithium battery: DC 3.7V, Charge by DC 5.0V
Test Voltage:	DC 3.7V
Sample Received Date:	Oct. 29, 2021
Sample tested Date:	Oct. 29, 2021 to Nov. 05, 2021
Company Name and Address shown on Report, the sample(s) and sample Information was/ were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified.	

3.3 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

3.4 Deviation from Standards

None.

3.5 Abnormalities from Standard Conditions

None.

3.6 Other Information Requested by the Customer

None.

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06
Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$
$$f(\text{GHz}) \text{ is the RF channel transmit frequency in GHz}$$

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

4.1.2 EUT RF Exposure

1) For BT Classic

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	3.91	3.0±1	4.0	2.512
Middle(2441MHz)	3.57	3.0±1	4.0	2.512
Highest(2480MHz)	3.07	2.5±1	3.5	2.239
π/4DQPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	4.5	4.0±1	5.0	3.162
Middle(2441MHz)	4.24	3.5±1	4.5	2.818
Highest(2480MHz)	3.68	3.0±1	4.0	2.512
8DPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	5.11	4.5±1	5.5	5.5
Middle(2441MHz)	4.83	4.0±1	5.0	5.0
Highest(2480MHz)	4.38	3.5±1	4.5	4.5

Worst case: 8DPSK mode						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune- up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	5.11	4.5±1	5.5	5.5	1.10	3.0
Middle (2441MHz)	4.83	4.0±1	5.0	5.0	0.99	
Highest (2480MHz)	4.38	3.5±1	4.5	4.5	0.89	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: EED32N81116601.

PHOTOGRAPHS OF EUT Constructional Details

Refer to Report No. EED32N81116601 for EUT external and internal photos.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.

*** End of Report ***