

TEST REPORT

Application No.: GZCR2409001046DS
Applicant: Walter Kidde Portable Equipment Inc.
Address of Applicant: 1016 Corporate Park Drive, Mebane, NC, 27302, USA
Manufacturer: Walter Kidde Portable Equipment Inc.
Address of Manufacturer: 1016 Corporate Park Drive, Mebane, NC, 27302, USA
Factory: Dongguan Fyrnetics Co., Ltd.
Address of Factory: No.1 Rongwen Road, Dongguan Changan, Guangdong, China 523842
Product Name: 2.4 GHz Wi-Fi (802.11 b/g/n) and Bluetooth® 5 (LE) module
Model No.: ESP32-S3-WROOM-1U-N8
Trade Mark: Kidde
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2024-09-05
Date of Test: 2024-09-13 to 2024-09-26
Date of Issue: 2024-12-09

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Ricky Liu

Ricky Liu
Manager





SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch (CMAA, CNAS, EEC Laboratory)

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663 t (86-20) 82155555 www.sgsgroup.com.cn
 中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 sgs.china@sgs.com

Revision Record			
Version	Report No.	Date	Remark
01	GZCR240900104601	2024-12-09	Original

Authorized for issue by			
			
		Jim Li/Project Engineer	
			
		Vico Cui/Reviewer	



2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2013) Section 11.12	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Below 1GHz		ANSI C63.10 (2013) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Above 1GHz		ANSI C63.10 (2013) Section 6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Maximum Conducted Output Power		ANSI C63.10 (2013) Section 11.9.2	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density		ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass

Note:

E.U.T./EUT means Equipment Under Test.

Pass means the test result passed the test standard requirement, please find the detailed decision rule in the report relative section.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch EMC Laboratory

No.198, Kazhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

3 Contents

	Page
1 Cover Page	1
2 Test Summary.....	3
3 Contents	4
4 General Information.....	6
4.1 Details of E.U.T.	6
4.2 Description of Support Units.....	6
4.3 Measurement Uncertainty	7
4.4 Test Location	7
4.5 Test Facility.....	8
4.6 Deviation from Standards.....	8
4.7 Abnormalities from Standard Conditions.....	8
5 Equipment List	9
6 Radio Spectrum Technical Requirement.....	12
6.1 Antenna Requirement	12
6.1.1 Test Requirement:	12
6.1.2 Conclusion	12
7 Radio Spectrum Matter Test Results.....	13
7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)	13
7.1.1 E.U.T. Operation	13
7.1.2 Test Mode Description	13
7.1.3 Test Setup Diagram	14
7.1.4 Measurement Procedure and Data.....	14
7.2 Radiated Emissions which fall in the restricted bands	17
7.2.1 E.U.T. Operation	17
7.2.2 Test Mode Description	17
7.2.3 Test Setup Diagram	18
7.2.4 Measurement Procedure and Data.....	18
7.3 Radiated Spurious Emissions Below 1GHz.....	35
7.3.1 E.U.T. Operation	35
7.3.2 Test Mode Description	35
7.3.3 Test Setup Diagram	36
7.3.4 Measurement Procedure and Data.....	36
7.4 Radiated Spurious Emissions Above 1GHz	39
7.4.1 E.U.T. Operation	39
7.4.2 Test Mode Description	39
7.4.3 Test Setup Diagram	39
7.4.4 Measurement Procedure and Data.....	40
7.5 Maximum Conducted Output Power	65
7.5.1 E.U.T. Operation	65
7.5.2 Test Mode Description	65
7.5.3 Test Setup Diagram	66



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.5.4	Measurement Procedure and Data.....	66
7.6	Minimum 6dB Bandwidth.....	67
7.6.1	E.U.T. Operation.....	67
7.6.2	Test Mode Description.....	67
7.6.3	Test Setup Diagram.....	67
7.6.4	Measurement Procedure and Data.....	67
7.7	Power Spectrum Density.....	68
7.7.1	E.U.T. Operation.....	68
7.7.2	Test Mode Description.....	68
7.7.3	Test Setup Diagram.....	68
7.7.4	Measurement Procedure and Data.....	68
7.8	Conducted Band Edges Measurement.....	69
7.8.1	E.U.T. Operation.....	69
7.8.2	Test Mode Description.....	69
7.8.3	Test Setup Diagram.....	70
7.8.4	Measurement Procedure and Data.....	70
7.9	Conducted Spurious Emissions.....	71
7.9.1	E.U.T. Operation.....	71
7.9.2	Test Mode Description.....	71
7.9.3	Test Setup Diagram.....	72
7.9.4	Measurement Procedure and Data.....	72
8	Test Setup Photo.....	73
9	EUT Constructional Details (EUT Photos).....	74
10	Appendix.....	75



4 General Information

4.1 Details of E.U.T.

Power supply: DC 3.3 V
 Cable(s): DC input ports
 Test Voltage: AC 120 V, 60 Hz powered by Note Book Computer refer to section 4.2
 Antenna Type: Flex-PIFA Antenna
 Antenna Gain: 4.4 dBi according to antenna specification
 Antenna Number: 1
 For BLE
 Operation Frequency: 2402MHz to 2480MHz
 Modulation Type: GFSK
 Number of Channels: 40
 Channel Spacing: 2MHz
 For 2.4GHz Wi-Fi
 Operation Frequency: 802.11b/g/n(HT20): 2412MHz to 2462MHz;802.11n(HT40): 2422MHz to 2452MHz
 Modulation Type: 802.11b: DSSS (CCK, DQPSK, DBPSK);802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
 Number of Channels: 802.11b/g/n(HT20):11;802.11n(HT40):7
 Channel Spacing: 5MHz
 Remark: The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Note Book Computer	LENOVO	ThinkPad T490	PF1D1MVJ



4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emissions at AC Power Line (150kHz-30MHz)	±3.22dB
Radiated Emissions which fall in the restricted bands	±5.14dB (3m); ±4.90dB (10m); ±4.88dB (1GHz-6GHz); ±5.06dB (6GHz-18GHz); ±5.30dB (18GHz-40GHz)
Radiated Spurious Emissions Below 1GHz	±3.08dB (9kHz to 150kHz); ±3.19dB (150kHz to 30MHz); ±5.14dB (30MHz-1GHz) (3m); ±4.90dB (30MHz-1GHz) (10m)
Radiated Spurious Emissions Above 1GHz	±4.88dB (1GHz-6GHz); ±5.06dB (6GHz-18GHz); ±5.30dB (18GHz-40GHz)
Conducted Peak Output Power	± 0.75dB
Minimum 6dB Bandwidth	± 0.274%
Power Spectrum Density	± 2.84dB
Conducted Band Edges Measurement	± 0.75dB
Conducted Spurious Emissions	± 0.75dB
<p>Remark:</p> <p>The U_{lab} (lab Uncertainty) is less than U_{CISPR} (CISPR Uncertainty) or U_{ETSI} (ETSI Uncertainty).</p> <p>Emission decision rule:</p> <ul style="list-style-type: none"> – Compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit, marked as Pass in the report. – Non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit, marked as Fail in the report. 	

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou Branch EMC Laboratory,
No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou,
Guangdong, China 510663

Tel: +86 20 82155555

No tests were sub-contracted.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch EMC Laboratory

No.198, Kezhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

● ACMA

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian/New Zealand Regulatory Compliance Mark (RCM).

● SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

● FCC Recognized Accredited Test Firm(Registration No.: 486818)

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: CN5016, Test Firm Registration Number: 486818.

● ISED (Registration No.: 4620B, CAB identifier: CN0052)

SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Innovation Science and Economic Development Canada for Wireless Device Testing laboratories to test to Canadian radio equipment requirements. Registration No. 4620B, CAB identifier: CN0052.

● VCCI (Registration No.: R-12460, C-12584, G-20107 and T-11179)

The 10m Semi-anechoic chamber, 966 Anechoic Chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-12460, C-12584, G-20107 and T-11179 respectively.

● CBTL (Lab Code: TL129)

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2017, the Basic Rules, IECEE 01 and Rules of procedure IECEE 02, and the relevant IECEE CB-Scheme Operational documents.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch EMC Laboratory

No.198, Kazhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Coaxial Cable	HangTianXing	2m	EMC0107	2023-08-24	2025-08-23
Shielding Room	ChangZhou ZhongYu	8m x 3m x 3.8m	EMC0306	2022-10-16	2025-10-15
Two-Line V-Network-GZ	Rohde & Schwarz	ENV216	EMC2135	2024-09-02	2025-09-01
EMI Test Receiver (9kHz-3.6GHz)	Rohde & Schwarz	ESR3	EMC2221	2024-05-13	2025-05-12
Test Software E3r	Audix	Ver.6.191211	GZE100-77	N/A	N/A

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
1GHz-26.5 GHz Pre-Amplifier	Agilent	8449B	EMC0521	2023-11-10	2024-11-09
EMI Test Receiver (10Hz-26.5GHz)	Rohde & Schwarz	ESIB26	EMC0522	2024-09-02	2025-09-01
Chamber cable (Above 1GHz)	Scoflex	KMKM-8.0m	EMC0545	2024-08-19	2026-08-18
Horn Antenna (1GHz-18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	EMC2026	2022-09-23	2025-09-22
Horn Antenna (14-40GHz)	SCHWARZBECK	BBHA 9170	EMC2041	2023-06-18	2026-06-17
EXA Signal Analyzer (10Hz-44GHz)	Keysight	N9010A	EMC2138	2024-08-19	2025-08-18
MXE EMI Receiver (10Hz-8.4GHz)	Keysight	N9038A	EMC2139	2023-10-20	2024-10-19
966 Anechoic Chamber	C.R.T	9m x 6m x 6m	EMC2142	2023-12-20	2026-12-19
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A



Radiated Spurious Emissions Below 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
966 Anechoic Chamber	Shenzhen C.R.T	CRTSGSSAC966	EMC2230	2022-04-12	2025-04-11
EMI Test Receiver(1Hz-8GHz)	Rohde & Schwarz	ESW8	EMC2229	2024-02-19	2025-02-18
Amplifier(9k-1000MHz)	SONOMA	310	EMC2237	2024-03-22	2025-03-21
TRILOG Broadband Antenna (25M-2GHz)	SCHWRZBECK	VULB 9168	EMC2238	2022-04-20	2025-04-19
Coaxial Cable	Mirco-COAX UTIFLEX ve	LA2-C125-8000	EMC2239	2023-06-14	2025-06-13
Test Software E3	Audix	Ver.6.191211	GZE100-81	N/A	N/A
Active Loop Antenna-RED	ETS-Lindgren	6502	EMC2190	2024-04-08	2026-04-07

Radiated Spurious Emissions Above 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
1GHz-26.5 GHz Pre-Amplifier	Agilent	8449B	EMC0521	2023-11-10	2024-11-09
EMI Test Receiver (10Hz-26.5GHz)	Rohde & Schwarz	ESIB26	EMC0522	2024-09-02	2025-09-01
Chamber cable (Above 1GHz)	Scoflex	KMKM-8.0m	EMC0545	2024-08-19	2026-08-18
Horn Antenna (1GHz-18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	EMC2026	2022-09-23	2025-09-22
Horn Antenna (14-40GHz)	SCHWARZBECK	BBHA 9170	EMC2041	2023-06-18	2026-06-17
2.4GHz Filter	Micro-Tronics	BRM 50702	EMC2069	2023-11-10	2024-11-09
EXA Signal Analyzer (10Hz-44GHz)	Keysight	N9010A	EMC2138	2024-08-19	2025-08-18
MXE EMI Receiver (10Hz-8.4GHz)	Keysight	N9038A	EMC2139	2023-10-20	2024-10-19
966 Anechoic Chamber	C.R.T	9m x 6m x 6m	EMC2142	2023-12-20	2026-12-19
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A

RF Conducted Test					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
MI CABLE	SGS-EMC	0.8M	EMC2137	2023-11-02	2025-11-01
4X4 Power sensor Unit	TST	TSPS2023R	EMC2226	2024-08-19	2025-08-18
Test Software	TST	V2.0	GZE100-78	N/A	N/A
EXA Signal Analyzer (10Hz-44GHz)	Keysight	N9010A	EMC2138	2024-08-19	2025-08-18





SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch

EMC-TRF-01 Rev 1.1

Report No.: GZCR240900104601

Page: 11 of 129

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DMM	Fluke	73	EMC0006	2024-06-13	2025-06-12



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch, EMC Laboratory. No.198, Kazhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663 t (86-20) 82155555 www.sgsgroup.com.cn
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 sgs.china@sgs.com

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 4.4 dBi.

Antenna location: Refer to internal photo.

7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		
Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz		

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 24.1 °C

Humidity: 53.6 % RH


Atmospheric Pressure: 1005 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	02	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.



Test Mode: 00 & 02; Line: Live line




Pol : LINE
Mode :
Model :
Power :

	Frequency MHz	Read Level dBuV	Cable Loss dB	LISN Factor dB	Measured Level dBuV	Limit Line dBuV	Over Limit dB	Remark
1	0.224	14.38	0.06	9.62	24.06	52.66	-28.60	Average
2	0.224	16.56	0.06	9.62	26.24	62.66	-36.42	QP
3	0.350	15.82	0.06	9.63	25.51	48.96	-23.45	Average
4	0.350	19.03	0.06	9.63	28.72	58.96	-30.24	QP
5	0.521	14.80	0.07	9.63	24.50	46.00	-21.50	Average
6	0.521	21.91	0.07	9.63	31.61	56.00	-24.39	QP
7	1.054	21.01	0.07	9.62	30.70	46.00	-15.30	Average
8	1.054	25.74	0.07	9.62	35.43	56.00	-20.57	QP
9	2.527	15.73	0.13	9.62	25.48	46.00	-20.52	Average
10	2.527	22.17	0.13	9.62	31.92	56.00	-24.08	QP
11	6.089	15.01	0.20	9.67	24.88	50.00	-25.12	Average
12	6.089	20.29	0.20	9.67	30.16	60.00	-29.84	QP



Test Mode: 00 & 02; Line: Neutral Line



Pol : NEUTRAL
Mode :
Model :
Power :

	Frequency MHz	Read Level dBuV	Cable Loss dB	LISN Factor dB	Measured Level dBuV	Limit Line dBuV	Over Limit dB	Remark
1	0.350	14.51	0.06	9.54	24.11	48.96	-24.85	Average
2	0.350	17.55	0.06	9.54	27.15	58.96	-31.81	QP
3	0.513	19.11	0.07	9.55	28.73	46.00	-17.27	Average
4	0.513	23.34	0.07	9.55	32.96	56.00	-23.04	QP
5	1.027	20.93	0.07	9.55	30.55	46.00	-15.45	Average
6	1.027	25.89	0.07	9.55	35.51	56.00	-20.49	QP
7	2.334	13.37	0.13	9.54	23.04	46.00	-22.96	Average
8	2.334	20.02	0.13	9.54	29.69	56.00	-26.31	QP
9	4.114	13.63	0.17	9.56	23.36	46.00	-22.64	Average
10	4.114	20.53	0.17	9.56	30.26	56.00	-25.74	QP
11	5.898	15.88	0.19	9.57	25.64	50.00	-24.36	Average
12	5.898	21.02	0.19	9.57	30.78	60.00	-29.22	QP



7.2 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 11.12

Limit:

Test Distance: 3 m

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.2.1 E.U.T. Operation

Operating Environment:


Temperature: 25.3 °C Humidity: 67.3 % RH Atmospheric Pressure: 1005 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	02	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.



7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data


- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.




Test Mode: 02; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2386.340	55.94	27.68	3.44	37.22	49.84	74.00	-24.16	VERTICAL Peak
2	2390.000	55.10	27.68	3.44	37.21	49.01	74.00	-24.99	VERTICAL peak
3 *	2412.000	106.61	27.74	3.46	37.21	100.60	74.00	26.60	VERTICAL peak




Test Mode: 02; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



	ReadAntenna	Cable	Preamp		Limit	Over		
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	Remark
1	2389.242	57.56	27.68	3.44	37.22	51.46	74.00	-22.54 HORIZONTAL peak
2	2390.000	56.80	27.68	3.44	37.21	50.71	74.00	-23.29 HORIZONTAL peak
3 *	2412.000	110.41	27.74	3.46	37.21	104.40	74.00	30.40 HORIZONTAL peak




Test Mode: 02; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1 *	2462.000	106.43	27.82	3.48	37.20	100.53	74.00	26.53	VERTICAL peak
2	2483.500	47.09	27.85	3.49	37.19	41.24	74.00	-32.76	VERTICAL peak
3	2488.159	50.05	27.85	3.49	37.19	44.20	74.00	-29.80	VERTICAL peak




Test Mode: 02; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 *	2462.000	110.74	27.82	3.48	37.20	104.84	74.00	30.84	HORIZONTAL peak
2	2483.500	56.36	27.85	3.49	37.19	50.51	74.00	-23.49	HORIZONTAL peak
3	2487.556	58.18	27.85	3.49	37.19	52.33	74.00	-21.67	HORIZONTAL peak




Test Mode: 02; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low



	ReadAntenna	Cable	Preamp		Limit	Over			
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2389.242	51.46	27.68	3.44	37.22	45.36	74.00	-28.64	VERTICAL peak
2	2390.000	49.66	27.68	3.44	37.21	43.57	74.00	-30.43	VERTICAL peak
3 *	2412.000	105.06	27.74	3.46	37.21	99.05	74.00	25.05	VERTICAL peak




Test Mode: 02; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2388.637	55.88	27.68	3.44	37.22	49.78	54.00	-4.22	HORIZONTAL Average
2	2388.637	64.82	27.68	3.44	37.22	58.72	74.00	-15.28	HORIZONTAL peak
3	2390.000	57.76	27.68	3.44	37.21	51.67	54.00	-2.33	HORIZONTAL Average
4	2390.000	65.06	27.68	3.44	37.21	58.97	74.00	-15.03	HORIZONTAL peak
5 *	2412.000	109.60	27.74	3.46	37.21	103.59	74.00	29.59	HORIZONTAL peak




Test Mode: 02; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over		
	MHz	Level	Loss	Factor	dBuV/m	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1 *	2462.000	103.61	27.82	3.48	37.20	97.71	74.00	23.71	VERTICAL peak
2	2483.500	54.28	27.85	3.49	37.19	48.43	54.00	-5.57	VERTICAL Average
3	2483.500	60.73	27.85	3.49	37.19	54.88	74.00	-19.12	VERTICAL peak
4	2484.793	52.92	27.85	3.49	37.19	47.07	54.00	-6.93	VERTICAL Average
5	2484.793	60.53	27.85	3.49	37.19	54.68	74.00	-19.32	VERTICAL peak




Test Mode: 02; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 *	2462.000	111.63	27.82	3.48	37.20	105.73	74.00	31.73	HORIZONTAL peak
2	2483.500	57.94	27.85	3.49	37.19	52.09	54.00	-1.91	HORIZONTAL Average
3	2483.500	63.53	27.85	3.49	37.19	57.68	74.00	-16.32	HORIZONTAL peak
4	2484.793	57.22	27.85	3.49	37.19	51.37	54.00	-2.63	HORIZONTAL Average
5	2484.793	63.50	27.85	3.49	37.19	57.65	74.00	-16.35	HORIZONTAL peak




Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp	Level	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2384.857	59.50	27.68	3.44	37.22	53.40	74.00	-20.60	VERTICAL peak
2	2390.000	59.24	27.68	3.44	37.21	53.15	74.00	-20.85	VERTICAL peak
3 *	2422.000	94.77	27.75	3.46	37.21	88.77	74.00	14.77	VERTICAL peak




Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp	Limit	Over		
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB	
1	2389.070	58.01	27.68	3.44	37.22	51.91	54.00	-2.09 HORIZONTAL Average
2	2389.070	66.15	27.68	3.44	37.22	60.05	74.00	-13.95 HORIZONTAL peak
3	2390.000	58.53	27.68	3.44	37.21	52.44	54.00	-1.56 HORIZONTAL Average
4	2390.000	64.11	27.68	3.44	37.21	58.02	74.00	-15.98 HORIZONTAL peak
5 *	2422.000	102.84	27.75	3.46	37.21	96.84	74.00	22.84 HORIZONTAL peak




Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 *	2452.000	92.03	27.80	3.47	37.20	86.10	74.00	12.10	VERTICAL peak
2	2483.500	56.34	27.85	3.49	37.19	50.49	74.00	-23.51	VERTICAL peak
3	2484.852	58.16	27.85	3.49	37.19	52.31	74.00	-21.69	VERTICAL peak




Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High



	ReadAntenna	Cable Preamp		Limit	Over			
Freq	Level Factor	Loss Factor	Level	Line	Limit	Pol/Phase	Remark	
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 *	2452.000	99.92	27.80	3.47	37.20	93.99	74.00	19.99 HORIZONTAL peak
2	2483.500	59.38	27.85	3.49	37.19	53.53	54.00	-0.47 HORIZONTAL Average
3	2483.500	62.81	27.85	3.49	37.19	56.96	74.00	-17.04 HORIZONTAL peak
4	2484.993	58.03	27.85	3.49	37.19	52.18	54.00	-1.82 HORIZONTAL Average
5	2484.993	62.50	27.85	3.49	37.19	56.65	74.00	-17.35 HORIZONTAL peak




Test Mode: 00; Polarity: Vertical; Modulation: GFSK; Channel: Low



	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
		dBuV	dB/m	dB	dB	dBuV/m	dB		
1	2363.473	50.79	27.64	3.43	37.23	44.63	74.00	-29.37	VERTICAL peak
2	2390.000	47.90	27.68	3.44	37.21	41.81	74.00	-32.19	VERTICAL peak
3 *	2402.000	97.12	27.71	3.45	37.21	91.07	74.00	17.07	VERTICAL peak




Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:Low



	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2375.322	53.97	27.66	3.44	37.22	47.85	74.00	-26.15	HORIZONTAL peak
2	2390.000	52.48	27.68	3.44	37.21	46.39	74.00	-27.61	HORIZONTAL peak
3 *	2402.000	104.92	27.71	3.45	37.21	98.87	74.00	24.87	HORIZONTAL peak




Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:High



	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
		Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 *	2480.000	102.00	27.84	3.48	37.19	96.13	74.00	22.13	VERTICAL peak
2	2483.500	57.58	27.85	3.49	37.19	51.73	74.00	-22.27	VERTICAL peak
3	2483.771	57.37	27.85	3.49	37.19	51.52	74.00	-22.48	VERTICAL peak



Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:High



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 *	2480.000	106.31	27.84	3.48	37.19	100.44	74.00	26.44	HORIZONTAL peak
2	2483.500	57.31	27.85	3.49	37.19	51.46	54.00	-2.54	HORIZONTAL Average
3	2483.500	62.02	27.85	3.49	37.19	56.17	74.00	-17.83	HORIZONTAL peak
4	2483.721	56.53	27.85	3.49	37.19	50.68	54.00	-3.32	HORIZONTAL Average
5	2483.721	61.46	27.85	3.49	37.19	55.61	74.00	-18.39	HORIZONTAL peak



7.3 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5

Limit:

Test Distance: 3 m

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 22.0 °C

Humidity: 52.9 % RH


Atmospheric Pressure: 1005 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	02	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.



7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data


- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:

- Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
- Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.



Test Mode: 00 & 02; Polarity: Horizontal




Site : 966 Chamber
Job :
Model :
Power :
Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	40.845	25.67	19.16	0.35	32.87	12.31	40.00	-27.69	VERTICAL	QP
2	58.407	26.80	18.99	0.41	32.87	13.33	40.00	-26.67	VERTICAL	QP
3	157.007	27.27	19.18	0.69	32.83	14.31	43.52	-29.21	VERTICAL	QP
4	400.432	26.24	21.60	1.16	32.94	16.06	46.02	-29.96	VERTICAL	QP
5	793.396	28.43	28.32	1.66	32.43	25.98	46.02	-20.04	VERTICAL	QP
6	932.272	26.62	29.77	1.78	31.80	26.37	46.02	-19.65	VERTICAL	QP



Test Mode: 00 & 02; Polarity: Vertical



Site : 966 Chamber
Job :
Model :
Power :
Test Mode :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Measured Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	40.276	26.38	19.16	0.35	32.87	13.02	40.00	-26.98	VERTICAL	QP
2	63.759	24.76	18.14	0.43	32.86	10.47	40.00	-29.53	VERTICAL	QP
3	165.487	26.19	18.99	0.71	32.83	13.06	43.52	-30.46	VERTICAL	QP
4	537.589	27.81	24.29	1.33	32.96	20.47	46.02	-25.55	VERTICAL	QP
5	848.056	27.86	28.87	1.70	32.34	26.09	46.02	-19.93	VERTICAL	QP
6	975.753	27.66	29.89	1.83	31.68	27.70	53.98	-26.28	VERTICAL	QP



7.4 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.6

Limit:

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance(meters)
Above 1000	500	3

7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 25.3 °C


Humidity: 67.3 % RH

Atmospheric Pressure: 1005 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	02	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.

7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data


- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.




Test Mode: 02; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1196.264	53.56	23.14	2.39	37.64	41.45	74.00	-32.55	VERTICAL peak
2	4456.315	45.00	34.00	4.61	36.63	46.98	74.00	-27.02	VERTICAL peak
3	4824.000	44.07	34.16	4.82	36.67	46.38	74.00	-27.62	VERTICAL peak
4	6874.906	44.56	34.88	5.83	36.87	48.40	74.00	-25.60	VERTICAL peak
5	7236.000	45.10	35.78	5.95	36.94	49.89	74.00	-24.11	VERTICAL peak
6	9648.000	41.25	38.70	7.05	36.82	50.18	74.00	-23.82	VERTICAL peak




Test Mode: 02; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1182.513	61.60	23.04	2.36	37.65	49.35	74.00	-24.65	HORIZONTAL peak
2	4405.090	45.76	33.74	4.61	36.62	47.49	74.00	-26.51	HORIZONTAL peak
3	4824.000	48.90	34.16	4.82	36.67	51.21	74.00	-22.79	HORIZONTAL peak
4	5713.856	47.35	32.65	5.27	36.78	48.49	74.00	-25.51	HORIZONTAL peak
5	7236.000	44.81	35.78	5.95	36.94	49.60	74.00	-24.40	HORIZONTAL peak
6	9648.000	41.47	38.70	7.05	36.82	50.40	74.00	-23.60	HORIZONTAL peak




Test Mode: 02; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:middle



	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1096.904	57.72	22.67	2.27	37.67	44.99	74.00	-29.01	VERTICAL peak
2	3223.928	53.10	28.84	3.94	36.81	49.07	74.00	-24.93	VERTICAL peak
3	4874.000	44.34	34.15	4.85	36.67	46.67	74.00	-27.33	VERTICAL peak
4	7035.727	45.01	35.19	5.88	36.91	49.17	74.00	-24.83	VERTICAL peak
5	7311.000	45.51	36.00	5.98	36.95	50.54	74.00	-23.46	VERTICAL peak
6	9748.000	41.46	38.81	7.11	36.81	50.57	74.00	-23.43	VERTICAL peak




Test Mode: 02; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:middle



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1168.920	63.17	22.96	2.34	37.65	50.82	74.00	-23.18	HORIZONTAL peak
2	4379.699	45.20	33.59	4.60	36.62	46.77	74.00	-27.23	HORIZONTAL peak
3	4874.000	44.65	34.15	4.85	36.67	46.98	74.00	-27.02	HORIZONTAL peak
4	7096.999	44.78	35.33	5.90	36.92	49.09	74.00	-24.91	HORIZONTAL peak
5	7311.000	44.99	36.00	5.98	36.95	50.02	74.00	-23.98	HORIZONTAL peak
6	9748.000	40.57	38.81	7.11	36.81	49.68	74.00	-24.32	HORIZONTAL peak




Test Mode: 02; Polarity: Vertical; Modulation:802.11b; Bandwidth:20MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1175.697	57.09	23.00	2.35	37.65	44.79	74.00	-29.21	VERTICAL peak
2	3261.418	52.79	28.89	3.98	36.79	48.87	74.00	-25.13	VERTICAL peak
3	4924.000	45.95	34.15	4.88	36.68	48.30	74.00	-25.70	VERTICAL peak
4	7076.516	45.36	35.28	5.89	36.91	49.62	74.00	-24.38	VERTICAL peak
5	7386.000	44.40	36.23	6.00	36.96	49.67	74.00	-24.33	VERTICAL peak
6	9848.000	41.38	38.88	7.15	36.81	50.60	74.00	-23.40	VERTICAL peak




Test Mode: 02; Polarity: Horizontal; Modulation:802.11b; Bandwidth:20MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1217.190	59.54	23.34	2.43	37.64	47.67	74.00	-26.33	HORIZONTAL peak
2	4482.150	45.17	34.12	4.62	36.63	47.28	74.00	-26.72	HORIZONTAL peak
3	4924.000	47.69	34.15	4.88	36.68	50.04	74.00	-23.96	HORIZONTAL peak
4	7076.516	45.19	35.28	5.89	36.91	49.45	74.00	-24.55	HORIZONTAL peak
5	7386.000	45.27	36.23	6.00	36.96	50.54	74.00	-23.46	HORIZONTAL peak
6	9848.000	41.61	38.88	7.15	36.81	50.83	74.00	-23.17	HORIZONTAL peak




Test Mode: 02; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1439.343	56.85	24.34	2.68	37.55	46.32	74.00	-27.68	VERTICAL peak
2	3261.418	51.33	28.89	3.98	36.79	47.41	74.00	-26.59	VERTICAL peak
3	4824.000	44.24	34.16	4.82	36.67	46.55	74.00	-27.45	VERTICAL peak
4	5713.856	46.11	32.65	5.27	36.78	47.25	74.00	-26.75	VERTICAL peak
5	7236.000	45.53	35.78	5.95	36.94	50.32	74.00	-23.68	VERTICAL peak
6	9648.000	41.98	38.70	7.05	36.82	50.91	74.00	-23.09	VERTICAL peak




Test Mode: 02; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1122.563	60.68	22.75	2.29	37.67	48.05	74.00	-25.95	HORIZONTAL peak
2	3280.326	52.85	28.91	3.99	36.79	48.96	74.00	-25.04	HORIZONTAL peak
3	4824.000	47.83	34.16	4.82	36.67	50.14	74.00	-23.86	HORIZONTAL peak
4	5746.982	46.03	32.65	5.30	36.79	47.19	74.00	-26.81	HORIZONTAL peak
5	7236.000	44.52	35.78	5.95	36.94	49.31	74.00	-24.69	HORIZONTAL peak
6	9648.000	41.67	38.70	7.05	36.82	50.60	74.00	-23.40	HORIZONTAL peak




Test Mode: 02; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:middle



	Read	Antenna	Cable	Preamp	Limit	Over			
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1096.904	54.81	22.67	2.27	37.67	42.08	74.00	-31.92	VERTICAL peak
2	3318.471	52.79	28.94	4.02	36.77	48.98	74.00	-25.02	VERTICAL peak
3	4874.000	43.43	34.15	4.85	36.67	45.76	74.00	-28.24	VERTICAL peak
4	6954.852	44.91	35.04	5.86	36.89	48.92	74.00	-25.08	VERTICAL peak
5	7311.000	45.44	36.00	5.98	36.95	50.47	74.00	-23.53	VERTICAL peak
6	9748.000	40.48	38.81	7.11	36.81	49.59	74.00	-24.41	VERTICAL peak




Test Mode: 02; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:middle



	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1096.904	54.61	22.67	2.27	37.67	41.88	74.00	-32.12	HORIZONTAL peak
2	3261.418	55.63	28.89	3.98	36.79	51.71	74.00	-22.29	HORIZONTAL peak
3	4874.000	44.34	34.15	4.85	36.67	46.67	74.00	-27.33	HORIZONTAL peak
4	6914.763	44.99	34.97	5.84	36.88	48.92	74.00	-25.08	HORIZONTAL peak
5	7311.000	44.71	36.00	5.98	36.95	49.74	74.00	-24.26	HORIZONTAL peak
6	9748.000	40.74	38.81	7.11	36.81	49.85	74.00	-24.15	HORIZONTAL peak




Test Mode: 02; Polarity: Vertical; Modulation:802.11g; Bandwidth:20MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1129.072	54.70	22.78	2.30	37.67	42.11	74.00	-31.89	VERTICAL peak
2	3318.471	53.74	28.94	4.02	36.77	49.93	74.00	-24.07	VERTICAL peak
3	4924.000	43.65	34.15	4.88	36.68	46.00	74.00	-28.00	VERTICAL peak
4	7035.727	44.20	35.19	5.88	36.91	48.36	74.00	-25.64	VERTICAL peak
5	7386.000	44.35	36.23	6.00	36.96	49.62	74.00	-24.38	VERTICAL peak
6	9848.000	41.37	38.88	7.15	36.81	50.59	74.00	-23.41	VERTICAL peak




Test Mode: 02; Polarity: Horizontal; Modulation:802.11g; Bandwidth:20MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1155.483	54.62	22.89	2.33	37.66	42.18	74.00	-31.82	HORIZONTAL peak
2	3337.710	53.24	28.95	4.03	36.76	49.46	74.00	-24.54	HORIZONTAL peak
3	4924.000	43.49	34.15	4.88	36.68	45.84	74.00	-28.16	HORIZONTAL peak
4	7076.516	44.26	35.28	5.89	36.91	48.52	74.00	-25.48	HORIZONTAL peak
5	7386.000	42.79	36.23	6.00	36.96	48.06	74.00	-25.94	HORIZONTAL peak
6	9848.000	40.13	38.88	7.15	36.81	49.35	74.00	-24.65	HORIZONTAL peak




Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
		dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1634.543	51.16	24.81	2.78	37.42	41.33	74.00	-32.67	VERTICAL peak
2	4495.125	44.60	34.17	4.62	36.63	46.76	74.00	-27.24	VERTICAL peak
3	4844.000	43.23	34.15	4.84	36.67	45.55	74.00	-28.45	VERTICAL peak
4	6914.763	44.22	34.97	5.84	36.88	48.15	74.00	-25.85	VERTICAL peak
5	7266.000	44.32	35.86	5.96	36.94	49.20	74.00	-24.80	VERTICAL peak
6	9688.000	42.16	38.75	7.08	36.82	51.17	74.00	-22.83	VERTICAL peak




Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



	Freq	ReadAntenna	Cable	Preamp	Limit	Over		
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB	
1	1634.543	50.90	24.81	2.78	37.42	41.07	74.00	-32.93 HORIZONTAL peak
2	4456.315	44.80	34.00	4.61	36.63	46.78	74.00	-27.22 HORIZONTAL peak
3	4844.000	44.37	34.15	4.84	36.67	46.69	74.00	-27.31 HORIZONTAL peak
4	6835.278	44.22	34.79	5.81	36.87	47.95	74.00	-26.05 HORIZONTAL peak
5	7266.000	43.61	35.86	5.96	36.94	48.49	74.00	-25.51 HORIZONTAL peak
6	9688.000	41.85	38.75	7.08	36.82	50.86	74.00	-23.14 HORIZONTAL peak




Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:middle



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1634.543	51.32	24.81	2.78	37.42	41.49	74.00	-32.51	VERTICAL peak
2	4482.150	45.14	34.12	4.62	36.63	47.25	74.00	-26.75	VERTICAL peak
3	4874.000	43.32	34.15	4.85	36.67	45.65	74.00	-28.35	VERTICAL peak
4	7035.727	44.15	35.19	5.88	36.91	48.31	74.00	-25.69	VERTICAL peak
5	7311.000	44.07	36.00	5.98	36.95	49.10	74.00	-24.90	VERTICAL peak
6	9748.000	43.29	38.81	7.11	36.81	52.40	74.00	-21.60	VERTICAL peak




Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:middle



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1374.295	52.70	24.20	2.64	37.57	41.97	74.00	-32.03	HORIZONTAL peak
2	4482.150	43.55	34.12	4.62	36.63	45.66	74.00	-28.34	HORIZONTAL peak
3	4874.000	43.97	34.15	4.85	36.67	46.30	74.00	-27.70	HORIZONTAL peak
4	7035.727	43.66	35.19	5.88	36.91	47.82	74.00	-26.18	HORIZONTAL peak
5	7311.000	43.81	36.00	5.98	36.95	48.84	74.00	-25.16	HORIZONTAL peak
6	9748.000	41.81	38.81	7.11	36.81	50.92	74.00	-23.08	HORIZONTAL peak




Test Mode: 02; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1390.276	52.08	24.24	2.65	37.57	41.40	74.00	-32.60	VERTICAL peak
2	3261.418	55.12	28.89	3.98	36.79	51.20	74.00	-22.80	VERTICAL peak
3	4904.000	43.62	34.15	4.86	36.68	45.95	74.00	-28.05	VERTICAL peak
4	6106.616	44.44	32.89	5.47	36.81	45.99	74.00	-28.01	VERTICAL Peak
5	7356.000	45.14	36.12	5.99	36.95	50.30	74.00	-23.70	VERTICAL peak
6	9808.000	41.23	38.86	7.14	36.81	50.42	74.00	-23.58	VERTICAL peak




Test Mode: 02; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp	Limit	Over		
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB	
1	1414.597	57.25	24.29	2.67	37.56	46.65	74.00	-27.35 HORIZONTAL peak
2	3299.344	51.50	28.93	4.01	36.78	47.66	74.00	-26.34 HORIZONTAL peak
3	4904.000	44.53	34.15	4.86	36.68	46.86	74.00	-27.14 HORIZONTAL peak
4	6954.852	44.61	35.04	5.86	36.89	48.62	74.00	-25.38 HORIZONTAL peak
5	7356.000	44.23	36.12	5.99	36.95	49.39	74.00	-24.61 HORIZONTAL peak
6	9808.000	42.35	38.86	7.14	36.81	51.54	74.00	-22.46 HORIZONTAL peak




Test Mode: 00; Polarity: Vertical; Modulation: GFSK; Channel: Low



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1447.688	57.64	24.35	2.68	37.53	47.14	74.00	-26.86	VERTICAL peak
2	3299.344	55.35	28.93	4.01	36.78	51.51	74.00	-22.49	VERTICAL peak
3	4804.000	44.45	34.16	4.81	36.66	46.76	74.00	-27.24	VERTICAL peak
4	6488.754	45.57	33.84	5.64	36.83	48.22	74.00	-25.78	VERTICAL peak
5	7206.000	47.48	35.63	5.93	36.93	52.11	74.00	-21.89	VERTICAL peak
6	9205.540	45.70	37.97	6.73	36.86	53.54	74.00	-20.46	VERTICAL peak




Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:Low



	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Loss	Factor	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1103.264	61.18	22.69	2.28	37.67	48.48	74.00	-25.52	HORIZONTAL peak
2	3280.326	55.63	28.91	3.99	36.79	51.74	74.00	-22.26	HORIZONTAL peak
3	4804.000	45.60	34.16	4.81	36.66	47.91	74.00	-26.09	HORIZONTAL peak
4	6602.265	44.98	34.07	5.69	36.84	47.90	74.00	-26.10	HORIZONTAL peak
5	7206.000	45.51	35.63	5.93	36.93	50.14	74.00	-23.86	HORIZONTAL peak
6	8995.123	45.65	37.59	6.57	36.90	52.91	74.00	-21.09	HORIZONTAL peak




Test Mode: 00; Polarity: Vertical; Modulation:GFSK; Channel:middle



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1103.264	60.76	22.69	2.28	37.67	48.06	74.00	-25.94	VERTICAL peak
2	3318.471	53.89	28.94	4.02	36.77	50.08	74.00	-23.92	VERTICAL peak
3	4880.000	46.87	34.15	4.85	36.67	49.20	74.00	-24.80	VERTICAL peak
4	6954.852	44.64	35.04	5.86	36.89	48.65	74.00	-25.35	VERTICAL peak
5	7320.000	44.60	36.07	5.98	36.95	49.70	74.00	-24.30	VERTICAL peak
6	9152.479	43.04	37.85	6.68	36.87	50.70	74.00	-23.30	VERTICAL peak




Test Mode: 00; Polarity: Horizontal; Modulation: GFSK; Channel: middle



	Freq	ReadAntenna	Cable Preamp		Limit	Over		
	MHz	Level	Factor	Loss Factor	Level	Line	Limit	Pol/Phase
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	1245.663	53.63	23.65	2.51	37.63	42.16	74.00	-31.84 HORIZONTAL
2	4456.315	44.38	34.00	4.61	36.63	46.36	74.00	-27.64 HORIZONTAL
3	4880.000	44.24	34.15	4.85	36.67	46.57	74.00	-27.43 HORIZONTAL
4	6954.852	43.76	35.04	5.86	36.89	47.77	74.00	-26.23 HORIZONTAL
5	7320.000	43.77	36.07	5.98	36.95	48.87	74.00	-25.13 HORIZONTAL
6	9099.724	44.25	37.75	6.64	36.88	51.76	74.00	-22.24 HORIZONTAL




Test Mode: 00; Polarity: Vertical; Modulation: GFSK; Channel: High



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1464.522	57.37	24.38	2.69	37.53	46.91	74.00	-27.09	VERTICAL peak
2	3280.326	52.82	28.91	3.99	36.79	48.93	74.00	-25.07	VERTICAL peak
3	4960.000	49.04	34.15	4.89	36.69	51.39	74.00	-22.61	VERTICAL peak
4	6835.278	44.96	34.79	5.81	36.87	48.69	74.00	-25.31	VERTICAL peak
5	7440.000	44.36	36.33	6.02	36.96	49.75	74.00	-24.25	VERTICAL peak
6	9047.272	45.77	37.67	6.60	36.89	53.15	74.00	-20.85	VERTICAL peak



Test Mode: 00; Polarity: Horizontal; Modulation:GFSK; Channel:High



	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1103.264	60.11	22.69	2.28	37.67	47.41	74.00	-26.59	HORIZONTAL peak
2	3261.418	54.50	28.89	3.98	36.79	50.58	74.00	-23.42	HORIZONTAL peak
3	4960.000	49.45	34.15	4.89	36.69	51.80	74.00	-22.20	HORIZONTAL peak
4	5813.812	48.79	32.67	5.35	36.79	50.02	74.00	-23.98	HORIZONTAL peak
5	7440.000	44.66	36.33	6.02	36.96	50.05	74.00	-23.95	HORIZONTAL peak
6	9152.479	45.48	37.85	6.68	36.87	53.14	74.00	-20.86	HORIZONTAL peak



7.5 Maximum Conducted Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2013) Section 11.9.2

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 22.3 °C

Humidity: 75.0 % RH


Atmospheric Pressure: 1005 mbar

7.5.2 Test Mode Description

Pre-scan / Mode	Description
Final test Code	
Final test 00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test 01	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test 02	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.



7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details

7.6 Minimum 6dB Bandwidth

Test Requirement	47 CFR Part 15, Subpart C 15.247a(2)
Test Method:	ANSI C63.10 (2013) Section 11.8.1
Limit:	≥500 kHz

7.6.1 E.U.T. Operation


Operating Environment:

Temperature: 22.3 °C Humidity: 75.0 % RH Atmospheric Pressure: 1005 mbar

7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	01	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	02	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch, EMC Laboratory

No.198, Kazhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

7.7 Power Spectrum Density

Test Requirement	47 CFR Part 15, Subpart C 15.247(e)
Test Method:	ANSI C63.10 (2013) Section 11.10.2
Limit:	≤8dBm in any 3 kHz band during any time interval of continuous transmission

7.7.1 E.U.T. Operation


Operating Environment:

Temperature: 22.3 °C Humidity: 75.0 % RH Atmospheric Pressure: 1005 mbar

7.7.2 Test Mode Description

Pre-scan / Mode	Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	01	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	02	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.

7.7.3 Test Setup Diagram



7.7.4 Measurement Procedure and Data

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch
Inspection & Testing Services

No.198, Kazhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

7.8 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.13.3.2

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.8.1 E.U.T. Operation

Operating Environment:


Temperature: 22.3 °C Humidity: 75.0 % RH Atmospheric Pressure: 1005 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	01	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	02	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.



7.8.3 Test Setup Diagram



7.8.4 Measurement Procedure and Data

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch, EMC Laboratory

No.198, Kazhu Road, Science City, Economic & Technological Development Area, Guangzhou, Guangdong, China 510663
中国·广东·广州高新技术产业开发区科学城科珠路198号 邮编: 510663

t (86-20) 82155555 www.sgsgroup.com.cn
t (86-20) 82155555 sgs.china@sgs.com

7.9 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.9.1 E.U.T. Operation

Operating Environment:

Temperature: 22.3 °C

Humidity: 75.0 % RH


Atmospheric Pressure: 1005 mbar

7.9.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	00	TX mode(1Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	01	TX mode(2Mbps)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	02	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40), final test modes are considering the modulation and worse data rates. Only the data of worst case is recorded in the report.



7.9.3 Test Setup Diagram



7.9.4 Measurement Procedure and Data

Please Refer to Appendix for Details

8 Test Setup Photo

Refer to Setup Photos for GZCR240900104601



9 EUT Constructional Details (EUT Photos)

Refer to External and Internal Photos for GZCR2409001046DS

