



東莞市新盛電子有限公司

Dongguan City Xinsheng Electronics Co.,Ltd

客户名称 Customer: gongjin

客户料号 Customer Material number: 8000000034591341

物料名称 Material name: Internal antenna

物料型号 Material type: 400621-22627-01

物料描述 Material description: Internal Antenna, 3.0dBI@5.15GHz, 50Ω, FR4, 17.5*9.8*0.8mm, L=55mm, RF113, White, IPEX, EmP242-B-155(W) (Xinsheng),

T&W-researched

版 本 Edition: V1

供 应 商 承 认 The supplier acknowledge	
工 程 Engineering	批 准 Approval
袁裕深	叶晔
盖章签署 Signed	
日 期 Date	2021-4-19

供应商名称 Supplier name: 东莞市新盛电子有限公司

Dongguan City Xinsheng Electronics Co.,Ltd

供应商地址 Supplier Address: 东莞市大岭山镇大塘朗管理区六村

6Village, Datanglang District, Dalingshan, Dongguan, Guangdong, PRC

电 话 Telephone: 886-769-85639708 85639728

传 真 Fax: 886-769-85652960

网 址 Website: <http://www.hsinsec.com>

电子邮箱 E-mail: zll@hsinsec.com

[illegible]




Specification

1. Antenna Electrical Properties:

1.1	Frequency	5.15-5.85GHz
1.2	Impedance	50 ohm Nominal
1.3	VSWR	1.92:1 Max
1.4	Return Loss	-10 dB Max.
1.5	Polarization	Line
1.6	Gain	3.16dBi







2. Physical Properties:

2.1	Operating Temperature	-30~+60℃
2.2	Storage Temperature	-30~+70℃
2.3	Humidity	≤95℃ @ 25℃
2.4	Cable Length	55mm
2.5	Cable	1.13 Coaxial Cable
2.6	Connector	IPEX



CUSTOMER DRAWING

HSF



CH-1	1. 34-1. 40	Unit: mm
CH-2	1. 02-1. 10	
CH-3	1. 10-1. 25	

TOLERANCES UNLESS OTHERWISE SPECIFIED			
X.	/	.XXX	/
.X	±0.25	X.°	±1°
.XX	±0.15	.X°	±0.5°

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF KUNSHAN COCENTRA ELECTRONICS Co.LTD. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF KUNSHAN COCENTRA ELECTRONICS Co.LTD.

Notes:

- 1: Material and finish (Plating)
 △ Housing: PBT (Black) UL94V-0.
 △ Shell: Phosphor bronze: Au over Ni
 △ Contact: Phosphor bronze: Au over Ni
- 2: Impedance: 50 OHM Nominal
- 3: Frequency Rating: DC TO 6 GHZ
- 4: VSWR: DC -- 3GHz 1.3max.
 3 GHz -- 6GHz 1.5max.
- 5: Cable retention force 10N min.
- 6: The harmful material of this part should be compliance with CCT document QW-QA-10.

PRODUCT NUMBER ORDER

ANC 0 1 13 L - 1 2 1
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Production Code :
 ANC: ANTENNA PLUG for cable
- ② Height after mated broad end :
 0 : SPEC.
- ③ Miltch Cable Ø :
 113: Cable Ø 1.13mm
- ④ Shell Gold Plating Thickness :
 L: Plating Gold 0.5 u" min.
- ⑤ Product design generation:
 1: First generation.
- ⑥ Customer identification code:
 2: Another CUS
- ⑦ Color of Housing:
 1: Black


SERIES: ANTENNA CABLE END SERIES		TITLE: AN Plug for OD 1.13mm	
APPD:		PART No.: 2212-0215004-01	
CKD:		DWG No.:	
DR:			
UNITS MM	MAT'L NA	FINISH NA	SCALE 1:1
		SHEET 1/1	REV. DX1



5Test Results

Antenna


1 Test Setup






東莞市新盛電子有限公司
Dongguan City Xinsheng Electronics Co.,Ltd

Configuration and Coordinate





2. Antenna S-parameter test results






東莞市新盛電子有限公司


Dongguan City Xinsheng Electronics Co.,Ltd

3. 2D Radiation patterns test results (Passive Antenna)


H Theta=90 freq=5150MHz




V Phi=90 freq=5150MHz




H Theta=90 freq=5550MHz




V Phi=90 freq=5550MHz



H Theta=90 freq=5850MHz




V Phi=90 freq=5850MHz






4. 3D Radiation patterns test results (Passive Antenna)


5150MHZ



5550MHZ



5850MHZ





5.Test Value

gain @efficiency 增益和效率		
frequency 频率(Hz)	gain 增益(dBi)	efficiency 效率
5150M	2.91	72%
5350M	3.11	74%
5550M	3.14	72%
5750M	3.16	73%
5850M	3.05	73%