Frequency: 2480 MHz; Duty Cycle: 1:1.29033; Room Ambient Temperature: 24.0°C; Liquid Temperature: 23.0°C Medium parameters used: f = 2480 MHz; σ = 2.111 S/m; ϵ_r = 54.068; ρ = 1000 kg/m³ DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg
- Electronics: DAE4 Sn1258; Calibrated: 5/22/2018
- Probe: EX3DV4 SN7501; ConvF(7.83, 7.83, 7.83); Calibrated: 5/4/2018, ConvF(7.83, 7.83, 7.83); Calibrated: 5/4/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Phantom: ELI v5.0 B; Type: QDOVA002AA; Serial: 1248

Rear/GFSK DH5_ch 78/Area Scan (9x9x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.230 W/kg

Rear/GFSK DH5_ch 78/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.212 V/m; Power Drift = 0.08 dB Peak SAR (extrapolated) = 0.349 W/kg SAR(1 g) = 0.153 W/kg; SAR(10 g) = 0.071 W/kg Maximum value of SAR (measured) = 0.257 W/kg



0 dB = 0.257 W/kg = -5.90 dBW/kg

Frequency: 2480 MHz; Duty Cycle: 1:1.29033; Room Ambient Temperature: 24.0°C; Liquid Temperature: 23.0°C Medium parameters used: f = 2480 MHz; σ = 2.111 S/m; ϵ_r = 54.068; ρ = 1000 kg/m³ DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg
- Electronics: DAE4 Sn1258; Calibrated: 5/22/2018
- Probe: EX3DV4 SN7501; ConvF(7.83, 7.83, 7.83); Calibrated: 5/4/2018, ConvF(7.83, 7.83, 7.83); Calibrated: 5/4/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Phantom: ELI v5.0 B; Type: QDOVA002AA; Serial: 1248

Front/GFSK DH5_ch 78/Area Scan (9x9x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.552 W/kg

Front/GFSK DH5_ch 78/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 14.87 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 1.50 W/kg

SAR(1 g) = 0.459 W/kg; SAR(10 g) = 0.198 W/kg

Maximum value of SAR (measured) = 1.09 W/kg



0 dB = 1.09 W/kg = 0.37 dBW/kg

Frequency: 2480 MHz; Duty Cycle: 1:1.29033; Room Ambient Temperature: 24.0°C; Liquid Temperature: 23.0°C Medium parameters used: f = 2480 MHz; σ = 2.111 S/m; ϵ_r = 54.068; ρ = 1000 kg/m³ DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg

- Electronics: DAE4 Sn1258; Calibrated: 5/22/2018

- Probe: EX3DV4 SN7501; ConvF(7.83, 7.83, 7.83); Calibrated: 5/4/2018, ConvF(7.83, 7.83, 7.83); Calibrated: 5/4/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm

(Mechanical Surface Detection)

- Phantom: ELI v5.0 B; Type: QDOVA002AA; Serial: 1248

Rear/GFSK DH5_ch 78 w/ Diaper/Area Scan (9x9x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.0536 W/kg

Rear/GFSK DH5_ch 78 w/ Diaper/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm,

dz=5mm

Reference Value = 4.837 V/m; Power Drift = -0.19 dB Peak SAR (extrapolated) = 0.0970 W/kg

SAR(1 g) = 0.038 W/kg; SAR(10 g) = 0.015 W/kg

Maximum value of SAR (measured) = 0.0592 W/kg



0 dB = 0.0592 W/kg = -12.28 dBW/kg

Frequency: 2480 MHz; Duty Cycle: 1:1.29033; Room Ambient Temperature: 24.0°C; Liquid Temperature: 23.0°C Medium parameters used: f = 2480 MHz; σ = 2.111 S/m; ϵ_r = 54.068; ρ = 1000 kg/m³ DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg
- Electronics: DAE4 Sn1258: Calibrated: 5/22/2018
- Probe: EX3DV4 SN7501; ConvF(7.83, 7.83, 7.83); Calibrated: 5/4/2018, ConvF(7.83, 7.83, 7.83); Calibrated: 5/4/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Phantom: ELI v5.0 B; Type: QDOVA002AA; Serial: 1248

Front/GFSK DH5 ch 78 w/ Diaper/Area Scan (9x9x1): Measurement grid: dx=12mm, dy=12mm

Maximum value of SAR (measured) = 0.684 W/kg

Front/GFSK DH5_ch 78 w/ Diaper/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm,

dy=5mm, dz=5mm Reference Value = 15.82 V/m; Power Drift = 0.07 dB Peak SAR (extrapolated) = 1.30 W/kg SAR(1 g) = 0.362 W/kg; SAR(10 g) = 0.153 W/kg Maximum value of SAR (measured) = 0.934 W/kg



Frequency: 2480 MHz; Duty Cycle: 1:1.29033; Room Ambient Temperature: 24.0°C; Liquid Temperature: 23.0°C Medium parameters used: f = 2480 MHz; σ = 2.111 S/m; ϵ_r = 54.068; ρ = 1000 kg/m³ DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg
- Electronics: DAE4 Sn1258; Calibrated: 5/22/2018
- Probe: EX3DV4 SN7501; ConvF(7.83, 7.83, 7.83); Calibrated: 5/4/2018, ConvF(7.83, 7.83, 7.83); Calibrated: 5/4/2018;
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Phantom: ELI v5.0 B; Type: QDOVA002AA; Serial: 1248

Rear/GFSK DH5_ch 78 w/ Wet Diaper/Area Scan (9x9x1): Measurement grid: dx=12mm, dy=12mm Maximum value of SAR (measured) = 0.0172 W/kg

Rear/GFSK DH5_ch 78 w/ Wet Diaper/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.259 V/m; Power Drift = -0.81 dB Peak SAR (extrapolated) = 0.0320 W/kg SAR(1 g) = 0.00816 W/kg; SAR(10 g) = 0.00304 W/kg Maximum value of SAR (measured) = 0.0185 W/kg



0 dB = 0.0185 W/kg = -17.33 dBW/kg

Frequency: 2480 MHz; Duty Cycle: 1:1.29033; Room Ambient Temperature: 24.0°C; Liquid Temperature: 23.0°C Medium parameters used: f = 2480 MHz; σ = 2.111 S/m; ϵ_r = 54.068; ρ = 1000 kg/m³ DASY5 Configuration:

- Area Scan Setting: Find Secondary Maximum Within: 2.0 dB and with a peak SAR value greater than 0.0012W/kg

- Electronics: DAE4 Sn1258; Calibrated: 5/22/2018

- Probe: EX3DV4 - SN7501; ConvF(7.83, 7.83, 7.83); Calibrated: 5/4/2018, ConvF(7.83, 7.83, 7.83); Calibrated: 5/4/2018;

- Sensor-Surface: 1.4mm (Mechanical Surface Detection (Locations From Previous Scan Used)), Sensor-Surface: 1.4mm

(Mechanical Surface Detection)

- Phantom: ELI v5.0 B; Type: QDOVA002AA; Serial: 1248

Front/GFSK DH5_ch 78 w/ Wet Diaper/Area Scan (9x9x1): Measurement grid: dx=12mm, dy=12mm Maximum value of SAR (measured) = 0.364 W/kg

Front/GFSK DH5_ch 78 w/ Wet Diaper/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm,

dy=5mm, dz=5mm Reference Value = 11.93 V/m; Power Drift = -0.09 dB Peak SAR (extrapolated) = 1.01 W/kg SAR(1 g) = 0.316 W/kg; SAR(10 g) = 0.126 W/kg

Maximum value of SAR (measured) = 0.658 W/kg



0 dB = 0.658 W/kg = -1.82 dBW/kg