



# FCC RF Test Report

APPLICANT : Locus Solutions,LLC  
EQUIPMENT : GO Tracker 1.6  
BRAND NAME : Emerson  
MODEL NAME : GO Tracker 1.6  
FCC ID : AMH101013  
STANDARD : 47 CFR Part 2, and 90(S)  
CLASSIFICATION : PCS Licensed Transmitter (PCB)

The product was received on Nov. 24, 2020 and completely tested on Apr. 13, 2021. We, Sporton International (ShenZhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

This product installed a RF module (Brand Name: Quectel, Model Name: BG96, FCC ID: XMR201707BG96) during the test, only Conducted Power and RSE test items are tested in this report, all the other test results are quoted on module RF report.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (ShenZhen) Inc., the test report shall not be reproduced except in full.

Reviewed by: Derreck Chen / Supervisor

Approved by: Eric Shih / Manager



**Sporton International (ShenZhen) Inc.**

**1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055  
People's Republic of China**



## TABLE OF CONTENTS

|                                                              |           |
|--------------------------------------------------------------|-----------|
| REVISION HISTORY.....                                        | 3         |
| SUMMARY OF TEST RESULT .....                                 | 4         |
| <b>1 GENERAL DESCRIPTION .....</b>                           | <b>5</b>  |
| 1.1 Applicant.....                                           | 5         |
| 1.2 Manufacturer .....                                       | 5         |
| 1.3 Feature of Equipment Under Test.....                     | 5         |
| 1.4 Product Specification of Equipment Under Test .....      | 5         |
| 1.5 Modification of EUT .....                                | 6         |
| 1.6 Maximum Conducted Power .....                            | 6         |
| 1.7 Testing Site.....                                        | 7         |
| 1.8 Test Software .....                                      | 8         |
| 1.9 Applied Standards .....                                  | 8         |
| <b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>    | <b>9</b>  |
| 2.1 Test Mode.....                                           | 9         |
| 2.2 Connection Diagram of Test System .....                  | 10        |
| 2.3 Support Unit used in test configuration and system ..... | 10        |
| 2.4 Frequency List of Low/Middle/High Channels .....         | 11        |
| <b>3 TEST RESULT .....</b>                                   | <b>12</b> |
| 3.1 Conducted Output Power Measurement.....                  | 12        |
| 3.2 Field Strength of Spurious Radiation Measurement .....   | 13        |
| <b>4 LIST OF MEASURING EQUIPMENT .....</b>                   | <b>15</b> |
| <b>5 UNCERTAINTY OF EVALUATION .....</b>                     | <b>16</b> |
| <b>APPENDIX A. TEST RESULTS OF CONDUCTED TEST</b>            |           |
| <b>APPENDIX B. TEST RESULTS OF RADIATED TEST</b>             |           |



## REVISION HISTORY

| REPORT NO. | VERSION | DESCRIPTION             | ISSUED DATE   |
|------------|---------|-------------------------|---------------|
| FW0N2403   | Rev. 01 | Initial issue of report | Apr. 27, 2021 |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |

## SUMMARY OF TEST RESULT

| Report Section | FCC Rule           | Description                                      | Limit                               | Result | Remark                                     |
|----------------|--------------------|--------------------------------------------------|-------------------------------------|--------|--------------------------------------------|
| 3.1            | §2.1046            | Conducted Output Power                           | Reporting only                      | PASS   | -                                          |
| -              | §2.1049<br>§90.209 | Occupied Bandwidth and<br>26dB Bandwidth         | Reporting only                      | PASS   | 1                                          |
| -              | §2.1051<br>§90.691 | Emission masks –<br>In-band emissions            | $< 50+10\log_{10}(P[\text{Watts}])$ | PASS   | 1                                          |
| -              | §2.1051<br>§90.691 | Emission masks –<br>Out of band emissions        | $< 43+10\log_{10}(P[\text{Watts}])$ | PASS   | 1                                          |
| 3.2            | §2.1053<br>§90.691 | Field Strength of Spurious<br>Radiation          | $< 43+10\log_{10}(P[\text{Watts}])$ | PASS   | Under limit<br>24.32 dB at<br>1633.500 MHz |
| -              | §2.1055<br>§90.213 | Frequency Stability for<br>Temperature & Voltage | $< 2.5 \text{ ppm}$                 | PASS   | 1                                          |

**Remark :**

1. All conducted test items except for power were leveraged from module RF reports which can refer to Report No. R2003A0151-R7 for LTE Cat M1 and RXA1706-0199RF08 for NB-IOT Cat-NB1.

**Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



# 1 General Description

## 1.1 Applicant

Locus Solutions,LLC

7121 Fairway Dr. Suite #400 | Palm Beach Gardens, FL 33418 USA

## 1.2 Manufacturer

Shenzhen Zhenhua Communication Equipment Co.Ltd

Zhenhua Industrial Park, No.44, Tiezai Rd., Xixiang Town,BaoAn, Shenzhen, Guang Dong, China

## 1.3 Feature of Equipment Under Test

| Product Feature                 |                                         |
|---------------------------------|-----------------------------------------|
| Equipment                       | GO Tracker 1.6                          |
| Brand Name                      | Emerson                                 |
| Model Name                      | GO Tracker 1.6                          |
| FCC ID                          | AMH101013                               |
| EUT supports Radios application | GSM/LTE Category M1/NB-IOT Category NB1 |
| IMEI Code                       | Radiated: 867035049240144               |
| HW Version                      | 0                                       |
| SW Version                      | 6.4.A01                                 |
| EUT Stage                       | Production Unit                         |

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4 Product Specification of Equipment Under Test

| Product Specification subjective to this standard |                                                                                    |
|---------------------------------------------------|------------------------------------------------------------------------------------|
| Tx Frequency                                      | LTE Category M1: 814.7 ~ 823.3 MHz<br>NB-IOT Category NB1 : 814.1 MHz ~ 823.9 MHz  |
| Rx Frequency                                      | LTE Category M1: 859.7 ~ 868.3 MHz<br>NB-IOT Category NB1 : 859.1 MHz ~ 868.9 MHz  |
| Bandwidth                                         | LTE Category M1:1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz<br>NB-IOT Category NB1:200KHz |
| Sub-carrier Spacing                               | NB-IoT: 3.75kHz / 15kHz                                                            |
| Maximum Output Power to Antenna                   | LTE Cat M1: 22.93 dBm<br>NB-IoT: 23.18 dBm                                         |
| Antenna Gain                                      | -5.51 dBi                                                                          |
| Type of Modulation                                | LTE Cat M1: QPSK / 16QAM<br>NB-IoT: BPSK / QPSK                                    |

## 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.6 Maximum Conducted Power

| LTE Band 26-Cat M1        |                       | QPSK                        | 16QAM                       |
|---------------------------|-----------------------|-----------------------------|-----------------------------|
| BW (MHz)                  | Frequency Range (MHz) | Maximum Conducted power (W) | Maximum Conducted power (W) |
| 1.4                       | 814.7 ~ 823.3         | 0.1910                      | 0.1828                      |
| 3                         | 815.5 ~ 822.5         | 0.1820                      | 0.1778                      |
| 5                         | 816.5 ~ 821.5         | 0.1963                      | 0.1807                      |
| 10                        | 819.0                 | 0.1820                      | 0.1702                      |
| 15                        | 821.5                 | 0.1928                      | 0.1845                      |
| LTE Band 26-NB-IoT        |                       | BPSK                        | QPSK                        |
| Sub-Carrier Spacing (kHz) | Frequency Range (MHz) | Maximum Conducted power (W) | Maximum Conducted power (W) |
| 3.75                      | 814.1 ~ 823.9         | 0.1795                      | 0.1742                      |
| 15                        | 814.1 ~ 823.9         | 0.2075                      | 0.2080                      |



## 1.7 Testing Site

Sporton International (Shenzhen) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

|                           |                                                                                                                                                                         |                            |                                       |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|---------------------------------------|
| <b>Test Firm</b>          | Sporton International (Shenzhen) Inc.                                                                                                                                   |                            |                                       |
| <b>Test Site Location</b> | 1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China<br>TEL: +86-755-86379589<br>FAX: +86-755-86379595 |                            |                                       |
| <b>Test Site No.</b>      | <b>Sporton Site No.</b>                                                                                                                                                 | <b>FCC Designation No.</b> | <b>FCC Test Firm Registration No.</b> |
|                           | TH01-SZ                                                                                                                                                                 | CN1256                     | 421272                                |

|                           |                                                                                                                                                                                           |                            |                                       |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|---------------------------------------|
| <b>Test Firm</b>          | Sporton International (Shenzhen) Inc.                                                                                                                                                     |                            |                                       |
| <b>Test Site Location</b> | 101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City Guangdong Province China 518103<br>TEL: +86-755-33202398 |                            |                                       |
| <b>Test Site No.</b>      | <b>Sporton Site No.</b>                                                                                                                                                                   | <b>FCC Designation No.</b> | <b>FCC Test Firm Registration No.</b> |
|                           | 03CH03-SZ                                                                                                                                                                                 | CN1256                     | 421272                                |



## 1.8 Test Software

| Item | Site      | Manufacturer | Name | Version     |
|------|-----------|--------------|------|-------------|
| 1.   | 03CH03-SZ | AUDIX        | E3   | 6.2009-8-24 |

## 1.9 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 90(S)
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 971168 D02 Misc Rev Approv License Devices v02r01

### Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is 30 MHz to 9000 MHz.


#### For LTE Cat M1:

| Test Items                 | Band                                                                                                                                                                                                                                                                                                                                                                                                      | Bandwidth (MHz) |   |   |    |    |    | Modulation |       | RB # |      |      | Test Channel |   |   |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|---|---|----|----|----|------------|-------|------|------|------|--------------|---|---|
|                            |                                                                                                                                                                                                                                                                                                                                                                                                           | 1.4             | 3 | 5 | 10 | 15 | 20 | QPSK       | 16QAM | 1    | Half | Full | L            | M | H |
| Max. Output Power          | 26                                                                                                                                                                                                                                                                                                                                                                                                        | v               | v | v | v  | v  | -  | v          | v     | v    | -    | v    | v            | v | v |
| Radiated Spurious Emission | 26                                                                                                                                                                                                                                                                                                                                                                                                        | v               | v | v | v  | v  | -  | v          |       | v    |      |      | v            | v | v |
| Note                       | 1. The mark "v" means that this configuration is chosen for testing<br>2. The mark "-" means that this bandwidth is not supported.<br>3. LTE Band26 transmit frequency for part22 rule is 824MHz-849MHz, for part90 rule is 814MHz-824MHz. ERP over 15MHz bandwidth complies the ERP limit line of part22 rule, therefore ERP of the partial frequency spectrum which falls within part 22 also complies. |                 |   |   |    |    |    |            |       |      |      |      |              |   |   |

#### For NB-IoT:

| Test Items                 | Band | Sub-carrier Spacing (kHz) |    | Modulation |      | Tones # |   |    | Test Channel |   |   |
|----------------------------|------|---------------------------|----|------------|------|---------|---|----|--------------|---|---|
|                            |      | 3.75                      | 15 | BPSK       | QPSK | 1       | - | 12 | L            | M | H |
| Max. Output Power          | 26   | v                         | v  | v          | v    | v       | - | v  | v            | v | v |
| Radiated Spurious Emission | 26   |                           | v  |            | v    | v       |   |    | v            | v | v |

## 2.2 Connection Diagram of Test System



## 2.3 Support Unit used in test configuration and system

| Item | Equipment        | Trade Name | Model No. | FCC ID | Data Cable | Power Cord        |
|------|------------------|------------|-----------|--------|------------|-------------------|
| 1.   | System Simulator | Anritsu    | MT8820C   | N/A    | N/A        | Unshielded, 1.8 m |

## 2.4 Frequency List of Low/Middle/High Channels

| LTE Band 26 Cat M1 Channel and Frequency List |                        |        |        |         |
|-----------------------------------------------|------------------------|--------|--------|---------|
| BW [MHz]                                      | Channel/Frequency(MHz) | Lowest | Middle | Highest |
| 15                                            | Channel                | 26765  | -      | -       |
|                                               | Frequency              | 821.5  | -      | -       |
| 10                                            | Channel                | -      | 26740  | -       |
|                                               | Frequency              | -      | 819    | -       |
| 5                                             | Channel                | 26715  | 26740  | 26765   |
|                                               | Frequency              | 816.5  | 819    | 821.5   |
| 3                                             | Channel                | 26705  | 26740  | 26775   |
|                                               | Frequency              | 815.5  | 819    | 822.5   |
| 1.4                                           | Channel                | 26697  | 26740  | 26783   |
|                                               | Frequency              | 814.7  | 819    | 823.3   |

| LTE Band 26 NB IoT Channel and Frequency List |                        |        |        |         |
|-----------------------------------------------|------------------------|--------|--------|---------|
| Sub-carrier Spacing (kHz)                     | Channel/Frequency(MHz) | Lowest | Middle | Highest |
| 15                                            | Channel                | 26691  | 26740  | 26789   |
|                                               | Frequency              | 814.1  | 819    | 823.9   |
| 3.75                                          | Channel                | 26691  | 26740  | 26789   |
|                                               | Frequency              | 814.1  | 819    | 823.9   |

### 3 Test Result

#### 3.1 Conducted Output Power Measurement

##### 3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.

##### 3.1.4 Test Setup



##### 3.1.5 Test Result of Conducted Output Power

Please refer to Appendix A.

## 3.2 Field Strength of Spurious Radiation Measurement

### 3.2.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI/TIA-603-E. The power of any emission FCC Part 90.691 on any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth at least  $43 + 10 \log (P)$  dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log_{10}(P[\text{Watts}])$  dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

### 3.2.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

### 3.2.3 Test Procedures


1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10.  $\text{EIRP (dBm)} = \text{S.G. Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$
11.  $\text{ERP (dBm)} = \text{EIRP} - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
13. The limit line is derived from  $43 + 10 \log(P)$  dB below the transmitter power P(Watts)

### 3.2.4 Test Setup

For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



### 3.2.5 Test Result of Field Strength of Spurious Radiated

Please refer to Appendix B.



## 4 List of Measuring Equipment

| Instrument                | Manufacturer         | Model No. | Serial No.   | Characteristics | Calibration Date | Test Date     | Due Date      | Remark                |
|---------------------------|----------------------|-----------|--------------|-----------------|------------------|---------------|---------------|-----------------------|
| Spectrum Analyzer         | R&S                  | FSV40     | 101078       | 10Hz~40GHz      | Apr. 08, 2021    | Apr. 13, 2021 | Apr. 07, 2022 | Conducted (TH01-SZ)   |
| EMI Test Receiver&SA      | KEYSIGHT             | N9038A    | MY54450083   | 20Hz~8.4GHz     | Apr. 10, 2020    | Mar. 12, 2021 | Apr. 09, 2021 | Radiation (03CH03-SZ) |
| EXA Spectrum Analyzer     | KEYSIGHT             | N9010A    | MY55150246   | 10Hz~44GHz;     | Apr. 10, 2020    | Mar. 12, 2021 | Apr. 09, 2021 | Radiation (03CH03-SZ) |
| Bilog Antenna             | TeseQ                | CBL6112D  | 35408        | 30MHz~2GHz      | Jun. 22, 2020    | Mar. 12, 2021 | Jun. 21, 2022 | Radiation (03CH03-SZ) |
| Double Ridge Horn Antenna | SCHWARZBECK          | BBHA9120D | 9120D-1355   | 1GHz~18GHz      | Apr. 30, 2020    | Mar. 12, 2021 | Apr. 29, 2021 | Radiation (03CH03-SZ) |
| Amplifier                 | Burgeon              | BPA-530   | 102210       | 0.01Hz~3000MHz  | Oct. 17, 2019    | Mar. 12, 2021 | Oct. 16, 2021 | Radiation (03CH03-SZ) |
| Amplifier                 | Agilent Technologies | 83017A    | MY39501302   | 500MHz~26.5GHz  | Dec. 25, 2020    | Mar. 12, 2021 | Dec. 24, 2021 | Radiation (03CH03-SZ) |
| AC Power Source           | Chroma               | 61601     | 616010001985 | N/A             | NCR              | Mar. 12, 2021 | NCR           | Radiation (03CH03-SZ) |
| Turn Table                | EM                   | EM1000    | N/A          | 0~360 degree    | NCR              | Mar. 12, 2021 | NCR           | Radiation (03CH03-SZ) |
| Antenna Mast              | EM                   | EM1000    | N/A          | 1 m~4 m         | NCR              | Mar. 12, 2021 | NCR           | Radiation (03CH03-SZ) |

NCR: No Calibration Required



## 5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage  $K=2$  to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

|                                                                         |       |
|-------------------------------------------------------------------------|-------|
| Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ ) | 3.0dB |
|-------------------------------------------------------------------------|-------|

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

|                                                                         |       |
|-------------------------------------------------------------------------|-------|
| Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ ) | 3.6dB |
|-------------------------------------------------------------------------|-------|



## Appendix A. Test Results of Conducted Test

### Conducted Output Power (Average power)

#### LTE Band 26 – Cat M1:

| BW<br>[MHz]     | Modulation | RB<br>Size | RB<br>Offset | Index |   |    | Power<br>Low<br>Ch. / Freq. | Power<br>Middle<br>Ch. / Freq. | Power<br>High<br>Ch. / Freq. |
|-----------------|------------|------------|--------------|-------|---|----|-----------------------------|--------------------------------|------------------------------|
| Channel         |            |            |              | L     | M | H  | 26765                       |                                |                              |
| Frequency (MHz) |            |            |              |       |   |    | 821.5                       |                                |                              |
| 15              | QPSK       | 1          | 0            | 0     | 0 | 11 | 22.82                       |                                |                              |
| 15              | QPSK       | 1          | 5            | 0     | 0 | 11 | 22.79                       |                                |                              |
| 15              | QPSK       | 6          | 0            | 0     | 0 | 11 | 22.85                       |                                |                              |
| 15              | 16QAM      | 1          | 0            | 0     | 0 | 11 | 22.23                       |                                |                              |
| 15              | 16QAM      | 1          | 5            | 0     | 0 | 11 | 22.20                       |                                |                              |
| 15              | 16QAM      | 6          | 0            | 0     | 0 | 11 | 22.66                       |                                |                              |
| Channel         |            |            |              | L     | M | H  |                             | 26740                          |                              |
| Frequency (MHz) |            |            |              |       |   |    |                             | 819                            |                              |
| 10              | QPSK       | 1          | 0            | 0     | 0 | 7  |                             | 22.60                          |                              |
| 10              | QPSK       | 1          | 5            | 0     | 0 | 7  |                             | 22.53                          |                              |
| 10              | QPSK       | 6          | 0            | 0     | 0 | 7  |                             | 22.56                          |                              |
| 10              | 16QAM      | 1          | 0            | 0     | 0 | 7  |                             | 21.42                          |                              |
| 10              | 16QAM      | 1          | 5            | 0     | 0 | 7  |                             | 21.43                          |                              |
| 10              | 16QAM      | 6          | 0            | 0     | 0 | 7  |                             | 22.31                          |                              |
| Channel         |            |            |              | L     | M | H  | 26715                       | 26740                          | 26765                        |
| Frequency (MHz) |            |            |              |       |   |    | 816.5                       | 819                            | 821.5                        |
| 5               | QPSK       | 1          | 0            | 0     | 0 | 3  | 22.86                       | 22.62                          | 22.52                        |
| 5               | QPSK       | 1          | 5            | 0     | 0 | 3  | 22.85                       | 22.61                          | 22.53                        |
| 5               | QPSK       | 6          | 0            | 0     | 0 | 3  | 22.93                       | 22.58                          | 22.61                        |
| 5               | 16QAM      | 1          | 0            | 0     | 0 | 3  | 22.07                       | 21.16                          | 21.62                        |
| 5               | 16QAM      | 1          | 5            | 0     | 0 | 3  | 22.14                       | 21.23                          | 21.69                        |
| 5               | 16QAM      | 6          | 0            | 0     | 0 | 3  | 22.57                       | 22.44                          | 22.44                        |
| Channel         |            |            |              | L     | M | H  | 26705                       | 26740                          | 26775                        |
| Frequency (MHz) |            |            |              |       |   |    | 815.5                       | 819                            | 822.5                        |
| 3               | QPSK       | 1          | 0            | 0     | 0 | 1  | 22.58                       | 22.59                          | 22.29                        |
| 3               | QPSK       | 1          | 5            | 0     | 0 | 1  | 22.54                       | 22.60                          | 22.29                        |
| 3               | QPSK       | 6          | 0            | 0     | 0 | 1  | 22.48                       | 22.60                          | 22.25                        |
| 3               | 16QAM      | 1          | 0            | 0     | 0 | 1  | 22.03                       | 21.18                          | 21.64                        |
| 3               | 16QAM      | 1          | 5            | 0     | 0 | 1  | 22.06                       | 21.13                          | 21.71                        |
| 3               | 16QAM      | 6          | 0            | 0     | 0 | 1  | 22.50                       | 22.45                          | 22.28                        |
| Channel         |            |            |              | L     | M | H  | 26697                       | 26740                          | 26783                        |
| Frequency (MHz) |            |            |              |       |   |    | 814.7                       | 819                            | 823.3                        |
| 1.4             | QPSK       | 1          | 0            | 0     | 0 | 0  | 22.46                       | 22.80                          | 22.76                        |
| 1.4             | QPSK       | 1          | 5            | 0     | 0 | 0  | 22.35                       | 22.79                          | 22.68                        |
| 1.4             | QPSK       | 6          | 0            | 0     | 0 | 0  | 22.34                       | 22.51                          | 22.81                        |
| 1.4             | 16QAM      | 1          | 0            | 0     | 0 | 0  | 21.89                       | 21.16                          | 22.31                        |
| 1.4             | 16QAM      | 1          | 5            | 0     | 0 | 0  | 21.71                       | 21.23                          | 22.35                        |
| 1.4             | 16QAM      | 6          | 0            | 0     | 0 | 0  | 22.19                       | 22.62                          | 22.35                        |

**LTE Band 26 – NB IoT:**

| Sub-carrier<br>Spacing<br>(KHz) | Modulation | RB Size | RB Offset | Power<br>Low<br>Ch. / Freq. | Power<br>Middle<br>Ch. / Freq. | Power<br>High<br>Ch. / Freq. |
|---------------------------------|------------|---------|-----------|-----------------------------|--------------------------------|------------------------------|
| Channel                         |            |         |           | 26691                       | 26740                          | 26789                        |
| Frequency (MHz)                 |            |         |           | 814.1                       | 819                            | 823.9                        |
| 3.75                            | BPSK       | 1       | 0         | 22.41                       | 22.11                          | 22.11                        |
| 3.75                            | BPSK       | 1       | 47        | 22.54                       | 22.21                          | 22.08                        |
| 3.75                            | QPSK       | 1       | 0         | 22.41                       | 22.15                          | 22.08                        |
| 3.75                            | QPSK       | 1       | 47        | 22.39                       | 22.08                          | 22.04                        |
| 15                              | BPSK       | 1       | 0         | 23.10                       | 22.40                          | 22.67                        |
| 15                              | BPSK       | 1       | 11        | 23.17                       | 22.45                          | 22.69                        |
| 15                              | QPSK       | 1       | 0         | 23.15                       | 22.41                          | 22.68                        |
| 15                              | QPSK       | 1       | 11        | 23.11                       | 22.43                          | 22.72                        |
| 15                              | QPSK       | 12      | 0         | 23.18                       | 22.92                          | 23.08                        |



## Appendix B. Test Results of Radiated Test

### Radiated Spurious Emission

LTE Band 26 – Cat M1:

| LTE Band 26 / 5MHz / QPSK |                   |             |               |                   |                   |                    |                      |                       |                    |
|---------------------------|-------------------|-------------|---------------|-------------------|-------------------|--------------------|----------------------|-----------------------|--------------------|
| Channel                   | Frequency ( MHz ) | ERP ( dBm ) | Limit ( dBm ) | Over Limit ( dB ) | SPA Reading (dBm) | S.G. Power ( dBm ) | TX Cable loss ( dB ) | TX Antenna Gain (dBi) | Polarization (H/V) |
| Lowest                    | 1628.5            | -47.33      | -13           | -34.33            | -53.66            | -50.56             | 3.98                 | 9.36                  | H                  |
|                           | 2442.75           | -46.34      | -13           | -33.34            | -56.76            | -49.89             | 4.85                 | 10.55                 | H                  |
|                           | 3257              | -55.70      | -13           | -42.70            | -68.44            | -60.63             | 5.50                 | 12.58                 | H                  |
|                           | 1628.5            | -43.23      | -13           | -30.23            | -49.60            | -46.46             | 3.98                 | 9.36                  | V                  |
|                           | 2442.75           | -45.68      | -13           | -32.68            | -56.49            | -49.23             | 4.85                 | 10.55                 | V                  |
|                           | 3257              | -54.77      | -13           | -41.77            | -68.03            | -59.70             | 5.50                 | 12.58                 | V                  |
| Middle                    | 1633.5            | -48.66      | -13           | -35.66            | -54.97            | -51.91             | 4.00                 | 9.40                  | H                  |
|                           | 2450.25           | -46.95      | -13           | -33.95            | -57.35            | -50.52             | 4.88                 | 10.60                 | H                  |
|                           | 3267              | -55.62      | -13           | -42.62            | -68.28            | -60.55             | 5.52                 | 12.60                 | H                  |
|                           | 1633.5            | -37.32      | -13           | -24.32            | -43.63            | -40.57             | 4.00                 | 9.40                  | V                  |
|                           | 2450.25           | -42.29      | -13           | -29.29            | -53.07            | -45.86             | 4.88                 | 10.60                 | V                  |
|                           | 3267              | -54.36      | -13           | -41.36            | -67.52            | -59.29             | 5.52                 | 12.60                 | V                  |
| Highest                   | 1638.5            | -48.67      | -13           | -35.67            | -54.96            | -51.84             | 4.10                 | 9.42                  | H                  |
|                           | 2457.75           | -46.51      | -13           | -33.51            | -56.89            | -50.09             | 4.90                 | 10.63                 | H                  |
|                           | 3277              | -54.94      | -13           | -41.94            | -67.52            | -59.86             | 5.55                 | 12.62                 | H                  |
|                           | 1638.5            | -39.95      | -13           | -26.95            | -46.21            | -43.12             | 4.10                 | 9.42                  | V                  |
|                           | 2457.75           | -46.89      | -13           | -33.89            | -57.64            | -50.47             | 4.90                 | 10.63                 | V                  |
|                           | 3277              | -54.74      | -13           | -41.74            | -67.81            | -59.66             | 5.55                 | 12.62                 | V                  |

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

| LTE Band 26 / 10MHz / QPSK |                   |             |               |                   |                   |                    |                      |                       |                    |
|----------------------------|-------------------|-------------|---------------|-------------------|-------------------|--------------------|----------------------|-----------------------|--------------------|
| Channel                    | Frequency ( MHz ) | ERP ( dBm ) | Limit ( dBm ) | Over Limit ( dB ) | SPA Reading (dBm) | S.G. Power ( dBm ) | TX Cable loss ( dB ) | TX Antenna Gain (dBi) | Polarization (H/V) |
| Middle                     | 1629              | -42.01      | -13           | -29.01            | -48.33            | -45.26             | 4.00                 | 9.40                  | H                  |
|                            | 2443.5            | -38.43      | -13           | -25.43            | -48.85            | -42.00             | 4.88                 | 10.60                 | H                  |
|                            | 3258              | -52.11      | -13           | -39.11            | -64.84            | -57.04             | 5.52                 | 12.60                 | H                  |
|                            | 1629              | -49.06      | -13           | -36.06            | -55.42            | -52.31             | 4.00                 | 9.40                  | V                  |
|                            | 2443.5            | -50.55      | -13           | -37.55            | -61.35            | -54.12             | 4.88                 | 10.60                 | V                  |
|                            | 3258              | -54.91      | -13           | -41.91            | -68.16            | -59.84             | 5.52                 | 12.60                 | V                  |

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



| LTE Band 26 / 15MHz / QPSK |                   |             |               |                   |                   |                    |                      |                       |                    |
|----------------------------|-------------------|-------------|---------------|-------------------|-------------------|--------------------|----------------------|-----------------------|--------------------|
| Channel                    | Frequency ( MHz ) | ERP ( dBm ) | Limit ( dBm ) | Over Limit ( dB ) | SPA Reading (dBm) | S.G. Power ( dBm ) | TX Cable loss ( dB ) | TX Antenna Gain (dBi) | Polarization (H/V) |
| Lowest                     | 1629.5            | -42.90      | -13           | -29.90            | -49.22            | -46.13             | 3.98                 | 9.36                  | H                  |
|                            | 2444.25           | -40.31      | -13           | -27.31            | -50.73            | -43.86             | 4.85                 | 10.55                 | H                  |
|                            | 3259              | -51.19      | -13           | -38.19            | -63.92            | -56.12             | 5.50                 | 12.58                 | H                  |
|                            | 1629.5            | -49.40      | -13           | -36.40            | -55.75            | -52.63             | 3.98                 | 9.36                  | V                  |
|                            | 2444.25           | -49.70      | -13           | -36.70            | -60.50            | -53.25             | 4.85                 | 10.55                 | V                  |
|                            | 3259              | -55.30      | -13           | -42.30            | -68.54            | -60.23             | 5.50                 | 12.58                 | V                  |

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

#### LTE Band 26 – NB IoT:

| LTE Band 26 / 15kHz / QPSK |                   |             |               |                   |                   |                    |                      |                       |                    |
|----------------------------|-------------------|-------------|---------------|-------------------|-------------------|--------------------|----------------------|-----------------------|--------------------|
| Channel                    | Frequency ( MHz ) | ERP ( dBm ) | Limit ( dBm ) | Over Limit ( dB ) | SPA Reading (dBm) | S.G. Power ( dBm ) | TX Cable loss ( dB ) | TX Antenna Gain (dBi) | Polarization (H/V) |
| Lowest                     | 1632              | -45.09      | -13           | -32.09            | -51.40            | -48.32             | 3.98                 | 9.36                  | H                  |
|                            | 2448              | -48.49      | -13           | -35.49            | -58.89            | -52.04             | 4.85                 | 10.55                 | H                  |
|                            | 3264              | -60.38      | -13           | -47.38            | -73.06            | -65.31             | 5.50                 | 12.58                 | H                  |
|                            | 1632              | -43.88      | -13           | -30.88            | -50.21            | -47.11             | 3.98                 | 9.36                  | V                  |
|                            | 2448              | -42.86      | -13           | -29.86            | -53.65            | -46.41             | 4.85                 | 10.55                 | V                  |
|                            | 3264              | -60.66      | -13           | -47.66            | -73.85            | -65.59             | 5.50                 | 12.58                 | V                  |
| Middle                     | 1664              | -56.79      | -13           | -43.79            | -63.04            | -60.04             | 4.00                 | 9.40                  | H                  |
|                            | 2496              | -51.98      | -13           | -38.98            | -62.27            | -55.55             | 4.88                 | 10.60                 | H                  |
|                            | 3328              | -64.30      | -13           | -51.30            | -76.48            | -69.23             | 5.52                 | 12.60                 | H                  |
|                            | 1664              | -51.72      | -13           | -38.72            | -57.75            | -54.97             | 4.00                 | 9.40                  | V                  |
|                            | 2496              | -51.24      | -13           | -38.24            | -61.87            | -54.81             | 4.88                 | 10.60                 | V                  |
|                            | 3328              | -63.22      | -13           | -50.22            | -75.81            | -68.15             | 5.52                 | 12.60                 | V                  |
| Highest                    | 1696              | -54.88      | -13           | -41.88            | -61.22            | -58.05             | 4.10                 | 9.42                  | H                  |
|                            | 2544              | -56.46      | -13           | -43.46            | -66.76            | -60.04             | 4.90                 | 10.63                 | H                  |
|                            | 3392              | -63.80      | -13           | -50.80            | -75.81            | -68.72             | 5.55                 | 12.62                 | H                  |
|                            | 1696              | -52.49      | -13           | -39.49            | -58.61            | -55.66             | 4.10                 | 9.42                  | V                  |
|                            | 2544              | -56.55      | -13           | -43.55            | -67.19            | -60.13             | 4.90                 | 10.63                 | V                  |
|                            | 3392              | -63.02      | -13           | -50.02            | -75.57            | -67.94             | 5.55                 | 12.62                 | V                  |

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.