

Applicant: Otter Products, LLC.	
FCC ID: 2AEEV-OBFTC0120A	
Date: 2022-10-05	
RF Exposure Requirements (FCC KDB 680106 D01 v03r01)	
Requirements	Statements
(a) Power transfer frequency is less than 1 MHz	No, the frequency over than 1MHz.
(b) Output power from each primary coil is less than 15 watts	No, the output power from one of coils is 15 watts(max), another of coils is 5 watts(max)
(c) The system may consist of more than one source primary coils, charging one or more clients. If more than one primary coil is present, the coil pairs may be powered on at the same time.	Yes, the EUT has two primary coils, can be powered on at the same time.
(d) Client device is placed directly in contact with the transmitter.	Yes, client device is placed directly in contact with the transmitter.
(e) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).	No, portable device.
(f) The aggregate H-field strengths anywhere at or beyond 15 cm surrounding the device, and 20 cm away from the surface from all coils that by design can simultaneously transmit, and while those coils are simultaneously energized, are demonstrated to be less than 50% of the applicable MPE limit.	Yes, please refer to the RF exposure Evaluation report.

Steve Dressor

Steve Dressor, Regulatory Engineering Manager
Otter Products, LLC.
Tel: (970) 980-2092
E-mail: steve.dressor@otterproducts.com