



## WiBear11n-DF2 MPE calculation

**Model number: AN00J93176**

**FCC ID PV7-WIBEAR11N-DF2**

**IC: 7738A-WB11NDF2**

According to FCC §15.247(b)(4) and §1.1307(b)(1), systems operation under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

### MPE Prediction

<i>Frequency range (MHz)</i>	<i>Power density (mW/cm<sup>2</sup>)</i>
400 – 1500	f/2000
1500 - 100000	1 mW/cm <sup>2</sup>

Equation for calculation

$$S = P * G / (4\pi R^2)$$

Where: S – Power density  
P – Power input to antenna  
G – Antenna gain relative to isotropic radiator  
R – Distance to antenna

Maximum peak output power at antenna terminal at 2.5GHz band: +22.5 dBm (178 mW)

Maximum peak output power at antenna terminal at 5GHz band: +21.5 dBm (141 mW)

Antenna gain at 2.5GHz band: 3.0 dBi

Antenna gain at 5GHz band: 4.1 dBi

Prediction distance: 20cm

MPE limit for General Population/Uncontrolled Exposure: 1 mW/cm<sup>2</sup>

### Intermediate results:

MPE safe distance at 2.5GHz: **5.31 cm**

MPE safe distance at 5GHz: **5.38 cm**

Power density at 20cm distance at 2.5GHz: **0.0706 mW/cm<sup>2</sup>**



Power density at 20cm distance at 5GHz: **0.0722 mW/cm<sup>2</sup>**

**Final results:**

MPE safe distance: **5.38 cm**

Power density at 20cm distance: **0.0722 mW/cm<sup>2</sup>**

Best Regards

A handwritten signature in purple ink that reads 'Imad Hjije'.

Imad Hjije