



## MPE Calculations

Systems operating under the provision of 47 CFR 1.1307(b)(1) shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the FCC guidelines.

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user or nearby persons and can therefore be considered a mobile transmitter per 47 CFR 2.1091(b). The MPE calculation for this exposure is shown below.

### Using the Antennas with highest output power:

The peak radiated output power (EIRP) is calculated as follows:

<i>Antenna</i>	<i>Frequency (GHz)</i>	<i>Power input to the antenna (P) (dBm)</i>	<i>Power gain of the antenna (G) (dBi)</i>	<i>EIRP (P+G) (dBm)</i>	<i>EIRP <math>\text{Log}^{-1}(\text{dBm}/10)</math> (mW)</i>
Ethertronics (Chain A)	2.4	23.83	3.00	26.83	481.95
Ethertronics (Chain A)	5	20.91	5.00	25.91	389.94
Ethertronics (Chain B)	2.4	23.63	3.00	26.63	460.26
Ethertronics (Chain B)	5	20.61	5.00	25.61	363.92

$\text{EIRP} = P + G$

Where

P = Power input to the antenna (mW).

G = Power gain of the antenna (dBi)

The numeric gain (G) of the antenna with a gain specified in dB is determined by:

<i>Antenna</i>	<i>Frequency (GHz)</i>	<i>Antenna Gain (G) (dBi)</i>	<i>Numeric Antenna Gain <math>\text{Log}^{-1}(\text{dBm}/10)</math> (dB)</i>
Ethertronics (Chain A)	2.4	3.00	2.00
Ethertronics (Chain A)	5	5.00	3.16
Ethertronics (Chain B)	2.4	3.00	2.00
Ethertronics (Chain B)	5	5.00	3.16

$G = \text{Log}^{-1}(\text{dB antenna gain}/10)$



### Power density at the specific separation:

<i>Antenna</i>	<i>Frequency (GHz)</i>	<i>Power input to the antenna (P) (mW)</i>	<i>Numeric Power Gain of the Antenna (G) (dB)</i>	<i>Maximum Power Spectral Density <math>S=PG/(4R^2\pi)</math> (mW/cm<sup>2</sup>)</i>	<i>Maximum Power Spectral Density Limit (mW/cm<sup>2</sup>)</i>
Ethertronics (Chain A)	2.4	241.55	2.00	0.096	1.00
Ethertronics (Chain A)	5	123.31	3.16	0.078	1.00
Ethertronics (Chain B)	2.4	230.67	2.00	0.092	1.00
Ethertronics (Chain B)	5	115.08	3.16	0.072	1.00

$$S = PG/(4R^2\pi)$$

Where

S = Maximum power density (mW/cm<sup>2</sup>)

P = Power input to the antenna (mW).

G = Numeric power gain of the antenna

R = Distance to the center of the radiation of the antenna (20cm = limit for MPE)

The maximum permissible exposure (MPE) for the general population is 1mW/cm<sup>2</sup>.

The power density at 20cm does not exceed the 1mW/cm<sup>2</sup> limit. Therefore, the exposure condition is compliant with FCC rules.

### Aggregate Maximum Power Spectral Density:

<i>Antenna</i>	<i>Frequency (GHz)</i>	<i>Maximum Power Spectral Density Chain A (dBi)</i>	<i>Maximum Power Spectral Density Chain B (dBi)</i>	<i>Maximum Power Spectral Density Aggregate Chain A &amp; B (dBi)</i>	<i>Maximum Power Spectral Density Limit (mW/cm<sup>2</sup>)</i>
Ethertronics	2.4	0.096	0.092	0.094	1.00
Ethertronics	5	0.078	0.072	0.075	1.00