

FCC - TEST REPORTReport Number : **709502301742-00C** Date of Issue: June 26, 2023Model : Fotric P9, Fotric P8, Fotric P7, Fotric P6, Fotric P5, Fotric P4Product Type : Infrared Thermal CameraApplicant : FOTRIC INC.Address : No. 14, Lane 2500, Xiupu Road, Pudong, 201201 Shanghai,
PEOPLE'S REPUBLIC OF CHINAManufacturer : FOTRIC INC.Address : No. 14, Lane 2500, Xiupu Road, Pudong, 201201 Shanghai,
PEOPLE'S REPUBLIC OF CHINATest Result : ☒ **Positive** ☐ **Negative**Total pages including
Appendices : 76

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.

1 Table of Contents

1	Table of Contents	2
2	Details about the Test Laboratory.....	3
3	Description of the Equipment under Test	4
4	Summary of Test Standards.....	6
5	Summary of Test Results.....	7
6	General Remarks	8
7	Test Setups	9
8	Systems test configuration.....	12
9	Technical Requirement	13
9.1	Conducted Emission	13
9.2	Conducted peak output power.....	18
9.3	6dB bandwidth	19
9.4	Power spectral density.....	24
9.5	Spurious RF conducted emissions	29
9.6	Band edge	54
9.7	Spurious radiated emissions for transmitter	63
10	Test Equipment List.....	73
11	System Measurement Uncertainty	74
12	Photographs of Test Set-ups	75
13	Photographs of EUT	76



2 Details about the Test Laboratory

Details about the Test Laboratory

Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
No.16 Lane, 1951 Du Hui Road,
Shanghai 201108,
P.R. China

Test Firm FCC
Registration
Number: 820234

Designation
number: CN1183

IC Company
Number: 25988

CAB identifier: CN0101

Telephone: +86 21 6141 0123
Fax: +86 21 6140 8600

3 Description of the Equipment under Test

Product:	Infrared Thermal Camera
Model no.:	Fotric P9, Fotric P8, Fotric P7, Fotric P6, Fotric P5, Fotric P4
FCC ID:	2AZTCJAGUAR
Options and accessories:	Test harness
Rating:	DC 3.6V Li-ion Battery
RF Transmission Frequency:	2402~2480MHz for Bluetooth For 2.4G & 5G Wi-Fi For 802.11b/g/n-HT20: 2412~2462 MHz For 802.11n-HT40: 2422~2452 MHz 5180~5240 MHz (U-NII-1) 5260~5320 MHz (U-NII-2A) 5500~5720 MHz (U-NII-2C) 5745~5825 MHz (U-NII-3)
No. of Operated Channel:	79 channels for Bluetooth 4.2+EDR 40 channels for Bluetooth 4.2 BLE 2.4GHz WIFI: 11 for 802.11b/802.11g/802.11(H20); 7 for 802.11n(HT40) 5180~5240 MHz (U-NII-1): Channel 36 - 48 5260~5320 MHz (U-NII-2A): Channel 52 - 64 5500~5720 MHz (U-NII-2C): Channel 100 - 144 5745~5825 MHz (U-NII-3): Channel 149 - 165
Modulation:	Bluetooth 4.2+EDR FHSS: GFSK, $\pi/4$ DQPSK, 8DPSK Bluetooth 4.2+BLE DHSS: GFSK For Wi-Fi: Direct Sequence Spread Spectrum (DSSS) for 802.11b Orthogonal Frequency Division Multiplexing (OFDM) for 802.11a/b/g/n/ac
Hardware Version:	0.6.2.4
Software Version:	V3.0.0
Data speed:	1. Bluetooth 4.2+EDR FHSS: 1Mbps, 2Mbps, 3Mbps 2. Bluetooth 4.2+BLE DHSS: 1Mbps 3. Wi-Fi: 11b 1 ~ 11Mbps, 11g/a 6 ~ 54Mbps, 11n HT20 6.5 ~ 72.2Mbps, 11n HT 40 13.5 ~ 150Mbps, 11ac VHT40 13.5 ~ 200Mbps, 11ac VHT80 29.3 ~ 433.3Mbps

Antenna Type:	PIFA Antenna
Antenna Gain:	1.79dBi for 2.4GHz; 7.19dBi for 5GHz
Description of the EUT:	The Equipment Under Test (EUT) is an Infrared Thermal Camera with Bluetooth and Wi-Fi Module. The EUT support Bluetooth 4.2+EDR and support BLE function and Wi-Fi operated at 5GHz and 2.4GHz. Only 2.4G BLE included in this report.
Test sample no.:	SHA-716542-2

The sample's mentioned in this report is/are submitted/ supplied/ manufactured by client. The laboratory therefore assumes no responsibility for accuracy of information on the brand name, model number, origin of manufacture, consignment or any information supplied.

4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators

All the test methods were according to KDB 558074 D01 15.247 Meas Guidance v05r02 and ANSI C63.10 (2013).

5 Summary of Test Results

Technical Requirements						
FCC Part 15 Subpart C						
Test Condition		Pages	Test Site	Test Result		
				Pass	Fail	N/A
§15.207	Conducted emission AC power port	13-17	Site 1	☒	☐	☐
§15.247 (b) (1)	Conducted peak output power	18	Site 1	☒	☐	☐
§15.247(a)(1)	20dB bandwidth	---	---	☐	☐	☒
§15.247(a)(1)	Carrier frequency separation	---	---	☐	☐	☒
§15.247(a)(1)(iii)	Number of hopping frequencies	---	---	☐	☐	☒
§15.247(a)(1)(iii)	Dwell Time	---	---	☐	☐	☒
§15.247(a)(2)	6dB bandwidth	19-23	Site 1	☒	☐	☐
§15.247(e)	Power spectral density	24-28	Site 1	☒	☐	☐
§15.247(d)	Spurious RF conducted emissions	29-53	Site 1	☒	☐	☐
§15.247(d)	Band edge	54-62	Site 1	☒	☐	☐
§15.247(d) & §15.209	Spurious radiated emissions for transmitter	63-72	Site 1	☒	☐	☐
§15.203	Antenna requirement	See note 1		☒	☐	☐

Remark 1: N/A – Not Applicable.

Note 1: The EUT uses a PIFA antenna, which gain is 1.79dBi for 2.4GHz. In accordance to §15.203, It is considered sufficiently to comply with the provisions of this section.

6 General Remarks

Remarks

This submittal(s) (test report) is intended for FCC ID: 2AZTCJAGUAR complies with Section 15.207,15.209,15.247 of the FCC Part 15, Subpart C Rules

This report is only for 2.4GHz Wi-Fi.

According to the client's declaration, all the models have the same electrical circuit board and mechanical structure, except schematic and hardware circuit, except pixel, lens or physical size differences., and we chose the Fotric P7 to perform all the tests.

SUMMARY:

All tests according to the regulations cited on page 5 were

■ - Performed

□ - **Not** Performed

The Equipment under Test

■ - **Fulfills** the general approval requirements.

□ - **Does not** fulfill the general approval requirements.

Sample Received Date: March 24, 2023

Testing Start Date: March 27, 2023


Testing End Date: June 25, 2023

-TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch

Reviewed by:

Prepared by:

Tested by:



Hui TONG
Review Engineer




Jiaxi XU
Project Engineer



Yiquan WANG
Test Engineer


7 Test Setups

7.1 AC Power Line Conducted Emission test setups




7.2 Radiated test setups


9kHz ~ 30MHz Test Setup:




30MHz ~ 1GHz Test Setup:




1GHz ~ 18GHz Test Setup:



18GHz ~ 25GHz Test Setup:



7.3 Conducted RF test setups



8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
Notebook	Lenove	E470	PF-OU5TS7 17/09

Test software: QRCT.exe

The system was configured to channel 1(2412MHz), 6(2437MHz), and 11(2462MHz) for 802.11 b/g/n HT20 test and channel 3(2422MHz), 6(2437MHz), 9(2452MHz) for 802.11n (HT40).

Non-hopping mode: The system was configured to operate at a signal channel transmitting. The test software allows the configuration and operation at the worst-case duty and the highest transmit power.

9 Technical Requirement

9.1 Conducted Emission

Test Method

1. The EUT was placed on a table, which is 0.8m above ground plane
2. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.).
3. Maximum procedure was performed to ensure EUT compliance
4. A EMI test receiver is used to test the emissions from both sides of AC line

Limit

According to §15.207 & RSS-GEN 8.8, conducted emissions limit as below:

Frequency MHz	QP Limit dB μ V	AV Limit dB μ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

Decreasing linearly with logarithm of the frequency

Conducted Emission

150k-30MHz Conducted Emission Test


EUT Information

EUT Name: Infrared Thermal Camera
Model: Fotric P7
Client: FOTRIC INC.
Op Cond: Power on, TX_b_2412MHz, AC 230/50Hz, T21.3, H56.3%, P100.6kPa
Operator: Wang Yiquan
Standard: FCC part 15.207(a)
Comment: Phase L
Sample No.: SHA-716542-2

Scan Setup: Voltage with 2-Line-LISN pre [EMI conducted]

Hardware Setup: Voltage with 2-Line-LISN
Receiver: [ESR 3]
Level Unit: dBuV

Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamp
9 kHz - 150 kHz	100 Hz	PK+	200 Hz	0.02 s	0 dB
150 kHz - 30 MHz	4.5 kHz	PK+; AVG	9 kHz	0.01 s	0 dB



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.177000	53.02	---	64.63	11.61	1000.0	9.000	L1	19.6
0.186000	---	37.98	54.21	16.23	1000.0	9.000	L1	19.6
0.433500	43.37	---	57.19	13.82	1000.0	9.000	L1	19.6
0.456000	---	30.54	46.77	16.23	1000.0	9.000	L1	19.6
1.081500	37.33	---	56.00	18.67	1000.0	9.000	L1	19.6
1.216500	---	29.98	46.00	16.02	1000.0	9.000	L1	19.6
2.886000	---	25.80	46.00	20.20	1000.0	9.000	L1	19.6
2.994000	33.53	---	56.00	22.47	1000.0	9.000	L1	19.6
5.442000	---	28.38	50.00	21.62	1000.0	9.000	L1	19.6
5.748000	33.57	---	60.00	26.43	1000.0	9.000	L1	19.6
14.208000	25.75	---	60.00	34.25	1000.0	9.000	L1	19.8
14.235000	---	16.95	50.00	33.05	1000.0	9.000	L1	19.8

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB) + 10dB Attenuator

150k-30MHz Conducted Emission Test


EUT Information

EUT Name: Infrared Thermal Camera
 Model: Fotric P7
 Client: FOTRIC INC.
 Op Cond: Power on, TX_b_2412MHz, AC 230/50Hz, T21.3, H56.3%, P100.6kPa
 Operator: Wang Yiquan
 Standard: FCC part 15.207(a)
 Comment: Phase N
 Sample No.: SHA-716542-2

Scan Setup: Voltage with 2-Line-LISN pre [EMI conducted]

Hardware Setup: Voltage with 2-Line-LISN
 Receiver: [ESR 3]
 Level Unit: dBuV

Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamp
9 kHz - 150 kHz	100 Hz	PK+	200 Hz	0.02 s	0 dB
150 kHz - 30 MHz	4.5 kHz	PK+; AVG	9 kHz	0.01 s	0 dB



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.154500	---	42.19	55.75	13.56	1000.0	9.000	N	19.6
0.177000	45.16	---	64.63	19.47	1000.0	9.000	N	19.6
0.433500	42.99	---	57.19	14.20	1000.0	9.000	N	19.6
0.532500	---	30.09	46.00	15.91	1000.0	9.000	N	19.6
1.468500	34.52	---	56.00	21.48	1000.0	9.000	N	19.6
1.468500	---	26.08	46.00	19.92	1000.0	9.000	N	19.6
2.616000	---	27.32	46.00	18.68	1000.0	9.000	N	19.6
2.634000	33.53	---	56.00	22.47	1000.0	9.000	N	19.6
5.401500	32.41	---	60.00	27.59	1000.0	9.000	N	19.7
5.401500	---	27.55	50.00	22.45	1000.0	9.000	N	19.7
13.371000	---	17.08	50.00	32.92	1000.0	9.000	N	19.9
13.371000	22.87	---	60.00	37.13	1000.0	9.000	N	19.9

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB) + 10dB Attenuator

9.2 Conducted peak output power

Test Method

1. Use the following spectrum analyzer settings:
RBW > the 6 dB bandwidth of the emission being measured, VBW $\geq$ 3RBW, Span $\geq$ 3RBW
Sweep = auto, Detector function = peak, Trace = max hold.
2. Add a correction factor to the display.
3. Use a spectrum analyzer to measure the average power.

Limits

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤ 1	≤ 30

Test result as below table

Mode	Frequency (MHz)	Average Power (dBm) §15.247 (b) (1)		
		Result	limit	Verdict
802.11b	2412MHz	16.71	≤ 30	Pass
	2437MHz	16.46	≤ 30	Pass
	2462MHz	16.46	≤ 30	Pass

Mode	Frequency (MHz)	Average Power (dBm) §15.247 (b) (1)		
		Result	limit	Verdict
802.11g	2412MHz	12.53	≤ 30	Pass
	2437MHz	12.28	≤ 30	Pass
	2462MHz	12.43	≤ 30	Pass

Mode	Frequency (MHz)	Average Power (dBm) §15.247 (b) (1)		
		Result	limit	Verdict
802.11n(HT20)	2412MHz	11.63	≤ 30	Pass
	2437MHz	11.47	≤ 30	Pass
	2462MHz	11.65	≤ 30	Pass

Mode	Frequency (MHz)	Average Power (dBm) §15.247 (b) (1)		
		Result	limit	Verdict
802.11n(HT40)	2422MHz	12.10	≤ 30	Pass
	2437MHz	12.67	≤ 30	Pass
	2452MHz	12.10	≤ 30	Pass

9.3 6dB bandwidth

Test Method

1. Use the following spectrum analyzer settings:
RBW=100K, VBW $\geq$ 3RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Use the automatic bandwidth measurement capability of an instrument, may be employed using the X dB bandwidth mode with X set to 6 dB, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be $\geq$ 6 dB.
3. Allow the trace to stabilize, record the X dB Bandwidth value.

Limit

Limit [kHz]


≥ 500

N/A


Test result

Test Mode	Frequency MHz	6dB bandwidth (MHz)		Result
		result	limit	verdict
802.11b	2412	8.538	≥ 0.5	Pass
	2437	8.21	≥ 0.5	Pass
	2462	8.595	≥ 0.5	Pass
802.11g	2412	15.06	≥ 0.5	Pass
	2437	16.377	≥ 0.5	Pass
	2462	15.659	≥ 0.5	Pass
802.11n(HT20)	2412	15.065	≥ 0.5	Pass
	2437	17.593	≥ 0.5	Pass
	2462	17.196	≥ 0.5	Pass
802.11n(HT40)	2422	32.602	≥ 0.5	Pass
	2437	35.496	≥ 0.5	Pass
	2452	33.84	≥ 0.5	Pass


6 dB Bandwidth




11G_Ant1_2412




11G_Ant1_2437




11G_Ant1_2462







11N40 Ant1 2422



11N40 Ant1 2437



11N40 Ant1 2452



9.4 Power spectral density

Test Method

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance:

1. Set analyzer center frequency to DTS channel center frequency.
RBW=3kHz, VBW≥3RBW, Span=1.5 times DTS bandwidth, Detector=Peak, Sweep=auto, Trace= max hold.
2. Allow trace to fully stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
3. Repeat above procedures until other frequencies measured were completed.

Limit

Limit [dBm]

≤8

Test result

802.11 b

Frequency MHz	Power spectral density dBm/3kHz	Result
Low channel 2412MHz	-5.2	Pass
Middle channel 2437MHz	-6.25	Pass
High channel 2462MHz	-4.54	Pass

802.11 g


Frequency MHz	Power spectral density dBm	Result
Low channel 2412MHz	-11.41	Pass
Middle channel 2437MHz	-12.86	Pass
High channel 2462MHz	-12.15	Pass

802.11 n (HT20)


Frequency MHz	Power spectral density dBm	Result
Low channel 2412MHz	-10.64	Pass
Middle channel 2437MHz	-13.22	Pass
High channel 2462MHz	-12.5	Pass

802.11 n (HT40)


Frequency MHz	Power spectral density dBm	Result
Low channel 2422MHz	-14.9	Pass
Middle channel 2437MHz	-15.09	Pass
High channel 2452MHz	-15.15	Pass

Power spectral density


11G_Ant1_2412




11G_Ant1_2437




11G_Ant1_2462




11N20SISO_Ant1_2412




11N20SISO_Ant1_2437




11N20SISO_Ant1_2462




11N40SISO_Ant1_2422



11N40SISO_Ant1_2437



11N40SISO_Ant1_2452




9.5 Spurious RF conducted emissions


Test Method


1. Establish a reference level by using the following procedure:
 - a. Set RBW=100 kHz. VBW $\geq$ 3RBW. Detector =peak, Sweep time = auto couple, Trace mode = max hold.
 - b. Allow trace to fully stabilize, use the peak marker function to determine the maximum PSD level.
2. Use the maximum PSD level to establish the reference level.
 - a. Set the center frequency and span to encompass frequency range to be measured.
 - b. Use the peak marker function to determine the maximum amplitude level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements, report the three highest emissions relative to the limit.
3. Repeat above procedures until other frequencies measured were completed.


Limit


Frequency Range MHz	Limit (dBc)
30-25000	-20



Spurious RF conducted emissions



































































9.6 Band edge


Test Method

- 1 Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 100 kHz, VBW $\geq$ RBW, Sweep = auto, Detector function = peak, Trace = max hold.
- 2 Allow the trace to stabilize, use the peak and delta measurement to record the result.
- 3 The level displayed must comply with the limit specified in this Section.

Limit



According to §15.247(d) and RSS-247 5.5, in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a) and RSS-Gen 8.10, must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)) and RSS-Gen.


Test result








China


















China



9.7 Spurious radiated emissions for transmitter

Test Method

1. The EUT was placed on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
3. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. Use the following spectrum analyzer settings According to C63.10:

For Below 1GHz

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious
 RBW = 100 kHz to 120 kHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

For Peak unwanted emissions Above 1GHz:

Span = wide enough to capture the peak level of the in-band emission and all spurious
 RBW = 1MHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

Procedures for average unwanted emissions measurements above 1000 MHz

- a) RBW = 1MHz.
- b) $VBW \geq [3 \times RBW]$.
- c) Detector = RMS (power averaging), if $[\text{span} / (\# \text{ of points in sweep})] \leq RBW / 2$.
 Satisfying this condition can require increasing the number of points in the sweep or reducing the span. If the condition is not satisfied, then the detector mode shall be set to peak.
- d) Averaging type = power (i.e., rms) (As an alternative, the detector and averaging type may be set for linear voltage averaging. Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.)
- e) Sweep time = auto.
- f) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, then the number of traces shall be increased by a factor of $1 / D$, where D is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific emission is demonstrated to be continuous—i.e., 100% duty cycle—then rather than turning ON and OFF with the transmit cycle, at least 100 traces shall be averaged.)
- g) If tests are performed with the EUT transmitting at a duty cycle less than 98%, then a correction factor shall be added to the measurement results prior to comparing with the emission limit, to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:

- 1) If power averaging (rms) mode was used in the preceding step e), then the correction factor is $[10 \log (1 / D)]$, where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 3 dB shall be added to the measured emission levels.
- 2) If linear voltage averaging mode was used in the preceding step e), then the correction factor is $[20 \log (1 / D)]$, where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 6 dB shall be added to the measured emission levels.
- 3) If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission.

Limit

The radio emission outside the operating frequency band shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Radiated emissions which fall in the restricted bands, as defined in section 15.205 and RSS-GEN 8.10 must comply with the radiated emission limits specified in section 15.209.

Frequency MHz	Field Strength uV/m	Measured Distance Meters
0.009~0.490	2400/F (kHz)	300
0.490~1.705	24000/F (kHz)	30
1.705~30	30	30

Frequency MHz	Field Strength uV/m	Field Strength dBuV/m	Detector
30-88	100	40	QP
88-216	150	43.5	QP
216-960	200	46	QP
960-1000	500	54	QP
Above 1000	500	54	AV
Above 1000	5000	74	PK

Spurious radiated emissions for transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit. The only worse case test result is listed in the report.

Transmitting spurious emission test result as below:

Test mode: 802.11B					
Channel 1 (2412MHz)					
Frequency (MHz)	Measure Level (dBuV/M)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2383.43	45.68	74.00	28.32	Peak	Horizontal
4823.96	44.13	74.00	29.87	Peak	Horizontal
2385.66	44.96	74.00	29.04	Peak	Vertical
4823.96	44.95	74.00	29.05	Peak	Vertical

Test mode: 802.11B					
Channel 6 (2437MHz)					
Frequency (MHz)	Measure Level (dBuV/M)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
4874.30	44.90	74.00	27.73	Peak	Horizontal
4874.30	44.95	74.00	30.57	Peak	Vertical

Test mode: 802.11B					
Channel 1 (2462MHz)					
Frequency (MHz)	Measure Level (dBuV/M)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2483.68	47.06	74.00	25.41	Peak	Horizontal
4924.11	44.22	74.00	26.3	Peak	Horizontal
2483.73	46.47	74.00	25.79	Peak	Vertical
4924.09	44.56	74.00	31.49	Peak	Vertical

Test mode: 802.11G					
Channel 1 (2412MHz)					
Frequency (MHz)	Measure Level (dBuV/M)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2383.30	45.47	74.00	28.53		
4824.43	44.28	74.00	29.72	Peak	Horizontal
2387.45	46.17	74.00	27.83	Peak	Vertical
4823.86	44.54	74.00	29.46	Peak	Vertical

Test mode: 802.11G					
Channel 6 (2437MHz)					
Frequency (MHz)	Measure Level (dBuV/M)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
4873.73	44.80	74.00	29.2		
4873.73	44.13	74.00	29.87	Peak	Vertical

Test mode: 802.11G					
Channel 11 (2462MHz)					
Frequency (MHz)	Measure Level (dBuV/M)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2483.77	46.82	74.00	27.18		
4924.73	44.60	74.00	29.40	Peak	Horizontal
2483.50	46.63	74.00	27.37	Peak	Vertical
4923.60	45.02	74.00	28.98	Peak	Vertical

Test mode: 802.11N(HT20)					
Channel 1 (2412MHz)					
Frequency (MHz)	Measure Level (dBuV/M)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2388.76	44.75	74.00	29.25		
4823.86	45.35	74.00	28.65	Peak	Horizontal
2384.86	45.24	74.00	28.76	Peak	Vertical
4825.00	44.7	74.00	29.3	Peak	Vertical

Test mode: 802.11N(HT20)					
Channel 6 (2437MHz)					
Frequency (MHz)	Measure Level (dBuV/M)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
4874.30	44.24	74.00	29.76		
4875.43	44.56	74.00	29.44	Peak	Vertical

Test mode: 802.11N(HT20)					
Channel 11 (2462MHz)					
Frequency (MHz)	Measure Level (dBuV/M)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2483.60	48.38	74.00	25.62		
4928.13	44.3	74.00	29.70	Peak	Horizontal
2483.74	47.09	74.00	26.91	Peak	Vertical
4921.90	44.6	74.00	29.4	Peak	Vertical

Test mode: 802.11N(HT40)					
Channel 3 (2422MHz)					
Frequency (MHz)	Measure Level (dBuV/M)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2389.11	52.28	74.00	21.72	Peak	Horizontal
4844.00	45.35	74.00	28.65	Peak	Horizontal
2389.68	50.16	74.00	23.84	Peak	Vertical
4844.00	44.70	74.00	29.3	Peak	Vertical

Test mode: 802.11N(HT40)					
Channel 6 (2437MHz)					
Frequency (MHz)	Measure Level (dBuV/M)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
4874.30	44.59	74.00	29.41	Peak	Horizontal
4875.43	44.75	74.00	29.25	Peak	Vertical

Test mode: 802.11N(HT40)					
Channel 11 (2452MHz)					
Frequency (MHz)	Measure Level (dBuV/M)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2484.43	52.82	74.00	21.18	Peak	Horizontal
4904.11	44.38	74.00	29.62	Peak	Horizontal
2484.26	48.81	74.00	25.19	Peak	Vertical
4904.14	44.76	74.00	29.24	Peak	Vertical

Remark:

- (1) Emission level= Original Receiver Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss -Amplifier gain
- (3) Margin = limit – Corrected Reading

The worst case of Radiated Emission below 1GHz:

30-1000MHz Radiated Emission

EUT Information


EUT Name:	Infrared Thermal Camera
Model	Fotric P7
Client:	FOTRIC INC.
Op Cond	Power on, TX_b_2412MHz, AC 230/50Hz, T21.3, H56.3%, P100.6kPa
Operator:	Wang Yiquan
Standard	FCC part 15.209(a)
Comment:	Horizontal
Sample No.:	SHA-716542-2

Sweep Setup: RE_VULB9168_pre_Cont_30-1000 [EMI radiated]

Hardware Setup:	RE_VULB9168
Receiver:	[ESR 3]
Level Unit:	dBuV/m

Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
30 MHz - 1 GHz	48.5 kHz	PK+	120 kHz	0.2 s	20 dB

RE_VULB9168_pre_Cont_30-1000



Limit and Margin

Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBuV/m)
71.400000	23.1	1000.0	120.000	169.2	H	178.0	18.3	16.9	40.0
123.640000	30.8	1000.0	120.000	246.4	H	245.0	18.4	12.7	43.5
148.840000	36.2	1000.0	120.000	141.7	H	325.0	21.0	7.3	43.5
239.600000	35.6	1000.0	120.000	159.9	H	288.0	19.5	10.4	46.0
334.960000	25.3	1000.0	120.000	131.2	H	31.0	22.6	20.7	46.0
552.000000	36.7	1000.0	120.000	222.9	H	103.0	27.5	9.3	46.0

30-1000MHz Radiated Emission

EUT Information


EUT Name: Infrared Thermal Camera
Model: Fotric P7
Client: FOTRIC INC.
Op Cond: Power on, TX_b_2412MHz, AC 230/50Hz, T21.3, H56.3%, P100.6kPa
Operator: Wang Yiquan
Standard: FCC part 15.209(a)
Comment: Vertical
Sample No.: SHA-716542-2

Sweep Setup: RE_VULB9168_pre_Cont_30-1000 [EMI radiated]

Hardware Setup: RE_VULB9168
Receiver: [ESR 3]
Level Unit: dBuV/m

Subrange	Step Size	Detectors	Bandwidth	Sweep Time	Preamp
30 MHz - 1 GHz	48.5 kHz	PK+	120 kHz	0.2 s	20 dB

RE_VULB9168_pre_Cont_30-1000



Limit and Margin

Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBuV/m)
31.080000	32.4	1000.0	120.000	199.4	V	327.0	19.3	7.6	40.0
37.760000	30.7	1000.0	120.000	159.3	V	230.0	19.7	9.3	40.0
71.480000	26.6	1000.0	120.000	167.6	V	60.0	18.3	13.4	40.0
129.920000	34.2	1000.0	120.000	198.2	V	172.0	19.3	9.3	43.5
209.840000	30.6	1000.0	120.000	189.9	V	0.0	17.6	12.9	43.5
552.000000	38.1	1000.0	120.000	169.7	V	118.0	27.5	7.9	46.0

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), therefore no data appear in the report.

10 Test Equipment List

List of Test Instruments
Test Site1

	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DATE	CAL. DUE DATE
C	Signal spectrum analyzer	Agilent	N9020B	MY59050168	2023-2-10	2024-2-9
RE	EMI Test Receiver	Rohde & Schwarz	ESR3	101906	2022-8-1	2023-7-31
	Signal Analyzer	Rohde & Schwarz	FSV40	101091	2022-8-1	2023-7-31
	Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9168	961	2019-9-23	2024-9-22
	Horn Antenna	Rohde & Schwarz	HF907	102393	2021-3-15	2024-3-14
	Pre-amplifier	Rohde & Schwarz	SCU-18D	19006451	2022-8-1	2023-7-31
	Loop antenna	Rohde & Schwarz	HFH2-Z2	100443	2022-6-13	2023-6-12
	Loop antenna	Rohde & Schwarz	HFH2-Z2	100443	2023-6-12	2024-6-11
	DOUBLE-RIDGED WAVEGUIDE HORN WITH PRE-AMPLIFIER (18 GHZ - 40 GHZ)	ETS-Lindgren	3116C-PA	002222727	2020-9-23	2023-9-22
	3m Semi-anechoic chamber	TDK	9X6X6	----	2021-5-8	2024-5-7
CE	EMI Test Receiver	Rohde & Schwarz	ESR3	101907	2022-8-1	2023-7-31
	LISN	Rohde & Schwarz	ENV216	101924	2022-8-1	2023-7-31

Measurement Software Information			
Test Item	Software	Manufacturer	Version
C	MTS 8310	MWRFtest	2.0.0.0
RE	EMC 32	Rohde & Schwarz	V10.50.40
CE	EMC 32	Rohde & Schwarz	V9.15.03

C - Conducted RF tests

- Conducted peak output power
- 6dB bandwidth and 99% Occupied Bandwidth
- Power spectral density*
- Spurious RF conducted emissions
- Band edge

11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

Items	Extended Uncertainty
Conducted Disturbance at Mains Terminals	150kHz to 30MHz, LISN, 3.16dB
Radiated Disturbance	30MHz to 1GHz, 5.03dB (Horizontal) 5.12dB (Vertical) 1GHz to 18GHz, 5.49dB 18GHz to 40GHz, 5.63dB
Carrier power conducted measurement	50MHz~18GHz, 1.238dB
Spurious Emission Conducted Measurement	9kHz ~40GHz, 1.224dB

Measurement Uncertainty Decision Rule:

Determination of conformity with the specification limits is based on the decision rule according to IEC Guide 115: 2021, clause 4.4.3 and 4.5.1.

12 Photographs of Test Set-ups

Refer to the < Test Setup photos >.

13 Photographs of EUT

Refer to the < External Photos > & < Internal Photos >.

-----End of Test Report-----