



Test Data

1. Chain 0


802.11b 20MHz Chain0 2412MHz




802.11g 20MHz Chain0 2412MHz




802.11b 20MHz Chain0 2437MHz




802.11g 20MHz Chain0 2437MHz









802.11b 20MHz Chain0 2462MHz



802.11g 20MHz Chain0 2462MHz




2. Chain 1




3. MIMO


802.11n 20MHz Chain0 2412MHz




802.11n 20MHz Chain1 2412MHz




802.11n 20MHz Chain0 2437MHz




802.11n 20MHz Chain1 2437MHz




802.11n 20MHz Chain0 2462MHz




802.11n 20MHz Chain1 2462MHz




802.11n 40MHz Chain0 2422MHz




802.11n 40MHz Chain1 2422MHz




802.11n 40MHz Chain0 2437MHz




802.11n 40MHz Chain1 2437MHz




802.11n 40MHz Chain0 2452MHz




802.11n 40MHz Chain1 2452MHz




802.11ax 20MHz Chain0 2412MHz




802.11ax 20MHz Chain1 2412MHz




802.11ax 20MHz Chain0 2437MHz




802.11ax 20MHz Chain1 2437MHz




802.11ax 20MHz Chain0 2462MHz




802.11ax 20MHz Chain1 2462MHz




802.11ax 40MHz Chain0 2422MHz




802.11ax 40MHz Chain1 2422MHz




802.11ax 40MHz Chain0 2437MHz




802.11ax 40MHz Chain1 2437MHz



802.11ax 40MHz Chain0 2452MHz



802.11ax 40MHz Chain1 2452MHz



Beamformig

Temperature: 23.7 ~ 23.8°C **Test date:** June 13 ~ 14, 2024
Humidity: 55 ~ 58% RH **Tested by:** Marco Chan







POWER DENSITY 802.11n HT20					
Freq. (MHz)	Ch0 PSD	Ch1 PSD	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Result
2412	-12.43	-11.75	-9.07	8.00	PASS
2437	-6.56	-5.96	-3.24	8.00	PASS
2462	-11.91	-10.78	-8.30	8.00	PASS

POWER DENSITY 802.11n HT40					
Freq. (MHz)	Ch0 PSD	Ch1 PSD	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Result
2422	-16.09	-15.55	-12.80	8.00	PASS
2437	-11.34	-10.84	-8.07	8.00	PASS
2452	-13.73	-14.08	-10.89	8.00	PASS


POWER DENSITY 802.11ax HE20						
Freq. (MHz)	RU Config	Ch0 PSD	Ch1 PSD	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Result
2412	full	-11.53	-11.86	-8.68	8.00	PASS
2437	full	-7.44	-6.27	-3.81	8.00	PASS
2462	full	-11.36	-10.33	-7.80	8.00	PASS

POWER DENSITY 802.11ax HE40						
Freq. (MHz)	RU Config	Ch0 PSD	Ch1 PSD	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Result
2422	full	-16.16	-16.59	-13.36	8.00	PASS
2437	full	-14.07	-12.44	-10.17	8.00	PASS
2452	full	-14.38	-14.20	-11.28	8.00	PASS


Test Data




802.11n 40MHz Chain0 2422MHz




802.11n 40MHz Chain1 2422MHz




802.11n 40MHz Chain0 2437MHz




802.11n 40MHz Chain1 2437MHz




802.11n 40MHz Chain0 2452MHz




802.11n 40MHz Chain1 2452MHz




802.11ax 20MHz Chain0 2412MHz




802.11ax 20MHz Chain1 2412MHz




802.11ax 20MHz Chain0 2437MHz




802.11ax 20MHz Chain1 2437MHz




802.11ax 20MHz Chain0 2462MHz




802.11ax 20MHz Chain1 2462MHz




802.11ax 40MHz Chain0 2422MHz




802.11ax 40MHz Chain1 2422MHz




802.11ax 40MHz Chain0 2437MHz




802.11ax 40MHz Chain1 2437MHz



802.11ax 40MHz Chain0 2452MHz



802.11ax 40MHz Chain1 2452MHz



4.5 CONDUCTED BANDEDGE AND SPURIOUS EMISSION

4.5.1 Test Limit

According to §15.247(d),

In any 100 kHz bandwidth outside the authorized frequency band,

Non-restricted bands shall be attenuated at least 20 dB/30 dB relative to the maximum PSD level in 100 kHz by RF conducted or a radiated measurement which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

4.5.2 Test Procedure

Test method Refer as KDB 558074 D01.

1. EUT RF output port connected to the SA by RF cable, and the path loss was compensated to result.
2. SA setting, RBW=100kHz, VBW=300kHz, Detector=Peak, Trace mode = max hold, SWT = Auto.
3. In any 100 kHz bandwidth outside the authorized frequency band, shall be attenuated at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when conducted power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

4.5.3 Test Setup

Refer to section 1.8.

4.5.4 Test Result

Test Data

Non-Beamformig

Temperature:	20.3 ~ 24.5°C	Test date:	May 21 ~ June 27, 2024
Humidity:	53 ~ 64% RH	Tested by:	Marco Chan

Beamformig


Temperature:	23.7 ~ 23.8°C	Test date:	June 13 ~ 14, 2024
Humidity:	55 ~ 58% RH	Tested by:	Marco Chan

Non-Beamformig

Reference Level

1. Chain 0

802.11b 20MHz Chain0 2412MHz



802.11g 20MHz Chain0 2412MHz




802.11b 20MHz Chain0 2437MHz



802.11g 20MHz Chain0 2437MHz



802.11b 20MHz Chain0 2462MHz



802.11g 20MHz Chain0 2462MHz

