

Electric Vehicle AC Charging Station
Model No.: GMEV40CIE1B-WC

Rated Power: 9.6kW AC

Rated Voltage: 208-240V AC

Protection Level: Type 3

Conforms to: UL Std.2594/

UL Std.2231/ UL Std.1998

Conforms to: CSA Std.C22.2#280

For use with Electric Vehicles

Ventilation Not Required

Temperature Limits: -30°C to 50°C

Power Frequency: 50/60Hz

Rated Current: 40A

MMQ: 0.4kWh

CTEP COA No.: 5929-23

Production Date: 24-01

Made in China

Borne de recharge AC pour Véhicule Électrique
Modèle: GMEV40CIE1B-WC

Puissance nominale: 9.6kW AC

Tension nominale: 208-240V AC

Niveau de protection: Type 3

Conforme à: UL Std.2594/

UL Std.2231/ UL Std.1998

Conforme à: CSA Std.C22.2#280

Pour utilisation avec Véhicule Électrique

Ventilation non requise

Température de fonctionnement: -30°C to 50°C

Fréquence d'alimentation: 50/60Hz

Courant nominal: 40A

MMQ: 0.4kWh

Numéro COA CTEP: 5929-23

Date de production: 24-01

Fabriqué au Chine



5005806

Eaton Corporation
1-877-ETN-CARE

S/N: E J G - X X X - X X X X



FCC ID: UH2-GMEV40IW

IC: 4706C-GMEV40IW

Contains FCC ID: 2AC7Z-ESPWROOM32

Contient IC: 21098-ESPWROOM32

