



Maximum Permissible Exposure Evaluation FCC ID: 2BK80-R12E

Report No.	:	TBR-C-202404-0185-2
Applicant	:	Shenzhen TBZ Technology Co., LTD.
Equipment Under Test (EUT)		
EUT Name	:	AIBOT2 AI humanoid robot
Model No.	:	R12E
Series Model No.	:	----
Brand Name	:	----
Sample ID	:	HC-C-202404-0185-01-01-1#&HC-C-202404-0185-01-01-2#
Receipt Date	:	2024-09-19
Test Date	:	2024-09-19 to 2025-03-04
Issue Date	:	2025-03-04
Standards	:	FCC Part 2.1091
Test Method	:	KDB 447498 D01 General RF Exposure Guidance v06
Conclusions	:	PASS
In the configuration tested, the EUT complied with the standards specified above.		
Test By	:	<div> <div>ZKN ZHOU</div> <div>Wade Lv</div> <div>Ivan Su</div> </div>
Reviewed By	:	
Approved By	:	
<p>This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.</p>		

CONTENTS

CONTENTS.....	2
1. GENERAL INFORMATION ABOUT EUT.....	4
1.1 Client Information.....	4
1.2 General Description of EUT (Equipment Under Test)	4
2. MEASUREMENT UNCERTAINTY.....	5
3. TEST FACILITY.....	6
4. METHOD OF MEASUREMENT FOR FCC.....	7
5. TEST RESULT.....	8



Revision History

Report No.	Version	Description	Issued Date
TBR-C-202404-0185-2	Rev.01	Initial issue of report	2025-03-04



1. General Information about EUT

1.1 Client Information

Applicant	:	Shenzhen TBZ Technology Co., LTD.
Address	:	C808, ZiGuang Information Harbor, Nanshan District, ShenZhen City. Guangdong, China
Manufacturer	:	Shenzhen TBZ Technology Co., LTD.
Address	:	C808, ZiGuang Information Harbor, Nanshan District, ShenZhen City. Guangdong, China

1.2 General Description of EUT (Equipment Under Test)

EUT Name	:	AIBOT2 AI humanoid robot
Models No.	:	R12E
Model Different	:	----
Product Description	Operation Frequency:	2.4G: 2401MHz~2481MHz Bluetooth V5.0: 2402MHz~2480MHz 802.11b/g/n(HT20): 2412MHz~2462MHz
	Modulation Type:	2.4G & Bluetooth & BLE: GFSK, Pi/4-DQPSK, 8DPSK 802.11b: DSSS (DQPSK, DBPSK, CCK) 802.11g: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11a: OFDM (QPSK, BPSK, 16QAM, 64QAM) 802.11n: OFDM (QPSK, BPSK, 16QAM, 64QAM)
	Antenna Gain:	1.30dBi PCB Antenna for 2.4G -0.58dBi PCB Antenna for BT&2.4G WIFI
Power Rating	:	Adapter(KA1801A-0902000US) INPUT: 100-240V~50/60Hz 0.55A Max OUTPUT: 9V/2000mA DC 7.2V 3300mAh Rechargeable Li-ion battery
Software Version	:	1.0.0
Hardware Version	:	TBZ_R12_MAIN_V1.1 2024.12.06
Remark: The above antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.		



2. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty (ULab)
Conducted Emission	Level Accuracy: 9kHz~150kHz 150kHz to 30MHz	± 3.50 dB ± 3.10 dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	± 4.60 dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	± 4.50 dB
Radiated Emission	Level Accuracy: Above 1000MHz	± 4.20 dB
Temperature	/	$\pm 0.6^{\circ}\text{C}$
Humidity	/	$\pm 4\%$
Supply voltages	/	$\pm 2\%$
Time	/	$\pm 4\%$



3. Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1/F., Building 6, Rundongsheng Industrial Zone, Longzhu, Xixiang, Bao'an District, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

CNAS (L5813)

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

A2LA Certificate No.: 4750.01

The laboratory has been accredited by American Association for Laboratory Accreditation(A2LA) to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the technical competence in the field of Electrical Testing. And the A2LA Certificate No.: 4750.01.FCC Accredited Test Site Number: 854351. Designation Number: CN1223.

IC Registration No.: (11950A)

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A. CAB identifier: CN0056.



4. Method of Measurement for FCC

4.1 EUT Operation Condition:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.2 Exposure Evaluation:

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=(PG)/4\pi R^2$$

Where

S: power density

P: power input to the antenna

G: power gain of the antenna in the direction of interest relative to an isotropic radiator.

R: distance to the center of radiation of the antenna

4.3 Simultaneous transmission MPE Considerations

According to KDB447498 D01 v06: All transmitters and antennas in the host must be either evaluated for MPE compliance, by measurement or computational modeling, or qualify for the standalone MPE test exclusion in section 7.1. Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 . This means that:

$$\sum \text{ of MPE ratios } \leq 1.0$$



5. Test Result

Mode	N _{TX}	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/cm ²) [S]
2.4G	1	3.291	3±1	4	1.3	20	0.00067

Note:

N_{TX}= Number of Transmit Antennas

RF Output power specifies that Maximum Conducted Peak Output Power.

Mode	N _{TX}	Conducted Power(max) (dBm)	Turn-up Power (dB)	Max tune up power (dBm) [P]	ANT Gain (dBi) [G]	Distance (cm) [R]	Power Density (mW/cm ²) [S]
BT	1	2.556	2±1	3	-0.58	20	0.00035
BLE	1	6.759	6±1	7	-0.58	20	0.00087
2.4G WIFI	1	14.75	14±1	15	-0.58	20	0.00550

Note:

N_{TX}= Number of Transmit Antennas

RF Output power specifies that Maximum Conducted Peak Output Power.

Conclusion:

As specified in Table 1B of 47 CFR 1.1310- Limits for Maximum Permissible Exposure (MPE),

Limits for General Population/ Uncontrolled Exposure

Frequency Range (MHz)	Power density (mW/ cm ²)
300-1,500	F/1500
1,500-100,000	1.0

Summary simultaneous transmission information:

The sample supports two antennas for 2.4G and (Bluetooth & WLAN).

The 2.4G Antenna and (Bluetooth & WLAN) Antenna can transmit simultaneous.

The 2.4G and (Bluetooth & WLAN) with two different Antenna.

According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

\sum of MPE ratios ≤ 1.0

Summary simultaneous transmission results:

2.4G Antenna + (Bluetooth&2.4G WIFI) Antenna Maximum Simultaneous transmission MPE Ratios is $0.00067+0.00550=0.00567 \leq 1.0$

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

-----END OF THE REPORT-----

