Applica							
FCC ID		VPYLB1PJ	IC:	772C-LB1PJ			
Section 15.212 Modular Transmitters / Section 3.2 of RSS-Gen							
R	equest for Mo	odular Approval	D :	C 1'4'	Comply (Y/N)		
		Requirements		Device Conditions			
	Single Modular Approval Requirements The radio elements must have the radio The module has its own RF shielding."						
1	frequency circ Physical/discr may be locate	cuitry must be shielded. rete and tuning capacitors ed external to the shield, but e module assembly.	Shield Can is employed on the board structure, please see exhibition External Photo, the emission measurement was conducted without further shielding added.		Y		
2	The module shall have buffered modulation/data input(s) (if such inputs are provided) to ensure that the module will comply with the requirements set out in the applicable RSS standard under conditions of excessive data rates or over-modulation.				Y		
3	supply regula ensure that the the requirement standard regar power supply device which Requirements standard regar design of the	chall have its own power tion on the module. This is to be module will comply with ents set out in the applicable rdless of the design of the ing circuitry in the host houses the module. It is set out in the applicable rdless of the power supplying circuitry in the which houses the module.	The adopted IC Quintegrated its own regulation.		Y		
4	provisions for and antennas Equipment ce contain a deta	hall comply with the rexternal power amplifiers detailed in this standard. The ertification submission shall ailed description of the of all antennas that will be module.	The EUT meets the FCC antenna Requirements. The specific PCB antenna shall attach to the module via an ANT pin by soldering.		Y		
5	with the appli alone configu	the module shall be tested for compliance the the applicable standard in a stand-one configuration, i.e. the module must the inside another device during testing. The modular transmitter was tested in a stand-alone configuration via a SDIO or UART Interface.			Y		
6		hall comply with the uipment labelling	The device is too s information requir user manual and p	red will be put on the	Y		

7	The modular transmitter complies with all specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer will provide adequate instructions along with the module to explain any such requirements. A copy of these instructions is included in this application for equipment authorization:	Instructions in User Manual	Y
8a	Address compliance with the Commission's RF exposure limits in Sections 1.1310 and 2.1091.	Please refer the Maximum Permissible Exposure Information.	Υ
8b	The module shall comply with applicable RSS-102 exposure requirements, which are based on the intended use/configurations.	Please refer the Maximum Permissible Exposure Information.	Υ
9	Is the modular device for an Industry Canada licensed exempt service?		Y

A **limited modular approval** may be granted for single or split modular transmitters that do not comply with all of the above requirements, *e.g.*, shielding, minimum signaling amplitude, buffered modulation/data inputs, or power supply regulation, if the manufacturer can demonstrate by alternative means in the application for equipment authorization that the modular transmitter meets all the applicable Part 15 requirements under the operating conditions in which the transmitter will be used. Limited modular approval also may be granted in those instances where compliance with RF exposure rules is demonstrated only for particular product configurations. The applicant for certification must state how control of the end product into which the module will be installed will be maintained such that full compliance of the end product is always ensured.

J Watamah

Name: Takahiro Watanabe

Title: Senior Manager

Product Development Sec. 1 IoT Module Products Dept.

Communication Modules Division

Communication & Sensor Business Unit

Company: Murata Manufacturing Co., Ltd.

Date: 2018-01-29