





Report No. : EED32Q80822802



Check No.: 7818170624



RF Exposure Evaluation Report

Product
Trade mark
Model/Type reference
Serial Number
Report Number
FCC ID
Date of Issue
Test Standards

: P20 PRO Oscillating-Vibrating Electric Toothbrush

: usmile : usmile P20 PRO : N/A

EED32Q80822802 •

2A5YZ-P20PRO

Jun. 26, 2024 47 CFR Part 1.1307 47 CFR Part 1.1310 47 CFR Part 2,1091 47 CFR Part 2.1093 KDB 447498 D04 Interim General RF Exposure Guidance v01

Report Seal



www.cti-cert.com E-mail:info@cti-cert.com Complaint call:0755-33681700 Complaint E-mail:complaint@cti-cert.com Hotline:400-6788-333



Report No. : EED32Q80822802

2 Version

Page 2 of 7

Version No.	Date	Description			
00	Jun. 06, 2024	Original			
01	Jul. 26, 2024	Updated the position of TYPE-C on the PCB, the fuse and VS layout on the back of the PCB, the horizontal layout of the lithium protection chip, and the internal wiring to modify the power supply par			



	: EED32Q80822	2802			Page 3	3 of 7
3 Co	ntents					Pa
1 COVER F	PAGE	~			 	га
2 VERSION				••••••	••••••	
	тѕ					
4.1 CLIEN 4.2 GENE 4.3 PROE 4.4 TEST 4.5 DEVIJ 4.6 ABNO	L INFORMATION THE INFORMATION CAL DESCRIPTION DUCT SPECIFICATION LOCATION ATION FROM STAND DRMALITIES FROM S TR INFORMATION RE	OF EUT N SUBJECTIVE TO ARDS TANDARD COND	O THIS STANDA	RD	 ٢	
5.1.1 5.1.2 ⁻	XPOSURE COMPLIAI Limits Test Procedure EUT RF Exposure				 	







Page 4 of 7

Report No. : EED32Q80822802

General Information 4

4.1 Client Information

Applicant:	Guangzhou Stars Pulse Co., Ltd.					
Address of Applicant:	Room 2001, 2002, 2003, 2004, 2005, No.239 Tianhe North Road, Tianhe District, Guangzhou City, Guangdong Province, China					
Manufacturer:	Guangzhou Stars Pulse Co., Ltd.					
Address of Manufacturer:	Room 2001, 2002, 2003, 2004, 2005, No.239 Tianhe North Road, Tianhe District, Guangzhou City, Guangdong Province, China					
Factory:	Dongguan Huabel Electronic Technology Co., Ltd.					
Address of Factory:	No.9, Industrial Northern Road, Songshan Lake Park, Dongguan City, Guangdong Province, P.R. China					

4.2 General Description of EUT

Product Name:	P20 PRO Oscillating-Vibrating El			
Model No.(EUT):	usmile P20 PRO	6	(C)	
Trade Mark:	usmile			

4.3 Product Specification subjective to this standard

Frequency Range: 2402MHz~2480MHz			(\mathcal{S})		(\mathcal{O})	
Modulation Type: BLE: GFSK					J	
Test Power Grade:	Default					
Test Software of EUT:	DTM.exe	-10-		- 0		-
Antenna Type: Multilayer chip Antenna						
Antenna Gain:	2.67 dBi	0		(U)		0
Power Supply:	Battery:	DC 3.7V				
Sample Received Date: Jun. 17,		24	- 0.10		-0.5	
Sample tested Date:	Jun. 20, 20	24 to Jul. 03, 2024				
	0					

Remark:

Company Name and Address shown on Report, the sample(s) and sample Information was/ were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified.







Report No. : EED32Q80822802

Page 5 of 7

4.4 Test Location



- All tests were performed at: Centre Testing International Group Co., Ltd Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China Telephone: +86 (0) 755 33683668 Fax:+86 (0) 755 33683385 No tests were sub-contracted. FCC Designation No.: CN1164
- 4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.







Page 6 of 7

5 SAR Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Limits

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold Pth (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). Pth is given by Formula

$$P_{\rm th} \,({\rm mW}) = \begin{cases} ERP_{20 \,\,{\rm cm}} (d/20 \,\,{\rm cm})^x & d \le 20 \,\,{\rm cm} \\ \\ ERP_{20 \,\,{\rm cm}} & 20 \,\,{\rm cm} < d \le 40 \,\,{\rm cm} \end{cases}$$

where

$$\kappa = -\log_{10}\left(\frac{60}{ERP_{20}\,\mathrm{cm}\sqrt{f}}\right)$$

and f is in GHz, d is the separation distance (cm), and ERP20cm is per Formula (B.1).

$$P_{\text{th}} (\text{mW}) = ERP_{20 \text{ cm}} (\text{mW}) = \begin{cases} 2040f & 0.3 \text{ GHz} \le f < 1.5 \text{ GHz} \\ \\ 3060 & 1.5 \text{ GHz} \le f \le 6 \text{ GHz} \end{cases}$$
(B. 1)

The 1 mW Blanket Exemption of § 1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.









Ì

Report No. : EED32Q80822802



5.1.3 EUT RF Exposure Evaluation

For Stand alone:

For Bluetooth LE:

2	Frequency	Available maximum time-	Antenna	ERP	Available maximum time-	Limit	Result
	(MHz)	averaged power	gain	(dBm)	averaged power	(mW)	
-		(dBm)	(dBi)		(mW)		
	2480	-0.65	2.67	-0.13	0.971	≤2.717	PASS

Note:

①EIRP=Available maximum time-averaged power+Antenna gain;②ERP=EIRP-2.15;

③According to §1.1307(b)(3)(i)(B),RF sources with available maximum time-averaged power or

effective radiated power (ERP), whichever is greater, of less than or equal to the threshold Pth (mW).

(4) The test data refer to the report of No. EED32Q80822801. Only the worst case data was recorded in the report.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced

*** End of Report ***

except in full.