

FCC SAR EVALUATION REPORT

**In accordance with the requirements of
FCC 47 CFR Part 2(2.1093), ANSI/IEEE C95.1-1992 and
IEEE Std 1528-2013**

Product Name : Mobile Phone

Brand Name : Blackview

Model Name : BV6200

Family Model : N/A

Report No. : S23081002902001

FCC ID : 2A7DX-BV6200

Prepared for

DOKE COMMUNICATION (HK) LIMITED
RM 1902 EASEY COMM BLDG 253-261 HENNESSY ROAD
WANCHAI HK CHINA

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.
1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street,
Bao'an District, Shenzhen 518126 P.R.China.
Tel. 400-800-6106, 0755-2320 0050, 0755-2320 0090
Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION

Applicant's name DOKE COMMUNICATION (HK) LIMITED
Address..... RM 1902 EASEY COMM BLDG 253-261 HENNESSY ROAD WANCHAI HK CHINA
Manufacturer's Name . Shenzhen DOKE Electronic Co., Ltd
Address..... 801, Building3, 7th Industrial Zone, Yulv Community, Yutang Road, Guangming District, Shenzhen, China.
Product description
Product name Mobile Phone
Brand Name Blackview
Model and/or type reference BV6200
Family Model N/A
FCC 47 CFR Part 2(2.1093)
ANSI/IEEE C95.1-1992
Standards IEEE Std 1528-2013
Published RF exposure KDB procedures

This device described above has been tested by Shenzhen NTEK. In accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 and KDB 865664 D01. Testing has shown that this device is capable of compliance with localized specific absorption rate (SAR) specified in FCC 47 CFR Part 2(2.1093) and ANSI/IEEE C95.1-1992. The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK, this document may be altered or revised by Shenzhen NTEK, personal only, and shall be noted in the revision of the document.

Test Sample Number S230810029002

Date of Test

Date (s) of performance of tests... Aug. 14, 2023 ~ Aug. 24, 2023

Date of Issue Sep. 11, 2023

Test Result **Pass**

Prepared By :
(Test Engineer)

Jack Li

(Jack Li)

Approved By :
(Lab Manager)

Alex

(Alex Li)

※ ※ **Revision History** ※ ※

REV.	DESCRIPTION	ISSUED DATE	REMARK
Rev.1.0	Initial Test Report Release	Sep. 11, 2023	Jack Li

TABLE OF CONTENTS

1. General Information	6
1.1. RF exposure limits.....	6
1.2. Statement of Compliance	7
1.3. EUT Description	7
1.4. Test specification(s)	9
1.5. Ambient Condition.....	9
2. SAR Measurement System	10
2.1. SATIMO SAR Measurement Set-up Diagram	10
2.2. Robot	11
2.3. E-Field Probe.....	12
2.3.1. E-Field Probe Calibration	12
2.4. SAM phantoms	13
2.4.1. Technical Data	14
2.5. Device Holder	15
2.6. Test Equipment List	16
3. SAR Measurement Procedures	19
3.1. Power Reference	19
3.2. Area scan & Zoom scan.....	19
3.3. Description of interpolation/extrapolation scheme	21
3.4. Volumetric Scan	21
3.5. Power Drift	21
4. System Verification Procedure	22
4.1. Tissue Verification	22
4.1.1. Tissue Dielectric Parameter Check Results	23
4.2. System Verification Procedure	24
4.2.1. System Verification Results	25
5. SAR Measurement variability and uncertainty	26
5.1. SAR measurement variability.....	26
5.2. SAR measurement uncertainty	26
6. RF Exposure Positions	27
6.1. Ear and handset reference point	27
6.2. Definition of the cheek position	27
6.3. Definition of the tilt position	29
6.4. Body Worn Accessory	29
6.5. Wireless Router Devices	30
7. RF Output Power	31
7.1. GSM Conducted Power	31
7.2. WCDMA Conducted Power	31
7.3. LTE Conducted Power	33

7.4. WLAN & Bluetooth Output Power	46
8. Antenna Location.....	48
9. Stand-alone SAR test exclusion.....	48
10. SAR Results	49
10.1. SAR measurement Result.....	49
10.1.1. SAR measurement Result of GSM850	49
10.1.2. SAR measurement Result of GSM1900.....	50
10.1.3. SAR measurement Result of WCDMA Band 2	51
10.1.4. SAR measurement Result of WCDMA Band 4.....	52
10.1.5. SAR measurement Result of WCDMA Band 5	53
10.1.6. SAR measurement Result of LTE Band 2	54
10.1.7. SAR measurement Result of LTE Band 4	56
10.1.8. SAR measurement Result of LTE Band 5	58
10.1.9. SAR measurement Result of LTE Band 7	60
10.1.10. SAR measurement Result of LTE Band 12	62
10.1.11. SAR measurement Result of LTE Band 13	64
10.1.12. SAR measurement Result of LTE Band 17	66
10.1.13. SAR measurement Result of WLAN 2.4G	68
10.1.14. SAR measurement Result of WLAN 5.2G	69
10.1.15. SAR measurement Result of WLAN 5.8G	70
10.2. Simultaneous Transmission Analysis.....	71
11. Appendix A. Photo documentation	72
12. Appendix B. System Check Plots.....	73
13. Appendix C. Plots of High SAR Measurement.....	90
14. Appendix D. Calibration Certificate	151

1. General Information

1.1. RF exposure limits

(A).Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B).Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

NOTE: **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. **SAR for hands, wrists, feet and ankles** is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

General Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

NOTE

Localized Head, Neck and Trunk LIMIT

1.6 W/kg

APPLIED TO THIS EUT

1.2. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for BV6200 are as follows.

RF Exposure Conditions		Max Reported SAR Value(W/kg)
1-g Head		0.861
1-g Body-Worn (Separation distance of 10mm)		0.772
1-g Hotspot (Separation distance of 10mm)		0.772
Max Simultaneous Tx	Head	1.337
	Body-Worn	0.938
	Hotspot	0.938

Note: The Max Simultaneous Tx is calculated based on the same configuration and test position. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR Part 2(2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 & KDB 865664 D01.

1.3. EUT Description

Device Information			
Product Name	Mobile Phone		
Brand Name	Blackview		
Model Name	BV6200		
Family Model	N/A		
Model Difference	N/A		
FCC ID	2A7DX-BV6200		
Device Phase	Identical Prototype		
Exposure Category	General population / Uncontrolled environment		
Antenna Type	PIFA Antenna		
Battery Information	DC 3.85V, 13000mAh, 50.05Wh		
HW Version	HCT-M662MB-A2		
SW Version	BV6200_NEU_M662_V1.0		
Device Operating Configurations			
Supporting Mode(s)	GSM850/1900,WCDMABand2/4/5,LTEBand2/4/5/7/12/13/17, WLAN 2.4/5G, Bluetooth		
Test Modulation	GSM(GMSK/8PSK), WCDMA(QPSK), LTE(QPSK/16QAM), WLAN(DSSS/OFDM), Bluetooth(GFSK, $\pi/4$ -DQPSK, 8DPSK),		
Device Class	B		
Operating Frequency	Band	Tx (MHz)	Rx (MHz)

Range(s)	GSM 850	824-849	869-894
	GSM 1900	1850-1910	1930-1990
	WCDMA Band 2	1850-1910	1930-1990
	WCDMA Band 4	1710-1755	2110-2155
	WCDMA Band 5	824-849	869-894
	LTE Band 2	1850-1910	1930-1990
	LTE Band 4	1710-1755	2110-2155
	LTE Band 5	824-849	869-894
	LTE Band 7	2500-2570	2620-2690
	LTE Band 12	699-716	729-746
	LTE Band 13	777-787	746-756
	LTE Band 17	704-716	734-746
	WLAN 2.4G	2412-2462	
	WLAN 5.2G	5180-5240	
	WLAN 5.8G	5745-5825	
	Bluetooth	2402-2480	
GPRS Multislot Class(12)	Max Number of Timeslots in Uplink		4
	Max Number of Timeslots in Downlink		4
	Max Total Timeslot		5
EGPRS Multislot Class(12)	Max Number of Timeslots in Uplink		4
	Max Number of Timeslots in Downlink		4
	Max Total Timeslot		5
Power Class	4, tested with power level 5(GSM 850)		
	1, tested with power level 0(GSM 1900)		
	3, tested with power control —all”(WCDMA Band 2)		
	3, tested with power control —all”(WCDMA Band 4)		
	3, tested with power control —all”(WCDMA Band 5)		
	3, tested with power control all Max.(LTE Band 2)		
	3, tested with power control all Max.(LTE Band 4)		
	3, tested with power control all Max.(LTE Band 5)		
	3, tested with power control all Max.(LTE Band 7)		
	3, tested with power control all Max.(LTE Band 12)		
	3, tested with power control all Max.(LTE Band 13)		
	3, tested with power control all Max.(LTE Band 17)		

1.4. Test specification(s)


FCC 47 CFR Part 2(2.1093)
ANSI/IEEE C95.1-1992
IEEE Std 1528-2013
KDB 865664 D01 SAR measurement 100 MHz to 6 GHz
KDB 865664 D02 RF Exposure Reporting
KDB 447498 D01 General RF Exposure Guidance
KDB 248227 D01 802.11 Wi-Fi SAR
KDB 941225 D01 3G SAR Procedures
KDB 941225 D05 SAR for LTE Devices
KDB 941225 D06 Hotspot SAR
KDB 648474 D04 Handset SAR

1.5. Ambient Condition

Ambient temperature	20°C – 24°C
Relative Humidity	30% – 70%

2. SAR Measurement System

2.1. SATIMO SAR Measurement Set-up Diagram



These measurements were performed with the automated near-field scanning system OPENSAR from SATIMO. The system is based on a high precision robot (working range: 901 mm), which positions the probes with a positional repeatability of better than ± 0.03 mm. The SAR measurements were conducted with dosimetric probe (manufactured by SATIMO), designed in the classical triangular configuration and optimized for dosimetric evaluation.

The first step of the field measurement is the evaluation of the voltages induced on the probe by the device under test. Probe diode detectors are nonlinear. Below the diode compression point, the output voltage is proportional to the square of the applied E-field; above the diode compression point, it is linear to the applied E-field. The compression point depends on the diode, and a calibration procedure is necessary for each sensor of the probe.

The Keithley multimeter reads the voltage of each sensor and send these three values to the PC. The corresponding E field value is calculated using the probe calibration factors, which are stored in the working directory. This evaluation includes linearization of the diode characteristics. The field calculation is done separately for each sensor. Each component of the E field is displayed on the "Dipole Area Scan Interface" and the total E field is displayed on the "3D Interface"

2.2. Robot

The SATIMO SAR system uses the high precision robots from KUKA. For the 6-axis controller system, the robot controller version (KUKA) from KUKA is used. The KUKA robot series have many features that are important for our application:



- High precision (repeatability ± 0.03 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)

2.3. E-Field Probe

This E-field detection probe is composed of three orthogonal dipoles linked to special Schottky diodes with low detection thresholds. The probe allows the measurement of electric fields in liquids such as the one defined in the IEEE and CENELEC standards.

For the measurements the Specific Dosimetric E-Field Probe SN 08/16 EPG0287 with following specifications is used



- Dynamic range: 0.01-100 W/kg
 - Tip Diameter : 2.5 mm
 - Distance between probe tip and sensor center: 1 mm
 - Distance between sensor center and the inner phantom surface: 2 mm (repeatability better than ± 1 mm).
 - Probe linearity: ± 0.08 dB
 - Axial isotropy: ± 0.01 dB
 - Hemispherical Isotropy: ± 0.01 dB
 - Calibration range: 650MHz to 5900MHz for head & body simulating liquid.
 - Lower detection limit: 8mW/kg
- Angle between probe axis (evaluation axis) and surface normal line: less than 30° .

2.3.1. E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy shall be evaluated and within ± 0.25 dB. The sensitivity parameters (Norm X, Norm Y, and Norm Z), the diode compression parameter (DCP) and the conversion factor (Conv F) of the probe are tested. The calibration data can be referred to appendix D of this report.

2.4. SAM phantoms


Photo of SAM phantom SN 16/15 SAM119



The SAM phantom is used to measure the SAR relative to people exposed to electro-magnetic field radiated by Smart Phones.

2.4.1. Technical Data

Serial Number	Shell thickness	Filling volume	Dimensions	Positionner Material	Permittivity	Loss Tangent
SN 16/15 SAM119	2 mm ±0.2 mm	27 liters	Length:1000 mm Width:500 mm Height:200 mm	Gelcoat with fiberglass	3.4	0.02




Serial Number	Left Head(mm)		Right Head(mm)		Flat Part(mm)	
SN 16/15 SAM119	2	2.02	2	2.08	1	2.09
	3	2.05	3	2.06	2	2.06
	4	2.07	4	2.07	3	2.08
	5	2.08	5	2.08	4	2.10
	6	2.05	6	2.07	5	2.10
	7	2.05	7	2.05	6	2.07
	8	2.07	8	2.06	7	2.07
	9	2.08	9	2.06	-	-

The test, based on ultrasonic system, allows measuring the thickness with an accuracy of 10 μm .

2.5. Device Holder

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1 degree.



Serial Number	Holder Material	Permittivity	Loss Tangent
SN 16/15 MSH100	Delrin	3.7	0.005

2.6. Test Equipment List

This table gives a complete overview of the SAR measurement equipment.

Devices used during the test described are marked ☒

	Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
					Last Cal.	Due Date
☒	MVG	E FIELD PROBE	SSE2	SN 08/16 EPGO287	Jan. 10, 2023	Jan. 09, 2024
☒	MVG	750 MHz Dipole	SID750	SN 03/15 DIP 0G750-355	Mar. 01, 2021	Feb. 28, 2024
☒	MVG	835 MHz Dipole	SID835	SN 03/15 DIP 0G835-347	Mar. 01, 2021	Feb. 28, 2024
☐	MVG	900 MHz Dipole	SID900	SN 03/15 DIP 0G900-348	Mar. 01, 2021	Feb. 28, 2024
☒	MVG	1800 MHz Dipole	SID1800	SN 03/15 DIP 1G800-349	Mar. 01, 2021	Feb. 28, 2024
☒	MVG	1900 MHz Dipole	SID1900	SN 03/15 DIP 1G900-350	Mar. 01, 2021	Feb. 28, 2024
☐	MVG	2000 MHz Dipole	SID2000	SN 03/15 DIP 2G000-351	Mar. 01, 2021	Feb. 28, 2024
☐	MVG	2300 MHz Dipole	SID2300	SN 03/16 DIP 2G300-358	Mar. 01, 2021	Feb. 28, 2024
☒	MVG	2450 MHz Dipole	SID2450	SN 03/15 DIP 2G450-352	Mar. 01, 2021	Feb. 28, 2024
☒	MVG	2600 MHz Dipole	SID2600	SN 03/15 DIP 2G600-356	Mar. 01, 2021	Feb. 28, 2024
☐	MVG	3500 MHz Dipole	SID3500	SN 09/12 DIP 3G500-360	Oct. 15, 2022	Oct. 14, 2025
☒	MVG	5000 MHz Dipole	SWG5500	SN 13/14 WGA 33	Mar. 01, 2021	Feb. 28, 2024
☒	MVG	Liquid measurement Kit	SCLMP	SN 21/15 OCPG 72	NCR	NCR
☒	MVG	Power Amplifier	N.A	AMPLISAR_28/14_003	NCR	NCR
☒	KEITHLEY	Millivoltmeter	2000	4072790	NCR	NCR
☒	R&S	Universal radio communication tester	CMU200	117858	May 29, 2023	May 28, 2024
☒	R&S	Wideband radio communication	CMW500	103917	May 29, 2023	May 28, 2024

		tester				
☒	HP	Network Analyzer	8753D	3410J01136	May 29, 2023	May 28, 2024
☒	Agilent	MXG Vector Signal Generator	N5182A	MY47070317	May 29, 2023	May 28, 2024
☒	Agilent	Power meter	E4419B	MY45102538	May 29, 2023	May 28, 2024
☒	Agilent	Power sensor	E9301A	MY41495644	May 29, 2023	May 28, 2024
☒	Agilent	Power sensor	E9301A	US39212148	May 29, 2023	May 28, 2024
☒	MCLI/USA	Directional Coupler	CB11-20	0D2L51502	Jul. 04, 2023	Jul. 03, 2024
☒	N/A	Thermometer	N/A	LES-085	Mar. 27, 2023	Mar. 26, 2026
☒	MVG	SAM Phantom	SSM2	SN 16/15 SAM119	NCR	NCR
☒	MVG	Device Holder	SMPPD	SN 16/15 MSH100	NCR	NCR
☒	Shenzhen Tianxu Communication Technology Co., Ltd.	Human Simulating Liquid	Head 750	Head 750	NCR	NCR
☒	Shenzhen Tianxu Communication Technology Co., Ltd.	Human Simulating Liquid	Head 835	Head 835	NCR	NCR
☒	Shenzhen Tianxu Communication Technology Co., Ltd.	Human Simulating Liquid	Head 1800	Head 1800	NCR	NCR
☒	Shenzhen Tianxu Communication Technology Co., Ltd.	Human Simulating Liquid	Head 1900	Head 1900	NCR	NCR
☒	Shenzhen Tianxu Communication Technology Co., Ltd.	Human Simulating Liquid	Head 2450	Head 2450	NCR	NCR

	Co., Ltd.					
☒	Shenzhen Tianxu Communication Technology Co., Ltd.	Human Simulating Liquid	Head 2600	Head 2600	NCR	NCR
☒	Shenzhen Tianxu Communication Technology Co., Ltd.	Human Simulating Liquid	Head 5200	Head 5200	NCR	NCR
☒	Shenzhen Tianxu Communication Technology Co., Ltd.	Human Simulating Liquid	Head 5800	Head 5800	NCR	NCR

3. SAR Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For Wi-Fi/BT power measurement, use engineering software to configure EUT Wi-Fi/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band.
- (d) Connect EUT RF port through RF cable to the power meter, and measure Wi-Fi/BT output power.

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT Wi-Fi/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix A demonstrates.
- (c) Set scan area, grid size and other setting on the OPENSAR software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band.
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg.

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

3.1. Power Reference

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

3.2. Area scan & Zoom scan

The area scan is a 2D scan to find the hot spot location on the DUT. The zoom scan is a 3D scan

above the hot spot to calculate the 1g and 10g SAR value.

Measurement of the SAR distribution with a grid of 8 to 16 mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8 * 4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

From the scanned SAR distribution, identify the position of the maximum SAR value, in addition identify the positions of any local maxima with SAR values within 2 dB of the maximum value that will not be within the zoom scan of other peaks; additional peaks shall be measured only when the primary peak is within 2 dB of the SAR compliance limit (e.g., 1 W/kg for 1,6 W/kg 1 g limit, or 1,26 W/kg for 2 W/kg, 10 g limit).

Area scan & Zoom scan scan parameters extracted from FCC KDB 865664 D01 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5 \text{ mm}$
Maximum probe angle from probe axis to phantom surface normal at the measurement location			30° ± 1°	20° ± 1°
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$			$\leq 2 \text{ GHz}: \leq 15 \text{ mm}$ $2 - 3 \text{ GHz}: \leq 12 \text{ mm}$	$3 - 4 \text{ GHz}: \leq 12 \text{ mm}$ $4 - 6 \text{ GHz}: \leq 10 \text{ mm}$
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			$\leq 2 \text{ GHz}: \leq 8 \text{ mm}$ $2 - 3 \text{ GHz}: \leq 5 \text{ mm}^*$	$3 - 4 \text{ GHz}: \leq 5 \text{ mm}^*$ $4 - 6 \text{ GHz}: \leq 4 \text{ mm}^*$
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	$3 - 4 \text{ GHz}: \leq 4 \text{ mm}$ $4 - 5 \text{ GHz}: \leq 3 \text{ mm}$ $5 - 6 \text{ GHz}: \leq 2 \text{ mm}$
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	$3 - 4 \text{ GHz}: \leq 3 \text{ mm}$ $4 - 5 \text{ GHz}: \leq 2.5 \text{ mm}$ $5 - 6 \text{ GHz}: \leq 2 \text{ mm}$
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	$3 - 4 \text{ GHz}: \geq 28 \text{ mm}$ $4 - 5 \text{ GHz}: \geq 25 \text{ mm}$ $5 - 6 \text{ GHz}: \geq 22 \text{ mm}$

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

* When zoom scan is required and the *reported* SAR from the *area scan based 1-g SAR estimation* procedures of KDB 447498 is $\leq 1.4 \text{ W/kg}$, $\leq 8 \text{ mm}$, $\leq 7 \text{ mm}$ and $\leq 5 \text{ mm}$ zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

3.3. Description of interpolation/extrapolation scheme

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimise measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is using to determinate this highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1 mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10 grams and 1 gram requires a very fine resolution in the three dimensional scanned data array.

3.4. Volumetric Scan

The volumetric scan consists to a full 3D scan over a specific area. This 3D scan is useful form multi Tx SAR measurement. Indeed, it is possible with OpenSAR to add, point by point, several volumetric scan to calculate the SAR value of the combined measurement as it is define in the standard IEEE1528 and IEC62209.

3.5. Power Drift

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In OpenSAR measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in V/m. If the power drifts more than $\pm 5\%$, the SAR will be retested.


4. System Verification Procedure

4.1. Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% of weight)	Head Tissue									
	750	835	900	1800	1900	2000	2450	2600	5200	5800
Frequency Band (MHz)										
Water	34.40	34.40	34.40	55.36	55.36	57.87	57.87	57.87	65.53	65.53
NaCl	0.79	0.79	0.79	0.35	0.35	0.16	0.16	0.16	0.00	0.00
1,2-Propanediol	64.81	64.81	64.81	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Triton X-100	0.00	0.00	0.00	30.45	30.45	19.97	19.97	19.97	24.24	24.24
DGBE	0.00	0.00	0.00	13.84	13.84	22.00	22.00	22.00	10.23	10.23

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid depth from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm.

Photo of Liquid depth for Head Position	Photo of Liquid depth for Body Position
	

4.1.1. Tissue Dielectric Parameter Check Results

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine of the dielectric parameter are within the tolerances of the specified target values. The measured conductivity and relative permittivity should be within $\pm 5\%$ of the target values.


Tissue Type	Measured Frequency (MHz)	Target Tissue		Measured Tissue		Liquid Temp.	Test Date
		$\epsilon_r (\pm 5\%)$	$\sigma \text{ (S/m)} (\pm 5\%)$	ϵ_r	$\sigma \text{ (S/m)}$		
Head 750	750	41.96 (39.86~44.06)	0.89 (0.85~0.93)	40.28	0.89	21.5 °C	Aug. 18, 2023
Head 850	835	41.50 (39.43~43.58)	0.90 (0.86~0.95)	41.97	0.92	21.5 °C	Aug. 21, 2023
Head 1800	1800	40.00 (38.00~42.00)	1.40 (1.33~1.47)	39.91	1.38	21.7 °C	Aug. 22, 2023
Head 1900	1900	40.00 (38.00~42.00)	1.40 (1.33~1.47)	38.23	1.43	21.5 °C	Aug. 24, 2023
Head 2450	2450	39.20 (37.24~41.16)	1.80 (1.71~1.89)	37.61	1.77	21.5 °C	Aug. 16, 2023
Head 2600	2600	39.01 (37.06~40.96)	1.96 (1.86~2.06)	38.03	1.95	21.4 °C	Aug. 17, 2023
Head 5200	5200	36.00 (34.20~37.80)	4.66 (4.43~4.89)	34.75	4.58	21.5 °C	Aug. 23, 2023
Head 5800	5800	35.30 (33.54~37.07)	5.27 (5.01~5.53)	34.38	5.21	21.9 °C	Aug. 14, 2023

NOTE: The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 °C of the conditions expected during the SAR evaluation to satisfy protocol requirements.

4.2. System Verification Procedure

The system verification is performed for verifying the accuracy of the complete measurement system and performance of the software. The dipole is connected to the signal source consisting of signal generator and amplifier via a directional coupler, N-connector cable and adaption to SMA. It is fed with a power of 100mW (below 5GHz) or 100mW (above 5GHz). To adjust this power a power meter is used. The power sensor is connected to the cable before the system verification to measure the power at this point and do adjustments at the signal generator. At the outputs of the directional coupler both return loss as well as forward power are controlled during the system verification to make sure that emitted power at the dipole is kept constant. This can also be checked by the power drift measurement after the test (result on plot).

The system verification is shown as below picture:



4.2.1. System Verification Results

Comparing to the original SAR value provided by SATIMO, the verification data should be within its specification of $\pm 10\%$. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance verification can meet the variation criterion and the plots can be referred to Appendix B of this report.

System Verification	Target SAR (1W)		Measured SAR		Liquid Temp.	Delta (%)		Test Date
	(±10%)		(Normalized to 1W)			1-g (±10%)	10-g (±10%)	
	1-g (W/Kg)	10-g (W/Kg)	1-g (W/Kg)	10-g (W/Kg)				
750MHz	8.53 (7.68~9.38)	5.56 (5.01~6.11)	8.71	5.99	21.5 °C	2.11%	7.73%	Aug. 18, 2023
835MHz	9.84 (8.86~10.82)	6.22 (5.60~6.84)	9.74	6.20	21.5 °C	-1.02%	-0.32%	Aug. 21, 2023
1800MHz	37.96 (34.17~41.75)	19.81 (17.83~21.79)	37.09	19.23	21.7 °C	-2.29%	-2.93%	Aug. 22, 2023
1900MHz	40.37 (36.34~44.40)	20.48 (18.44~22.52)	44.13	21.71	21.5 °C	9.31%	6.01%	Aug. 24, 2023
2450MHz	53.69 (48.33~59.05)	23.94 (21.55~26.33)	54.11	22.29	21.5 °C	0.78%	-5.35%	Aug. 16, 2023
2600MHz	55.83 (50.25~61.41)	24.19 (21.78~26.60)	55.45	23.37	21.4 °C	-0.68%	-3.39%	Aug. 17, 2023
5200MHz	162.34 (146.11~178.57)	55.42 (49.88~60.96)	159.88	60.74	21.5 °C	-1.52%	9.60%	Aug. 23, 2023
5800MHz	178.89 (161.01~196.77)	59.32 (53.39~65.25)	176.52	55.20	21.9 °C	-1.32%	-6.95%	Aug. 14, 2023

5. SAR Measurement variability and uncertainty

5.1. SAR measurement variability

Per KDB865664 D01 SAR measurement 100 MHz to 6 GHz, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

5.2. SAR measurement uncertainty

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

6. RF Exposure Positions

6.1. Ear and handset reference point

Figure 6.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled “M”, the left ear reference point (ERP) is marked “LE”, and the right ERP is marked —RE



Fig 6.1.1 Front, back, and side views of SAM phantom

6.2. Definition of the cheek position

1. Define two imaginary lines on the handset, the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset: the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 6.2.1 and Figure 6.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 6.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 6.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
2. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
3. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP
4. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
5. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.

6. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 6.2.3. The actual rotation angles should be documented in the test report.




Fig 6.2.1 Handset vertical and horizontal reference lines—fixed case




Fig 6.2.2 Handset vertical and horizontal reference lines—“clam-shell case”




Fig 6.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

6.3. Definition of the tilt position

1. While maintaining the orientation of the handset, retract the handset parallel to the reference plane far enough away from the phantom to enable a rotation of the device by 15 degree.
2. Rotate the Handset around the horizontal line by 15 degree (see Figure 6.3.1).
3. While maintaining the orientation of the handset, move the handset towards the phantom on a line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact is on the pinna. If the contact is at any location other than the pinna, e.g., the antenna with the back of the phantom head, the angle of the handset shall be reduced. In this case, the tilt position is obtained if any part of the handset is in contact with the pinna as well as a second part of the handset is in contact with the phantom, e.g., the antenna with the back of the head.




Figure 6.3.1 – Tilt position of the wireless device on the left side of SAM

6.4. Body Worn Accessory

1. Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6.4.1). Per KDB 648474 D04, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $< 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.
2. Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest

spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Figure 6.4.1 – Test positions for body-worn devices

6.5. Wireless Router Devices

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WLAN simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WLAN transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WLAN transmitter according to FCC KDB Publication 447498 D01 publication procedures. The —Portable Hotspot” feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

7. RF Output Power

7.1. GSM Conducted Power

Band GSM850	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up	128	189	251	Tune-up	128	189	251
Frequency (MHz)	(dBm)	824.2	836.4	848.8		824.2	836.4	848.8
GSM (GMSK)	34.00	33.60	33.36	33.51	24.97	24.57	24.33	24.48
GPRS(GMSK,1 Tx slot)	34.00	33.62	33.41	33.51	24.97	24.59	24.38	24.48
GPRS(GMSK,2 Tx slot)	33.50	33.09	32.85	32.95	27.48	27.07	26.83	26.93
GPRS(GMSK,3 Tx slot)	32.00	31.59	31.32	31.48	27.74	27.33	27.06	27.22
GPRS(GMSK,4 Tx slot)	31.00	30.68	30.40	30.52	27.99	27.67	27.39	27.51
EGPRS(8PSK,1 Tx slot)	28.00	27.83	27.63	27.76	18.97	18.80	18.60	18.73
EGPRS(8PSK,2 Tx slot)	27.50	27.15	26.36	26.44	21.48	21.13	20.34	20.42
EGPRS(8PSK,3 Tx slot)	25.00	24.60	24.74	24.59	20.74	20.34	20.48	20.33
EGPRS(8PSK,4 Tx slot)	24.00	23.42	23.16	23.59	20.99	20.41	20.15	20.58

Band GSM1900	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up	512	661	810	Tune-up	512	661	810
Frequency (MHz)	(dBm)	1850.2	1880	1909.8		1850.2	1880	1909.8
GSM (GMSK)	31.50	31.37	31.48	31.47	22.47	22.34	22.45	22.44
GPRS(GMSK,1 Tx slot)	31.50	31.37	31.47	31.48	22.47	22.34	22.44	22.45
GPRS(GMSK,2 Tx slot)	31.50	30.89	31.02	31.04	25.48	24.87	25.00	25.02
GPRS(GMSK,3 Tx slot)	30.00	29.42	29.59	29.62	25.74	25.16	25.33	25.36
GPRS(GMSK,4 Tx slot)	29.00	28.34	28.50	28.56	25.99	25.33	25.49	25.55
EGPRS(8PSK,1 Tx slot)	30.00	29.29	29.64	29.52	20.97	20.26	20.61	20.49
EGPRS(8PSK,2 Tx slot)	29.00	28.28	28.56	28.76	22.98	22.26	22.54	22.74
EGPRS(8PSK,3 Tx slot)	27.00	26.22	26.75	26.92	22.74	21.96	22.49	22.66
EGPRS(8PSK,4 Tx slot)	26.00	25.15	25.19	25.59	22.99	22.14	22.18	22.58

7.2. WCDMA Conducted Power

WCDMA Band 2	Burst-Averaged output Power (dBm)			
Tx Channel	Tune-up (dBm)	9262	9400	9538
Frequency (MHz)		1852.4	1880	1907.6
RMC12.2K	25.50	25.27	25.10	24.99
HSDPA Sub 1	24.50	24.32	24.11	24.02

HSDPA Sub 2	24.00	23.90	23.71	23.61
HSDPA Sub 3	23.00	22.79	22.67	22.50
HSDPA Sub 4	23.00	22.81	22.69	22.60
HSUPA Sub 1	24.00	22.70	23.83	23.80
HSUPA Sub 2	24.50	24.15	24.06	23.82
HSUPA Sub 3	23.00	22.42	22.75	22.66
HSUPA Sub 4	24.50	24.25	24.06	24.01
HSUPA Sub 5	23.50	23.02	23.47	23.39
WCDMA Band 4	Burst-Averaged output Power (dBm)			
Tx Channel	Tune-up (dBm)	1312	1413	1513
Frequency (MHz)		1712.4	1732.6	1752.6
RMC12.2K	25.50	24.92	25.06	25.01
HSDPA Sub 1	24.50	23.98	24.09	24.07
HSDPA Sub 2	24.00	23.60	23.76	23.75
HSDPA Sub 3	23.00	22.47	22.55	22.62
HSDPA Sub 4	23.00	22.23	22.14	22.76
HSUPA Sub 1	24.00	22.29	23.89	23.81
HSUPA Sub 2	24.00	23.81	23.96	23.87
HSUPA Sub 3	23.00	21.91	22.76	22.83
HSUPA Sub 4	24.50	23.95	24.11	24.06
HSUPA Sub 5	23.50	22.62	23.21	23.19
WCDMA Band 5	Burst-Averaged output Power (dBm)			
Tx Channel	Tune-up (dBm)	4132	4182	4233
Frequency (MHz)		826.4	836.4	846.6
RMC12.2K	24.50	24.45	24.32	24.29
HSDPA Sub 1	23.50	23.49	23.36	23.31
HSDPA Sub 2	23.50	23.05	23.05	22.50
HSDPA Sub 3	22.50	22.07	21.70	21.84
HSDPA Sub 4	22.00	21.95	21.87	21.85
HSUPA Sub 1	23.50	21.89	23.25	23.06
HSUPA Sub 2	23.50	23.44	23.26	23.07
HSUPA Sub 3	22.50	21.98	21.96	22.23
HSUPA Sub 4	23.50	23.48	23.35	23.30
HSUPA Sub 5	23.00	22.20	22.71	22.60

7.3. LTE Conducted Power

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18607/1850.7	18900/1880	19193/1909.3
LTE Band 2	1.4MHz	QPSK	1	0	25.00	24.76	24.55	24.17
			1	2	25.00	24.89	24.67	23.96
			1	5	25.00	24.81	24.53	23.71
			3	0	25.00	24.88	24.65	23.83
			3	1	25.00	24.92	24.69	23.82
			3	2	25.00	24.90	24.65	23.81
			6	0	24.00	23.90	23.69	22.85
		16QAM	1	0	24.50	23.99	23.80	22.90
			1	2	24.50	24.07	23.88	23.00
			1	5	24.50	24.00	23.73	22.89
			3	0	24.00	23.76	23.61	22.76
			3	1	24.00	23.84	23.65	22.79
			3	2	24.00	23.80	23.64	22.79
			6	0	23.00	22.99	22.74	21.91
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18615/1851.5	18900/1880	19185/1908.5
LTE Band 2	3MHz	QPSK	1	0	24.50	24.30	24.11	23.78
			1	7	24.50	24.34	24.09	23.73
			1	14	24.50	24.32	24.07	23.73
			8	0	23.50	23.35	23.13	22.80
			8	4	23.50	23.39	23.15	22.83
			8	7	23.50	23.37	23.13	22.78
			15	0	23.50	23.37	23.15	22.81
		16QAM	1	0	24.00	23.57	23.32	22.94
			1	7	24.00	23.49	23.34	22.99
			1	14	24.00	23.56	23.28	22.88
			8	0	22.50	22.42	22.17	21.85
			8	4	22.50	22.42	22.20	21.88
			8	7	22.50	22.41	22.15	21.81
			15	0	22.50	22.35	22.14	21.79
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		

			RB Size	RB Offset		18625/1852.5	18900/1880	19175/1907.5
LTE Band 2	5MHz	QPSK	1	0	24.50	24.20	23.99	23.71
			1	12	24.50	24.35	24.08	23.76
			1	24	24.50	24.24	23.97	23.61
			12	0	23.50	23.36	23.13	22.81
			12	6	23.50	23.43	23.18	22.88
			12	11	23.50	23.37	23.13	22.80
			25	0	23.50	23.39	23.14	22.83
		16QAM	1	0	24.00	23.36	23.28	23.01
			1	12	24.00	23.52	23.26	22.90
			1	24	24.00	23.58	23.24	22.83
			12	0	22.50	22.33	22.09	21.80
			12	6	22.50	22.39	22.15	21.85
			12	11	22.50	22.36	22.11	21.77
			25	0	22.50	22.39	22.12	21.82
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18650/1855	18900/1880	19150/1905
LTE Band 2	10MHz	QPSK	1	0	24.50	24.28	24.09	23.91
			1	24	24.50	24.46	24.19	23.92
			1	49	24.50	24.34	24.03	23.68
			25	0	24.00	23.46	23.21	22.98
			25	12	24.00	23.46	23.20	22.94
			25	24	24.00	23.50	23.20	22.92
			50	0	23.50	23.47	23.23	22.96
		16QAM	1	0	24.00	23.47	23.32	23.10
			1	24	24.00	23.65	23.48	23.12
			1	49	24.00	23.57	23.19	22.83
			25	0	22.50	22.45	22.19	21.97
			25	12	22.50	22.46	22.17	21.91
			25	24	22.50	22.49	22.19	21.89
			50	0	22.50	22.47	22.19	21.95
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18675/1857.5	18900/1880	19125/1902.5
LTE Band	15MHz	QPSK	1	0	24.50	24.23	24.09	23.98
			1	37	24.50	24.37	24.08	23.89

2			1	74	24.50	24.23	23.97	23.64
			36	0	23.50	23.45	23.19	23.08
			36	18	23.50	23.45	23.18	22.97
			36	37	23.50	23.46	23.17	22.91
			75	0	23.50	23.46	23.20	23.00
		16QAM	1	0	24.00	23.46	23.29	23.20
			1	37	24.00	23.71	23.26	23.18
			1	74	24.00	23.44	23.23	22.88
			36	0	22.50	22.42	22.12	22.03
			36	18	22.50	22.43	22.12	21.91
			36	37	22.50	22.44	22.10	21.85
			75	0	22.50	22.44	22.16	21.97
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		18700/1860	18900/1880	19100/1900
LTE Band 2	20MHz	QPSK	1	0	24.50	24.08	24.02	23.95
			1	49	24.50	24.42	24.15	24.00
			1	99	24.50	23.94	23.83	23.50
			50	0	23.50	23.42	23.21	23.18
			50	24	23.50	23.47	23.22	23.07
			50	49	23.50	23.47	23.17	22.93
			100	0	23.50	23.43	23.18	23.03
		16QAM	1	0	24.00	23.35	23.20	23.09
			1	49	24.00	23.68	23.43	23.27
			1	99	24.00	23.23	22.99	22.70
			50	0	22.50	22.40	22.19	22.14
			50	24	22.50	22.44	22.18	22.01
			50	49	22.50	22.45	22.15	21.91
			100	0	22.50	22.41	22.14	22.00

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		19957/1710.7	20175/1732.5	20393/1754.3
LTE Band 4	1.4MHz	QPSK	1	0	24.00	23.53	23.85	23.76
			1	2	24.00	23.65	23.93	23.88
			1	5	24.00	23.55	23.83	23.80
			3	0	24.00	23.62	23.93	23.88
			3	1	24.00	23.67	23.93	23.87

				3	2	24.00	23.64	23.90	23.87
				6	0	23.00	22.65	22.95	22.90
				1	0	23.50	22.64	23.05	22.90
				1	2	23.50	22.81	23.18	23.16
				1	5	23.50	22.69	23.07	22.97
				3	0	23.00	22.55	22.82	22.81
				3	1	23.00	22.54	22.91	22.87
				3	2	23.00	22.55	22.84	22.84
				6	0	22.50	21.69	22.03	21.98
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)			
			RB Size	RB Offset		19965/1711.5	20175/1732.5	20385/1753.5	
LTE Band 4	3MHz	QPSK	1	0	24.50	24.17	24.47	24.43	
			1	7	24.50	24.13	24.49	24.16	
			1	14	24.50	24.18	24.46	24.03	
			8	0	24.00	23.19	23.53	22.98	
			8	4	24.00	23.26	23.55	23.10	
			8	7	24.00	23.23	23.52	23.04	
			15	0	24.00	23.24	23.57	22.99	
		16QAM	1	0	24.00	23.30	23.74	23.21	
			1	7	24.00	23.35	23.66	23.20	
			1	14	24.00	23.29	23.57	23.18	
			8	0	23.00	22.19	22.58	22.03	
			8	4	23.00	22.27	22.56	22.09	
			8	7	23.00	22.24	22.55	22.05	
			15	0	23.00	22.19	22.54	21.97	
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)			
			RB Size	RB Offset		19975/1712.5	20175/1732.5	20375/1752.5	
LTE Band 4	5MHz	QPSK	1	0	24.50	23.57	23.93	23.76	
			1	12	24.50	23.71	24.01	23.86	
			1	24	24.50	23.65	23.91	23.76	
			12	0	23.50	22.72	23.06	22.87	
			12	6	23.50	22.80	23.09	22.94	
			12	11	23.50	22.77	23.05	22.93	
			25	0	23.50	22.75	23.07	22.91	
		16QAM	1	0	23.50	22.72	23.18	22.99	
			1	12	23.50	22.90	23.27	23.05	

			1	24	23.50	22.79	23.10	22.95
			12	0	22.50	21.65	22.03	21.88
			12	6	22.50	21.72	22.06	21.91
			12	11	22.50	21.73	22.02	21.89
			25	0	22.50	21.74	22.07	21.92
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20000/1715	20175/1732.5	20350/1750
LTE Band 4	10MHz	QPSK	1	0	24.50	23.69	24.07	23.89
			1	24	24.50	23.91	24.14	23.96
			1	49	24.50	23.89	23.99	23.88
			25	0	23.50	22.89	23.18	23.00
			25	12	23.50	22.92	23.14	22.99
			25	24	23.50	23.03	23.12	23.03
			50	0	23.50	22.95	23.17	23.02
		16QAM	1	0	23.50	22.91	23.21	23.04
			1	24	23.50	23.12	23.30	23.26
			1	49	23.50	23.07	23.15	23.13
			25	0	22.50	21.84	22.17	21.97
			25	12	22.50	21.87	22.12	21.97
			25	24	22.50	21.99	22.10	22.01
			50	0	22.50	21.92	22.17	22.00
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20025/1717.5	20175/1732.5	20325/1747.5
LTE Band 4	15MHz	QPSK	1	0	24.50	23.58	23.95	23.79
			1	37	24.50	23.87	24.07	23.91
			1	74	24.50	23.85	23.92	23.78
			36	0	23.50	22.85	23.15	22.95
			36	18	23.50	22.97	23.12	22.98
			36	37	23.50	23.00	23.10	22.93
			75	0	23.50	22.96	23.12	22.98
		16QAM	1	0	23.50	22.80	23.20	23.03
			1	37	23.50	22.99	23.29	23.19
			1	74	23.50	23.06	23.04	22.96
			36	0	22.50	21.79	22.08	21.90
			36	18	22.50	21.89	22.08	21.95
			36	37	22.50	21.95	22.06	21.89

			75	0	22.50	21.91	22.07	21.94
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20050/1720	20175/1732.5	20300/1745
LTE Band 4	20MHz	QPSK	1	0	24.50	23.38	23.73	23.51
			1	49	24.50	23.97	24.10	23.98
			1	99	24.50	23.70	23.75	23.57
			50	0	23.50	22.90	23.17	22.98
			50	24	23.50	23.00	23.13	22.99
			50	49	23.50	23.06	23.09	22.98
			100	0	23.50	22.95	23.10	22.96
		16QAM	1	0	23.50	22.62	22.95	22.79
			1	49	23.50	23.14	23.35	23.24
			1	99	23.50	22.95	22.93	22.82
			50	0	22.50	21.86	22.13	22.25
			50	24	22.50	21.97	22.11	22.44
			50	49	22.50	22.03	22.08	22.47
			100	0	22.50	21.91	22.08	22.40

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20407/824.7	20525/836.5	20643/848.3
LTE Band 5	1.4MHz	QPSK	1	0	24.50	23.95	24.14	24.00
			1	2	24.50	24.07	24.24	24.10
			1	5	24.50	23.96	24.12	23.95
			3	0	24.50	24.01	24.20	24.05
			3	1	24.50	24.06	24.25	24.07
			3	2	24.50	24.04	24.19	24.04
			6	0	23.50	23.01	23.23	23.05
		16QAM	1	0	23.50	23.27	23.47	23.32
			1	2	23.50	23.42	23.48	23.36
			1	5	23.50	23.31	23.44	23.21
			3	0	23.50	23.05	23.22	23.07
			3	1	23.50	22.98	23.20	23.08
			3	2	23.50	23.05	23.15	23.06
			6	0	22.50	22.16	22.34	22.19
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		

			RB Size	RB Offset		20415/825.5	20525/836.5	20635/847.5
LTE Band 5	3MHz	QPSK	1	0	24.50	23.97	24.20	24.12
			1	7	24.50	24.02	24.20	24.04
			1	14	24.50	24.04	24.24	24.04
			8	0	23.50	23.00	23.24	23.14
			8	4	23.50	23.09	23.30	23.13
			8	7	23.50	23.06	23.24	23.07
			15	0	23.50	23.02	23.24	23.10
		16QAM	1	0	24.00	23.36	23.43	23.38
			1	7	24.00	23.30	23.45	23.42
			1	14	24.00	23.34	23.56	23.39
			8	0	22.50	22.10	22.27	22.21
			8	4	22.50	22.13	22.35	22.19
			8	7	22.50	22.08	22.33	22.16
			15	0	22.50	22.02	22.29	22.13
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20425/826.5	20525/836.5	20625/846.5
LTE Band 5	5MHz	QPSK	1	0	24.50	23.92	24.08	24.02
			1	12	24.50	24.05	24.19	24.10
			1	24	24.50	23.96	24.11	23.93
			12	0	23.50	23.01	23.22	23.20
			12	6	23.50	23.12	23.32	23.17
			12	11	23.50	23.05	23.28	23.05
			25	0	23.50	23.04	23.26	23.14
		16QAM	1	0	24.00	23.22	23.42	23.28
			1	12	24.00	23.31	23.54	23.33
			1	24	24.00	23.17	23.49	23.25
			12	0	22.50	22.00	22.23	22.19
			12	6	22.50	22.09	22.30	22.15
			12	11	22.50	22.06	22.24	22.05
			25	0	22.50	22.06	22.29	22.16
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20450/829	20525/836.5	20600/844
LTE Band	10MHz	QPSK	1	0	24.50	24.00	24.17	24.27
			1	24	24.50	24.19	24.33	24.22

5			1	49	24.50	24.15	24.18	24.05
			25	0	23.50	23.14	23.28	23.31
			25	12	23.50	23.12	23.31	23.23
			25	24	23.50	23.18	23.32	23.09
			50	0	23.50	23.18	23.33	23.21
		16QAM	1	0	24.00	23.31	23.37	23.60
			1	24	24.00	23.36	23.56	23.37
			1	49	24.00	23.49	23.49	23.35
			25	0	22.50	22.12	22.30	22.29
			25	12	22.50	22.13	22.35	22.23
			25	24	22.50	22.19	22.34	22.12
			50	0	22.50	22.17	22.37	22.23

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20775/2502.5	21100/2535	21425/2567.5
LTE Band 7	5MHz	QPSK	1	0	25.50	25.06	24.68	24.54
			1	12	25.50	25.01	24.70	24.64
			1	24	25.50	24.94	24.65	24.63
			12	0	24.50	24.07	23.75	23.68
			12	6	24.50	24.08	23.77	23.73
			12	11	24.50	24.03	23.73	23.72
			25	0	24.50	24.09	23.76	23.72
		16QAM	1	0	24.50	24.14	23.92	23.74
			1	12	24.50	24.22	23.82	23.77
			1	24	24.50	24.13	23.92	23.91
			12	0	23.50	23.02	22.72	22.62
			12	6	23.50	23.04	22.74	22.69
			12	11	23.50	22.98	22.71	22.67
			25	0	23.50	23.06	22.77	22.70
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		20800/2505	21100/2535	21400/2565
LTE Band 7	10MHz	QPSK	1	0	25.50	25.18	24.86	24.62
			1	24	25.50	25.09	24.81	24.66
			1	49	25.50	25.07	24.81	24.75
			25	0	24.50	24.18	23.85	23.69
			25	12	24.50	24.11	23.85	23.71

				25	24	24.50	24.15	23.92	23.81
				50	0	24.50	24.17	23.91	23.78
				1	0	24.50	24.33	24.11	23.88
				1	24	24.50	24.19	24.01	23.96
				1	49	24.50	24.31	23.98	23.98
				25	0	23.50	23.16	22.83	22.67
				25	12	23.50	23.09	22.83	22.70
				25	24	23.50	23.12	22.90	22.79
				50	0	23.50	23.18	22.88	22.76
				RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
Band	Band Width	Modulation		RB Size	RB Offset		20825/2507.5	21100/2535	21375/2562.5
LTE Band 7	15MHz	QPSK		1	0	25.50	25.11	24.84	24.54
				1	37	25.50	25.05	24.75	24.57
				1	74	25.50	25.00	24.74	24.63
				36	0	24.50	24.12	23.85	23.67
				36	18	24.50	24.11	23.90	23.68
				36	37	24.50	24.14	23.90	23.78
				75	0	24.50	24.13	23.90	23.69
		16QAM		1	0	24.50	24.25	24.07	23.90
				1	37	24.50	24.16	23.98	23.86
				1	74	24.50	24.30	24.02	23.86
				36	0	23.50	23.05	22.79	22.63
				36	18	23.50	23.06	22.83	22.64
				36	37	23.50	23.07	22.86	22.72
				75	0	23.50	23.09	22.87	22.68
Band	Band Width	Modulation		RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
				RB Size	RB Offset		20850/2510	21100/2535	21350/2560
LTE Band 7	20MHz	QPSK		1	0	25.50	24.95	24.79	24.49
				1	49	25.50	25.08	24.86	24.66
				1	99	25.50	24.81	24.59	24.47
				50	0	24.50	24.10	23.83	23.72
				50	24	24.50	24.14	23.92	23.68
				50	49	24.50	24.18	23.93	23.72
				100	0	24.50	24.10	23.88	23.72
		16QAM		1	0	24.50	24.04	24.08	23.68
				1	49	24.50	24.41	24.15	23.96

			1	99	24.50	24.13	23.77	23.61
			50	0	23.50	23.07	22.81	22.73
			50	24	23.50	23.09	22.89	22.69
			50	49	23.50	23.16	22.89	22.70
			100	0	23.50	23.10	22.86	22.72

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23017/699.7	23095/707.5	23173/715.3
LTE Band 12	1.4MHz	QPSK	1	0	25.00	24.46	24.34	24.33
			1	2	25.00	24.63	24.45	24.46
			1	5	25.00	24.44	24.27	24.34
			3	0	25.00	24.59	24.40	24.44
			3	1	25.00	24.62	24.41	24.48
			3	2	25.00	24.56	24.38	24.45
		16QAM	6	0	24.00	23.56	23.40	23.43
			1	0	24.00	23.81	23.63	23.46
			1	2	24.00	23.82	23.64	23.79
			1	5	24.00	23.74	23.60	23.61
			3	0	24.00	23.60	23.35	23.44
			3	1	24.00	23.61	23.41	23.43
			3	2	24.00	23.56	23.35	23.40
			6	0	23.00	22.70	22.47	22.53
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23025/700.5	23095/707.5	23165/714.5
LTE Band 12	3MHz	QPSK	1	0	24.50	24.49	24.29	24.32
			1	7	24.50	24.45	24.29	24.31
			1	14	24.50	24.40	24.25	24.34
			8	0	23.50	23.43	23.32	23.33
			8	4	23.50	23.47	23.33	23.40
			8	7	23.50	23.41	23.27	23.32
			15	0	23.50	23.40	23.31	23.32
		16QAM	1	0	24.00	23.66	23.52	23.61
			1	7	24.00	23.79	23.64	23.63
			1	14	24.00	23.75	23.53	23.48
			8	0	23.00	22.55	22.44	22.38
			8	4	23.00	22.53	22.43	22.43

			8	7	23.00	22.53	22.36	22.41
			15	0	22.50	22.46	22.35	22.32
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23035/701.5	23095/707.5	23155/713.5
LTE Band 12	5MHz	QPSK	1	0	24.50	24.36	24.22	24.20
			1	12	24.50	24.45	24.33	24.34
			1	24	24.50	24.26	24.19	24.23
			12	0	23.50	23.40	23.35	23.27
			12	6	23.50	23.49	23.33	23.37
			12	11	23.50	23.45	23.22	23.32
			25	0	23.50	23.43	23.27	23.30
		16QAM	1	0	24.00	23.59	23.54	23.53
			1	12	24.00	23.76	23.65	23.58
			1	24	24.00	23.60	23.51	23.43
			12	0	23.00	22.43	22.36	22.29
			12	6	23.00	22.52	22.37	22.37
			12	11	23.00	22.46	22.25	22.34
			25	0	22.50	22.49	22.31	22.33
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23060/704	23095/707.5	23130/711
LTE Band 12	10MHz	QPSK	1	0	25.00	24.52	24.39	24.33
			1	24	25.00	24.44	24.34	24.38
			1	49	25.00	24.24	24.29	24.31
			25	0	24.00	23.37	23.38	23.50
			25	12	24.00	23.39	23.32	23.30
			25	24	24.00	23.29	23.24	23.42
			50	0	23.50	23.35	23.32	23.46
		16QAM	1	0	24.00	23.78	23.75	23.65
			1	24	24.00	23.69	23.61	23.58
			1	49	24.00	23.56	23.58	23.52
			25	0	23.00	22.39	22.39	22.53
			25	12	23.00	22.42	22.35	22.34
			25	24	23.00	22.33	22.27	22.40
			50	0	22.50	22.36	22.34	22.45

Band	Band	Modulation	RB	Tune-up	Channel/Frequency(MHz)
------	------	------------	----	---------	------------------------

	Width		Configuration		(dBm)			
			RB Size	RB Offset		23205/779.5	23230/782	23255/784.5
LTE Band 13	5MHz	QPSK	1	0	24.50	24.35	24.29	24.25
			1	12	24.50	24.40	24.34	24.29
			1	24	24.50	24.21	24.14	24.11
			12	0	23.50	23.38	23.38	23.37
			12	6	23.50	23.49	23.40	23.35
			12	11	23.50	23.40	23.35	23.25
			25	0	23.50	23.41	23.34	23.31
		16QAM	1	0	24.00	23.58	23.62	23.47
			1	12	24.00	23.80	23.65	23.54
			1	24	24.00	23.47	23.40	23.46
			12	0	23.00	22.41	22.37	22.36
			12	6	23.00	22.51	22.43	22.37
			12	11	23.00	22.45	22.35	22.26
			25	0	22.50	22.44	22.37	22.34
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		N/A	23230/782	N/A
LTE Band 13	10MHz	QPSK	1	0	24.50	N/A	24.45	N/A
			1	24	24.50	N/A	24.45	N/A
			1	49	24.50	N/A	24.21	N/A
			25	0	23.50	N/A	23.41	N/A
			25	12	23.50	N/A	23.42	N/A
			25	24	23.50	N/A	23.31	N/A
			50	0	23.50	N/A	23.33	N/A
		16QAM	1	0	24.00	N/A	23.75	N/A
			1	24	24.00	N/A	23.67	N/A
			1	49	24.00	N/A	23.54	N/A
			25	0	22.50	N/A	22.43	N/A
			25	12	22.50	N/A	22.43	N/A
			25	24	22.50	N/A	22.34	N/A
			50	0	22.50	N/A	22.36	N/A

Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23755/706.5	23790/710	23825/713.5

LTE Band 17	5MHz	QPSK	1	0	24.50	24.32	24.30	24.28
			1	12	24.50	24.34	24.35	24.30
			1	24	24.50	24.24	24.33	24.27
			12	0	23.50	23.36	23.44	23.32
			12	6	23.50	23.39	23.39	23.40
			12	11	23.50	23.29	23.35	23.35
			25	0	23.50	23.36	23.39	23.37
		16QAM	1	0	24.00	23.65	23.58	23.64
			1	12	24.00	23.60	23.69	23.55
			1	24	24.00	23.59	23.50	23.46
			12	0	22.50	22.40	22.43	22.31
			12	6	22.50	22.42	22.39	22.37
			12	11	22.50	22.29	22.34	22.35
			25	0	22.50	22.39	22.40	22.35
Band	Band Width	Modulation	RB Configuration		Tune-up (dBm)	Channel/Frequency(MHz)		
			RB Size	RB Offset		23780/709	23790/710	23800/711
LTE Band 17	10MHz	QPSK	1	0	25.00	24.40	24.35	24.37
			1	24	25.00	24.50	24.46	24.50
			1	49	25.00	24.34	24.33	24.33
			25	0	24.00	23.52	23.55	23.58
			25	12	24.00	23.41	23.43	23.45
			25	24	24.00	23.42	23.46	23.50
			50	0	24.00	23.47	23.54	23.52
		16QAM	1	0	24.00	23.60	23.63	23.59
			1	24	24.00	23.72	23.68	23.71
			1	49	24.00	23.52	23.58	23.55
			25	0	23.00	22.54	22.60	22.57
			25	12	23.00	22.41	22.44	22.44
			25	24	23.00	22.42	22.47	22.47
			50	0	23.00	22.49	22.54	22.53

7.4. WLAN & Bluetooth Output Power

Mode	Channel	Frequency (MHz)	Tune-up (dBm)	Output Power (dBm)
802.11b	1	2412	16.00	15.57
	6	2437	16.00	15.22
	11	2462	16.00	15.43
802.11g	1	2412	13.50	13.32
	6	2437	13.50	13.36
	11	2462	13.50	13.17
802.11n HT20	1	2412	11.50	11.19
	6	2437	11.50	11.36
	11	2462	11.50	10.94
802.11n HT40	3	2422	10.50	10.36
	6	2437	10.50	10.33
	9	2452	10.50	10.16

NOTE: Power measurement results of WLAN 2.4G.

Mode	Channel	Frequency (MHz)	Tune-up (dBm)	Output Power (dBm)
802.11a	36	5180	11.00	10.54
	40	5200	11.00	9.88
	48	5240	11.00	9.84
802.11n HT20	36	5180	10.50	10.37
	40	5200	10.50	10.05
	48	5240	10.50	10.06
802.11n HT40	38	5190	10.50	10.06
	46	5230	10.50	9.47
802.11ac VHT20	36	5180	11.00	10.55
	40	5200	11.00	10.09
	48	5240	11.00	10.08
802.11ac VHT40	38	5190	10.00	9.99
	46	5230	10.00	9.51
802.11ac VHT80	42	5210	10.00	9.97

NOTE: Power measurement results of WLAN 5.2G.

Mode	Channel	Frequency (MHz)	Tune-up (dBm)	Output Power (dBm)
------	---------	-----------------	---------------	--------------------

802.11a	149	5745	11.50	10.67
	157	5785	11.50	11.13
	165	5825	11.50	11.38
802.11n HT20	149	5745	11.50	10.70
	157	5785	11.50	10.93
	165	5825	11.50	11.30
802.11n HT40	151	5755	11.50	10.85
	159	5795	11.50	11.09
802.11ac VHT20	149	5745	11.50	10.65
	157	5785	11.50	11.17
	165	5825	11.50	11.25
802.11ac VHT40	151	5755	11.50	10.86
	159	5795	11.50	11.06
802.11ac VHT80	155	5775	11.50	11.13


NOTE: Power measurement results of WLAN 5.8G.

BR+EDR	Output Power (dBm)				
	Data Rates	Tune-up (dBm)	Channel		
			0CH	39CH	78CH
	1M	9.00	7.01	7.75	8.04
	2M	9.00	7.88	8.16	8.37
	3M	9.00	8.05	8.82	8.99

BLE	Channel	Tune-up (dBm)	Output Power (dBm)	
			1M	2M
	0CH	-3.00	-3.50	-4.51
	19CH	-3.00	-3.94	-3.95
	39CH	-3.00	-3.70	-3.92

NOTE: Power measurement results of Bluetooth.

8. Antenna Location



Note: Since the confidentiality request of EUT, the antenna location example diagram see as above.

Distance of the Antenna to the EUT surface/edge						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
WWAN Main ANT	≤ 25mm	≤ 25mm	≤ 25mm	≤ 25mm	> 25mm	≤ 25mm
WLAN & Bluetooth	≤ 25mm	≤ 25mm	> 25mm	≤ 25mm	≤ 25mm	>25mm
Positions for SAR tests						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
WWAN Main ANT	Yes	Yes	Yes	Yes	NO	Yes
WLAN & Bluetooth	Yes	Yes	NO	Yes	Yes	NO

9. Stand-alone SAR test exclusion

Refer to FCC KDB 447498D01, the 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$$

- $f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	P _{max} (dBm)	P _{max} (mW)	Distance (mm)	f (GHz)	Calculation Result	SAR Exclusion threshold	SAR test exclusion
------	---------------------------	--------------------------	------------------	------------	-----------------------	----------------------------	-----------------------

Bluetooth	9.00	7.94	5	2.480	2.49	3	Yes
-----------	------	------	---	-------	------	---	-----

NOTE: Standalone SAR test exclusion for Bluetooth.

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{f_{\text{(GHz)}}}/x] \text{ W/kg}$$
 for test separation distances $\leq 50\text{mm}$, where $x = 7.5$ for 1-g SAR and $x = 18.75$ for 10-g SAR.

When the minimum test separation distance is $< 5 \text{ mm}$, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	Position	P_{max} (dBm)	P_{max} (mW)	Distance (mm)	f (GHz)	x	Estimated SAR (W/Kg)
Bluetooth	Head	9.00	7.94	5	2.48	7.5	0.332
Bluetooth	Body	9.00	7.94	10	2.48	7.5	0.166
Bluetooth	Hotspot	9.00	7.94	10	2.48	7.5	0.166

NOTE: Estimated SAR calculation for Bluetooth

10. SAR Results

10.1. SAR measurement Result

10.1.1. SAR measurement Result of GSM850

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Left Cheek	189/836.4	GPRS(GMSK 4TS)	0.750	0.570	0.18	30.40	31.00	0.861	2023/8/21	1#
Left Tilt 15 Degree	189/836.4	GPRS(GMSK 4TS)	0.436	0.325	-2.24	30.40	31.00	0.501	2023/8/21	
Right Cheek	189/836.4	GPRS(GMSK 4TS)	0.711	0.524	-2.87	30.40	31.00	0.816	2023/8/21	
Right Tilt 15 Degree	189/836.4	GPRS(GMSK 4TS)	0.349	0.263	0.76	30.40	31.00	0.401	2023/8/21	
Left Cheek	128/824.2	GPRS(GMSK 4TS)	0.725	0.542	3.65	30.68	31.00	0.780	2023/8/21	
Left	251/848.8	GPRS(GMSK	0.740	0.560	1.48	30.52	31.00	0.826	2023/8/21	

Cheek		4TS)								
Left Cheek Repeated	189/836.4	GPRS(GMSK 4TS)	0.748	0.564	2.21	30.40	31.00	0.859	2023/8/21	

NOTE: Head SAR test results of GSM850.

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	189/836.4	GPRS(GMSK 4TS)	0.408	0.244	-1.83	30.40	31.00	0.468	2023/8/21	
Back Side	189/836.4	GPRS(GMSK 4TS)	0.672	0.415	2.51	30.40	31.00	0.772	2023/8/21	2#

NOTE: Body-Worn SAR test results of GSM850

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	189/836.4	GPRS(GMSK 4TS)	0.408	0.244	-1.83	30.40	31.00	0.468	2023/8/21	
Back Side	189/836.4	GPRS(GMSK 4TS)	0.672	0.415	2.51	30.40	31.00	0.772	2023/8/21	2#
Left Side	189/836.4	GPRS(GMSK 4TS)	0.204	0.125	0.70	30.40	31.00	0.234	2023/8/21	
Right Side	189/836.4	GPRS(GMSK 4TS)	0.210	0.127	-3.21	30.40	31.00	0.241	2023/8/21	
Bottom Side	189/836.4	GPRS(GMSK 4TS)	0.350	0.216	-1.91	30.40	31.00	0.402	2023/8/21	

NOTE: Hotspot SAR test results of GSM850

10.1.2. SAR measurement Result of GSM1900

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Left Cheek	661/1880	GPRS(GMSK 4TS)	0.180	0.098	-1.43	28.50	29.00	0.202	2023/8/24	3#
Left Tilt 15 Degree	661/1880	GPRS(GMSK 4TS)	0.099	0.053	-0.91	28.50	29.00	0.111	2023/8/24	

Right Cheek	661/1880	GPRS(GMSK 4TS)	0.165	0.090	0.14	28.50	29.00	0.185	2023/8/24	
Right Tilt 15 Degree	661/1880	GPRS(GMSK 4TS)	0.074	0.038	3.81	28.50	29.00	0.083	2023/8/24	

NOTE: Head SAR test results of GSM1900

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	661/1880	GPRS(GMSK 4TS)	0.222	0.114	-0.20	28.50	29.00	0.249	2023/8/24	
Back Side	661/1880	GPRS(GMSK 4TS)	0.338	0.181	-0.15	28.50	29.00	0.379	2023/8/24	4#

NOTE: Body-Worn SAR test results of GSM1900

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	661/1880	GPRS(GMSK 4TS)	0.222	0.114	-0.20	28.50	29.00	0.249	2023/8/24	
Back Side	661/1880	GPRS(GMSK 4TS)	0.338	0.181	-0.15	28.50	29.00	0.379	2023/8/24	4#
Left Side	661/1880	GPRS(GMSK 4TS)	0.105	0.056	2.12	28.50	29.00	0.118	2023/8/24	
Right Side	661/1880	GPRS(GMSK 4TS)	0.108	0.057	1.62	28.50	29.00	0.121	2023/8/24	
Bottom Side	661/1880	GPRS(GMSK 4TS)	0.175	0.092	-3.62	28.50	29.00	0.196	2023/8/24	

NOTE: Hotspot SAR test results of GSM1900

10.1.3. SAR measurement Result of WCDMA Band 2

Test Position of Head	Test channel /Freq	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Left Cheek	9400/1880	RMC12.2K	0.297	0.168	-0.59	25.10	25.50	0.326	2023/8/24	5#

NOTE: Head SAR test results of WCDMA Band 2

NOTE: Body-Worn SAR test results of WCDMA Band 2

NOTE: Hotspot SAR test results of WCDMA Band 2

Test Position of Head	Test channel /Freq	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						

Left Cheek	1413/1732.6	RMC12.2K	0.178	0.106	-1.45	25.06	25.50	0.197	2023/8/22	7#
Left Tilt 15 Degree	1413/1732.6	RMC12.2K	0.097	0.057	-2.41	25.06	25.50	0.107	2023/8/22	
Right Cheek	1413/1732.6	RMC12.2K	0.157	0.092	3.05	25.06	25.50	0.174	2023/8/22	
Right Tilt 15 Degree	1413/1732.6	RMC12.2K	0.073	0.042	0.05	25.06	25.50	0.081	2023/8/22	

NOTE: Head SAR test results of WCDMA Band 4

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	1413/1732.6	RMC12.2K	0.186	0.099	1.62	25.06	25.50	0.206	2023/8/22	
Back Side	1413/1732.6	RMC12.2K	0.294	0.158	1.66	25.06	25.50	0.325	2023/8/22	8#

NOTE: Body-Worn SAR test results of WCDMA Band 4

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	1413/1732.6	RMC12.2K	0.186	0.099	1.62	25.06	25.50	0.206	2023/8/22	
Back Side	1413/1732.6	RMC12.2K	0.294	0.153	1.66	25.06	25.50	0.325	2023/8/22	8#
Left Side	1413/1732.6	RMC12.2K	0.093	0.048	-1.79	25.06	25.50	0.103	2023/8/22	
Right Side	1413/1732.6	RMC12.2K	0.099	0.051	-1.07	25.06	25.50	0.110	2023/8/22	
Bottom Side	1413/1732.6	RMC12.2K	0.150	0.081	3.17	25.06	25.50	0.166	2023/8/22	

NOTE: Hotspot SAR test results of WCDMA Band 4

10.1.5. SAR measurement Result of WCDMA Band 5

Test Position of Head	Test channel /Freq	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Left Cheek	4182/836.4	RMC12.2K	0.467	0.348	1.21	24.32	24.50	0.487	2023/8/21	9#
Left Tilt 15 Degree	4182/836.4	RMC12.2K	0.248	0.185	2.89	24.32	24.50	0.258	2023/8/21	
Right Cheek	4182/836.4	RMC12.2K	0.439	0.311	-0.82	24.32	24.50	0.458	2023/8/21	
Right Tilt 15 Degree	4182/836.4	RMC12.2K	0.239	0.176	-0.52	24.32	24.50	0.249	2023/8/21	

NOTE: Head SAR test results of WCDMA Band 5

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
Front Side	4182/836.4	RMC12.2K	0.234	0.174	3.58	24.32	24.50	0.244	2023/8/21	
Back Side	4182/836.4	RMC12.2K	0.380	0.292	-3.10	24.32	24.50	0.396	2023/8/21	10#

NOTE: Body-Worn SAR test results of WCDMA Band 5

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	4182/836.4	RMC12.2K	0.234	0.174	3.58	24.32	24.50	0.244	2023/8/21	
Back Side	4182/836.4	RMC12.2K	0.380	0.292	-3.10	24.32	24.50	0.396	2023/8/21	10#
Left Side	4182/836.4	RMC12.2K	0.126	0.097	-1.12	24.32	24.50	0.131	2023/8/21	
Right Side	4182/836.4	RMC12.2K	0.129	0.098	1.11	24.32	24.50	0.134	2023/8/21	
Bottom Side	4182/836.4	RMC12.2K	0.210	0.158	3.32	24.32	24.50	0.219	2023/8/21	

NOTE: Hotspot SAR test results of WCDMA Band 5

10.1.6. SAR measurement Result of LTE Band 2

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Left Cheek	18900/1880	20M QPSK(1,49)	0.471	0.289	2.79	24.15	24.50	0.511	2023/8/24	17#
Left Tilt 15 Degree	18900/1880	20M QPSK(1,49)	0.247	0.144	0.95	24.15	24.50	0.268	2023/8/24	
Right Cheek	18900/1880	20M QPSK(1,49)	0.436	0.257	-1.54	24.15	24.50	0.473	2023/8/24	
Right Tilt 15 Degree	18900/1880	20M QPSK(1,49)	0.211	0.123	0.22	24.15	24.50	0.229	2023/8/24	
50%RB										
Left Cheek	18900/1880	20M QPSK(50,24)	0.258	0.152	0.22	23.22	23.50	0.275	2023/8/24	
Left Tilt 15 Degree	18900/1880	20M QPSK(50,24)	0.132	0.083	4.01	23.22	23.50	0.141	2023/8/24	
Right Cheek	18900/1880	20M QPSK(50,24)	0.241	0.152	4.24	23.22	23.50	0.257	2023/8/24	
Right Tilt 15 Degree	18900/1880	20M QPSK(50,24)	0.113	0.063	0.15	23.22	23.50	0.121	2023/8/24	

NOTE: Head SAR test results of LTE Band 2

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										
Front Side	18900/1880	20M QPSK(1,49)	0.318	0.158	3.39	24.15	24.50	0.345	2023/8/24	
Back Side	18900/1880	20M QPSK(1,49)	0.485	0.251	-0.09	24.15	24.50	0.526	2023/8/24	18#
50%RB										
Front Side	18900/1880	20M QPSK(50,24)	0.163	0.094	0.00	23.22	23.50	0.174	2023/8/24	
Back Side	18900/1880	20M QPSK(50,24)	0.284	0.128	2.22	23.22	23.50	0.303	2023/8/24	

NOTE: Body-Worn SAR test results of LTE Band 2

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	18900/1880	20M QPSK(1,49)	0.318	0.158	3.39	24.15	24.50	0.345	2023/8/24	
Back Side	18900/1880	20M QPSK(1,49)	0.485	0.251	-0.09	24.15	24.50	0.526	2023/8/24	18#
Left Side	18900/1880	20M QPSK(1,49)	0.153	0.079	3.76	24.15	24.50	0.166	2023/8/24	
Right Side	18900/1880	20M QPSK(1,49)	0.147	0.076	1.32	24.15	24.50	0.159	2023/8/24	
Bottom Side	18900/1880	20M QPSK(1,49)	0.245	0.120	-1.58	24.15	24.50	0.266	2023/8/24	
50%RB										
Front Side	18900/1880	20M QPSK(50,24)	0.163	0.094	0.00	23.22	23.50	0.174	2023/8/24	
Back Side	18900/1880	20M QPSK(50,24)	0.284	0.128	2.22	23.22	23.50	0.303	2023/8/24	
Left Side	18900/1880	20M QPSK(50,24)	0.086	0.045	-2.20	23.22	23.50	0.092	2023/8/24	
Right Side	18900/1880	20M QPSK(50,24)	0.077	0.042	-0.53	23.22	23.50	0.082	2023/8/24	
Bottom Side	18900/1880	20M QPSK(50,24)	0.123	0.071	1.83	23.22	23.50	0.131	2023/8/24	

NOTE: Hotspot SAR test results of LTE Band 2

10.1.7. SAR measurement Result of LTE Band 4

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Left Cheek	20175/1732.5	20M QPSK(1,49)	0.295	0.184	-0.24	24.10	24.50	0.323	2023/8/22	19#

Left Tilt 15 Degree	20175/1732.5	20M QPSK(1,49)	0.175	0.108	-0.45	24.10	24.50	0.192	2023/8/22	
Right Cheek	20175/1732.5	20M QPSK(1,49)	0.268	0.164	0.14	24.10	24.50	0.294	2023/8/22	
Right Tilt 15 Degree	20175/1732.5	20M QPSK(1,49)	0.142	0.086	-0.94	24.10	24.50	0.156	2023/8/22	
50%RB										
Left Cheek	20175/1732.5	20M QPSK(50,0)	0.150	0.096	3.25	23.17	23.50	0.162	2023/8/22	
Left Tilt 15 Degree	20175/1732.5	20M QPSK(50,0)	0.090	0.055	4.95	23.17	23.50	0.097	2023/8/22	
Right Cheek	20175/1732.5	20M QPSK(50,0)	0.135	0.090	-0.02	23.17	23.50	0.146	2023/8/22	
Right Tilt 15 Degree	20175/1732.5	20M QPSK(50,0)	0.076	0.050	3.95	23.17	23.50	0.082	2023/8/22	

NOTE: Head SAR test results of LTE Band 4

Test Position of Body- Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										
Front Side	20175/1732.5	20M QPSK(1,49)	0.174	0.090	0.41	24.10	24.50	0.191	2023/8/22	
Back Side	20175/1732.5	20M QPSK(1,49)	0.264	0.143	2.38	24.10	24.50	0.289	2023/8/22	20#
50%RB										
Front Side	20175/1732.5	20M QPSK(50,0)	0.100	0.054	2.85	23.17	23.50	0.108	2023/8/22	
Back Side	20175/1732.5	20M QPSK(50,0)	0.135	0.079	4.93	23.17	23.50	0.146	2023/8/22	

NOTE: Body-Worn SAR test results of LTE Band 4

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	20175/1732.5	20M QPSK(1,49)	0.174	0.090	0.41	24.10	24.50	0.191	2023/8/22	
Back Side	20175/1732.5	20M QPSK(1,49)	0.264	0.143	2.38	24.10	24.50	0.289	2023/8/22	20#
Left Side	20175/1732.5	20M QPSK(1,49)	0.084	0.044	3.90	24.10	24.50	0.092	2023/8/22	
Right Side	20175/1732.5	20M QPSK(1,49)	0.093	0.050	2.11	24.10	24.50	0.102	2023/8/22	
Bottom Side	20175/1732.5	20M QPSK(1,49)	0.145	0.078	0.53	24.10	24.50	0.159	2023/8/22	
50%RB										
Front Side	20175/1732.5	20M QPSK(50,0)	0.100	0.054	2.85	23.17	23.50	0.108	2023/8/22	
Back Side	20175/1732.5	20M QPSK(50,0)	0.135	0.079	4.93	23.17	23.50	0.146	2023/8/22	
Left Side	20175/1732.5	20M QPSK(50,0)	0.045	0.023	-3.00	23.17	23.50	0.049	2023/8/22	
Right Side	20175/1732.5	20M QPSK(50,0)	0.049	0.026	0.46	23.17	23.50	0.053	2023/8/22	
Bottom Side	20175/1732.5	20M QPSK(50,0)	0.074	0.043	1.19	23.17	23.50	0.080	2023/8/22	

NOTE: Hotspot SAR test results of LTE Band 4

10.1.8. SAR measurement Result of LTE Band 5

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Left Cheek	20525/836.5	10M QPSK(1,24)	0.537	0.404	1.15	24.33	24.50	0.558	2023/8/21	21#

Left Tilt 15 Degree	20525/836.5	10M QPSK(1,24)	0.310	0.233	-3.08	24.33	24.50	0.322	2023/8/21	
Right Cheek	20525/836.5	10M QPSK(1,24)	0.496	0.354	-3.83	24.33	24.50	0.516	2023/8/21	
Right Tilt 15 Degree	20525/836.5	10M QPSK(1,24)	0.244	0.182	0.17	24.33	24.50	0.254	2023/8/21	
50%RB										
Left Cheek	20525/836.5	10M QPSK(25,24)	0.279	0.224	0.01	23.32	23.50	0.291	2023/8/21	
Left Tilt 15 Degree	20525/836.5	10M QPSK(25,24)	0.169	0.118	-0.90	23.32	23.50	0.176	2023/8/21	
Right Cheek	20525/836.5	10M QPSK(25,24)	0.270	0.177	2.06	23.32	23.50	0.281	2023/8/21	
Right Tilt 15 Degree	20525/836.5	10M QPSK(25,24)	0.135	0.094	-3.30	23.32	23.50	0.141	2023/8/21	

NOTE: Head SAR test results of LTE Band 5

Test Position of Body- Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)	Date	Plot
			1g	10g						
1RB										
Front Side	20525/836.5	10M QPSK(1,24)	0.348	0.208	3.35	24.33	24.50	0.362	2023/8/21	
Back Side	20525/836.5	10M QPSK(1,24)	0.572	0.360	0.01	24.33	24.50	0.595	2023/8/21	22#
50%RB										
Front Side	20525/836.5	10M QPSK(25,24)	0.193	0.117	2.85	23.32	23.50	0.201	2023/8/21	
Back Side	20525/836.5	10M QPSK(25,24)	0.337	0.209	-0.97	23.32	23.50	0.351	2023/8/21	

NOTE: Body-Worn SAR test results of LTE Band 5

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	20525/836.5	10M QPSK(1,24)	0.348	0.208	3.35	24.33	24.50	0.362	2023/8/21	
Back Side	20525/836.5	10M QPSK(1,24)	0.572	0.360	0.01	24.33	24.50	0.595	2023/8/21	22#
Left Side	20525/836.5	10M QPSK(1,24)	0.174	0.108	3.18	24.33	24.50	0.181	2023/8/21	
Right Side	20525/836.5	10M QPSK(1,24)	0.183	0.113	3.85	24.33	24.50	0.190	2023/8/21	
Bottom Side	20525/836.5	10M QPSK(1,24)	0.300	0.183	-2.25	24.33	24.50	0.312	2023/8/21	
50%RB										
Front Side	20525/836.5	10M QPSK(25,24)	0.193	0.117	2.85	23.32	23.50	0.201	2023/8/21	
Back Side	20525/836.5	10M QPSK(25,24)	0.337	0.209	-0.97	23.32	23.50	0.351	2023/8/21	
Left Side	20525/836.5	10M QPSK(25,24)	0.093	0.059	-1.73	23.32	23.50	0.097	2023/8/21	
Right Side	20525/836.5	10M QPSK(25,24)	0.095	0.059	0.23	23.32	23.50	0.099	2023/8/21	
Bottom Side	20525/836.5	10M QPSK(25,24)	0.169	0.097	-0.31	23.32	23.50	0.176	2023/8/21	

NOTE: Hotspot SAR test results of LTE Band 5

10.1.9. SAR measurement Result of LTE Band 7

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Left Cheek	21100/2535	20M QPSK(1,49)	0.167	0.093	-3.65	24.86	25.50	0.194	2023/8/17	23#

Left Tilt 15 Degree	21100/2535	20M QPSK(1,49)	0.084	0.047	0.46	24.86	25.50	0.097	2023/8/17	
Right Cheek	21100/2535	20M QPSK(1,49)	0.155	0.082	2.74	24.86	25.50	0.180	2023/8/17	
Right Tilt 15 Degree	21100/2535	20M QPSK(1,49)	0.082	0.044	1.24	24.86	25.50	0.095	2023/8/17	
50%RB										
Left Cheek	21100/2535	20M QPSK(50,49)	0.086	0.055	0.40	23.93	24.50	0.098	2023/8/17	
Left Tilt 15 Degree	21100/2535	20M QPSK(50,49)	0.050	0.026	4.44	23.93	24.50	0.057	2023/8/17	
Right Cheek	21100/2535	20M QPSK(50,49)	0.079	0.048	1.93	23.93	24.50	0.090	2023/8/17	
Right Tilt 15 Degree	21100/2535	20M QPSK(50,49)	0.049	0.023	2.87	23.93	24.50	0.056	2023/8/17	

NOTE: Head SAR test results of LTE Band 7

Test Position of Body-Worn with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	21100/2535	20M QPSK(1,49)	0.114	0.059	-1.07	24.86	25.50	0.132	2023/8/17	
Back Side	21100/2535	20M QPSK(1,49)	0.183	0.096	-0.60	24.86	25.50	0.212	2023/8/17	24#
50%RB										
Front Side	21100/2535	20M QPSK(50,49)	0.058	0.034	1.79	23.93	24.50	0.066	2023/8/17	
Back Side	21100/2535	20M QPSK(50,49)	0.109	0.049	1.38	23.93	24.50	0.124	2023/8/17	

NOTE: Body-Worn SAR test results of LTE Band 7

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										

Front Side	21100/2535	20M QPSK(1,49)	0.114	0.059	-1.07	24.86	25.50	0.132	2023/8/17	
Back Side	21100/2535	20M QPSK(1,49)	0.183	0.096	-0.60	24.86	25.50	0.212	2023/8/17	24#
Left Side	21100/2535	20M QPSK(1,49)	0.054	0.027	-0.51	24.86	25.50	0.063	2023/8/17	
Right Side	21100/2535	20M QPSK(1,49)	0.060	0.030	3.68	24.86	25.50	0.070	2023/8/17	
Bottom Side	21100/2535	20M QPSK(1,49)	0.095	0.049	1.20	24.86	25.50	0.110	2023/8/17	
50%RB										
Front Side	21100/2535	20M QPSK(50,49)	0.058	0.034	1.79	23.93	24.50	0.066	2023/8/17	
Back Side	21100/2535	20M QPSK(50,49)	0.109	0.049	1.38	23.93	24.50	0.124	2023/8/17	
Left Side	21100/2535	20M QPSK(50,49)	0.030	0.014	1.61	23.93	24.50	0.034	2023/8/17	
Right Side	21100/2535	20M QPSK(50,49)	0.034	0.017	4.36	23.93	24.50	0.039	2023/8/17	
Bottom Side	21100/2535	20M QPSK(50,49)	0.053	0.026	1.97	23.93	24.50	0.060	2023/8/17	

NOTE: Hotspot SAR test results of LTE Band 7

10.1.10. SAR measurement Result of LTE Band 12

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Left Cheek	23095/707.5	10M QPSK(1,0)	0.449	0.364	3.79	24.39	25.00	0.517	2023/8/18	25#
Left Tilt 15 Degree	23095/707.5	10M QPSK(1,0)	0.237	0.190	0.17	24.39	25.00	0.273	2023/8/18	
Right Cheek	23095/707.5	10M QPSK(1,0)	0.410	0.322	2.46	24.39	25.00	0.472	2023/8/18	
Right Tilt 15	23095/707.5	10M QPSK(1,0)	0.202	0.159	-3.56	24.39	25.00	0.232	2023/8/18	

Degree										
50%RB										
Left Cheek	23095/707.5	10M QPSK(25,0)	0.232	0.202	-1.85	23.38	24.00	0.268	2023/8/18	
Left Tilt 15 Degree	23095/707.5	10M QPSK(25,0)	0.134	0.099	-0.42	23.38	24.00	0.155	2023/8/18	
Right Cheek	23095/707.5	10M QPSK(25,0)	0.229	0.161	1.20	23.38	24.00	0.264	2023/8/18	
Right Tilt 15 Degree	23095/707.5	10M QPSK(25,0)	0.103	0.092	0.77	23.38	24.00	0.119	2023/8/18	

NOTE: Head SAR test results of LTE Band 12

Test Position of Body-Worn with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	23095/707.5	10M QPSK(1,0)	0.378	0.284	2.77	24.39	25.00	0.435	2023/8/18	
Back Side	23095/707.5	10M QPSK(1,0)	0.586	0.464	-1.33	24.39	25.00	0.674	2023/8/18	26#
50%RB										
Front Side	23095/707.5	10M QPSK(25,0)	0.214	0.150	2.20	23.38	24.00	0.247	2023/8/18	
Back Side	23095/707.5	10M QPSK(25,0)	0.312	0.270	-1.60	23.38	24.00	0.360	2023/8/18	

NOTE: Body-Worn SAR test results of LTE Band 12

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	23095/707.5	10M QPSK(1,0)	0.378	0.284	2.77	24.39	25.00	0.435	2023/8/18	
Back Side	23095/707.5	10M QPSK(1,0)	0.586	0.464	-1.33	24.39	25.00	0.674	2023/8/18	26#
Left Side	23095/707.5	10M QPSK(1,0)	0.184	0.143	-3.70	24.39	25.00	0.212	2023/8/18	
Right	23095/707.5	10M QPSK(1,0)	0.186	0.147	-0.45	24.39	25.00	0.214	2023/8/18	

Side										
Bottom Side	23095/707.5	10M QPSK(1,0)	0.300	0.228	-1.13	24.39	25.00	0.345	2023/8/18	
50%RB										
Front Side	23095/707.5	10M QPSK(25,0)	0.214	0.150	2.20	23.38	24.00	0.247	2023/8/18	
Back Side	23095/707.5	10M QPSK(25,0)	0.312	0.270	-1.60	23.38	24.00	0.360	2023/8/18	
Left Side	23095/707.5	10M QPSK(25,0)	0.103	0.080	-0.62	23.38	24.00	0.119	2023/8/18	
Right Side	23095/707.5	10M QPSK(25,0)	0.094	0.086	-2.44	23.38	24.00	0.108	2023/8/18	
Bottom Side	23095/707.5	10M QPSK(25,0)	0.160	0.121	-0.21	23.38	24.00	0.185	2023/8/18	

NOTE: Hotspot SAR test results of LTE Band 12

10.1.11. SAR measurement Result of LTE Band 13

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Left Cheek	23230/782	10M QPSK(1,0)	0.451	0.354	-0.78	24.45	24.50	0.456	2023/8/18	27#
Left Tilt 15 Degree	23230/782	10M QPSK(1,0)	0.257	0.200	0.93	24.45	24.50	0.260	2023/8/18	
Right Cheek	23230/782	10M QPSK(1,0)	0.388	0.292	1.10	24.45	24.50	0.392	2023/8/18	
Right Tilt 15 Degree	23230/782	10M QPSK(1,0)	0.191	0.142	-2.02	24.45	24.50	0.193	2023/8/18	
50%RB										
Left Cheek	23230/782	10M QPSK(25,12)	0.260	0.202	-0.83	23.42	23.50	0.265	2023/8/18	
Left Tilt 15 Degree	23230/782	10M QPSK(25,12)	0.139	0.105	3.42	23.42	23.50	0.142	2023/8/18	
Right	23230/782	10M QPSK(25,12)	0.231	0.167	3.56	23.42	23.50	0.235	2023/8/18	

Cheek										
Right Tilt 15 Degree	23230/782	10M QPSK(25,12)	0.100	0.075	3.40	23.42	23.50	0.102	2023/8/18	

NOTE: Head SAR test results of LTE Band 13

Test Position of Body-Worn with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	23230/782	10M QPSK(1,0)	0.288	0.217	2.98	24.45	24.50	0.291	2023/8/18	
Back Side	23230/782	10M QPSK(1,0)	0.468	0.363	-0.33	24.45	24.50	0.473	2023/8/18	28#
50%RB										
Front Side	23230/782	10M QPSK(25,12)	0.147	0.109	-1.81	23.42	23.50	0.150	2023/8/18	
Back Side	23230/782	10M QPSK(25,12)	0.255	0.188	3.05	23.42	23.50	0.260	2023/8/18	

NOTE: Body-Worn SAR test results of LTE Band 13

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	23230/782	10M QPSK(1,0)	0.288	0.217	2.98	24.45	24.50	0.291	2023/8/18	
Back Side	23230/782	10M QPSK(1,0)	0.468	0.363	-0.33	24.45	24.50	0.473	2023/8/18	28#
Left Side	23230/782	10M QPSK(1,0)	0.150	0.116	-1.99	24.45	24.50	0.152	2023/8/18	
Right Side	23230/782	10M QPSK(1,0)	0.141	0.109	0.62	24.45	24.50	0.143	2023/8/18	
Bottom Side	23230/782	10M QPSK(1,0)	0.235	0.177	-1.40	24.45	24.50	0.238	2023/8/18	
50%RB										
Front Side	23230/782	10M QPSK(25,12)	0.147	0.109	-1.81	23.42	23.50	0.150	2023/8/18	
Back Side	23230/782	10M QPSK(25,12)	0.255	0.188	3.05	23.42	23.50	0.260	2023/8/18	

Left Side	23230/782	10M QPSK(25,12)	0.075	0.062	3.50	23.42	23.50	0.076	2023/8/18	
Right Side	23230/782	10M QPSK(25,12)	0.080	0.062	-0.08	23.42	23.50	0.081	2023/8/18	
Bottom Side	23230/782	10M QPSK(25,12)	0.137	0.100	1.59	23.42	23.50	0.140	2023/8/18	

NOTE: Hotspot SAR test results of LTE Band 13

10.1.12. SAR measurement Result of LTE Band 17

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Left Cheek	23790/710	10M QPSK(1,24)	0.463	0.372	2.60	24.46	25.00	0.524	2023/8/18	29#
Left Tilt 15 Degree	23790/710	10M QPSK(1,24)	0.277	0.216	3.97	24.46	25.00	0.314	2023/8/18	
Right Cheek	23790/710	10M QPSK(1,24)	0.395	0.308	-2.37	24.46	25.00	0.447	2023/8/18	
Right Tilt 15 Degree	23790/710	10M QPSK(1,24)	0.206	0.164	-2.92	24.46	25.00	0.233	2023/8/18	
50%RB										
Left Cheek	23790/710	10M QPSK(25,0)	0.277	0.215	3.30	23.55	24.00	0.307	2023/8/18	
Left Tilt 15 Degree	23790/710	10M QPSK(25,0)	0.165	0.118	-2.75	23.55	24.00	0.183	2023/8/18	
Right Cheek	23790/710	10M QPSK(25,0)	0.208	0.176	-3.50	23.55	24.00	0.231	2023/8/18	
Right Tilt 15 Degree	23790/710	10M QPSK(25,0)	0.114	0.089	1.88	23.55	24.00	0.126	2023/8/18	

NOTE: Head SAR test results of LTE Band 17

Test Position of	Test channel	Mode	SAR Value (W/kg)	Power Drift(%)	Conducted Power	Tune-up Power	Scaled SAR	Date	Plot
------------------	--------------	------	------------------	----------------	-----------------	---------------	------------	------	------

Body-Worn with 10mm	/Freq.		1-g	10-g		(dBm)	(dBm)	1-g (W/Kg)		
1RB										
Front Side	23790/710	10M QPSK(1,24)	0.360	0.279	0.68	24.46	25.00	0.408	2023/8/18	
Back Side	23790/710	10M QPSK(1,24)	0.576	0.455	-0.41	24.46	25.00	0.652	2023/8/18	30#
50%RB										
Front Side	23790/710	10M QPSK(25,0)	0.198	0.148	-0.60	23.55	24.00	0.220	2023/8/18	
Back Side	23790/710	10M QPSK(25,0)	0.334	0.250	-0.05	23.55	24.00	0.370	2023/8/18	

NOTE: Body-Worn SAR test results of LTE Band 17

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
1RB										
Front Side	23790/710	10M QPSK(1,24)	0.360	0.279	0.68	24.46	25.00	0.408	2023/8/18	
Back Side	23790/710	10M QPSK(1,24)	0.576	0.455	-0.41	24.46	25.00	0.652	2023/8/18	30#
Left Side	23790/710	10M QPSK(1,24)	0.186	0.144	-0.34	24.46	25.00	0.211	2023/8/18	
Right Side	23790/710	10M QPSK(1,24)	0.183	0.143	3.92	24.46	25.00	0.207	2023/8/18	
Bottom Side	23790/710	10M QPSK(1,24)	0.310	0.238	-1.79	24.46	25.00	0.351	2023/8/18	
50%RB										
Front Side	23790/710	10M QPSK(25,0)	0.198	0.148	-0.60	23.55	24.00	0.220	2023/8/18	
Back Side	23790/710	10M QPSK(25,0)	0.334	0.250	-0.05	23.55	24.00	0.370	2023/8/18	
Left Side	23790/710	10M QPSK(25,0)	0.109	0.082	0.18	23.55	24.00	0.121	2023/8/18	
Right Side	23790/710	10M QPSK(25,0)	0.104	0.073	-0.05	23.55	24.00	0.115	2023/8/18	
Bottom Side	23790/710	10M QPSK(25,0)	0.157	0.126	-1.19	23.55	24.00	0.174	2023/8/18	

NOTE: Hotspot SAR test results of LTE Band 17

10.1.13. SAR measurement Result of WLAN 2.4G

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Left Cheek	1/2412	802.11b	0.431	0.228	0.16	15.57	16.00	0.476	2023/8/16	15#
Left Tilt 15 Degree	1/2412	802.11b	0.230	0.122	1.84	15.57	16.00	0.254	2023/8/16	
Right Cheek	1/2412	802.11b	0.371	0.186	-1.03	15.57	16.00	0.410	2023/8/16	
Right Tilt 15 Degree	1/2412	802.11b	0.176	0.092	-3.58	15.57	16.00	0.194	2023/8/16	

NOTE: Head SAR test results of WLAN2.4G

Test Position of Body-Worn with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	1/2412	802.11b	0.090	0.052	3.21	15.57	16.00	0.099	2023/8/16	
Back Side	1/2412	802.11b	0.133	0.079	-1.81	15.57	16.00	0.147	2023/8/16	16#

NOTE: Body-worn SAR test results of WLAN2.4G

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	1/2412	802.11b	0.090	0.052	3.21	15.57	16.00	0.099	2023/8/16	
Back Side	1/2412	802.11b	0.133	0.079	-1.81	15.57	16.00	0.147	2023/8/16	16#
Right Side	1/2412	802.11b	0.054	0.031	2.11	15.57	16.00	0.060	2023/8/16	
Top Side	1/2412	802.11b	0.051	0.030	-0.37	15.57	16.00	0.056	2023/8/16	

NOTE: Hotspot SAR test results of WLAN2.4G

10.1.14. SAR measurement Result of WLAN 5.2G

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Left Cheek	36/5180	802.11ac VHT20	0.134	0.074	1.58	10.55	11.00	0.149	2023/8/23	11#
Left Tilt 15 Degree	36/5180	802.11ac VHT20	0.080	0.042	1.27	10.55	11.00	0.089	2023/8/23	
Right Cheek	36/5180	802.11ac VHT20	0.126	0.067	-1.76	10.55	11.00	0.140	2023/8/23	
Right Tilt 15 Degree	36/5180	802.11ac VHT20	0.060	0.031	-0.45	10.55	11.00	0.067	2023/8/23	

NOTE: Head SAR test results of WLAN5.2G

Test Position of Body-Worn with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	36/5180	802.11ac VHT20	0.060	0.039	0.01	10.55	11.00	0.067	2023/8/23	
Back Side	36/5180	802.11ac VHT20	0.077	0.052	-2.98	10.55	11.00	0.085	2023/8/23	13#

NOTE: Body-worn SAR test results of WLAN5.2G

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	36/5180	802.11ac VHT20	0.060	0.039	0.01	10.55	11.00	0.067	2023/8/23	
Back Side	36/5180	802.11ac VHT20	0.077	0.052	-2.98	10.55	11.00	0.085	2023/8/23	13#
Right Side	36/5180	802.11ac VHT20	0.030	0.020	0.62	10.55	11.00	0.033	2023/8/23	
Top Side	36/5180	802.11ac VHT20	0.024	0.016	0.39	10.55	11.00	0.027	2023/8/23	

NOTE: Hotspot SAR test results of WLAN5.2G

10.1.15. SAR measurement Result of WLAN 5.8G

Test Position of Head	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Left Cheek	165/5825	802.11a	0.117	0.075	-2.04	11.38	11.50	0.120	2023/8/14	12#
Left Tilt 15 Degree	165/5825	802.11a	0.066	0.042	-2.54	11.38	11.50	0.068	2023/8/14	
Right Cheek	165/5825	802.11a	0.107	0.069	0.95	11.38	11.50	0.110	2023/8/14	
Right Tilt 15 Degree	165/5825	802.11a	0.058	0.037	-3.43	11.38	11.50	0.060	2023/8/14	

NOTE: Head SAR test results of WLAN5.8G

Test Position of Body-Worn with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	165/5825	802.11a	0.060	0.049	2.34	11.38	11.50	0.062	2023/8/14	
Back Side	165/5825	802.11a	0.076	0.063	3.31	11.38	11.50	0.078	2023/8/14	14#

NOTE: Body-worn SAR test results of WLAN5.8G

Test Position of Hotspot with 10mm	Test channel /Freq.	Mode	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 1-g (W/Kg)	Date	Plot
			1-g	10-g						
Front Side	165/5825	802.11a	0.060	0.049	2.34	11.38	11.50	0.062	2023/8/14	
Back Side	165/5825	802.11a	0.076	0.063	3.31	11.38	11.50	0.078	2023/8/14	14#
Right Side	165/5825	802.11a	0.031	0.026	3.39	11.38	11.50	0.032	2023/8/14	
Top	165/5825	802.11a	0.033	0.027	2.66	11.38	11.50	0.034	2023/8/14	

Side										
------	--	--	--	--	--	--	--	--	--	--

NOTE: Hotspot SAR test results of WLAN5.8G

10.2. Simultaneous Transmission Analysis

Per KDB 447498 D01, simultaneous transmission SAR is compliant if,

- 1) Scalar SAR summation $< 1.6\text{W/kg}$.
- 2) $\text{SPLSR} = (\text{SAR}_1 + \text{SAR}_2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2]$, where (x_1, y_1, z_1) and (x_2, y_2, z_2) are the coordinates of the extrapolated peak SAR locations in the zoom scan. If $\text{SPLSR} \leq 0.04$, simultaneously transmission SAR measurement is not necessary.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WWAN	DTS			
Head	Left Cheek	0.861	0.476	1.337	N/A	N/A
	Left Tilt 15 Degree	0.501	0.254	0.755	N/A	N/A
	Right Cheek	0.816	0.410	1.226	N/A	N/A
	Right Tilt 15 Degree	0.401	0.194	0.595	N/A	N/A
Body-Worn	Front Side	0.468	0.099	0.567	N/A	N/A
	Back Side	0.772	0.147	0.919	N/A	N/A
Hotspot	Front Side	0.468	0.099	0.567	N/A	N/A
	Back Side	0.772	0.147	0.919	N/A	N/A
	Left Side	0.234	N/A	0.234	N/A	N/A
	Right Side	0.241	0.060	0.301	N/A	N/A
	Top Side	N/A	0.056	0.056	N/A	N/A
	Bottom Side	0.402	N/A	0.402	N/A	N/A

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WWAN	NII			
Head	Left Cheek	0.861	0.149	1.010	N/A	N/A
	Left Tilt 15 Degree	0.501	0.089	0.590	N/A	N/A
	Right Cheek	0.816	0.140	0.956	N/A	N/A
	Right Tilt 15 Degree	0.401	0.067	0.468	N/A	N/A

Body-Worn	Front Side	0.468	0.067	0.535	N/A	N/A
	Back Side	0.772	0.085	0.857	N/A	N/A
Hotspot	Front Side	0.468	0.067	0.535	N/A	N/A
	Back Side	0.772	0.085	0.857	N/A	N/A
	Left Side	0.234	N/A	0.234	N/A	N/A
	Right Side	0.241	0.033	0.274	N/A	N/A
	Top Side	N/A	0.027	0.027	N/A	N/A
	Bottom Side	0.402	N/A	0.402	N/A	N/A

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WWAN	DSS			
Head	Left Cheek	0.861	0.332	1.193	N/A	N/A
	Left Tilt 15 Degree	0.501	0.332	0.833	N/A	N/A
	Right Cheek	0.816	0.332	1.148	N/A	N/A
	Right Tilt 15 Degree	0.401	0.332	0.733	N/A	N/A
Body-Worn	Front Side	0.468	0.166	0.634	N/A	N/A
	Back Side	0.772	0.166	0.938	N/A	N/A
Hotspot	Front Side	0.468	0.166	0.634	N/A	N/A
	Back Side	0.772	0.166	0.938	N/A	N/A
	Left Side	0.234	N/A	0.234	N/A	N/A
	Right Side	0.241	0.166	0.407	N/A	N/A
	Top Side	N/A	0.166	0.166	N/A	N/A
	Bottom Side	0.402	N/A	0.402	N/A	N/A

11. Appendix A. Photo documentation

Refer to appendix Test Setup photo---SAR

12. Appendix B. System Check Plots

Table of contents
MEASUREMENT 1 System Performance Check - 750MHz
MEASUREMENT 2 System Performance Check - 835MHz
MEASUREMENT 3 System Performance Check - 1800MHz
MEASUREMENT 4 System Performance Check - 1900MHz
MEASUREMENT 5 System Performance Check - 2450MHz
MEASUREMENT 6 System Performance Check - 2600MHz
MEASUREMENT 7 System Performance Check - 5200MHz
MEASUREMENT 8 System Performance Check - 5800MHz

MEASUREMENT 1

Date of measurement: 18/8/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW750</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.49</u>


B. SAR Measurement Results

Frequency (MHz)	750.000000
Relative permittivity (real part)	40.281774
Relative permittivity (imaginary part)	21.312354
Conductivity (S/m)	0.888015
Variation (%)	2.730000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=3.00

SAR Peak: 1.30 W/kg

SAR 10g (W/Kg)	0.599332
SAR 1g (W/Kg)	0.871321



MEASUREMENT 2

Date of measurement: 21/8/2023


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW835</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>
ConvF	<u>1.50</u>


B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative permittivity (real part)	41.965600
Relative permittivity (imaginary part)	19.773670
Conductivity (S/m)	0.917279
Variation (%)	-2.720000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=3.00

SAR Peak: 1.30 W/kg

SAR 10g (W/Kg)	0.620333
SAR 1g (W/Kg)	0.974172



MEASUREMENT 3

Date of measurement: 22/8/2023


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW1800</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>
ConvF	<u>1.73</u>


B. SAR Measurement Results

Frequency (MHz)	1800.000000
Relative permittivity (real part)	39.908501
Relative permittivity (imaginary part)	13.783729
Conductivity (S/m)	1.378373
Variation (%)	2.980000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=2.00

SAR Peak: 6.82 W/kg

SAR 10g (W/Kg)	1.923307
SAR 1g (W/Kg)	3.709066



MEASUREMENT 4


Date of measurement: 24/8/2023

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.91</u>

B. SAR Measurement Results



Frequency (MHz)	1900.000000
Relative permittivity (real part)	38.227563
Relative permittivity (imaginary part)	13.523204
Conductivity (S/m)	1.427449
Variation (%)	2.220000



Maximum location: X=5.00, Y=2.00

SAR Peak: 6.70 W/kg

SAR 10g (W/Kg)	2.171347
SAR 1g (W/Kg)	4.413221



MEASUREMENT 5

Date of measurement: 16/8/2023


A. Experimental conditions.

Area Scan	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
ZoomScan	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW2450</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>
ConvF	<u>1.98</u>


B. SAR Measurement Results

Frequency (MHz)	2450.000000
Relative permittivity (real part)	37.609327
Relative permittivity (imaginary part)	13.017689
Conductivity (S/m)	1.771852
Variation (%)	1.290000

SURFACE SAR





VOLUME SAR



Maximum location: X=-1.00, Y=-1.00

SAR Peak: 9.83 W/kg

SAR 10g (W/Kg)	2.229106
SAR 1g (W/Kg)	5.411340



MEASUREMENT 6

Date of measurement: 17/8/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2600</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.87</u>


B. SAR Measurement Results

Frequency (MHz)	2600.000000
Relative permittivity (real part)	38.025084
Relative permittivity (imaginary part)	13.499677
Conductivity (S/m)	1.949953
Variation (%)	0.250000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=-11.00

SAR Peak: 10.29 W/kg

SAR 10g (W/Kg)	2.337037
SAR 1g (W/Kg)	5.545199



MEASUREMENT 7


Date of measurement: 23/8/2023

A. Experimental conditions.

Area Scan	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
ZoomScan	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Dipole</u>
Band	<u>CW5200</u>
Channels	<u>Middle</u>
Signal	<u>CW (Crest factor: 1.0)</u>
ConvF	<u>1.80</u>

B. SAR Measurement Results



Frequency (MHz)	5200.000000
Relative permittivity (real part)	34.747545
Relative permittivity (imaginary part)	15.846034
Conductivity (S/m)	4.577743
Variation (%)	2.800000



Maximum location: X=0.00, Y=6.00

SAR Peak: 40.06 W/kg

SAR 10g (W/Kg)	6.074162
SAR 1g (W/Kg)	15.988032



MEASUREMENT 8

Date of measurement: 14/8/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW5800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>2.07</u>


B. SAR Measurement Results

Frequency (MHz)	5800.000000
Relative permittivity (real part)	34.375995
Relative permittivity (imaginary part)	16.175053
Conductivity (S/m)	5.211962
Variation (%)	-0.500000

SURFACE SAR





VOLUME SAR



Maximum location: X=0.00, Y=6.00

SAR Peak: 57.37 W/kg

SAR 10g (W/Kg)	5.520228
SAR 1g (W/Kg)	17.652190



13. Appendix C. Plots of High SAR Measurement

Table of contents
MEASUREMENT 1 GSM 850 Head
MEASUREMENT 2 GSM 850 Body
MEASUREMENT 3 GSM 1900 Head
MEASUREMENT 4 GSM 1900 Body
MEASUREMENT 5 WCDMA Band 2 Head
MEASUREMENT 6 WCDMA Band 2 Body
MEASUREMENT 7 WCDMA Band 4 Head
MEASUREMENT 8 WCDMA Band 4 Body
MEASUREMENT 9 WCDMA Band 5 Head
MEASUREMENT 10 WCDMA Band 5 Body
MEASUREMENT 11 WLAN 5.2G Head
MEASUREMENT 12 WLAN 5.8G Head
MEASUREMENT 13 WLAN 5.2G Body
MEASUREMENT 14 WLAN 5.8G Body
MEASUREMENT 15 WLAN 2.4G Head
MEASUREMENT 16 WLAN 2.4G Body
MEASUREMENT 17 LTE Band 2 Head
MEASUREMENT 18 LTE Band 2 Body
MEASUREMENT 19 LTE Band 4 Head
MEASUREMENT 20 LTE Band 4 Body
MEASUREMENT 21 LTE Band 5 Head
MEASUREMENT 22 LTE Band 5 Body
MEASUREMENT 23 LTE Band 7 Head
MEASUREMENT 24 LTE Band 7 Body
MEASUREMENT 25 LTE Band 12 Head
MEASUREMENT 26 LTE Band 12 Body
MEASUREMENT 27 LTE Band 13 Head
MEASUREMENT 28 LTE Band 13 Body
MEASUREMENT 29 LTE Band 17 Head
MEASUREMENT 30 LTE Band 17 Body

MEASUREMENT 1

Date of measurement: 21/8/2023


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Left head</u>
Device Position	<u>Cheek</u>
Band	<u>GSM850</u>
Channels	<u>Middle</u>
Signal	<u>TDMA (Crest factor: 2.0)</u>
ConvF	<u>1.50</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	41.974682
Relative permittivity (imaginary part)	19.780870
Conductivity (S/m)	0.919151
Variation (%)	0.180000

SURFACE SAR





VOLUME SAR



Maximum location: X=-53.00, Y=-21.00

SAR Peak: 0.90 W/kg

SAR 10g (W/Kg)	0.569940
SAR 1g (W/Kg)	0.750229



MEASUREMENT 2

Date of measurement: 21/8/2023


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body</u>
Band	<u>GSM850</u>
Channels	<u>Middle</u>
Signal	<u>TDMA (Crest factor: 2.0)</u>
ConvF	<u>1.50</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	41.974682
Relative permittivity (imaginary part)	19.780870
Conductivity (S/m)	0.919151
Variation (%)	2.510000

SURFACE SAR





VOLUME SAR



Maximum location: X=-6.00, Y=-45.00

SAR Peak: 1.00 W/kg

SAR 10g (W/Kg)	0.415259
SAR 1g (W/Kg)	0.671536



MEASUREMENT 3

Date of measurement: 24/8/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>GSM1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 2.0)</u>
<u>ConvF</u>	<u>1.91</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	38.313965
Relative permittivity (imaginary part)	13.976862
Conductivity (S/m)	1.459806
Variation (%)	-1.430000

SURFACE SAR





VOLUME SAR



Maximum location: X=-51.00, Y=-51.00

SAR Peak: 0.29 W/kg

SAR 10g (W/Kg)	0.097994
SAR 1g (W/Kg)	0.180098



MEASUREMENT 4

Date of measurement: 24/8/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>GSM1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 2.0)</u>
<u>ConvF</u>	<u>1.91</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	38.313965
Relative permittivity (imaginary part)	13.976862
Conductivity (S/m)	1.459806
Variation (%)	-0.150000

SURFACE SAR





VOLUME SAR



Maximum location: X=18.00, Y=-23.00

SAR Peak: 0.64 W/kg

SAR 10g (W/Kg)	0.181075
SAR 1g (W/Kg)	0.338420



MEASUREMENT 5

Date of measurement: 24/8/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>Band2 WCDMA1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.91</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	38.313965
Relative permittivity (imaginary part)	13.976862
Conductivity (S/m)	1.459806
Variation (%)	-0.590000

SURFACE SAR





VOLUME SAR



Maximum location: X=-51.00, Y=-51.00

SAR Peak: 0.45 W/kg

SAR 10g (W/Kg)	0.167897
SAR 1g (W/Kg)	0.297129



MEASUREMENT 6

Date of measurement: 24/8/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band2 WCDMA1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.91</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	38.313965
Relative permittivity (imaginary part)	13.976862
Conductivity (S/m)	1.459806
Variation (%)	0.410000

SURFACE SAR





VOLUME SAR



Maximum location: X=-7.00, Y=5.00

SAR Peak: 0.71 W/kg

SAR 10g (W/Kg)	0.226884
SAR 1g (W/Kg)	0.440998



MEASUREMENT 7

Date of measurement: 22/8/2023


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Left head</u>
Device Position	<u>Cheek</u>
Band	<u>Band4 WCDMA1700</u>
Channels	<u>Middle</u>
Signal	<u>WCDMA (Crest factor: 1.0)</u>
ConvF	<u>1.73</u>


B. SAR Measurement Results

Frequency (MHz)	1732.600000
Relative permittivity (real part)	40.368202
Relative permittivity (imaginary part)	13.736029
Conductivity (S/m)	1.321711
Variation (%)	-1.450000

SURFACE SAR





VOLUME SAR



Maximum location: X=-50.00, Y=-49.00

SAR Peak: 0.27 W/kg

SAR 10g (W/Kg)	0.105655
SAR 1g (W/Kg)	0.178007



MEASUREMENT 8

Date of measurement: 22/8/2023


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body</u>
Band	<u>Band4 WCDMA1700</u>
Channels	<u>Middle</u>
Signal	<u>WCDMA (Crest factor: 1.0)</u>
ConvF	<u>1.73</u>


B. SAR Measurement Results

Frequency (MHz)	1732.600000
Relative permittivity (real part)	40.368202
Relative permittivity (imaginary part)	13.736029
Conductivity (S/m)	1.321711
Variation (%)	1.660000

SURFACE SAR





VOLUME SAR



Maximum location: X=19.00, Y=5.00

SAR Peak: 0.48 W/kg

SAR 10g (W/Kg)	0.153123
SAR 1g (W/Kg)	0.293606



MEASUREMENT 9

Date of measurement: 21/8/2023


A. Experimental conditions.

Area Scan	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
Phantom	<u>Left head</u>
Device Position	<u>Cheek</u>
Band	<u>Band5 WCDMA850</u>
Channels	<u>Middle</u>
Signal	<u>WCDMA (Crest factor: 1.0)</u>
ConvF	<u>1.50</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	41.974682
Relative permittivity (imaginary part)	19.780870
Conductivity (S/m)	0.919151
Variation (%)	1.210000

SURFACE SAR





VOLUME SAR



Maximum location: X=-53.00, Y=-25.00

SAR Peak: 0.58 W/kg

SAR 10g (W/Kg)	0.348218
SAR 1g (W/Kg)	0.466642



MEASUREMENT 10

Date of measurement: 21/8/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band5 WCDMA850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.50</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	41.974682
Relative permittivity (imaginary part)	19.780870
Conductivity (S/m)	0.919151
Variation (%)	-3.010000

SURFACE SAR





VOLUME SAR



Maximum location: X=17.00, Y=8.00

SAR Peak: 0.47 W/kg

SAR 10g (W/Kg)	0.291928
SAR 1g (W/Kg)	0.380141



MEASUREMENT 11

Date of measurement: 23/8/2023


A. Experimental conditions.

Area Scan	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
ZoomScan	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
Phantom	<u>Left head</u>
Device Position	<u>Cheek</u>
Band	<u>IEEE 802.11ac U-NII</u>
Channels	<u>Low</u>
Signal	<u>IEEE802.11ac (Crest factor: 1.0)</u>
ConvF	<u>1.80</u>


B. SAR Measurement Results

Frequency (MHz)	5180.000000
Relative permittivity (real part)	34.813698
Relative permittivity (imaginary part)	15.858084
Conductivity (S/m)	4.563604
Variation (%)	1.580000

SURFACE SAR





VOLUME SAR



Maximum location: X=-15.00, Y=5.00

SAR Peak: 0.32 W/kg

SAR 10g (W/Kg)	0.074161
SAR 1g (W/Kg)	0.134190



MEASUREMENT 12

Date of measurement: 14/8/2023


A. Experimental conditions.

Area Scan	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
ZoomScan	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
Phantom	<u>Left head</u>
Device Position	<u>Cheek</u>
Band	<u>IEEE 802.11a U-NII</u>
Channels	<u>High</u>
Signal	<u>IEEE802.11a (Crest factor: 1.0)</u>
ConvF	<u>2.07</u>


B. SAR Measurement Results

Frequency (MHz)	5825.000000
Relative permittivity (real part)	34.309906
Relative permittivity (imaginary part)	16.155984
Conductivity (S/m)	5.228256
Variation (%)	-2.040000

SURFACE SAR





VOLUME SAR



Maximum location: X=-16.00, Y=26.00

SAR Peak: 0.26 W/kg

SAR 10g (W/Kg)	0.075046
SAR 1g (W/Kg)	0.117399



MEASUREMENT 13

Date of measurement: 23/8/2023


A. Experimental conditions.

Area Scan	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
ZoomScan	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body</u>
Band	<u>IEEE 802.11ac U-NII</u>
Channels	<u>Low</u>
Signal	<u>IEEE802.11ac (Crest factor: 1.0)</u>
ConvF	<u>1.80</u>


B. SAR Measurement Results

Frequency (MHz)	5180.000000
Relative permittivity (real part)	34.813698
Relative permittivity (imaginary part)	15.858084
Conductivity (S/m)	4.563604
Variation (%)	-2.980000

SURFACE SAR





VOLUME SAR



Maximum location: X=-22.00, Y=-18.00

SAR Peak: 0.20 W/kg

SAR 10g (W/Kg)	0.052391
SAR 1g (W/Kg)	0.076619



MEASUREMENT 14

Date of measurement: 14/8/2023


A. Experimental conditions.

Area Scan	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
ZoomScan	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body</u>
Band	<u>IEEE 802.11a U-NII</u>
Channels	<u>High</u>
Signal	<u>IEEE802.11a (Crest factor: 1.0)</u>
ConvF	<u>2.07</u>


B. SAR Measurement Results

Frequency (MHz)	5825.000000
Relative permittivity (real part)	34.309906
Relative permittivity (imaginary part)	16.155984
Conductivity (S/m)	5.228256
Variation (%)	3.309999

SURFACE SAR





VOLUME SAR



Maximum location: X=-9.00, Y=27.00

SAR Peak: 0.14 W/kg

SAR 10g (W/Kg)	0.062896
SAR 1g (W/Kg)	0.075694



MEASUREMENT 15

Date of measurement: 16/8/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>IEEE 802.11b ISM</u>
<u>Channels</u>	<u>Low</u>
<u>Signal</u>	<u>IEEE802.11b (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.98</u>


B. SAR Measurement Results

Frequency (MHz)	2412.000000
Relative permittivity (real part)	37.706027
Relative permittivity (imaginary part)	12.966889
Conductivity (S/m)	1.737563
Variation (%)	0.160000

SURFACE SAR





VOLUME SAR



Maximum location: X=-32.00, Y=13.00

SAR Peak: 0.73 W/kg

SAR 10g (W/Kg)	0.227931
SAR 1g (W/Kg)	0.431245



MEASUREMENT 16

Date of measurement: 16/8/2023


A. Experimental conditions.

Area Scan	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
ZoomScan	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body</u>
Band	<u>IEEE 802.11b ISM</u>
Channels	<u>Low</u>
Signal	<u>IEEE802.11b (Crest factor: 1.0)</u>
ConvF	<u>1.98</u>


B. SAR Measurement Results

Frequency (MHz)	2412.000000
Relative permittivity (real part)	37.706027
Relative permittivity (imaginary part)	12.966889
Conductivity (S/m)	1.737563
Variation (%)	-1.810000

SURFACE SAR





VOLUME SAR



Maximum location: X=-12.00, Y=1.00

SAR Peak: 0.23 W/kg

SAR 10g (W/Kg)	0.078526
SAR 1g (W/Kg)	0.132983



MEASUREMENT 17

Date of measurement: 24/8/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 2</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.91</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	38.313965
Relative permittivity (imaginary part)	13.976862
Conductivity (S/m)	1.459806
Variation (%)	2.790000

SURFACE SAR





VOLUME SAR



Maximum location: X=-53.00, Y=-56.00

SAR Peak: 0.68 W/kg

SAR 10g (W/Kg)	0.288506
SAR 1g (W/Kg)	0.470897



MEASUREMENT 18

Date of measurement: 24/8/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 2</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.91</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	38.313965
Relative permittivity (imaginary part)	13.976862
Conductivity (S/m)	1.459806
Variation (%)	-0.090000

SURFACE SAR





VOLUME SAR



Maximum location: X=-9.00, Y=5.00

SAR Peak: 0.78 W/kg

SAR 10g (W/Kg)	0.250807
SAR 1g (W/Kg)	0.484583



MEASUREMENT 19

Date of measurement: 22/8/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 4</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.73</u>


B. SAR Measurement Results

Frequency (MHz)	1732.500000
Relative permittivity (real part)	40.376102
Relative permittivity (imaginary part)	13.720879
Conductivity (S/m)	1.320635
Variation (%)	-0.240000

SURFACE SAR





VOLUME SAR



Maximum location: X=-52.00, Y=-50.00

SAR Peak: 0.42 W/kg

SAR 10g (W/Kg)	0.184212
SAR 1g (W/Kg)	0.294628



MEASUREMENT 20

Date of measurement: 22/8/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 4</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.73</u>


B. SAR Measurement Results

Frequency (MHz)	1732.500000
Relative permittivity (real part)	40.376102
Relative permittivity (imaginary part)	13.720879
Conductivity (S/m)	1.320635
Variation (%)	2.380000

SURFACE SAR





VOLUME SAR



Maximum location: X=-11.00, Y=-10.00

SAR Peak: 0.42 W/kg

SAR 10g (W/Kg)	0.143316
SAR 1g (W/Kg)	0.264219



MEASUREMENT 21

Date of measurement: 21/8/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 5</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.50</u>


B. SAR Measurement Results

Frequency (MHz)	836.500000
Relative permittivity (real part)	41.976952
Relative permittivity (imaginary part)	19.782669
Conductivity (S/m)	0.919345
Variation (%)	1.150000

SURFACE SAR





VOLUME SAR



Maximum location: X=-53.00, Y=-20.00

SAR Peak: 0.65 W/kg

SAR 10g (W/Kg)	0.403561
SAR 1g (W/Kg)	0.536516



MEASUREMENT 22

Date of measurement: 21/8/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 5</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.50</u>


B. SAR Measurement Results

Frequency (MHz)	836.500000
Relative permittivity (real part)	41.976952
Relative permittivity (imaginary part)	19.782669
Conductivity (S/m)	0.919345
Variation (%)	0.010000

SURFACE SAR





VOLUME SAR



Maximum location: X=-24.00, Y=-41.00

SAR Peak: 0.81 W/kg

SAR 10g (W/Kg)	0.359695
SAR 1g (W/Kg)	0.571997



MEASUREMENT 23

Date of measurement: 17/8/2023


A. Experimental conditions.

Area Scan	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
ZoomScan	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
Phantom	<u>Left head</u>
Device Position	<u>Cheek</u>
Band	<u>LTE band 7</u>
Channels	<u>Middle</u>
Signal	<u>LTE (Crest factor: 1.0)</u>
ConvF	<u>1.87</u>


B. SAR Measurement Results

Frequency (MHz)	2535.000000
Relative permittivity (real part)	38.360386
Relative permittivity (imaginary part)	13.367577
Conductivity (S/m)	1.882600
Variation (%)	-3.650000

SURFACE SAR





VOLUME SAR



Maximum location: X=-48.00, Y=-37.00

SAR Peak: 0.27 W/kg

SAR 10g (W/Kg)	0.093171
SAR 1g (W/Kg)	0.166619



MEASUREMENT 24

Date of measurement: 17/8/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 7</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.87</u>


B. SAR Measurement Results

Frequency (MHz)	2535.000000
Relative permittivity (real part)	38.360386
Relative permittivity (imaginary part)	13.367577
Conductivity (S/m)	1.882600
Variation (%)	-0.600000

SURFACE SAR





VOLUME SAR



Maximum location: X=9.00, Y=-36.00

SAR Peak: 0.36 W/kg

SAR 10g (W/Kg)	0.096245
SAR 1g (W/Kg)	0.182860



MEASUREMENT 25

Date of measurement: 18/8/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 12</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.49</u>


B. SAR Measurement Results

Frequency (MHz)	707.500000
Relative permittivity (real part)	40.824425
Relative permittivity (imaginary part)	21.624104
Conductivity (S/m)	0.849947
Variation (%)	3.790000

SURFACE SAR





VOLUME SAR



Maximum location: X=-54.00, Y=-26.00

SAR Peak: 0.53 W/kg

SAR 10g (W/Kg)	0.363908
SAR 1g (W/Kg)	0.449079



MEASUREMENT 26

Date of measurement: 18/8/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 12</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.49</u>


B. SAR Measurement Results

Frequency (MHz)	707.500000
Relative permittivity (real part)	40.824425
Relative permittivity (imaginary part)	21.624104
Conductivity (S/m)	0.849947
Variation (%)	-1.330000

SURFACE SAR





VOLUME SAR



Maximum location: X=7.00, Y=44.00

SAR Peak: 0.71 W/kg

SAR 10g (W/Kg)	0.463555
SAR 1g (W/Kg)	0.586283



MEASUREMENT 27

Date of measurement: 18/8/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 13</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.49</u>


B. SAR Measurement Results

Frequency (MHz)	782.000000
Relative permittivity (real part)	39.936774
Relative permittivity (imaginary part)	20.881654
Conductivity (S/m)	0.907192
Variation (%)	-0.780000

SURFACE SAR





VOLUME SAR



Maximum location: X=-54.00, Y=-26.00

SAR Peak: 0.53 W/kg

SAR 10g (W/Kg)	0.353628
SAR 1g (W/Kg)	0.451373



MEASUREMENT 28

Date of measurement: 18/8/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 13</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.49</u>


B. SAR Measurement Results

Frequency (MHz)	782.000000
Relative permittivity (real part)	39.936774
Relative permittivity (imaginary part)	20.881654
Conductivity (S/m)	0.907192
Variation (%)	-0.330000

SURFACE SAR





VOLUME SAR



Maximum location: X=6.00, Y=1.00

SAR Peak: 0.57 W/kg

SAR 10g (W/Kg)	0.363487
SAR 1g (W/Kg)	0.467549



MEASUREMENT 29

Date of measurement: 18/8/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 17</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.49</u>


B. SAR Measurement Results

Frequency (MHz)	710.000000
Relative permittivity (real part)	40.809074
Relative permittivity (imaginary part)	21.564554
Conductivity (S/m)	0.850602
Variation (%)	2.600000

SURFACE SAR





VOLUME SAR



Maximum location: X=-54.00, Y=-26.00

SAR Peak: 0.54 W/kg

SAR 10g (W/Kg)	0.372479
SAR 1g (W/Kg)	0.463349



MEASUREMENT 30

Date of measurement: 18/8/2023


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 17</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>
<u>ConvF</u>	<u>1.49</u>


B. SAR Measurement Results

Frequency (MHz)	710.000000
Relative permittivity (real part)	40.809074
Relative permittivity (imaginary part)	21.564554
Conductivity (S/m)	0.850602
Variation (%)	-0.410000

SURFACE SAR





VOLUME SAR



Maximum location: X=-5.00, Y=-5.00

SAR Peak: 0.69 W/kg

SAR 10g (W/Kg)	0.455485
SAR 1g (W/Kg)	0.575741



14. Appendix D. Calibration Certificate

Table of contents
E Field Probe - SN 08/16 EPGO287
750 MHz Dipole - SN 03/15 DIP 0G750-355
835 MHz Dipole - SN 03/15 DIP 0G835-347
1800 MHz Dipole - SN 03/15 DIP 1G800-349
1900 MHz Dipole - SN 03/15 DIP 1G900-350
2450 MHz Dipole - SN 03/15 DIP 2G450-352
2600 MHz Dipole - SN 03/15 DIP 2G600-356
5000-6000 MHz Dipole - SN 13/14 WGA 33
Extended Calibration Certificate



COMOSAR E-Field Probe Calibration Report

Ref : ACR.60.1.21.MVGB.A

SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

BUILDING E, FENDA SCIENCE PARK, SANWEI
COMMUNITY, XIXIANG STREET,
BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA
MVG COMOSAR DOSIMETRIC E-FIELD PROBE
SERIAL NO.: SN 08/16 EPG0287

Calibrated at MVG

Z.I. de la pointe du diable

Technopôle Brest Iroise – 295 avenue Alexis de Rochon
29280 PLOUZANE - FRANCE

Calibration date: 01/10/2023



Accreditations #2-6789 and #2-6814
Scope available on www.cofrac.fr


Summary:

This document presents the method and results from an accredited COMOSAR E-Field Probe calibration performed at MVG, using the CALIPROBE test bench, for use with a MVG COMOSAR system only. The test results covered by accreditation are traceable to the International System of Units (SI).



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.60.1.21.MVGB.A

	Name	Function	Date	Signature
Prepared by :	Jérôme Luc	Technical Manager	1/10/2023	
Checked by :	Jérôme Luc	Technical Manager	1/10/2023	
Approved by :	Yann Toutain	Laboratory Director	1/10/2023	

2023.01.10
11:27:33
+01'00'

	Customer Name
Distribution :	SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

Issue	Name	Date	Modifications
A	Jérôme Luc	1/10/2023	Initial release



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.60.1.21.MVGB.A

TABLE OF CONTENTS

1	Device Under Test	4
2	Product Description	4
2.1	General Information	4
3	Measurement Method	4
3.1	Linearity	4
3.2	Sensitivity	5
3.3	Lower Detection Limit	5
3.4	Isotropy	5
3.1	Boundary Effect	5
4	Measurement Uncertainty	6
5	Calibration Measurement Results	6
5.1	Sensitivity in air	6
5.2	Linearity	7
5.3	Sensitivity in liquid	8
5.4	Isotropy	9
6	List of Equipment	10



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.60.1.21.MVGB.A

1 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR DOSIMETRIC E FIELD PROBE
Manufacturer	MVG
Model	SSE2
Serial Number	SN 08/16 EPGO287
Product Condition (new / used)	Used
Frequency Range of Probe	0.15 GHz-6GHz
Resistance of Three Dipoles at Connector	Dipole 1: R1=0.211 MΩ Dipole 2: R2=0.199 MΩ Dipole 3: R3=0.199 MΩ

2 PRODUCT DESCRIPTION

2.1 GENERAL INFORMATION

MVG's COMOSAR E field Probes are built in accordance to the IEEE 1528, FCC KDB865664 D01, CENELEC EN62209 and CEI/IEC 62209 standards.



Figure 1 – MVG COMOSAR Dosimetric E field Dipole

Probe Length	330 mm
Length of Individual Dipoles	2 mm
Maximum external diameter	8 mm
Probe Tip External Diameter	2.5 mm
Distance between dipoles / probe extremity	1 mm

3 MEASUREMENT METHOD

The IEEE 1528, FCC KDB865664 D01, CENELEC EN62209 and CEI/IEC 62209 standards provide recommended practices for the probe calibrations, including the performance characteristics of interest and methods by which to assess their affect. All calibrations / measurements performed meet the fore mentioned standards.

3.1 LINEARITY

The evaluation of the linearity was done in free space using the waveguide, performing a power sweep to cover the SAR range 0.01W/kg to 100W/kg.



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.60.1.21.MVGB.A

3.2 SENSITIVITY

The sensitivity factors of the three dipoles were determined using a two step calibration method (air and tissue simulating liquid) using waveguides as outlined in the standards.

3.3 LOWER DETECTION LIMIT

The lower detection limit was assessed using the same measurement set up as used for the linearity measurement. The required lower detection limit is 10 mW/kg.

3.4 ISOTROPY

The axial isotropy was evaluated by exposing the probe to a reference wave from a standard dipole with the dipole mounted under the flat phantom in the test configuration suggested for system validations and checks. The probe was rotated along its main axis from 0 to 360 degrees in 15-degree steps. The hemispherical isotropy is determined by inserting the probe in a thin plastic box filled with tissue-equivalent liquid, with the plastic box illuminated with the fields from a half wave dipole. The dipole is rotated about its axis (0°–180°) in 15° increments. At each step the probe is rotated about its axis (0°–360°).

3.1 BOUNDARY EFFECT

The boundary effect is defined as the deviation between the SAR measured data and the expected exponential decay in the liquid when the probe is oriented normal to the interface. To evaluate this effect, the liquid filled flat phantom is exposed to fields from either a reference dipole or waveguide. With the probe normal to the phantom surface, the peak spatial average SAR is measured and compared to the analytical value at the surface.

The boundary effect uncertainty can be estimated according to the following uncertainty approximation formula based on linear and exponential extrapolations between the surface and $d_{be} + d_{step}$ along lines that are approximately normal to the surface:

$$SAR_{uncertainty} [\%] = \delta SAR_{be} \frac{(d_{be} + d_{step})^2}{2d_{step}} \frac{(e^{-d_{be}/\delta} - e^{-d_{be} + d_{step}/\delta})}{\delta/2} \quad \text{for } (d_{be} + d_{step}) < 10 \text{ mm}$$

where

$SAR_{uncertainty}$	is the uncertainty in percent of the probe boundary effect
d_{be}	is the distance between the surface and the closest <i>zoom-scan</i> measurement point, in millimetre
d_{step}	is the separation distance between the first and second measurement points that are closest to the phantom surface, in millimetre, assuming the boundary effect at the second location is negligible
δ	is the minimum penetration depth in millimetres of the head tissue-equivalent liquids defined in this standard, i.e., $\delta \approx 14$ mm at 3 GHz;
δSAR_{be}	in percent of SAR is the deviation between the measured SAR value, at the distance d_{be} from the boundary, and the analytical SAR value.



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.60.1.21.MVGB.A

The measured worst case boundary effect SARuncertainty[%] for scanning distances larger than 4mm is 1.0% Limit .2%).

4 MEASUREMENT UNCERTAINTY

The guidelines outlined in the IEEE 1528, OET 65 Bulletin C, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty associated with an E-field probe calibration using the waveguide technique. All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

Uncertainty analysis of the probe calibration in waveguide					
ERROR SOURCES	Uncertainty value (%)	Probability Distribution	Divisor	ci	Standard Uncertainty (%)
Expanded uncertainty 95 % confidence level k = 2					14 %

5 CALIBRATION MEASUREMENT RESULTS

Calibration Parameters	
Liquid Temperature	20 +/- 1 °C
Lab Temperature	20 +/- 1 °C
Lab Humidity	30-70 %

5.1 SENSITIVITY IN AIR

Normx dipole 1 (μV/(V/m) ²)	Normy dipole 2 (μV/(V/m) ²)	Normz dipole 3 (μV/(V/m) ²)
0.72	0.66	0.77

DCP dipole 1 (mV)	DCP dipole 2 (mV)	DCP dipole 3 (mV)
107	110	110

Calibration curves $e_i=f(V)$ (i=1,2,3) allow to obtain E-field value using the formula:


$$E = \sqrt{E_1^2 + E_2^2 + E_3^2}$$



COMOSAR E-FIELD PROBE CALIBRATION REPORT


Ref: ACR.60.1.21.MVGB.A

Calibration curves



5.2 LINEARITY

Linearity



Linearity: +/- 1.90% (+/- 0.08dB)



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.60.1.21.MVGB.A

5.3 SENSITIVITY IN LIQUID

<u>Liquid</u>	<u>Frequency</u> <u>(MHz +/-</u> <u>100MHz)</u>	<u>ConvF</u>
HL750	750	1.49
HL850	835	1.50
HL900	900	1.61
HL1800	1800	1.73
HL1900	1900	1.91
HL2000	2000	1.97
HL2300	2300	1.92
HL2450	2450	1.98
HL2600	2600	1.87
HL3300	3300	1.79
HL3500	3500	1.85
HL3700	3700	1.79
HL3900	3900	2.07
HL4200	4200	2.21
HL4600	4600	2.25
HL4900	4900	2.05
HL5200	5200	1.80
HL5400	5400	2.05
HL5600	5600	2.16
HL5800	5800	2.07

LOWER DETECTION LIMIT: 8mW/kg




COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.60.1.21.MVGB.A

5.4 ISOTROPY

HL1800 MHz





COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.60.1.21.MVGB.A

6 LIST OF EQUIPMENT

Equipment Summary Sheet				
Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date
Flat Phantom	MVG	SN-20/09-SAM71	Validated. No cal required.	Validated. No cal required.
COMOSAR Test Bench	Version 3	NA	Validated. No cal required.	Validated. No cal required.
Network Analyzer	Rohde & Schwarz ZVM	100203	05/2022	05/2025
Network Analyzer – Calibration kit	Rohde & Schwarz ZV-Z235	101223	05/2022	05/2025
Multimeter	Keithley 2000	1160271	02/2022	02/2025
Signal Generator	Rohde & Schwarz SMB	106589	04/2022	04/2025
Amplifier	Aethercomm	SN 046	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Power Meter	NI-USB 5680	170100013	05/2022	05/2025
Directional Coupler	Narda 4216-20	01386	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Waveguide	Mega Industries	069Y7-158-13-712	Validated. No cal required.	Validated. No cal required.
Waveguide Transition	Mega Industries	069Y7-158-13-701	Validated. No cal required.	Validated. No cal required.
Waveguide Termination	Mega Industries	069Y7-158-13-701	Validated. No cal required.	Validated. No cal required.
Temperature / Humidity Sensor	Testo 184 H1	44220687	05/2020	05/2023



SAR Reference Dipole Calibration Report

Ref : ACR.60.2.21.MVGB.A

SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

BUILDING E, FENDA SCIENCE PARK, SANWEI
COMMUNITY, XIXIANG STREET,
BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA
MVG COMOSAR REFERENCE DIPOLE

FREQUENCY: 750 MHZ

SERIAL NO.: SN 03/15 DIP0G750-355

Calibrated at MVG

Z.I. de la pointe du diable

Technopôle Brest Iroise – 295 avenue Alexis de Rochon

29280 PLOUZANE - FRANCE

Calibration date: 03/01/2021



Accreditations #2-6789 and #2-6814
Scope available on www.cofrac.fr


Summary:

This document presents the method and results from an accredited SAR reference dipole calibration performed at MVG, using the COMOSAR test bench. The test results covered by accreditation are traceable to the International System of Units (SI).



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.2.21.MVGB.A

	Name	Function	Date	Signature
Prepared by :	Jérôme Luc	Technical Manager	3/1/2021	
Checked by :	Jérôme Luc	Technical Manager	3/1/2021	
Approved by :	Yann Toutain	Laboratory Director	3/1/2021	

2021.03.0
1 13:08:18
+01'00'

	Customer Name
Distribution :	SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

Issue	Name	Date	Modifications
A	Jérôme Luc	3/1/2021	Initial release



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.2.21.MVGB.A

TABLE OF CONTENTS

1	Introduction.....	4
2	Device Under Test	4
3	Product Description	4
3.1	General Information	4
4	Measurement Method	5
4.1	Return Loss Requirements	5
4.2	Mechanical Requirements	5
5	Measurement Uncertainty.....	5
5.1	Return Loss	5
5.2	Dimension Measurement	5
5.3	Validation Measurement	5
6	Calibration Measurement Results.....	6
6.1	Return Loss and Impedance	6
6.2	Mechanical Dimensions	6
7	Validation measurement	7
7.1	Measurement Condition	7
7.2	Head Liquid Measurement	7
7.3	Measurement Result	8
8	List of Equipment	10



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.2.21.MVGB.A

1 INTRODUCTION

This document contains a summary of the requirements set forth by the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards for reference dipoles used for SAR measurement system validations and the measurements that were performed to verify that the product complies with the fore mentioned standards.

2 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR 750 MHz REFERENCE DIPOLE
Manufacturer	MVG
Model	SID750
Serial Number	SN 03/15 DIP0G750-355
Product Condition (new / used)	Used

3 PRODUCT DESCRIPTION

3.1 GENERAL INFORMATION

MVG's COMOSAR Validation Dipoles are built in accordance to the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards. The product is designed for use with the COMOSAR test bench only.



Figure 1 – MVG COMOSAR Validation Dipole



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.2.21.MVGB.A

4 MEASUREMENT METHOD

The IEEE 1528, FCC KDBs and CEI/IEC 62209 standards provide requirements for reference dipoles used for system validation measurements. The following measurements were performed to verify that the product complies with the fore mentioned standards.

4.1 RETURN LOSS REQUIREMENTS

The dipole used for SAR system validation measurements and checks must have a return loss of -20 dB or better. The return loss measurement shall be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. A direct method is used with a network analyser and its calibration kit, both with a valid ISO17025 calibration.

4.2 MECHANICAL REQUIREMENTS

The IEEE Std. 1528 and CEI/IEC 62209 standards specify the mechanical components and dimensions of the validation dipoles, with the dimension's frequency and phantom shell thickness dependent. The COMOSAR test bench employs a 2 mm phantom shell thickness therefore the dipoles sold for use with the COMOSAR test bench comply with the requirements set forth for a 2 mm phantom shell thickness. A direct method is used with a ISO17025 calibrated caliper.

5 MEASUREMENT UNCERTAINTY

All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

5.1 RETURN LOSS

The following uncertainties apply to the return loss measurement:

Frequency band	Expanded Uncertainty on Return Loss
400-6000MHz	0.08 LIN

5.2 DIMENSION MEASUREMENT

The following uncertainties apply to the dimension measurements:

Length (mm)	Expanded Uncertainty on Length
0 - 300	0.20 mm
300 - 450	0.44 mm

5.3 VALIDATION MEASUREMENT

The guidelines outlined in the IEEE 1528, FCC KDBs, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty for validation measurements.

Scan Volume	Expanded Uncertainty
-------------	----------------------

Page: 5/10

Template_ACR.DDD.N.YY.MVGB.ISSUE_SAR Reference Dipole vG

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.




SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.2.21.MVGB.A

1 g	19 % (SAR)
10 g	19 % (SAR)

6 CALIBRATION MEASUREMENT RESULTS

6.1 RETURN LOSS AND IMPEDANCE



Frequency (MHz)	Return Loss (dB)	Requirement (dB)	Impedance
750	-23.80	-20	56.4 Ω - 0.1 j Ω

6.2 MECHANICAL DIMENSIONS

Frequency MHz	L mm		h mm		d mm	
	required	measured	required	measured	required	measured
300	420.0 $\pm$ 1 %		250.0 $\pm$ 1 %		6.35 $\pm$ 1 %	
450	290.0 $\pm$ 1 %		166.7 $\pm$ 1 %		6.35 $\pm$ 1 %	
750	176.0 $\pm$ 1 %	-	100.0 $\pm$ 1 %	-	6.35 $\pm$ 1 %	-
835	161.0 $\pm$ 1 %		89.8 $\pm$ 1 %		3.6 $\pm$ 1 %	
900	149.0 $\pm$ 1 %		83.3 $\pm$ 1 %		3.6 $\pm$ 1 %	
1450	89.1 $\pm$ 1 %		51.7 $\pm$ 1 %		3.6 $\pm$ 1 %	
1500	80.5 $\pm$ 1 %		50.0 $\pm$ 1 %		3.6 $\pm$ 1 %	
1640	79.0 $\pm$ 1 %		45.7 $\pm$ 1 %		3.6 $\pm$ 1 %	
1750	75.2 $\pm$ 1 %		42.9 $\pm$ 1 %		3.6 $\pm$ 1 %	
1800	72.0 $\pm$ 1 %		41.7 $\pm$ 1 %		3.6 $\pm$ 1 %	
1900	68.0 $\pm$ 1 %		39.5 $\pm$ 1 %		3.6 $\pm$ 1 %	
1950	66.3 $\pm$ 1 %		38.5 $\pm$ 1 %		3.6 $\pm$ 1 %	
2000	64.5 $\pm$ 1 %		37.5 $\pm$ 1 %		3.6 $\pm$ 1 %	
2100	61.0 $\pm$ 1 %		35.7 $\pm$ 1 %		3.6 $\pm$ 1 %	
2300	55.5 $\pm$ 1 %		32.6 $\pm$ 1 %		3.6 $\pm$ 1 %	
2450	51.5 $\pm$ 1 %		30.4 $\pm$ 1 %		3.6 $\pm$ 1 %	

Page: 6/10

Template_ACR.DDD.N.YY.MVGB.ISSUE_SAR Reference Dipole vG

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.2.21.MVGB.A

2600	48.5 ±1 %.		28.8 ±1 %.		3.6 ±1 %.	
3000	41.5 ±1 %.		25.0 ±1 %.		3.6 ±1 %.	
3500	37.0±1 %.		26.4 ±1 %.		3.6 ±1 %.	
3700	34.7±1 %.		26.4 ±1 %.		3.6 ±1 %.	

7 VALIDATION MEASUREMENT

The IEEE Std. 1528, FCC KDBs and CEI/IEC 62209 standards state that the system validation measurements must be performed using a reference dipole meeting the fore mentioned return loss and mechanical dimension requirements. The validation measurement must be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. Per the standards, the dipole shall be positioned below the bottom of the phantom, with the dipole length centered and parallel to the longest dimension of the flat phantom, with the top surface of the dipole at the described distance from the bottom surface of the phantom.

7.1 MEASUREMENT CONDITION

Software	OPENSAR V5
Phantom	SN 13/09 SAM68
Probe	SN 41/18 EPG0333
Liquid	Head Liquid Values: ϵ_r' : 41.8 σ : 0.82
Distance between dipole center and liquid	15.0 mm
Area scan resolution	$dx=8mm/dy=8mm$
Zoon Scan Resolution	$dx=8mm/dy=8mm/dz=5mm$
Frequency	750750 MHz
Input power	20 dBm
Liquid Temperature	20 +/- 1 °C
Lab Temperature	20 +/- 1 °C
Lab Humidity	30-70 %

7.2 HEAD LIQUID MEASUREMENT

Frequency MHz	Relative permittivity (ϵ_r')		Conductivity (σ) S/m	
	required	measured	required	measured
300	45.3 ±10 %		0.87 ±10 %	
450	43.5 ±10 %		0.87 ±10 %	
750	41.9 ±10 %	41.8	0.89 ±10 %	0.82
835	41.5 ±10 %		0.90 ±10 %	
900	41.5 ±10 %		0.97 ±10 %	
1450	40.5 ±10 %		1.20 ±10 %	
1500	40.4 ±10 %		1.23 ±10 %	
1640	40.2 ±10 %		1.31 ±10 %	
1750	40.1 ±10 %		1.37 ±10 %	
1800	40.0 ±10 %		1.40 ±10 %	
1900	40.0 ±10 %		1.40 ±10 %	
1950	40.0 ±10 %		1.40 ±10 %	
2000	40.0 ±10 %		1.40 ±10 %	

Page: 7/10

Template_ACR.DDD.N.YY.MVGB.ISSUE_SAR Reference Dipole vG

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.2.21 MVGB.A

2100	39.8 ±10 %		1.49 ±10 %	
2300	39.5 ±10 %		1.67 ±10 %	
2450	39.2 ±10 %		1.80 ±10 %	
2600	39.0 ±10 %		1.96 ±10 %	
3000	38.5 ±10 %		2.40 ±10 %	
3500	37.9 ±10 %		2.91 ±10 %	

7.3 MEASUREMENT RESULT



The IEEE Std. 1528 and CEI/IEC 62209 standards state that the system validation measurements should produce the SAR values shown below (for phantom thickness of 2 mm), within the uncertainty for the system validation. All SAR values are normalized to 1 W forward power. In bracket, the measured SAR is given with the used input power.

Frequency MHz	1 g SAR (W/kg/W)		10 g SAR (W/kg/W)	
	required	measured	required	measured
300	2.85		1.94	
450	4.58		3.06	
750	8.49	8.53 (0.85)	5.55	5.56 (0.56)
835	9.56		6.22	
900	10.9		6.99	
1450	29		16	
1500	30.5		16.8	
1640	34.2		18.4	
1750	36.4		19.3	
1800	38.4		20.1	
1900	39.7		20.5	
1950	40.5		20.9	
2000	41.1		21.1	
2100	43.6		21.9	
2300	48.7		23.3	
2450	52.4		24	
2600	55.3		24.6	
3000	63.8		25.7	
3500	67.1		25	



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.2.21.MVGB.A





SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.2.21.MVGB.A

8 LIST OF EQUIPMENT

Equipment Summary Sheet				
Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date
SAM Phantom	MVG	SN-13/09-SAM68	Validated. No cal required.	Validated. No cal required.
COMOSAR Test Bench	Version 3	NA	Validated. No cal required.	Validated. No cal required.
Network Analyzer	Rohde & Schwarz ZVM	100203	05/2019	05/2022
Network Analyzer – Calibration kit	Rohde & Schwarz ZV-Z235	101223	05/2019	05/2022
Calipers	Mitutoyo	SN 0009732	10/2019	10/2022
Reference Probe	MVG	EPGO333 SN 41/18	05/2020	05/2021
Multimeter	Keithley 2000	1160271	02/2020	02/2023
Signal Generator	Rohde & Schwarz SMB	106589	04/2019	04/2022
Amplifier	Aethercomm	SN 046	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Power Meter	NI-USB 5680	170100013	05/2019	05/2022
Directional Coupler	Narda 4216-20	01386	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Temperature / Humidity Sensor	Testo 184 H1	44220687	05/2020	05/2023



SAR Reference Dipole Calibration Report

Ref : ACR.60.3.21.MVGB.A

SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

BUILDING E, FENDA SCIENCE PARK, SANWEI
COMMUNITY, XIXIANG STREET,
BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA

MVG COMOSAR REFERENCE DIPOLE

FREQUENCY: 835 MHZ

SERIAL NO.: SN 03/15 DIP0G835-347

Calibrated at MVG

Z.I. de la pointe du diable

Technopôle Brest Iroise – 295 avenue Alexis de Rochon
29280 PLOUZANE - FRANCE

Calibration date: 03/01/2021



Accreditations #2-6789 and #2-6814
Scope available on www.cofrac.fr

Summary:

This document presents the method and results from an accredited SAR reference dipole calibration performed at MVG, using the COMOSAR test bench. The test results covered by accreditation are traceable to the International System of Units (SI).



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.3.21.MVGB.A

	Name	Function	Date	Signature
Prepared by :	Jérôme Luc	Technical Manager	3/1/2021	<i>JL</i>
Checked by :	Jérôme Luc	Technical Manager	3/1/2021	<i>JL</i>
Approved by :	Yann Toutain	Laboratory Director	3/1/2021	<i>Yann Toutain</i>

2021.03.0
1 13:09:12
+01'00'

	Customer Name
Distribution :	SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

Issue	Name	Date	Modifications
A	Jérôme Luc	3/1/2021	Initial release



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.3.21.MVGB.A

TABLE OF CONTENTS

1	Introduction.....	4
2	Device Under Test	4
3	Product Description	4
3.1	General Information	4
4	Measurement Method	5
4.1	Return Loss Requirements	5
4.2	Mechanical Requirements	5
5	Measurement Uncertainty.....	5
5.1	Return Loss	5
5.2	Dimension Measurement	5
5.3	Validation Measurement	5
6	Calibration Measurement Results.....	6
6.1	Return Loss and Impedance	6
6.2	Mechanical Dimensions	6
7	Validation measurement	7
7.1	Measurement Condition	7
7.2	Head Liquid Measurement	7
7.3	Measurement Result	8
8	List of Equipment	10



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.3.21.MVGB.A

1 INTRODUCTION

This document contains a summary of the requirements set forth by the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards for reference dipoles used for SAR measurement system validations and the measurements that were performed to verify that the product complies with the fore mentioned standards.

2 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR 835 MHz REFERENCE DIPOLE
Manufacturer	MVG
Model	SID835
Serial Number	SN 03/15 DIP0G835-347
Product Condition (new / used)	Used

3 PRODUCT DESCRIPTION

3.1 GENERAL INFORMATION

MVG's COMOSAR Validation Dipoles are built in accordance to the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards. The product is designed for use with the COMOSAR test bench only.



Figure 1 – MVG COMOSAR Validation Dipole



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.3.21.MVGB.A

4 MEASUREMENT METHOD

The IEEE 1528, FCC KDBs and CEI/IEC 62209 standards provide requirements for reference dipoles used for system validation measurements. The following measurements were performed to verify that the product complies with the fore mentioned standards.

4.1 RETURN LOSS REQUIREMENTS

The dipole used for SAR system validation measurements and checks must have a return loss of -20 dB or better. The return loss measurement shall be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. A direct method is used with a network analyser and its calibration kit, both with a valid ISO17025 calibration.

4.2 MECHANICAL REQUIREMENTS

The IEEE Std. 1528 and CEI/IEC 62209 standards specify the mechanical components and dimensions of the validation dipoles, with the dimension's frequency and phantom shell thickness dependent. The COMOSAR test bench employs a 2 mm phantom shell thickness therefore the dipoles sold for use with the COMOSAR test bench comply with the requirements set forth for a 2 mm phantom shell thickness. A direct method is used with a ISO17025 calibrated caliper.

5 MEASUREMENT UNCERTAINTY

All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

5.1 RETURN LOSS

The following uncertainties apply to the return loss measurement:

Frequency band	Expanded Uncertainty on Return Loss
400-6000MHz	0.08 LIN

5.2 DIMENSION MEASUREMENT

The following uncertainties apply to the dimension measurements:

Length (mm)	Expanded Uncertainty on Length
0 - 300	0.20 mm
300 - 450	0.44 mm

5.3 VALIDATION MEASUREMENT

The guidelines outlined in the IEEE 1528, FCC KDBs, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty for validation measurements.

Scan Volume	Expanded Uncertainty
-------------	----------------------




SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.3.21.MVGB.A

1 g	19 % (SAR)
10 g	19 % (SAR)

6 CALIBRATION MEASUREMENT RESULTS

6.1 RETURN LOSS AND IMPEDANCE



Frequency (MHz)	Return Loss (dB)	Requirement (dB)	Impedance
835	-25.44	-20	54.4 Ω - 2.9 j Ω

6.2 MECHANICAL DIMENSIONS

Frequency MHz	L mm		h mm		d mm	
	required	measured	required	measured	required	measured
300	420.0 $\pm$ 1 %.		250.0 $\pm$ 1 %.		6.35 $\pm$ 1 %.	
450	290.0 $\pm$ 1 %.		166.7 $\pm$ 1 %.		6.35 $\pm$ 1 %.	
750	176.0 $\pm$ 1 %.		100.0 $\pm$ 1 %.		6.35 $\pm$ 1 %.	
835	161.0 $\pm$ 1 %.	-	89.8 $\pm$ 1 %.	-	3.6 $\pm$ 1 %.	-
900	149.0 $\pm$ 1 %.		83.3 $\pm$ 1 %.		3.6 $\pm$ 1 %.	
1450	89.1 $\pm$ 1 %.		51.7 $\pm$ 1 %.		3.6 $\pm$ 1 %.	
1500	80.5 $\pm$ 1 %.		50.0 $\pm$ 1 %.		3.6 $\pm$ 1 %.	
1640	79.0 $\pm$ 1 %.		45.7 $\pm$ 1 %.		3.6 $\pm$ 1 %.	
1750	75.2 $\pm$ 1 %.		42.9 $\pm$ 1 %.		3.6 $\pm$ 1 %.	
1800	72.0 $\pm$ 1 %.		41.7 $\pm$ 1 %.		3.6 $\pm$ 1 %.	
1900	68.0 $\pm$ 1 %.		39.5 $\pm$ 1 %.		3.6 $\pm$ 1 %.	
1950	66.3 $\pm$ 1 %.		38.5 $\pm$ 1 %.		3.6 $\pm$ 1 %.	
2000	64.5 $\pm$ 1 %.		37.5 $\pm$ 1 %.		3.6 $\pm$ 1 %.	
2100	61.0 $\pm$ 1 %.		35.7 $\pm$ 1 %.		3.6 $\pm$ 1 %.	
2300	55.5 $\pm$ 1 %.		32.6 $\pm$ 1 %.		3.6 $\pm$ 1 %.	
2450	51.5 $\pm$ 1 %.		30.4 $\pm$ 1 %.		3.6 $\pm$ 1 %.	

Page: 6/10

Template_ACR.DDD.N.YY.MVGB.ISSUE_SAR Reference Dipole vG

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.3.21.MVGB.A

2600	48.5 ±1 %.		28.8 ±1 %.		3.6 ±1 %.	
3000	41.5 ±1 %.		25.0 ±1 %.		3.6 ±1 %.	
3500	37.0±1 %.		26.4 ±1 %.		3.6 ±1 %.	
3700	34.7±1 %.		26.4 ±1 %.		3.6 ±1 %.	

7 VALIDATION MEASUREMENT

The IEEE Std. 1528, FCC KDBs and CEI/IEC 62209 standards state that the system validation measurements must be performed using a reference dipole meeting the fore mentioned return loss and mechanical dimension requirements. The validation measurement must be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. Per the standards, the dipole shall be positioned below the bottom of the phantom, with the dipole length centered and parallel to the longest dimension of the flat phantom, with the top surface of the dipole at the described distance from the bottom surface of the phantom.

7.1 MEASUREMENT CONDITION

Software	OPENSAR V5
Phantom	SN 13/09 SAM68
Probe	SN 41/18 EPG0333
Liquid	Head Liquid Values: ϵ_r' : 40.6 sigma : 0.89
Distance between dipole center and liquid	15.0 mm
Area scan resolution	dx=8mm/dy=8mm
Zoon Scan Resolution	dx=8mm/dy=8mm/dz=5mm
Frequency	835835 MHz
Input power	20 dBm
Liquid Temperature	20 +/- 1 °C
Lab Temperature	20 +/- 1 °C
Lab Humidity	30-70 %

7.2 HEAD LIQUID MEASUREMENT

Frequency MHz	Relative permittivity (ϵ_r')		Conductivity (σ) S/m	
	required	measured	required	measured
300	45.3 ±10 %		0.87 ±10 %	
450	43.5 ±10 %		0.87 ±10 %	
750	41.9 ±10 %		0.89 ±10 %	
835	41.5 ±10 %	40.6	0.90 ±10 %	0.89
900	41.5 ±10 %		0.97 ±10 %	
1450	40.5 ±10 %		1.20 ±10 %	
1500	40.4 ±10 %		1.23 ±10 %	
1640	40.2 ±10 %		1.31 ±10 %	
1750	40.1 ±10 %		1.37 ±10 %	
1800	40.0 ±10 %		1.40 ±10 %	
1900	40.0 ±10 %		1.40 ±10 %	
1950	40.0 ±10 %		1.40 ±10 %	
2000	40.0 ±10 %		1.40 ±10 %	

Page: 7/10

Template_ACR.DDD.N.YY.MVGB.ISSUE_SAR Reference Dipole vG

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.3.21.MVGB.A

2100	39.8 ±10 %		1.49 ±10 %	
2300	39.5 ±10 %		1.67 ±10 %	
2450	39.2 ±10 %		1.80 ±10 %	
2600	39.0 ±10 %		1.96 ±10 %	
3000	38.5 ±10 %		2.40 ±10 %	
3500	37.9 ±10 %		2.91 ±10 %	

7.3 MEASUREMENT RESULT

The IEEE Std. 1528 and CEI/IEC 62209 standards state that the system validation measurements should produce the SAR values shown below (for phantom thickness of 2 mm), within the uncertainty for the system validation. All SAR values are normalized to 1 W forward power. In bracket, the measured SAR is given with the used input power.

Frequency MHz	1 g SAR (W/kg/W)		10 g SAR (W/kg/W)	
	required	measured	required	measured
300	2.85		1.94	
450	4.58		3.06	
750	8.49		5.55	
835	9.56	9.84 (0.98)	6.22	6.22 (0.62)
900	10.9		6.99	
1450	29		16	
1500	30.5		16.8	
1640	34.2		18.4	
1750	36.4		19.3	
1800	38.4		20.1	
1900	39.7		20.5	
1950	40.5		20.9	
2000	41.1		21.1	
2100	43.6		21.9	
2300	48.7		23.3	
2450	52.4		24	
2600	55.3		24.6	
3000	63.8		25.7	
3500	67.1		25	



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.3.21.MVGB.A

