



RF Exposure Evaluation Declaration

FCC ID: Z9G-EDF131

APPLICANT: Edifier International Limited

Application Type: Certification

Product: Gaming Speakers

Model No.: EDF701001

Brand Name: EDIFIER, HECATE

FCC Rule Part(s): FCC Part 2 (Section 2.1091)
KDB 447498 D01 General RF Exposure Guidance v06
IEEE C95.1-1992

Test Date: February 01 ~ 04, 2021

Reviewed By:

Jame Yuan

Approved By:

Robin Wu



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Shenzhen) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2101RSU081-U2	Rev. 01	Initial Report	02-25-2021	Valid

1. PRODUCT INFORMATION

1.1. Equipment Description

Product Name	Gaming Speakers
Model No.	EDF701001
Operating Temp.	0 ~ 45°C
Rated Input	100-240V~50/60Hz, 400mA
Bluetooth Version	v5.0 single mode, BR/EDR only

1.2. Product Specification Subjective to this Report

Operating Frequency	2402~2480MHz
Channel Number	79
Type of modulation	GFSK, Pi/4 DQPSK, 8DPSK
Data Rate	1Mbps (GFSK), 2Mbps ($\pi/4$ DQPSK), 3Mbps (8DPSK)
Antenna Type	PIFA Antenna
Antenna Gain	-0.29dBi

2. RF Exposure Evaluation

2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	f/1500	6
1500-100,000	--	--	1	30

f= Frequency in MHz

Calculation Formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2. Test Result of RF Exposure Evaluation

Product	Gaming Speakers
Test Item	RF Exposure Evaluation

Test Mode	Frequency Band (MHz)	Maximum Output Power (dBm)	E.I.R.P (dBm)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)
Bluetooth	2402 ~ 2480	12.04	11.75	0.0030	1

CONCLUSION:

The Max Power Density at R (20 cm) = 0.0030mW/cm² < 1mW/cm².

So the EUT complies with the requirement.

_____ The End _____

Appendix - EUT Photograph

Refer to “2101RSU081-UE” file.