

# **CERTIFICATION TEST REPORT**

# **Report Number. :** 12220680-E2V2

- Applicant : SRAM LLC 1000 W Fulton Market 4<sup>th</sup> Floor Chicago, IL 60607 U.S.A.
  - Model : 55501
  - FCC ID : C9O-PMB1
    - IC : 10161A-PMB1
- EUT Description : TIRE PRESSURE MONITOR
- Test Standard(s) : FCC 47 CFR PART 15 SUBPART C ISED RSS-210 ISSUE 9 ISED RSS-GEN ISSUE 5

Date Of Issue: June 27, 2018

Prepared by: UL Verification Services Inc. 47173 Benicia Street Fremont, CA 94538 U.S.A. TEL: (510) 771-1000 FAX: (510) 661-0888



# **REPORT REVISION HISTORY**

Rev.	lssue Date	Revisions	Revised By
V1	06/05/2018	Initial Issue	
V2	06/27/2018	Updated cover page, Sections 1, 5.2, 9, 9.1, and 9.2.	Steven Tran

Page 2 of 38

# TABLE OF CONTENTS

RE	POR	RT REVISION HISTORY	2
TA	BLE	OF CONTENTS	3
1.	AT	TESTATION OF TEST RESULTS	4
2.	ΤE	ST METHODOLOGY	5
3.	FA	CILITIES AND ACCREDITATION	5
4.	СА	LIBRATION AND UNCERTAINTY	6
4	4.1.	MEASURING INSTRUMENT CALIBRATION	6
4	4.2.	SAMPLE CALCULATION	6
4	1.3.	MEASUREMENT UNCERTAINTY	6
5.	EQ	UIPMENT UNDER TEST	7
5	5.1.	EUT DESCRIPTION	7
5	5.2.	MAXIMUM FUNDAMENTAL FIELD STRENGTH	7
5	5.3.	DESCRIPTION OF AVAILABLE ANTENNAS	7
5	5.4.	SOFTWARE AND FIRMWARE	7
5	5.5.	WORST-CASE CONFIGURATION AND MODE	7
5	5.6.	DESCRIPTION OF TEST SETUP	8
6.	ΤE	ST AND MEASUREMENT EQUIPMENT1	1
7.	ME	ASUREMENT METHODS1	2
8.	AN	ITENNA PORT TEST RESULTS1	3
8	3.1.	ON TIME AND DUTY CYCLE1	13
8	3.2.	99% BANDWIDTH1	14
8	3.3.	20dB BANDWIDTH1	15
9.	RA	DIATED TEST RESULTS1	7
g	9.1.	TRANSMITTER ABOVE 1 GHz1	19
g	9.2.	FUNDAMENTAL FREQUENCY RADIATED EMISSION2	29
g	9.3.	WORSE CASE BELOW 30MHz	30
g	9.4.	WORST CASE BELOW 1GHz	32
g	9.5.	WORST CASE 18-26 GHz	34
10.	5	SETUP PHOTOS	6

Page 3 of 38

# **1. ATTESTATION OF TEST RESULTS**

	STANDARD	TEST RESULTS			
APPLICABLE STANDARDS					
DATE TESTED:	May 11, 2018 – June 27, 2018				
SERIAL NUMBER: AGG10127 (Conducted), AGG10292 (Radiated)		292 (Radiated)			
MODEL:	55501				
EUT DESCRIPTION:	Tire Pressure Monitor				
COMPANY NAME:	SRAM LLC 1000 W Fulton Market 4 <sup>th</sup> Floor Chicago, IL 60607 U.S.A.				

CFR 47 Part 15 Subpart CCompliesISED RSS-210 Issue 9CompliesISED RSS-GEN Issue 5Complies

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

**Note:** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of the U.S. government.

Approved & Released For UL Verification Services Inc. By:

Prepared By:

Dan Coronia CONSUMER TECHNOLOGY DIVISION Operations Leader UL Verification Services Inc. glen June

Glenn Escano CONSUMER TECHNOLOGY DIVISION Test Engineer UL Verification Services Inc.

Page 4 of 38

# 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with FCC CFR 47 Part 2, FCC CFR 47 Part 15, ANSI C63.10-2013, RSS-GEN Issue 5, and RSS-210 Issue 9.

# 3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

47173 Benicia Street	47266 Benicia Street
Chamber A (ISED:2324B-1)	Chamber D (ISED:22541-1)
Chamber B (ISED:2324B-2)	Chamber E (ISED:22541-2)
Chamber C (ISED:2324B-3)	Chamber F (ISED:22541-3)
47685 Kato Road	Chamber G (ISED:22541-4)
Chamber K*	Chamber H (ISED:22541-5)

\*Note: Chamber K does not currently have an ISED number.

The above test sites and facilities are covered under FCC Test Firm Registration # 208313. Chambers A through C are covered under ISED company address code 2324B with site numbers 2324B -1 through 2324B-3, respectively. Chambers D through H are covered under ISED company address code 22541 with site numbers 22541 -1 through 22541-5, respectively.

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <u>http://nist.gov/standards/scopes/2000650.htm.</u>

Page 5 of 38

# 4. CALIBRATION AND UNCERTAINTY

# 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

# 4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided:

Field Strength (dBuV/m) = Measured Voltage (dBuV) + Antenna Factor (dB/m) + Cable Loss (dB) – Preamp Gain (dB) 36.5 dBuV + 18.7 dB/m + 0.6 dB – 26.9 dB = 28.9 dBuV/m

# 4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Worst Case Conducted Disturbance, 9KHz to 0.15 MHz	3.84 dB
Worst Case Conducted Disturbance, 0.15 to 30 MHz	3.65 dB
Worst Case Radiated Disturbance, 9KHz to 30 MHz	3.15 dB
Worst Case Radiated Disturbance, 30 to 1000 MHz	5.36 dB
Worst Case Radiated Disturbance, 1000 to 18000 MHz	4.32 dB
Worst Case Radiated Disturbance, 18000 to 26000 MHz	4.45 dB
Worst Case Radiated Disturbance, 26000 to 40000 MHz	5.24 dB

Uncertainty figures are valid to a confidence level of 95%.

# 5. EQUIPMENT UNDER TEST

# 5.1. EUT DESCRIPTION

The EUT is a Tire Pressure Monitor which is using BLE and ANT+ technologies, powered by CR1632, a coin cell battery.

# 5.2. MAXIMUM FUNDAMENTAL FIELD STRENGTH

The transmitter has a maximum peak fundamental field strength as follows:

Frequency Range	Mode	Peak E-field Strength	Avg E-field Strength	Distance
(MHz)		(dBuV/m)	(dBuV/m)	(m)
2405 - 2475	ANT +	87.75	87.13	3.00

# 5.3. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes a chip antenna, with a maximum gain of -2 dBi.

# 5.4. SOFTWARE AND FIRMWARE

The EUT firmware installed during testing was A-1.0.

The test utility software used during testing was Lightblue v2.6.4

# 5.5. WORST-CASE CONFIGURATION AND MODE

Radiated emissions below 1GHz and above 18GHz were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

Band edge and radiated emissions between 1GHz and 18GHz were performed with the EUT set to transmit at the highest power on low, middle and high channels.

The fundamental of the EUT was investigated in three orthogonal orientations X, Y, Z, it was determined that Y orientation was worst-case orientation; therefore, all final radiated testing was performed with the EUT in Y orientation.

Page 7 of 38

# 5.6. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

Support Equipment List						
Description Manufacturer Model Serial Number						
Ipod Touch	Apple	MKJ02LL/A	CCQVRHY2GGNL			

#### TEST SETUP

The EUT is powered by a coin cell battery. The iPod Touch wirelessly sends commands to the EUT.

Page 8 of 38

### SETUP DIAGRAM FOR CONDUCTED TESTS



Note – The DC power supply is used only during testing. During normal operation the EUT is powered by a supplied CR1632, coin cell battery.

Page 9 of 38

#### SETUP DIAGRAM FOR RADIATED TESTS



Page 10 of 38

# 6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST								
Description	Manufacturer	Model	ID Num	Cal Due	Last Cal			
Amplifier, 10KHz to 1GHz, 32dB	Agilent (Keysight) Technologies	8447D	T10	02/14/2019	02/14/2018			
Antenna, Broadband Hybrid, 30MHz to 2000MHz	Sunol Sciences Corp.	JB1	T130	10/16/2018	10/16/2017			
Antenna, Horn 1-18GHz	ETS-Lindgren	3117	T345	04/25/2019	04/25/2018			
Antenna, Horn 1-18GHz	ETS-Lindgren	3117	EMC4294	04/30/2019	04/17/2018			
Antenna, Horn, 18-26GHz	ARA	MWH-1826G	T89	01/18/2019	01/18/2018			
Bluetooth Tester	Rohde & Schwarz (Koeln) GmbH & Co. KG	СВТ	T258	02/23/2019	02/23/2018			
RF Amplifier, 1-18GHz	MITEQ	AFS42- 00101800-25-S- 42	T1165	06/12/2019	06/12/2018			
RF Preamplifier, 1-26GHz	Agilent	8449B	T404	03/09/2019	03/09/2018			
Semi anechoic Chamber A	TDK RF SOLUTIONS INC.	N/A	T1199	02/19/2020	02/19/2018			
Spectrum Analyzer, PXA, 3Hz to 44GHz	Agilent (Keysight) Technologies	N9030A	T1466	04/16/2019	04/16/2018			
ESW EMI Test Receiver	Rohde & Schwarz	ESR44	PRE0179522	05/11/2019	05/11/2018			
Thermo-Hygrometer	Extech Instruments Corporation	445703	T916	06/23/2018	06/23/2017			
Thermometer - Digital	Control Company	14-650-118	PRE0177862	02/22/2019	02/22/2018			
Thermometer - Digital	Control Company	14-650-118	PRE0177861	02/26/2019	02/26/2018			

Test Software List						
Description	Manufacturer	Model	Version			
Antenna Port Software	UL	UL RF	Ver 7.9, Jan 24, 2018			
Radiated Software	UL	UL EMC	Ver 9.5, Dec 01, 2016			

Page 11 of 38

# 7. MEASUREMENT METHODS

On Time and Duty Cycle: ANSI C63.10-2013 Section 11.6

Occupied BW (20dB): ANSI C63.10-2013 Section 6.9.2

Occupied BW (99%): ANSI C63.10-2013 Section 6.9.3

Radiated Spurious Emissions 30-1000MHz: ANSI C63.10-2013 Section 6.3 and 6.5

Radiated Spurious Emissions above 1GHz: ANSI C63.10-2013 Section 6.3 and 6.6

Radiated Band-edge: ANSI C63.10-2013 Section 6.10.5

Page 12 of 38

# 8. ANTENNA PORT TEST RESULTS

# 8.1. ON TIME AND DUTY CYCLE

### LIMITS

None; for reporting purposes only.

#### PROCEDURE

KDB 558074 Zero-Span Spectrum Analyzer Method.

### **ON TIME AND DUTY CYCLE RESULTS**

Mode	<b>ON</b> Time	Period	<b>Duty Cycle</b>	Duty	Duty Cycle	1/T
	В		x	Cycle	<b>Correction Factor</b>	Minimum VBW
	(msec)	(msec)	(linear)	(%)	(dB)	(kHz)
ANT+	1.00	1.00	1.000	100.0%	0.00	0.010

Det 20 2 2	2110),390 1Bm	ט, Condui 0++on 30	dB	<b>∆</b> Mkr2	80.1 ms 0.04 dB	Center Fred
#Peak					0.04 GD	2.44000000 GHz
Log 10 dB/ Offst	2R ()				¢	Start Fred 2.44000000 GHz
0.2 dB						Stop Fred 2.44000000 GHz
#PAvg						<b>CF Step</b> 8.00000000 MHz <u>Auto</u> Mar
Center 2.4	140 000 G M⊔⊸	Hz		Sucon 100 mc (	Span 0 Hz	Freq Offset
Marker	Trace	Type	X Axis	Ameep 100 ms (.	plitude	0.00000000 Hz
1R 1 2R	(1) (1) (1)	Time Time Time Time	10 ms 80.1 ms 9.9 ms	0. ( 0.	85 dBm 3.03 dB 84 dBm	Signal Track
28		TIME	80.1 WS	ł	9.84 QB	

### 8.2. 99% **BANDWIDTH**

### <u>LIMITS</u>

None; for reporting purposes only.

#### TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The RBW is set to  $\geq$  1% of the 20 dB bandwidth. The VBW is set to  $\geq$  RBW. The sweep time is coupled

#### **RESULTS**

Channel	Frequency	99% Bandwidth
	(MHz)	(KHz)
Low	2405	915.42
Mid	2440	882.79
High	2475	914.17





Page 14 of 38

### 8.3. 20dB BANDWIDTH

### <u>LIMITS</u>

None; for reporting purposes only.

### TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. The RBW is set to  $\geq$  1% of the 20 dB bandwidth. The VBW is set to  $\geq$  RBW. The sweep time is coupled

#### **RESULTS**

Channel	Frequency	20dB Bandwidth
	(MHz)	(KHz)
Low	2405	942.4
Middle	2440	889.7
High	2475	953.6

Page 15 of 38





Page 16 of 38

# 9. RADIATED TEST RESULTS

### <u>LIMITS</u>

FCC 15.249 FCC §15.205 and §15.209

RSS-GEN, Section 8.9 and 8.10.

Operation within the bands 902–928 MHz, 2400–2483.5 MHz, 5725–5875 MHZ, and 24.0–24.25 GHz.

(a) Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts/ meter)	Field strength of harmonics (microvolts/ meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24.0–24.25 GHz	250	2500

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation.

(e) As shown in Sec. 15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

Frequency (MHz)	Field strength (microvolts/meter)	Measure- ment dis- tance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100 **	3
88–216	150 **	3
216-960	200 **	3
Above 960	500	3

\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 MHz, 76– 88 MHz, 174–216 MHz or 470–806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

Page 17 of 38

#### TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For pre-scans above 1 GHz the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 30 KHz for peak measurements.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T (10 Hz) video bandwidth with peak detector for average measurements.

The spectrum from 1 GHz to 18 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in each applicable band. Below 1GHz and above 18GHz emissions, the channel with the highest output power was tested.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

Page 18 of 38

# 9.1. TRANSMITTER ABOVE 1 GHz

# **BANDEDGE (LOW CHANNEL)**



### HORIZONTAL RESULT

### **Trace Markers**

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T407 (dB)	Amp/Cbl/Fltr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	44.13	Pk	31.8	-21.5	54.43	-	-	74	-19.57	171	254	Н
2	* 2.371	45.24	Pk	31.7	-21.3	55.64	-	-	74	-18.36	171	254	Н
3	* 2.39	26.6	VA1T	31.8	-21.5	36.9	54	-17.1	-	-	171	254	Н
4	* 2.381	28.5	VA1T	31.7	-21.5	38.7	54	-15.3	-	-	171	254	Н

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

### VERTICAL RESULT



### Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T407 (dB)	Amp/Cbl/Fltr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	* 2.371	45.61	Pk	31.7	-21.3	56.01	-	-	74	-17.99	162	200	V
4	* 2.381	28.39	VA1T	31.7	-21.5	38.59	54	-15.41	-	-	162	200	V
1	* 2.39	44.83	Pk	31.8	-21.5	55.13	-	-	74	-18.87	162	200	V
3	* 2.39	26.58	VA1T	31.8	-21.5	36.88	54	-17.12	-	-	162	200	V

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

Page 20 of 38

### **BANDEDGE (HIGH CHANNEL)**



# HORIZONTAL RESULT

#### **Trace Markers**

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T407 (dB)	Amp/Cbl/Fltr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	36.57	Pk	32.4	-21.5	47.47	-	-	74	-26.53	175	242	Н
3	* 2.484	24.99	VA1T	32.4	-21.5	35.89	54	-18.11	-	-	175	242	Н
2	2.503	38.73	Pk	32.5	-21.4	49.83		-	74	-24.17	175	242	Н
4	2.538	25.11	VA1T	32.3	-21.2	36.21	54	-17.79	-	-	175	242	Н

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

Page 21 of 38

### **VERTICAL RESULT**



### Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T407 (dB)	Amp/Cbl/Fltr/Pad (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	44.57	Pk	32.4	-21.5	55.47	-	-	74	-18.53	166	120	V
3	* 2.484	26.9	VA1T	32.4	-21.5	37.8	54	-16.2	-	-	166	120	V
4	2.505	26.99	VA1T	32.5	-21.4	38.09	54	-15.91	-	-	166	120	V
2	2.559	45.68	Pk	32.4	-21.3	56,78	-	-	74	-17.22	166	120	V

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

Page 22 of 38

### HARMONICS AND SPURIOUS EMISSIONS



# LOW CHANNEL RESULTS

### HORIZTONAL



Page 23 of 38

### **RADIATED EMISSIONS**

Frequency (GHz)	Meter Reading	Det	AF T407	Amp/Cbl/Fltr/Pad (dB)	Corrected Reading	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin	Azimuth (Degs)	Height (cm)	Polarity
	(aBuv)		(aB)		(aBuv/m)				(aB)			
* 1.373	31.88	PKFH	29.2	-9.8	51.28	-	-	74	-22.72	141	200	Н
* 1.373	18.27	VA1T	29.2	-9.8	37.67	54	-16.33	-	-	141	200	Н
* 1.32	31.65	PKFH	29	-9.9	50.75	-	-	74	-23.25	123	102	V
* 1.32	18.56	VA1T	29	-9.9	37.66	54	-16.34	-	-	123	102	V
* 4.81	40.9	PKFH	34.2	-31	44.1	-	-	74	-29.9	336	180	Н
* 4.81	30.79	VA1T	34.2	-31	33.99	54	-20.01	-	-	336	180	Н
7.215	46.19	PKFH	35.5	-26.8	54.89	-	-	74	-19.11	152	185	Н
7.215	40.74	VA1T	35.5	-26.8	49.44	54	-4.56	-	-	152	185	Н
* 4.81	41.33	PKFH	34.2	-31	44.53	-	-	74	-29.47	69	105	V
* 4.81	31.35	VA1T	34.2	-31	34.55	54	-19.45	-	-	69	105	V
7.214	44.7	PKFH	35.5	-26.8	53.4	-	-	74	-20.6	130	123	V
7.215	38.82	VA1T	35.5	-26.8	47.52	54	-6.48	-	-	130	123	V

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band PKFH - FHSS: RB=100k/1MHz VB=3 x RB, Peak

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

Page 24 of 38

### **MID CHANNEL RESULTS**



### HORIZTONAL



Page 25 of 38

### **RADIATED EMISSIONS**

Frequency (GHz)	Meter Reading	Det	AF T407	Amp/Cbl/Fltr/Pad (dB)	Corrected Reading	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin	Azimuth (Degs)	Height (cm)	Polarity
. ,	(dBuV)		(dB)	· · /	(dBuV/m)	, ,	· ,	· · ·	(dĔ)	,	• •	
* 1.374	31.42	PKFH	29.2	-9.8	50.82	-	-	74	-23.18	173	103	Н
* 1.375	18.28	VA1T	29.2	-9.8	37.68	54	-16.32	-	-	173	103	Н
* 1.34	31.48	PKFH	29.3	-9.8	50.98	-	-	74	-23.02	240	102	V
* 1.342	17.7	VA1T	29.3	-9.8	37.2	54	-16.8	-	-	240	102	V
* 4.88	41.09	PKFH	34.1	-31	44.19	-	-	74	-29.81	54	108	Н
* 4.88	31.87	VA1T	34.1	-31	34.97	54	-19.03	-	-	54	108	Н
* 7.32	44.51	PKFH	35.5	-26.9	53.11	-	-	74	-20.89	166	210	Н
* 7.32	38.34	VA1T	35.5	-26.9	46.94	54	-7.06	-	-	166	210	Н
* 4.881	39.29	PKFH	34.1	-31	42.39	-	-	74	-31.61	359	275	V
* 4.88	28.18	VA1T	34.1	-31	31.28	54	-22.72	-	-	359	275	V
* 7.32	43.81	PKFH	35.5	-26.9	52.41	-	-	74	-21.59	142	104	V
* 7.32	37.08	VA1T	35.5	-26.9	45.68	54	-8.32	-	-	142	104	V

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

PKFH - FHSS: RB=100k/1MHz VB=3 x RB, Peak

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

Page 26 of 38

### **HIGH CHANNEL RESULTS**



### HORIZTONAL



Page 27 of 38

### **RADIATED EMISSIONS**

Frequency (GHz)	Meter Reading (dBuV)	Det	AF T407 (dB)	Amp/Cbl/Fltr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 1.326	31.72	PKFH	29.1	-10	50.82	-	-	74	-23.18	194	200	Н
* 1.326	18.38	VA1T	29.1	-10	37.48	54	-16.52	-	-	194	200	Н
* 1.293	30.8	PKFH	28.7	-10	49.5	-	-	74	-24.5	266	201	V
* 1.295	16.99	VA1T	28.7	-10	35.69	54	-18.31	-	-	266	201	V
* 4.95	41.55	PKFH	34.2	-31.1	44.65	-	-	74	-29.35	35	107	Н
* 4.95	32.83	VA1T	34.2	-31.1	35.93	54	-18.07	-	-	35	107	Н
* 7.424	43.39	PKFH	35.5	-26.9	51.99	-	-	74	-22.01	165	166	Н
* 7.425	36.36	VA1T	35.5	-26.9	44.96	54	-9.04	-	-	165	166	Н
* 4.95	42.52	PKFH	34.2	-31.1	45.62	-	-	74	-28.38	355	143	V
* 4.95	34.75	VA1T	34.2	-31.1	37.85	54	-16.15	-	-	355	143	V
* 7.424	42.29	PKFH	35.5	-26.9	50.89	-	-	74	-23.11	142	105	V
* 7.425	35.51	VA1T	35.5	-26.9	44.11	54	-9.89	-	-	142	105	V

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band PKFH - FHSS: RB=100k/1MHz VB=3 x RB, Peak

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

Page 28 of 38

# 9.2. FUNDAMENTAL FREQUENCY RADIATED EMISSION

							1					
Frequency (GHz)	Meter Reading (dBuV)	Det	AF T407 (dB)	Amp/Cbl/Fl tr/Pad (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
	62.69	PKFH	32	-7.8	86.89	-	-	114	-27.11	359	190	н
2.405	62.06	VA1T	32	-7.8	86.26	94	-7.74	-	-	359	190	н
2.405	63.55	PKFH	32	-7.8	87.75	-	-	114	-26.25	347	109	V
	62.93	VA1T	32	-7.8	87.13	94	-6.87	-	-	347	109	V
	56.65	PKFH	32.2	-7.6	81.25	-	-	114	-32.75	355	321	н
2440	55.98	VA1T	32.2	-7.6	80.58	94	-13.42	-	-	355	321	н
2440	57.58	PKFH	32.2	-7.6	82.18	-	-	114	-31.82	331	100	V
	56.91	VA1T	32.2	-7.6	81.51	94	-12.49	-	-	331	100	V
	52.6	PKFH	32.3	-7.7	77.2	-	-	114	-36.8	356	280	н
2475	51.77	VA1T	32.3	-7.7	76.37	94	-17.63	-	-	356	280	н
2475	53.25	PKFH	32.3	-7.7	77.85	-	-	114	-36.15	349	136	V
	52.28	VA1T	32.3	-7.7	76.88	94	-17.12	-	-	349	136	V

PKFH - FHSS: RB=1MHz VB=3 x RB, Peak

VA1T - FHSS: Linear Voltage Average VB=1/Ton where: Ton is transmit duration

Page 29 of 38

# 9.3. WORSE CASE BELOW 30MHz

### SPURIOUS EMISSIONS BELOW 30 MHz (WORST-CASE CONFIGURATION)



Page 30 of 38

#### Below 30MHz DATA

Marker	Frequency	Meter	Det	Loop	Cbl	Dist Corr	Corrected	Peak Limit	Margin	Avg Limit	Margin	Peak Limit	Margin	Avg Limit	Margin	Azimuth
	(MHz)	Reading		Antenna	(dB)	300m	Reading	(dBuV/m)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(dB)	(Degs)
		(dBuV)		(dB/m)			(dBuVolts)									
1	.01166	51.14	Pk	18	.1	-80	-10.76	66.25	-77.01	46.25	-57.01	-	-	-		0-360
5	.05821	40.42	Pk	11.8	.1	-80	-27.68	52.28	-79.96	32.28	-59.96	-		-		0-360
6	.19217	47.47	Pk	11	.1	-80	-21.43	-	-	-	-	41.95	-63.38	21.95	-43.38	0-360
2	.28307	43.5	Pk	10.9	.1	-80	-25.5	-	-	-	-	38.57	-64.07	18.57	-44.07	0-360

Pk - Peak detector

Marker	Frequency	Meter	Det	Loop	Cbl	Dist	Corrected	QP Limit	Margin	Peak Limit	Margin	Avg Limit	Margin	Azimuth
	(MHz)	Reading		Antenna	(dB)	Corr	Reading	(dBuV/m)	(dB)	(dBuV/m)	(dB)	(dBuV/m)	(dB)	(Degs)
		(dBuV)		(dB/m)		30m	(dBuVolts)							
7	.70196	35.97	Pk	11	.1	-40	7.07	30.69	-23.62	-	-	-	-	0-360
3	1.21075	30.94	Pk	11.3	.2	-40	2.44	25.97	-23.53	-	-	-	-	0-360
8	20.17076	12.74	Pk	10.9	.7	-40	-15.66	29.5	-45.16	-	-	-	-	0-360
4	27.77505	13.18	Pk	9.9	.8	-40	-16.12	29.5	-45.62	-	-	-	-	0-360

Pk - Peak detector

Page 31 of 38

# 9.4. WORST CASE BELOW 1GHz





Page 32 of 38

#### Below 1GHz Data

Marker	Frequency	Meter	Det	AF T130 (dB/m)	Amp/Cbl (dB/m)	DC Corr (dB)	Corrected	QPk Limit (dBuV/m)	Margin	Azimuth	Height	Polarity
	(MHz)	Reading					Reading		(dB)	(Degs)	(cm)	
		(dBuV)					(dBuV/m)					
1	69.9178	28.43	Pk	12.1	-26.7	0	13.83	40	-26.17	0-360	200	Н
3	70.0454	34	Pk	12.1	-26.7	0	19.4	40	-20.6	0-360	100	V
4	79.9929	33.69	Pk	11.5	-26.6	0	18.59	40	-21.41	0-360	100	V
2	91.9385	33.41	Pk	12.1	-26.5	0	19.01	43.52	-24.51	0-360	300	Н
5	184.0174	35.26	Pk	15.1	-25.5	0	24.86	43.52	-18.66	0-360	100	V
6	312.0146	31.92	Pk	17.8	-24.6	0	25.12	46.02	-20.9	0-360	101	н

Pk - Peak detector

Page 33 of 38

# 9.5. WORST CASE 18-26 GHz





Page 34 of 38

#### <u> 18 – 26GHz DATA</u>

Marker	Frequency	Meter	Det	T449 AF	Amp/Cbl	Dist Corr	Corrected	Avg Limit	Margin	Peak Limit	PK
	(GHz)	Reading		(dB/m)	(dB)	(dB)	Reading	(dBuV/m)	(dB)	(dBuV/m)	Margin
		(dBuV)					(dBuVolts)				(dB)
1	18.999	38.7	Pk	32.5	-24.8	-9.5	36.9	54	-17.1	74	-37.1
2	21.485	38	Pk	33.2	-25.3	-9.5	36.4	54	-17.6	74	-37.6
3	23.6	38.24	Pk	33.9	-24	-9.5	38.64	54	-15.36	74	-35.36
4	19.332	37.37	Pk	32.6	-24.9	-9.5	35.57	54	-18.43	74	-38.43
5	21.543	37.76	Pk	33.2	-25.3	-9.5	36.16	54	-17.84	74	-37.84
6	24.312	38.3	Pk	33.9	-24.4	-9.5	38.3	54	-15.7	74	-35.7

Pk - Peak detector

Page 35 of 38