

## RF Exposure Report

**Report No.:** SA181221C07D

**FCC ID:** VBNAHFB-01

**Test Model:** AHFB

**Received Date:** Oct. 15, 2019

**Test Date:** Apr. 16 ~ Apr. 23, 2020

**Issued Date:** Jun. 08, 2020

**Applicant:** Nokia Solutions and Networks

**Address:** 3201 Olympus Blvd, Dallas, Texas 75019

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Lin Kou Laboratories

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

**Test Location:** No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City  
33383, Taiwan

**FCC Registration /** 788550 / TW0003

**Designation Number:**



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

<b>Release Control Record</b> .....	<b>3</b>
<b>1 Certificate of Conformity</b> .....	<b>4</b>
<b>2 RF Exposure</b> .....	<b>5</b>
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula .....	5
2.3 Classification .....	5
2.4 Antenna Gain .....	5
<b>3 Calculation Result of Maximum Tune up Power</b> .....	<b>6</b>
<b>4 Brief Summary of results</b> .....	<b>6</b>

### Release Control Record

Issue No.	Description	Date Issued
SA181221C07D	Original release	Jun. 08, 2020

## 1 Certificate of Conformity

**Product:** AirScale Base Station RRH 1.9GHz

**Brand:** Nokia

**Test Model:** AHFB

**Sample Status:** Mass product

**Applicant:** Nokia Solutions and Networks

**Test Date:** Apr. 16 ~ Apr. 23, 2020

**Standards:** FCC Part 2 (Section 2.1091)

**References Test** KDB 447498 D01 General RF Exposure Guidance v06

**Guidance:** IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

**Prepared by :** Pettie Chen , **Date:** Jun. 08, 2020  
Pettie Chen / Senior Specialist

**Approved by :** Bruce Chen , **Date:** Jun. 08, 2020  
Bruce Chen / Senior Project Engineer

## 2 RF Exposure

### 2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
300-1500	...	...	F/300	6
1500-100,000	...	...	5	6
(B)Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

### 2.2 MPE Calculation Formula

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$r$  = distance between observation point and center of the radiator in cm

### 2.3 Classification

#### For General Population:

The antenna of this product, under normal use condition, is greater than 171cm away from the body of the user. So, this device is classified as fixed Device.

#### For Occupational Population:

The antenna of this product, under normal use condition, is at least 77cm away from the body of the user. So, this device is classified as fixed device and installations by professional service personnel.

### 2.4 Antenna Gain

Antenna Type	Direction Panel antenna with 12.5dBi gain
Antenna Model	AAFA
Antenna Ports	Nex10
Antenna Connector	N type

Note:

1. This device operate with Multiple Antennas Using Multiple-input, Multiple-output (MIMO) Technology for uncorrelated Transmission.
2. A representative Nokia antenna, AAFA 12.5dBi, is referred to comply with the EIRP limits.

### 3 Calculation Result of Maximum Tune up Power

#### For General Population:

Function	Frequency Band (MHz)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
LTE Band 25 (Multi Carrier)	1962.5	55.60	171	0.988	1

#### For Occupational Population:

Function	Frequency Band (MHz)	EIRP (dBm)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
LTE Band 25 (Multi Carrier)	1962.5	55.60	77	4.873	5

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

### 4 Brief Summary of results

The wireless device described within this report has been shown to be capable of compliance with the basic restrictions related to human exposure to electromagnetic fields for both General public and Occupational. The calculations shown in this report were made in accordance the procedures specified in the applied test specification(s)

Configuration	Required Compliance Boundary(cm)	
	Occupational	General Population
LTE Band 25 (Multi Carrier)	77	171

--- END ---