

FCC ID:2AOGIZWA046

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Antenna Type: External Antenna

Antenna Gain: 2dBi

Transmit power

Frequency (MHz)	Max Output power (dBuV/m)	EIRP power (dBm)	Conducted power (dBm)
908.4	89.23	-6.03	-8.03
916	86.44	-8.82	-10.82

$\text{EIRP} = \text{E} - 104.8 + 20 \log(D)$

Conducted power = EIRP - Antenna gain

Modulation	Channel Freq. (GHz)	Conducted power (dBm)	Conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	1g SAR Exclusion threshold	SAR test exclusion
GFSK	0.9084	-8.03	0.157	-8 \pm 1	-7	0.200	<5	0.03803	3.00	YES
	0.916	-10.82	0.083	-10 \pm 1	-9	0.126	<5	0.02410	3.00	YES

Conclusion:

For the max result : $0.03803 \leq 1$, No SAR is required.

Alex Li

Signature:

Date: 2024-04-09

NAME AND TITLE (Please print or type): Alex /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen 518126 P.R. China