

CFR 47 FCC PART 15 SUBPART C

TEST REPORT

For

Smart POS

MODEL NUMBER: D60

REPORT NUMBER: 4790950508-1-RF-3

ISSUE DATE: October 14, 2023

FCC ID:2AGQ6-D60

Prepared for

**Dspread Technology(Beijing) Inc
Rm.407, B12C, #10(Universal Business Park), Jiuxianqiao Road, Chaoyang District,
Beijing, 100015, China**

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	October 14, 2023	Initial Issue	

Summary of Test Results

Test Item	Clause	Limit/Requirement	Result
Antenna Requirement	N/A	FCC Part 15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	ANSI C63.10-2013, Clause 6.2	FCC Part 15.207	Pass
Conducted Output Power	ANSI C63.10-2013, Clause 11.9.1.3	FCC Part 15.247 (b)(3)	Pass
6dB Bandwidth and 99% Occupied Bandwidth	ANSI C63.10-2013, Clause 11.8.1	FCC Part 15.247 (a)(2)	Pass
Power Spectral Density	ANSI C63.10-2013, Clause 11.10.2	FCC Part 15.247 (e)	Pass
Conducted Band edge and spurious emission	ANSI C63.10-2013, Clause 11.11	FCC Part 15.247(d)	Pass
Radiated Band edge and Spurious Emission	ANSI C63.10-2013, Clause 11.12 & Clause 11.13	FCC Part 15.247 (d) FCC Part 15.205/15.209	Pass
Duty Cycle	ANSI C63.10-2013, Clause 11.6	None; for reporting purposes only.	Pass

*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

*The measurement result for the sample received is <Pass> according to <CFR 47 FCC PART 15 SUBPART C

ISED RSS-247 Issue 3> when <Simple Acceptance> decision rule is applied.

CONTENTS

1. ATTESTATION OF TEST RESULTS.....	6
2. TEST METHODOLOGY.....	7
3. FACILITIES AND ACCREDITATION.....	7
4. CALIBRATION AND UNCERTAINTY	8
4.1. MEASURING INSTRUMENT CALIBRATION	8
4.2. MEASUREMENT UNCERTAINTY.....	8
5. EQUIPMENT UNDER TEST	9
5.1. DESCRIPTION OF EUT	9
5.2. CHANNEL LIST	9
5.3. MAXIMUM POWER	9
5.4. TEST CHANNEL CONFIGURATION	10
5.5. THE WORSE CASE POWER SETTING PARAMETER	10
5.6. WORST-CASE CONFIGURATIONS.....	11
5.7. DESCRIPTION OF AVAILABLE ANTENNAS	12
5.8. SUPPORT UNITS FOR SYSTEM TEST	13
6. MEASURING EQUIPMENT AND SOFTWARE USED.....	14
7. ANTENNA PORT TEST RESULTS	17
7.1. CONDUCTED OUTPUT POWER	17
7.2. 6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH.....	18
7.3. POWER SPECTRAL DENSITY	20
7.4. CONDUCTED BAND EDGE AND SPURIOUS EMISSION	21
7.5. DUTY CYCLE	23
8. RADIATED TEST RESULTS.....	24
8.1. RESTRICTED BANDEDGE	31
8.2. SPURIOUS EMISSIONS(1 GHZ~3 GHZ)	49
8.3. SPURIOUS EMISSIONS(3 GHZ~18 GHZ)	55
8.4. SPURIOUS EMISSIONS(9 KHZ~30 MHZ)	79
8.5. SPURIOUS EMISSIONS(18 GHZ~26 GHZ)	82
8.6. SPURIOUS EMISSIONS(30 MHZ~1 GHZ)	84
9. ANTENNA REQUIREMENT	86
10. AC POWER LINE CONDUCTED EMISSION	87
11. TEST DATA.....	90

Appendix A: Duty Cycle.....	90
Appendix B: Maximum Conducted Output Power	93
Appendix C: -6dB Bandwidth	94
Appendix D: Occupied Channel Bandwidth.....	99
Appendix E: Maximum Power Spectral Density Level.....	104
Appendix F: Band Edge	109
Appendix G: Conducted RF Spurious Emission.....	116

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Dspread Technology(Beijing) Inc
Address: Rm.407, B12C, #10(Universal Business Park), Jiuxianqiao Road,
Chaoyang District, Beijing, 100015, China

Manufacturer Information


Company Name: Dspread Technology(Beijing) Inc
Address: Rm.407, B12C, #10(Universal Business Park), Jiuxianqiao Road,
Chaoyang District, Beijing, 100015, China

EUT Information

EUT Name: Smart POS
Model: D60
Sample Received Date: August 2, 2023
Sample Status: Normal
Sample ID: 6327587
Date of Tested: September 2, 2023 to October 14, 2023

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	Pass


Prepared By:



Kebo Zhang

Senior Project Engineer

Checked By:



Denny Huang

Senior Project Engineer

Approved By:



Stephen Guo

Operations Manager

2. TEST METHODOLOGY

All tests were performed in accordance with the standard CFR 47 FCC PART 15 SUBPART C , KDB 558074 D01 15.247 Meas Guidance v05r02, KDB 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part 2, ANSI C63.10-2013 and ISED RSS-GEN Issue 5.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046. VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B , the VCCI registration No. is C-20012 and T-20011
----------------------------------	---

Note 1:

All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China.

Note 2:

The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3:

For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 26 GHz)	5.78 dB (1 GHz ~ 18 GHz)
	5.23 dB (18 GHz ~ 26 GHz)
Duty Cycle	±0.028%
DTS and 99% Occupied Bandwidth	±0.0196%
Maximum Conducted Output Power	±0.686 dB
Maximum Power Spectral Density Level	±0.743 dB
Conducted Band-edge Compliance	±1.328 dB
Conducted Unwanted Emissions In Non-restricted Frequency Bands	±0.746 dB (9 kHz ~ 1 GHz)
	±1.328dB (1 GHz ~ 26 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	Smart POS
Model	D60

Frequency Range:	2412 MHz to 2462 MHz
Type of Modulation:	IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK) IEEE 802.11g/n: OFDM(64-QAM, 16-QAM, QPSK, BPSK)
Rated Input:	5Vdc, 2 A
Battery:	7.2 Vdc

5.2. CHANNEL LIST

Channel List For Bandwidth=20 MHz							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	4	2427	7	2442	10	2457
2	2417	5	2432	8	2447	11	2462
3	2422	6	2437	9	2452	/	/

Channel List For Bandwidth=40 MHz							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	5	2432	7	2442	9	2452
4	2427	6	2437	8	2447	/	/

5.3. MAXIMUM POWER

IEEE Std. 802.11	Frequency (MHz)	Channel Number	Maximum Conducted AVG Output Power (dBm)
b	2412 ~ 2462	1-11[11]	12.28
g	2412 ~ 2462	1-11[11]	16.00
n HT20	2412 ~ 2462	1-11[11]	15.29
n HT40	2422 ~ 2452	3-9[7]	11.85

5.4. TEST CHANNEL CONFIGURATION

IEEE Std. 802.11	Test Channel Number	Frequency
b	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
g	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
n HT20	CH 1(Low Channel), CH 6(MID Channel), CH 11(High Channel)	2412 MHz, 2437 MHz, 2462 MHz
n HT40	CH 3(Low Channel), CH 6(MID Channel), CH 9(High Channel)	2422 MHz, 2437 MHz, 2452 MHz

5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band							
Test Software		MP Tool					
Modulation Mode	Transmit Antenna Number	Test Channel					
		NCB: 20MHz			NCB: 40MHz		
		CH 1	CH 6	CH 11	CH 3	CH 6	CH 9
802.11b	1	14	14	14	/		
802.11g	1	18	18	18			
802.11n HT20	1	17.5	17.5	17.5			
802.11n HT40	1	/			13.5	13.5	13.5

5.6. WORST-CASE CONFIGURATIONS

The EUT was tested in the following configuration(s):

Controlled in test mode using a software application on the EUT supplied by customer. The application was used to enable a continuous transmission and to select the mode, test channels, bandwidth, data rates as required.

Test channels referring to section 5.4.

Maximum power setting referring to section 5.5.

Worst-case data rates as provided by the client were:

802.11b mode: 1 Mbps
802.11g mode: 6 Mbps
802.11n HT20 mode: MCS0
802.11n HT40 mode: MCS0

The measured additional path loss was included in any path loss calculations for all RF cable used during tested.

5.7. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2412-2462	PIFA Antenna	2.73

Test Mode	Transmit and Receive Mode	Description
IEEE 802.11b	☒ 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11g	☒ 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11n HT20	☒ 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
IEEE 802.11n HT40	☒ 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.

Note:

1.BT&WLAN 2.4G, BT & WLAN 5G, WLAN 2.4G & WLAN 5G can't transmit simultaneously.
(declared by client)

5.8. SUPPORT UNITS FOR SYSTEM TEST

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Remarks
1	Laptop	Lenovo	E14	/

I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	Type C	/	1.0	/


ACCESSORIES

Item	Equipment	Brand Name	Model Name	Remarks
1	Adapter	N/A	TPA-46050200UU	Input: 100-240V~, 50/60Hz, 0.3A Output: 5 Vdc, 2A, 10W

TEST SETUP

The EUT can work in engineering mode with a software through a Laptop.

SETUP DIAGRAM FOR TESTS



6. MEASURING EQUIPMENT AND SOFTWARE USED

R&S TS 8997 Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Power sensor, Power Meter	R&S	OSP120	100921	Mar.31,2023	Mar.30,2024
Vector Signal Generator	R&S	SMBV100A	261637	Oct.17, 2022	Oct.16, 2023
Signal Generator	R&S	SMB100A	178553	Oct.17, 2022	Oct.16, 2023
Signal Analyzer	R&S	FSV40	101118	Oct.17, 2022	Oct.16, 2023
Software					
Description	Manufacturer		Name		Version
For R&S TS 8997 Test System	Rohde & Schwarz		EMC 32		10.60.10
Tonsend RF Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Wideband Radio Communication Tester	R&S	CMW500	155523	Oct.17, 2022	Oct.16, 2023
Wireless Connectivity Tester	R&S	CMW270	1201.0002N75-102	Sep.28, 2022	Sep.27, 2023
PXA Signal Analyzer	Keysight	N9030A	MY55410512	Oct.17, 2022	Oct.16, 2023
MXG Vector Signal Generator	Keysight	N5182B	MY56200284	Oct.17, 2022	Oct.16, 2023
MXG Vector Signal Generator	Keysight	N5172B	MY56200301	Oct.17, 2022	Oct.16, 2023
DC power supply	Keysight	E3642A	MY55159130	Oct.17, 2022	Oct.16, 2023
Temperature & Humidity Chamber	SANMOOD	SG-80-CC-2	2088	Oct.17, 2022	Oct.16, 2023
Attenuator	Aglient	8495B	2814a12853	Oct.18, 2022	Oct.17, 2023
RF Control Unit	Tonscend	JS0806-2	23B80620666	April 18,2023	April 17,2024
Software					
Description	Manufacturer	Name		Version	
Tonsend SRD Test System	Tonsend	JS1120-3 RF Test System		V3.2.22	

Conducted Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
EMI Test Receiver	R&S	ESR3	101961	Oct.17, 2022	Oct.16, 2023
Two-Line V-Network	R&S	ENV216	101983	Oct.17, 2022	Oct.16, 2023
Artificial Mains Networks	Schwarzbeck	NSLK 8126	8126465	Oct.17, 2022	Oct.16, 2023
Software					
Description			Manufacturer	Name	Version
Test Software for Conducted Emissions			Farad	EZ-EMC	Ver. UL-3A1

Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Oct.17, 2022	Oct.16, 2023
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130959	Aug.02, 2021	Aug.01, 2024
Preamplifier	HP	8447D	2944A09099	Oct.17, 2022	Oct.16, 2023
EMI Measurement Receiver	R&S	ESR26	101377	Oct.17, 2022	Oct.16, 2023
Horn Antenna	TDK	HRN-0118	130940	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Oct.17, 2022	Oct.16, 2023
Horn Antenna	Schwarzbeck	BBHA9170	697	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-2	TRS-307-00003	Oct.17, 2022	Oct.16, 2023
Preamplifier	TDK	PA-02-3	TRS-308-00002	Oct.17, 2022	Oct.16, 2023
Loop antenna	Schwarzbeck	1519B	00008	Dec.14, 2021	Dec.13, 2024
Preamplifier	TDK	PA-02-001-3000	TRS-302-00050	Oct.17, 2022	Oct.16, 2023
Preamplifier	Mini-Circuits	ZX60-83LN-S+	SUP01202035	Oct.17, 2022	Oct.16, 2023
High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Dec.01,2022	Nov.30,2023
Highpass Filter	Wainwright	WHKX10-5850-6500-1800-40SS	4	Dec.01,2022	Nov.30,2023
Band Reject Filter	Wainwright	WRCJV12-5695-5725-5850-5880-40SS	4	Dec.01,2022	Nov.30,2023
Band Reject Filter	Wainwright	WRCJV20-5120-5150-	2	Dec.01,2022	Nov.30,2023

		5350-5380-60SS			
Band Reject Filter	Wainwright	WRCJV20-5440-5470-5725-5755-60SS	1	Dec.01,2022	Nov.30,2023
Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	Dec.01,2022	Nov.30,2023
Band Reject Filter	Wainwright	WRCD5-1879-1879.85-1880.15-1881-40SS	1	Dec.01,2022	Nov.30,2023
Notch Filter	Wainwright	WHJ10-882-980-7000-40SS	1	Dec.01,2022	Nov.30,2023
Software					
Description			Manufacturer	Name	Version
Test Software for Radiated Emissions			Farad	EZ-EMC	Ver. UL-3A1

Other Instrument					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Temperature humidity probe	OMEGA	ITHX-SD-5	18470007	Oct.22, 2022	Oct.21, 2023
Barometer	Yiyi	Baro	N/A	Oct.24, 2022	Oct.23, 2023
Attenuator	Agilent	8495B	2814a12853	Oct.18, 2022	Oct.17, 2023

7. ANTENNA PORT TEST RESULTS

7.1. CONDUCTED OUTPUT POWER

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3)	AVG Output Power	1 watt or 30 dBm	2400-2483.5

TEST PROCEDURE


Refer to ANSI C63.10-2013 clause 11.9.2.3.1.

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the average output power, after any corrections for external attenuators and cables.

The test result in dBm by adding $[10 \log (1 / D)]$, where D is the duty cycle.

TEST SETUP



TEST ENVIRONMENT

Temperature	25.6°C	Relative Humidity	67.5%
Atmosphere Pressure	101kPa	Test Voltage	DC 7.2 V

TEST DATE / ENGINEER

Test Date	September 22, 2023	Test By	Johnson Liu
-----------	--------------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix B

7.2. 6DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(a)(2)	6 dB Bandwidth	≥ 500 kHz	2400-2483.5
ISED RSS-Gen Clause 6.7	99 % Occupied Bandwidth	For reporting purposes only.	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.


Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Frequency Span	For 6 dB Bandwidth: Enough to capture all products of the modulation carrier emission For 99 % Occupied Bandwidth: Between 1.5 times and 5.0 times the OBW
Detector	Peak
RBW	For 6 dB Bandwidth: 100 kHz For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth
VBW	For 6 dB Bandwidth: $\geq 3 \times$ RBW For 99 % Occupied Bandwidth: $\geq 3 \times$ RBW
Trace	Max hold
Sweep	Auto couple

a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.

b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP



TEST ENVIRONMENT

Temperature	25.6°C	Relative Humidity	67.5%
Atmosphere Pressure	101kPa	Test Voltage	DC 7.2 V

TEST DATE / ENGINEER

Test Date	September 22, 2023	Test By	Johnson Liu
-----------	--------------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix C&D

7.3. POWER SPECTRAL DENSITY

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.247 (e)	Power Spectral Density	8 dBm in any 3 kHz band	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.10.5.


Connect the EUT to the spectrum analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	power averaging (rms)
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x OBW bandwidth
Trace	Employ trace averaging(rms)mode over a minimum of 100 traces
Sweep time	Auto couple

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST SETUP



TEST ENVIRONMENT

Temperature	25.6°C	Relative Humidity	67.5%
Atmosphere Pressure	101kPa	Test Voltage	DC 7.2 V

TEST DATE / ENGINEER

Test Date	September 22, 2023	Test By	Johnson Liu
-----------	--------------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix E

7.4. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.11 and 11.13.

Connect the EUT to the spectrum analyzer and use the following settings for reference level measurement:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.


Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.

Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span}/\text{RBW}$
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.

TEST SETUP



TEST ENVIRONMENT

Temperature	25.6°C	Relative Humidity	67.5%
Atmosphere Pressure	101kPa	Test Voltage	DC 7.2 V

TEST DATE / ENGINEER

Test Date	September 22, 2023	Test By	Johnson Liu
-----------	--------------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix F&G

7.5. DUTY CYCLE


LIMITS

None; for reporting purposes only.

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.6 Zero – Span Spectrum Analyzer method.

TEST SETUP



TEST ENVIRONMENT

Temperature	25.6°C	Relative Humidity	67.5%
Atmosphere Pressure	101kPa	Test Voltage	DC 7.2 V

TEST DATE / ENGINEER

Test Date	September 22, 2023	Test By	Johnson Liu
-----------	--------------------	---------	-------------

TEST RESULTS

Please refer to section "Test Data" - Appendix A

8. RADIATED TEST RESULTS

LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c**TEST PROCEDURE**

Below 30 MHz

The setting of the spectrum analyzer

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω. For example, the measurement frequency X kHz resulted in a level of Y dBuV/m, which is equivalent to $Y - 51.5 = Z$ dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyzer

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.


Above 1 GHz

The setting of the spectrum analyzer

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.5. ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

For Restricted Bandedge:

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. PK=Peak: Peak detector.
4. AV=Average: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.
7. Both horizontal and vertical have been tested, only the worst data was recorded in the report.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (9 kHz ~ 30 MHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.
4. All modes have been tested, but only the worst data was recorded in the report.
5. $\text{dBuA/m} = \text{dBuV/m} - 20\log_{10}[120\pi] = \text{dBuV/m} - 51.5$

For Radiate Spurious Emission (30 MHz ~ 1 GHz):

Note:

1. Result Level = Read Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (1 GHz ~ 3 GHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (3 GHz ~ 18 GHz):

Note:


1. Peak Result = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.5.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (18 GHz ~ 26 GHz):


Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. All modes have been tested, but only the worst data was recorded in the report.


TEST SETUP



Below 1 GHz and above 30 MHz



Above 1 GHz



TEST ENVIRONMENT

Temperature	25.1℃	Relative Humidity	66%
Atmosphere Pressure	101kPa	Test Voltage	


TEST DATE / ENGINEER

Test Date	October 10, 2023	Test By	Rex Huang
-----------	------------------	---------	-----------

TEST RESULTS


8.1. RESTRICTED BANDEDGE

Test Mode:	802.11b PK	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2385.960	22.03	32.14	54.17	74.00	-19.83	peak
2	2390.000	17.51	32.16	49.67	74.00	-24.33	peak

Test Mode:	802.11b AV	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2385.960	14.19	32.14	46.33	54.00	-7.67	AVG
2	2390.000	8.45	32.16	40.61	54.00	-13.39	AVG

Test Mode:	802.11b PK	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2385.960	24.48	32.14	56.62	74.00	-17.38	peak
2	2390.000	20.56	32.16	52.72	74.00	-21.28	peak

Test Mode:	802.11b AV	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2385.960	13.29	32.14	45.43	54.00	-8.57	AVG
2	2390.000	7.99	32.16	40.15	54.00	-13.85	AVG

Test Mode:	802.11b PK	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	20.48	32.44	52.92	74.00	-21.08	peak
2	2487.955	22.50	32.46	54.96	74.00	-19.04	peak

Test Mode:	802.11b AV	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	9.35	32.44	41.79	54.00	-12.21	AVG
2	2487.955	13.04	32.46	45.50	54.00	-8.50	AVG

Test Mode:	802.11g PK	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.560	36.60	32.16	68.76	74.00	-5.24	peak
2	2390.000	36.35	32.16	68.51	74.00	-5.49	peak

Test Mode:	802.11g AV	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.560	17.81	32.16	49.97	54.00	-4.03	AVG
2	2390.000	18.79	32.16	50.95	54.00	-3.05	AVG

Test Mode:	802.11g PK	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	37.67	32.44	70.11	74.00	-3.89	peak
2	2483.940	39.32	32.44	71.76	74.00	-2.24	peak
3	2487.955	33.28	32.46	65.74	74.00	-8.26	peak

Test Mode:	802.11g AV	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	20.02	32.44	52.46	54.00	-1.54	AVG
2	2483.940	19.43	32.44	51.87	54.00	-2.13	AVG
3	2487.955	19.35	32.46	51.81	54.00	-2.19	AVG

Test Mode:	802.11n HT20 PK	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	40.59	32.16	72.75	74.00	-1.25	peak

Test Mode:	802.11n HT20 AV	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	20.39	32.16	52.55	54.00	-1.45	AVG

Test Mode:	802.11n HT20 PK	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	38.98	32.44	71.42	74.00	-2.58	peak
2	2484.930	40.25	32.44	72.69	74.00	-1.31	peak

Test Mode:	802.11n HT20 AV	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	20.54	32.44	52.98	54.00	-1.02	AVG
2	2484.930	18.75	32.44	51.19	54.00	-2.81	AVG

Test Mode:	802.11n HT40 PK	Frequency(MHz):	2422
Polarity:	Horizontal	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.380	40.62	32.16	72.78	74.00	-1.22	peak
2	2390.000	39.80	32.16	71.96	74.00	-2.04	peak

Test Mode:	802.11n HT40 AV	Frequency(MHz):	2422
Polarity:	Horizontal	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2389.380	17.92	32.16	50.08	54.00	-3.92	AVG
2	2390.000	18.60	32.16	50.76	54.00	-3.24	AVG

Test Mode:	802.11n HT40 PK	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	7.2 Vdc



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	39.95	32.44	72.39	74.00	-1.61	peak
2	2484.320	40.42	32.44	72.86	74.00	-1.14	peak


Test Mode:	802.11n HT40 AV	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	7.2 Vdc



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	14.06	32.44	46.50	54.00	-7.50	AVG
2	2484.320	13.54	32.44	45.98	54.00	-8.02	AVG


8.2. SPURIOUS EMISSIONS(1 GHZ~3 GHZ)

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1480.000	44.97	-12.80	32.17	74.00	-41.83	peak
2	1956.000	44.45	-11.21	33.24	74.00	-40.76	peak
3	2280.000	52.21	-9.61	42.60	74.00	-31.40	peak
4	2412.000	55.83	-8.94	46.89	/	/	fundamental
5	2572.000	47.95	-8.27	39.68	74.00	-34.32	peak
6	2790.000	43.78	-7.62	36.16	74.00	-37.84	peak

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1772.000	44.99	-11.82	33.17	74.00	-40.83	peak
2	2064.000	44.99	-10.73	34.26	74.00	-39.74	peak
3	2322.000	55.76	-9.40	46.36	74.00	-27.64	peak
4	2412.000	58.87	-8.93	49.94	/	/	fundamental
5	2568.000	54.43	-8.28	46.15	74.00	-27.85	peak
6	2954.000	44.15	-7.11	37.04	74.00	-36.96	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1218.000	47.92	-14.02	33.90	74.00	-40.10	peak
2	1778.000	45.02	-11.79	33.23	74.00	-40.77	peak
3	2352.000	51.78	-9.24	42.54	74.00	-31.46	peak
4	2437.000	57.08	-8.82	48.26	/	/	fundamental
5	2568.000	55.75	-8.28	47.47	74.00	-26.53	peak
6	2828.000	43.71	-7.50	36.21	74.00	-37.79	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1506.000	45.15	-12.69	32.46	74.00	-41.54	peak
2	2124.000	43.70	-10.42	33.28	74.00	-40.72	peak
3	2346.000	52.61	-9.28	43.33	74.00	-30.67	peak
4	2437.000	56.11	-8.80	47.31	/	/	fundamental
5	2568.000	56.36	-8.28	48.08	74.00	-25.92	peak
6	2824.000	43.85	-7.51	36.34	74.00	-37.66	peak

Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	7.2 Vdc



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1230.000	47.84	-13.96	33.88	74.00	-40.12	peak
2	1728.000	46.82	-11.95	34.87	74.00	-39.13	peak
3	2344.000	48.04	-9.30	38.74	74.00	-35.26	peak
4	2462.000	54.84	-8.68	46.16	/	/	fundamental
5	2556.000	55.97	-8.32	47.65	74.00	-26.35	peak
6	2892.000	44.44	-7.31	37.13	74.00	-36.87	peak


Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	7.2 Vdc



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1230.000	47.06	-13.96	33.10	74.00	-40.90	peak
2	1818.000	50.33	-11.66	38.67	74.00	-35.33	peak
3	2344.000	49.39	-9.30	40.09	74.00	-33.91	peak
4	2462.000	57.98	-8.68	49.30	/	/	fundamental
5	2566.000	56.77	-8.29	48.48	74.00	-25.52	peak
6	2772.000	49.39	-7.67	41.72	74.00	-32.28	peak


8.3. SPURIOUS EMISSIONS(3 GHZ~18 GHZ)

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	53.77	-0.26	53.51	74.00	-20.49	peak
2	4815.000	52.50	-0.26	52.24	54.00	-1.76	AVG
3	9195.000	36.37	10.56	46.93	74.00	-27.07	peak
4	10935.000	35.10	14.54	49.64	74.00	-24.36	peak
5	11730.000	32.63	17.22	49.85	74.00	-24.15	peak
6	13980.000	28.06	21.92	49.98	74.00	-24.02	peak
7	17955.000	24.23	25.42	49.65	74.00	-24.35	peak

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	50.65	-0.26	50.39	74.00	-23.61	peak
2	9075.000	36.21	10.52	46.73	74.00	-27.27	peak
3	11070.000	33.96	15.03	48.99	74.00	-25.01	peak
4	12645.000	31.20	17.92	49.12	74.00	-24.88	peak
5	13875.000	28.56	21.70	50.26	74.00	-23.74	peak
6	17955.000	24.24	25.42	49.66	74.00	-24.34	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	52.80	-0.03	52.77	74.00	-21.23	peak
2	4875.000	50.83	-0.03	50.80	54.00	-3.20	AVG
3	9180.000	36.99	10.56	47.55	74.00	-26.45	peak
4	11400.000	34.11	16.23	50.34	74.00	-23.66	peak
5	12705.000	32.52	18.06	50.58	74.00	-23.42	peak
6	13620.000	29.42	21.15	50.57	74.00	-23.43	peak
7	18000.000	23.88	25.69	49.57	74.00	-24.43	peak

Test Mode:	802.11b	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	49.46	-0.03	49.43	74.00	-24.57	peak
2	9090.000	36.18	10.51	46.69	74.00	-27.31	peak
3	11040.000	33.97	14.91	48.88	74.00	-25.12	peak
4	11820.000	32.65	17.47	50.12	74.00	-23.88	peak
5	13650.000	29.45	21.21	50.66	74.00	-23.34	peak
6	17970.000	23.89	25.51	49.40	74.00	-24.60	peak

Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	50.76	0.14	50.90	74.00	-23.10	peak
2	9255.000	36.10	10.59	46.69	74.00	-27.31	peak
3	11055.000	34.65	14.96	49.61	74.00	-24.39	peak
4	11775.000	32.83	17.35	50.18	74.00	-23.82	peak
5	13530.000	29.68	20.96	50.64	74.00	-23.36	peak
6	17940.000	23.87	25.34	49.21	74.00	-24.79	peak

Test Mode:	802.11b	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	47.95	0.14	48.09	74.00	-25.91	peak
2	9225.000	36.10	10.58	46.68	74.00	-27.32	peak
3	11010.000	34.92	14.81	49.73	74.00	-24.27	peak
4	11820.000	32.94	17.47	50.41	74.00	-23.59	peak
5	13470.000	29.10	20.77	49.87	74.00	-24.13	peak
6	17985.000	24.04	25.60	49.64	74.00	-24.36	peak

Test Mode:	802.11g	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4830.000	53.11	-0.20	52.91	74.00	-21.09	peak
2	4830.000	42.89	-0.20	42.69	54.00	-11.31	AVG
3	7230.000	39.98	6.53	46.51	74.00	-27.49	peak
4	9240.000	36.45	10.58	47.03	74.00	-26.97	peak
5	11745.000	32.43	17.27	49.70	74.00	-24.30	peak
6	13590.000	28.83	21.09	49.92	74.00	-24.08	peak
7	18000.000	23.74	25.69	49.43	74.00	-24.57	peak

Test Mode:	802.11g	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4830.000	49.73	-0.20	49.53	74.00	-24.47	peak
2	7215.000	40.90	6.54	47.44	74.00	-26.56	peak
3	11070.000	34.42	15.03	49.45	74.00	-24.55	peak
4	11880.000	32.34	17.63	49.97	74.00	-24.03	peak
5	13920.000	28.80	21.79	50.59	74.00	-23.41	peak
6	17955.000	24.45	25.42	49.87	74.00	-24.13	peak

Test Mode:	802.11g	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	52.84	-0.03	52.81	74.00	-21.19	peak
2	4875.000	43.85	-0.03	43.82	54.00	-10.18	AVG
3	7305.000	38.17	6.47	44.64	74.00	-29.36	peak
4	9300.000	36.30	10.61	46.91	74.00	-27.09	peak
5	11745.000	33.10	17.27	50.37	74.00	-23.63	peak
6	14025.000	28.09	21.86	49.95	74.00	-24.05	peak
7	17985.000	24.10	25.60	49.70	74.00	-24.30	peak

Test Mode:	802.11g	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	50.02	-0.03	49.99	74.00	-24.01	peak
2	7305.000	40.14	6.47	46.61	74.00	-27.39	peak
3	9240.000	36.76	10.58	47.34	74.00	-26.66	peak
4	11865.000	32.20	17.59	49.79	74.00	-24.21	peak
5	13455.000	29.69	20.71	50.40	74.00	-23.60	peak
6	17955.000	25.46	25.42	50.88	74.00	-23.12	peak

Test Mode:	802.11g	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	54.40	0.14	54.54	74.00	-19.46	peak
2	4920.000	44.36	0.14	44.50	54.00	-9.50	AVG
3	9135.000	36.57	10.55	47.12	74.00	-26.88	peak
4	11415.000	33.54	16.29	49.83	74.00	-24.17	peak
5	12645.000	32.63	17.92	50.55	74.00	-23.45	peak
6	13890.000	29.12	21.72	50.84	74.00	-23.16	peak
7	17940.000	24.61	25.34	49.95	74.00	-24.05	peak

Test Mode:	802.11g	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	48.62	0.14	48.76	74.00	-25.24	peak
2	9195.000	36.15	10.56	46.71	74.00	-27.29	peak
3	10890.000	34.31	14.39	48.70	74.00	-25.30	peak
4	12690.000	32.09	18.02	50.11	74.00	-23.89	peak
5	13860.000	29.19	21.67	50.86	74.00	-23.14	peak
6	18000.000	24.95	25.69	50.64	74.00	-23.36	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	50.83	-0.26	50.57	74.00	-23.43	peak
2	7230.000	41.35	6.53	47.88	74.00	-26.12	peak
3	10755.000	34.55	13.90	48.45	74.00	-25.55	peak
4	11535.000	33.52	16.70	50.22	74.00	-23.78	peak
5	13575.000	29.87	21.06	50.93	74.00	-23.07	peak
6	18000.000	24.75	25.69	50.44	74.00	-23.56	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	47.88	-0.26	47.62	74.00	-26.38	peak
2	7230.000	38.81	6.53	45.34	74.00	-28.66	peak
3	9240.000	36.41	10.58	46.99	74.00	-27.01	peak
4	11055.000	34.98	14.96	49.94	74.00	-24.06	peak
5	13920.000	29.57	21.79	51.36	74.00	-22.64	peak
6	17685.000	26.52	23.82	50.34	74.00	-23.66	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	49.92	-0.03	49.89	74.00	-24.11	peak
2	9300.000	36.71	10.61	47.32	74.00	-26.68	peak
3	10890.000	34.31	14.39	48.70	74.00	-25.30	peak
4	12240.000	31.00	17.79	48.79	74.00	-25.21	peak
5	13920.000	28.25	21.79	50.04	74.00	-23.96	peak
6	18000.000	23.62	25.69	49.31	74.00	-24.69	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4860.000	48.49	-0.09	48.40	74.00	-25.60	peak
2	7755.000	37.73	6.31	44.04	74.00	-29.96	peak
3	9240.000	36.38	10.58	46.96	74.00	-27.04	peak
4	11865.000	32.14	17.59	49.73	74.00	-24.27	peak
5	13860.000	28.09	21.67	49.76	74.00	-24.24	peak
6	17955.000	23.88	25.42	49.30	74.00	-24.70	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2462
Polarity:	Horizontal	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	50.51	0.14	50.65	74.00	-23.35	peak
2	9270.000	36.16	10.59	46.75	74.00	-27.25	peak
3	11745.000	33.22	17.27	50.49	74.00	-23.51	peak
4	13620.000	29.22	21.15	50.37	74.00	-23.63	peak
5	17610.000	26.95	23.38	50.33	74.00	-23.67	peak
6	18000.000	25.06	25.69	50.75	74.00	-23.25	peak

Test Mode:	802.11n HT20	Frequency(MHz):	2462
Polarity:	Vertical	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4920.000	48.01	0.14	48.15	74.00	-25.85	peak
2	9195.000	37.32	10.56	47.88	74.00	-26.12	peak
3	10215.000	36.46	12.43	48.89	74.00	-25.11	peak
4	11025.000	34.72	14.85	49.57	74.00	-24.43	peak
5	12675.000	32.46	17.99	50.45	74.00	-23.55	peak
6	17985.000	24.45	25.60	50.05	74.00	-23.95	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2422
Polarity:	Horizontal	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4815.000	44.90	-0.26	44.64	74.00	-29.36	peak
2	9180.000	36.84	10.56	47.40	74.00	-26.60	peak
3	11895.000	32.26	17.68	49.94	74.00	-24.06	peak
4	12675.000	32.91	17.99	50.90	74.00	-23.10	peak
5	13125.000	31.26	19.26	50.52	74.00	-23.48	peak
6	18000.000	24.60	25.69	50.29	74.00	-23.71	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2422
Polarity:	Vertical	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4830.000	41.54	-0.20	41.34	74.00	-32.66	peak
2	7410.000	36.73	6.39	43.12	74.00	-30.88	peak
3	8985.000	36.66	10.37	47.03	74.00	-26.97	peak
4	11055.000	33.97	14.96	48.93	74.00	-25.07	peak
5	13455.000	29.05	20.71	49.76	74.00	-24.24	peak
6	17970.000	23.97	25.51	49.48	74.00	-24.52	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2437
Polarity:	Horizontal	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	44.45	-0.03	44.42	74.00	-29.58	peak
2	9315.000	36.05	10.61	46.66	74.00	-27.34	peak
3	11010.000	34.41	14.81	49.22	74.00	-24.78	peak
4	11805.000	32.14	17.43	49.57	74.00	-24.43	peak
5	13860.000	28.43	21.67	50.10	74.00	-23.90	peak
6	17970.000	23.75	25.51	49.26	74.00	-24.74	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2437
Polarity:	Vertical	Test Voltage:	7.2 Vdc




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	42.06	-0.03	42.03	74.00	-31.97	peak
2	7305.000	38.49	6.47	44.96	74.00	-29.04	peak
3	9135.000	35.97	10.55	46.52	74.00	-27.48	peak
4	11055.000	34.55	14.96	49.51	74.00	-24.49	peak
5	13995.000	28.38	21.95	50.33	74.00	-23.67	peak
6	17670.000	25.81	23.73	49.54	74.00	-24.46	peak

Test Mode:	802.11n HT40	Frequency(MHz):	2452
Polarity:	Horizontal	Test Voltage:	7.2 Vdc



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7305.000	37.76	6.47	44.23	74.00	-29.77	peak
2	9300.000	35.77	10.61	46.38	74.00	-27.62	peak
3	11055.000	34.35	14.96	49.31	74.00	-24.69	peak
4	12165.000	32.01	17.84	49.85	74.00	-24.15	peak
5	14415.000	29.78	20.26	50.04	74.00	-23.96	peak
6	18000.000	23.93	25.69	49.62	74.00	-24.38	peak


Test Mode:	802.11n HT40	Frequency(MHz):	2452
Polarity:	Vertical	Test Voltage:	7.2 Vdc



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7560.000	38.08	6.33	44.41	74.00	-29.59	peak
2	9195.000	37.18	10.56	47.74	74.00	-26.26	peak
3	10875.000	35.09	14.32	49.41	74.00	-24.59	peak
4	11865.000	31.99	17.59	49.58	74.00	-24.42	peak
5	13860.000	28.61	21.67	50.28	74.00	-23.72	peak
6	17940.000	24.15	25.34	49.49	74.00	-24.51	peak


8.4. SPURIOUS EMISSIONS(9 KHZ~30 MHZ)

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	7.2 VDC




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.0100	77.22	-101.40	-24.18	47.60	-71.78	peak
2	0.0108	76.01	-101.39	-25.38	46.93	-72.31	peak
3	0.0160	71.47	-101.37	-29.90	43.52	-73.42	peak
4	0.0273	68.99	-101.38	-32.39	38.88	-71.27	peak
5	0.0466	64.67	-101.46	-36.79	34.23	-71.02	peak
6	0.0675	62.64	-101.56	-38.92	31.02	-69.94	peak

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	7.2 VDC



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.1595	75.86	-101.65	-25.79	23.55	-49.34	peak
2	0.1794	72.77	-101.68	-28.91	22.53	-51.44	peak
3	0.2149	70.20	-101.75	-31.55	20.96	-52.51	peak
4	0.2469	68.42	-101.80	-33.38	19.75	-53.13	peak
5	0.2620	66.81	-101.81	-35.00	19.24	-54.24	peak
6	0.3234	62.98	-101.88	-38.90	17.41	-56.31	peak


Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	7.2 VDC



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.5039	64.93	-62.07	2.86	33.56	-30.70	peak
2	0.7861	63.33	-62.14	1.19	29.69	-28.50	peak
3	1.5443	58.85	-62.03	-3.18	23.83	-27.01	peak
4	3.7100	56.70	-61.41	-4.71	29.54	-34.25	peak
5	6.8936	55.59	-61.22	-5.63	29.54	-35.17	peak
6	13.0907	55.13	-60.93	-5.80	29.54	-35.34	peak


8.5. SPURIOUS EMISSIONS(18 GHZ~26 GHZ)

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	7.2 VDC



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18592.000	49.75	-5.31	44.44	74.00	-29.56	peak
2	19392.000	50.62	-5.57	45.05	74.00	-28.95	peak
3	21600.000	49.52	-4.54	44.98	74.00	-29.02	peak
4	22160.000	49.08	-4.31	44.77	74.00	-29.23	peak
5	24000.000	48.21	-2.75	45.46	74.00	-28.54	peak
6	25000.000	47.86	-2.10	45.76	74.00	-28.24	peak


Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	7.2 VDC



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18960.000	49.01	-5.25	43.76	74.00	-30.24	peak
2	20240.000	49.32	-5.61	43.71	74.00	-30.29	peak
3	21400.000	48.54	-4.72	43.82	74.00	-30.18	peak
4	22272.000	48.08	-4.20	43.88	74.00	-30.12	peak
5	23088.000	48.02	-3.41	44.61	74.00	-29.39	peak
6	24568.000	47.10	-2.33	44.77	74.00	-29.23	peak


8.6. SPURIOUS EMISSIONS(30 MHZ~1 GHZ)

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Horizontal	Test Voltage:	7.2 Vdc



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	32.9100	42.41	-18.69	23.72	40.00	-16.28	QP
2	224.9700	40.58	-17.72	22.86	46.00	-23.14	QP
3	338.4600	42.68	-13.44	29.24	46.00	-16.76	QP
4	375.3200	40.03	-12.92	27.11	46.00	-18.89	QP
5	493.6600	36.90	-10.83	26.07	46.00	-19.93	QP
6	576.1100	44.46	-9.88	34.58	46.00	-11.42	QP

Test Mode:	802.11b	Frequency(MHz):	2412
Polarity:	Vertical	Test Voltage:	7.2 Vdc



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	32.9100	50.13	-18.69	31.44	40.00	-8.56	QP
2	88.2000	45.97	-22.05	23.92	43.50	-19.58	QP
3	182.2899	37.97	-16.51	21.46	43.50	-22.04	QP
4	224.9700	42.01	-17.72	24.29	46.00	-21.71	QP
5	389.8700	38.46	-12.90	25.56	46.00	-20.44	QP
6	442.2500	37.73	-11.94	25.79	46.00	-20.21	QP

9. ANTENNA REQUIREMENT

REQUIREMENT

Please refer to FCC part 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC part 15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

DESCRIPTION

Pass

10. AC POWER LINE CONDUCTED EMISSION

LIMITS

Please refer to CFR 47 FCC §15.207 (a).


FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

TEST PROCEDURE

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

TEST SETUP



TEST ENVIRONMENT


Temperature	22.8°C	Relative Humidity	66%
Atmosphere Pressure	101kPa	Test Voltage	AC 120 V, 60 Hz

TEST DATE / ENGINEER

Test Date	October 9, 2023	Test By	Kebo Zhang
-----------	-----------------	---------	------------

TEST RESULTS

Test Mode:	802.11b	Frequency(MHz):	2412
Line:	Line		




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1621	28.25	9.59	37.84	65.36	-27.52	QP
2	0.1621	15.81	9.59	25.40	55.36	-29.96	AVG
3	0.2172	24.13	9.59	33.72	62.93	-29.21	QP
4	0.2172	10.68	9.59	20.27	52.93	-32.66	AVG
5	0.5403	25.38	9.60	34.98	56.00	-21.02	QP
6	0.5403	14.33	9.60	23.93	46.00	-22.07	AVG
7	0.7626	21.24	9.60	30.84	56.00	-25.16	QP
8	0.7626	13.17	9.60	22.77	46.00	-23.23	AVG
9	19.0617	18.09	9.82	27.91	60.00	-32.09	QP
10	19.0617	7.35	9.82	17.17	50.00	-32.83	AVG
11	28.1441	17.24	9.76	27.00	60.00	-33.00	QP
12	28.1441	2.58	9.76	12.34	50.00	-37.66	AVG

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.

Test Mode:	802.11b	Frequency(MHz):	2412
Line:	Neutral		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1634	18.61	9.52	28.13	65.29	-37.16	QP
2	0.1634	6.18	9.52	15.70	55.29	-39.59	AVG
3	0.2204	22.04	9.58	31.62	62.80	-31.18	QP
4	0.2204	8.86	9.58	18.44	52.80	-34.36	AVG
5	1.0632	21.86	9.52	31.38	56.00	-24.62	QP
6	1.0632	6.73	9.52	16.25	46.00	-29.75	AVG
7	9.1956	20.25	9.62	29.87	60.00	-30.13	QP
8	9.1956	10.01	9.62	19.63	50.00	-30.37	AVG
9	19.8335	23.37	9.74	33.11	60.00	-26.89	QP
10	19.8335	11.10	9.74	20.84	50.00	-29.16	AVG
11	27.4925	26.43	9.73	36.16	60.00	-23.84	QP
12	27.4925	8.85	9.73	18.58	50.00	-31.42	AVG

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.

11. TEST DATA

Appendix A: Duty Cycle

Mode	Antenna	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)	Final setting For VBW (kHz)
b	Ant1	8.384	8.422	0.9955	99.55	0.02	N/A	0.01
g	Ant1	1.392	1.436	0.9694	96.94	0.14	0.72	1
n20	Ant1	1.302	1.346	0.9673	96.73	0.14	0.77	1
n40	Ant1	0.648	0.692	0.9364	93.64	0.29	1.54	2

Test Mode	N1 (msec)	N2 (msec)	N3 (msec)	N3-N2 (msec)	N3-N1 (msec)
b	3.078	3.116	11.50	8.384	8.422
g	0.008	0.052	1.444	1.392	1.436
n20	1.336	1.380	2.682	1.302	1.346
n40	0.2095	0.2535	0.9015	0.648	0.692

Note:

Duty Cycle Correction Factor=10log (1/x).

Where: x is Duty Cycle (Linear)


Where: T is On Time


On Time=N3-N2

Period=N3-N1

If that calculated VBW is not available on the analyzer then the next higher value should be used.

If the EUT is configured to transmit with duty cycle $\geq 98\%$, set VBW $\leq$ RBW/100 (i.e., 10 kHz) but not less than 10 Hz.





Appendix B: Maximum Conducted Output Power

Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
b	2412	Ant1	12.05	≤30	Pass
b	2437	Ant1	12.06	≤30	Pass
b	2462	Ant1	12.28	≤30	Pass
g	2412	Ant1	16.00	≤30	Pass
g	2437	Ant1	15.87	≤30	Pass
g	2462	Ant1	16.0	≤30	Pass
n20	2412	Ant1	15.29	≤30	Pass
n20	2437	Ant1	15.26	≤30	Pass
n20	2462	Ant1	15.24	≤30	Pass
n40	2422	Ant1	11.85	≤30	Pass
n40	2437	Ant1	11.68	≤30	Pass
n40	2452	Ant1	11.70	≤30	Pass

Note: 1. Conducted Power=Meas. Level+ Correction Factor

2. The Duty Cycle Factor (refer to section 7.5) had already compensated to the test data.

Appendix C: -6dB Bandwidth

Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
b	2412	Ant1	8.024	≥ 0.5	Pass
	2437		7.540	≥ 0.5	Pass
	2462		8.053	≥ 0.5	Pass
g	2412		15.29	≥ 0.5	Pass
	2437		15.03	≥ 0.5	Pass
	2462		14.95	≥ 0.5	Pass
n20	2412		14.96	≥ 0.5	Pass
	2437		15.46	≥ 0.5	Pass
	2462		15.12	≥ 0.5	Pass
n40	2422		35.00	≥ 0.5	Pass
	2437		35.08	≥ 0.5	Pass
	2452		35.06	≥ 0.5	Pass

Test Graphs

-6dB Bandwidth NVNT b 2412MHz Ant1



-6dB Bandwidth NVNT b 2437MHz Ant1



-6dB Bandwidth NVNT b 2462MHz Ant1



-6dB Bandwidth NVNT g 2412MHz Ant1



-6dB Bandwidth NVNT g 2437MHz Ant1



-6dB Bandwidth NVNT g 2462MHz Ant1



-6dB Bandwidth NVNT n20 2412MHz Ant1



-6dB Bandwidth NVNT n20 2437MHz Ant1



-6dB Bandwidth NVNT n20 2462MHz Ant1



-6dB Bandwidth NVNT n40 2422MHz Ant1



-6dB Bandwidth NVNT n40 2437MHz Ant1



-6dB Bandwidth NVNT n40 2452MHz Ant1



Appendix D: Occupied Channel Bandwidth

Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
b	2412	Ant1	12.786
	2437		12.822
	2462		12.783
g	2412		16.464
	2437		16.474
	2462		16.415
n20	2412		17.569
	2437		17.581
	2462		17.569
n40	2422		36.055
	2437		35.968
	2452		35.988

Test Graphs

OBW NVNT b 2412MHz Ant1



OBW NVNT b 2437MHz Ant1



OBW NVNT b 2462MHz Ant1



OBW NVNT g 2412MHz Ant1



OBW NVNT g 2437MHz Ant1



OBW NVNT g 2462MHz Ant1



OBW NVNT n20 2412MHz Ant1



OBW NVNT n20 2437MHz Ant1



OBW NVNT n20 2462MHz Ant1



OBW NVNT n40 2422MHz Ant1



OBW NVNT n40 2437MHz Ant1



OBW NVNT n40 2452MHz Ant1



Appendix E: Maximum Power Spectral Density Level

Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm/3kHz)	Correction Factor (dB)	Final PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
b	2412	Ant1	-19.683	0.02	-19.663	≤8	Pass
b	2437	Ant1	-19.539	0.02	-19.519	≤8	Pass
b	2462	Ant1	-19.459	0.02	-19.439	≤8	Pass
g	2412	Ant1	-18.241	0.14	-18.101	≤8	Pass
g	2437	Ant1	-18.363	0.14	-18.223	≤8	Pass
g	2462	Ant1	-18.136	0.14	-17.996	≤8	Pass
n20	2412	Ant1	-18.835	0.14	-18.695	≤8	Pass
n20	2437	Ant1	-18.651	0.14	-18.511	≤8	Pass
n20	2462	Ant1	-18.513	0.14	-18.373	≤8	Pass
n40	2422	Ant1	-25.373	0.29	-25.083	≤8	Pass
n40	2437	Ant1	-25.321	0.29	-25.031	≤8	Pass
n40	2452	Ant1	-25.359	0.29	-25.069	≤8	Pass

For Correction Factor (dB), please refer to section 7.5.

Test Graphs

PSD NVNT b 2412MHz Ant1




PSD NVNT b 2437MHz Ant1




PSD NVNT b 2462MHz Ant1




PSD NVNT g 2412MHz Ant1




PSD NVNT g 2437MHz Ant1



PSD NVNT g 2462MHz Ant1




PSD NVNT n20 2412MHz Ant1



PSD NVNT n20 2437MHz Ant1



PSD NVNT n20 2462MHz Ant1



PSD NVNT n40 2422MHz Ant1



PSD NVNT n40 2437MHz Ant1



PSD NVNT n40 2452MHz Ant1



Appendix F: Band Edge

Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
b	2412	Ant1	-49.43	≤ -30	Pass
	2462		-50.1	≤ -30	Pass
g	2412		-32.07	≤ -30	Pass
	2462		-47.42	≤ -30	Pass
n20	2412		-33.27	≤ -30	Pass
	2462		-45.54	≤ -30	Pass
n40	2422		-37.3	≤ -30	Pass
	2452		-40.07	≤ -30	Pass

Test Graphs

Band Edge NVNT b 2412MHz Ant1 Ref



Band Edge NVNT b 2412MHz Ant1 Emission



Band Edge NVNT b 2462MHz Ant1 Ref



Band Edge NVNT b 2462MHz Ant1 Emission



Band Edge NVNT g 2412MHz Ant1 Ref



Band Edge NVNT g 2412MHz Ant1 Emission



Band Edge NVNT g 2462MHz Ant1 Ref



Band Edge NVNT g 2462MHz Ant1 Emission



Band Edge NVNT n20 2412MHz Ant1 Ref



Band Edge NVNT n20 2412MHz Ant1 Emission




Band Edge NVNT n20 2462MHz Ant1 Ref



Band Edge NVNT n20 2462MHz Ant1 Emission




Band Edge NVNT n40 2422MHz Ant1 Ref




Band Edge NVNT n40 2422MHz Ant1 Emission



Band Edge NVNT n40 2452MHz Ant1 Ref





Appendix G: Conducted RF Spurious Emission

Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
b	2412	Ant1	-43.61	≤ -30	Pass
	2437		-43.78	≤ -30	Pass
	2462		-43.78	≤ -30	Pass
g	2412		-45.3	≤ -30	Pass
	2437		-44.07	≤ -30	Pass
	2462		-45.05	≤ -30	Pass
n20	2412		-45.52	≤ -30	Pass
	2437		-43.39	≤ -30	Pass
	2462		-44.07	≤ -30	Pass
n40	2422		-38.75	≤ -30	Pass
	2437		-38.8	≤ -30	Pass
	2452		-36.95	≤ -30	Pass

Test Graphs

Tx. Spurious NVNT b 2412MHz Ant1 Ref



Tx. Spurious NVNT b 2412MHz Ant1 Emission



Tx. Spurious NVNT b 2437MHz Ant1 Ref



Tx. Spurious NVNT b 2437MHz Ant1 Emission




Tx. Spurious NVNT b 2462MHz Ant1 Ref



Tx. Spurious NVNT b 2462MHz Ant1 Emission



Tx. Spurious NVNT g 2412MHz Ant1 Ref



Tx. Spurious NVNT g 2412MHz Ant1 Emission



Tx. Spurious NVNT g 2437MHz Ant1 Ref



Tx. Spurious NVNT g 2437MHz Ant1 Emission



Tx. Spurious NVNT g 2462MHz Ant1 Ref



Tx. Spurious NVNT g 2462MHz Ant1 Emission



Tx. Spurious NVNT n20 2412MHz Ant1 Ref






Tx. Spurious NVNT n20 2412MHz Ant1 Emission




Tx. Spurious NVNT n20 2437MHz Ant1 Ref






Tx. Spurious NVNT n40 2422MHz Ant1 Ref



Tx. Spurious NVNT n40 2422MHz Ant1 Emission




Tx. Spurious NVNT n40 2437MHz Ant1 Ref



Tx. Spurious NVNT n40 2437MHz Ant1 Emission



Tx. Spurious NVNT n40 2452MHz Ant1 Ref



Tx. Spurious NVNT n40 2452MHz Ant1 Emission



END OF REPORT