



# RADIO EXPOSURE TEST REPORT

FCC ID : MSQ-RTBE8H00  
Equipment : ROG STRIX WiFi 7 Tri-Band Gaming Router  
Brand Name : ASUS  
Model Name : GS-BE18000, GS-BE12000  
Applicant : ASUSTeK COMPUTER INC.  
1F., No. 15, Lide Rd., Beitou, Taipei City 112, Taiwan  
Standard : 47 CFR Part 2.1091

The product was received on Jan. 09, 2025, and testing was started from Jan. 09, 2025 and completed on Feb. 27, 2025. We, Sporton International Inc. Hsinchu Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091 and shown compliance with the applicable technical standards.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. Hsinchu Laboratory, the test report shall not be reproduced except in full.

Approved by: Sam Chen

**Sporton International Inc. Hsinchu Laboratory**

No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)



## Table of Contents

|                                                 |          |
|-------------------------------------------------|----------|
| History of this test report.....                | 3        |
| Summary of Test Result.....                     | 4        |
| <b>1 General Description .....</b>              | <b>5</b> |
| 1.1 EUT General Information .....               | 5        |
| 1.2 Antenna Information .....                   | 6        |
| 1.3 Table for Multiple Listing .....            | 7        |
| 1.4 Table for EUT Support Function.....         | 7        |
| 1.5 Accessories .....                           | 7        |
| 1.6 Applicable Standards .....                  | 8        |
| 1.7 Testing Location .....                      | 8        |
| <b>2 Maximum Permissible Exposure .....</b>     | <b>9</b> |
| 2.1 Limit of Maximum Permissible Exposure ..... | 9        |
| 2.2 MPE Calculation Method .....                | 9        |
| 2.3 MPE Exemption .....                         | 10       |
| 2.4 Calculated Result and Limit.....            | 11       |

### Photographs of EUT v01





## Summary of Test Result

| Report Clause | Ref Std. Clause | Test Items          | Result (PASS/FAIL) | Remark |
|---------------|-----------------|---------------------|--------------------|--------|
| 2             | -               | Exposure evaluation | PASS               | -      |

**Conformity Assessment Condition:**

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the chapter "Measurement Uncertainty".

**Disclaimer:**

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

**Reviewed by: Sam Chen**

**Report Producer: Muse Chan**



# 1 General Description

## 1.1 EUT General Information

| RF General Information |                                                                                                           |                                                                                                           |                                                                                                                                                                                                                                                                                 |
|------------------------|-----------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Evaluation Mode        | Frequency Range (MHz)                                                                                     | Operating Frequency (MHz)                                                                                 | Modulation Type                                                                                                                                                                                                                                                                 |
| 2.4GHz WLAN            | 2400-2483.5                                                                                               | 2412-2462                                                                                                 | 802.11b: DSSS (DBPSK, DQPSK, CCK)<br>802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)<br>VHT: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)<br>802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)<br>802.11be: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM) |
| 5GHz WLAN              | 5150-5250<br>5250-5350<br>5470-5725<br>5725-5850                                                          | 5180-5250<br>5250-5320<br>5500-5720<br>5745-5825                                                          | 802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)<br>802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)<br>802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)<br>802.11be: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM)                                 |
| 6GHz WLAN              | For Indoor Access Point /Subordinate: 5925-7125<br>For Standard Power Access Point: 5925-6425 / 6525-6875 | For Indoor Access Point /Subordinate: 5955-7095<br>For Standard Power Access Point: 5955-6415 / 6535-6855 | 802.11a: OFDM (BPSK, QPSK, 16QAM, 64QAM)<br>802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)<br>802.11be: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM, 4096QAM)                                                                                                 |



## 1.2 Antenna Information

| Ant. | Port   |      |      | Brand   | Model Name      | Antenna Type   | Connector | Gain (dBi) |
|------|--------|------|------|---------|-----------------|----------------|-----------|------------|
|      | 2.4GHz | 5GHz | 6GHz |         |                 |                |           |            |
| 1    | 1      | 1    | -    | LYNwave | MLX24X-121AA0-A | PCB Antenna    | I-PEX     | Note 1     |
| 2    | 2      | 2    | -    | LYNwave | MLX24X-121AA0-A | PCB Antenna    | I-PEX     |            |
| 3    | -      | -    | 4    | LYNwave | MLX24X-121AA0-A | Dipole Antenna | I-PEX     |            |
| 4    | -      | -    | 2    | LYNwave | MLX24X-121AA0-A | Dipole Antenna | I-PEX     |            |
| 5    | -      | 3    | -    | LYNwave | MLX24X-121AA0-A | Dipole Antenna | I-PEX     |            |
| 6    | -      | 4    | -    | LYNwave | MLX24X-121AA0-A | Dipole Antenna | I-PEX     |            |
| 7    | -      | -    | 1    | LYNwave | MLX24X-121AA0-A | Dipole Antenna | I-PEX     |            |
| 8    | -      | -    | 3    | LYNwave | MLX24X-121AA0-A | Dipole Antenna | I-PEX     |            |

Note 1:

| Ant. | Antenna Gain (dBi) |                  |                   |                   |                  |                  |                  |                  |                  |
|------|--------------------|------------------|-------------------|-------------------|------------------|------------------|------------------|------------------|------------------|
|      | WLAN 2.4GHz        | WLAN 5GHz UNII 1 | WLAN 5GHz UNII 2A | WLAN 5GHz UNII 2C | WLAN 5GHz UNII 3 | WLAN 6GHz UNII 5 | WLAN 6GHz UNII 6 | WLAN 6GHz UNII 7 | WLAN 6GHz UNII 8 |
| 1    | 2.87               | 4.03             | 4.06              | 3.8               | 2.74             | -                | -                | -                | -                |
| 2    | 2.66               | 2.23             | 3.44              | 3.5               | 3.04             | -                | -                | -                | -                |
| 3    | -                  | -                | -                 | -                 | -                | 4.66             | 3.16             | 3.19             | 3.36             |
| 4    | -                  | -                | -                 | -                 | -                | 3.59             | 4.42             | 3.92             | 3.08             |
| 5    | -                  | 4.56             | 5.15              | 4.91              | 4.77             | -                | -                | -                | -                |
| 6    | -                  | 2.04             | 2.49              | 3.65              | 3.25             | -                | -                | -                | -                |
| 7    | -                  | -                | -                 | -                 | -                | 4.57             | 4.78             | 4.74             | 3.82             |
| 8    | -                  | -                | -                 | -                 | -                | 4.65             | 3.94             | 4.11             | 4.32             |

| Item | Directional Gain (dBi) |                  |                   |                   |                  |                  |                  |                  |                  |
|------|------------------------|------------------|-------------------|-------------------|------------------|------------------|------------------|------------------|------------------|
|      | WLAN 2.4GHz            | WLAN 5GHz UNII 1 | WLAN 5GHz UNII 2A | WLAN 5GHz UNII 2C | WLAN 5GHz UNII 3 | WLAN 6GHz UNII 5 | WLAN 6GHz UNII 6 | WLAN 6GHz UNII 7 | WLAN 6GHz UNII 8 |
| 2T1S | 5.38                   | -                | -                 | -                 | -                | -                | -                | -                | -                |
| 2T2S | 2.87                   | -                | -                 | -                 | -                | -                | -                | -                | -                |
| 4T1S | -                      | 5.4              | 5.57              | 5.43              | 4.91             | 6.77             | 6.44             | 6.79             | 5.87             |
| 4T2S | -                      | 4.56             | 5.15              | 4.91              | 4.77             | 4.66             | 4.78             | 4.74             | 4.32             |
| 4T4S | -                      | 4.56             | 5.15              | 4.91              | 4.77             | 4.66             | 4.78             | 4.74             | 4.32             |

Note 2: Maximum Directional Gain following KDB662911 D03.

**For WLAN 2.4GHz function:****For IEEE 802.11b/g/n/VHT/ax/be mode (2TX/2RX):**

Port 1 and Port 2 can be use as transmitting/receiving antenna.

Port 1 and Port 2 could transmit/receive simultaneously.

**For WLAN 5GHz function:****For IEEE 802.11n/ac/ax/be mode (4TX/4RX):**

Port 1, Port 2, Port 3 and Port 4 can be use as transmitting/receiving antenna.

Port 1, Port 2, Port 3 and Port 4 could transmit/receive simultaneously.

**For WLAN 6GHz function:****For IEEE 802.11ax/be mode (4TX/4RX):**

Port 1, Port 2, Port 3 and Port 4 can be use as transmitting/receiving antenna.

Port 1, Port 2, Port 3 and Port 4 could transmit/receive simultaneously.



### 1.3 Table for Multiple Listing

| EUT | Equipment Name                             | Model Name | Description                                             |
|-----|--------------------------------------------|------------|---------------------------------------------------------|
| 1   | ROG STRIX WiFi 7<br>Tri-Band Gaming Router | GS-BE18000 | The housing processing technique uses spray painting.   |
| 2   |                                            | GS-BE12000 | The housing processing technique uses a textured finish |

Note 1: From the above models, model: GS-BE18000 (EUT 1) was selected as representative model for the test and its data was recorded in this report.

Note 2: The above information was declared by manufacturer.

### 1.4 Table for EUT Support Function

| Function  | Supports Band                 |
|-----------|-------------------------------|
| AP Router | Master                        |
| Bridge    | Slave without radar detection |
| Repeater  | Master                        |
| Mesh      | Master                        |

Note1: The USB port on this device supports both storage and WWAN functionality and EUT in WWAN mode, 2.5G WAN Port 8 will be fixed in LAN function.

Note2: The above information was declared by manufacturer.

#### 1.4.1 Table for Permissive Change

This product is an extension of original one reported under Sporton project number: FA510722

Below is the table for the change of the product with respect to the original one.

| Modifications                                                                                                                                                                                                                 | Performance Checking |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|
| 1. Adding UNII 2A and UNII 2C (5250~5350 MHz, 5470~5725 MHz) for this device.<br>2. Adding 160MHz in 5GHz for this device.<br>3. Adding 6GHz UNII 5~8 for this device.<br>4. Updating the MPE distance to "59cm" from "47cm". | MPE                  |

### 1.5 Accessories

| Accessories                   |            |                 |                                                    |
|-------------------------------|------------|-----------------|----------------------------------------------------|
| Equipment Name                | Brand Name | Model Name      | Rating                                             |
| Adapter                       | LEI        | MU36D1120300-A1 | INPUT: 100-240V ~ 50/60Hz, 1.0A<br>OUTPUT: 12V, 3A |
| Others                        |            |                 |                                                    |
| RJ-45 cable*1, shielded, 1.5m |            |                 |                                                    |



## 1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2.1091
- ♦ KDB 447498 D04 Interim General RF Exposure Guidance v01

The following reference test guidance is not within the scope of accreditation of TAF.

- ♦ 47 CFR Part 1.1307
- ♦ 47 CFR Part 1.1310

## 1.7 Testing Location

| Testing Location Information                              |                                                                                    |
|-----------------------------------------------------------|------------------------------------------------------------------------------------|
| Test Lab. : Sporton International Inc. Hsinchu Laboratory |                                                                                    |
| Hsinchu                                                   | ADD: No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.) |
| (TAF: 3787)                                               | TEL: 886-3-656-9065      FAX: 886-3-656-9085                                       |
|                                                           | Test site Designation No. TW3787 with FCC.                                         |
|                                                           | Conformity Assessment Body Identifier (CABID) TW3787 with ISED.                    |





## 2 Maximum Permissible Exposure

### 2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|------------------------------------------|------------------------------------------------------------------|
| 0.3-3.0               | 614                               | 1.63                              | *(100)                                   | <6                                                               |
| 3.0-30                | 1842/f                            | 4.89/f                            | *(900/f <sup>2</sup> )                   | <6                                                               |
| 30-300                | 61.4                              | 0.163                             | 1.0                                      | <6                                                               |
| 300-1500              | -                                 | -                                 | f/300                                    | <6                                                               |
| 1500-100,000          | -                                 | -                                 | 5                                        | <6                                                               |

(B) Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|------------------------------------------|------------------------------------------------------------------|
| 0.3-1.34              | 614                               | 1.63                              | *(100)                                   | <30                                                              |
| 1.34-30               | 824/f                             | 2.19/f                            | *(180/f <sup>2</sup> )                   | <30                                                              |
| 30-300                | 27.5                              | 0.073                             | 0.2                                      | <30                                                              |
| 300-1500              | -                                 | -                                 | f/1500                                   | <30                                                              |
| 1500-100,000          | -                                 | -                                 | 1.0                                      | <30                                                              |

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 2.2 MPE Calculation Method

The MPE was calculated at 59 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



## 2.3 MPE Exemption

Option (A): 1.1307(b)(3)(i)(A): Available maximum time-averaged power is < 1 mW

Option (B): 1.1307(b)(3)(i)(B): Device operates between 300 MHz and 6 GHz and the maximum time-averaged power or effective radiated power (ERP), whichever is greater, <= P<sub>th</sub>.

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

$d$  = the separation distance (cm);

Option (C): 1.1307(b)(3)(i)(C): ERP is below a threshold calculated based on the distance

$R$  between the person and the antenna / radiating structure, where  $R > \lambda / 2 \pi$ .

| Single RF Sources Subject to Routine Environmental Evaluation |                       |
|---------------------------------------------------------------|-----------------------|
| RF Source frequency (MHz)                                     | Threshold ERP (watts) |
| 0.3-1.34                                                      | $1,920 R^2$ .         |
| 1.34-30                                                       | $3,450 R^2/f^2$ .     |
| 30-300                                                        | $3.83 R^2$ .          |
| 300-1,500                                                     | $0.0128 R^2 f$ .      |
| 1,500-100,000                                                 | $19.2 R^2$ .          |
| Note: R is in meters, f is in MHz.                            |                       |



## 2.4 Calculated Result and Limit

### Exposure Environment: General Population / Uncontrolled Exposure

| Mode       | DG (dBi) | Power (dBm) | ERP (dBm) | Tolerance (dB) | Tune-up ERP (mW) | Distance (cm) | Option | TL ERP (mW) | TL Ratio |
|------------|----------|-------------|-----------|----------------|------------------|---------------|--------|-------------|----------|
| 2.4G;D1D   | 5.38     | 28.01       | 31.24     | 0.50           | 1492.794         | 59            | C      | 6683.6      | 0.2234   |
| 5.2G;D1D   | 5.40     | 29.89       | 33.14     | 0.50           | 2312.065         | 59            | C      | 6683.6      | 0.3461   |
| 5.3G;D1D   | 5.57     | 23.95       | 27.37     | 0.45           | 605.341          | 59            | C      | 6683.6      | 0.0906   |
| 5.6G;D1D   | 5.43     | 23.95       | 27.23     | 0.50           | 592.925          | 59            | C      | 6683.6      | 0.0887   |
| 5.8G;D1D   | 4.91     | 29.96       | 32.72     | 0.50           | 2098.940         | 59            | C      | 6683.6      | 0.3142   |
| Band12;G7D | 0.00     | 24.00       | 21.85     | 0.50           | 171.791          | 59            | C      | 3114.5      | 0.0552   |
| 6.2G;D1D   | 6.77     | 29.19       | 33.81     | 0.03           | 2421.029         | 59            | C      | 6683.6      | 0.3624   |
| 6.4G;D1D   | 6.44     | 23.46       | 27.75     | 0.09           | 608.135          | 59            | C      | 6683.6      | 0.0910   |
| 6.7G;D1D   | 4.74     | 31.24       | 33.83     | 0.01           | 2421.029         | 59            | C      | 6683.6      | 0.3624   |
| 7.0G;D1D   | 5.87     | 21.47       | 25.19     | 0.50           | 370.681          | 59            | C      | 6683.6      | 0.0555   |

### Simultaneous Transmission Analysis Mode:

#### Mode 1: EUT + WLAN 2.4GHz + WLAN 5GHz + WLAN 6GHz

| Mode           | DG (dBi) | Power (dBm) | ERP (dBm) | Tolerance (dB) | Tune-up ERP (mW) | Distance (cm) | Option | TL ERP (mW) | TL Ratio |
|----------------|----------|-------------|-----------|----------------|------------------|---------------|--------|-------------|----------|
| 2.4G;D1D       | 5.38     | 28.01       | 31.24     | 0.50           | 1492.794         | 59            | C      | 6683.6      | 0.2234   |
| 5.2G;D1D       | 5.40     | 29.89       | 33.14     | 0.50           | 2312.065         | 59            | C      | 6683.6      | 0.3461   |
| 6.7G;D1D       | 4.74     | 31.24       | 33.83     | 0.01           | 2421.029         | 59            | C      | 6683.6      | 0.3624   |
| Sum TL Ratio_C | 0.9319   |             |           |                |                  |               |        |             |          |
| Ratio Limit    | 1        |             |           |                |                  |               |        |             |          |

#### Mode 2: EUT + WLAN 2.4GHz + WLAN 5GHz + WLAN 6GHz + WWAN

| Mode           | DG (dBi) | Power (dBm) | ERP (dBm) | Tolerance (dB) | Tune-up ERP (mW) | Distance (cm) | Option | TL ERP (mW) | TL Ratio |
|----------------|----------|-------------|-----------|----------------|------------------|---------------|--------|-------------|----------|
| 2.4G;D1D       | 5.38     | 28.01       | 31.24     | 0.50           | 1492.794         | 59            | C      | 6683.6      | 0.2234   |
| 5.2G;D1D       | 5.40     | 29.89       | 33.14     | 0.50           | 2312.065         | 59            | C      | 6683.6      | 0.3461   |
| Band12;G7D     | 0.00     | 24.00       | 21.85     | 0.50           | 171.791          | 59            | C      | 3114.5      | 0.0552   |
| 6.7G;D1D       | 4.74     | 31.24       | 33.83     | 0.01           | 2421.029         | 59            | C      | 6683.6      | 0.3624   |
| Sum TL Ratio_C | 0.9871   |             |           |                |                  |               |        |             |          |
| Ratio Limit    | 1        |             |           |                |                  |               |        |             |          |

—THE END—