

FCC Part 15C&RSS-247 Test Report

FCC ID:2AD4XONYXGOMIX

IC:12714A-ONYXGOMIX

Report Number.....: ZKT-230531L4056-1

Date of Test..... May. 18, 2023 to Jun. 30, 2023

Date of issue.....: Jul. 03, 2023

Total number of pages..... 49

Test Result: PASS

Testing Laboratory.....: Shenzhen ZKT Technology Co., Ltd.

Address: 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name: LOUD Audio, LLC

Address: 19820 North Creek Parkway, Suite #201, Bothell, WA 98011-8227, USA

Manufacturer's name: LOUD Audio, LLC

Address: 19820 North Creek Parkway, Suite #201, Bothell, WA 98011-8227, USA

Factory's name: Watson E.P. Industries (Dongguan) Co., Ltd.

Address: 2, Jin Wei Road, Gu Kang, Jin He Industrial Zone 2, Zhang Mu Tou, Dongguan, Guangdong, P.R. China

Factory's name: Watson E.P. Industries Pet Co Ltd

Address: 14 Jalan Mesin Watson Industrial Building Singapore 368814

Test specification:

Standard.....: FCC CFR Title 47 Part 15 Subpart C Section 15.247
RSS-247 Issue 2: February 2017
RSS-GEN, Issue 5: March 2019
ANSI C63.10:2013

Test procedure.....: /

Non-standard test method: N/A

Test Report Form No.....: TRF-EL-111_V0

Test Report Form(s) Originator.....: ZKT Testing

Master TRF: Dated: 2021-04-22

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name.....: MOBILE MIX

Trademark



Model/Type reference.....: MOBILE MIX


Ratings.....: DC 5V from Adapter

Testing procedure and testing location:

Testing Laboratory.....: Shenzhen ZKT Technology Co., Ltd.

Address.....: 1/F, No. 101, Building B, No. 6, Tangwei Community
Industrial Avenue, Fuhai Street, Bao'an District,
Shenzhen, China

Tested by (name + signature).....: Alen He



Reviewer (name + signature).....: Joe Liu



Approved (name + signature).....: Lake Xie



Table of Contents

	Page
1. VERSION	5
2. TEST SUMMARY	6
2.1 TEST FACILITY	7
2.2 MEASUREMENT UNCERTAINTY	7
3. GENERAL INFORMATION	8
3.1 GENERAL DESCRIPTION OF EUT	8
3.2 Test Setup Configuration	9
3.3 Support Equipment	9
3.4 Test Mode	10
3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	11
4. EMC EMISSION TEST	12
4.1 Conducted emissions	12
4.1.1 POWER LINE CONDUCTED EMISSION Limits	12
4.1.2 TEST PROCEDURE	12
4.1.3 DEVIATION FROM TEST STANDARD	12
4.1.4 TEST SETUP	13
4.1.5 EUT OPERATING CONDITIONS	13
4.1.6 Test Result	14
4.2 Radiated emissions	16
4.2.1 Radiated Emission Limits	16
4.2.2 TEST PROCEDURE	16
4.2.3 DEVIATION FROM TEST STANDARD	17
4.2.4 TEST SETUP	17
4.2.5 EUT OPERATING CONDITIONS	18
4.2.6 TEST RESULTS	19
5. RADIATED BAND EMISSION MEASUREMENT	24
5.1 Test Requirement:	24
5.2 TEST PROCEDURE	24
5.3 DEVIATION FROM TEST STANDARD	25
5.4 TEST SETUP	25
5.5 EUT OPERATING CONDITIONS	25
5.6 TEST RESULT	26
6. CONDUCTED BAND EDGE AND SPURIOUS EMISSION	27
6.1 Limit	27
6.2 Test Setup	27
6.3 Test procedure	27
6.4 DEVIATION FROM STANDARD	27
6.5 Test Result	28
7. 20DB BANDWIDTH & 99% OCB	33
7.1 Test Setup	33
7.2 Limit	33
7.3 Test procedure	33
7.4 DEVIATION FROM STANDARD	33

7.5 Test Result	34
8. MAXIMUM PEAK OUTPUT POWER	36
8.1 Block Diagram Of Test Setup	36
8.2 Limit	36
8.3 Test procedure	36
8.4 DEVIATION FROM STANDARD	36
8.5 Test Result	36
9. HOPPING CHANNEL SEPARATION	39
9.1 Test Setup	39
9.2 Test procedure	39
9.3 DEVIATION FROM STANDARD	39
9.4 Test Result	40
10.NUMBER OF HOPPING FREQUENCY	41
10.1 Test Setup	41
10.2 Test procedure	41
10.3 DEVIATION FROM STANDARD	41
10.4 Test Result	42
11. DWELL TIME	43
11.1 Test Setup	43
11.2 Test procedure	43
11.3 DEVIATION FROM STANDARD	43
11.4 Test Result	44
12. ANTENNA REQUIREMENT	48
13. TEST SETUP PHOTO	49
14. EUT CONSTRUCTIONAL DETAILS	49

1. VERSION

Report No.	Version	Description	Approved
ZKT-230531L4056-1	Rev.01	Initial issue of report	Jul. 03, 2023

2. TEST SUMMARY

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C RSS-247 Issue 2: February 2017			
Standard Section	Test Item	Result	Remark
15.203/15.247 (c) RSS-Gen 6.8	Antenna Requirement	PASS	
15.207 RSS-Gen 8.8	AC Power Line Conducted Emission	PASS	
15.247 (b)(1) RSS-247.5.4(4)	Conducted Peak Output Power	PASS	
15.247 (a)(1) RSS-247.5.1(2) RSS-Gen.6.7	20dB Occupied Bandwidth & 99% OCB	PASS	
15.247 (a)(1) RSS-247.5.1(4)	Carrier Frequencies Separation	PASS	
15.247 (a)(1)(iii) RSS-247.5.1(4)	Hopping Channel Number	PASS	
15.247 (a)(1)(iii) RSS-247.5.1(5)	Dwell Time	PASS	
15.205/15.209 RSS-Gen.6.13 RSS-Gen.8.10	Radiated Emission and Restricted Bandedge	PASS	
15.247(d) RSS-247 5.5	Conducted Unwanted emissions and Bandedge	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

2.1 TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.

Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street,
Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225

Designation Number: CN1299

IC Registered No.: 27033

Test lab CAB identifier:CN0110

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power conducted	$\pm 0.16\text{dB}$
3	Spurious emissions conducted	$\pm 0.21\text{dB}$
4	All emissions radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	MOBILE MIX
Model No.:	MOBILE MIX
Sample ID:	ZKT230531L4056-1#
Serial No.:	N/A
Model Different.:	N/A
HVIN:	MOBILE MIX
Hardware Version:	V600
Software Version:	V0.05
Sample(s) Status:	Engineer sample
Channel numbers:	79
Channel separation:	2402MHz~2480MHz
Modulation technology:	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Antenna Type:	PCB antenna
Antenna gain:	2.01dBi
Power supply:	DC 5V from Adapter
Adapter Information:	Manufacturer:Dongguan Dongsong Electronics Co., Ltd. Model:DYS806-050120W-3 Input:100-240V~50/60Hz 0.3A MAX Output:DC 5.0V/1.2A

Operation Frequency each of channel

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz

16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz

3.2 Test Setup Configuration


Conducted Emission



Radiated Emission




Conducted Spurious



3.3 Support Equipment

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	MOBILE MIX		MOBILE MIX	N/A	EUT
AE	Notebook	lenovo	B40-80	MP07F6JD	AE

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

3.4 Test Mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

Test Software	Bluetest3.exe
Power level setup	<5dBm

3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation & RF Conducted Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	9020A	MY45109572	Oct. 17, 2022	Oct. 17, 2023
2	Spectrum Analyzer (1GHz-40GHz)	Agilent	E4446A	100363	Oct. 17, 2022	Oct. 17, 2023
3	Test Receiver (9kHz-7GHz)	R&S	ESCI7	101169	Oct. 17, 2022	Oct. 17, 2023
4	Bilog Antenna (30MHz-1400MHz)	Schwarzbeck	VULB9168	00877	Oct. 17, 2022	Oct. 17, 2023
5	Horn Antenna (1GHz-18GHz)	SCHWARZBEC K	BBHA9120D	1541	Oct. 17, 2022	Oct. 17, 2023
6	Horn Antenna (18GHz-40GHz)	A.H. System	SAS-574	588	Oct. 17, 2022	Oct. 17, 2023
7	Amplifier (30-1000MHz)	EM Electronics	EM330 Amplifier	N/A	Oct. 17, 2022	Oct. 17, 2023
8	Amplifier (1GHz-40GHz)	QUANJUDA	DLE-161	097	Oct. 17, 2022	Oct. 17, 2023
9	Loop Antenna (9kHz-30MHz)	SCHWARZBEC K	FMZB1519B	014	Oct. 17, 2022	Oct. 17, 2023
10	RF cables1 (9kHz-30MHz)	N/A	9kHz-30MHz	N/A	Oct. 17, 2022	Oct. 17, 2023
11	RF cables2 (30MHz-1GHz)	N/A	30MHz-1GHz	N/A	Oct. 17, 2022	Oct. 17, 2023
12	RF cables3 (1GHz-40GHz)	N/A	1GHz-40GHz	N/A	Oct. 17, 2022	Oct. 17, 2023
13	CMW500 Test	R&S	CMW500	106504	Oct. 17, 2022	Oct. 17, 2023
14	ESG Signal Generator	Agilent	E4421B	GB40051203	Oct. 17, 2022	Oct. 17, 2023
15	Signal Generator	Agilent	N5182A	MY47420215	Oct. 17, 2022	Oct. 17, 2023
16	Power Meter	Anritsu	ML2495A	N/A	Oct. 17, 2022	Oct. 17, 2023
17	D.C. Power Supply	LongWei	TPR-6405D	\	\	\
18	Software	Audix	E3	6.101223a	\	\

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	LISN	R&S	ENV216	101471	Oct. 17, 2022	Oct. 17, 2023
2	LISN	CYBERTEK	EM5040A	E1850400149	Oct. 17, 2022	Oct. 17, 2023
3	Test Cable	N/A	C01	N/A	Oct. 17, 2022	Oct. 17, 2023
4	Test Cable	N/A	C02	N/A	Oct. 17, 2022	Oct. 17, 2023
5	EMI Test Receiver	R&S	ESRP3	101946	Oct. 17, 2022	Oct. 17, 2023
6	Absorbing Clamp	DZ	ZN23201	N/A	Oct. 17, 2022	Oct. 17, 2023
7	Software	Audix	E3	6.101223a	\	\

4. EMC EMISSION TEST

4.1 Conducted emissions

Test Requirement:	FCC Part15 C Section 15.207& RSS-Gen [8.8]
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.


4.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes


4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 230V, the worst voltage was AC 120V and the data recording in the report.

4.1.6 Test Result

Temperature :	26℃	Relative Humidity:	54%
Pressure :	101kPa	Phase :	L
Test Voltage :	AC 120V/60Hz		




	Read Freq	Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.37	31.52	9.66	0.05	41.23	48.47	-7.24	Average
2	0.37	34.31	9.66	0.05	44.02	58.47	-14.45	QP
3	0.41	29.29	9.67	0.05	39.01	47.64	-8.63	Average
4	0.41	39.33	9.67	0.05	49.05	57.64	-8.59	QP
5	12.45	30.04	9.59	0.10	39.73	50.00	-10.27	Average
6	12.45	44.21	9.59	0.10	53.90	60.00	-6.10	QP
7	14.59	30.62	9.54	0.10	40.26	50.00	-9.74	Average
8	14.59	44.61	9.54	0.10	54.25	60.00	-5.75	QP
9	18.33	36.85	9.59	0.10	46.54	50.00	-3.46	Average
10	18.33	39.94	9.59	0.10	49.63	60.00	-10.37	QP
11	20.49	33.04	9.63	0.10	42.77	50.00	-7.23	Average
12	20.49	39.06	9.63	0.10	48.79	60.00	-11.21	QP

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor
4. The test data shows only the worst case GFSK mode

Temperature :	26°C	Relative Humidity:	54%
Pressure :	101kPa	Phase :	N
Test Voltage :	AC 120V/60Hz		



	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.37	31.15	9.60	0.05	40.80	48.43	-7.63	Average
2	0.37	36.16	9.60	0.05	45.81	58.43	-12.62	QP
3	0.41	29.06	9.62	0.05	38.73	47.64	-8.91	Average
4	0.41	42.55	9.62	0.05	52.22	57.64	-5.42	QP
5	10.23	29.46	9.71	0.10	39.27	50.00	-10.73	Average
6	10.23	44.19	9.71	0.10	54.00	60.00	-6.00	QP
7	12.19	31.71	9.73	0.10	41.54	50.00	-8.46	Average
8	12.19	43.05	9.73	0.10	52.88	60.00	-7.12	QP
9	15.15	30.77	9.75	0.10	40.62	50.00	-9.38	Average
10	15.15	43.59	9.75	0.10	53.44	60.00	-6.56	QP
11	18.14	35.74	9.78	0.10	45.62	50.00	-4.38	Average
12	18.14	39.61	9.78	0.10	49.49	60.00	-10.51	QP

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor
4. The test data shows only the worst case GFSK mode

4.2 Radiated emissions

Test Requirement:	FCC Part15 C Section 15.209 & RSS-247 [5.5]				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	1/T	Average

4.2.1 Radiated Emission Limits

Frequencies (MHz)	Field Strength (micровolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
- h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD


No deviation

4.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


4.2.6 TEST RESULTS

Between 9KHz – 30MHz


The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

Between 30MHz – 1GHz

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz		



Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz		



Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. The test data shows only the worst case GFSK mode

Above 1 GHz Test Results (GFSK Worst Case):
1GHz~25GHz

GFSK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2402MHz									
V	4804.00	56.74	30.55	5.77	24.66	56.62	74.00	-17.38	Pk
V	4804.00	46.39	30.55	5.77	24.66	46.27	54.00	-7.73	AV
V	7206.00	55.67	30.33	6.32	24.55	56.21	74.00	-17.79	Pk
V	7206.00	45.43	30.33	6.32	24.55	45.97	54.00	-8.03	AV
V	9608.00	53.01	30.85	7.45	24.69	54.3	74.00	-19.7	Pk
V	9608.00	43.28	30.85	7.45	24.69	44.57	54.00	-9.43	AV
V	12010.00	51.27	31.02	8.99	25.57	54.81	74.00	-19.19	Pk
V	12010.00	42.06	31.02	8.99	25.57	45.6	54.00	-8.4	AV
H	4804.00	56.33	30.55	5.77	24.66	56.21	74.00	-17.79	Pk
H	4804.00	46.27	30.55	5.77	24.66	46.15	54.00	-7.85	AV
H	7206.00	54.86	30.33	6.32	24.55	55.4	74.00	-18.6	Pk
H	7206.00	44.16	30.33	6.32	24.55	44.7	54.00	-9.3	AV
H	9608.00	52.81	30.85	7.45	24.69	54.1	74.00	-19.9	Pk
H	9608.00	42.35	30.85	7.45	24.69	43.64	54.00	-10.36	AV
H	12010.00	51.39	31.02	8.99	25.57	54.93	74.00	-19.07	Pk
H	12010.00	42.03	31.02	8.99	25.57	45.57	54.00	-8.43	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2441MHz									
V	4882.00	56.31	30.55	5.77	24.66	56.19	74.00	-17.81	Pk
V	4882.00	46.47	30.55	5.77	24.66	46.35	54.00	-7.65	AV
V	7323.00	54.96	30.33	6.32	24.55	55.5	74.00	-18.5	Pk
V	7323.00	44.73	30.33	6.32	24.55	45.27	54.00	-8.73	AV
V	9764.00	52.63	30.85	7.45	24.69	53.92	74.00	-20.08	Pk
V	9764.00	42.36	30.85	7.45	24.69	43.65	54.00	-10.35	AV
V	12205.00	51.03	31.02	8.99	25.57	54.57	74.00	-19.43	Pk
V	12205.00	41.74	31.02	8.99	25.57	45.28	54.00	-8.72	AV
H	4882.00	56.33	30.55	5.77	24.66	56.21	74.00	-17.79	Pk
H	4882.00	46.05	30.55	5.77	24.66	45.93	54.00	-8.07	AV
H	7323.00	54.03	30.33	6.32	24.55	54.57	74.00	-19.43	Pk
H	7323.00	44.12	30.33	6.32	24.55	44.66	54.00	-9.34	AV
H	9764.00	52.36	30.85	7.45	24.69	53.65	74.00	-20.35	Pk
H	9764.00	42.16	30.85	7.45	24.69	43.45	54.00	-10.55	AV
H	12205.00	51.85	31.02	8.99	25.57	55.39	74.00	-18.61	Pk
H	12205.00	42.04	31.02	8.99	25.57	45.58	54.00	-8.42	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-ampli fier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2480MHz									
V	4960.00	56.43	30.55	5.77	24.66	56.31	74.00	-17.69	Pk
V	4960.00	45.1	30.55	5.77	24.66	44.98	54.00	-9.02	AV
V	7440.00	54.36	30.33	6.32	24.55	54.9	74.00	-19.1	Pk
V	7440.00	45.02	30.33	6.32	24.55	45.56	54.00	-8.44	AV
V	9920.00	52.31	30.85	7.45	24.69	53.6	74.00	-20.4	Pk
V	9920.00	42.16	30.85	7.45	24.69	43.45	54.00	-10.55	AV
V	12400.00	50.36	31.02	8.99	25.57	53.9	74.00	-20.1	Pk
V	12400.00	41.27	31.02	8.99	25.57	44.81	54.00	-9.19	AV
H	4960.00	56.83	30.55	5.77	24.66	56.71	74.00	-17.29	Pk
H	4960.00	45.77	30.55	5.77	24.66	45.65	54.00	-8.35	AV
H	7440.00	54.16	30.33	6.32	24.55	54.7	74.00	-19.3	Pk
H	7440.00	45.23	30.33	6.32	24.55	45.77	54.00	-8.23	AV
H	9920.00	52.39	30.85	7.45	24.69	53.68	74.00	-20.32	Pk
H	9920.00	42.35	30.85	7.45	24.69	43.64	54.00	-10.36	AV
H	12400.00	51.07	31.02	8.99	25.57	54.61	74.00	-19.39	Pk
H	12400.00	41.23	31.02	8.99	25.57	44.77	54.00	-9.23	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

5. RADIATED BAND EMISSION MEASUREMENT

5.1 Test Requirement:

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Average	1MHz	1/T	Average

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 1/T for Average

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

5.3 DEVIATION FROM TEST STANDARD

No deviation

5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULT

PASS

Remark: All modes of GFSK, $\pi/4$ DQPSK, 8DPSK were tested, only the worst result of GFSK was reported as below.

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Detector Type	Result
GFSK	Low Channel: 2402MHz									
	H	2390.00	54.63	30.22	4.85	23.98	53.24	74.00	PK	PASS
	H	2390.00	45.16	30.22	4.85	23.98	43.77	54.00	AV	PASS
	H	2400.00	53.86	30.22	4.85	23.98	52.47	74.00	PK	PASS
	H	2400.00	44.42	30.22	4.85	23.98	43.03	54.00	AV	PASS
	V	2390.00	54.16	30.22	4.85	23.98	52.77	74.00	PK	PASS
	V	2390.00	45.39	30.22	4.85	23.98	44	54.00	AV	PASS
	V	2400.00	53.58	30.22	4.85	23.98	52.19	74.00	PK	PASS
	V	2400.00	44.27	30.22	4.85	23.98	42.88	54.00	AV	PASS
	High Channel: 2480MHz									
	H	2483.50	55.32	30.22	4.85	23.98	53.93	74.00	PK	PASS
	H	2483.50	45.16	30.22	4.85	23.98	43.77	54.00	AV	PASS
	H	2485.50	54.63	30.22	4.85	23.98	53.24	74.00	PK	PASS
	H	2485.50	44.28	30.22	4.85	23.98	42.89	54.00	AV	PASS
	V	2483.50	53.62	30.22	4.85	23.98	52.23	74.00	PK	PASS
	V	2483.50	44.29	30.22	4.85	23.98	42.9	54.00	AV	PASS
	V	2485.50	53.76	30.22	4.85	23.98	52.37	74.00	PK	PASS
	V	2485.50	44.19	30.22	4.85	23.98	42.8	54.00	AV	PASS
Remark:										
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit										

6. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

Test Requirement:	FCC Part15 C Section 15.247 (d) & RSS-247 5.5
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02 and RSS-Gen

6.1 Limit

Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

6.2 Test Setup



6.3 Test procedure

Using the following spectrum analyzer setting:

- A) Set the RBW = 100KHz.
- B) Set the VBW = 300KHz.
- C) Sweep time = auto couple.
- D) Detector function = peak.
- E) Trace mode = max hold.
- F) Allow trace to fully stabilize.

6.4 DEVIATION FROM STANDARD

No deviation.

6.5 Test Result


Non-Hopping

Modulation	Packet	Channel	OOB Emission Frequency (MHz)	OOB Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result
GFSK	DH1	0	2400.00	-52.717	-16.76	-36	PASS
			2299.83	-22.330	-16.76	-5.570	PASS
		39	36.24	-50.677	-17.69	-32.987	PASS
		78	2483.50	-55.744	-18.7	-37	PASS
			4960.45	-48.745	-18.7	-30.045	PASS
$\pi/4$ DQPSK	2-DH1	0	2400.00	-48.751	-16.76	-32	PASS
			36.24	-51.407	-16.76	-34.647	PASS
		39	36.24	-51.362	-17.75	-33.612	PASS
		78	2483.50	-56.379	-18.63	-38	PASS
			4959.83	-48.623	-18.63	-29.993	PASS
8DPSK	3-DH1	0	2400.00	-50.457	-16.71	-34	PASS
			36.24	-51.311	-16.71	-34.601	PASS
		39	24531.8	-51.784	-17.73	-34.054	PASS
		78	2483.50	-56.178	-18.66	-38	PASS
			4959.83	-45.924	-18.66	-27.264	PASS

Hopping

Hopping							
Modulation	Packet	Channel	OOB Emission Frequency (MHz)	OOB Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result
GFSK	DH1	Hopping	2396.95	-51.815	-16.89	-34.925	PASS
			2400.00	-55.069	-16.89	-38.179	PASS
			2483.50	-55.873	-18.8	-37.073	PASS
$\pi/4$ DQPSK	2-DH1		2397.98	-51.337	-16.91	-34.427	PASS
			2400.00	-51.484	-16.91	-34.574	PASS
			2483.50	-55.659	-18.81	-36.849	PASS
8DPSK	3-DH1		2400.00	-50.799	-16.9	-33.899	PASS
			2483.50	-54.632	-18.78	-35.852	PASS


Test Graphs




Out Of Band Emission
GFSK_DH1_Channel 0




Out Of Band Emission
 $\pi/4$ DQPSK_2-DH1_Channel 0




Spurious Emission
GFSK_DH1_Channel 0



Spurious Emission
 $\pi/4$ DQPSK_2-DH1_Channel 0




Out Of Band Emission
GFSK_DH1_Channel 39




Out Of Band Emission
 $\pi/4$ DQPSK_2-DH1_Channel 39




Spurious Emissions
GFSK_DH1_Channel 39




Spurious Emissions
 $\pi/4$ DQPSK_2-DH1_Channel 39




Out Of Band Emission
GFSK_DH1_Channel 78




Out Of Band Emission
 $\pi/4$ DQPSK_2-DH1_Channel 78




Spurious Emission
GFSK_DH1_Channel 78




Spurious Emission
 $\pi/4$ DQPSK_2-DH1_Channel 78




Out Of Band Emission
8DPSK_3-DH1_Channel 0




Spurious Emission
8DPSK_3-DH1_Channel 0




Out Of Band Emission
8DPSK_3-DH1_Channel 39




Spurious Emissions
8DPSK_3-DH1_Channel 39



Out Of Band Emission
8DPSK_3-DH1_Channel 78



Spurious Emission
8DPSK_3-DH1_Channel 78



Out Of Band Emission(Left)
GFSK_DH1_Channel Hopping



Out Of Band Emission(Left)
 $\pi/4$ DQPSK_2-DH1_Channel Hopping




Out Of Band Emission(Right)
GFSK_DH1_Channel Hopping



Out Of Band Emission(Right)
 $\pi/4$ DQPSK_2-DH1_Channel Hopping



Out Of Band Emission(Left)
8DPSK_3-DH1_Channel Hopping




Out Of Band Emission(Right)
8DPSK_3-DH1_Channel Hopping

7. 20DB BANDWIDTH & 99% OCB

Test Requirement:	FCC Part15 C Section 15.247 (a)(1) & RSS-247.5.1(2) RSS-Gen 6.7
Test Method:	ANSI C63.10:2013and RSS-Gen

7.1 Test Setup



7.2 Limit

N/A

7.3 Test procedure

1. Set RBW = 30 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


7.4 DEVIATION FROM STANDARD

No deviation.

7.5 Test Result

Mode	Test channel	20dB Emission Bandwidth (MHz)	99% Bandwidth (MHz)	Result
GFSK	Lowest	0.923	0.847	Pass
	Middle	0.922	0.845	
	Highest	0.916	0.846	
$\pi/4$ -DQPSK	Lowest	1.333	1.195	Pass
	Middle	1.336	1.190	
	Highest	1.320	1.187	
8-DPSK	Lowest	1.290	1.173	Pass
	Middle	1.294	1.173	
	Highest	1.264	1.169	

Test Graphs







$\pi/4$ DQPSK_2-DH1_Channel 39




$\pi/4$ DQPSK_2-DH1_Channel 78



8DPSK_3-DH1_Channel 0



8DPSK_3-DH1_Channel 39




8DPSK_3-DH1_Channel 78

Void

8. Maximum Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(1) & RSS-247.5.4(4)
Test Method:	ANSI C63.10:2013 and RSS-Gen
Limit:	20.97dBm(for GFSK), 20.97dBm(for EDR)

8.1 Block Diagram Of Test Setup



8.2 Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

8.3 Test procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3MHz. VBW = 3MHz. Sweep = auto; Detector Function = Peak.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.

8.4 DEVIATION FROM STANDARD


No deviation.


8.5 Test Result

Mode	Test Channel	Peak Output Power (dBm)	LIMIT (dBm)	Result
GFSK	CH00	3.276	20.96	Pass
	CH39	2.321	20.96	
	CH78	1.336	20.96	
$\pi/4$ -DQPSK	CH00	5.568	20.96	
	CH39	4.694	20.96	
	CH78	3.662	20.96	
8DPSK	CH00	3.277	20.96	
	CH39	2.298	20.96	
	CH78	1.331	20.96	

Mode	Test Channel	Conducted Output Power (dBm)	Antenna Gain	EIRP output power (dBm)	LIMIT (dBm)
GFSK	CH00	3.276	2.01	5.286	36.00
	CH39	2.321	2.01	4.331	36.00
	CH78	1.336	2.01	3.346	36.00
$\pi/4$ -DQPSK	CH00	5.568	2.01	7.578	36.00
	CH39	4.694	2.01	6.704	36.00
	CH78	3.662	2.01	5.672	36.00
8DPSK	CH00	3.277	2.01	5.287	36.00
	CH39	2.298	2.01	4.308	36.00
	CH78	1.331	2.01	3.341	36.00

Test plots







Peak Output Power
 $\pi/4$ DQPSK_Channel 39




Peak Output Power
 $\pi/4$ DQPSK_Channel 78



Peak Output Power
8DPSK_Channel 0



Peak Output Power
8DPSK_Channel 39



Peak Output Power
8DPSK_Channel 78

Void

9. HOPPING CHANNEL SEPARATION

Test Requirement:	FCC Part15 C Section 15.247 (a)(1) & RSS-247.5.1(4)
Test Method:	ANSI C63.10:2013 and RSS-Gen
Receiver setup:	RBW=100KHz, VBW=300KHz, detector=Peak
Limit:	GFSK: 20dB bandwidth $\pi/4$ -DQPSK & 8DPSK: 0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)

9.1 Test Setup



9.2 Test procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 100kHz. VBW = 300kHz , Span = 3.0MHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.


9.3 DEVIATION FROM STANDARD

No deviation.

9.4 Test Result

Modulation	Separation (MHz)	Limit(MHz)	Result
GFSK	1.000	0.922	PASS
$\pi/4$ -DQPSK	1.000	0.890	PASS
8-DPSK	1.000	0.863	PASS

Test Graphs



10. NUMBER OF HOPPING FREQUENCY

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)(iii) & RSS-247.5.1(4)
Test Method:	ANSI C63.10:2013 and RSS-Gen
Receiver setup:	RBW=100kHz, VBW=300kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak
Limit:	15 channels

10.1 Test Setup



10.2 Test procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 100kHz. VBW = 300kHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
4. Set the spectrum analyzer: Start Frequency = 2.4GHz, Stop Frequency = 2.4835GHz. Sweep=auto;

10.3 DEVIATION FROM STANDARD

No deviation.

10.4 Test Result


Test Graphs



11. DWELL TIME

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)(iii) & RSS-247.5.1(4)
Test Method:	ANSI C63.10:2013 and RSS-Gen
Receiver setup:	RBW=1MHz, VBW=3MHz, Span=0Hz, Detector=Peak
Limit:	0.4 Second

11.1 Test Setup



11.2 Test procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set spectrum analyzer span = 0Hz;
3. Set RBW = 1MHz and VBW = 3MHz. Sweep = as necessary to capture the entire dwell time per hopping channel. Set the EUT for DH5, DH3 and DH1 packet transmitting.
4. Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g.. data rate. modulation format. etc.). repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).


11.3 DEVIATION FROM STANDARD


No deviation.

11.4 Test Result


Modulation	Packet	Channel	Pulse Width (ms)	Number of Pulses in 31.6 seconds	Dwell Time (ms)	Limit (ms)	Result
GFSK	DH5	CH0 (2402MHz)	2.880	107	308.16	< 400	PASS
	DH5	CH39 (2441MHz)	2.896	106	306.98		PASS
	DH5	CH78 (2480MHz)	2.896	107	309.87		PASS
$\pi/4$ DQPSK	2-DH5	CH0 (2402MHz)	2.896	107	309.87		PASS
	2-DH5	CH39 (2441MHz)	2.896	107	309.87		PASS
	2-DH5	CH78 (2480MHz)	2.896	107	309.87		PASS
8DPSK	3-DH5	CH0 (2402MHz)	2.896	107	309.87		PASS
	3-DH5	CH39 (2441MHz)	2.896	107	309.87		PASS
	3-DH5	CH78 (2480MHz)	2.896	107	309.87		PASS

Test Graphs






Pulse Width
GFSK_DH5



Number of Pulses in 31.6 seconds
GFSK_DH5




Pulse Width
GFSK_DH5



Number of Pulses in 31.6 seconds
GFSK_DH5




Pulse Width
 $\pi/4$ DQPSK_2-DH5



Number of Pulses in 31.6 seconds
 $\pi/4$ DQPSK_2-DH5




Pulse Width
 $\pi/4$ DQPSK_2-DH5




Number of Pulses in 31.6 seconds
 $\pi/4$ DQPSK_2-DH5




Pulse Width
 $\pi/4$ DQPSK_2-DH5



Number of Pulses in 31.6 seconds
 $\pi/4$ DQPSK_2-DH5




Pulse Width
8DPSK_3-DH5



Number of Pulses in 31.6 seconds
8DPSK_3-DH5




Pulse Width
8DPSK_3-DH5



Number of Pulses in 31.6 seconds
8DPSK_3-DH5




Pulse Width
8DPSK_3-DH5



Number of Pulses in 31.6 seconds
8DPSK_3-DH5

12. Antenna Requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c) & RSS-Gen 6.8
<p>15.203 requirement:</p> <p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(c) (1)(i) requirement:</p> <p>(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.</p>	
EUT Antenna:	
The antenna is PCB antenna, the best case gain of the antennas is 2.01dBi.	
	

13. Test Setup Photo

Reference to the **appendix I** for details.

14. EUT Constructional Details

Reference to the appendix II for details.

***** END OF REPORT *****