



品名：WAG-B1.01.L.0806 工規

History List

[illegible]

WAG-B.01.L.0806 Specification

1. Explanation of part number :

WAG - B - 01 - L - 0806
(1) (2) (3) (4) (5)

(1) Product Type : Wireless Antenna

(2) Material : FPC

(3) Frequency : 699-960Mhz, 1710-2170, 2500-2690 Mhz

(4) Coaxial Cable Type : 00

(5) Suffix : 088

2. Electrical Specification :

2-1. Frequency Band:

Frequency Band	MHz
GSM	699-960Mhz, 1710-2170, 2500-2690 Mhz

UNLESS OTHER SPECIFIED TOLERANCES ON :

X=±2 X.X=±0.1 X.XX=±0.05

ANGLES=±

HOLEDIA=±

浙江海通通讯电子股份有限公司

SCALE :

UNIT : mm

DRAWN BY : 程国富

CHECKED BY : 于超群

DESIGNED BY : 于超群

APPROVED BY : 夏彪

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : WAG-F-LTE12-00-052 Specification

DOCUMENT
NO.

PAGE REV.
P0

2-2. Impedance

50 ohm nominal

2-3 VSWR:

Frequency Band	704	960	1710	2170	2500	2690
2-3-1. Typical Value:	-10.4	-5.6	-5	-7.8	-5.9	-16.8
2-3-2 Measuring Method	1. A 50Ω coaxial cable is connected to the fpcb antenna. Then this cable is connected to a network analyzer to measure the VSWR. 2. Keeping this jig away from metal at least 20 cm.					
2-3-3 Picture						


2-4. Measure and Chamber

2-4-1 Measure method

1. Using a low loss coaxial cable to link a standard handset jig
2. Fixed this handset jig on chamber's rotator plane

UNLESS OTHER SPECIFIED TOLERANCES ON : X=±2 X.X=±0.1 X.XX=±0.05 ANGLES=± HOLEDIA=±		浙江海通通讯电子股份有限公司	
SCALE :	UNIT : mm	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION	
DRAWN BY : 程国富	CHECKED BY : 于超群		
DESIGNED BY : 于超群	APPROVED BY : 夏彪		
TITLE : <u>WAG-F-LTE12-00-052</u> Specification		DOCUMENT NO.	PAGE REV. P0
PAGE 2 OF 5			

3. Linking jig into network analyzer port and using a probing horn antenna to collect data.
 4. Using another standard gain horn antenna to calibrated those data
- ### 2-4-2 Chamber definition



1. An anechoic chamber (8mx4mx3.5m) which satisfied far-field condition was applied to avoid multi-path effect
2. The quiet room region is 40cmx40cmx40cm at the center of rotator
3. The distance between DUT and standard antenna is 4.38 m
4. Probing antenna (9120D horn antenna) and standard gain horn antenna (BBHA9120 LPF 700MHz ~6GHz)

UNLESS OTHER SPECIFIED TOLERANCES ON : X=±2 X.X=±0.1 X.XX=±0.05 ANGLES=± HOLEDIA=±		浙江海通通讯电子股份有限公司	
SCALE :	UNIT : mm	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION	
DRAWN BY : 程国富	CHECKED BY : 于超群		
DESIGNED BY : 于超群	APPROVED BY : 夏彪		
TITLE : <u>WAG-F-LTE12-00-052</u> Specification		DOCUMENT NO.	PAGE REV. P0

2-4-3 Antenna OTA

B1	19.25	
	19.01	
	19.2	-94.1
B2	19.1	
	18.93	
	18.41	-94.64
B3	19.71	
	19.65	
	20.27	-94.81
B4	19.51	
	19.49	
	19.58	-94.41
B5	17.53	
	18.62	
	17.53	-92.49
B7	18.73	
	18.93	
	19.27	-95.83
B8	17.81	
	18.29	
	18	-93.97
B12	17.85	
	18.73	
	17.9	-95.39
B13	18.8	
	18.89	
	18.3	-93.99
B17	18.65	
	18.45	
	18.08	-93.33
B26	17.66	
	17.54	
	16.67	-94.75
B28	18.62	
	19.42	
	18.03	-92.99
B38 (10M)	18.7	
	19.83	
	19.49	-95.59

UNLESS OTHER SPECIFIED TOLERANCES ON :

X=±2 X.X=±0.1 X.XX=±0.05

ANGLES=±

HOLEDIA=±

浙江海通通讯电子股份有限公司

SCALE :

UNIT : mm

DRAWN BY : 程国富

CHECKED BY : 于超群

DESIGNED BY : 于超群

APPROVED BY : 夏彪

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : **WAG-F-LTE12-00-052** Specification

DOCUMENT
NO.

PAGE REV.
P0

B40 (10M)	18.47	
	18.97	
	18.16	-91.5

850	25.71	
	26.65	
	27.33	-102.14
900	25.79	
	27.14	
	27.6	-103.49
1800	25.86	
	26.29	
	26.73	-104.43
1900	26.85	
	27.33	
	26.8	-105.62
W1	19.56	
	19.06	
	19.47	-105.89
W2	20.49	
	20.47	
	19.75	-107.47
W4	20.09	
	20.07	
	20.17	-107.34
W5	17.48	
	17.98	
	17.15	-105.48
W8	17.15	
	17.88	
	17.82	-106.93

UNLESS OTHER SPECIFIED TOLERANCES ON : X=±2 X.X=±0.1 X.XX=±0.05 ANGLES=± HOLEDIA=±		浙江海通通讯电子股份有限公司	
SCALE :	UNIT : mm	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION	
DRAWN BY : 程国富	CHECKED BY : 于超群		
DESIGNED BY : 于超群	APPROVED BY : 夏彪		
TITLE : <u>WAG-F-LTE12-00-052</u> Specification		DOCUMENT NO.	PAGE REV. P0

2-4- Antenna Efficiency

Frequency	Efficiency	Efficiency . dB	Gain . dBi
870000000	22%	-6.55	-3.71
880000000	22%	-6.53	-3.48
890000000	21%	-6.71	-3.56
900000000	20%	-6.99	-3.83
910000000	18%	-7.37	-3.53
920000000	16%	-7.85	-3.68
930000000	15%	-8.36	-3.91
940000000	13%	-8.80	-4.05
950000000	13%	-9.02	-4.19
960000000	13%	-9.02	-4.41
1800000000	14%	-8.50	-4.51
1810000000	14%	-8.64	-3.97
1820000000	14%	-8.68	-4.09
1830000000	13%	-8.74	-4.29
1840000000	14%	-8.64	-5.11
1850000000	14%	-8.64	-5.07
1860000000	14%	-8.67	-4.65
1870000000	13%	-8.76	-4.38
1880000000	13%	-8.87	-4.58
1890000000	13%	-8.82	-4.40
1900000000	13%	-8.78	-4.42
1910000000	14%	-8.68	-4.34
1920000000	13%	-8.82	-4.41
1930000000	13%	-8.96	-4.80
1940000000	12%	-9.13	-4.79
1950000000	12%	-9.25	-4.84
1960000000	11%	-9.63	-4.97
1970000000	10%	-9.96	-5.18
1980000000	9%	-10.33	-5.61
1990000000	9%	-10.51	-6.07
2000000000	9%	-10.56	-6.59
2010000000	9%	-10.51	-6.75
2020000000	9%	-10.25	-6.86
2030000000	10%	-10.05	-6.60
2040000000	10%	-9.95	-6.55
2050000000	10%	-9.82	-6.30

UNLESS OTHER SPECIFIED TOLERANCES ON :

X=±2 X.X=±0.1 X.XX=±0.05

ANGLES=±

HOLEDIA=±

SCALE :

UNIT : mm

DRAWN BY : 程国富

CHECKED BY : 于超群

DESIGNED BY : 于超群

APPROVED BY : 夏彪

TITLE : **WAG-F-LTE12-00-052 Specification**

DOCUMENT
NO.

PAGE REV.
P0

浙江海通通讯电子股份有限公司

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

2060000000	11%	-9.57	-5.86
2070000000	12%	-9.33	-5.45
2080000000	12%	-9.27	-5.54
2090000000	12%	-9.27	-5.72
2100000000	12%	-9.22	-5.65
2110000000	12%	-9.05	-5.59
2120000000	13%	-8.91	-5.57
2130000000	13%	-8.81	-5.58
2140000000	13%	-8.85	-5.63
2150000000	13%	-9.02	-5.64
2160000000	12%	-9.18	-5.69
2170000000	12%	-9.31	-5.64
2180000000	12%	-9.27	-5.32
2190000000	12%	-9.25	-4.89
2200000000	12%	-9.19	-5.10
2300000000	16%	-7.85	-3.53
2310000000	17%	-7.71	-3.16
2320000000	17%	-7.63	-3.41
2330000000	18%	-7.56	-3.44
2340000000	18%	-7.47	-3.37
2350000000	18%	-7.34	-3.38
2360000000	20%	-7.01	-3.09
2370000000	21%	-6.70	-2.96
2380000000	22%	-6.59	-2.95
2390000000	22%	-6.52	-2.93
2400000000	23%	-6.46	-2.98
2500000000	28%	-5.58	-1.54
2510000000	28%	-5.48	-1.35
2520000000	30%	-5.21	-1.28
2530000000	31%	-5.09	-1.18
2540000000	31%	-5.05	-1.14
2550000000	31%	-5.04	-1.10
2560000000	31%	-5.11	-1.05
2570000000	31%	-5.02	-1.03
2580000000	32%	-4.96	-1.16
2590000000	32%	-4.96	-1.27
2600000000	33%	-4.86	-1.09
2610000000	33%	-4.75	-1.12
2620000000	35%	-4.61	-1.05
2630000000	35%	-4.55	-1.70
2640000000	35%	-4.57	-1.72
2650000000	35%	-4.58	-1.79
UNLESS OTHER SPECIFIED TOLERANCES ON : X=±2 X.X=±0.1 X.XX=±0.05 ANGLES=± HOLEDIA=±		浙江海通通讯电子股份有限公司	
SCALE :	UNIT : mm	THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION	
DRAWN BY : 程国富	CHECKED BY : 于超群		
DESIGNED BY : 于超群	APPROVED BY : 夏彪		
TITLE : <u>WAG-F-LTE12-00-052</u> Specification		DOCUMENT NO.	PAGE REV. P0
PAGE 7 OF 5			

2660000000	33%	-4.77	-1.25
2670000000	32%	-4.97	-1.51
2680000000	32%	-5.00	-1.30
2690000000	32%	-5.01	-1.33

Frequency	Efficiency	Efficiency . dB	Gain . dBi
780000000	22%	-6.49	-4.02
790000000	24%	-6.22	-3.54
800000000	24%	-6.17	-3.47
810000000	24%	-6.23	-3.38
820000000	22%	-6.59	-3.58
830000000	19%	-7.11	-3.63
840000000	17%	-7.75	-3.67
850000000	14%	-8.39	-4.88
860000000	12%	-9.13	-4.74
870000000	10%	-9.82	-4.70
880000000	10%	-10.20	-6.03
890000000	10%	-10.12	-6.40

Frequency	Efficiency	Efficiency . dB	Gain . dBi
750000000	20%	-6.92	-4.02
760000000	21%	-6.74	-5.72
770000000	22%	-6.61	-6.43
780000000	21%	-6.73	-4.02
790000000	20%	-6.89	-5.96
800000000	19%	-7.13	-4.05
810000000	21%	-6.84	-3.78

Frequency	Efficiency	Efficiency . dB	Gain . dBi
700000000	26%	-5.88	-4.25
710000000	25%	-6.08	-4.26
720000000	23%	-6.30	-4.31
730000000	22%	-6.61	-4.11
740000000	20%	-6.98	-4.12
750000000	18%	-7.47	-4.02
760000000	15%	-8.14	-5.72
770000000	13%	-8.90	-6.43
780000000	10%	-9.85	-4.02
790000000	9%	-10.68	-5.96

UNLESS OTHER SPECIFIED TOLERANCES ON :

X=±2 X.X=±0.1 X.XX=±0.05

ANGLES=±

HOLEDIA=±

浙江海通通讯电子股份有限公司

SCALE :

UNIT : mm

DRAWN BY : 程国富

CHECKED BY : 于超群

DESIGNED BY : 于超群

APPROVED BY : 夏彪

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : **WAG-F-LTE12-00-052 Specification**

DOCUMENT
NO.

PAGE REV.
P0

3. Antenna Dimensions (mm) :

