

# **FCC Test Report**

Report No.: AGC12845221008FE02

**FCC ID** : 2A9RD-SVBR01CP

**APPLICATION PURPOSE**: Original Equipment

**PRODUCT DESIGNATION**: Charging pile

**BRAND NAME** : Sveabot

**MODEL NAME** : SVBR01CP

**APPLICANT** : Sveabot Tek AB

**DATE OF ISSUE** : Jan. 12, 2023

**STANDARD(S)** : FCC Part 15.247

**REPORT VERSION**: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd



Page 2 of 44

## **REPORT REVISE RECORD**

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Jan. 12, 2023	Valid	Initial Release



Page 3 of 44

## **TABLE OF CONTENTS**

1. VERIFICATION OF COMPLIANCE	5
2. GENERAL INFORMATION	<del>(</del>
2.1. PRODUCT DESCRIPTION	6
2.2. TABLE OF CARRIER FREQUENCYS	ε
2.3. RELATED SUBMITTAL(S)/GRANT(S)	7
2.4. TEST METHODOLOGY	7
2.5. SPECIAL ACCESSORIES	7
2.6. EQUIPMENT MODIFICATIONS	7
2.7. ANTENNA REQUIREMENT	7
3. MEASUREMENT UNCERTAINTY	8
4. DESCRIPTION OF TEST MODES	9
5. SYSTEM TEST CONFIGURATION	10
5.1. CONFIGURATION OF TESTED SYSTEM	10
5.2. EQUIPMENT USED IN TESTED SYSTEM	10
5.3. SUMMARY OF TEST RESULTS	10
6. TEST FACILITY	11
7. PEAK OUTPUT POWER	12
7.1. MEASUREMENT PROCEDURE	12
7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	12
7.3. LIMITS AND MEASUREMENT RESULT	13
8. BANDWIDTH	15
8.1. MEASUREMENT PROCEDURE	15
8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	15
8.3. LIMITS AND MEASUREMENT RESULTS	15
9. CONDUCTED SPURIOUS EMISSION	19
9.1. MEASUREMENT PROCEDURE	19
9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
9.3. MEASUREMENT EQUIPMENT USED	
9.4. LIMITS AND MEASUREMENT RESULT	19
10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY	



Page 4 of 44

10.1. MEASUREMENT PROCEDURE	26
10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
10.3. MEASUREMENT EQUIPMENT USED	
10.4. LIMITS AND MEASUREMENT RESULT	26
11. RADIATED EMISSION	28
11.1. MEASUREMENT PROCEDURE	28
11.2. TEST SETUP	29
11.3. LIMITS AND MEASUREMENT RESULT	30
11.4. TEST RESULT	30
12. LINE CONDUCTED EMISSION TEST	40
12.1. LIMITS OF LINE CONDUCTED EMISSION TEST	40
12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	40
12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	41
12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	41
12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	41
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	44
APPENDIX B: PHOTOGRAPHS OF EUT	44



Page 5 of 44

## 1. VERIFICATION OF COMPLIANCE

Applicant	Sveabot Tek AB		
Address	Hogmossevagen 11, SE-641 39, Katrineholm, Sweden		
Manufacturer	Sveabot Tek AB		
Address	Hogmossevagen 11, SE-641 39, Katrineholm, Sweden		
Factory	FJ Dynamics Technology (Fujian) Co., Ltd.		
Address	Unit 3, Yimei Zhineng Industrial Park, No. 30 Zhihui Avenue, Nanyu Town, Gaoxin District, Fuzhou City, Fujian Province, China		
Product Designation	Charging pile		
Brand Name	Sveabot		
Test Model	SVBR01CP		
Date of receipt of test item	Nov. 21, 2022		
Date of test	Nov. 23, 2022 to Jan. 12, 2023		
Deviation	No any deviation from the test method		
Condition of Test Sample	Normal		
Test Result	Pass		
Report Template	AGCRT-US-BLE/RF		

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC part 15.247.

Alan Duan
(Project Engineer)

Reviewed By

Calvin Liu
(Reviewer)

Approved By

Max Zhang
(Authorized Officer)

Jan. 12, 2023



Page 6 of 44

## 2. GENERAL INFORMATION

## 2.1. PRODUCT DESCRIPTION

The EUT is designed as a "Charging pile". It is designed by way of utilizing the GFSK technology to achieve the system operation.

A major technical description of EUT is described as following

Operation Frequency	2.402 GHz to 2.480GHz		
RF Output Power	1.534dBm (Max)		
Bluetooth Version	V4.2		
Modulation	BR □GFSK, EDR □π /4-DQPSK, □8DPSK BLE □GFSK 1Mbps □GFSK 2Mbps		
Number of channels	40 Channels		
Antenna Designation	FPC Antenna (Comply with requirements of the FCC part 15.203)		
Antenna Gain	2.69dBi		
Hardware Version	V1.0		
Software Version	V1.0		
Power Supply	DC 58.8V by adapter		

## 2.2. TABLE OF CARRIER FREQUENCYS

Frequency Band Channel Number		Frequency		
	0	2402 MHz		
	1	2404 MHz		
2400~2483.5MHz	:	:		
	38	2478 MHz		
	39	2480 MHz		



Page 7 of 44

## 2.3. RELATED SUBMITTAL(S)/GRANT(S)

This submittal(s) (test report) is intended for **FCC ID: 2A9RD-SVBR01CP** filing to comply with the FCC Part 15.247 requirements.

#### 2.4. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013). Radiated testing was performed at an antenna to EUT distance 3 meters.

#### 2.5. SPECIAL ACCESSORIES

Refer to section 5.2.

## 2.6. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

## 2.7. ANTENNA REQUIREMENT

This intentional radiator is designed with a permanently attached antenna of an antenna to ensure that no antenna other than that furnished by the responsible party shall be used with the device. For more information of the antenna, please refer to the APPENDIX B: PHOTOGRAPHS OF EUT.



Page 8 of 44

## 3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty		
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 3.1 \text{ Db}$		
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 4.0 \text{ Db}$		
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.8 \text{ Db}$		
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ Db}$		
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ Db}$		
Uncertainty of spurious emissions, conducted	U <sub>c</sub> = ±2.7 %		
Uncertainty of Occupied Channel Bandwidth	U <sub>c</sub> = ±2 %		




Page 9 of 44

## 4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION	
1	Low channel TX	
2	Middle channel TX	
3	High channel TX	

#### Note:

- 1. Only the result of the worst case was recorded in the report, if no other cases.
- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 3. For Conducted Test method, a temporary antenna connector is provided by the manufacture.






Page 10 of 44


## 5. SYSTEM TEST CONFIGURATION

## **5.1. CONFIGURATION OF TESTED SYSTEM**

Radiated Emission Configure:



Conducted Emission Configure:



## **5.2. EQUIPMENT USED IN TESTED SYSTEM**

Item	Equipment	Model No.	ID or Specification	Remark
1	Charging pile	SVBR01CP	2A9RD-SVBR01CP	EUT
2	Xiaomi router	R4A	N/A	AE
3	Bluetooth speaker	SRS-XB01	N/A	AE
4	Adapter	Adapter FY58809500 Input: 100-240V, 50/60H Output: DC 58.8V, 9		AE

## 5.3. SUMMARY OF TEST RESULTS

FCC RULES	C RULES DESCRIPTION OF TEST	
15.247 (b)(3)	15.247 (b)(3) Peak Output Power	
15.247 (a)(2)	15.247 (a)(2) 6 dB Bandwidth	
15.247 (d)	15.247 (d) Conducted Spurious Emission	
15.247 (e)	15.247 (e) Maximum Conducted Output Power Density	
15.209	15.209 Radiated Emission	
15.207 Conducted Emission		Compliant



Page 11 of 44

## **6. TEST FACILITY**

Test Site Attestation of Global Compliance (Shenzhen) Co., Ltd		
Location	1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China	
Designation Number	CN1259	
FCC Test Firm Registration Number	975832	
A2LA Cert. No.	5054.02	
Description	Attestation of Global Compliance (Shenzhen) Co., Ltd is accredited by A2LA	

## **TEST EQUIPMENT OF CONDUCTED EMISSION TEST**

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due		
TEST RECEIVER	R&S	ESPI	101206	Mar. 28, 2022	Mar. 27, 2023		
LISN	R&S	ESH2-Z5	100086	Jun. 08, 2022	Jun. 07, 2023		
Test software	R&S	ES-K1	Ver.V1.71	N/A	N/A		

## TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Mar. 28, 2022	Mar. 27, 2023
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Aug. 04, 2022	Aug. 03, 2023
2.4GHz Filter	EM Electronics	2400-2500MHz	N/A	N/A	N/A
Attenuator	ZHINAN	E-002	N/A	Aug. 04, 2022	Aug. 03, 2024
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Oct. 31, 2021	Oct. 30, 2023
Active loop antenna (9K-30MHz)	ZHINAN	ZN30900C	18051	Mar. 12, 2022	Mar. 21, 2024
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	Apr. 23, 2021	Apr. 22, 2023
Broadband Preamplifier	ETS LINDGREN	3117PA	00225134	Aug. 04, 2022	Aug. 03, 2024
ANTENNA	SCHWARZBECK	VULB9168	494	Jan. 08, 2021	Jan. 07, 2023
ANTENNA	SCHWARZBECK	VULB9168	494	Jan. 05, 2023	Jan. 04, 2025
Test software	Tonscend	JS32-RE	Ver.2.5	N/A	N/A



Page 12 of 44

## 7. PEAK OUTPUT POWER


## 7.1. MEASUREMENT PROCEDURE

For peak power test:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. RBW ≥ DTS bandwidth
- 3. VBW≥3\*RBW.
- 4. SPAN≥VBW.
- 5. Sweep: Auto.
- 6. Detector function: Peak.
- 7. Trace: Max hold.

Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.

## 7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) PEAK POWER TEST SETUP






Page 13 of 44

## 7.3. LIMITS AND MEASUREMENT RESULT

1101 2111111 0 71112 1112/1001(211112111 1/2002)								
	Test Data of Conducted Output Power							
Test Mode	Test Channel (MHz)	Peak Power (dBm)	Limits (dBm)	Pass or Fail				
	2402	1.534	≤30	Pass				
GFSK 1M	2440	-0.421	≤30	Pass				
	2480	1.023	≤30	Pass				

**Test Graphs of Conducted Output Power** Q R RF 50 Ω AL CONTROL OF THE PNO: Fast FGain:Low Frequency Avg Type: Log-Pwr Avg|Hold: 100/100 Trig: Free Run #Atten: 40 dB **Auto Tune** Mkr1 2.401 987 GHz 1.534 dBm 10 dB/div Ref 20.00 dBm Center Freq 2.402000000 GHz Start Freq 2.399500000 GHz Stop Freq 2.404500000 GHz CF Step 500.000 kHz Freq Offset 0 Hz Scale Type Center 2.402000 GHz #Res BW 1.5 MHz Span 5.000 MHz Sweep 1.066 ms (1000 pts) <u>Lin</u> **#VBW 5.0 MHz** 

Test\_Graph\_LE1M\_ANT1\_2402\_1Mbps\_Peak Power











Page 15 of 44

## 8. BANDWIDTH

#### 8.1. MEASUREMENT PROCEDURE

#### 6dB bandwidth:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 kHz, VBW ≥ 3×RBW.
- 4. Set SPA Trace 1 Max hold, then View.

### Occupied bandwidth:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hoping channel
  The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video
  bandwidth (VBW) shall be approximately three times RBW; Sweep = auto; Detector function = peak
- 4. Set SPA Trace 1 Max hold, then View.


**Note:** The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

## 8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 7.2.


#### 8.3. LIMITS AND MEASUREMENT RESULTS

Test Data of Occupied Bandwidth and DTS Bandwidth								
Test Mode	Test Channel (MHz)	99% Occupied Bandwidth (MHz)	-6dB Bandwidth (MHz)	Limits (MHz)	Pass or Fail			
	2402	1.015	0.642	≥0.5	Pass			
GFSK 1M	2440	1.016	0.641	≥0.5	Pass			
	2480	1.016	0.641	≥0.5	Pass			







**Test Graphs of Occupied Bandwidth** 02:12:14 PM Jan 03, 2023 Radio Std: None SENSE:INT Center Freq: 2.402000000 GHz
Trig: Free Run Avg|Hol
#Atten: 30 dB Frequency Center Freq 2.402000000 GHz Avg|Hold: 10/10 Radio Device: BTS Ref 30.00 dBm Center Freq 2.402000000 GHz Span 3 MHz Sweep 4.133 ms Center 2.402 GHz #Res BW 30 kHz **CF Step** #VBW 100 kHz 300,000 kHz Man Auto 7.93 dBm **Total Power Occupied Bandwidth** 1.0146 MHz Freq Offset 0 Hz **Transmit Freq Error** -5.729 kHz % of OBW Power 99.00 % x dB Bandwidth 1.261 MHz x dB -26.00 dB Test\_Graph\_LE1M\_ANT1\_2402\_1Mbps\_OBW 02:16:32 PM Jan 03, 2023 Radio Std: None Center Freq: 2.440000000 GHz
Trig: Free Run Avg|Hol Frequency Center Freq 2.440000000 GHz Avg|Hold:>10/10 Radio Device: BTS Ref 30.00 dBm Center Freq 2.440000000 GHz Center 2.44 GHz #Res BW 30 kHz Span 3 MHz Sweep 4.133 ms CF Step 300.000 kHz **#VBW 100 kHz** <u>Auto</u> **Total Power** 5.91 dBm **Occupied Bandwidth** 1.0158 MHz Freq Offset 0 Hz % of OBW Power **Transmit Freq Error** -7.548 kHz 99.00 % x dB Bandwidth -26.00 dB 1.260 MHz x dB Test\_Graph\_LE1M\_ANT1\_2440\_1Mbps\_OBW











Freq Offset





Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test\_Graph\_LE1M\_ANT1\_2480\_1Mbps\_DTSBW

% of OBW Power

x dB

99.00 %

-6.00 dB

Transmit Freg Error

x dB Bandwidth

1.0254 MHz

-11.041 kHz

640.9 kHz



Page 19 of 44

## 9. CONDUCTED SPURIOUS EMISSION

## 9.1. MEASUREMENT PROCEDURE

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

## 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)


The same as described in section 7.2.

#### 9.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6.

#### 9.4. LIMITS AND MEASUREMENT RESULT

LIMITS AND MEASUREMENT RESULT					
Applicable Limite	Measurement Result				
Applicable Limits	Test Data	Criteria			
In any 100 kHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power.	At least -20dBc than the reference level	PASS			






Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Test\_Graph\_LE1M\_ANT1\_2402\_1Mbps\_Lower Band Emissions

























02:19:08 PM Jan 03, 2023


TRACE 1 2 3 4 5 6


TYPE MWWWWW Avg Type: Log-Pwr Avg|Hold: 10/10 Frequency Center Freq 2.480000000 GHz PNO: Wide ↔→ IFGain:Low Trig: Free Run #Atten: 30 dB **Auto Tune** Mkr1 2.479 980 3 GHz 0.638 dBm 10 dB/div Ref 20.00 dBm Center Freq 2.480000000 GHz Start Freq 2.478500000 GHz Stop Freq 2.481500000 GHz CF Step 300.000 kHz <sub>ት</sub>ሌሎስ Freq Offset 0 Hz **Scale Type** Center 2.480000 GHz #Res BW 100 kHz Span 3.000 MHz Sweep 2.000 ms (30000 pts) <u>Lin</u> #VBW 300 kHz











0 Hz

<u>Lin</u>

**Scale Type** 

Log



Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands Frequency Avg Type: Log-Pwi Avg|Hold: 100/100 Center Freq 2.398500000 GHz Trig: Free Run #Atten: 30 dB TYPE **Auto Tune** Mkr2 2.400 000 0 GHz -51.322 dBm Ref 20.00 dBm Center Freq 2.398500000 GHz Start Freq 2.390000000 GHz Stop Freq 2.407000000 GHz Start 2.390000 GHz #Res BW 100 kHz Stop 2.407000 GHz 2.000 ms (30000 pts) CF Step 1.700000 MHz **#VBW** 300 kHz Auto Man 1.000 dBm -51.322 dBm Freq Offset 0 Hz Scale Type Log <u>Lin</u> Test\_Graph\_LE1M\_ANT1\_2402\_1Mbps\_Lower Band Edge Emissions Avg Type: Log-Pwr Avg|Hold: 100/100 Frequency Center Freq 2.487500000 GHz Trig: Free Run #Atten: 30 dB PNO: Fast ↔ IFGain:Low **Auto Tune** Mkr2 2.483 500 0 GHz -58.052 dBm Ref 20.00 dBm Center Frea 2.487500000 GHz Start Freq 2.475000000 GHz <u>2</u> Stop Freq 2 500000000 GHz Start 2.47500 GHz #Res BW 100 kHz Stop 2.50000 GHz Sweep 4.000 ms (30000 pts) **CF Step** #VBW 300 kHz 2.500000 MHz <u>Auto</u> 0.607 dBm -58.052 dBm Freq Offset

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Test\_Graph\_LE1M\_ANT1\_2480\_1Mbps\_Higher Band Edge Emissions



Page 26 of 44

## 10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY

#### 10.1. MEASUREMENT PROCEDURE

- (1). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- (2). Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- (3). Set the SPA Trace 1 Max hold, then View.

Note: The method of PKPSD in the KDB 558074 item 8.4 was used in this testing.

## 10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

Refer to Section 7.2.

#### 10.3. MEASUREMENT EQUIPMENT USED


Refer to Section 6.

#### 10.4. LIMITS AND MEASUREMENT RESULT

Test Data of Conducted Output Power Spectral Density							
Test Mode	Test Channel (MHz)	Power density (dBm/3kHz)	Limit (dBm/3kHz)	Pass or Fail			
	2402	-14.062	<b>≤8</b>	Pass			
GFSK 1M	2440	-16.167	≤8	Pass			
	2480	-14.700	<b>≤8</b>	Pass			


Test Graphs of Conducted Output Power Spectral Density













Page 28 of 44

## 11. RADIATED EMISSION


#### 11.1. MEASUREMENT PROCEDURE

- The EUT was placed on the top of the turntable 0.1 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.




## 11.2. TEST SETUP


## Radiated Emission Test-Setup Frequency Below 30MHz



## RADIATED EMISSION TEST SETUP 30MHz-1000MHz



## RADIATED EMISSION TEST SETUP ABOVE 1000MHz





Page 30 of 44

## 11.3. LIMITS AND MEASUREMENT RESULT

15.209 Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

## 11.4. TEST RESULT

## Radiated emission below 30MHz


The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.



Page 31 of 44

## Radiated emission from 30MHz to 1000MHz

EUT	Charging pile	Model Name	SVBR01CP
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal




NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	55.22	22.35	12.03	40.00	17.65	100	10	Horizontal
2	99.84	27.73	21.38	43.50	15.77	100	290	Horizontal
3	320.03	26.68	21.33	46.00	19.32	100	30	Horizontal
4	466.5	30.55	26.35	46.00	15.45	100	190	Horizontal
5	621.7	31.97	27.79	46.00	14.03	100	270	Horizontal
6	880.69	36.58	33.22	46.00	9.42	100	110	Horizontal

**RESULT: PASS** 



Page 32 of 44

EUT	Charging pile	Model Name	SVBR01CP
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical



NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	55.22	28.47	14.15	40.00	11.53	100	230	Vertical
2	116.33	26.00	16.63	43.50	17.50	100	170	Vertical
3	138.64	26.34	19.71	43.50	17.16	100	210	Vertical
4	699.3	33.27	29.02	46.00	12.73	100	240	Vertical
5	774.96	34.86	30.83	46.00	11.14	100	120	Vertical
6	849.65	36.92	32.27	46.00	9.08	100	270	Vertical

## RESULT: PASS Note:

- 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.
- 2. All test modes had been tested. The mode 1 is the worst case and recorded in the report.



Page 33 of 44

## Radiated emission above 1GHz

EUT	Charging pile	Model Name	SVBR01CP
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4804.000	45.26	0.08	45.34	74	-28.66	peak
4804.000	36.17	0.08	36.25	54	-17.75	AVG
7206.000	41.05	2.21	43.26	74	-30.74	peak
7206.000	30.59	2.21	32.8	54	-21.2	AVG

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

EUT	Charging pile	Model Name	SVBR01CP
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4804.000	45.36	0.08	45.44	74	-28.56	peak
4804.000	35.18	0.08	35.26	54	-18.74	AVG
7206.000	40.15	2.21	42.36	74	-31.64	peak
7206.000	31.48	2.21	33.69	54	-20.31	AVG
_						

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.



Page 34 of 44

EUT	Charging pile	Model Name	SVBR01CP
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4880.000	46.34	0.14	46.48	74	-27.52	peak
4880.000	47.51	0.14	47.65	54	-6.35	AVG
7320.000	41.05	2.36	43.41	74	-30.59	peak
7320.000	32.49	2.36	34.85	54	-19.15	AVG
Remark:						

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

EUT	Charging pile	Model Name	SVBR01CP
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	- Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4880.000	46.28	0.14	46.42	74	-27.58	peak
4880.000	37.54	0.14	37.68	54	-16.32	AVG
7320.000	41.05	2.36	43.41	74	-30.59	peak
7320.000	32.49	2.36	34.85	54	-19.15	AVG

## Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.



Page 35 of 44

EUT	Charging pile	Model Name	SVBR01CP
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4960.000	46.28	0.22	46.5	74	-27.5	peak
4960.000	36.57	0.22	36.79	54	-17.21	AVG
7440.000	41.05	2.64	43.69	74	-30.31	peak
7440.000	30.55	2.64	33.19	54	-20.81	AVG
Remark:	·			·	·	

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

EUT	Charging pile	Model Name	SVBR01CP
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4960.000	44.59	0.22	44.81	74	-29.19	peak
4960.000	35.87	0.22	36.09	54	-17.91	AVG
7440.000	39.57	2.64	42.21	74	-31.79	peak
7440.000	28.64	2.64	31.28	54	-22.72	AVG


Factor = Antenna Factor + Cable Loss - Pre-amplifier.

## **RESULT: PASS**

The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.

Factor = Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.







Test result for band edge emission at restricted bands


EUT	Charging pile	Model Name	SVBR01CP
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal

Test Graph for Peak Measurement






**RESULT: PASS** 







**EUT** Charging pile **Model Name** SVBR01CP 25° C **Temperature Relative Humidity** 55.4% 960hPa **Test Voltage** Normal Voltage **Pressure Test Mode** Mode 1 **Antenna** Vertical

Test Graph for Peak Measurement





**RESULT: PASS** 







**EUT** Charging pile **Model Name** SVBR01CP 25° C **Temperature Relative Humidity** 55.4% 960hPa **Test Voltage** Normal Voltage **Pressure Test Mode** Mode 3 **Antenna** Horizontal

Test Graph for Peak Measurement






**RESULT: PASS** 






**EUT** Charging pile **Model Name** SVBR01CP 25° C **Temperature Relative Humidity** 55.4% 960hPa Normal Voltage **Pressure Test Voltage Test Mode** Mode 3 **Antenna** Vertical

Test Graph for Peak Measurement





## **RESULT: PASS**

Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer.



Page 40 of 44

## 12. LINE CONDUCTED EMISSION TEST


## 12.1. LIMITS OF LINE CONDUCTED EMISSION TEST

F	Maximum RF Line Voltage				
Frequency	Q.P.( dBuV)	Average( dBuV)			
150kHz~500kHz	66-56	56-46			
500kHz~5MHz	56	46			
5MHz~30MHz	60	50			

#### Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

## 12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST





Page 41 of 44

#### 12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.1 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 58.8V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.


### 12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

#### 12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST



## Line Conducted Emission Test Line 1-L



## MEASUREMENT RESULT: "agc fin"

2022/11/25 14:	42					
Frequency MHz		Transd dB		_	Detector	Line
0.326000	41.20	5.9	60	18.4	QP	L1
0 202000	24 10	E 7	50	2/1 1	OD	T 1

0.382000 QP 0.762000 31.50 5.4 56 24.5 QP ь1 0.818000 32.10 5.4 56 23.9 QP ь1 1.306000 27.80 5.8 56 28.2 QP ь1 6.0 1.418000 27.60 56 28.4 QP ь1


## MEASUREMENT RESULT: "agc\_fin2"

2022/11/25 14:42

2022/11/20 11:12							
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	
0.274000	27.80	6.1	51	23.2	AV	L1	
0.326000	31.90	5.9	50	17.7	AV	L1	
0.382000	27.20	5.7	48	21.0	AV	L1	
0.762000	22.50	5.4	46	23.5	AV	L1	
0.818000	23.10	5.4	46	22.9	AV	L1	
0.870000	22.40	5.4	46	23.6	AV	L1	



## Line Conducted Emission Test Line 2-N



## MEASUREMENT RESULT: "agc\_fin"

2022/11/25 14:38							
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	
0.326000	40.10	5.9	60	19.5	QP	N	
0.550000	25.50	5.4	56	30.5	QP	N	
0.766000	28.30	5.4	56	27.7	QP	N	
0.814000	29.40	5.4	56	26.6	QP	N	
1.306000	28.00	5.8	56	28.0	QP	N	
1.414000	27.50	6.0	56	28.5	QP	N	

## MEASUREMENT RESULT: "agc fin2"

2/11/25 14: Frequency MHz		Transd dB	Limit dBµV	Margin dB	Detector	Line
0.214000 0.270000 0.326000	27.80 28.30 30.90	6.5 6.2 5.9	53 51 50	25.2 22.8 18.7		N N N
0.378000 1.418000 1.906000	24.40 20.00 20.10	5.8 6.0 6.4	48 46 46	23.9 26.0	AV AV AV	N N N

## **RESULT: PASS**

Note: All the test modes had been tested, the mode 1 was the worst case. Only the data of the worst case would be record in this test report.



Page 44 of 44

## APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Refer to the Report No.: AGC12845221008AP02

APPENDIX B: PHOTOGRAPHS OF EUT

Refer to the Report No.: AGC12845221008AP03

----END OF REPORT----



## Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7.Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.