

The image displays a series of 20 pages from the Lockitron LK2000 manual, arranged in two rows of ten. The top row includes the 'QUICK START GUIDE', 'Overview of Product Features & Layout', 'Interior Assembly', 'Parts List', 'Installation Preparation', 'Preparation for Installation', 'Installing the Lock', 'Installing the Handle', 'Installing the Lock Mechanism', and 'Installing the Door Handle'. The bottom row continues with 'Installing the Door Handle', 'Installing the Door Handle', 'Installing the Door Handle', 'Installing the Door Handle', 'Installing the Door Handle', 'Installing the Door Handle', 'Installing the Door Handle', 'Installing the Door Handle', 'Installing the Door Handle', and 'Installing the Door Handle'. Each page contains detailed diagrams, text instructions, and numbered steps for the installation process.

材质: 105g无光铜										SCALE 1:1	LOCKIN 鹿客			
表面处理: 无										SHEET 1/1				
SELECT			V							UNIT mm	物料名称: 说明书			
Dim \ TOL	A	B	C	EPS	EPE	EPP	BAG	CTN	LABEL					
0-6	0.05	0.05	0.10						0.20		产品名称	料号	设计	核准
6-30	0.10	0.15	0.20	0.50	0.50	0.50	3.00		0.20					
30-120	0.15	0.20	0.30	0.50	0.50	0.50	5.00	2.00	0.25					
120-300	0.20	0.30	0.40	1.00	1.00	1.00	10.00	3.00	0.30					
300-450	0.25	0.40	0.50	2.00	2.00	2.00	15.00	5.00	0.50					
450-600	0.30	0.50	0.60	3.00	3.00	3.00	20.00	5.00	0.80		411	0524157001	Tamia	龙宏伟
DRAFT TOLERANCE			+ 0.20		CRITICAL DIM. MARK				*					