

FCC SAR TEST REPORT

FCC ID : UZ7MC9401
Equipment : Mobile Computer
Brand Name : ZEBRA
Model Name : MC9401
Applicant : Zebra Technologies Corporation
1 Zebra Plaza, Holtsville, NY 11742
Manufacturer : Zebra Technologies Corporation
1 Zebra Plaza, Holtsville, NY 11742
Standard : FCC 47 CFR Part 2 (2.1093)

The product was received on Jul. 10, 2023 and testing was started from Jul. 28, 2023 and completed on Aug. 11, 2023. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample provide by manufacturer and the test data has been evaluated in accordance with the test procedures given in 47 CFR Part 2.1093 and FCC KDB and has been pass the FCC requirement.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Laboratory, the test report shall not be reproduced except in full.



Approved by: Cona Huang / Deputy Manager



Sporton International Inc. EMC & Wireless Communications Laboratory

No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan



Table of Contents

1. Statement of Compliance	4
2. Guidance Applied.....	4
3. Equipment Under Test (EUT) Information.....	5
3.1 General Information	5
4. RF Exposure Limits.....	6
4.1 Uncontrolled Environment.....	6
4.2 Controlled Environment.....	6
5. Specific Absorption Rate (SAR).....	7
5.1 Introduction	7
5.2 SAR Definition.....	7
6. System Description and Setup	8
6.1 Test Site Location.....	8
6.2 E-Field Probe	9
6.3 Data Acquisition Electronics (DAE)	9
6.4 Phantom.....	10
6.5 Device Holder.....	11
7. Measurement Procedures	12
7.1 Spatial Peak SAR Evaluation.....	12
7.2 Power Reference Measurement.....	13
7.3 Area Scan	13
7.4 Zoom Scan.....	14
7.5 Volume Scan Procedures.....	14
7.6 Power Drift Monitoring.....	14
8. Test Equipment List.....	15
9. System Verification	16
9.1 Tissue Verification	16
9.2 System Performance Check Results.....	17
10. RF Exposure Positions	18
10.1 Body Worn Accessory	18
10.2 Extremity Exposure	18
10.3 Wireless Router.....	19
11. WiFi/Bluetooth Output Power (Unit: dBm)	20
12. Antenna Location	28
13. SAR Test Results	29
13.1 Hotspot SAR	30
13.2 Body Worn Accessory SAR.....	32
13.3 Extremity SAR.....	34
13.4 Repeated SAR Measurement	36
14. Simultaneous Transmission Analysis	37
14.1 Hotspot Exposure Conditions.....	38
14.2 Body-Worn Accessory Exposure Conditions	38
14.3 Extremity Exposure Conditions	38
15. Uncertainty Assessment	39
16. References.....	39
Appendix A. Plots of System Performance Check	
Appendix B. Plots of High SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. Test Setup Photos	



History of this test report

Report No.	Version	Description	Issued Date
FA362117	01	Initial issue of report	Aug. 23, 2023

1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) for Zebra Technologies Corporation, Mobile Computer, MC9401, are as follows.

Equipment Class	Frequency Band	Highest SAR Summary			Highest Simultaneous Transmission 1g SAR (W/kg)	Highest Simultaneous Transmission 10g SAR (W/kg)
		Body-worn (Separation 0mm)	Hotspot (Separation 10mm)	Extremity (Separation 0mm)		
		1g SAR (W/kg)		10g SAR (W/kg)		
DXX	NFC			< 0.01		0.94
DTS	2.4GHz WLAN	0.48	0.86	0.46	1.24	0.94
NII	5GHz WLAN	1.01		0.45	1.24	0.94
DSS	Bluetooth	0.01	0.03	0.03	1.24	0.94
Date of Testing:		2023/7/28 ~ 2023/8/11				

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC test. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg for Partial-Body 1g SAR, 4.0 W/kg for Extremity 10g SAR) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications

Reviewed by: Jason Wang
Report Producer: Daisy Peng

2. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards, the below KDB standard may not including in the TAF code without accreditation.

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 941225 D06 Hotspot Mode SAR v02r01

3. Equipment Under Test (EUT) Information

3.1 General Information

Product Feature & Specification	
Equipment Name	Mobile Computer
Brand Name	ZEBRA
Model Name	MC9401
FCC ID	UZ7MC9401
Wireless Technology and Frequency Range	WLAN 2.4 GHz Band: 2400 MHz ~ 2483.5 MHz WLAN 5.2 GHz Band: 5150 MHz ~ 5250 MHz WLAN 5.3 GHz Band: 5250 MHz ~ 5350 MHz WLAN 5.6 GHz Band: 5470 MHz ~ 5725 MHz WLAN 5.8 GHz Band: 5725 MHz ~ 5850 MHz Bluetooth: 2400 MHz ~ 2483.5 MHz NFC : 13.56 MHz
Mode	WLAN: 802.11a/b/g/n/ac/ax HT20/HT40/VHT20/VHT40/VHT80/VHT160/HE20/HE40/HE80/HE160 Bluetooth BR/EDR/LE NFC: ASK
HW Version	EV
SW Version	13-05-28.00-TG-U00-PRD-NEM-04
FW Version	FUSION_QA_6_1.0.0.001_T
MFD	08JUN23
EUT Stage	Identical Prototype
Remark:	
1. The device 2.4GHz WLAN/BT support hotspot operation via 5GHz receive signal.	

Accessories Information				
Adapter USB Wall Charger	Brand Name	Zebra	Model Number	PWR-WUA5V12W0US
Battery Standard Battery (7000mAh)	Brand Name	Zebra	Model Number	BT-000370
Earphone USB-C Audio Headset	Brand Name	Zebra	Model Number	HDST-USBC-PTT1-01
USB Cable (Type C to Type A)	Brand Name	Zebra	Model Number	CBL-TC2X-USBC-01
Holster	Brand Name	Zebra	Model Number	SG-MC9X-SHLSTG-01
USB Cable (CUP)	Brand Name	Zebra	Model Number	CBL-MC93-USBCHG-01

4. RF Exposure Limits

4.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

4.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

5. Specific Absorption Rate (SAR)

5.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

5.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

6. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- The DASY system in SAR Configuration is shown above
- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running windows software and the DASY software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

6.1 Test Site Location

The SAR measurement facilities used to collect data are within both Sporton Lab list below test site location are accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190 and 3786) and the FCC designation No. TW1190 and TW3786 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC test.

Test Site	EMC & Wireless Communications Laboratory		Wensan Laboratory		
Test Site Location	TW1190 No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan		TW3786 No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan		
Test Site No.	SAR01-HY	SAR03-HY	SAR08-HY	SAR09-HY	SAR15-HY
	SAR04-HY	SAR05-HY	SAR11-HY	SAR12-HY	SAR16-HY
	SAR06-HY	SAR10-HY	SAR13-HY	SAR14-HY	SAR17-HY

6.2 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

<ES3DV3 Probe>

Construction	Symmetric design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – 4 GHz; Linearity: ± 0.2 dB (30 MHz – 4 GHz)	
Directivity	± 0.2 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)	
Dynamic Range	5 μ W/g – >100 mW/g; Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 3.9 mm (body: 12 mm) Distance from probe tip to dipole centers: 3.0 mm	

<EX3DV4 Probe>

Construction	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – >6 GHz Linearity: ± 0.2 dB (30 MHz – 6 GHz)	
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 μ W/g – >100 mW/g Linearity: ± 0.2 dB (noise: typically <1 μ W/g)	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

6.3 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.




Fig 5.1 Photo of DAE

6.4 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

6.5 Device Holder

<Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

<Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

7. Measurement Procedures

The measurement procedures are as follows:

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

7.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

7.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

7.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

7.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm $2 - 3$ GHz: ≤ 5 mm*	$3 - 4$ GHz: ≤ 5 mm* $4 - 6$ GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	$3 - 4$ GHz: ≤ 4 mm $4 - 5$ GHz: ≤ 3 mm $5 - 6$ GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	$3 - 4$ GHz: ≤ 3 mm $4 - 5$ GHz: ≤ 2.5 mm $5 - 6$ GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	$3 - 4$ GHz: ≥ 28 mm $4 - 5$ GHz: ≥ 25 mm $5 - 6$ GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

7.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

7.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

8. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	2450MHz System Validation Kit ⁽²⁾	D2450V2	736	Aug. 17, 2021	Aug. 15, 2023
SPEAG	5GHz System Validation Kit ⁽²⁾	D5GHzV2	1171	Apr. 20, 2021	Apr. 17, 2024
SPEAG	13MHz System Validation Kit	CLA13	1022	Sep. 01, 2022	Aug. 31, 2023
SPEAG	Data Acquisition Electronics	DAE4	853	Jul. 14, 2023	Jul. 13, 2024
SPEAG	Data Acquisition Electronics	DAE4	1694	Nov. 18, 2022	Nov. 17, 2023
SPEAG	Dosimetric E-Field Probe	EX3DV4	7306	Jul. 18, 2023	Jul. 17, 2024
SPEAG	Dosimetric E-Field Probe	EX3DV4	7439	Feb. 21, 2023	Feb. 20, 2024
RCPTWN	Thermometer	HTC-1	TM685-1	Mar. 21, 2023	Mar. 20, 2024
RCPTWN	Thermometer	HTC-1	TM560-2	Mar. 21, 2023	Mar. 20, 2024
R&S	BT Base Station	CBT32	101136	Oct. 25, 2022	Oct. 24, 2023
SPEAG	Device Holder	N/A	N/A	N/A	N/A
Anritsu	Signal Generator	MG3710A	6201502524	Oct. 12, 2022	Oct. 11, 2023
Keysight	ENA Network Analyzer	E5071C	MY46104758	Sep. 22, 2022	Sep. 21, 2023
SPEAG	Dielectric Probe Kit	DAK-3.5	1270	May. 22, 2023	May. 21, 2024
SPEAG	Dielectric Probe Kit	DAK-12	1169	Aug. 29, 2022	Aug. 28, 2023
LINE SEIKI	Digital Thermometer	DTM3000-spezial	3796	Jan. 13, 2023	Jan. 12, 2024
Anritsu	Power Meter	ML2495A	1804003	Oct. 17, 2022	Oct. 16, 2023
Anritsu	Power Sensor	MA2411B	1726150	Oct. 17, 2022	Oct. 16, 2023
Anritsu	Spectrum Analyzer	N9010A	MY53470118	Jan. 10, 2023	Jan. 09, 2024
Mini-Circuits	Power Amplifier	ZVE-8G+	6418	Oct. 14, 2022	Oct. 13, 2023
ATM	Dual Directional Coupler	C122H-10	P610410z-02	Note 1	
Warison	Directional Coupler	WCOU-10-50S-10	WR889BMC4B1	Note 1	
Woken	Attenuator 1	WK0602-XX	N/A	Note 1	
PE	Attenuator 2	PE7005-10	N/A	Note 1	
PE	Attenuator 3	PE7005- 3	N/A	Note 1	

General Note:

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.
2. The dipole calibration interval can be extended to 3 years with justification according to KDB 865664 D01. The dipoles are also not physically damaged, or repaired during the interval. The justification data in appendix C can be found which the return loss is < -20dB, within 20% of prior calibration, the impedance is within 5 ohm of prior calibration for each dipole.

9. System Verification

9.1 Tissue Verification

The tissue dielectric parameters of tissue-equivalent media used for SAR measurements must be characterized within a temperature range of 18°C to 25°C, measured with calibrated instruments and apparatuses, such as network analyzers and temperature probes. The temperature of the tissue-equivalent medium during SAR measurement must also be within 18°C to 25°C and within $\pm 2^\circ\text{C}$ of the temperature when the tissue parameters are characterized. The tissue dielectric measurement system must be calibrated before use. The dielectric parameters must be measured before the tissue-equivalent medium is used in a series of SAR measurements.

The liquid tissue depth was at least 15cm in the phantom for all SAR testing

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
13	22.5	0.757	53.426	0.75	55.00	0.93	-2.86	± 5	2023/8/11
2450	22.5	1.830	38.900	1.80	39.20	1.67	-0.77	± 5	2023/7/28
2450	22.6	1.790	38.600	1.80	39.20	-0.56	-1.53	± 5	2023/7/31
2450	22.6	1.820	38.800	1.80	39.20	1.11	-1.02	± 5	2023/8/1
2450	22.6	1.800	38.700	1.80	39.20	0.00	-1.28	± 5	2023/8/3
2450	22.5	1.840	38.900	1.80	39.20	2.22	-0.77	± 5	2023/8/4
5250	22.7	4.770	36.000	4.71	35.95	1.27	0.14	± 5	2023/7/29
5250	22.7	4.580	35.400	4.71	35.95	-2.76	-1.53	± 5	2023/8/2
5600	22.7	5.170	35.300	5.07	35.50	1.97	-0.56	± 5	2023/7/29
5600	22.7	4.970	34.800	5.07	35.50	-1.97	-1.97	± 5	2023/8/2
5750	22.7	5.360	35.000	5.22	35.35	2.68	-0.99	± 5	2023/7/29
5750	22.7	5.140	34.600	5.22	35.35	-1.53	-2.12	± 5	2023/8/2

9.2 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)	Measured 10g SAR (W/kg)	Targeted 10g SAR (W/kg)	Normalized 10g SAR (W/kg)	Deviation (%)	Test Site
2023/8/11	13	250	CLA13-1022	EX3DV4 - SN7306	DAE4 Sn853	0.142	0.560	0.568	1.43	0.088	0.349	0.352	0.57	SAR05
2023/7/28	2450	250	D2450V2-736	EX3DV4 - SN7439	DAE4 Sn1694	13.100	54.200	52.4	-3.32	6.140	25.300	24.56	-2.92	SAR10
2023/7/31	2450	50	D2450V2-736	EX3DV4 - SN7439	DAE4 Sn1694	2.440	54.200	48.8	-9.96	1.150	25.300	23	-9.09	SAR10
2023/8/1	2450	50	D2450V2-736	EX3DV4 - SN7439	DAE4 Sn1694	2.450	54.200	49	-9.59	1.150	25.300	23	-9.09	SAR10
2023/8/3	2450	50	D2450V2-736	EX3DV4 - SN7439	DAE4 Sn1694	2.470	54.200	49.4	-8.86	1.170	25.300	23.4	-7.51	SAR10
2023/8/4	2450	50	D2450V2-736	EX3DV4 - SN7439	DAE4 Sn1694	2.460	54.200	49.2	-9.23	1.170	25.300	23.4	-7.51	SAR10
2023/7/29	5250	100	D5GHzV2-1171-5250	EX3DV4 - SN7439	DAE4 Sn1694	8.100	80.300	81	0.87	2.320	23.000	23.2	0.87	SAR10
2023/8/2	5250	50	D5GHzV2-1171-5250	EX3DV4 - SN7439	DAE4 Sn1694	3.720	80.300	74.4	-7.35	1.060	23.000	21.2	-7.83	SAR10
2023/7/29	5600	100	D5GHzV2-1171-5600	EX3DV4 - SN7439	DAE4 Sn1694	8.800	83.400	88	5.52	2.520	23.700	25.2	6.33	SAR10
2023/8/2	5600	50	D5GHzV2-1171-5600	EX3DV4 - SN7439	DAE4 Sn1694	4.250	83.400	85	1.92	1.200	23.700	24	1.27	SAR10
2023/7/29	5750	100	D5GHzV2-1171-5750	EX3DV4 - SN7439	DAE4 Sn1694	8.460	80.400	84.6	5.22	2.400	22.800	24	5.26	SAR10
2023/8/2	5750	50	D5GHzV2-1171-5750	EX3DV4 - SN7439	DAE4 Sn1694	3.950	80.400	79	-1.74	1.110	22.800	22.2	-2.63	SAR10




Fig 8.3.1 System Performance Check Setup



Fig 8.3.2 Setup Photo

10. RF Exposure Positions

10.1 Body Worn Accessory

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 9.4). Per KDB648474 D04v01r03, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $> 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-chip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Fig 9.4 Body Worn Position

10.2 Extremity Exposure

For smart phones with a display diagonal dimension $> 15.0 \text{ cm}$ or an overall diagonal dimension $> 16.0 \text{ cm}$ that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, According to KDB648474 D04v01r03, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance

1. The normally required head and body-worn accessory SAR test procedures for handsets, including hotspot mode, must be applied.
2. The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at $\leq 25 \text{ mm}$ from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions.⁶ The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR $> 1.2 \text{ W/kg}$.



10.3 Wireless Router

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 v02r01 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.



11. WiFi/Bluetooth Output Power (Unit: dBm)

General Note:

1. For each antenna, maximum transmit power in SISO operation is equal to the power in MIMO operation, RF exposure was perform MIMO mode only
2. Additional 2.4GHz WLAN SISO operation was using perform Sim-Tx analysis with Bluetooth transmitter.
3. The maximum output power specified for production units are determined for all applicable 802.11 transmission modes in each standalone and aggregated frequency band. Maximum output power is measured for the highest maximum output power configuration(s) in each frequency band according to the default power measurement procedures. For "Not required", SAR Test reduction was applied from KDB 248227 guidance, Sec. 2.1, b), 1) when the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration, additional output power measurements were not necessary.
4. Per KDB 248227 D01v02r02, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
5. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
6. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
7. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures. 18 The initial test position procedure is described in the following:
 - a. When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
 - b. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
 - c. For all positions/configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
8. Per 201904 TCBC workshops, General principles of FCC KDB Publication 248227 D01 can be applied to determine the SAR Initial Test Configurations and test reduction for 802.11ax SAR testing. For the table below the 802.11ax maximum power is SU (non-OFDMA), and the SU maximum power also higher than RU (OFDMA)
9. In applying the test guidance, the IEEE 802.11 mode with the maximum output power (out of all modes) should be considered for testing
10. For modes with the same maximum output power, the guidance from section 5.3.2 a) of FCC KDB Publication 248227 D01 should be applied, with 802.11ax being considered as the highest 802.11 mode for the appropriate frequency bands
11. When SAR testing for 802.11ax is required
 - a. If the maximum output power is highest for OFDMA scenarios, choose the tone size with the maximum number of tones and the highest maximum output power
 - b. Otherwise, consider the fully allocated channel for SAR testing
 - c. When SAR testing is required on RU sizes less than the fully allocated channel, use the RU number closest to the middle of the channel, choosing the higher RU number when two RUs are equidistant to the middle of the channel



<2.4GHz WLAN>																	
				Ant 6			Ant 7			Ant 6+7 (6)		Ant 6+7 (7)		Ant 6+7			
	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Duty Cycle %	
2.4GHz WLAN	802.11b 1Mbps	1	2412	21.20	21.50	86.06	21.10	21.50	86.06	21.40	21.50	21.30	21.50	24.36	24.50	86.06	
		6	2437	21.50	21.50		21.40	21.50		21.30	21.50	21.50	21.50	24.41	24.50		
		11	2462	20.30	20.50		20.20	20.50		19.10	20.50	20.20	20.50	22.70	23.50		
	802.11g 6Mbps	1	2412	Not required	19.00	Not required	Not required	19.00	Not required	Not required	19.00	Not required	19.00	Not required	22.00	Not required	
		6	2437		19.50			19.50			20.00		20.00		23.00		
		11	2462		18.50			18.50			18.50		18.50		21.50		
	802.11n-HT20 MCS0	1	2412		19.00			19.00			19.00		19.00		22.00		
		6	2437		20.00			20.00			20.00		20.00		23.00		
		11	2462		18.00			18.00			18.50		18.50		21.50		
	802.11n-HT40 MCS0	3	2422		18.00			18.00			18.00		18.00		21.00		
		6	2437		17.50			17.50			17.50		17.50		20.50		
		9	2452		16.00			16.00			16.00		16.00		19.00		
	802.11ac-VHT20 MCS0	1	2412		19.00			19.00			19.00		19.00		22.00		
		6	2437		20.00			20.00			20.00		20.00		23.00		
		11	2462		18.00			18.00			18.50		18.50		21.50		
	802.11ac-VHT40 MCS0	3	2422		18.00			18.00			18.00		18.00		21.00		
		6	2437		17.50			17.50			17.50		17.50		20.50		
		9	2452		16.00			16.00			16.00		16.00		19.00		
	802.11ax-HE20 MCS0	1	2412		19.00			19.00			19.00		19.00		22.00		
		6	2437		20.00			20.00			20.00		20.00		23.00		
		11	2462		18.00			18.00			18.50		18.50		21.50		
	802.11ax-HE40 MCS0	3	2422		18.00			18.00			18.00		18.00		21.00		
		6	2437		17.50			17.50			17.50		17.50		20.50		
		9	2452		16.00			16.00			16.00		16.00		19.00		



<5.2GHz WLAN>																
				Ant 6			Ant 7			Ant 6+7 (6)		Ant 6+7 (7)		Ant 6+7		
	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.2GHz WLAN	802.11a 6Mbps	36	5180	Not required	18.50	Not required	Not required	17.00	Not required	Not required	18.50	Not required	17.00	Not required	20.82	Not required
		40	5200		19.50			18.50			19.50		18.50		22.04	
		44	5220		19.50			18.50			19.50		18.50		22.04	
		48	5240		19.00			17.50			19.00		17.50		21.32	
	802.11n-HT20 MCS0	36	5180		18.50			18.00			18.50		18.00		21.27	
		40	5200		20.50			19.00			20.50		19.00		22.82	
		44	5220		20.50			19.00			20.50		19.00		22.82	
		48	5240		19.50			18.00			19.50		18.00		21.82	
	802.11n-HT40 MCS0	38	5190		16.50			15.50			16.50		15.50		19.04	
		46	5230		19.50			18.00			19.50		18.00		21.82	
	802.11ac-VHT20 MCS0	36	5180		18.50			18.00			18.50		18.00		21.27	
		40	5200		20.50			19.00			20.50		19.00		22.82	
		44	5220		20.50			19.00			20.50		19.00		22.82	
		48	5240		19.50			18.00			19.50		18.00		21.82	
	802.11ac-VHT40 MCS0	38	5190		16.50			15.50			16.50		15.50		19.04	
		46	5230		19.50			18.00			19.50		18.00		21.82	
	802.11ac-VHT80 MCS0	42	5210		17.50			16.00			17.50		16.00		19.82	
	802.11ax-HE20 MCS0	36	5180		18.50			18.00			18.50		18.00		21.27	
		40	5200		20.50			19.00			20.50		19.00		22.82	
		44	5220		20.50			19.00			20.50		19.00		22.82	
		48	5240		19.50			18.50			19.50		18.50		22.04	
	802.11ax-HE40 MCS0	38	5190		16.50			15.50			16.50		15.50		19.04	
		46	5230		19.50			18.00			19.50		18.00		21.82	
	802.11ax-HE80 MCS0	42	5210		17.50			16.50			17.50		16.50		20.04	



<5.3GHz WLAN>

				Ant 6			Ant 7			Ant 6+7 (6)		Ant 6+7 (7)		Ant 6+7		
	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.3GHz WLAN	802.11a 6Mbps	52	5260	Not required	19.50	Not required	Not required	18.50	Not required	19.00	19.50	17.90	18.50	21.50	22.04	85.57
		56	5280		19.50			18.50		19.20	19.50	18.30	18.50	21.78	22.04	
		60	5300		20.00			18.50		19.90	20.50	18.50	19.00	22.27	22.82	
		64	5320		18.50			17.50		18.10	18.50	17.20	17.50	20.68	21.04	
	802.11n-HT20 MCS0	52	5260		19.50			18.50		Not required	19.50	Not required	18.50	Not required	22.04	Not required
		56	5280		19.50			18.50			19.50		18.50		22.04	
		60	5300		20.00			18.50			20.00		18.50		22.32	
		64	5320		18.50			17.50			18.50		17.50		21.04	
	802.11n-HT40 MCS0	54	5270		21.00			20.00			18.00		18.00		21.00	
		62	5310		16.50			16.50			16.50		16.50		19.50	
	802.11ac-VHT20 MCS0	52	5260		19.50			18.50			19.50		18.50		22.04	
		56	5280		19.50			18.50			19.50		18.50		22.04	
		60	5300		20.00			18.50			20.00		18.50		22.32	
		64	5320		18.50			17.50			18.50		17.50		21.04	
	802.11ac-VHT40 MCS0	54	5270		21.00			20.00			18.00		18.00		21.00	
		62	5310		16.50			16.50			16.50		16.50		19.50	
	802.11ac-VHT80 MCS0	58	5290		15.50			15.50			15.50		15.50		18.50	
	802.11ac-VHT160 MCS0	50	5250		13.00			13.00			13.00		13.00		16.00	
	802.11ax-HE20 MCS0	52	5260		19.50			18.50			19.50		18.50		22.04	
		56	5280		19.50			18.50			19.50		18.50		22.04	
		60	5300		20.00			18.50			20.00		18.50		22.32	
		64	5320		18.50			17.50			18.50		17.50		21.04	
	802.11ax-HE40 MCS0	54	5270		21.00			20.00			18.00		18.00		21.00	
		62	5310		16.50			16.50			16.50		16.50		19.50	
	802.11ax-HE80 MCS0	58	5290		15.50			15.50			15.50		15.50		18.50	
	802.11ax-HE160 MCS0	50	5250		13.00			13.00			13.00		13.00		16.00	



FCC SAR TEST REPORT

Report No. : FA362117

<5.5GHz WLAN>																
				Ant 6			Ant 7			Ant 6+7 (6)		Ant 6+7 (7)		Ant 6+7		
	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.5GHz WLAN	802.11a 6Mbps	100	5500	Not required	19.00	Not required	Not required	19.00	Not required	19.00	19.00	18.40	19.00	21.72	22.00	85.57
		116	5580		19.00			19.00		18.70	19.00	18.50	19.00	21.61	22.00	
		124	5620		19.00			19.00		18.10	19.00	18.10	19.00	21.11	22.00	
		132	5660		19.00			19.00		18.60	19.00	18.70	19.00	21.66	22.00	
		144	5720		19.50			19.50		18.70	19.50	19.30	19.50	22.02	22.50	
	802.11n-HT20 MCS0	100	5500		19.00			19.00		Not required	19.00	Not required	19.00	Not required	22.00	Not required
		116	5580		19.00			19.00			19.00		19.00		22.00	
		124	5620		19.00			19.00			19.00		19.00		22.00	
		132	5660		19.00			19.00			19.00		19.00		22.00	
		144	5720		19.50			19.50			19.50		19.50		22.50	
	802.11n-HT40 MCS0	102	5510		17.50			17.50			17.50		17.50		20.50	
		110	5550		19.00			19.00			19.00		19.00		22.00	
		126	5630		19.00			19.00			19.00		19.00		22.00	
		134	5670		19.00			19.00			19.00		19.00		22.00	
		142	5710		19.00			19.00			19.00		19.00		22.00	
	802.11ac-VHT20 MCS0	100	5500		19.00			19.00			19.00		19.00		22.00	
		116	5580		19.00			19.00			19.00		19.00		22.00	
		124	5620		19.00			19.00			19.00		19.00		22.00	
		132	5660		19.00			19.00			19.00		19.00		22.00	
		144	5720		19.50			19.50			19.50		19.50		22.50	
	802.11ac-VHT40 MCS0	102	5510		17.50			17.50			17.50		17.50		20.50	
		110	5550		19.00			19.00			19.00		19.00		22.00	
		126	5630		19.00			19.00			19.00		19.00		22.00	
		134	5670		19.00			19.00			19.00		19.00		22.00	
		142	5710		19.00			19.00			19.00		19.00		22.00	
	802.11ac-VHT80 MCS0	106	5530		16.50			16.50			16.50		16.50		19.50	
		122	5610		19.00			19.00			19.00		19.00		22.00	
		138	5690		19.00			19.00			19.00		19.00		22.00	
	802.11ac-VHT160 MCS0	114	5570		14.00			14.00			14.00		14.00		17.00	
		100	5500		19.00			19.00			19.00		19.00		22.00	
	802.11ax-HE20 MCS0	116	5580		19.00			19.00			19.00		19.00		22.00	
		124	5620		19.00			19.00			19.00		19.00		22.00	
		132	5660		19.00			19.00			19.00		19.00		22.00	
		144	5720		19.50			19.50			19.50		19.50		22.50	
	802.11ax-HE40 MCS0	102	5510		17.50			17.50			17.50		17.50		20.50	
		110	5550		19.00			19.00			19.00		19.00		22.00	
		126	5630		19.00			19.00			19.00		19.00		22.00	
		134	5670		19.00			19.00			19.00		19.00		22.00	
		142	5710		19.00			19.00			19.00		19.00		22.00	
	802.11ax-HE80 MCS0	106	5530		16.50			16.50			16.50		16.50		19.50	
		122	5610		19.00			19.00			19.00		19.00		22.00	
		138	5690		19.00			19.00			19.00		19.00		22.00	
	802.11ax-HE160 MCS0	114	5570		14.00			14.00			14.00		14.00		17.00	




<5.8GHz WLAN>																
5.8GHz WLAN	Mode	Channel	Frequency (MHz)	Ant 6			Ant 7			Ant 6+7 (6)		Ant 6+7 (7)		Ant 6+7		
				Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Duty Cycle %	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11a 6Mbps	149	5745	Not required	20.00	Not required	Not required	20.00	Not required	19.10	20.00	19.80	20.00	22.47	23.00	85.57
		157	5785		20.00			20.00		19.00	20.00	19.40	20.00	22.21	23.00	
		165	5825		20.00			20.00		19.20	20.00	19.50	20.00	22.36	23.00	
	802.11n-HT20 MCS0	149	5745		20.00			20.00		Not required	20.00	Not required	20.00	Not required	23.00	Not required
		157	5785		20.00			20.00			20.00		20.00		23.00	
		165	5825		20.00			20.00			20.00		20.00		23.00	
	802.11n-HT40 MCS0	151	5755		19.50			19.50			19.50		19.50		22.50	
		159	5795		19.50			19.50			19.50		19.50		22.50	
	802.11ac-VHT20 MCS0	149	5745		20.00			20.00			20.00		20.00		23.00	
		157	5785		20.00			20.00			20.00		20.00		23.00	
		165	5825		20.00			20.00			20.00		20.00		23.00	
	802.11ac-VHT40 MCS0	151	5755		19.50			19.50			19.50		19.50		22.50	
		159	5795		19.50			19.50			19.50		19.50		22.50	
	802.11ac-VHT80 MCS0	155	5775		19.00			19.00			19.00		19.00		22.00	
		149	5745		20.00			20.00			20.00		20.00		23.00	
	802.11ax-HE20 MCS0	157	5785		20.00			20.00			20.00		20.00		23.00	
		165	5825		20.00			20.00			20.00		20.00		23.00	
		151	5755		19.50			19.50			19.50		19.50		22.50	
	802.11ax-HE40 MCS0	159	5795		19.50			19.50			19.50		19.50		22.50	
		155	5775		19.00			19.00			19.00		19.00		22.00	

<2.4GHz Bluetooth>

				Ant 6		
Bluetooth	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	BR / EDR 1Mbps	0	2402	3.18	4.00	76.80
		39	2441	5.61	6.00	
		78	2480	3.98	4.00	
	BR / EDR 2Mbps	0	2402	Not required	2.00	Not required
		39	2441		3.00	
		78	2480		2.00	
	BR / EDR 3Mbps	0	2402		2.00	
		39	2441		3.00	
		78	2480		2.00	
	LE 1Mbps	0	2402		3.50	
		19	2440		5.50	
		39	2480		4.00	
	LE 2Mbps	0	2402		3.50	
		19	2440		5.50	
		39	2480		4.00	

General Note:


- For 2.4GHz Bluetooth SAR testing was selected 1Mbps due to its highest average power and duty cycle is 76.80% considered in SAR testing, and the duty cycle would be scaled to theoretical 83.3% in reported SAR calculation.

BT Duty cycle



				Ant 7		
	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
Bluetooth	BR / EDR 1Mbps	0	2402	5.49	6.00	76.86
		39	2441	4.92	5.00	
		78	2480	4.76	5.00	
	BR / EDR 2Mbps	0	2402	Not required	3.50	Not required
		39	2441		3.00	
		78	2480		3.00	
	BR / EDR 3Mbps	0	2402		3.50	
		39	2441		3.00	
		78	2480		3.00	
	LE 1Mbps	0	2402		6.00	
		19	2440		5.50	
		39	2480		5.00	
	LE 2Mbps	0	2402		6.00	
		19	2440		5.50	
		39	2480		5.00	

General Note:

- For 2.4GHz Bluetooth SAR testing was selected 1Mbps due to its highest average power and duty cycle is 76.86% considered in SAR testing, and the duty cycle would be scaled to theoretical 83.3% in reported SAR calculation.

BT Duty cycle


12. Antenna Location



Distance of the Antenna to the EUT surface/edge						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
BT&WLAN Ant 6	≤ 25mm	≤ 25mm	>25mm	>25mm	≤ 25mm	≤ 25mm
BT&WLAN Ant 7	≤ 25mm	≤ 25mm	>25mm	>25mm	≤ 25mm	≤ 25mm

Positions for SAR tests; Hotspot mode						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
BT&WLAN Ant 6	Yes	Yes	No	No	Yes	Yes
BT&WLAN Ant 7	Yes	Yes	No	No	Yes	Yes

General Note:

- Referring to KDB 941225 D06 v02r01, when the overall device length and width are $\geq 9\text{cm} \times 5\text{cm}$, the test distance is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge

13. SAR Test Results

General Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
 - c. For WLAN/Bluetooth: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.

WLAN Note:

1. Per KDB 248227 D01v02r02, for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
2. Per KDB 248227 D01v02r02, WLAN5.2GHz SAR testing is not required when the WLAN5.3GHz band highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for WLAN5.2GHz band.
3. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
4. For all positions / configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions / configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
5. For determination of the scaling factor for report SAR of MIMO mode, if the hot spots are separated the scaling factors are individually determined from each transmit chain. If the hot spots are not spatially separated, the scaling factor is determined from the worst number of each transmit chain
6. Additional 2.4GHz WLAN SISO operation was using perform Sim-Tx analysis with Bluetooth transmitter.
7. During SAR testing the WLAN transmission was verified using a spectrum analyzer.

NFC Note:

1. NFC mainly operate in hand-held extremity exposure conditions and NFC sensing distance with other device or reading tag, therefore, Standalone 10-g extremity SAR testing for NFC will be performed with active mode and max power mode, with 100% duty cycle at 0mm separation distance.
2. NFC SAR is measured for all edges and surfaces of the device with a transmitting antenna located within 25 mm from that surface or edge.
3. NFC 13.56MHz antenna port is not available on the device to support conducted power measurement, therefore the measured results are referred to as reported SAR.
4. NFC SAR test tissue-simulating liquid parameter: refer to IEC/IEEE 62209-1528 2020.

**13.1 Hotspot SAR****<WLAN SAR>**

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Keypad	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	10mm	Ant 6	53Key	6	2437	21.50	21.50	1.000	86.06	1.162	0.02	0.066	0.077
	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	Ant 6	53Key	6	2437	21.50	21.50	1.000	86.06	1.162	0.04	0.165	0.192
	WLAN2.4GHz	802.11b 1Mbps	Left Side	10mm	Ant 6	53Key	6	2437	21.50	21.50	1.000	86.06	1.162	0.16	0.029	0.034
	WLAN2.4GHz	802.11b 1Mbps	Right Side	10mm	Ant 6	53Key	6	2437	21.50	21.50	1.000	86.06	1.162	0.01	0.379	0.440
	WLAN2.4GHz	802.11b 1Mbps	Right Side	10mm	Ant 6	43Key	6	2437	21.50	21.50	1.000	86.06	1.162	0.16	0.269	0.313
	WLAN2.4GHz	802.11b 1Mbps	Right Side	10mm	Ant 6	58Key	6	2437	21.50	21.50	1.000	86.06	1.162	-0.19	0.286	0.332
	WLAN2.4GHz	802.11b 1Mbps	Right Side	10mm	Ant 6	34Key	6	2437	21.50	21.50	1.000	86.06	1.162	0.13	0.288	0.335
	WLAN2.4GHz	802.11b 1Mbps	Right Side	10mm	Ant 6	29Key	6	2437	21.50	21.50	1.000	86.06	1.162	-0.02	0.274	0.318
	WLAN2.4GHz	802.11b 1Mbps	Front	10mm	Ant 7	53Key	6	2437	21.40	21.50	1.023	86.06	1.162	-0.11	0.078	0.093
	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	Ant 7	53Key	6	2437	21.40	21.50	1.023	86.06	1.162	-0.01	0.349	0.415
01	WLAN2.4GHz	802.11b 1Mbps	Left Side	10mm	Ant 7	53Key	6	2437	21.40	21.50	1.023	86.06	1.162	0.06	0.727	0.864
	WLAN2.4GHz	802.11b 1Mbps	Left Side	10mm	Ant 7	53Key	1	2412	21.10	21.50	1.096	86.06	1.162	0.02	0.563	0.717
	WLAN2.4GHz	802.11b 1Mbps	Left Side	10mm	Ant 7	53Key	11	2462	20.20	20.50	1.072	86.06	1.162	0.04	0.450	0.560
	WLAN2.4GHz	802.11b 1Mbps	Left Side	10mm	Ant 7	43Key	6	2437	21.40	21.50	1.023	86.06	1.162	-0.12	0.603	0.717
	WLAN2.4GHz	802.11b 1Mbps	Left Side	10mm	Ant 7	58Key	6	2437	21.40	21.50	1.023	86.06	1.162	0.01	0.679	0.807
	WLAN2.4GHz	802.11b 1Mbps	Left Side	10mm	Ant 7	34Key	6	2437	21.40	21.50	1.023	86.06	1.162	0.01	0.683	0.812
	WLAN2.4GHz	802.11b 1Mbps	Left Side	10mm	Ant 7	29Key	6	2437	21.40	21.50	1.023	86.06	1.162	-0.14	0.695	0.826
	WLAN2.4GHz	802.11b 1Mbps	Right Side	10mm	Ant 7	53Key	6	2437	21.40	21.50	1.023	86.06	1.162	-0.1	0.018	0.021
	WLAN2.4GHz	802.11b 1Mbps	Front	10mm	Ant 6+7(6)	53Key	6	2437	21.30	21.50	1.047	86.06	1.162	-0.1	0.065	0.079
	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	Ant 6+7(6)	53Key	6	2437	21.30	21.50	1.047	86.06	1.162	-0.14	0.423	0.515
	WLAN2.4GHz	802.11b 1Mbps	Left Side	10mm	Ant 6+7(6)	53Key	6	2437	21.30	21.50	1.047	86.06	1.162	0.02	0.646	0.786
	WLAN2.4GHz	802.11b 1Mbps	Left Side	10mm	Ant 6+7(6)	43Key	6	2437	21.30	21.50	1.047	86.06	1.162	-0.04	0.592	0.720
	WLAN2.4GHz	802.11b 1Mbps	Left Side	10mm	Ant 6+7(6)	58Key	6	2437	21.30	21.50	1.047	86.06	1.162	0.14	0.617	0.751
	WLAN2.4GHz	802.11b 1Mbps	Left Side	10mm	Ant 6+7(6)	34Key	6	2437	21.30	21.50	1.047	86.06	1.162	0.13	0.623	0.758
	WLAN2.4GHz	802.11b 1Mbps	Left Side	10mm	Ant 6+7(6)	29Key	6	2437	21.30	21.50	1.047	86.06	1.162	-0.18	0.565	0.687
	WLAN2.4GHz	802.11b 1Mbps	Right Side	10mm	Ant 6+7(6)	53Key	6	2437	21.30	21.50	1.047	86.06	1.162	0	0.122	0.148

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Keypad	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Front	10mm	Ant 6	53Key	39	2441	5.61	6.00	1.094	76.8	1.085	-0.07	0.001	0.001
	Bluetooth	1Mbps	Back	10mm	Ant 6	53Key	39	2441	5.61	6.00	1.094	76.8	1.085	-0.1	0.009	0.011
	Bluetooth	1Mbps	Left Side	10mm	Ant 6	53Key	39	2441	5.61	6.00	1.094	76.8	1.085	0.13	0.001	0.001
02	Bluetooth	1Mbps	Right Side	10mm	Ant 6	53Key	39	2441	5.61	6.00	1.094	76.8	1.085	0.16	0.022	0.026
	Bluetooth	1Mbps	Right Side	10mm	Ant 6	43Key	39	2441	5.61	6.00	1.094	76.8	1.085	-0.04	0.016	0.019
	Bluetooth	1Mbps	Right Side	10mm	Ant 6	58Key	39	2441	5.61	6.00	1.094	76.8	1.085	-0.15	0.020	0.024
	Bluetooth	1Mbps	Right Side	10mm	Ant 6	34Key	39	2441	5.61	6.00	1.094	76.8	1.085	0.17	0.019	0.023
	Bluetooth	1Mbps	Right Side	10mm	Ant 6	29Key	39	2441	5.61	6.00	1.094	76.8	1.085	-0.09	0.017	0.020
	Bluetooth	1Mbps	Front	10mm	Ant 7	53Key	0	2402	5.49	6.00	1.125	76.86	1.084	0.09	0.001	0.001
	Bluetooth	1Mbps	Back	10mm	Ant 7	53Key	0	2402	5.49	6.00	1.125	76.86	1.084	-0.12	0.005	0.006
	Bluetooth	1Mbps	Left Side	10mm	Ant 7	53Key	0	2402	5.49	6.00	1.125	76.86	1.084	0.13	0.013	0.016
	Bluetooth	1Mbps	Left Side	10mm	Ant 7	43Key	0	2402	5.49	6.00	1.125	76.86	1.084	-0.03	0.010	0.012
	Bluetooth	1Mbps	Left Side	10mm	Ant 7	58Key	0	2402	5.49	6.00	1.125	76.86	1.084	-0.18	0.011	0.013
	Bluetooth	1Mbps	Left Side	10mm	Ant 7	34Key	0	2402	5.49	6.00	1.125	76.86	1.084	-0.06	0.012	0.015
	Bluetooth	1Mbps	Left Side	10mm	Ant 7	29Key	0	2402	5.49	6.00	1.125	76.86	1.084	-0.15	0.012	0.015
	Bluetooth	1Mbps	Right Side	10mm	Ant 7	53Key	0	2402	5.49	6.00	1.125	76.86	1.084	0	0.001	0.001

**13.2 Body Worn Accessory SAR****<WLAN SAR>**

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Holster	Keypad	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	0mm	Ant 6	Holster	53Key	6	2437	21.50	21.50	1.000	86.06	1.162	0.07	0.105	0.122
	WLAN2.4GHz	802.11b 1Mbps	Left Side	0mm	Ant 6	Holster	53Key	6	2437	21.50	21.50	1.000	86.06	1.162	-0.03	0.037	0.043
	WLAN2.4GHz	802.11b 1Mbps	Right Side	0mm	Ant 6	Holster	53Key	6	2437	21.50	21.50	1.000	86.06	1.162	-0.05	0.204	0.237
	WLAN2.4GHz	802.11b 1Mbps	Right Side	0mm	Ant 6	Holster	43Key	6	2437	21.50	21.50	1.000	86.06	1.162	0.11	0.202	0.235
	WLAN2.4GHz	802.11b 1Mbps	Right Side	0mm	Ant 6	Holster	58Key	6	2437	21.50	21.50	1.000	86.06	1.162	0.04	0.203	0.236
	WLAN2.4GHz	802.11b 1Mbps	Right Side	0mm	Ant 6	Holster	34Key	6	2437	21.50	21.50	1.000	86.06	1.162	0.13	0.200	0.232
	WLAN2.4GHz	802.11b 1Mbps	Right Side	0mm	Ant 6	Holster	29Key	6	2437	21.50	21.50	1.000	86.06	1.162	0.17	0.191	0.222
	WLAN2.4GHz	802.11b 1Mbps	Front	0mm	Ant 7	Holster	53Key	6	2437	21.40	21.50	1.023	86.06	1.162	0.05	0.051	0.061
03	WLAN2.4GHz	802.11b 1Mbps	Left Side	0mm	Ant 7	Holster	53Key	6	2437	21.40	21.50	1.023	86.06	1.162	0.03	0.401	0.477
	WLAN2.4GHz	802.11b 1Mbps	Right Side	0mm	Ant 7	Holster	53Key	6	2437	21.40	21.50	1.023	86.06	1.162	0	0.016	0.019
	WLAN2.4GHz	802.11b 1Mbps	Left Side	0mm	Ant 7	Holster	43Key	6	2437	21.40	21.50	1.023	86.06	1.162	0.05	0.341	0.405
	WLAN2.4GHz	802.11b 1Mbps	Left Side	0mm	Ant 7	Holster	58Key	6	2437	21.40	21.50	1.023	86.06	1.162	-0.01	0.361	0.429
	WLAN2.4GHz	802.11b 1Mbps	Left Side	0mm	Ant 7	Holster	34Key	6	2437	21.40	21.50	1.023	86.06	1.162	-0.07	0.353	0.420
	WLAN2.4GHz	802.11b 1Mbps	Left Side	0mm	Ant 7	Holster	29Key	6	2437	21.40	21.50	1.023	86.06	1.162	0.16	0.374	0.445
	WLAN2.4GHz	802.11b 1Mbps	Front	0mm	Ant 6+7(6)	Holster	53Key	6	2437	21.30	21.50	1.047	86.06	1.162	-0.14	0.074	0.090
	WLAN2.4GHz	802.11b 1Mbps	Left Side	0mm	Ant 6+7(6)	Holster	53Key	6	2437	21.30	21.50	1.047	86.06	1.162	-0.17	0.382	0.465
	WLAN2.4GHz	802.11b 1Mbps	Right Side	0mm	Ant 6+7(6)	Holster	53Key	6	2437	21.30	21.50	1.047	86.06	1.162	-0.05	0.166	0.202
	WLAN2.4GHz	802.11b 1Mbps	Left Side	0mm	Ant 6+7(6)	Holster	43Key	6	2437	21.30	21.50	1.047	86.06	1.162	0.11	0.355	0.432
	WLAN2.4GHz	802.11b 1Mbps	Left Side	0mm	Ant 6+7(6)	Holster	58Key	6	2437	21.30	21.50	1.047	86.06	1.162	0.05	0.350	0.426
	WLAN2.4GHz	802.11b 1Mbps	Left Side	0mm	Ant 6+7(6)	Holster	34Key	6	2437	21.30	21.50	1.047	86.06	1.162	-0.02	0.356	0.433
	WLAN2.4GHz	802.11b 1Mbps	Left Side	0mm	Ant 6+7(6)	Holster	29Key	6	2437	21.30	21.50	1.047	86.06	1.162	0.05	0.366	0.445
	WLAN5GHz	802.11a 6Mbps	Front	0mm	Ant 6+7(6)	Holster	53Key	60	5300	19.90	20.50	1.148	85.57	1.169	0.03	0.307	0.412
	WLAN5GHz	802.11a 6Mbps	Left Side	0mm	Ant 6+7(6)	Holster	53Key	60	5300	19.90	20.50	1.148	85.57	1.169	0.12	0.461	0.619
	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	Ant 6+7(6)	Holster	53Key	60	5300	19.90	20.50	1.148	85.57	1.169	0.11	0.642	0.862
	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	Ant 6+7(6)	Holster	53Key	52	5260	19.00	19.50	1.122	85.57	1.169	0.15	0.596	0.782
	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	Ant 6+7(6)	Holster	53Key	56	5280	19.20	19.50	1.072	85.57	1.169	0.12	0.469	0.587
04	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	Ant 6+7(6)	Holster	53Key	64	5320	18.10	18.50	1.096	85.57	1.169	-0.01	0.677	0.868
	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	Ant 6+7(6)	Holster	43Key	64	5320	18.10	18.50	1.096	85.57	1.169	-0.13	0.663	0.850
	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	Ant 6+7(6)	Holster	58Key	64	5320	18.10	18.50	1.096	85.57	1.169	0.14	0.657	0.842
	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	Ant 6+7(6)	Holster	34Key	64	5320	18.10	18.50	1.096	85.57	1.169	-0.11	0.661	0.847
	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	Ant 6+7(6)	Holster	29Key	64	5320	18.10	18.50	1.096	85.57	1.169	0.03	0.675	0.865
	WLAN5GHz	802.11a 6Mbps	Front	0mm	Ant 6+7(6)	Holster	53Key	144	5720	18.70	19.50	1.202	85.57	1.169	-0.19	0.262	0.368
	WLAN5GHz	802.11a 6Mbps	Left Side	0mm	Ant 6+7(6)	Holster	53Key	144	5720	18.70	19.50	1.202	85.57	1.169	0.01	0.432	0.607
	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	Ant 6+7(6)	Holster	53Key	144	5720	18.70	19.50	1.202	85.57	1.169	0.02	0.601	0.845
	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	Ant 6+7(6)	Holster	53Key	100	5500	19.00	19.00	1.000	85.57	1.169	0.06	0.559	0.653
	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	Ant 6+7(6)	Holster	53Key	116	5580	18.70	19.00	1.072	85.57	1.169	0.02	0.619	0.775
05	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	Ant 6+7(6)	Holster	53Key	124	5620	18.10	19.00	1.230	85.57	1.169	0.04	0.607	0.873
	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	Ant 6+7(6)	Holster	53Key	132	5660	18.60	19.00	1.096	85.57	1.169	0.01	0.561	0.719
	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	Ant 6+7(6)	Holster	43Key	124	5620	18.10	19.00	1.230	85.57	1.169	0.04	0.575	0.827
	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	Ant 6+7(6)	Holster	58Key	124	5620	18.10	19.00	1.230	85.57	1.169	0.07	0.571	0.821
	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	Ant 6+7(6)	Holster	34Key	124	5620	18.10	19.00	1.230	85.57	1.169	0.07	0.569	0.818
	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	Ant 6+7(6)	Holster	29Key	124	5620	18.10	19.00	1.230	85.57	1.169	0.15	0.520	0.748
	WLAN5GHz	802.11a 6Mbps	Front	0mm	Ant 6+7(6)	Holster	53Key	149	5745	19.10	20.00	1.230	85.57	1.169	-0.09	0.337	0.485
	WLAN5GHz	802.11a 6Mbps	Left Side	0mm	Ant 6+7(6)	Holster	53Key	149	5745	19.10	20.00	1.230	85.57	1.169	-0.12	0.443	0.637
06	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	Ant 6+7(6)	Holster	53Key	149	5745	19.10	20.00	1.230	85.57	1.169	-0.02	0.699	1.005
	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	Ant 6+7(6)	Holster	53Key	157	5785	19.00	20.00	1.259	85.57	1.169	0.03	0.681	1.002
	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	Ant 6+7(6)	Holster	53Key	165	5825	19.20	20.00	1.202	85.57	1.169	0.04	0.663	0.932
	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	Ant 6+7(6)	Holster	43Key	149	5745	19.10	20.00	1.230	85.57	1.169	-0.16	0.691	0.994
	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	Ant 6+7(6)	Holster	58Key	149	5745	19.10	20.00	1.230	85.57	1.169	-0.02	0.639	0.919
	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	Ant 6+7(6)	Holster	34Key	149	5745	19.10	20.00	1.230	85.57	1.169	0.18	0.686	0.987
	WLAN5GHz	802.11a 6Mbps	Right Side	0mm	Ant 6+7(6)	Holster	29Key	149	5745	19.10	20.00	1.230	85.57	1.169	-0.17	0.618	0.889

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Holster	Keypad	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Front	0mm	Ant 6	Holster	53Key	39	2441	5.61	6.00	1.094	76.8	1.085	-0.07	0.003	0.004
	Bluetooth	1Mbps	Left Side	0mm	Ant 6	Holster	53Key	39	2441	5.61	6.00	1.094	76.8	1.085	0.03	0.001	0.001
07	Bluetooth	1Mbps	Right Side	0mm	Ant 6	Holster	53Key	39	2441	5.61	6.00	1.094	76.8	1.085	-0.1	0.010	0.012
	Bluetooth	1Mbps	Right Side	0mm	Ant 6	Holster	43Key	39	2441	5.61	6.00	1.094	76.8	1.085	0.04	0.006	0.007
	Bluetooth	1Mbps	Right Side	0mm	Ant 6	Holster	58Key	39	2441	5.61	6.00	1.094	76.8	1.085	-0.04	0.007	0.008
	Bluetooth	1Mbps	Right Side	0mm	Ant 6	Holster	34Key	39	2441	5.61	6.00	1.094	76.8	1.085	0.18	0.009	0.011
	Bluetooth	1Mbps	Right Side	0mm	Ant 6	Holster	29Key	39	2441	5.61	6.00	1.094	76.8	1.085	-0.19	0.008	0.009
	Bluetooth	1Mbps	Front	0mm	Ant 7	Holster	53Key	0	2402	5.49	6.00	1.125	76.86	1.084	-0.03	0.002	0.002
	Bluetooth	1Mbps	Left Side	0mm	Ant 7	Holster	53Key	0	2402	5.49	6.00	1.125	76.86	1.084	0.13	0.007	0.009
	Bluetooth	1Mbps	Right Side	0mm	Ant 7	Holster	53Key	0	2402	5.49	6.00	1.125	76.86	1.084	-0.1	0.001	0.001
	Bluetooth	1Mbps	Left Side	0mm	Ant 7	Holster	43Key	0	2402	5.49	6.00	1.125	76.86	1.084	0.09	0.006	0.007
	Bluetooth	1Mbps	Left Side	0mm	Ant 7	Holster	58Key	0	2402	5.49	6.00	1.125	76.86	1.084	0.04	0.005	0.006
	Bluetooth	1Mbps	Left Side	0mm	Ant 7	Holster	34Key	0	2402	5.49	6.00	1.125	76.86	1.084	-0.04	0.006	0.007
	Bluetooth	1Mbps	Left Side	0mm	Ant 7	Holster	29Key	0	2402	5.49	6.00	1.125	76.86	1.084	-0.06	0.007	0.009

**13.3 Extremity SAR****<WLAN SAR>**

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Keypad	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 6	53Key	6	2437	21.50	21.50	1.000	86.06	1.162	0.07	0.303	0.352
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 6	43Key	6	2437	21.50	21.50	1.000	86.06	1.162	0.03	0.261	0.303
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 6	58Key	6	2437	21.50	21.50	1.000	86.06	1.162	0.03	0.341	0.396
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 6	34Key	6	2437	21.50	21.50	1.000	86.06	1.162	0.02	0.275	0.320
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 6	29Key	6	2437	21.50	21.50	1.000	86.06	1.162	0.03	0.331	0.385
08	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 7	53Key	6	2437	21.40	21.50	1.023	86.06	1.162	-0.03	0.389	0.463
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 7	53Key	1	2412	21.10	21.50	1.096	86.06	1.162	0.09	0.309	0.394
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 7	53Key	11	2462	20.20	20.50	1.072	86.06	1.162	0.09	0.329	0.410
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 7	43Key	6	2437	21.40	21.50	1.023	86.06	1.162	-0.02	0.382	0.454
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 7	58Key	6	2437	21.40	21.50	1.023	86.06	1.162	-0.08	0.383	0.455
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 7	34Key	6	2437	21.40	21.50	1.023	86.06	1.162	0.01	0.376	0.447
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 7	29Key	6	2437	21.40	21.50	1.023	86.06	1.162	-0.04	0.381	0.453
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 6+7(6)	53Key	1	2412	21.40	21.50	1.023	86.06	1.162	-0.02	0.279	0.332
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 6+7(6)	43Key	1	2412	21.40	21.50	1.023	86.06	1.162	-0.05	0.261	0.310
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 6+7(6)	58Key	1	2412	21.40	21.50	1.023	86.06	1.162	-0.09	0.269	0.320
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 6+7(6)	34Key	1	2412	21.40	21.50	1.023	86.06	1.162	-0.07	0.278	0.331
	WLAN2.4GHz	802.11b 1Mbps	Back	0mm	Ant 6+7(6)	29Key	1	2412	21.40	21.50	1.023	86.06	1.162	-0.1	0.262	0.312
09	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 6+7(6)	53Key	60	5300	19.90	20.50	1.148	85.57	1.169	0.1	0.289	0.388
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 6+7(6)	43Key	60	5300	19.90	20.50	1.148	85.57	1.169	-0.13	0.273	0.366
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 6+7(6)	58Key	60	5300	19.90	20.50	1.148	85.57	1.169	0.01	0.262	0.352
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 6+7(6)	34Key	60	5300	19.90	20.50	1.148	85.57	1.169	0	0.267	0.358
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 6+7(6)	29Key	60	5300	19.90	20.50	1.148	85.57	1.169	0.16	0.251	0.337
10	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 6+7(6)	53Key	144	5720	18.70	19.50	1.202	85.57	1.169	-0.04	0.272	0.382
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 6+7(6)	43Key	144	5720	18.70	19.50	1.202	85.57	1.169	0.05	0.265	0.372
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 6+7(6)	58Key	144	5720	18.70	19.50	1.202	85.57	1.169	-0.05	0.259	0.364
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 6+7(6)	34Key	144	5720	18.70	19.50	1.202	85.57	1.169	0	0.266	0.374
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 6+7(6)	29Key	144	5720	18.70	19.50	1.202	85.57	1.169	0.01	0.271	0.381
11	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 6+7(6)	53Key	149	5745	19.10	20.00	1.230	85.57	1.169	-0.18	0.315	0.453
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 6+7(6)	43Key	149	5745	19.10	20.00	1.230	85.57	1.169	-0.03	0.307	0.442
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 6+7(6)	58Key	149	5745	19.10	20.00	1.230	85.57	1.169	0.02	0.303	0.436
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 6+7(6)	34Key	149	5745	19.10	20.00	1.230	85.57	1.169	0.03	0.301	0.433
	WLAN5GHz	802.11a 6Mbps	Back	0mm	Ant 6+7(6)	29Key	149	5745	19.10	20.00	1.230	85.57	1.169	-0.02	0.298	0.429

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Keypad	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
12	Bluetooth	1Mbps	Back	0mm	Ant 6	53Key	39	2441	5.61	6.00	1.094	76.8	1.085	-0.17	0.021	0.025
	Bluetooth	1Mbps	Back	0mm	Ant 6	43Key	39	2441	5.61	6.00	1.094	76.8	1.085	-0.11	0.018	0.021
	Bluetooth	1Mbps	Back	0mm	Ant 6	58Key	39	2441	5.61	6.00	1.094	76.8	1.085	-0.03	0.016	0.019
	Bluetooth	1Mbps	Back	0mm	Ant 6	34Key	39	2441	5.61	6.00	1.094	76.8	1.085	-0.01	0.019	0.023
	Bluetooth	1Mbps	Back	0mm	Ant 6	29Key	39	2441	5.61	6.00	1.094	76.8	1.085	0.13	0.016	0.019
	Bluetooth	1Mbps	Back	0mm	Ant 7	53Key	0	2402	5.49	6.00	1.125	76.86	1.084	-0.14	0.004	0.005
	Bluetooth	1Mbps	Back	0mm	Ant 7	43Key	0	2402	5.49	6.00	1.125	76.86	1.084	-0.05	0.003	0.004
	Bluetooth	1Mbps	Back	0mm	Ant 7	58Key	0	2402	5.49	6.00	1.125	76.86	1.084	0.04	0.003	0.004
	Bluetooth	1Mbps	Back	0mm	Ant 7	34Key	0	2402	5.49	6.00	1.125	76.86	1.084	-0.13	0.002	0.002
	Bluetooth	1Mbps	Back	0mm	Ant 7	29Key	0	2402	5.49	6.00	1.125	76.86	1.084	-0.01	0.003	0.004

<NFC SAR>

Plot No.	Band	Test Position	Gap (mm)	Keypad	Freq. (MHz)	Power Drift (dB)	Measured 10g SAR (W/kg)
13	NFC	Back	0mm	53Key	13.56	0	0.001
	NFC	Back	0mm	43Key	13.56	0.15	0.001
	NFC	Back	0mm	58Key	13.56	0.15	0.001
	NFC	Back	0mm	34Key	13.56	-0.05	0.001
	NFC	Back	0mm	29Key	13.56	-0.18	0.001

13.4 Repeated SAR Measurement

No.	Band	Mode	Test Position	Gap (mm)	Antenna	Keypad	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Ratio	Reported 1g SAR (W/kg)
1st	WLAN2.4GHz	802.11b 1Mbps	Left Side	10mm	Ant 7	53Key	6	2437	21.40	21.50	1.023	86.06	1.162	0.06	0.727	-	0.864
2nd	WLAN2.4GHz	802.11b 1Mbps	Left Side	10mm	Ant 7	53Key	6	2437	21.40	21.50	1.023	86.06	1.162	0.06	0.718	1.01	0.854

General Note:

1. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.
2. Per KDB 865664 D01v01r04, if the ratio among the repeated measurement is ≤ 1.2 and the measured SAR < 1.45 W/kg, only one repeated measurement is required.
3. The ratio is the difference in percentage between original and repeated *measured SAR*.
4. All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

14. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Body-worn	Hotspot	Extremity
1.	WLAN2.4GHz Ant 7 + Bluetooth Ant 6	Yes		
2.	WLAN2.4GHz Ant 6 + Bluetooth Ant 7	Yes		
3.	WLAN5GHz Ant 6+7 + Bluetooth Ant 6	Yes	Yes	
4.	WLAN5GHz Ant 6+7 + Bluetooth Ant 7	Yes	Yes	
5.	WLAN2.4GHz Ant 7 + WLAN5GHz Ant 6+7 ⁽¹⁾ + Bluetooth Ant 6	Yes	Yes	
6.	WLAN2.4GHz Ant 6 + WLAN5GHz Ant 6+7 ⁽¹⁾ + Bluetooth Ant 7	Yes	Yes	
7.	WLAN2.4GHz Ant 6+7 + WLAN5GHz ⁽¹⁾ Ant 6+7	Yes	Yes	
8.	WLAN2.4GHz Ant 7 + Bluetooth Ant 6 + NFC			Yes
9.	WLAN2.4GHz Ant 6 + Bluetooth Ant 7 + NFC			Yes
10.	WLAN5GHz Ant 6+7 + Bluetooth Ant 6 + NFC			Yes
11.	WLAN5GHz Ant 6+7 + Bluetooth Ant 7 + NFC			Yes
12.	WLAN2.4GHz Ant 7 +WLAN5GHz Ant 6+7 + Bluetooth Ant 6 + NFC			Yes
13.	WLAN2.4GHz Ant 6+ WLAN5GHz Ant 6+7 + Bluetooth Ant 7 + NFC			Yes
14.	WLAN2.4GHz Ant 6+7 + WLAN5GHz Ant 6+7 + NFC			Yes

General Note:

1. The device 2.4GHz WLAN/BT support hotspot operation via 5GHz receive signal.
2. The worst case WLAN reported SAR for each configuration was used for SAR summation. Therefore, the following summations represent the absolute worst cases for simultaneous transmission with WLAN.
3. The Scaled SAR summation is calculated based on the same configuration and test position.
4. Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
 - i) Scalar SAR summation < 1.6W/kg.
 - ii) $SPLSR = (SAR1 + SAR2)^{1.5} / (\min. \text{ separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - iii) If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
 - iv) Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg.

14.1 Hotspot Exposure Conditions

Exposure Position	1	2	3	4	5	6	2+5 Summed 1g SAR (W/kg)	1+6 Summed 1g SAR (W/kg)	4+5 Summed 1g SAR (W/kg)	4+6 Summed 1g SAR (W/kg)	2+4+5 Summed 1g SAR (W/kg)	1+4+6 Summed 1g SAR (W/kg)	3+4 Summed 1g SAR (W/kg)
	WLAN2.4GHz Ant 6 1g SAR (W/kg)	WLAN2.4GHz Ant 7 1g SAR (W/kg)	WLAN2.4GHz Ant 6+7 1g SAR (W/kg)	WLAN5GHz Ant 6+7 1g SAR (W/kg)	Bluetooth Ant 6 1g SAR (W/kg)	Bluetooth Ant 7 1g SAR (W/kg)							
Front	0.077	0.093	0.079		0.001	0.001	0.094	0.078	0.001	0.001	0.094	0.078	0.079
Back	0.192	0.415	0.515		0.011	0.006	0.426	0.198	0.011	0.006	0.426	0.198	0.515
Left side	0.034	0.864	0.786		0.001	0.016	0.865	0.050	0.001	0.016	0.865	0.050	0.786
Right side	0.440	0.021	0.148		0.026	0.001	0.047	0.441	0.026	0.001	0.047	0.441	0.148

14.2 Body-Worn Accessory Exposure Conditions

Exposure Position	1	2	3	4	5	6	2+5 Summed 1g SAR (W/kg)	1+6 Summed 1g SAR (W/kg)	4+5 Summed 1g SAR (W/kg)	4+6 Summed 1g SAR (W/kg)	2+4+5 Summed 1g SAR (W/kg)	1+4+6 Summed 1g SAR (W/kg)	3+4 Summed 1g SAR (W/kg)
	WLAN2.4GHz Ant 6 1g SAR (W/kg)	WLAN2.4GHz Ant 7 1g SAR (W/kg)	WLAN2.4GHz Ant 6+7 1g SAR (W/kg)	WLAN5GHz Ant 6+7 1g SAR (W/kg)	Bluetooth Ant 6 1g SAR (W/kg)	Bluetooth Ant 7 1g SAR (W/kg)							
Front with Holster	0.122	0.061	0.090	0.485	0.004	0.002	0.065	0.124	0.489	0.487	0.550	0.609	0.575
Left Side with Holster	0.043	0.477	0.465	0.637	0.001	0.009	0.478	0.052	0.638	0.646	1.115	0.689	1.102
Right Side with Holster	0.237	0.019	0.202	1.005	0.012	0.001	0.031	0.238	1.017	1.006	1.036	1.243	1.207

14.3 Extremity Exposure Conditions

Exposure Position	1	2	3	4	5	6	7	2+5+7 Summed 10g SAR (W/kg)	1+6+7 Summed 10g SAR (W/kg)	4+5+7 Summed 10g SAR (W/kg)	4+6+7 Summed 10g SAR (W/kg)	2+4+5+7 Summed 10g SAR (W/kg)	1+4+6+7 Summed 10g SAR (W/kg)	3+4+7 Summed 10g SAR (W/kg)
	WLAN2.4GHz Ant 6 10g SAR (W/kg)	WLAN2.4GHz Ant 7 10g SAR (W/kg)	WLAN2.4GHz Ant 6+7 10g SAR (W/kg)	WLAN5GHz Ant 6+7 10g SAR (W/kg)	Bluetooth Ant 6 10g SAR (W/kg)	Bluetooth Ant 7 10g SAR (W/kg)	NFC 10g SAR (W/kg)							
Back	0.396	0.463	0.332	0.453	0.025	0.005	0.001	0.489	0.402	0.479	0.459	0.942	0.855	0.786

Test Engineer : Hank Chiang, Jay Chien and Jocelyn Huang

15. Uncertainty Assessment

Per KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg and highest measured 10-g SAR is less 3.75W/kg. Therefore, the measurement uncertainty table is not required in this report.

Declaration of Conformity:

The test results with all measurement uncertainty excluded is presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

16. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 248227 D01 v02r02, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Oct 2015.
- [6] FCC KDB 447498 D01 v06, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Oct 2015
- [7] FCC KDB 941225 D06 v02r01, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", Oct 2015.
- [8] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [9] FCC KDB 865664 D02 v01r02, "RF Exposure Compliance Reporting and Documentation Considerations" Oct 2015.