



RF Exposure Evaluation Report

Application No.: ZR/2019/40035
Applicant: Nauto, Inc.
Address of Applicant: 220 Portage Avenue, Palo Alto, California 94306
Manufacturer: Nauto, Inc.
Address of Manufacturer: 220 Portage Avenue, Palo Alto, California 94306
Factory: DongGuan HeQin Electronic CO.,LTD
Address of Factory: Santun Road,Santun Village PortAvenue,Houjie Town,Dong Guan City,Guang Dong Province,P.R.China
EUT Description: In-vehicle Camera
Model No.: Nauto 3
Trade Mark: Nauto
FCC ID: 2AKJ5-N3
Standards: 47 CFR Part 2
47 CFR Part 22 subpart H
47 CFR Part 24 subpart E
47 CFR Part 27 subpart C
47 CFR Part 15 subpart C
Date of Receipt: 2019/5/10
Date of Test: 2019/5/10 to 2019/6/2
Date of Issue: 2019/6/2

Test Result:	PASS*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



1 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2019/6/2		Original

Authorized for issue by:				
				2019/6/2
		Mike Hu /Project Engineer		
				2019/6/2
		David Chen /Reviewer		





Contents

1	VERSION.....	2
2	GENERAL INFORMATION.....	4
2.1	CLIENT INFORMATION	4
2.2	TEST LOCATION	4
2.3	TEST FACILITY	4
2.4	GENERAL DESCRIPTION OF EUT.....	5
3	RF EXPOSURE EVALUATION	6
3.1	RF EXPOSURE COMPLIANCE REQUIREMENT	6
3.1.1	Limits	6
3.1.2	Test Procedure	6
3.1.3	EUT RF Exposure Evaluation	7



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

2 General Information

2.1 Client Information

Applicant:	Nauto, Inc.
Address of Applicant:	220 Portage Avenue, Palo Alto, California 94306
Manufacturer:	Nauto, Inc.
Address of Manufacturer:	220 Portage Avenue, Palo Alto, California 94306
Factory:	DongGuan HeQin Electronic CO.,LTD
Address of Factory:	Santun Road,Santun Village PortAvenue,Houjie Town,Dong Guan City,Guang Dong Province,P.R.China

2.2 Test Location

Company:	SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch
Address:	No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
Post code:	518057
Telephone:	+86 (0) 755 2601 2053
Fax:	+86 (0) 755 2671 0594
E-mail:	ee.shenzhen@sgs.com

2.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

• **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
 中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



2.4 General Description of EUT

EUT Description::	In-vehicle Camera
Model No.:	Nauto 3
Trade Mark:	Nauto
Hardware Version:	ISN-203014-NAA-000
Software Version:	ZSA191_USERDEBUG_Shipping_D15_201904221052
Antenna Gain:	WCDMA Band II: -4.0dBi; WCDMA Band V: -4.0dBi; LTE Band 2: -4.0dBi; LTE Band 4: -4.0dBi; LTE Band 5: -4.0dBi; LTE Band 12: -4.0dBi; BT/WiFi:-3.4 dBi;



3 RF Exposure Evaluation

3.1 RF Exposure Compliance Requirement

3.1.1 Limits

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

F=frequency in MHz
 *=Plane-wave equivalent power density
 RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

3.1.2 Test Procedure

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgsgroup.com.cn
 中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

3.1.3 EUT RF Exposure Evaluation

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.0 / 2.0 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Operating Band	Frequency (MHz)	Antenna Gain (dBi)	Max Conducted Average Output Power (dBm)	Output Power to Antenna (dBm)	EIRP(ERP) Limit (dBm)	Output Power to Antenna (mw)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)	conclusion
WCDMA B2	1852.4	-4.00	25.00	21.00	33.00	316.2278	0.0250	1.0000	Pass
WCDMA B5	826.4	-4.00	25.00	18.85	38.45	316.2278	0.0250	0.5509	Pass
LTE B2	1850.7	-4.00	25.00	21.00	33.00	316.2278	0.0250	1.0000	Pass
LTE B4	1710.7	-4.00	25.00	21.00	30.00	316.2278	0.0250	1.0000	Pass
LTE B5	824.70	-4.00	25.00	18.85	38.45	316.2278	0.0250	0.5498	Pass
LTE B12	699.70	-4.00	25.00	18.85	34.77	316.2278	0.0250	0.4665	Pass
Bluetooth	2402	-3.40	9.00	5.60	20.97	7.9433	0.0007	1.0000	Pass
2.4G WiFi	2412	-3.40	18.00	14.60	20.97	63.0957	0.0057	1.0000	Pass

Remark: Refer to report No. ZR/2019/4003501 for EUT test Max Conducted Output Power value.

