

FCC Test Report

Report No.: AGC15705240450FR01

FCC ID	:	UU8-RC65-1
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	Watch remote control
BRAND NAME	:	LEXIBOOK
MODEL NAME	:	RC65
APPLICANT	:	Lexibook America
DATE OF ISSUE	:	Jun. 28, 2024
STANDARD(S)	:	FCC Part 15 Subpart C §15.249
REPORT VERSION	:	V1.0







Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes	
V1.0	/	Jun. 28, 2024	Valid	Initial Release	



Table of Contents

1. General Information	4
2. Product Information	5
2.1 Product Technical Description	5
2.2 Test Frequency List	6
2.3 Related Submittal(S) / Grant (S)	7
2.4 Test Methodology	7
2.5 Antenna Requirement	7
3. Test Environment	8
3.1 Address of the Test Laboratory	8
3.2 Test Facility	8
3.3 Environmental Conditions	9
3.4 Measurement Uncertainty	9
3.5 List of Equipment Use	
4.System Test Configuration	
4.1 EUT Configuration	
4.2 EUT Exercise	
4.3 Configuration of Tested System	
4.4 Equipment Used In Tested System	
4.5 Summary of Test Results	
5. Description of Test Modes	14
6. Duty Cycle Measurement	
7. 20dB Bandwidth Measurement	
7.1 Provisions Applicable	
7.2 Measurement Procedure	
7.3 Measurement Setup (Block Diagram of Configuration)	
7.4 Measurement Results	
8. Field Strength of Fundamental and Radiated Spurious Emission	
8.1 Measurement Limit	
8.2 Measurement Procedure	
8.3 Measurement Setup (Block Diagram of Configuration)	
8.4 Measurement Result	
9. AC Power Line Conducted Emission	
9.1 Measurement Limit	
9.2 Measurement Setup (Block Diagram of Configuration)	
9.3 Preliminary Procedure of Line Conducted Emission Test	
9.4 Final Procedure of Line Conducted Emission Test	
9.5 Measurement Resul	
Appendix I: Photographs of Test Setup	
Appendix II: Photographs of Test EUT	



1. General Information

Applicant	Lexibook America				
Address	C/O Pramex International 1251 Avenue of the Americas, 3rd Fl., New York, NY10020, United States				
Manufacturer Lexibook America					
Address	C/O Pramex International 1251 Avenue of the Americas, 3rd Fl., New York, NY10020, United States				
Factory	Lexibook America				
Address	C/O Pramex International 1251 Avenue of the Americas, 3rd Fl., New York, NY10020, United States				
Product Designation	Watch remote control				
Brand Name	LEXIBOOK				
Test Model	RC65				
Series Model(s)	N/A				
Difference Description	N/A				
Date of receipt of test item	Apr. 19, 2024				
Date of Test	Apr. 19, 2024 to Jun. 28, 2024				
Deviation from Standard	No any deviation from the test method				
Condition of Test Sample	Normal				
Test Result	Pass				
Test Report Form No	AGCER-FCC-NTX-V1				

Note: The test results of this report relate only to the tested sample identified in this report.

Prepared By

Jouk Gai

Jack Gui (Project Engineer)

Jun. 28, 2024

Reviewed By

Calvin Liu (Reviewer)

Jun. 28, 2024

Approved By

Max Zhang (Authorized Officer)

Jun. 28, 2024



2. Product Information

2.1 Product Technical Description

Equipment Specification	Low Power Short Range Equipment
Frequency Band	2400MHz-2483.5MHz
Operation Frequency Range	2405MHz-2475MHz
Modulation Type	GFSK
Number of channels	71 channels
Channel Separation	1MHz
Field Strength of Fundamental	88.88dBµV/m (Peak)
Hardware Version	1.0
Software Version	1.0
Antenna Designation	PCB Antenna
Antenna Gain	0dBi
Power Supply	DC 3V by battery
Adapter Information	N/A



2.2 Test Frequency List

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
01	2405	25	2429	49	2453
02	2406	26	2430	50	2454
03	2407	27	2431	51	2455
04	2408	28	2432	52	2456
05	2409	29	2433	53	2457
06	2410	30	2434	54	2458
07	2411	31	2435	55	2459
08	2412	32	2436	56	2460
09	2413	33	2437	57	2461
10	2414	34	2438	58	2462
11	2415	35	2439	59	2463
12	2416	36	2440	60	2464
13	2417	37	2441	61	2465
14	2418	38	2442	62	2466
15	2419	39	2443	63	2467
16	2420	40	2444	64	2468
17	2421	41	2445	65	2469
18	2422	42	2446	66	2470
19	2423	43	2447	67	2471
20	2424	44	2448	68	2472
21	2425	45	2449	69	2473
22	2426	46	2450	70	2474
23	2427	47	2451	71	2475
24	2428	48	2452		



2.3 Related Submittal(S) / Grant (S)

This submittal(s) (test report) is intended for FCC ID: UU8-RC65-1, filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

2.4 Test Methodology

The tests were performed according to following standards:

No.	Identity	Document Title			
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations			
2	FCC 47 CFR Part 15	Radio Frequency Devices			
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices			

2.5 Antenna Requirement

Standard Requirement

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna is 0dBi.



3. Test Environment

3.1 Address of the Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories).

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842 (CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



3.3 Environmental Conditions

	Normal Conditions
Temperature range (°C)	15 - 35
Relative humidity range	20 % - 75 %
Pressure range (kPa)	86 - 106
Power supply	DC 3V by battery

3.4 Measurement Uncertainty

The reported uncertainty of measurement y \pm U, where expended uncertainty U is based on a standard

uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.9 \text{ dB}$
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of spurious emissions, conducted	U _c = ±2 %
Uncertainty of Occupied Channel Bandwidth	U _c = ±2 %



3.5 List of Equipment Use

• R	RF Conducted Test System								
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)		
\boxtimes	AGC-ER-E036	Spectrum Analyzer	Agilent	N9020A	MY49100060	2024-05-24	2025-05-23		
\boxtimes	AGC-ER-E062	Power Sensor	Agilent	U2021XA	MY54110007	2024-02-01	2025-01-31		
\boxtimes	AGC-ER-E063	Power Sensor	Agilent	U2021XA	MY54110009	2024-02-01	2025-01-31		
\boxtimes	AGC-ER-A001	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-09-21	2025-09-20		
\square	AGC-ER-E083	Signal Generator	Agilent	E4421B	US39340815	2024-05-23	2025-05-22		
	N/A	RF Connection Cable	N/A	1#	N/A	Each time	N/A		
	N/A	RF Connection Cable	N/A	2#	N/A	Each time	N/A		

• R	Radiated Spurious Emission								
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)		
	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2024-02-01	2025-01-31		
\boxtimes	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2024-05-24	2025-05-23		
\square	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2024-05-28	2025-05-27		
\boxtimes	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2024-03-05	2026-03-04		
\boxtimes	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10		
\boxtimes	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2024-03-31	2025-03-30		
\boxtimes	AGC-EM-E082	Horn Antenna	SCHWARZBECK	BBHA 9170	#768	2023-09-24	2025-09-23		
\boxtimes	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2022-08-04	2024-08-03		
\boxtimes	AGC-EM-A119	2.4G Filter	SongYi	N/A	N/A	2024-05-23	2025-05-22		
\square	AGC-EM-A138	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08		
	AGC-EM-A139	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08		

• A	AC Power Line Conducted Emission								
Used	Used Equipment No. Test Equipment Manufacturer Model No. Serial No. Last Cal. Date (YY-MM-DD) Next Cal. Date (YY-MM-DD)								
	AGC-EM-E045	EMI Test Receiver	R&S	ESPI	101206	2024-05-28	2025-05-27		
	AGC-EM-A130	6dB Attenuator	Eeatsheep	LM-XX-6-5W	DC-6GZ	2023-06-09	2025-06-08		
	AGC-EM-E023	AMN	R&S	100086	ESH2-Z5	2024-05-28	2025-05-27		



• Tes	Test Software							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information			
	AGC-EM-S001	CE Test System	R&S	ES-K1	V1.71			
	AGC-EM-S004	RE Test System	Tonscend	TS ⁺ Ver2.1(JS32-RE)	4.0.0.0			
	AGC-ER-S012	BT/WIFI Test System	Tonscend	JS1120-2	2.6			
\square	AGC-EM-S011	RSE Test System	Tonscend	TS+-Ver2.1(JS36-RSE)	4.0.0.0			



4.System Test Configuration

4.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

4.3 Configuration of Tested System

Radiated Emission Configure:



4.4 Equipment Used In Tested System

The following peripheral devices and interface cables were connected during the measurement: Test Accessories Come From The Laboratory

No.	Equipment	Manufacturer	Model No.	Specification Information	Cable
1	Control Box		USB-TTL		

Test Accessories Come From The Manufacturer

No	. Equipment	Manufacturer	Model No.	Specification Information	Cable
1	Watch remote control	Lexibook America	RC65		



4.5 Summary of Test Results

Item	FCC Rules	Description of Test	Result
1	§15.203	Antenna Equipment	Pass
2	§15.249(a)	Field Strength of Fundamental	Pass
3	§15.209&§15.249(d)	Radiated Emission& Band Edge	Pass
4	§15.205	Restricted Bands of Operation	Pass
5	§15.215	20dB Bandwidth	Pass
6	§15.207	AC Power Line Conducted Emission	N/A (See Note 2)

Note:

1. N/A means not applicable

2. This device is not AC powered and does not require this test.



5. Description of Test Modes

Summary Table of Test Cases				
Test Item	Equipment type / Modulation			
Test item	Short Distance and Low Power Consumption/ GFSK			
Radiated & Conducted Test Cases	Mode 1: Normal Transmission on channel 01 (Battery powered) Mode 2: Normal Transmission on channel 36 (Battery powered) Mode 2: Normal Transmission on channel 71 (Battery powered)			
AC Conducted Emission	N/A			
Note: 1. Only the result of the worst case was recorded in the report, if no other cases. 2. The battery is full-charged during the test.				

For Radiated Emission, 3axis were chosen for testing for each applicable mode.

For Conducted Test method, a temporary antenna connector is provided by the manufacture.

3. 4. 5. The fixed-frequency transmission of the prototype is debugged through the buttons or software declared by the manufacturer.



6. Duty Cycle Measurement


The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = Peak. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Operating mode	T(µs)	Duty Cycle (%)	Duty Cycle Factor (dB)	1/ T Minimum VBW (kHz)
GFSK_2405MHz	180	3.59	14.45	5.56
GFSK_2440MHz	180	3.59	14.45	5.56
GFSK_2475MHz	150	2.99	15.24	6.67

Remark:

1. Duty Cycle factor = 10 * log (1/ Duty cycle)

The test plots as follows:





7. 20dB Bandwidth Measurement


7.1 Provisions Applicable

N/A

7.2 Measurement Procedure

- 1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously.
- 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 30 kHz. Set the Video bandwidth (VBW) = 100 kHz. In order to make an accurate measurement.
- For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) ≥ 3 * RBW.
- 5. Measure and record the results in the test report.

7.3 Measurement Setup (Block Diagram of Configuration)







7.4 Measurement Results

Test Data of Occupied Bandwidth and -20dB Bandwidth								
Test Mode	Test Frequency (MHz)	Occupied Bandwidth (MHz)	-20dB Bandwidth (MHz)	Limits (MHz)	Pass or Fail			
	2405	1.1686	1.2360	N/A	Pass			
GFSK	2440	1.1860	1.2490	N/A	Pass			
	2475	1.2217	1.2870	N/A	Pass			

Test Graphs of Occupied Bandwidth and -20 Bandwidth









8. Field Strength of Fundamental and Radiated Spurious Emission

8.1 Measurement Limit

15.249 Limit in the below table has to be followed:

Fraguena, Danga	Field Strength of Fundamental	Field Strength of Harmonics	
Frequency Range	(millivolts/meter)	(microvolts/meter)	
900-928MHz	50	500	
2400-2483.5MHz	50	500	
5725-5875MHz	50	500	
24.0-24.25GHz	250	2500	

15.209 Limit in the below table has to be followed:

Frequency Range	Distance	Field Strengths Limit			
(MHz)	Meters	μV/m	dB(µV)/m		
0.009 ~ 0.490	300	2400/F(kHz)			
0.490 ~ 1.705	30	24000/F(kHz)			
1.705 ~ 30	30	30			
30 ~ 88	3	100	40.0		
88 ~ 216	3	150	43.5		
216 ~ 960	3	200	46.0		
960 ~ 1000	3	500	54.0		
Above 1000	3	Other:74.0 dB(µV)/m (Peak) 54.0 dB(µV)/m (Average)			

Remark:

1) Emission level dB μ V = 20 log Emission level μ V/m.

2) The smaller limit shall apply at the cross point between two frequency bands.

3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.



8.2 Measurement Procedure

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.



The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Start ~Stop Frequency	9kHz~150kHz/RB 200Hz for QP
Start ~Stop Frequency	150kHz~30MHz/RB 9kHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120kHz for QP
Start ~Stop Frequency	1GHz~26.5GHz
Start ~Stop T requency	1MHz/3MHz for Peak, 1MHz/3MHz for Average

Receiver Parameter	Setting	
Start ~Stop Frequency	9kHz~150kHz/RB 200Hz for QP	
Start ~Stop Frequency	150kHz~30MHz/RB 9kHz for QP	
Start ~Stop Frequency	30MHz~1000MHz/RB 120kHz for QP	

- The following is the test setup of Field Strength of Fundamental:
 - > Peak detection: RBW is greater than the main frequency OBW, VBW=50MHz / Sweep=AUTO
 - > Average detection: RBW is greater than the main frequency OBW, VBW=50MHz / Sweep=AUTO
- The following is the test setup of Band Edge:

The EUT operates at transmitting mode. The operate channel is tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.

- Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - > Peak detection: RBW=1MHz, VBW=3MHz / Sweep=AUTO
 - Average detection: RBW=1MHz; VBW=1/T / Sweep=AUTO (Duty cycle is less than 98%)
 - > Average detection: RBW=1MHz; VBW=3M / Sweep=AUTO
 - > Other procedures refer to clause 7.2.



• Quasi-Peak Measurements below 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. Span was set greater than 1MHz
- 3. RBW = as shown in the table above
- 4. Detector = CISPR quasi-peak
- 5. Sweep time = auto couple
- 6. Trace was allowed to stabilize

• Peak Measurements above 1GHz


- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize

• Average Measurements above 1GHz (Method VB)


- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW setting requirements are as follows:
- 4. If the EUT is configured to transmit with duty cycle \ge 98%, set VBW = 10 Hz.
- 5. If the EUT duty cycle is < 98%, set VBW \geq 1/T. T is the minimum transmission duration.
- 6. Detector = Peak
- 7. Sweep time = auto
- 8. Trace mode = max hold
- 8. Trace was allowed to stabilize




8.3 Measurement Setup (Block Diagram of Configuration)



Radiated Emission Test Setup 30MHz-1000MHz



Radiated Emission Test Setup Above 1000MHz





8.4 Measurement Result

EUT Name		Watch remote co	ntral					
Temperature		Watch remote control		Model Name		RC65		
Temperature		21.3 ℃		Relative Humic	Relative Humidity		62.4 %	
Pressure		960hPa		Test Voltage		Normal Vo	ltage	
Test Mode	Mode 1							
Peak Value								
Frequency M (MHz)		ured Level@3m (dBµV/m)	Correction Factor dB/m	Field Strength (dBµV/m)		t @3m µV/m)	Polarity	
2405		88.49	-10.06	98.55	11	4.00	Horizontal	
2405		84.29	-10.06	94.35	11	4.00	Vertical	
2440		88.32	-10.21	98.53	114.00		Horizontal	
2440		85.24	-10.21	95.45	11	4.00	Vertical	
2475		88.88	-10.59	99.47	11	4.00	Horizontal	
2475		86.10	-10.59	96.69	114.00		Vertical	
			Avera	ge Value				
Frequency M (MHz)		ured Level@3m (dBµV/m)	Correction Factor dB/m	Field Strength (dBµV/m)		t @3m µV/m)	Polarity	
2405		78.37	-10.06	88.43	9,	4.00	Horizontal	
2405		75.31	-10.06	85.37	94.00		Vertical	
2440		78.56	-10.21	88.77	94.00		Horizontal	
2440		75.74	-10.21	85.95	94.00		Vertical	
2475		79.33	-10.59	89.92	94.00		Horizontal	
2475		76.87	-10.59	87.46	94	4.00	Vertical	

Field Strength of Fundamental

RESULT: Pass


Note: Corr. Factor= Antenna Factor (dB/m) + Cable Loss (dB)



Radiated Emission Below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20dB below the permissible value need not be reported.

			Radia	ted Emiss	ion Test Res	ults at 30MHz	-1GHz			
EUT N	IT Name Watch remote contr			rol		Model Na	Model Name			
Tempe	erature	21.3°	°C			Relative H	lumidity	62.4%		
Press	ure	960h	Pa			Test Volta	ge	Normal Voltage		
Test M	lode	Mode	e 1			Antenna F	Polarity			
	130 120 110 100 90 80 70 60 50 40 30 20 10 0 	- QP Limit QP Detecto	- Horizontal PK	100M	FCC Part 150				16	
Final C	Data List									
NO.	Freq. [MHz		Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	
1	36.79	9	21.45	11.23	40.00	18.55	100	39	Horizontal	
2	60.07	7	23.73	17.86	40.00	16.27	100	328	Horizontal	
3	99.84	1	27.38	17.03	43.50	16.12	100	95	Horizontal	
4	141.5	5	26.39	16.13	43.50	17.11	100	179	Horizontal	
5	620.7	3	32.06	25.82	46.00	13.94	100	167	Horizontal	
6	890.3	9	35.87	29.84	46.00	10.13	100	127	Horizontal	





			Radia	ted Emiss	ion Test Resu	ults at 30MHz	-1GHz			
	lame	Watch	remote cont	rol		Model Na	me	RC65		
Temp	erature	21.3 ℃	1		Relative Humidity		62.4%			
Press	ure	960hF	'a			Test Volta	ge	Normal Voltage		
Test N	lode	Mode	1			Antenna F	Polarity	Vertical		
	130 120 110 90 80 70 60 90 80 40 30 20 10 0 -10 30M	- QP Limit QP Detector	Vertical PK	100M	FCC Part 15C				16	
Final [Data List									
NO.	Freq [MHz		Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	
NO. 1		:]							Polarity Vertical	
	[MHz	:] 5	[dBµV/m]	[dB]	[dBµV/m]	[dB]	[cm]	[°]	-	
1	[MHz 54.2	5 7	[dBµV/m] 27.53	[dB] 16.35	[dBµV/m] 40.00	[dB] 12.47	[cm] 100	[°] 133	Vertical	
1 2	[MHz 54.25 69.77	:] 5 7 1	[dBµV/m] 27.53 27.48	[dB] 16.35 14.73	[dBµV/m] 40.00 40.00	[dB] 12.47 12.52	[cm] 100 100	[°] 133 360	Vertical Vertical	
1 2 3	[MHz 54.25 69.77 100.8	:] 5 7 .1 .5	[dBµV/m] 27.53 27.48 37.27	[dB] 16.35 14.73 17.03	[dBµV/m] 40.00 40.00 43.50	[dB] 12.47 12.52 6.23	[cm] 100 100 100	[°] 133 360 4	Vertical Vertical Vertical	

RESULT: Pass

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Limit-Level.



UT Name	Watch remot	te control	Mod	el Name	RC65		
emperature	21.3 ℃		Rela	tive Humidity	62.4%)	
ressure	960hPa	960hPa		Test Voltage		Normal Voltage	
est Mode	Mode 1		Ante	nna Polarity	Horizo	ontal	
			l				
Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type	
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type	
4810.000	47.28	0.08	47.36	74	-26.64	peak	
4810.000	38.41	0.08	38.49	54	-15.51	AVG	
7215.000	41.56	2.21	43.77	74	-30.23	peak	
7215.000	31.39	2.21	33.6	54	-20.4	AVG	
Remark:			·				
	nna Factor + Cabl	e Loss – Pre-	amplifier.				
	nna Factor + Cable Watch remot			el Name	RC65		
Factor = Anter			Mod	el Name tive Humidity	RC65		
Factor = Anter	Watch remot		Mod Rela		62.4%		
Factor = Anter UT Name emperature	Watch remot		Mod Rela Test	tive Humidity	62.4%	al Voltage	
Factor = Anter	Watch remot 21.3℃ 960hPa Mode 1	te control	Mod Rela Test Ante	tive Humidity Voltage nna Polarity	62.4% Norma Vertic	al Voltage al	
Factor = Anter	Watch remot	te control Factor	Mod Rela Test Ante Emission Level	tive Humidity Voltage nna Polarity	62.4% Norma Vertic Margin	al Voltage al	
Factor = Anter	Watch remot	te control Factor (dB)	Mod Rela Test Ante Emission Level (dBµV/m)	tive Humidity Voltage mna Polarity Limits (dBµV/m)	62.4% Norma Vertica Margin (dB)	al Voltage al Value Type	
Factor = Anter	Watch remot	Factor (dB) 0.08	Mod Rela Test Ante Emission Level (dBµV/m) 47.85	tive Humidity Voltage mna Polarity Limits (dBµV/m) 74	62.4% 62.4% Norma Vertic Margin (dB) -26.15	al Voltage al Value Type peak	
Factor = Anter	Watch remot 21.3 ℃ 960hPa Mode 1 Meter Reading (dBµV) 47.77 38.51	Factor (dB) 0.08 0.08	Mod Rela Test Ante Emission Level (dBµV/m) 47.85 38.59	tive Humidity Voltage nna Polarity Limits (dBµV/m) 74 54	62.4% Norma Vertice Margin (dB) -26.15 -15.41	al Voltage al Value Type peak AVG	
Factor = Anter	Watch remote 21.3 °C 960hPa Mode 1 Meter Reading (dBμV) 47.77 38.51 42.48	te control Factor (dB) 0.08 0.08 2.21	Mod Relation Test Ante Emission Level (dBμV/m) 47.85 38.59 44.69	tive Humidity Voltage mna Polarity Limits (dBµV/m) 74 54 74	62.4% Norma Vertica Margin (dB) -26.15 -15.41 -29.31	al Voltage al Value Type peak	
Factor = Anter	Watch remot 21.3 ℃ 960hPa Mode 1 Meter Reading (dBµV) 47.77 38.51	Factor (dB) 0.08 0.08	Mod Rela Test Ante Emission Level (dBµV/m) 47.85 38.59	tive Humidity Voltage nna Polarity Limits (dBµV/m) 74 54	62.4% Norma Vertice Margin (dB) -26.15 -15.41	al Voltage al Value Type peak AVG peak	
Factor = Anter	Watch remote 21.3 °C 960hPa Mode 1 Meter Reading (dBμV) 47.77 38.51 42.48	te control Factor (dB) 0.08 0.08 2.21	Mod Relation Test Ante Emission Level (dBμV/m) 47.85 38.59 44.69	tive Humidity Voltage mna Polarity Limits (dBµV/m) 74 54 74	62.4% Norma Vertica Margin (dB) -26.15 -15.41 -29.31	al Voltage al Value Type peak AVG peak	

Radiated Emissions Test Results for Above 1GHz

RESULT: Pass



		Radiated Emissions Test Results for Above 1GHz	
--	--	--	--

EUT Name	Watch remote	e control		Mode	el Name	RC65		
Temperature	21.3 ℃	21.3℃ 960hPa			Relative Humidity Test Voltage		62.4%	
Pressure	960hPa						I Voltage	
Test Mode	Mode 2			Antenna Polarity		Horizontal		
Frequency	Meter Reading	Factor	Emission	n Level	Limits	Margin	Value Type	
(MHz)	(dBµV)	(dB)	(dBµV/	/m)	(dBµV/m)	(dB)	value Type	
4880.000	46.89	0.14	47.03	3	74	-26.97	peak	
4880.000	37.41	0.14	37.5	5	54	-16.45	AVG	
7320.000	42.36	2.36	44.72	2	74	-29.28	peak	
7320.000	32.52	2.36	34.8	8	54	-19.12	AVG	
	+ +							
Remark: Factor = Anter	nna Factor + Cable	e Loss – Pre-	amplifier.					
Factor = Anter	nna Factor + Cable Watch remote		amplifier.	Mode	el Name	RC65		
Factor = Anter			amplifier.	-	el Name ive Humidity	RC65 62.4%		
	Watch remote		amplifier.	Relat		62.4%	I Voltage	
Factor = Anter EUT Name Temperature Pressure	Watch remote 21.3℃		amplifier.	Relat	ive Humidity	62.4%	•	
Factor = Anter EUT Name Temperature Pressure	Watch remote 21.3℃ 960hPa		emplifier.	Relat Test Anter	ive Humidity Voltage	62.4% Norma		
Factor = Anter EUT Name Temperature Pressure Test Mode	Watch remote 21.3℃ 960hPa Mode 2	e control		Relat	ive Humidity Voltage nna Polarity	62.4% Norma Vertica	•	
Factor = Anter	Watch remote 21.3℃ 960hPa Mode 2 Meter Reading	e control	Emission	Relat Test ^v Anter Level [/] m)	ive Humidity Voltage nna Polarity Limits	62.4% Norma Vertica Margin		
Factor = Anter EUT Name Temperature Pressure Test Mode Frequency (MHz)	Watch remote 21.3℃ 960hPa Mode 2 Meter Reading (dBµV)	e control Factor (dB)	Emission (dBµV/	Relat Test Anter Level (m) 5	ive Humidity Voltage nna Polarity Limits (dBµV/m)	62.4% Norma Vertica Margin (dB)	l Value Type	
Factor = Anter EUT Name Temperature Pressure Test Mode Frequency (MHz) 4880.000	Watch remote 21.3℃ 960hPa Mode 2 Meter Reading (dBµV) 48.81	e control Factor (dB) 0.14	Emission (dBµV/ 48.9	Relat Test Anter Level /m) 5 9	ive Humidity Voltage nna Polarity Limits (dBµV/m) 74	62.4% Norma Vertica Margin (dB) -25.05	l 	
Factor = Anter EUT Name Temperature Pressure Test Mode Frequency (MHz) 4880.000 4880.000	Watch remote 21.3℃ 960hPa Mode 2 Meter Reading (dBµV) 48.81 38.45	e control Factor (dB) 0.14 0.14	Emission (dBµV/ 48.99 38.51	Relat Test Anter Level /m) 5 9 9	ive Humidity Voltage nna Polarity Limits (dBµV/m) 74 54	62.4% Norma Vertica Margin (dB) -25.05 -15.41	l 	
Factor = Anter EUT Name Temperature Pressure Test Mode Frequency (MHz) 4880.000 7320.000	Watch remote 21.3 °C 960hPa Mode 2 Meter Reading (dBµV) 48.81 38.45 42.23	E control Factor (dB) 0.14 0.14 2.36	Emission (dBµV/ 48.9 38.5 44.5	Relat Test Anter Level /m) 5 9 9	ive Humidity Voltage nna Polarity Limits (dBµV/m) 74 54 74	62.4% Norma Vertica Margin (dB) -25.05 -15.41 -29.41	l Value Type peak AVG peak	
Factor = Anter EUT Name Temperature Pressure Test Mode Frequency (MHz) 4880.000 7320.000	Watch remote 21.3 °C 960hPa Mode 2 Meter Reading (dBµV) 48.81 38.45 42.23	E control Factor (dB) 0.14 0.14 2.36	Emission (dBµV/ 48.9 38.5 44.5	Relat Test Anter Level /m) 5 9 9	ive Humidity Voltage nna Polarity Limits (dBµV/m) 74 54 74	62.4% Norma Vertica Margin (dB) -25.05 -15.41 -29.41	l Value Type peak AVG peak	

RESULT: Pass



EU	T Name	Watch rem	Watch remote control			Model Name		RC65		
Tei	nperature	21.3 ℃			Relativ	ve Humidity	62.4%	62.4%		
Pre	essure	960hPa			Test V	oltage	Normal V	Normal Voltage		
Test Mode		Mode 3			Anten	na Polarity	Horizonta	al		
		·		·						
	Frequency	Meter Reading	Factor	Emissio	n Level	Limits	Margin	Value Type		
	(MHz)	(dBµV)	(dB)	(dBµ\	V/m)	(dBµV/m)	(dB)	value Type		
	4950.000	47.45	0.22	47.6	67	74	-26.33	peak		
	4950.000	38.18	0.22	38.	.4	54	-15.6	AVG		
	7425.000	43.72	2.64	46.3	36	74	-27.64	peak		
	7425.000	41.63	2.64	44.2	27	54	-9.73	AVG		
	Remark:									
		na Factor + Ca	l ble Loss – Pre-a	amplifier.						
EU		na Factor + Cal		amplifier.	Model	Name	RC65			
	Factor = Anten			amplifier.		Name ve Humidity	RC65 62.4%			
Tei	Factor = Anten T Name	Watch rem		amplifier.	Relati			/oltage		
Tei Pre	Factor = Anten T Name nperature	Watch rem 21.3℃		amplifier.	Relati Test V	ve Humidity	62.4%	/oltage		
Tei Pre	Factor = Anten T Name mperature essure st Mode	Watch rem 21.3℃ 960hPa Mode 3			Relation Test V Anten	ve Humidity oltage na Polarity	62.4% Normal V Vertical	/oltage		
Tei Pre	Factor = Anten T Name mperature essure	Watch rem 21.3℃ 960hPa		Emissio	Relation Test V Anten	ve Humidity foltage na Polarity Limits	62.4%	 		
Tei Pre	Factor = Anten T Name mperature essure st Mode	Watch rem 21.3℃ 960hPa Mode 3	ote control		Relation Test V Anten	ve Humidity oltage na Polarity	62.4% Normal V Vertical	/oltage Value Type		
Tei Pre	Factor = Anten T Name nperature essure st Mode Frequency	Watch rem 21.3℃ 960hPa Mode 3 Meter Reading	ote control	Emissio	Relatin Test V Anten n Level	ve Humidity foltage na Polarity Limits	62.4% Normal V Vertical Margin	 		
Tei Pre	Factor = Anten T Name mperature essure st Mode Frequency (MHz)	Watch rem 21.3℃ 960hPa Mode 3 Meter Reading (dBµV)	ote control Factor (dB)	Emissio (dBµ\	Relatin Test V Anten n Level V/m) 91	ve Humidity oltage na Polarity Limits (dBµV/m)	62.4% Normal V Vertical Margin (dB)	Value Type		

Radiated Emissions Test Results for Above 1GHz

The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB 1. below the permissible value need not be reported.

34.09

54

-19.91

AVG

2. Factor = Antenna Factor + Cable loss – Pre-amplifier gain, Margin = Emission Level-Limit.

2.64

The "Factor" value can be calculated automatically by software of measurement system. 3.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

31.45

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

7425.000

Remark:

RESULT: Pass

Note:



Temperature21.3°CRelative Humidity62.4 %Pressure960hPaTest VoltageNormal Voltage	EUT Name	Watch remote control	Model Name	RC65
Pressure 960hPa Test Voltage Normal Voltage	Temperature	21.3 ℃	Relative Humidity	62.4 %
	Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode Mode 1 Antenna Polarity Horizontal	Test Mode	Mode 1	Antenna Polarity	Horizontal

		les	st Gr	aph for	Peak I	Measur	ement		
	ectrum Analyzer -								- 6 ×
K R T		0 Ω AC COI 00000 GHz	RREC	SENSE:I		ALIGN AUTO	09:38:46 AM Apr 23, TRACE 1 2 3		Frequency
Start Fre	q 2.37000	P	NO: Fast C	Trig: Free Ru	n Avg	Hold:>100/100		www	
		IF	Gain:Low	#Atten: 30 dB					Auto Tune
10 dB/div	Ref 126.	99 dBµV/m				Mkr	1 2.404 75 G 88.493 dBµV	HZ /m	Auto Tune
Log									
117									Center Fred
107									2.390000000 GH
97.0							↓	_	
87.0									Start Free
77.0							74.00 4)µVin	2.370000000 GHz
67.0				2				_	
57.0				Q ²					Stop Fred
47.0 47.0 47.0	depeters down	- Minor de same de same	and the second						2.41000000 GHz
37.0									2.410000000 GHz
	7000 GHz 1.0 MHz		#VB	W 3.0 MHz		Sween 1	Stop 2.41000 C .066 ms (1000	SHZ hte)	CF Step 4.000000 MHz
			# U B		SUNCTION				Auto Mar
MKR MODE T	1 f	× 2.404 7	5 GHz	Y 88.493 dBuV/m	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	Â.	
2 N	1 f	2.390 0 2.400 0	0 GHz	53.077 dBµV/m 62.362 dBµV/m					Freq Offset
4 N		2.400 0	UGHZ	62.362 dBµV/m					0 Hz
5								E	
7									
8									
10									
								P	
NEC						CTATU	2		

Test Graph for Peak Measurement

Test Graph for Average Measurement



RESULT: Pass



	5		
EUT Name	Watch remote control	Model Name	RC65
Temperature	21.3 ℃	Relative Humidity	62.4 %
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna Polarity	Vertical



Test Graph for Peak Measurement


Test Graph for Average Measurement




RESULT: Pass



EUT Name	Watch remote control	Model Name	RC65
Temperature	21.3℃	Relative Humidity	62.4 %
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna Polarity	Horizontal
	T (0) (D)	N 4 1	




Test Graph for Average Measurement



RESULT: Pass



EUT Name	Watch remote control	Model Name	RC65
Temperature	21.3 ℃	Relative Humidity	62.4 %
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna Polarity	Vertical
	T (0) (D)		•



Test Graph for Average Measurement



RESULT: Pass

Note: 1) Factor=Antenna Factor + Cable loss - Amplifier gain. Field Strength=Factor + Reading level

2) The factor had been edited in the "Input Correction" of the Spectrum Analyzer. So the Amplitude of test plots is equal to Reading level plus the Factor in dB. Use the A dB(μ V) to represent the Amplitude. Use the F dB(μ V/m) to represent the Field Strength. So A=F.



9. AC Power Line Conducted Emission

9.1 Measurement Limit


Frequency	Maximum RF Line Voltage				
Frequency	Q.P. (dBµV)	Average (dBµV)			
150kHz~500kHz	66-56	56-46			
500kHz~5MHz	56	46			
5MHz~30MHz	60	50			

Note:

1. The lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

9.2 Measurement Setup (Block Diagram of Configuration)





9.3 Preliminary Procedure of Line Conducted Emission Test

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

9.4 Final Procedure of Line Conducted Emission Test

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less – 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

9.5 Measurement Resul

N/A

Note: This device is not AC powered and does not require this test.



Report No.: AGC15705240450FR01 Page 36 of 36

Appendix I: Photographs of Test Setup

Refer to the Report No.: AGC15705240450AP01

Appendix II: Photographs of Test EUT

Refer to the Report No.: AGC15705240450AP02

-----End of Report-----



Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.