



TEST REPORT

Report Number: 14282062-E1V2

Applicant : APPLE, INC
1 APPLE PARK WAY
CUPERTINO, CA 95014, U.S.A.

Model : A2893, A2894, A2895, A2896

Brand : APPLE

FCC ID : BCG-E8154A, BCG-E8155A, BCG-E8156A

EUT Description : SMARTPHONE

Test Standard(s) : FCC CFR47 PART 2, 22H, 24E, 27, 90S, 90R, AND 96

Date Of Issue:
AUGUST 18, 2022

Prepared by:
UL Verification Services Inc.
47173 Benicia Street
Fremont, CA 94538, U.S.A.
TEL: (510) 319-4000
FAX: (510) 661-0888






Revision History

Rev.	Issue Date	Revisions	Revised By
V1	7/14/2022	Initial Review	Mengsitu Mekuria
V2	8/18/2022	Updated Section 5.1, 5.3 and 5.7	Binod Sitaula

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	4
2. TEST METHODOLOGY	5
3. FACILITIES AND ACCREDITATION	5
4. DECISION RULES AND MEASUREMENT UNCERTAINTY	6
4.1. METROLOGICAL TRACEABILITY	6
4.2. DECISION RULES	6
4.3. MEASUREMENT UNCERTAINTY	6
4.4. SAMPLE CALCULATION	6
5. INTRODUCTION OF TEST DATA REUSE	7
5.1. DESCRIPTION OF EUT	7
5.2. INTRODUCTION	7
5.3. MODEL DIFFERENCES	7
5.4. SPOT CHECK VERIFICATION RESULTS SUMMARY FOR A2893	8
5.5. SPOT CHECK VERIFICATION RESULTS SUMMARY FOR A2894	9
5.6. SPOT CHECK VERIFICATION RESULTS SUMMARY FOR A2895 AND A2896	10
REFERENCE DETAIL	11
5.7. SOFTWARE AND FIRMWARE	11
5.8. SPOT CHECK WORST-CASE CONFIGURATION AND MODE	11
5.9. DESCRIPTION OF TEST SETUP	12
6. TEST AND MEASUREMENT EQUIPMENT	14
Appendix A – Reference Test Report	15

1. ATTESTATION OF TEST RESULTS

Applicant Name and Address	APPLE, INC 1 APPLE PARK WAY CUPERTINO, CA 95014, U.S.A.	
Model	A2893, A2894, A2895, A2896	
Brand	APPLE	
FCC ID	BCG-E8154A, BCG-E8155A, BCG-E8156A	
EUT Description	SMARTPHONE	
Serial Number	A2893(J63VN2LFJ6), A2894(FWC0DV6K0P), A2895/A2896(F23CTXJ0HN) (Conducted) and A2893(FDYDVQH3C9), A2894(D4YFNP62Y3), A2895/A2896(WP6G04P4N3) (Radiated)	
Sample Receipt date	APRIL 29, 2022	
Date Tested	MAY 07, 2022 to JUNE 21, 2022	
Applicable Standards	FCC CFR47 2, 22H, 24E, 27, 90S, 90R, AND 96	
Test Results	COMPLIES	
<p>UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.</p> <p>The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.</p> <p>This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by A2LA, NIST, any agency of the Federal Government, or any agency of the U.S. government.</p>		
Approved & Released By:	Reviewed By:	Prepared By:
		
Mengistu Mekuria Staff Engineer UL LLC.	Tewodros Woldemichael Laboratory Engineer UL LLC.	Binod Sitaula Laboratory Engineer UL LLC.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with the following:

- ANSI C63.26:2015
- FCC CFR 47 Part 2, Part 22, Part 24, Part 27, Part 90, and Part 96
- [FCC KDB 971168 D01 v03r01](#): Power Meas License Digital Systems
- [FCC KDB 971168 D02 v02r01](#): Misc Rev Approv License Devices
- [FCC KDB 412172 D01 v01r01](#): Determining ERP and EIRP

3. FACILITIES AND ACCREDITATION

UL Verification Services Inc. is accredited by A2LA, certification #0751.05, for all testing performed within the scope of this report. Testing was performed at the locations noted below.

	Address	ISED CABID	ISED Company Number	FCC Registration
<input checked="" type="checkbox"/>	Building 1: 47173 Benicia Street, Fremont, CA 94538, USA	US0104	2324A	550739
<input checked="" type="checkbox"/>	Building 2: 47266 Benicia Street, Fremont, CA 94538, USA	US0104	22541	550739
<input type="checkbox"/>	Building 4: 47658 Kato Rd, Fremont, CA 94538, USA	US0104	2324B	550739

4. DECISION RULES AND MEASUREMENT UNCERTAINTY

4.1 METROLOGICAL TRACEABILITY

All test and measuring equipment utilized to perform the tests documented in this report are calibrated on a regular basis, with a maximum time between calibrations of one year or the manufacturers' recommendation, whichever is less, and where applicable is traceable to recognized national standards.

4.2 DECISION RULES

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4:2012 Clause 8.2. (Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

4.3 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	U _{Lab}
Worst Case Radiated Disturbance, 9KHz to 30 MHz	2.87 dB
Worst Case Radiated Disturbance, 30 to 1000 MHz	6.01 dB
Worst Case Radiated Disturbance, 1000 to 18000 MHz	4.73 dB
Worst Case Radiated Disturbance, 18000 to 26000 MHz	4.51 dB
Worst Case Radiated Disturbance, 26000 to 40000 MHz	5.29 dB
Occupied Channel Bandwidth	±1.22 %
Temperature	±2.26%
Supply voltages	±0.57 %
Time	±3.39 %

Uncertainty figures are valid to a confidence level of 95%.

4.4 SAMPLE CALCULATION

RADIATED EMISSIONS

Where relevant, the following sample calculation is provided:

Field Strength (dBuV/m) = Measured Voltage (dBuV) + Antenna Factor (dB/m) + Cable Loss (dB) – Preamp Gain (dB)
36.5 dBuV + 18.7 dB/m + 0.6 dB – 26.9 dB = 28.9 dBuV/m

5. INTRODUCTION OF TEST DATA REUSE

5.1 DESCRIPTION OF EUT

The Apple iPhone is a smartphone with multimedia functions (music, application support, and video), cellular GSM, GPRS, EGPRS, UMTS, LTE, 5G FR1, IEEE 802.11a/b/g/n/ac/ax, Bluetooth, Ultra-Wideband, GPS, NFC and MSS. All models except reference model support at least one UICC based SIM. The second SIM is either an UICC based p-SIM (physical SIM) or e-SIM (electronic SIM). The device supports a built-in inductive charging transmitter and receiver. The rechargeable battery is not user accessible.

Testing was performed on the parent model and is used to support the application for the parent and variants identified in this report based on the test plan submitted and approved via KDB inquiry by the FCC.

5.2 INTRODUCTION

This application for certification is leveraging the data reuse procedures from KDB 484596 D01 based on reference FCC ID: BCG-E8141A to cover variant model FCC ID: BCG-E8154A, BCG-E8155A, and BCG-E8156A. The major difference between the parent/reference model and the variant model is the depopulation in the variant model of the mmWave transmitter, and some LTE and 5G NR Bands. All other circuitry and features are identical. The data reuse test plan was approved via manufacturer KDB inquiry.

5.3 MODEL DIFFERENCES

The manufacturer hereby declares the following for models A2651, A2893, A2894, A2895, A2896.

A2651, A2893, A2894, A2895, and A2896 are highly similar, with the only differences being listed on the table below:

Model	FCC ID	Model Changes
A2651	BCG-E8141A	Reference model
A2893	BCG-E8154A	Variant model. Removed FR2 from the reference model.
A2894	BCG-E8155A	Variant model. Removed FR2, LTE B11/14/29/71, and 5G NR n14/n71 from the reference model.
A2895/A2896	BCG-E8156A	Variant model. Removed FR2, LTE B11/14/29/53/71, and 5G NR n14/n53/n71 from the reference model.

*Note:

They have the same PCB layout, design, common components, antennas, antenna locations and housing cases.

More specifically, their cellular modem, Wi-Fi, BT, NFC, WPT and UWB transmitters are identical, and removal of cellular bands is done by software and depopulation of band-specific components associated with the removed bands.

Spot check verification has been done on models A2893, A2894, and A2895/A2896 in accordance with the test plan approved via KDB inquiry. Comparison of the models, upper deviation is within 3dB range and all tests are under FCC Technical Limits. The results documented for model A2651 may be applied as representative to models A2893, A2894, and A2895/2896.

5.4 SPOT CHECK VERIFICATION RESULTS SUMMARY FOR A2893

A2893 SPOT CHECK RESULTS							
Technology	Worst Mode	Test Item	Measured	Original Model: A2651	Sub Model: A2893	Delta (dB)	Remarks
			Frequency (MHz)	FCC ID: BCG-E8141A (dBm)	FCC ID: BCG-E8154A (dBm)		
LTE BAND 5	QPSK @ 10 MHz BW	Cond Power	824-849	25.70	25.70	0	
5G NR BAND N5	QPSK @ 20 MHz BW	Cond Power	824-849	25.70	25.70	0	
	QPSK @ highest BW			-48.15	-49.06	-0.91	Noise Floor
LTE BAND 7	QPSK @ 20 MHz BW	Cond Power	2500-2570	25.70	25.70	0	
	QPSK @ highest BW	RSE		-41.98	-41.58	0.4	Noise Floor
5G NR BAND N7	BPSK @ 20 MHz BW	Cond Power	2500-2570	25.70	25.70	0	
LTE BAND 12	QPSK @ 10 MHz BW	Cond Power	699-716	25.70	25.70	0	
5G NR BAND N12	QPSK @ 15 MHz BW	Cond Power	699-716	25.70	25.70	0	
LTE BAND 13	QPSK @ 10 MHz BW	Cond Power	777-787	25.70	25.70	0	
LTE BAND 14	QPSK @ 10 MHz BW	Cond Power	788-798	25.70	25.70	0	
5G NR BAND N14	QPSK @ 10 MHz BW	Cond Power	788-798	25.70	25.70	0	
LTE BAND 17	QPSK @ 10 MHz BW	Cond Power	704-716	25.70	25.70	0	
LTE BAND 25	QPSK @ 20 MHz BW	Cond Power	1850-1915	25.70	25.70	0	
	QPSK @ highest BW	RSE		-48.83	-49.41	-0.58	Noise Floor
5G NR BAND N25	QPSK @ 20 MHz BW	Cond Power	1850-1915	25.70	25.70	0	
LTE BAND 26 (90S)	QPSK @ 10 MHz BW	Cond Power	814-824	25.70	25.70	0	
5G NR BAND N26 (90S)	QPSK @ 10 MHz BW	Cond Power	814-824	25.70	25.70	0	
LTE BAND 30	QPSK @ 10 MHz BW	Cond Power	2305-2315	25.20	25.20	0	
5G NR BAND N30	QPSK @ 5 MHz BW	Cond Power	2305-2315	25.20	25.20	0	
LTE BAND 41	16QAM @ 20 MHz BW	Cond Power	2496-2690	28.70	28.70	0	
5G NR BAND N41	BPSK @ 100 MHz BW	Cond Power	2496-2690	28.70	28.70	0	Ant2
LTE BAND 48	QPSK @ 20 MHz BW	Cond Power	3550-3700	26.00	26.00	0	Ant9
		RSE		-44.08	-40.99	3.09	Noise Floor
LTE BAND 66	QPSK @ 20 MHz BW	Cond Power	1710-1780	25.70	25.70	0	
5G NR BAND N66	BPSK @ 20 MHz BW	Cond Power	1710-1780	25.70	25.70	0	
5G NR BAND n70	QPSK @ 20 MHz BW	Cond Power	1695-1710	25.70	25.70	0	
LTE BAND 71	QPSK @ 20 MHz BW	Cond Power	663-698	25.70	25.70	0	
5G NR BAND n71	BPSK @ 20 MHz BW	Cond Power	663-698	25.70	25.70	0	
5G NR BAND N77	BPSK @ 100 MHz BW	Cond Power	3450-3550	28.70	28.70	0	Ant7
5G NR BAND N77	BPSK @ 100 MHz BW	Cond Power	3700-3980	28.70	28.70	0	Ant7

5.5 SPOT CHECK VERIFICATION RESULTS SUMMARY FOR A2894

A2894 SPOT CHECK RESULTS							
Technology	Worst Mode	Test Item	Measured	Original Model: A2651	Sub Model: A2894	Delta (dB)	Remarks
			Frequency (MHz)	FCC ID: BCG-E8141A (dBm)	FCC ID: BCG-E8155A (dBm)		
LTE BAND 5	QPSK @ 10 MHz BW	Cond Power	824-849	25.70	25.70	0	
5G NR BAND N5	QPSK @ 20 MHz BW	Cond Power	824-849	25.70	25.70	0	
	QPSK @ highest BW			-48.15	-52.6	-4.45	Noise Floor
LTE BAND 7	QPSK @ 20 MHz BW	Cond Power	2500-2570	25.70	25.70	0	
	QPSK @ highest BW	RSE		-41.98	-43.51	-1.53	Noise Floor
5G NR BAND N7	BPSK @ 20 MHz BW	Cond Power	2500-2570	25.70	25.70	0	
LTE BAND 12	QPSK @ 10 MHz BW	Cond Power	699-716	25.70	25.70	0	
5G NR BAND N12	QPSK @ 15 MHz BW	Cond Power	699-716	25.70	25.70	0	
LTE BAND 13	QPSK @ 10 MHz BW	Cond Power	777-787	25.70	25.70	0	
LTE BAND 17	QPSK @ 10 MHz BW	Cond Power	704-716	25.70	25.70	0	
LTE BAND 25	QPSK @ 20 MHz BW	Cond Power	1850-1915	25.70	25.70	0	
	QPSK @ highest BW	RSE		-48.83	-48.77	0.06	Noise Floor
5G NR BAND N25	QPSK @ 20 MHz BW	Cond Power	1850-1915	25.70	25.70	0	
LTE BAND 26 (90S)	QPSK @ 10 MHz BW	Cond Power	814-824	25.70	25.70	0	
5G NR BAND N26 (90S)	QPSK @ 10 MHz BW	Cond Power	814-824	25.70	25.70	0	
LTE BAND 30	QPSK @ 10 MHz BW	Cond Power	2305-2315	25.20	25.20	0	
5G NR BAND N30	QPSK @ 5 MHz BW	Cond Power	2305-2315	25.20	25.20	0	
LTE BAND 41	16QAM @ 20 MHz BW	Cond Power	2496-2690	28.70	28.70	0	
5G NR BAND N41	BPSK @ 100 MHz BW	Cond Power	2496-2690	28.70	28.70	0	Ant2
LTE BAND 48	QPSK @ 20 MHz BW	Cond Power	3550-3700	26.00	26.00	0	Ant9
		RSE		-44.08	-39.41	4.67	Noise Floor
LTE BAND 66	QPSK @ 20 MHz BW	Cond Power	1710-1780	25.70	25.70	0	
5G NR BAND N66	BPSK @ 20 MHz BW	Cond Power	1710-1780	25.70	25.70	0	
5G NR BAND n70	QPSK @ 20 MHz BW	Cond Power	1695-1710	25.70	25.70	0	
5G NR BAND N77	BPSK @ 100 MHz BW	Cond Power	3450-3550	28.70	28.70	0	Ant7
5G NR BAND N77	BPSK @ 100 MHz BW	Cond Power	3700-3980	28.70	28.70	0	Ant7

5.6 SPOT CHECK VERIFICATION RESULTS SUMMARY FOR A2895 AND A2896

A2895 AND A2896 SPOT CHECK RESULTS							
Technology	Worst Mode	Test Item	Measured	Original Model: A2651	Sub Model: A2895 AND A2896	Delta (dB)	Remarks
			Frequency (MHz)	FCC ID: BCG-E8141A (dBm)	FCC ID: BCG-E8156A (dBm)		
LTE BAND 5	QPSK @ 10 MHz BW	Cond Power	824-849	25.70	25.70	0	
5G NR BAND N5	QPSK @ 20 MHz BW	Cond Power	824-849	25.70	25.70	0	Noise Floor
	QPSK @ highest BW			-48.15	-53.02	-4.87	
LTE BAND 7	QPSK @ 20 MHz BW	Cond Power	2500-2570	25.70	25.70	0	Noise Floor
	QPSK @ highest BW	RSE		-41.98	-46.45	3.53	
5G NR BAND N7	BPSK @ 20 MHz BW	Cond Power	2500-2570	25.70	25.70	0	
LTE BAND 12	QPSK @ 10 MHz BW	Cond Power	699-716	25.70	25.70	0	
5G NR BAND N12	QPSK @ 15 MHz BW	Cond Power	699-716	25.70	25.70	0	
LTE BAND 13	QPSK @ 10 MHz BW	Cond Power	777-787	25.70	25.70	0	
LTE BAND 17	QPSK @ 10 MHz BW	Cond Power	704-716	25.70	25.70	0	
LTE BAND 25	QPSK @ 20 MHz BW	Cond Power	1850-1915	25.70	25.70	0	Noise Floor
	QPSK @ highest BW	RSE		-48.83	-47.45	-1.38	
5G NR BAND N25	QPSK @ 20 MHz BW	Cond Power	1850-1915	25.70	25.70	0	
LTE BAND 26 (90S)	QPSK @ 10 MHz BW	Cond Power	814-824	25.70	25.70	0	
5G NR BAND N26 (90S)	QPSK @ 10 MHz BW	Cond Power	814-824	25.70	25.70	0	
LTE BAND 30	QPSK @ 10 MHz BW	Cond Power	2305-2315	25.20	25.20	0	
5G NR BAND N30	QPSK @ 5 MHz BW	Cond Power	2305-2315	25.20	25.20	0	
LTE BAND 41	16QAM @ 20 MHz BW	Cond Power	2496-2690	28.70	28.70	0	
5G NR BAND N41	BPSK @ 100 MHz BW	Cond Power	2496-2690	28.70	28.70	0	Ant2
LTE BAND 48	QPSK @ 20 MHz BW	Cond Power	3550-3700	26.00	26.00	0	Ant9
		RSE		-44.08	-40.27	3.81	Noise Floor
LTE BAND 66	QPSK @ 20 MHz BW	Cond Power	1710-1780	25.70	25.70	0	
5G NR BAND N66	BPSK @ 20 MHz BW	Cond Power	1710-1780	25.70	25.70	0	
5G NR BAND n70	QPSK @ 20 MHz BW	Cond Power	1695-1710	25.70	25.70	0	
5G NR BAND N77	BPSK @ 100 MHz BW	Cond Power	3450-3550	28.70	28.70	0	Ant7
5G NR BAND N77	BPSK @ 100 MHz BW	Cond Power	3700-3980	28.70	28.70	0	Ant7

5.7 REFERENCE DETAIL

Reference application that contains the reused reference data.

Equipment Class	Reference FCC ID	Reference Application	Variant model FCC ID	Report Title/Section
PCE, CBE, TNE	BCG-E8141A	14040866-E8	BCG-E8154A	FCC LTE Report / All Sections
PCE, CBE, TNE			BCG-E8155A	FCC LTE Report / All Sections except LTE/5G NR Band B14/71 sections
PCE, CBE			BCG-E8156A	FCC LTE Report / All Sections except LTE/5G NR Band B14/71 sections

5.8 SOFTWARE AND FIRMWARE

The EUT firmware installed during testing was version 0.15.02.


5.9 SPOT CHECK WORST-CASE CONFIGURATION AND MODE

The spot checks were performed on the worst-case orientations and configurations based on the parent model of reference report.


5.10 DESCRIPTION OF TEST SETUP

SUPPORT TEST EQUIPMENT						
Description		Manufacturer	Model	Serial Number		FCC ID/ DoC
Laptop		Apple	MacBook Pro	HRP082673		BCGA1708
AC/DC adapter		Apple	A1718	C4H64450HH3GN8RA6		--
I/O CABLES (RF CONDUCTED TEST)						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	AC	3	US 115V	Un-shielded	2.0	N/A
2	USB	1	DC	Un-shielded	1.0	N/A
3	RF In/Out	1	EUT	Un-shielded	0.6	N/A
4	RF In/Out	1	Communication Test Set	Un-shielded	1.2	N/A
5	RF In/Out	1	Barrel	N/A	N/A	N/A
I/O CABLES (RF RADIATED TEST)						
Cable No.	Port	# of Identical Ports	Connector Type	Cable Type	Cable Length (m)	Remarks
1	RF In/Out	1	Antenna	Un-shielded	5.0	N/A

CONDUCTED SETUP



RADIATED SETUP



6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

TEST EQUIPMENT LIST				
Description	Manufacturer	Model	Asset	Cal Due
*Antenna, Horn 1-18GHz	ETS Lindgren	3117	79834	06/14/2222
*Antenna, Horn 1-18GHz	ETS Lindgren	3117	80403	06/13//2022
Antenna, Broadband Hybrid, 30MHz to 2000MHz	Sunol Sciences	JB3	85151	03/21/2023
*Amplifier, 1 to 18GHz	Miteq	AFS42-00101800-25-S-42	T1165	06/12/2022
Spectrum Analyzer, PXA 3Hz to 44GHz	Keysight	N9030A	85212	0/30/2023
Spectrum Analyzer, PSA, 3Hz to 44GHz	Keysight	N9030A	85213	01/19/2023
Spectrum Analyzer, PSA, 3Hz to 44GHz	Keysight	N9030A	125178	01/24/2023
Spectrum Analyzer, PXA, 3Hz to 44GHz	Keysight	N9030A	85201	02/01/2023
Spectrum Analyzer, PXA, 3Hz to 44GHz	Keysight	N9030A	85214	02/02/2023
Spectrum Analyzer, PXA 3Hz to 44GHz	Keysight	N9030A	80400	02/01/2023
Spectrum Analyzer, PXA 3Hz to 44GHz	Keysight	N9030A	80397	02/01/2023
Spectrum Analyzer, PXA, 3Hz to 50GHz w/Ext. Mixer	Keysight	N9030A	T342	02/01/2023
Spectrum Analyzer, PSA 3Hz to 44GHz	Keysight	E4440A	81311	02/02/2023
Directional Coupler	KRYTAR	152610	T1161	09/23/2022
Directional Coupler	KRYTAR	152610	T1536	09/23/2022
Directional Coupler	KRYTAR	152610	T1537	09/23/2022
Power Meter, P-series single channel	Keysight	N1912A	90630	01/24/2023
Power Meter, P-series single channel	Keysight	N1912A	90719	01/24/2023
Power Meter, P-series single channel	Agilent	N1911A	82174	01/24/2023
Power Sensor, P – series, 50MHz to 18GHz, Wideband	Keysight	N1921A	90389	01/25/2023
Filter, HPF 1.2GHz	Micro-Tronics	152043	152043	7/29/2022
Filter, BRF 1850 – 1910 MHz	Micro-Tronics	155055	155055	12/20/2022
Filter, BRF 2495 – 2690 MHz	Micro-Tronics	155050	155055	7/30/2022
Filter, BRF 3.4 – 3.8GHz	Micro-Tronics	208398	208398	7/30/2022
Spectrum Analyzer, PXA, 3Hz to 44GHz	Keysight	N9030A	80397	02/01/2023
Wideband Communication Test Set, Call Box	R&S GmbH & Co. KG	CMW500	85827	02/21/2023
Wideband Communication Test Set, Call Box	R&S GmbH & Co. KG	CMW500	80105	02/21/2023
Wideband Communication Test Set, Call Box	R&S GmbH & Co. KG	CMW500	159994	02/23/2023
Wideband Communication Test Set, Call Box	R&S GmbH & Co. KG	CMW500	85806	02/22/2023
Wideband Communication Test Set, Call Box	R&S GmbH & Co. KG	CMW500	85943	02/20/2023
Amplifier, 218GHz to 26.5GHz	Ampical	AMP18G26.5-60	215705	02/26/2023
Amplifier, 26.5GHz to 40GHz	Ampical	AMP26G40-65	172346	02/01/2023
Antenna, Horn 18 to 26.5GHz	ARA	MWH-1826/B	172362	02/09/2023
Antenna, Horn 26.5GHz to 40GHz	ARA	MWH-2640/B	172365	03/08/2023
Antenna, Active Loop 9KHz to 30MHz	EMCO	6502	T35	10/05/2022
UL AUTOMATION SOFTWARE				
CLT Software	UL	UL RF	Ver 3.4, May 20, 2022	
Power Measurement Software	UL	UL RF	Ver 3.1.4, April 29, 2022	
Radiated test software	UL	UL RF	Ver 9.5, Jan 21, 2022	

NOTES:

* Testing is completed before equipment expiration date.

Appendix A – Reference Test Report

Attached is the test report (14040866-E8) containing the reference data from the parent model as detailed in section 5.7.