

FCC SAR EVALUATION REPORT

**In accordance with the requirements of
FCC 47 CFR Part 2(2.1093), ANSI/IEEE C95.1-1992 and
IEEE Std 1528-2013**

Product Name : Mobile Phone

Trademark : ulefone

Model Name : GQ3087

Family Model : Armor X7, Armor X7S, Armor X7E, Armor
X7P, Armor X7A, Armor X7T, Armor X7 Pro,
Armor X7 lite, Armor X7 Plus

Report No. : STR191125001001E

FCC ID : 2AOWKGQ3087

Prepared for

Shenzhen Gotron Electronic CO.,LTD.
518, 5F, R&D building, Tsinghua Hi-Tech park, Nanshan district,
Shenzhen 518057 P.R.China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.
1/F, Building E, Fenda Science Park Sanwei, Xixiang, Bao'an District,
Shenzhen, Guangdong, China
Tel.: +86-755-6115 6588 Fax.: +86-755-6115 6599
Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION**Applicant's name**.....: Shenzhen Gotron Electronic CO.,LTD.Address.....: 518, 5F, R&D building, Tsinghua Hi-Tech park, Nanshan district,
Shenzhen 518057 P.R.China**Manufacturer's Name**.....: Shenzhen Gotron Electronic CO.,LTD.Address.....: 518, 5F, R&D building, Tsinghua Hi-Tech park, Nanshan district,
Shenzhen 518057 P.R.China**Product description**

Product name.....: Mobile Phone

Trademark.....: ulefone

Model Name.....: GQ3087

Family Model.....: Armor X7, Armor X7S, Armor X7E, Armor X7P, Armor X7A, Armor
X7T, Armor X7 Pro, Armor X7 lite, Armor X7 Plus
FCC 47 CFR Part 2(2.1093)

Standards.....: ANSI/IEEE C95.1-1992

IEEE Std 1528-2013

Published RF exposure KDB procedures


This device described above has been tested by Shenzhen NTEK. In accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 and KDB 865664 D01. Testing has shown that this device is capable of compliance with localized specific absorption rate (SAR) specified in FCC 47 CFR Part 2(2.1093) and ANSI/IEEE C95.1-1992. The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK, this document may be altered or revised by Shenzhen NTEK, personal only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests.....: Nov. 30, 2019 ~ Dec. 15, 2019

Date of Issue.....: Mar. 16, 2020

Test Result.....: **Pass**Prepared By
(Test Engineer): 
(Cheng Jiawen)Approved By
(Lab Manager): 
(Sam Chen)

※ ※ Revision History ※ ※

REV.	DESCRIPTION	ISSUED DATE	REMARK
Rev.1.0	Initial Test Report Release	Mar. 16, 2020	Cheng Jiawen

TABLE OF CONTENTS

1. General Information	6
1.1. RF exposure limits.....	6
1.2. Statement of Compliance	7
1.3. EUT Description	7
1.4. Test specification(s)	10
1.5. Ambient Condition.....	10
2. SAR Measurement System	11
2.1. SATIMO SAR Measurement Set-up Diagram	11
2.2. Robot	12
2.3. E-Field Probe.....	13
2.3.1. E-Field Probe Calibration	13
2.4. SAM phantoms	14
2.4.1. Technical Data	15
2.5. Device Holder	16
2.6. Test Equipment List	17
3. SAR Measurement Procedures	19
3.1. Power Reference	19
3.2. Area scan & Zoom scan.....	19
3.3. Description of interpolation/extrapolation scheme	21
3.4. Volumetric Scan	21
3.5. Power Drift	21
4. System Verification Procedure	22
4.1. Tissue Verification	22
4.1.1. Tissue Dielectric Parameter Check Results	23
4.2. System Verification Procedure	24
4.2.1. System Verification Results	24
5. SAR Measurement variability and uncertainty	26
5.1. SAR measurement variability.....	26
5.2. SAR measurement uncertainty	26
6. RF Exposure Positions	27
6.1. Ear and handset reference point	27
6.2. Definition of the cheek position	27
6.3. Definition of the tilt position	29
6.4. Body Worn Accessory	29
6.5. Wireless Router Devices	30
7. RF Output Power	31
7.1. GSM Conducted Power	31
7.2. WCDMA Conducted Power	31
7.3. LTE Conducted Power	33

7.4. WLAN & Bluetooth Output Power	45
7.4.1. Output Power Results Of WLAN	45
7.4.2. Output Power Results Of Bluetooth.....	46
8. Antenna Location.....	47
9. Stand-alone SAR test exclusion.....	48
10. SAR Results	49
10.1. SAR measurement results	49
10.1.1. SAR measurement Result of GSM850	49
10.1.2. SAR measurement Result of GSM1900.....	50
10.1.3. SAR measurement Result of WCDMA Band 2	51
10.1.4. SAR measurement Result of WCDMA Band 4	52
10.1.5. SAR measurement Result of WCDMA Band 5	53
10.1.6. SAR measurement Result of LTE Band 2	54
10.1.7. SAR measurement Result of LTE Band 4	56
10.1.8. SAR measurement Result of LTE Band 5	57
10.1.9. SAR measurement Result of LTE Band 7	60
10.1.10. SAR measurement Result of LTE Band 12	62
10.1.11. SAR measurement Result of LTE Band 17	63
10.1.12. SAR measurement Result of WLAN 2.4G	65
10.1.13. SAR measurement Result of WLAN 5.2G	66
10.1.14. SAR measurement Result of WLAN 5.8G	67
10.2. SAR Summation Scenario.....	67
11. Appendix A. Photo documentation	86
12. Appendix B. System Check Plots.....	87
13. Appendix C. Plots of High SAR Measurement.....	120
14. Appendix D. Calibration Certificate	177

1. General Information

1.1. RF exposure limits

(A).Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B).Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

NOTE: **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. **SAR for hands, wrists, feet and ankles** is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

General Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

NOTE
HEAD AND TRUNK LIMIT
1.6 W/kg
APPLIED TO THIS EUT

1.2. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for GQ3087 are as follows.

Band	Max Reported SAR Value(W/kg)			
	1-g Head	1-g Body-Worn (Separation distance of 10mm)	1-g Hotspot (Separation distance of 10mm)	Max Simultaneous Tx
GSM 850	1.129	1.121	1.121	1.597
GSM 1900	1.183	0.748	0.748	
WCDMA Band 2	0.902	0.700	0.700	
WCDMA Band 4	0.749	0.465	0.465	
WCDMA Band 5	0.739	0.929	0.929	
LTE Band 2	0.797	1.188	1.188	
LTE Band 4	0.708	0.415	0.415	
LTE Band 5	0.780	0.979	0.979	
LTE Band 7	1.194	0.798	0.798	
LTE Band 12	0.541	0.786	0.786	
LTE Band 17	0.421	0.672	0.672	
WLAN 2.4G	0.403	0.130	0.130	
WLAN 5.2G	0.305	0.235	0.235	
WLAN 5.8G	0.396	0.360	0.360	

Note: The Max Simultaneous Tx is calculated based on the same configuration and test position. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR Part 2(2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE Std 1528-2013 & KDB 865664 D01.

1.3. EUT Description

Device Information	
Product Name	Mobile Phone
Trade Name	ulefone
Model Name	GQ3087
Family Model	Armor X7, Armor X7S, Armor X7E, Armor X7P, Armor X7A, Armor X7T, Armor X7 Pro, Armor X7 lite, Armor X7 Plus
FCC ID	2AOWKGQ3087
Device Phase	Identical Prototype
Exposure Category	General population / Uncontrolled environment
Antenna	FPC Antenna

Battery Information		DC 3.85V, 4000mAh, 15.40Wh	
Device Operating Configurations			
Supporting Mode(s)		GSM 850/1900, WCDMA Band 2/4/5, LTE Band 2/4/5/7/12/17, WLAN 2.4G/5.2G/5.8G, Bluetooth, NFC	
Test Modulation		GSM(GMSK/8PSK), WCDMA(QPSK), LTE(QPSK/16QAM), WLAN(DSSS/OFDM), Bluetooth(GFSK, $\pi/4$ -DQPSK, 8DPSK), NFC(ASK)	
Device Class		B	
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM 850	824-849	869-894
	GSM 1900	1850-1910	1930-1990
	WCDMA Band 2	1850-1910	1930-1990
	WCDMA Band 4	1710-1755	2110-2155
	WCDMA Band 5	824-849	869-894
	LTE Band 2	1850-1910	1930-1990
	LTE Band 4	1710-1755	2110-2155
	LTE Band 5	824-849	869-894
	LTE Band 7	2500-2570	2620-2690
	LTE Band 12	699-716	729-746
	LTE Band 17	704-716	734-746
	WLAN 2.4G	2412-2462	
	WLAN 5.2G	5180-5240	
	WLAN 5.8G	5745-5825	
	Bluetooth	2402-2480	
	NFC	13.56	
GPRS Multislot Class(12)	Max Number of Timeslots in Uplink		4
	Max Number of Timeslots in Downlink		4
	Max Total Timeslot		5
EDGE Multislot Class(12)	Max Number of Timeslots in Uplink		4
	Max Number of Timeslots in Downlink		4
	Max Total Timeslot		5
Power Class	4, tested with power level 5(GSM 850)		
	1, tested with power level 0(GSM 1900)		
	3, tested with power control “all 1”(WCDMA Band 2)		
	3, tested with power control “all 1”(WCDMA Band 4)		
	3, tested with power control “all 1”(WCDMA Band 5)		
	3, tested with power control all Max.(LTE Band 2)		
	3, tested with power control all Max.(LTE Band 4)		
	3, tested with power control all Max.(LTE Band 5)		
	3, tested with power control all Max.(LTE Band 7)		

Test Channels (low-mid-high)	3, tested with power control all Max.(LTE Band 12)
	3, tested with power control all Max.(LTE Band 17)
	128-189-251(GSM 850)
	512-661-810(GSM 1900)
	9262-9400-9538(WCDMA Band 2)
	1312-1413-1513(WCDMA Band 4)
	4132-4182-4233(WCDMA Band 5)
	18607-18900-19193(LTE Band 2 BW=1.4MHz)
	18615-18900-19185(LTE Band 2 BW=3MHz)
	18625-18900-19175(LTE Band 2 BW=5MHz)
	18650-18900-19150(LTE Band 2 BW=10MHz)
	18675-18900-19125(LTE Band 2 BW=15MHz)
	18700-18900-19100(LTE Band 2 BW=20MHz)
	19957-20175-20393(LTE Band 4 BW=1.4MHz)
	19965-20175-20385(LTE Band 4 BW=3MHz)
	19975-20175-20375(LTE Band 4 BW=5MHz)
	20000-20175-20350(LTE Band 4 BW=10MHz)
	20025-20175-20325(LTE Band 4 BW=15MHz)
	20050-20175-20300(LTE Band 4 BW=20MHz)
	20407-20525-20643(LTE Band 5 BW=1.4MHz)
	20415-20525-20635(LTE Band 5 BW=3MHz)
	20425-20525-20625(LTE Band 5 BW=5MHz)
	20450-20525-20600(LTE Band 5 BW=10MHz)
	20775-21100-21425(LTE Band 7 BW=5MHz)
	20800-21100-21400(LTE Band 7 BW=10MHz)
	20825-21100-21375(LTE Band 7 BW=15MHz)
	20850-21100-21350(LTE Band 7 BW=20MHz)
	23017-23095-23173 (LTE Band 12 BW=1.4MHz)
	23025-23095-23165 (LTE Band 12 BW=3MHz)
	23035-23095-23155 (LTE Band 12 BW=5MHz)
	23060-23095-23130 (LTE Band 12 BW=10MHz)
	23755-23790-23825(LTE Band 17 BW=5MHz)
	23780-23790-23800(LTE Band 17 BW=10MHz)
	1-3-6-9-11(WLAN 2.4G)
	36-38-40-42-46-48(WLAN 5.2G)
	149-151-155-157-159-165(WLAN 5.8G)

1.4. Test specification(s)


FCC 47 CFR Part 2(2.1093)
ANSI/IEEE C95.1-1992
IEEE Std 1528-2013
KDB 865664 D01 SAR measurement 100 MHz to 6 GHz
KDB 865664 D02 RF Exposure Reporting
KDB 447498 D01 General RF Exposure Guidance
KDB 248227 D01 802.11 Wi-Fi SAR
KDB 941225 D01 3G SAR Procedures
KDB 941225 D05 SAR for LTE Devices
KDB 941225 D06 Hotspot SAR
KDB 648474 D04 Handset SAR

1.5. Ambient Condition

Ambient temperature	20°C – 24°C
Relative Humidity	30% – 70%

2. SAR Measurement System

2.1. SATIMO SAR Measurement Set-up Diagram



These measurements were performed with the automated near-field scanning system OPENSAR from SATIMO. The system is based on a high precision robot (working range: 901 mm), which positions the probes with a positional repeatability of better than ± 0.03 mm. The SAR measurements were conducted with dosimetric probe (manufactured by SATIMO), designed in the classical triangular configuration and optimized for dosimetric evaluation.

The first step of the field measurement is the evaluation of the voltages induced on the probe by the device under test. Probe diode detectors are nonlinear. Below the diode compression point, the output voltage is proportional to the square of the applied E-field; above the diode compression point, it is linear to the applied E-field. The compression point depends on the diode, and a calibration procedure is necessary for each sensor of the probe.

The Keithley multimeter reads the voltage of each sensor and send these three values to the PC. The corresponding E field value is calculated using the probe calibration factors, which are stored in the working directory. This evaluation includes linearization of the diode characteristics. The field calculation is done separately for each sensor. Each component of the E field is displayed on the "Dipole Area Scan Interface" and the total E field is displayed on the "3D Interface"

2.2. Robot

The SATIMO SAR system uses the high precision robots from KUKA. For the 6-axis controller system, the robot controller version (KUKA) from KUKA is used. The KUKA robot series have many features that are important for our application:



- High precision (repeatability ± 0.03 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)

2.3. E-Field Probe

This E-field detection probe is composed of three orthogonal dipoles linked to special Schottky diodes with low detection thresholds. The probe allows the measurement of electric fields in liquids such as the one defined in the IEEE and CENELEC standards.

For the measurements the Specific Dosimetric E-Field Probe SN 41/18 EPGO330 with following specifications is used



- Dynamic range: 0.01-100 W/kg
 - Tip Diameter: 2.5 mm
 - Distance between probe tip and sensor center: 1 mm
 - Distance between sensor center and the inner phantom surface: 2 mm (repeatability better than ± 1 mm).
 - Probe linearity: ± 0.10 dB
 - Axial isotropy: 0.06 dB
 - Hemispherical Isotropy: 0.09 dB
 - Calibration range: 650MHz to 5900MHz for head & body simulating liquid.
 - Lower detection limit: 9mW/kg
- Angle between probe axis (evaluation axis) and surface normal line: less than 30° .

2.3.1. E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy shall be evaluated and within ± 0.25 dB. The sensitivity parameters (Norm X, Norm Y, and Norm Z), the diode compression parameter (DCP) and the conversion factor (Conv F) of the probe are tested. The calibration data can be referred to appendix D of this report.

2.4. SAM phantoms


Photo of SAM phantom SN 16/15 SAM119



The SAM phantom is used to measure the SAR relative to people exposed to electro-magnetic field radiated by mobile phones.

2.4.1. Technical Data

Serial Number	Shell thickness	Filling volume	Dimensions	Positionner Material	Permittivity	Loss Tangent
SN 16/15 SAM119	2 mm ±0.2 mm	27 liters	Length:1000 mm Width:500 mm Height:200 mm	Gelcoat with fiberglass	3.4	0.02




Serial Number	Left Head(mm)		Right Head(mm)		Flat Part(mm)	
SN 16/15 SAM119	2	2.02	2	2.08	1	2.09
	3	2.05	3	2.06	2	2.06
	4	2.07	4	2.07	3	2.08
	5	2.08	5	2.08	4	2.10
	6	2.05	6	2.07	5	2.10
	7	2.05	7	2.05	6	2.07
	8	2.07	8	2.06	7	2.07
	9	2.08	9	2.06	-	-

The test, based on ultrasonic system, allows measuring the thickness with an accuracy of 10 μm .

2.5. Device Holder

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1 degree.



Serial Number	Holder Material	Permittivity	Loss Tangent
SN 16/15 MSH100	Delrin	3.7	0.005

2.6. Test Equipment List

This table gives a complete overview of the SAR measurement equipment.

Devices used during the test described are marked ☒

	Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
					Last Cal.	Due Date
☒	MVG	E FIELD PROBE	SSE2	SN 41/18 EPG0330	May 21, 2019	May 20, 2020
☒	MVG	750 MHz Dipole	SID750	SN 03/15 DIP 0G750-355	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	835 MHz Dipole	SID835	SN 03/15 DIP 0G835-347	Apr. 19, 2018	Apr. 18, 2021
☐	MVG	900 MHz Dipole	SID900	SN 03/15 DIP 0G900-348	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	1800 MHz Dipole	SID1800	SN 03/15 DIP 1G800-349	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	1900 MHz Dipole	SID1900	SN 03/15 DIP 1G900-350	Apr. 19, 2018	Apr. 18, 2021
☐	MVG	2000 MHz Dipole	SID2000	SN 03/15 DIP 2G000-351	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	2450 MHz Dipole	SID2450	SN 03/15 DIP 2G450-352	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	2600 MHz Dipole	SID2600	SN 03/15 DIP 2G600-356	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	5000 MHz Dipole	SWG5500	SN 13/14 WGA 33	Apr. 19, 2018	Apr. 18, 2021
☒	MVG	Liquid measurement Kit	SCLMP	SN 21/15 OCPG 72	NCR	NCR
☒	MVG	Power Amplifier	N.A	AMPLISAR_28/14_003	NCR	NCR
☒	KEITHLEY	Millivoltmeter	2000	4072790	NCR	NCR
☒	R&S	Universal radio communication tester	CMU200	117858	Aug. 06, 2019	Aug. 05, 2020
☒	R&S	Wideband radio communication tester	CMW500	103917	Aug. 28, 2019	Aug. 27, 2020
☒	HP	Network Analyzer	8753D	3410J01136	Aug. 06, 2019	Aug. 05, 2020
☒	Agilent	PSG Analog Signal Generator	E8257D	MY51110112	Aug. 06, 2019	Aug. 05, 2020

☒	Agilent	Power meter	E4419B	MY45102538	Aug. 06, 2019	Aug. 05, 2020
☒	Agilent	Power sensor	E9301A	MY41495644	Aug. 06, 2019	Aug. 05, 2020
☒	Agilent	Power sensor	E9301A	US39212148	Aug. 06, 2019	Aug. 05, 2020
☒	MCLI/USA	Directional Coupler	CB11-20	0D2L51502	Aug. 06, 2019	Aug. 05, 2020

3. SAR Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/Bluetooth power measurement, use engineering software to configure EUT WLAN/Bluetooth continuously transmission, at maximum RF power in each supported wireless interface and frequency band.
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/Bluetooth output power.

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/Bluetooth continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix A demonstrates.
- (c) Set scan area, grid size and other setting on the OPENSAR software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band.
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg.

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

3.1. Power Reference

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

3.2. Area scan & Zoom scan

The area scan is a 2D scan to find the hot spot location on the DUT. The zoom scan is a 3D scan above the hot spot to calculate the 1g and 10g SAR value.

Measurement of the SAR distribution with a grid of 8 to 16 mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8 * 4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

From the scanned SAR distribution, identify the position of the maximum SAR value, in addition identify the positions of any local maxima with SAR values within 2 dB of the maximum value that will not be within the zoom scan of other peaks; additional peaks shall be measured only when the primary peak is within 2 dB of the SAR compliance limit (e.g., 1 W/kg for 1,6 W/kg 1 g limit, or 1,26 W/kg for 2 W/kg, 10 g limit).

Area scan & Zoom scan scan parameters extracted from FCC KDB 865664 D01 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm *	3 – 4 GHz: ≤ 5 mm * 4 – 6 GHz: ≤ 4 mm *
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm

Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.

* When zoom scan is required and the *reported* SAR from the *area scan based 1-g SAR estimation* procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.

3.3. Description of interpolation/extrapolation scheme

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimise measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is using to determinate this highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1 mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10 grams and 1 gram requires a very fine resolution in the three dimensional scanned data array.

3.4. Volumetric Scan

The volumetric scan consists to a full 3D scan over a specific area. This 3D scan is useful form multi Tx SAR measurement. Indeed, it is possible with OpenSAR to add, point by point, several volumetric scan to calculate the SAR value of the combined measurement as it is define in the standard IEEE1528 and IEC62209.

3.5. Power Drift

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In OpenSAR measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in V/m. If the power drifts more than $\pm 5\%$, the SAR will be retested.

4. System Verification Procedure

4.1. Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% of weight)	Head Tissue									
Frequency Band (MHz)	750	835	900	1800	1900	2000	2450	2600	5200	5800
Water	34.40	34.40	34.40	55.36	55.36	57.87	57.87	57.87	65.53	65.53
NaCl	0.79	0.79	0.79	0.35	0.35	0.16	0.16	0.16	0.00	0.00
1,2-Propanediol	64.81	64.81	64.81	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Triton X-100	0.00	0.00	0.00	30.45	30.45	19.97	19.97	19.97	24.24	24.24
DGBE	0.00	0.00	0.00	13.84	13.84	22.00	22.00	22.00	10.23	10.23
Ingredients (% of weight)	Body Tissue									
Frequency Band (MHz)	750	835	900	1800	1900	2000	2450	2600	5200	5800
Water	50.30	50.30	50.30	69.91	69.91	71.88	71.88	71.88	79.54	79.54
NaCl	0.60	0.60	0.60	0.13	0.13	0.16	0.16	0.16	0.00	0.00
1,2-Propanediol	49.10	49.10	49.10	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Triton X-100	0.00	0.00	0.00	9.99	9.99	19.97	19.97	19.97	11.24	11.24
DGBE	0.00	0.00	0.00	19.97	19.97	7.99	7.99	7.99	9.22	9.22

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid depth from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm.

Photo of Liquid depth for Head Position	Photo of Liquid depth for Body Position
	

4.1.1. Tissue Dielectric Parameter Check Results

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameter are within the tolerances of the specified target values. The measured conductivity and relative permittivity should be within $\pm 5\%$ of the target values.


Tissue Type	Measured Frequency (MHz)	Target Tissue		Measured Tissue		Liquid Temp.	Test Date
		$\epsilon_r (\pm 5\%)$	σ (S/m) ($\pm 5\%$)	ϵ_r	σ (S/m)		
Head 750	750	41.90 (39.81~43.99)	0.89 (0.85~0.93)	41.23	0.91	21.5 °C	Dec. 04, 2019
Body 750	750	55.50 (52.73~58.27)	0.96 (0.91~1.01)	55.30	0.97	21.4 °C	Dec. 04, 2019
Head 850	835	41.50 (39.43~43.57)	0.90 (0.86~0.94)	40.53	0.94	21.5 °C	Dec. 15, 2019
Body 850	835	55.20 (52.44~57.96)	0.97 (0.92~1.01)	54.37	1.01	21.3 °C	Dec. 15, 2019
Head 1800	1800	40.00 (38.00~42.00)	1.40 (1.33~1.47)	38.48	1.41	21.5 °C	Dec. 10, 2019
Body 1800	1800	53.30 (50.64~55.96)	1.52 (1.44~1.59)	53.24	1.56	21.2 °C	Nov. 30, 2019
Head 1900	1900	40.00 (38.00~42.00)	1.40 (1.33~1.47)	40.96	1.46	21.5 °C	Dec. 04, 2019
Body 1900	1900	53.30 (50.64~55.96)	1.52 (1.44~1.59)	52.57	1.57	21.5 °C	Dec. 04, 2019
Head 2450	2450	39.20 (37.24~41.16)	1.80 (1.71~1.89)	38.72	1.88	21.5 °C	Dec. 10, 2019
Body 2450	2450	52.70 (50.07~55.33)	1.95 (1.85~2.04)	52.09	2.03	21.8 °C	Nov. 30, 2019
Head 2600	2600	39.00 (37.05~40.95)	1.96 (1.86~2.05)	38.40	2.03	21.1 °C	Dec. 10, 2019
Body 2600	2600	52.50 (49.88~55.13)	2.16 (2.05~2.27)	52.67	2.20	21.4 °C	Nov. 30, 2019
Head 5000	5200	36.00 (34.20~37.80)	4.66 (4.43~4.89)	35.83	4.63	21.5 °C	Dec. 06, 2019
Body 5000	5200	49.00 (46.55~51.45)	5.30 (5.04~5.57)	49.66	5.29	21.5 °C	Dec. 06, 2019
Head 5000	5800	35.30 (33.54~37.07)	5.27 (5.01~5.53)	34.74	5.18	21.9 °C	Dec. 06, 2019
Body 5000	5800	48.20 (45.79~50.61)	6.00 (5.70~6.30)	48.35	6.06	21.2 °C	Dec. 06, 2019

NOTE: The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 °C of the conditions expected during the SAR evaluation to satisfy protocol requirements.

4.2. System Verification Procedure

The system verification is performed for verifying the accuracy of the complete measurement system and performance of the software. The dipole is connected to the signal source consisting of signal generator and amplifier via a directional coupler, N-connector cable and adaption to SMA. It is fed with a power of 100mW (below 5GHz) or 100mW (above 5GHz). To adjust this power a power meter is used. The power sensor is connected to the cable before the system verification to measure the power at this point and do adjustments at the signal generator. At the outputs of the directional coupler both return loss as well as forward power are controlled during the system verification to make sure that emitted power at the dipole is kept constant. This can also be checked by the power drift measurement after the test (result on plot).

The system verification is shown as below picture:



4.2.1. System Verification Results

Comparing to the original SAR value provided by SATIMO, the verification data should be within its specification of $\pm 10\%$. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance verification can meet the variation criterion and the plots can be referred to Appendix B of this report.

System Verification	Target SAR (1W) (±10%)		Measured SAR (Normalized to 1W)		Liquid Temp.	Test Date
	1-g (W/Kg)	10-g (W/Kg)	1-g (W/Kg)	10-g (W/Kg)		
750MHz Head	8.49 (7.64~9.34)	5.55 (4.99~6.11)	8.53	5.51	21.5 °C	Dec. 04, 2019
750MHz Body	8.55 (7.69~9.41)	5.75 (5.17~6.33)	8.86	5.89	21.4 °C	Dec. 04, 2019
835MHz Head	9.56 (8.60~10.51)	6.22 (5.60~6.84)	9.45	6.02	21.5 °C	Dec. 15, 2019
835MHz Body	9.48 (8.53~10.42)	6.29 (5.66~6.91)	9.70	6.60	21.3 °C	Dec. 15, 2019
1800MHz Head	38.40 (34.56~42.24)	20.10 (18.09~22.11)	38.06	20.10	21.5 °C	Dec. 10, 2019
1800MHz Body	37.04 (33.34~40.74)	20.26 (18.23~22.29)	38.12	20.63	21.2 °C	Nov. 30, 2019
1900MHz Head	39.70 (35.73~43.67)	20.50 (18.45~22.55)	38.90	20.07	21.5 °C	Dec. 04, 2019
1900MHz Body	38.43 (34.59~42.27)	20.34 (18.31~22.37)	39.10	20.59	21.5 °C	Dec. 04, 2019
2450MHz Head	52.40 (47.16~57.64)	24.00 (21.60~26.40)	53.69	24.16	21.5 °C	Dec. 10, 2019
2450MHz Body	49.32 (44.39~54.25)	22.89 (20.60~25.17)	52.88	24.01	21.8 °C	Nov. 30, 2019
2600MHz Head	55.30 (49.77~60.83)	24.60 (22.14~27.06)	55.50	24.19	21.1 °C	Dec. 10, 2019
2600MHz Body	52.95 (47.66~58.25)	23.64 (21.28~26.00)	55.65	24.63	21.4 °C	Nov. 30, 2019
5200MHz Head	159.00 (143.10~174.90)	56.90 (51.21~62.59)	160.77	55.84	21.5 °C	Dec. 06, 2019
5200MHz Body	156.85 (141.17~172.54)	55.20 (49.68~60.72)	156.77	55.10	21.5 °C	Dec. 06, 2019
5800MHz Head	181.20 (163.08~199.32)	61.50 (55.35~67.65)	184.10	62.56	21.9 °C	Dec. 06, 2019
5800MHz Body	169.30 (152.37~186.23)	58.49 (52.64~64.34)	169.11	58.40	21.2 °C	Dec. 06, 2019

5. SAR Measurement variability and uncertainty

5.1. SAR measurement variability

Per KDB865664 D01 SAR measurement 100 MHz to 6 GHz, SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. The additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

- 1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg ($\sim 10\%$ from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

5.2. SAR measurement uncertainty

Per KDB865664 D01 SAR Measurement 100 MHz to 6 GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg, the extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. The equivalent ratio (1.5/1.6) is applied to extremity and occupational exposure conditions.

6. RF Exposure Positions

6.1. Ear and handset reference point

Figure 6.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled “M”, the left ear reference point (ERP) is marked “LE”, and the right ERP is marked “RE”.



Fig 6.1.1 Front, back, and side views of SAM phantom

6.2. Definition of the cheek position

1. Define two imaginary lines on the handset, the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset: the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 6.2.1 and Figure 6.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 6.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 6.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
2. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
3. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP
4. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
5. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.

6. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 6.2.3. The actual rotation angles should be documented in the test report.




Fig 6.2.1 Handset vertical and horizontal reference lines—"fixed case"




Fig 6.2.2 Handset vertical and horizontal reference lines—"clam-shell case"




Fig 6.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

6.3. Definition of the tilt position

1. While maintaining the orientation of the handset, retract the handset parallel to the reference plane far enough away from the phantom to enable a rotation of the device by 15 degree.
2. Rotate the Handset around the horizontal line by 15 degree (see Figure 6.3.1).
3. While maintaining the orientation of the handset, move the handset towards the phantom on a line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact is on the pinna. If the contact is at any location other than the pinna, e.g., the antenna with the back of the phantom head, the angle of the handset shall be reduced. In this case, the tilt position is obtained if any part of the handset is in contact with the pinna as well as a second part of the handset is in contact with the phantom, e.g., the antenna with the back of the head.




Figure 6.3.1 – Tilt position of the wireless device on the left side of SAM

6.4. Body Worn Accessory

1. Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 6.4.1). Per KDB 648474 D04, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $< 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.
2. Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest

spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Figure 6.4.1 – Test positions for body-worn devices

6.5. Wireless Router Devices

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WLAN simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 where SAR test considerations for handsets ($L \times W \geq 9 \text{ cm} \times 5 \text{ cm}$) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WLAN transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WLAN transmitter according to FCC KDB Publication 447498 D01 publication procedures. The “Portable Hotspot” feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

7. RF Output Power

7.1. GSM Conducted Power

Band GSM850	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up	128	189	251	Tune-up	128	189	251
Frequency (MHz)	(dBm)	824.2	836.4	848.8	(dBm)	824.2	836.4	848.8
GSM (GMSK)	35.00	34.28	34.30	34.26	25.97	25.25	25.27	25.23
GPRS(GMSK, 1 TS)	34.00	33.88	33.97	33.94	24.97	24.85	24.94	24.91
GPRS(GMSK, 2 TS)	34.00	33.67	33.72	33.66	27.98	27.65	27.70	27.64
GPRS(GMSK, 3 TS)	32.00	31.68	31.60	31.56	27.74	27.42	27.34	27.30
GPRS(GMSK, 4 TS)	30.50	30.32	30.27	30.23	27.49	27.31	27.26	27.22
EDGE(GMSK, 1 TS)	28.00	27.85	27.60	27.72	18.97	18.82	18.57	18.69
EDGE(GMSK, 2 TS)	28.00	26.88	27.07	27.09	21.98	20.86	21.05	21.07
EDGE(GMSK, 3 TS)	25.00	24.63	24.31	24.35	20.74	20.37	20.05	20.09
EDGE(GMSK, 4 TS)	24.00	23.14	22.80	22.85	20.99	20.13	19.79	19.84
Band GSM1900	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
Tx Channel	Tune-up	512	661	810	Tune-up	512	661	810
Frequency (MHz)	(dBm)	1850.2	1880.0	1909.8	(dBm)	1850.2	1880.0	1909.8
GSM (GMSK)	32.00	31.02	30.72	30.21	22.97	21.99	21.69	21.18
GPRS(GMSK, 1 TS)	32.00	31.31	31.01	30.51	22.97	22.28	21.98	21.48
GPRS(GMSK, 2 TS)	31.00	30.72	30.41	29.95	24.98	24.70	24.39	23.93
GPRS(GMSK, 3 TS)	29.00	29.00	28.20	27.76	24.74	24.74	23.94	23.50
GPRS(GMSK, 4 TS)	28.00	28.00	27.08	26.65	24.99	24.99	24.07	23.64
EDGE(GMSK, 1 TS)	29.00	28.63	28.41	28.10	19.97	19.60	19.38	19.07
EDGE(GMSK, 2 TS)	29.00	28.35	28.08	27.75	22.98	22.33	22.06	21.73
EDGE(GMSK, 3 TS)	28.00	27.64	27.37	27.06	23.74	23.38	23.11	22.80
EDGE(GMSK, 4 TS)	28.00	27.22	26.96	26.65	24.99	24.21	23.95	23.64

Note: The frame-averaged power is linearly scaled the maximum burst averaged power over 8 time slots.

The calculated method are shown as below:

Frame-averaged power = Maximum burst averaged power (1 TS) - 9.03 dB

Frame-averaged power = Maximum burst averaged power (2 TS) - 6.02 dB

Frame-averaged power = Maximum burst averaged power (3 TS) - 4.26 dB

Frame-averaged power = Maximum burst averaged power (4 TS) - 3.01 dB

7.2. WCDMA Conducted Power

Band	WCDMA Band 2			
Tx Channel	Tune-up	9262	9400	9538
Frequency (MHz)		1852.4	1880	1907.6

RMC 12.2Kbps	24.00	23.69	23.64	23.75
HSDPA Subtest-1	23.00	22.72	22.70	22.81
HSDPA Subtest-2	23.00	22.17	21.98	22.10
HSDPA Subtest-3	22.00	21.44	21.34	21.19
HSDPA Subtest-4	22.00	21.16	21.36	21.27
HSUPA Subtest-1	23.00	22.34	22.45	22.49
HSUPA Subtest-2	23.00	22.60	22.60	22.72
HSUPA Subtest-3	22.00	21.46	21.12	21.76
HSUPA Subtest-4	23.00	22.75	22.69	22.81
HSUPA Subtest-5	23.00	21.96	21.86	22.01
Band	WCDMA Band 4			
Tx Channel	Tune-up	1312	1413	1513
Frequency (MHz)		1712.4	1732.6	1752.6
RMC 12.2Kbps	24.00	23.40	22.89	22.54
HSDPA Subtest-1	23.00	22.31	21.93	21.60
HSDPA Subtest-2	22.00	21.78	21.25	21.08
HSDPA Subtest-3	21.00	20.90	20.15	19.89
HSDPA Subtest-4	21.00	20.82	20.19	20.13
HSUPA Subtest-1	22.00	21.86	21.46	21.14
HSUPA Subtest-2	23.00	22.18	21.76	21.57
HSUPA Subtest-3	21.00	20.77	20.72	20.43
HSUPA Subtest-4	23.00	22.32	21.92	21.61
HSUPA Subtest-5	22.00	21.32	20.91	20.79
Band	WCDMA Band 5			
Tx Channel	Tune-up	4132	4182	4233
Frequency (MHz)		826.4	836.4	846.6
RMC 12.2Kbps	24.00	23.67	23.30	23.10
HSDPA Subtest-1	23.00	22.69	22.60	22.25
HSDPA Subtest-2	23.00	22.29	22.24	21.50
HSDPA Subtest-3	22.00	21.14	20.73	20.80
HSDPA Subtest-4	22.00	21.34	21.28	20.71
HSUPA Subtest-1	23.00	22.25	22.15	21.77
HSUPA Subtest-2	23.00	22.55	22.53	22.20
HSUPA Subtest-3	22.00	21.40	21.30	20.87
HSUPA Subtest-4	23.00	22.67	22.58	22.22
HSUPA Subtest-5	22.00	21.73	21.70	21.23

7.3. LTE Conducted Power

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18607/1850.7	18900/1880	19193/1909.3
LTE Band 2	1.4MHz	QPSK	1	0	24.00	23.83	23.79	23.31
			1	2	24.00	23.92	23.89	23.41
			1	5	24.00	23.72	23.75	23.30
			3	0	24.00	23.70	23.59	23.22
			3	1	24.00	23.68	23.46	23.25
			3	2	24.00	23.65	23.30	23.21
			6	0	23.00	22.68	22.42	22.34
		16QAM	1	0	23.00	22.57	22.19	21.93
			1	2	23.00	22.65	22.27	22.00
			1	5	23.00	22.61	22.14	21.92
			3	0	23.00	22.71	22.23	22.28
			3	1	23.00	22.74	22.27	22.28
			3	2	23.00	22.70	22.24	22.28
			6	0	22.00	21.79	21.25	21.41
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18615/1851.5	18900/1880	19185/1908.5
LTE Band 2	3MHz	QPSK	1	0	24.00	23.33	23.38	23.44
			1	7	24.00	23.56	23.69	23.58
			1	14	24.00	23.25	23.29	23.28
			8	0	23.00	22.18	22.28	22.37
			8	4	23.00	22.22	22.32	22.36
			8	7	23.00	22.20	22.22	22.31
			15	0	23.00	22.14	22.13	22.25
		16QAM	1	0	23.00	22.29	21.92	22.54
			1	7	23.00	22.44	22.21	22.67
			1	14	23.00	22.25	21.85	22.50
			8	0	22.00	21.17	21.15	21.30
			8	4	22.00	21.19	21.15	21.29
			8	7	22.00	21.15	21.14	21.27
			15	0	22.00	21.05	21.18	21.26
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		

			RB Size	RB Offset		18625/1852.5	18900/1880	19175/1907.5
LTE Band 2	5MHz	QPSK	1	0	24.00	23.06	23.31	23.19
			1	12	24.00	23.39	23.60	23.47
			1	24	24.00	22.95	23.19	23.07
			12	0	23.00	22.14	22.19	22.15
			12	6	23.00	22.17	22.19	22.14
			12	11	23.00	22.17	22.17	22.06
			25	0	23.00	22.18	22.20	22.12
		16QAM	1	0	23.00	22.29	22.41	22.09
			1	12	23.00	22.67	22.73	22.55
			1	24	23.00	22.25	22.40	22.18
			12	0	22.00	21.17	21.12	21.01
			12	6	22.00	21.23	21.14	21.01
			12	11	22.00	21.21	20.97	20.98
			25	0	22.00	21.13	20.98	21.07
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18650/1855	18900/1880	19150/1905
LTE Band 2	10MHz	QPSK	1	0	24.00	23.15	23.26	23.22
			1	24	24.00	23.18	23.28	23.38
			1	49	24.00	23.03	23.00	23.11
			25	0	23.00	21.93	22.07	22.16
			25	12	23.00	22.02	22.04	22.07
			25	24	23.00	22.05	22.05	22.03
			50	0	23.00	22.02	22.09	22.06
		16QAM	1	0	23.00	22.34	22.03	21.74
			1	24	23.00	22.51	22.16	21.86
			1	49	23.00	22.20	22.05	21.76
			25	0	22.00	20.98	21.03	21.08
			25	12	22.00	21.07	20.99	21.00
			25	24	22.00	21.07	21.04	21.00
			50	0	22.00	21.01	21.08	21.02
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18675/1857.5	18900/1880	19125/1902.5
LTE Band	15MHz	QPSK	1	0	24.00	23.10	23.23	22.90
			1	37	24.00	23.30	23.39	23.39

2			1	74	24.00	23.16	22.86	22.97
			36	0	23.00	22.03	22.41	22.28
			36	18	23.00	22.13	22.30	22.33
			36	37	23.00	22.10	22.22	22.24
			75	0	23.00	22.09	22.33	22.26
		16QAM	1	0	23.00	22.11	22.00	22.18
			1	37	23.00	22.28	22.40	22.44
			1	74	23.00	21.87	21.95	22.18
			36	0	22.00	21.00	21.14	21.13
			36	18	22.00	21.08	21.09	21.12
			36	37	22.00	21.02	21.05	21.05
			75	0	22.00	20.99	21.20	21.10
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		18700/1860	18900/1880	19100/1900
LTE Band 2	20MHz	QPSK	1	0	24.00	22.80	23.03	22.81
			1	49	24.00	23.10	23.29	23.36
			1	99	24.00	22.99	22.73	22.92
			50	0	23.00	21.75	22.09	21.93
			50	24	23.00	21.94	22.07	22.00
			50	49	23.00	21.77	22.14	21.85
			100	0	23.00	21.75	22.10	21.89
		16QAM	1	0	23.00	22.08	21.79	21.98
			1	49	23.00	22.23	22.20	22.20
			1	99	23.00	21.86	21.89	21.91
			50	0	22.00	20.86	21.01	20.93
			50	24	22.00	20.98	21.02	21.01
			50	49	22.00	20.75	21.10	20.85
			100	0	22.00	20.74	21.08	20.89

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		19957/1710.7	20175/1732.5	20393/1754.3
LTE Band 4	1.4MHz	QPSK	1	0	24.00	23.17	22.92	22.48
			1	2	24.00	23.27	23.07	22.63
			1	5	24.00	23.17	22.87	22.49
			3	0	24.00	23.17	22.92	22.58
			3	1	24.00	23.21	22.94	22.61

			3	2	24.00	23.16	22.93	22.60
			6	0	23.00	22.24	21.85	21.53
		16QAM	1	0	23.00	21.92	21.87	21.63
			1	2	23.00	22.07	22.00	21.77
			1	5	23.00	21.93	21.90	21.68
			3	0	23.00	22.27	22.01	21.75
			3	1	23.00	22.25	22.01	21.82
			3	2	23.00	22.35	22.00	21.82
			6	0	22.00	21.36	21.00	20.69
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		19965/1711.5	20175/1732.5	20385/1753.5
LTE Band 4	3MHz	QPSK	1	0	24.00	23.24	22.85	22.61
			1	7	24.00	23.50	23.10	22.85
			1	14	24.00	23.21	22.80	22.51
			8	0	23.00	22.20	21.84	21.54
			8	4	23.00	22.24	21.87	21.60
			8	7	23.00	22.19	21.87	21.54
			15	0	23.00	22.15	21.81	21.52
		16QAM	1	0	23.00	21.99	22.18	21.74
			1	7	23.00	22.25	22.43	21.99
			1	14	23.00	21.89	22.18	21.69
			8	0	22.00	21.16	20.90	20.62
			8	4	22.00	21.20	20.89	20.60
			8	7	22.00	21.16	20.90	20.54
			15	0	22.00	21.22	20.85	20.52
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		19975/1712.5	20175/1732.5	20375/1752.5
LTE Band 4	5MHz	QPSK	1	0	24.00	23.10	22.76	22.55
			1	12	24.00	23.45	23.10	22.95
			1	24	24.00	23.05	22.77	22.47
			12	0	23.00	22.16	21.86	21.61
			12	6	23.00	22.23	21.85	21.61
			12	11	23.00	22.13	21.80	21.49
			25	0	23.00	22.16	21.83	21.54
		16QAM	1	0	23.00	22.38	21.93	22.03
			1	12	23.00	22.53	22.31	22.31

			1	24	23.00	22.31	22.01	21.98
			12	0	22.00	21.09	20.88	20.65
			12	6	22.00	21.13	20.96	20.63
			12	11	22.00	21.11	20.86	20.51
			25	0	22.00	21.21	20.88	20.56
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20000/1715	20175/1732.5	20350/1750
LTE Band 4	10MHz	QPSK	1	0	24.00	23.13	22.84	22.76
			1	24	24.00	23.13	22.95	22.82
			1	49	24.00	22.99	22.88	22.57
			25	0	23.00	22.13	21.94	21.73
			25	12	23.00	22.09	21.91	21.64
			25	24	23.00	22.10	21.91	21.52
			50	0	23.00	22.16	21.89	21.64
		16QAM	1	0	23.00	22.48	21.90	21.58
			1	24	23.00	22.48	22.06	21.60
			1	49	23.00	22.25	22.03	21.36
			25	0	22.00	21.17	20.93	20.76
			25	12	22.00	21.18	20.95	20.69
			25	24	22.00	21.16	20.93	20.57
			50	0	22.00	21.11	20.94	20.64
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20025/1717.5	20175/1732.5	20325/1747.5
LTE Band 4	15MHz	QPSK	1	0	24.00	23.04	22.77	22.73
			1	37	24.00	23.33	23.04	23.02
			1	74	24.00	22.80	22.76	22.43
			36	0	23.00	22.18	22.06	21.81
			36	18	23.00	22.19	21.99	21.80
			36	37	23.00	22.12	21.89	21.63
			75	0	23.00	22.19	21.95	21.80
		16QAM	1	0	23.00	22.18	22.07	21.89
			1	37	23.00	22.46	22.36	22.22
			1	74	23.00	21.84	22.17	21.60
			36	0	22.00	21.06	21.01	20.91
			36	18	22.00	21.06	20.99	20.86
			36	37	22.00	21.00	20.94	20.71

			75	0	22.00	21.13	20.91	20.73
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20050/1720	20175/1732.5	20300/1745
LTE Band 4	20MHz	QPSK	1	0	24.00	22.96	22.70	22.62
			1	49	24.00	23.21	22.99	22.86
			1	99	24.00	22.69	22.59	22.32
			50	0	22.00	21.91	21.87	21.84
			50	24	22.00	21.96	21.87	21.77
			50	49	22.00	21.86	21.69	21.58
			100	0	22.00	21.90	21.85	21.69
		16QAM	1	0	23.00	22.15	21.85	21.82
			1	49	23.00	22.21	22.21	22.00
			1	99	23.00	21.82	21.91	21.53
			50	0	21.00	20.98	20.92	20.88
			50	24	21.00	21.00	20.96	20.85
			50	49	21.00	20.86	20.83	20.61
			100	0	21.00	20.90	20.89	20.79

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20407/824.7	20525/836.5	20643/848.3
LTE Band 5	1.4MHz	QPSK	1	0	24.00	23.12	23.32	22.77
			1	2	24.00	23.23	23.45	22.87
			1	5	24.00	23.08	23.33	22.75
			3	0	24.00	23.03	23.22	22.83
			3	1	24.00	23.10	23.22	22.85
			3	2	24.00	22.97	23.21	22.81
			6	0	23.00	22.26	22.33	21.82
		16QAM	1	0	23.00	21.80	22.20	21.92
			1	2	23.00	21.94	22.36	22.02
			1	5	23.00	21.83	22.23	21.86
			3	0	23.00	22.09	22.28	22.01
			3	1	23.00	22.14	22.32	21.97
			3	2	23.00	22.14	22.27	22.01
			6	0	22.00	21.25	21.36	20.96
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		

			RB Size	RB Offset		20415/825.5	20525/836.5	20635/847.5
LTE Band 5	3MHz	QPSK	1	0	24.00	23.09	23.27	22.92
			1	7	24.00	23.40	23.68	23.19
			1	14	24.00	23.05	23.25	22.83
			8	0	23.00	22.16	22.31	21.92
			8	4	23.00	22.17	22.34	21.96
			8	7	23.00	22.12	22.29	21.85
			15	0	23.00	22.08	22.21	21.85
		16QAM	1	0	23.00	22.37	22.30	21.75
			1	7	23.00	22.69	22.69	22.12
			1	14	23.00	22.39	22.27	21.56
			8	0	22.00	21.11	21.21	20.88
			8	4	22.00	21.18	21.25	20.91
			8	7	22.00	21.11	21.18	20.82
			15	0	22.00	21.08	21.13	20.91
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20425/826.5	20525/836.5	20625/846.5
LTE Band 5	5MHz	QPSK	1	0	24.00	23.05	23.20	22.86
			1	12	24.00	23.57	23.69	23.02
			1	24	24.00	23.04	23.16	22.73
			12	0	23.00	22.10	22.22	21.99
			12	6	23.00	22.15	22.26	21.96
			12	11	23.00	22.01	22.23	21.85
			25	0	23.00	22.12	22.21	21.92
		16QAM	1	0	23.00	22.32	22.38	22.16
			1	12	23.00	22.87	22.67	22.45
			1	24	23.00	22.50	22.29	21.90
			12	0	22.00	21.08	21.08	20.98
			12	6	22.00	21.13	21.19	20.97
			12	11	22.00	21.05	21.09	20.78
			25	0	22.00	21.07	21.13	20.88
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20450/829	20525/836.5	20600/844
LTE Band	10MHz	QPSK	1	0	24.00	23.18	23.19	23.16
			1	24	24.00	23.31	23.38	23.10

5			1	49	24.00	23.31	23.14	22.80
			25	0	23.00	22.30	22.21	22.21
			25	12	23.00	22.21	22.22	22.03
			25	24	23.00	22.28	22.19	21.90
			50	0	23.00	22.28	22.16	22.10
		16QAM	1	0	23.00	21.87	22.51	22.22
			1	24	23.00	22.09	22.62	22.24
			1	49	23.00	22.04	22.41	21.89
			25	0	22.00	21.25	21.22	21.15
			25	12	22.00	21.18	21.21	21.00
			25	24	22.00	21.22	21.16	20.92
			50	0	22.00	21.21	21.13	21.14

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20775/2502.5	21100/2535	21425/2567.5
LTE Band 7	5MHz	QPSK	1	0	23.00	21.16	21.64	22.31
			1	12	23.00	21.58	22.07	22.84
			1	24	23.00	21.10	21.76	22.44
			12	0	22.00	20.28	20.75	21.48
			12	6	22.00	20.28	20.83	21.52
			12	11	22.00	20.25	20.80	21.46
			25	0	22.00	20.30	20.79	21.46
		16QAM	1	0	22.00	20.78	20.94	21.55
			1	12	22.00	21.14	21.48	22.00
			1	24	22.00	20.72	21.04	21.56
			12	0	21.00	19.30	19.72	20.48
			12	6	21.00	19.34	19.80	20.52
			12	11	21.00	19.28	19.79	20.50
			25	0	21.00	19.28	19.82	20.45
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20800/2505	21100/2535	21400/2565
LTE Band 7	10MHz	QPSK	1	0	23.00	21.30	21.61	22.36
			1	24	23.00	21.32	21.83	22.57
			1	49	23.00	21.25	21.89	22.56
			25	0	22.00	20.29	20.79	21.45
			25	12	22.00	20.27	20.83	21.50

			25	24	22.00	20.35	20.90	21.49
			50	0	22.00	20.34	20.82	21.46
		16QAM	1	0	22.00	20.74	20.83	21.19
			1	24	22.00	20.80	21.08	21.32
			1	49	22.00	20.73	21.08	21.29
			25	0	21.00	19.40	19.79	20.48
			25	12	21.00	19.33	19.85	20.49
			25	24	21.00	19.41	19.94	20.52
			50	0	21.00	19.34	19.90	20.48
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20825/2507.5	21100/2535	21375/2562.5
LTE Band 7	15MHz	QPSK	1	0	23.00	21.20	21.50	22.23
			1	37	23.00	21.45	22.04	22.66
			1	74	23.00	21.19	21.86	22.45
			36	0	22.00	20.28	20.75	21.47
			36	18	22.00	20.31	20.82	21.54
			36	37	22.00	20.36	20.94	21.64
			75	0	22.00	20.34	20.87	21.51
		16QAM	1	0	22.00	20.35	21.01	21.40
			1	37	22.00	20.68	21.47	21.74
			1	74	22.00	20.33	21.28	21.51
			36	0	21.00	19.25	19.75	20.52
			36	18	21.00	19.26	19.83	20.56
			36	37	21.00	19.34	19.96	20.60
			75	0	21.00	19.38	19.86	20.52
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		20850/2510	21100/2535	21350/2560
LTE Band 7	20MHz	QPSK	1	0	23.00	21.06	21.28	21.95
			1	49	23.00	21.37	21.84	22.49
			1	99	23.00	21.16	21.75	22.28
			50	0	22.00	20.21	20.69	21.31
			50	24	22.00	20.28	20.86	21.41
			50	49	22.00	20.40	20.88	21.42
			100	0	22.00	20.28	20.78	21.32
		16QAM	1	0	22.00	20.37	20.67	21.19
			1	49	22.00	20.59	21.25	21.65

			1	99	22.00	20.48	21.14	21.40
			50	0	21.00	19.32	19.73	20.30
			50	24	21.00	19.34	19.94	20.42
			50	49	21.00	19.44	19.96	20.43
			100	0	21.00	19.32	19.83	20.37

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23017/699.7	23095/707.5	23173/715.3
LTE Band 12	1.4MHz	QPSK	1	0	22.00	21.71	21.72	21.64
			1	2	22.00	21.95	21.86	21.73
			1	5	22.00	21.99	21.71	21.58
			3	0	22.00	21.97	21.86	21.68
			3	1	22.00	21.99	21.86	21.65
			3	2	22.00	22.00	21.83	21.65
		16QAM	6	0	21.00	20.91	20.75	20.61
			1	0	22.00	20.95	20.96	20.47
			1	2	22.00	21.15	21.09	20.59
			1	5	22.00	21.11	20.97	20.41
			3	0	22.00	21.10	21.13	20.80
			3	1	22.00	21.12	21.12	20.79
			3	2	22.00	21.16	21.06	20.80
			6	0	21.00	20.09	19.95	19.80
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23025/700.5	23095/707.5	23165/714.5
LTE Band 12	3MHz	QPSK	1	0	23.00	21.64	21.73	21.68
			1	7	23.00	22.12	22.08	21.94
			1	14	23.00	21.85	21.71	21.60
			8	0	21.00	20.81	20.71	20.69
			8	4	21.00	20.83	20.77	20.67
			8	7	21.00	20.86	20.75	20.60
			15	0	21.00	20.80	20.77	20.60
		16QAM	1	0	22.00	21.13	21.02	20.56
			1	7	22.00	21.55	21.30	20.89
			1	14	22.00	21.26	20.93	20.42
			8	0	20.00	19.86	19.86	19.67
			8	4	20.00	19.89	19.81	19.69

			8	7	20.00	19.89	19.81	19.64
			15	0	20.00	19.85	19.77	19.73
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23035/701.5	23095/707.5	23155/713.5
LTE Band 12	5MHz	QPSK	1	0	23.00	21.59	21.74	21.63
			1	12	23.00	22.11	22.12	22.00
			1	24	23.00	21.71	21.62	21.53
			12	0	21.00	20.80	20.79	20.68
			12	6	21.00	20.90	20.85	20.73
			12	11	21.00	20.86	20.77	20.57
			25	0	21.00	20.79	20.79	20.67
		16QAM	1	0	22.00	20.89	21.26	20.95
			1	12	22.00	21.46	21.75	21.32
			1	24	22.00	21.11	21.23	20.85
			12	0	20.00	19.86	19.85	19.58
			12	6	20.00	19.98	19.83	19.66
			12	11	20.00	19.94	19.83	19.53
			25	0	20.00	19.86	19.83	19.70
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23060/704	23095/707.5	23130/711
LTE Band 12	10MHz	QPSK	1	0	23.00	21.75	21.80	21.75
			1	24	23.00	22.02	21.88	21.76
			1	49	23.00	21.81	21.67	21.60
			25	0	21.00	20.87	20.87	20.71
			25	12	21.00	20.85	20.81	20.74
			25	24	21.00	20.87	20.85	20.68
			50	0	21.00	20.85	20.87	20.71
		16QAM	1	0	22.00	20.57	21.27	20.94
			1	24	22.00	20.84	21.29	20.94
			1	49	22.00	20.65	21.13	20.79
			25	0	20.00	19.90	19.94	19.77
			25	12	20.00	19.90	19.89	19.78
			25	24	20.00	19.88	19.92	19.70
			50	0	20.00	19.87	19.90	19.77

Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23755/706.5	23790/710	23825/713.5
LTE Band 17	5MHz	QPSK	1	0	23.00	22.65	22.61	22.53
			1	12	23.00	23.00	22.84	22.89
			1	24	23.00	22.59	22.49	22.48
			12	0	22.00	21.82	21.61	21.55
			12	6	22.00	21.76	21.69	21.59
			12	11	22.00	21.69	21.64	21.45
			25	0	22.00	21.74	21.69	21.57
		16QAM	1	0	23.00	21.96	21.92	22.05
			1	12	23.00	22.35	22.19	22.34
			1	24	23.00	21.89	21.76	21.90
			12	0	21.00	20.76	20.70	20.57
			12	6	21.00	20.75	20.73	20.61
			12	11	21.00	20.70	20.71	20.48
			25	0	21.00	20.81	20.67	20.52
Band	Band Width	Modulation	RB Configuration		Tune-up	Channel/Frequency(MHz)		
			RB Size	RB Offset		23780/709	23790/710	23800/711
LTE Band 17	10MHz	QPSK	1	0	23.00	22.74	22.69	22.67
			1	24	23.00	22.79	22.71	22.68
			1	49	23.00	22.62	22.49	22.55
			25	0	22.00	21.77	21.73	21.65
			25	12	22.00	21.68	21.63	21.61
			25	24	22.00	21.73	21.69	21.65
			50	0	22.00	21.77	21.73	21.63
		16QAM	1	0	23.00	21.55	22.12	21.88
			1	24	23.00	21.65	22.14	21.87
			1	49	23.00	21.43	21.86	21.63
			25	0	21.00	20.78	20.78	20.69
			25	12	21.00	20.74	20.74	20.65
			25	24	21.00	20.75	20.74	20.65
			50	0	21.00	20.76	20.77	20.68

7.4. WLAN & Bluetooth Output Power

7.4.1. Output Power Results Of WLAN

Mode	Channel	Frequency (MHz)	Tune-up	Output Power (dBm)
802.11b	1	2412	14.00	13.38
	6	2437	14.00	13.26
	11	2462	14.00	12.50
802.11g	1	2412	13.00	12.79
	6	2437	13.00	12.90
	11	2462	13.00	12.12
802.11n HT20	1	2412	13.00	12.59
	6	2437	13.00	12.52
	11	2462	13.00	11.70
802.11n HT40	3	2422	13.00	12.94
	6	2437	13.00	12.61
	9	2452	13.00	12.28

NOTE: Power measurement results of WLAN 2.4G.

Mode	Channel	Frequency (MHz)	Tune-up	Output Power (dBm)
802.11a	36	5180	10.00	9.24
	40	5200	10.00	8.52
	48	5240	10.00	8.02
802.11n HT20	36	5180	9.50	9.07
	40	5200	9.50	8.33
	48	5240	9.50	7.98
802.11n HT40	38	5190	6.00	4.41
	46	5230	6.00	5.88
802.11ac VHT20	36	5180	9.00	8.96
	40	5200	9.00	8.30
	48	5240	9.00	7.97
802.11ac VHT40	38	5190	9.00	8.44
	46	5230	9.00	7.76
802.11ac VHT80	42	5210	7.00	6.18

NOTE: Power measurement results of WLAN 5.2G.

Mode	Channel	Frequency (MHz)	Tune-up	Output Power (dBm)
802.11a	149	5745	10.00	9.37
	157	5785	8.00	7.75
	165	5825	8.00	6.79

802.11n HT20	149	5745	9.00	8.27
	157	5785	8.00	7.57
	165	5825	8.00	6.67
802.11n HT40	151	5755	8.00	7.69
	159	5795	8.00	6.27
802.11ac VHT20	149	5745	9.00	8.20
	157	5785	7.00	6.39
	165	5825	7.00	5.49
802.11ac VHT40	151	5755	8.00	7.88
	159	5795	8.00	6.31
802.11ac VHT80	155	5775	7.00	6.97


NOTE: Power measurement results of WLAN 5.8G.

7.4.2. Output Power Results Of Bluetooth

BR+EDR	Output Power (dBm)				
	Channel	Tune-up	Data Rates		
			1M	2M	3M
	0CH	8.000	7.665	6.903	6.907
	39CH	7.000	6.920	6.171	6.154
	78CH	6.000	5.778	5.023	4.984

BLE	Channel	Tune-up	Output Power (dBm)
	0CH	-4.000	-5.500
	19CH	-4.000	-4.837
	39CH	-4.000	-5.853

8. Antenna Location



Distance of the Antenna to the EUT surface/edge						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
WWAN Main	≤ 25mm	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	≤ 25mm
WLAN & Bluetooth	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	≤ 25mm	>25mm
Positions for SAR tests						
Antennas	Front Side	Back Side	Left Side	Right Side	Top Side	Bottom Side
WWAN Main	Yes	Yes	Yes	Yes	NO	Yes
WLAN & Bluetooth	Yes	Yes	NO	Yes	Yes	NO

9. Stand-alone SAR test exclusion

Refer to FCC KDB 447498D01, the 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	P_{max} (dBm)	P_{max} (mW)	Distance (mm)	f (GHz)	Calculation Result	SAR Exclusion threshold	SAR test exclusion
Bluetooth	8.000	6.310	5	2.480	2.0	3.0	Yes

NOTE: Standalone SAR test exclusion for Bluetooth

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}/x}] \text{ W/kg}$ for test separation distances $\leq 50\text{mm}$, where $x = 7.5$ for 1-g SAR and $x = 18.75$ for 10-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	Position	P_{max} (dBm)	P_{max} (mW)	Distance (mm)	f (GHz)	x	Estimated SAR (W/Kg)
Bluetooth	Head	8.000	6.310	5	2.480	7.5	0.265
Bluetooth	Body	8.000	6.310	10	2.480	7.5	0.132
Bluetooth	Hotspot	8.000	6.310	10	2.480	7.5	0.132

NOTE: Estimated SAR calculation for Bluetooth

10. SAR Results

10.1. SAR measurement results

10.1.1. SAR measurement Result of GSM850

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	189/836.4	GPRS(GMSK 2TS)	1.055	0.786	0.07	33.72	34.00	1.125
Left Tilt 15 Degree	189/836.4	GPRS(GMSK 2TS)	0.514	0.403	-4.07	33.72	34.00	0.548
Right Cheek	189/836.4	GPRS(GMSK 2TS)	0.734	0.595	2.86	33.72	34.00	0.783
Right Tilt 15 Degree	189/836.4	GPRS(GMSK 2TS)	0.499	0.369	3.78	33.72	34.00	0.532
Left Cheek	128/824.2	GPRS(GMSK 2TS)	1.030	0.813	-0.87	33.67	34.00	1.111
Left Cheek	251/848.8	GPRS(GMSK 2TS)	1.044	0.813	1.02	33.66	34.00	1.129
Left Cheek Repeated	251/848.8	GPRS(GMSK 2TS)	1.035	0.805	0.05	33.66	34.00	1.119

NOTE: Head SAR test results of GSM850.

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	189/836.4	GPRS(GMSK 2TS)	0.669	0.525	4.38	33.72	34.00	0.714
Back Side	189/836.4	GPRS(GMSK 2TS)	1.051	0.760	-1.56	33.72	34.00	1.121
Back Side Repeated	189/836.4	GPRS(GMSK 2TS)	1.039	0.748	-0.16	33.72	34.00	1.108
Back Side	128/824.2	GPRS(GMSK 2TS)	0.942	0.678	2.65	33.67	34.00	1.016
Back Side	251/848.8	GPRS(GMSK 2TS)	0.931	0.677	3.63	33.66	34.00	1.007

NOTE: Body-Worn SAR test results of GSM850

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				

Front Side	189/836.4	GPRS(GMSK 2TS)	0.669	0.525	4.38	33.72	34.00	0.714
Back Side	189/836.4	GPRS(GMSK 2TS)	1.051	0.760	-1.56	33.72	34.00	1.121
Back Side Repeated	189/836.4	GPRS(GMSK 2TS)	1.039	0.748	-0.16	33.72	34.00	1.108
Left Side	189/836.4	GPRS(GMSK 2TS)	0.734	0.603	-1.00	33.72	34.00	0.783
Right Side	189/836.4	GPRS(GMSK 2TS)	0.468	0.338	0.83	33.72	34.00	0.499
Bottom Side	189/836.4	GPRS(GMSK 2TS)	0.381	0.277	-4.92	33.72	34.00	0.406
Back Side	128/824.2	GPRS(GMSK 2TS)	0.942	0.678	2.65	33.67	34.00	1.016
Back Side	251/848.8	GPRS(GMSK 2TS)	0.931	0.677	3.63	33.66	34.00	1.007

NOTE: Hotspot SAR test results of GSM850

10.1.2. SAR measurement Result of GSM1900

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	661/1880	GPRS(GMSK 4TS)	0.957	0.549	0.60	27.08	28.00	1.183
Left Cheek Repeated	661/1880	GPRS(GMSK 4TS)	0.933	0.534	-0.12	27.08	28.00	1.153
Left Tilt 15 Degree	661/1880	GPRS(GMSK 4TS)	0.568	0.321	-1.76	27.08	28.00	0.702
Right Cheek	661/1880	GPRS(GMSK 4TS)	0.646	0.489	0.73	27.08	28.00	0.798
Right Tilt 15 Degree	661/1880	GPRS(GMSK 4TS)	0.472	0.267	-1.11	27.08	28.00	0.583
Left Cheek	512/1850.2	GPRS(GMSK 4TS)	0.848	0.480	3.06	28.00	28.00	0.848
Left Cheek	810/1909.8	GPRS(GMSK 4TS)	0.856	0.480	-3.08	26.65	28.00	1.168

NOTE: Head SAR test results of GSM1900

Test Position	Test	Test Mode	SAR Value	Power	Conducted	Tune-up	Scaled
---------------	------	-----------	-----------	-------	-----------	---------	--------

of Body-Worn with 10mm	channel /Freq.		(W/kg)		Drift (±5%)	power (dBm)	power (dBm)	SAR 1g (W/Kg)
			1g	10g				
Front Side	661/1880	GPRS(GMSK 4TS)	0.491	0.252	3.89	27.08	28.00	0.607
Back Side	661/1880	GPRS(GMSK 4TS)	0.605	0.312	0.23	27.08	28.00	0.748

NOTE: Body-Worn SAR test results of GSM1900

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	661/1880	GPRS(GMSK 4TS)	0.491	0.252	3.89	27.08	28.00	0.607
Back Side	661/1880	GPRS(GMSK 4TS)	0.605	0.312	0.23	27.08	28.00	0.748
Left Side	661/1880	GPRS(GMSK 4TS)	0.429	0.219	1.19	27.08	28.00	0.530
Right Side	661/1880	GPRS(GMSK 4TS)	0.289	0.153	-2.18	27.08	28.00	0.357
Bottom Side	661/1880	GPRS(GMSK 4TS)	0.221	0.109	0.78	27.08	28.00	0.273

NOTE: Hotspot SAR test results of GSM1900

10.1.3. SAR measurement Result of WCDMA Band 2

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	9400/1880	RMC12.2K	0.830	0.490	-1.68	23.64	24.00	0.902
Left Cheek Repeated	9400/1880	RMC12.2K	0.818	0.487	0.03	23.64	24.00	0.889
Left Tilt 15 Degree	9400/1880	RMC12.2K	0.451	0.268	1.93	23.64	24.00	0.490
Right Cheek	9400/1880	RMC12.2K	0.728	0.459	-2.97	23.64	24.00	0.791
Right Tilt 15 Degree	9400/1880	RMC12.2K	0.362	0.216	2.07	23.64	24.00	0.393
Left Cheek	9262/1852.4	RMC12.2K	0.680	0.406	1.44	23.69	24.00	0.730
Left Cheek	9538/1907.6	RMC12.2K	0.749	0.441	3.43	23.75	24.00	0.793

NOTE: Head SAR test results of WCDMA Band 2

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	9400/1880	RMC12.2K	0.491	0.258	3.87	23.64	24.00	0.533
Back Side	9400/1880	RMC12.2K	0.644	0.342	-0.05	23.64	24.00	0.700

NOTE: Body-Worn SAR test results of WCDMA Band 2

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	9400/1880	RMC12.2K	0.491	0.258	3.87	23.64	24.00	0.533
Back Side	9400/1880	RMC12.2K	0.644	0.342	-0.05	23.64	24.00	0.700
Left Side	9400/1880	RMC12.2K	0.515	0.272	-0.08	23.64	24.00	0.560
Right Side	9400/1880	RMC12.2K	0.305	0.159	-4.95	23.64	24.00	0.331
Bottom Side	9400/1880	RMC12.2K	0.245	0.131	3.54	23.64	24.00	0.266

NOTE: Hotspot SAR test results of WCDMA Band 2

10.1.4. SAR measurement Result of WCDMA Band 4

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	1413/1732.6	RMC12.2K	0.580	0.363	-1.64	22.89	24.00	0.749
Left Tilt 15 Degree	1413/1732.6	RMC12.2K	0.305	0.187	-0.60	22.89	24.00	0.394
Right Cheek	1413/1732.6	RMC12.2K	0.530	0.335	4.09	22.89	24.00	0.684
Right Tilt 15 Degree	1413/1732.6	RMC12.2K	0.260	0.158	3.81	22.89	24.00	0.336

NOTE: Head SAR test results of WCDMA Band 4

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	1413/1732.6	RMC12.2K	0.275	0.176	4.88	22.89	24.00	0.355
Back Side	1413/1732.6	RMC12.2K	0.360	0.233	0.51	22.89	24.00	0.465

NOTE: Body-Worn SAR test results of WCDMA Band 4

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	1413/1732.6	RMC12.2K	0.275	0.176	4.88	22.89	24.00	0.355
Back Side	1413/1732.6	RMC12.2K	0.360	0.233	0.51	22.89	24.00	0.465

Left Side	1413/1732.6	RMC12.2K	0.285	0.188	0.41	22.89	24.00	0.368
Right Side	1413/1732.6	RMC12.2K	0.177	0.117	3.05	22.89	24.00	0.229
Bottom Side	1413/1732.6	RMC12.2K	0.134	0.083	-2.90	22.89	24.00	0.173

NOTE: Hotspot SAR test results of WCDMA Band 4

10.1.5. SAR measurement Result of WCDMA Band 5

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	4182/836.4	RMC12.2K	0.629	0.475	-0.12	23.30	24.00	0.739
Left Tilt 15 Degree	4182/836.4	RMC12.2K	0.347	0.263	0.01	23.30	24.00	0.408
Right Cheek	4182/836.4	RMC12.2K	0.540	0.412	4.93	23.30	24.00	0.634
Right Tilt 15 Degree	4182/836.4	RMC12.2K	0.268	0.204	4.32	23.30	24.00	0.315

NOTE: Head SAR test results of WCDMA Band 5

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	4182/836.4	RMC12.2K	0.603	0.412	-0.44	23.30	24.00	0.708
Back Side	4182/836.4	RMC12.2K	0.781	0.539	-0.05	23.30	24.00	0.918
Back Side	4132/826.4	RMC12.2K	0.776	0.522	-0.08	23.67	24.00	0.837
Back Side	4233/846.6	RMC12.2K	0.755	0.500	-1.99	23.10	24.00	0.929

NOTE: Body-Worn SAR test results of WCDMA Band 5

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	4182/836.4	RMC12.2K	0.603	0.412	-0.44	23.30	24.00	0.708
Back Side	4182/836.4	RMC12.2K	0.781	0.539	-0.05	23.30	24.00	0.918
Left Side	4182/836.4	RMC12.2K	0.616	0.421	2.69	23.30	24.00	0.724
Right Side	4182/836.4	RMC12.2K	0.349	0.239	-3.18	23.30	24.00	0.410
Bottom Side	4182/836.4	RMC12.2K	0.266	0.179	-2.59	23.30	24.00	0.313
Back Side	4132/826.4	RMC12.2K	0.776	0.522	-0.08	23.67	24.00	0.837
Back Side	4233/846.6	RMC12.2K	0.755	0.500	-1.99	23.10	24.00	0.929

NOTE: Hotspot SAR test results of WCDMA Band 5

10.1.6. SAR measurement Result of LTE Band 2

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left Cheek	18900/1880	20M QPSK(1,49)	0.677	0.431	-2.60	23.29	24.00	0.797
Left Tilt 15 Degree	18900/1880	20M QPSK(1,49)	0.419	0.248	-3.25	23.29	24.00	0.493
Right Cheek	18900/1880	20M QPSK(1,49)	0.640	0.375	3.46	23.29	24.00	0.754
Right Tilt 15 Degree	18900/1880	20M QPSK(1,49)	0.300	0.175	-0.78	23.29	24.00	0.353
50%RB								
Left Cheek	18900/1880	1.4M QPSK(3,0)	0.644	0.401	1.60	23.59	24.00	0.708
Left Tilt 15 Degree	18900/1880	1.4M QPSK(3,0)	0.371	0.223	-2.24	23.59	24.00	0.408
Right Cheek	18900/1880	1.4M QPSK(3,0)	0.553	0.342	2.18	23.59	24.00	0.608
Right Tilt 15 Degree	18900/1880	1.4M QPSK(3,0)	0.280	0.152	-2.03	23.59	24.00	0.308

NOTE: Head SAR test results of LTE Band 2

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	18900/1880	20M QPSK(1,49)	0.654	0.439	-0.11	23.29	24.00	0.770
Back Side	18900/1880	20M QPSK(1,49)	1.009	0.581	-1.63	23.29	24.00	1.188
Back Side Repeated	18900/1880	20M QPSK(1,49)	0.996	0.569	0.08	23.29	24.00	1.173
Back Side	18700/1860	20M QPSK(1,49)	0.942	0.509	2.30	23.10	24.00	1.159

Back Side	19100/1900	20M QPSK(1,49)	0.966	0.525	-4.56	23.36	24.00	1.119
50%RB								
Front Side	18900/1880	1.4M QPSK(3,0)	0.404	0.225	2.67	23.59	24.00	0.444
Back Side	18900/1880	1.4M QPSK(3,0)	0.630	0.329	-1.35	23.59	24.00	0.692
100%RB								
Back Side	18900/1880	20M QPSK(100,0)	0.544	0.323	0.09	22.10	23.00	0.669

NOTE: Body-Worn SAR test results of LTE Band 2

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conduc ted power (dBm)	Tune-u p power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	18900/1880	20M QPSK(1,49)	0.654	0.439	-0.11	23.29	24.00	0.770
Back Side	18900/1880	20M QPSK(1,49)	1.009	0.581	-1.63	23.29	24.00	1.188
Back Side Repeated	18900/1880	20M QPSK(1,49)	0.996	0.569	0.08	23.29	24.00	1.173
Left Side	18900/1880	20M QPSK(1,49)	0.597	0.429	0.84	23.29	24.00	0.703
Right Side	18900/1880	20M QPSK(1,49)	0.461	0.249	-3.50	23.29	24.00	0.543
Bottom Side	18900/1880	20M QPSK(1,49)	0.410	0.226	2.04	23.29	24.00	0.483
Back Side	18700/1860	20M QPSK(1,49)	0.942	0.509	2.30	23.10	24.00	1.159
Back Side	19100/1900	20M QPSK(1,49)	0.966	0.525	-4.56	23.36	24.00	1.119
50%RB								
Front Side	18900/1880	1.4M QPSK(3,0)	0.404	0.225	2.67	23.59	24.00	0.444
Back Side	18900/1880	1.4M QPSK(3,0)	0.630	0.329	-1.35	23.59	24.00	0.692
Left Side	18900/1880	1.4M QPSK(3,0)	0.368	0.228	-4.08	23.59	24.00	0.404
Right Side	18900/1880	1.4M QPSK(3,0)	0.263	0.130	3.65	23.59	24.00	0.289
Bottom Side	18900/1880	1.4M QPSK(3,0)	0.233	0.134	-0.40	23.59	24.00	0.256
100%RB								
Back Side	18900/1880	20M QPSK(100,0)	0.544	0.323	0.09	22.10	23.00	0.669

NOTE: Hotspot SAR test results of LTE Band 2

10.1.7. SAR measurement Result of LTE Band 4

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left Cheek	20175/1732.5	20M QPSK(1,49)	0.561	0.338	1.13	22.99	24.00	0.708
Left Tilt 15 Degree	20175/1732.5	20M QPSK(1,49)	0.289	0.173	3.84	22.99	24.00	0.365
Right Cheek	20175/1732.5	20M QPSK(1,49)	0.521	0.311	2.97	22.99	24.00	0.657
Right Tilt 15 Degree	20175/1732.5	20M QPSK(1,49)	0.235	0.147	-2.77	22.99	24.00	0.297
50%RB								
Left Cheek	20175/1732.5	1.4M QPSK(3,1)	0.504	0.317	3.34	22.94	24.00	0.643
Left Tilt 15 Degree	20175/1732.5	1.4M QPSK(3,1)	0.268	0.154	2.13	22.94	24.00	0.342
Right Cheek	20175/1732.5	1.4M QPSK(3,1)	0.464	0.288	2.72	22.94	24.00	0.592
Right Tilt 15 Degree	20175/1732.5	1.4M QPSK(3,1)	0.216	0.127	4.98	22.94	24.00	0.276

NOTE: Head SAR test results of LTE Band 4

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	20175/1732.5	20M QPSK(1,49)	0.275	0.184	-1.32	22.99	24.00	0.347
Back Side	20175/1732.5	20M QPSK(1,49)	0.329	0.216	-1.11	22.99	24.00	0.415
50%RB								
Front Side	20175/1732.5	1.4M QPSK(3,1)	0.247	0.172	0.12	22.94	24.00	0.315

	5							
Back Side	20175/1732.5	1.4M QPSK(3,1)	0.307	0.193	-4.90	22.94	24.00	0.392

NOTE: Body-Worn SAR test results of LTE Band 4

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conduc ted power (dBm)	Tune-u p power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	20175/1732.5	20M QPSK(1,49)	0.275	0.184	-1.32	22.99	24.00	0.347
Back Side	20175/1732.5	20M QPSK(1,49)	0.329	0.216	-1.11	22.99	24.00	0.415
Left Side	20175/1732.5	20M QPSK(1,49)	0.236	0.151	-0.67	22.99	24.00	0.298
Right Side	20175/1732.5	20M QPSK(1,49)	0.142	0.095	-4.61	22.99	24.00	0.179
Bottom Side	20175/1732.5	20M QPSK(1,49)	0.112	0.078	4.33	22.99	24.00	0.141
50%RB								
Front Side	20175/1732.5	1.4M QPSK(3,1)	0.247	0.172	0.12	22.94	24.00	0.315
Back Side	20175/1732.5	1.4M QPSK(3,1)	0.307	0.193	-4.90	22.94	24.00	0.392
Left Side	20175/1732.5	1.4M QPSK(3,1)	0.208	0.141	-4.50	22.94	24.00	0.265
Right Side	20175/1732.5	1.4M QPSK(3,1)	0.132	0.087	-4.11	22.94	24.00	0.168
Bottom Side	20175/1732.5	1.4M QPSK(3,1)	0.103	0.071	0.45	22.94	24.00	0.131

NOTE: Hotspot SAR test results of LTE Band 4

10.1.8. SAR measurement Result of LTE Band 5

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left	20525/836.5	10M QPSK(1,24)	0.676	0.507	-0.95	23.38	24.00	0.780

Cheek								
Left Tilt 15 Degree	20525/836.5	10M QPSK(1,24)	0.347	0.257	1.16	23.38	24.00	0.400
Right Cheek	20525/836.5	10M QPSK(1,24)	0.596	0.450	1.63	23.38	24.00	0.687
Right Tilt 15 Degree	20525/836.5	10M QPSK(1,24)	0.287	0.212	4.78	23.38	24.00	0.331
50%RB								
Left Cheek	20525/836.5	1.4M QPSK(3,1)	0.621	0.438	-2.07	23.22	24.00	0.743
Left Tilt 15 Degree	20525/836.5	1.4M QPSK(3,1)	0.329	0.221	-1.42	23.22	24.00	0.394
Right Cheek	20525/836.5	1.4M QPSK(3,1)	0.559	0.426	3.25	23.22	24.00	0.669
Right Tilt 15 Degree	20525/836.5	1.4M QPSK(3,1)	0.251	0.181	-2.32	23.22	24.00	0.300

NOTE: Head SAR test results of LTE Band 5

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	20525/836.5	10M QPSK(1,24)	0.685	0.475	2.87	23.38	24.00	0.790
Back Side	20525/836.5	10M QPSK(1,24)	0.817	0.568	-0.68	23.38	24.00	0.942
Back Side Repeated	20525/836.5	10M QPSK(1,24)	0.800	0.561	0.04	23.38	24.00	0.923
Back Side	20450/829	10M QPSK(1,24)	0.808	0.560	-3.33	23.31	24.00	0.947
Back Side	20600/844	10M QPSK(1,24)	0.796	0.546	3.97	23.10	24.00	0.979
50%RB								
Front Side	20525/836.5	1.4M QPSK(3,1)	0.617	0.427	-2.98	23.22	24.00	0.738
Back Side	20525/836.5	1.4M QPSK(3,1)	0.644	0.489	1.06	23.22	24.00	0.771
100%RB								

Back Side	20525/836.5	10M QPSK(50,0)	0.577	0.398	0.07	22.16	23.00	0.700
-----------	-------------	-------------------	-------	-------	------	-------	-------	-------

NOTE: Body-Worn SAR test results of LTE Band 5

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	20525/836.5	10M QPSK(1,24)	0.685	0.475	2.87	23.38	24.00	0.790
Back Side	20525/836.5	10M QPSK(1,24)	0.817	0.568	-0.68	23.38	24.00	0.942
Back Side Repeated	20525/836.5	10M QPSK(1,24)	0.800	0.561	0.04	23.38	24.00	0.923
Left Side	20525/836.5	10M QPSK(1,24)	0.651	0.457	4.00	23.38	24.00	0.751
Right Side	20525/836.5	10M QPSK(1,24)	0.384	0.267	1.29	23.38	24.00	0.443
Bottom Side	20525/836.5	10M QPSK(1,24)	0.322	0.221	4.73	23.38	24.00	0.371
Back Side	20450/829	10M QPSK(1,24)	0.808	0.560	-3.33	23.31	24.00	0.947
Back Side	20600/844	10M QPSK(1,24)	0.796	0.546	3.97	23.10	24.00	0.979
50%RB								
Front Side	20525/836.5	1.4M QPSK(3,1)	0.617	0.427	-2.98	23.22	24.00	0.738
Back Side	20525/836.5	1.4M QPSK(3,1)	0.644	0.489	1.06	23.22	24.00	0.771
Left Side	20525/836.5	1.4M QPSK(3,1)	0.577	0.404	-1.04	23.22	24.00	0.691
Right Side	20525/836.5	1.4M QPSK(3,1)	0.334	0.229	-4.92	23.22	24.00	0.400
Bottom Side	20525/836.5	1.4M QPSK(3,1)	0.278	0.197	1.08	23.22	24.00	0.333
100%RB								
Back Side	20525/836.5	10M QPSK(50,0)	0.577	0.398	0.07	22.16	23.00	0.700

NOTE: Hotspot SAR test results of LTE Band 5

10.1.9. SAR measurement Result of LTE Band 7

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left Cheek	21100/2535	20M QPSK(1,49)	0.914	0.500	-2.05	21.84	23.00	1.194
Left Cheek Repeated	21100/2535	20M QPSK(1,49)	0.903	0.489	0.02	21.84	23.00	1.179
Left Tilt 15 Degree	21100/2535	20M QPSK(1,49)	0.510	0.282	4.60	21.84	23.00	0.666
Right Cheek	21100/2535	20M QPSK(1,49)	0.607	0.474	3.16	21.84	23.00	0.793
Right Tilt 15 Degree	21100/2535	20M QPSK(1,49)	0.453	0.244	3.80	21.84	23.00	0.592
Left Cheek	20850/2510	20M QPSK(1,49)	0.800	0.410	-0.21	21.37	23.00	1.164
Left Cheek	21350/2560	20M QPSK(1,49)	0.850	0.455	3.33	22.49	23.00	0.956
50%RB								
Left Cheek	21100/2535	20M QPSK(50,49)	0.525	0.263	4.22	20.88	22.00	0.679
Left Tilt 15 Degree	21100/2535	20M QPSK(50,49)	0.285	0.158	-1.41	20.88	22.00	0.369
Right Cheek	21100/2535	20M QPSK(50,49)	0.486	0.241	-0.11	20.88	22.00	0.629
Right Tilt 15 Degree	21100/2535	20M QPSK(50,49)	0.227	0.140	-2.07	20.88	22.00	0.294
100%RB								
Left Cheek	21100/2535	20M QPSK(100,0)	0.551	0.276	0.13	20.78	22.00	0.730

NOTE: Head SAR test results of LTE Band 7

Test Position of Body-Wor n with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conduc ted power (dBm)	Tune-u p power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	21100/2535	20M QPSK(1,49)	0.473	0.228	0.24	21.84	23.00	0.618
Back Side	21100/2535	20M QPSK(1,49)	0.611	0.301	-2.22	21.84	23.00	0.798
50%RB								
Front Side	21100/2535	20M QPSK(50,49)	0.237	0.123	-3.36	20.88	22.00	0.307
Back Side	21100/2535	20M QPSK(50,49)	0.307	0.151	-4.85	20.88	22.00	0.397

NOTE: Body-Worn SAR test results of LTE Band 7

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conduc ted power (dBm)	Tune-u p power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	21100/2535	20M QPSK(1,49)	0.473	0.228	0.24	21.84	23.00	0.618
Back Side	21100/2535	20M QPSK(1,49)	0.611	0.301	-2.22	21.84	23.00	0.798
Left Side	21100/2535	20M QPSK(1,49)	0.477	0.236	-0.27	21.84	23.00	0.623
Right Side	21100/2535	20M QPSK(1,49)	0.293	0.139	3.79	21.84	23.00	0.383
Bottom Side	21100/2535	20M QPSK(1,49)	0.220	0.109	1.21	21.84	23.00	0.287
50%RB								
Front Side	21100/2535	20M QPSK(50,49)	0.237	0.123	-3.36	20.88	22.00	0.307
Back Side	21100/2535	20M QPSK(50,49)	0.307	0.151	-4.85	20.88	22.00	0.397
Left Side	21100/2535	20M QPSK(50,49)	0.275	0.138	-0.54	20.88	22.00	0.356
Right Side	21100/2535	20M QPSK(50,49)	0.158	0.074	-4.47	20.88	22.00	0.204
Bottom Side	21100/2535	20M QPSK(50,49)	0.126	0.062	-1.31	20.88	22.00	0.163

NOTE: Hotspot SAR test results of LTE Band 7

10.1.10. SAR measurement Result of LTE Band 12

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left Cheek	23095/707.5	10M QPSK(1,24)	0.418	0.330	-0.11	21.88	23.00	0.541
Left Tilt 15 Degree	23095/707.5	10M QPSK(1,24)	0.239	0.187	-0.10	21.88	23.00	0.309
Right Cheek	23095/707.5	10M QPSK(1,24)	0.396	0.310	1.81	21.88	23.00	0.513
Right Tilt 15 Degree	23095/707.5	10M QPSK(1,24)	0.201	0.160	1.77	21.88	23.00	0.260
50%RB								
Left Cheek	23095/707.5	1.4M QPSK(3,2)	0.366	0.300	1.78	21.83	22.00	0.381
Left Tilt 15 Degree	23095/707.5	1.4M QPSK(3,2)	0.206	0.167	3.87	21.83	22.00	0.214
Right Cheek	23095/707.5	1.4M QPSK(3,2)	0.352	0.278	-3.10	21.83	22.00	0.366
Right Tilt 15 Degree	23095/707.5	1.4M QPSK(3,2)	0.187	0.148	-2.40	21.83	22.00	0.194

NOTE: Head SAR test results of LTE Band 12

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	23095/707.5	10M QPSK(1,24)	0.460	0.353	-4.07	21.88	23.00	0.595
Back Side	23095/707.5	10M QPSK(1,24)	0.607	0.468	-0.63	21.88	23.00	0.786
50%RB								
Front Side	23095/707.5	1.4M QPSK(3,2)	0.405	0.317	-3.26	21.83	22.00	0.421

Back Side	23095/707.5	1.4M QPSK(3,2)	0.549	0.402	3.30	21.83	22.00	0.571
-----------	-------------	----------------	-------	-------	------	-------	-------	-------

NOTE: Body-Worn SAR test results of LTE Band 12

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	23095/707.5	10M QPSK(1,24)	0.460	0.353	-4.07	21.88	23.00	0.595
Back Side	23095/707.5	10M QPSK(1,24)	0.607	0.468	-0.63	21.88	23.00	0.786
Left Side	23095/707.5	10M QPSK(1,24)	0.443	0.340	0.75	21.88	23.00	0.573
Right Side	23095/707.5	10M QPSK(1,24)	0.269	0.203	0.60	21.88	23.00	0.348
Bottom Side	23095/707.5	10M QPSK(1,24)	0.230	0.176	-4.21	21.88	23.00	0.298
50%RB								
Front Side	23095/707.5	1.4M QPSK(3,2)	0.405	0.317	-3.26	21.83	22.00	0.421
Back Side	23095/707.5	1.4M QPSK(3,2)	0.549	0.402	3.30	21.83	22.00	0.571
Left Side	23095/707.5	1.4M QPSK(3,2)	0.406	0.292	2.26	21.83	22.00	0.422
Right Side	23095/707.5	1.4M QPSK(3,2)	0.235	0.180	-1.87	21.83	22.00	0.244
Bottom Side	23095/707.5	1.4M QPSK(3,2)	0.204	0.153	-2.50	21.83	22.00	0.212

NOTE: Hotspot SAR test results of LTE Band 12

10.1.11. SAR measurement Result of LTE Band 17

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Left Cheek	23790/710	10M QPSK(1,24)	0.394	0.311	-0.33	22.71	23.00	0.421
Left Tilt	23790/710	10M QPSK(1,24)	0.226	0.183	4.30	22.71	23.00	0.242

15 Degree								
Right Cheek	23790/710	10M QPSK(1,24)	0.365	0.286	-0.98	22.71	23.00	0.390
Right Tilt 15 Degree	23790/710	10M QPSK(1,24)	0.180	0.144	1.35	22.71	23.00	0.192
50%RB								
Left Cheek	23790/710	10M QPSK(25,0)	0.221	0.183	-1.39	21.73	22.00	0.235
Left Tilt 15 Degree	23790/710	10M QPSK(25,0)	0.119	0.094	2.25	21.73	22.00	0.127
Right Cheek	23790/710	10M QPSK(25,0)	0.188	0.161	2.10	21.73	22.00	0.200
Right Tilt 15 Degree	23790/710	10M QPSK(25,0)	0.105	0.083	2.25	21.73	22.00	0.112

NOTE: Head SAR test results of LTE Band 17

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	23790/710	10M QPSK(1,24)	0.509	0.388	1.50	22.71	23.00	0.544
Back Side	23790/710	10M QPSK(1,24)	0.629	0.483	-1.31	22.71	23.00	0.672
50%RB								
Front Side	23790/710	10M QPSK(25,0)	0.286	0.202	4.88	21.73	22.00	0.304
Back Side	23790/710	10M QPSK(25,0)	0.336	0.284	-4.19	21.73	22.00	0.358

NOTE: Body-Worn SAR test results of LTE Band 17

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
1RB								
Front Side	23790/710	10M QPSK(1,24)	0.509	0.388	1.50	22.71	23.00	0.544

Back Side	23790/710	10M QPSK(1,24)	0.629	0.483	-1.31	22.71	23.00	0.672
Left Side	23790/710	10M QPSK(1,24)	0.497	0.381	-0.03	22.71	23.00	0.531
Right Side	23790/710	10M QPSK(1,24)	0.275	0.209	-4.12	22.71	23.00	0.294
Bottom Side	23790/710	10M QPSK(1,24)	0.249	0.193	3.83	22.71	23.00	0.266
50%RB								
Front Side	23790/710	10M QPSK(25,0)	0.286	0.202	4.88	21.73	22.00	0.304
Back Side	23790/710	10M QPSK(25,0)	0.336	0.284	-4.19	21.73	22.00	0.358
Left Side	23790/710	10M QPSK(25,0)	0.289	0.202	-1.67	21.73	22.00	0.308
Right Side	23790/710	10M QPSK(25,0)	0.162	0.113	2.86	21.73	22.00	0.172
Bottom Side	23790/710	10M QPSK(25,0)	0.131	0.110	0.96	21.73	22.00	0.139

NOTE: Hotspot SAR test results of LTE Band 17

10.1.12. SAR measurement Result of WLAN 2.4G

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Left Cheek	6/2437	802.11b	0.340	0.203	-0.30	13.26	14.00	0.403
Left Tilt 15 Degree	6/2437	802.11b	0.240	0.111	2.88	13.26	14.00	0.285
Right Cheek	6/2437	802.11b	0.275	0.174	-0.06	13.26	14.00	0.326
Right Tilt 15 Degree	6/2437	802.11b	0.178	0.081	4.84	13.26	14.00	0.211

NOTE: Head SAR test results of WLAN 2.4G

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	6/2437	802.11b	0.067	0.041	-3.14	13.26	14.00	0.079
Back Side	6/2437	802.11b	0.110	0.066	-1.91	13.26	14.00	0.130

NOTE: Body-Worn SAR test results of WLAN 2.4G

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	6/2437	802.11b	0.067	0.041	-3.14	13.26	14.00	0.079
Back Side	6/2437	802.11b	0.110	0.066	-1.91	13.26	14.00	0.130
Right Side	6/2437	802.11b	0.026	0.016	-0.43	13.26	14.00	0.031
Top Side	6/2437	802.11b	0.038	0.020	2.42	13.26	14.00	0.045

NOTE: Hotspot SAR test results of WLAN 2.4G

10.1.13. SAR measurement Result of WLAN 5.2G

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Right Cheek	40/5200	802.11a	0.217	0.100	-0.47	8.52	10.00	0.305
Right Tilt 15 Degree	40/5200	802.11a	0.127	0.056	0.50	8.52	10.00	0.179
Left Cheek	40/5200	802.11a	0.202	0.091	-4.68	8.52	10.00	0.284
Left Tilt 15 Degree	40/5200	802.11a	0.107	0.048	0.47	8.52	10.00	0.150

NOTE: Head SAR test results of WLAN 5.2G

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	40/5200	802.11a	0.102	0.069	3.01	8.52	10.00	0.143
Back Side	40/5200	802.11a	0.167	0.111	-3.93	8.52	10.00	0.235

NOTE: Body-Worn SAR test results of WLAN 5.2G

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	40/5200	802.11a	0.102	0.069	3.01	8.52	10.00	0.143
Back Side	40/5200	802.11a	0.167	0.111	-3.93	8.52	10.00	0.235
Right Side	40/5200	802.11a	0.034	0.027	0.44	8.52	10.00	0.048
Top Side	40/5200	802.11a	0.051	0.038	0.21	8.52	10.00	0.072

NOTE: Hotspot SAR test results of WLAN 5.2G

10.1.14. SAR measurement Result of WLAN 5.8G

Test Position of Head	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Right Cheek	149/5745	802.11a	0.342	0.155	2.63	9.37	10.00	0.396
Right Tilt 15 Degree	149/5745	802.11a	0.212	0.074	-1.10	9.37	10.00	0.245
Left Cheek	149/5745	802.11a	0.269	0.137	-2.87	9.37	10.00	0.311
Left Tilt 15 Degree	149/5745	802.11a	0.182	0.066	3.94	9.37	10.00	0.210

NOTE: Head SAR test results of WLAN 5.8G

Test Position of Body-Worn with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	149/5745	802.11a	0.192	0.100	0.97	9.37	10.00	0.222
Back Side	149/5745	802.11a	0.311	0.164	-1.00	9.37	10.00	0.360

NOTE: Body-Worn SAR test results of WLAN 5.8G

Test Position of Hotspot with 10mm	Test channel /Freq.	Test Mode	SAR Value (W/kg)		Power Drift (±5%)	Conducted power (dBm)	Tune-up power (dBm)	Scaled SAR 1g (W/Kg)
			1g	10g				
Front Side	149/5745	802.11a	0.192	0.100	0.97	9.37	10.00	0.222
Back Side	149/5745	802.11a	0.311	0.164	-1.00	9.37	10.00	0.360
Right Side	149/5745	802.11a	0.074	0.038	0.68	9.37	10.00	0.086
Top Side	149/5745	802.11a	0.102	0.057	2.67	9.37	10.00	0.118

NOTE: Hotspot SAR test results of WLAN 5.2G

10.2. SAR Summation Scenario

Per KDB 447498 D01, simultaneous transmission SAR is compliant if,

- 1) Scalar SAR summation $< 1.6\text{W/kg}$.
- 2) $\text{SPLSR} = (\text{SAR}_1 + \text{SAR}_2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2]$, where (x_1, y_1, z_1) and (x_2, y_2, z_2) are the coordinates of the extrapolated peak SAR locations in the zoom scan. If $\text{SPLSR} \leq 0.04$, simultaneously transmission SAR measurement is not necessary.

Test Position	Scaled SAR _{MAX}	Σ 1-g SAR	SPLSR	Remark
---------------	---------------------------	-----------	-------	--------

		GSM 850	WLAN 2.4G	(W/Kg)		
Head	Left Cheek	1.129	0.403	1.532	N/A	N/A
	Left Tilt 15 Degree	0.548	0.285	0.833	N/A	N/A
	Right Cheek	0.783	0.326	1.109	N/A	N/A
	Right Tilt 15 Degree	0.532	0.211	0.743	N/A	N/A
Body-Worn	Front Side	0.714	0.079	0.793	N/A	N/A
	Back Side	1.121	0.130	1.251	N/A	N/A
Hotspot	Front Side	0.714	0.079	0.793	N/A	N/A
	Back Side	1.121	0.130	1.251	N/A	N/A
	Left Side	0.783	N/A	0.783	N/A	N/A
	Right Side	0.499	0.031	0.530	N/A	N/A
	Top Side	N/A	0.045	0.045	N/A	N/A
	Bottom Side	0.406	N/A	0.406	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM850 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 1900	WLAN 2.4G			
Head	Left Cheek	1.183	0.403	1.586	N/A	N/A
	Left Tilt 15 Degree	0.702	0.285	0.987	N/A	N/A
	Right Cheek	0.798	0.326	1.125	N/A	N/A
	Right Tilt 15 Degree	0.583	0.211	0.794	N/A	N/A
Body-Worn	Front Side	0.607	0.079	0.686	N/A	N/A
	Back Side	0.748	0.130	0.878	N/A	N/A
Hotspot	Front Side	0.607	0.079	0.686	N/A	N/A
	Back Side	0.748	0.130	0.878	N/A	N/A
	Left Side	0.530	N/A	0.530	N/A	N/A
	Right Side	0.357	0.031	0.388	N/A	N/A
	Top Side	N/A	0.045	0.045	N/A	N/A
	Bottom Side	0.273	N/A	0.273	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM1900 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 2	WLAN 2.4G			
Head	Left Cheek	0.902	0.403	1.305	N/A	N/A
	Left Tilt 15 Degree	0.490	0.285	0.775	N/A	N/A
	Right Cheek	0.791	0.326	1.117	N/A	N/A
	Right Tilt 15 Degree	0.393	0.211	0.604	N/A	N/A
Body-Worn	Front Side	0.533	0.079	0.613	N/A	N/A

	Back Side	0.700	0.130	0.830	N/A	N/A
Hotspot	Front Side	0.533	0.079	0.613	N/A	N/A
	Back Side	0.700	0.130	0.830	N/A	N/A
	Left Side	0.560	N/A	0.560	N/A	N/A
	Right Side	0.331	0.031	0.362	N/A	N/A
	Top Side	N/A	0.045	0.045	N/A	N/A
	Bottom Side	0.266	N/A	0.266	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 2 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 4	WLAN 2.4G			
Head	Left Cheek	0.749	0.403	1.152	N/A	N/A
	Left Tilt 15 Degree	0.394	0.285	0.678	N/A	N/A
	Right Cheek	0.684	0.326	1.010	N/A	N/A
	Right Tilt 15 Degree	0.336	0.211	0.547	N/A	N/A
Body-Worn	Front Side	0.355	0.079	0.435	N/A	N/A
	Back Side	0.465	0.130	0.595	N/A	N/A
Hotspot	Front Side	0.355	0.079	0.435	N/A	N/A
	Back Side	0.465	0.130	0.595	N/A	N/A
	Left Side	0.368	N/A	0.368	N/A	N/A
	Right Side	0.229	0.031	0.259	N/A	N/A
	Top Side	N/A	0.045	0.045	N/A	N/A
	Bottom Side	0.173	N/A	0.173	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 4 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 5	WLAN 2.4G			
Head	Left Cheek	0.739	0.403	1.142	N/A	N/A
	Left Tilt 15 Degree	0.408	0.285	0.692	N/A	N/A
	Right Cheek	0.634	0.326	0.961	N/A	N/A
	Right Tilt 15 Degree	0.315	0.211	0.526	N/A	N/A
Body-Worn	Front Side	0.708	0.079	0.788	N/A	N/A
	Back Side	0.929	0.130	1.059	N/A	N/A
Hotspot	Front Side	0.708	0.079	0.788	N/A	N/A
	Back Side	0.929	0.130	1.059	N/A	N/A
	Left Side	0.724	N/A	0.724	N/A	N/A
	Right Side	0.410	0.031	0.441	N/A	N/A
	Top Side	N/A	0.045	0.045	N/A	N/A

	Bottom Side	0.313	N/A	0.313	N/A	N/A
--	-------------	-------	-----	-------	-----	-----

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 5 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 2	WLAN 2.4G			
Head	Left Cheek	0.797	0.403	1.200	N/A	N/A
	Left Tilt 15 Degree	0.493	0.285	0.778	N/A	N/A
	Right Cheek	0.754	0.326	1.080	N/A	N/A
	Right Tilt 15 Degree	0.353	0.211	0.564	N/A	N/A
Body-Worn	Front Side	0.770	0.079	0.850	N/A	N/A
	Back Side	1.188	0.130	1.319	N/A	N/A
Hotspot	Front Side	0.770	0.079	0.850	N/A	N/A
	Back Side	1.188	0.130	1.319	N/A	N/A
	Left Side	0.703	N/A	0.703	N/A	N/A
	Right Side	0.543	0.031	0.574	N/A	N/A
	Top Side	N/A	0.045	0.045	N/A	N/A
	Bottom Side	0.483	N/A	0.483	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 2 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 4	WLAN 2.4G			
Head	Left Cheek	0.708	0.403	1.111	N/A	N/A
	Left Tilt 15 Degree	0.365	0.285	0.649	N/A	N/A
	Right Cheek	0.657	0.326	0.983	N/A	N/A
	Right Tilt 15 Degree	0.297	0.211	0.508	N/A	N/A
Body-Worn	Front Side	0.347	0.079	0.426	N/A	N/A
	Back Side	0.415	0.130	0.546	N/A	N/A
Hotspot	Front Side	0.347	0.079	0.426	N/A	N/A
	Back Side	0.415	0.130	0.546	N/A	N/A
	Left Side	0.298	N/A	0.298	N/A	N/A
	Right Side	0.179	0.031	0.210	N/A	N/A
	Top Side	N/A	0.045	0.045	N/A	N/A
	Bottom Side	0.141	N/A	0.141	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 4 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 5	WLAN 2.4G			
Head	Left Cheek	0.780	0.403	1.183	N/A	N/A
	Left Tilt 15 Degree	0.400	0.285	0.685	N/A	N/A

	Right Cheek	0.687	0.326	1.014	N/A	N/A
	Right Tilt 15 Degree	0.331	0.211	0.542	N/A	N/A
Body-Worn	Front Side	0.790	0.079	0.870	N/A	N/A
	Back Side	0.979	0.130	1.110	N/A	N/A
Hotspot	Front Side	0.790	0.079	0.870	N/A	N/A
	Back Side	0.979	0.130	1.110	N/A	N/A
	Left Side	0.751	N/A	0.751	N/A	N/A
	Right Side	0.443	0.031	0.474	N/A	N/A
	Top Side	N/A	0.045	0.045	N/A	N/A
	Bottom Side	0.371	N/A	0.371	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 5 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 7	WLAN 2.4G			
Head	Left Cheek	1.194	0.403	1.597	N/A	N/A
	Left Tilt 15 Degree	0.666	0.285	0.951	N/A	N/A
	Right Cheek	0.793	0.326	1.119	N/A	N/A
	Right Tilt 15 Degree	0.592	0.211	0.803	N/A	N/A
Body-Worn	Front Side	0.618	0.079	0.697	N/A	N/A
	Back Side	0.798	0.130	0.929	N/A	N/A
Hotspot	Front Side	0.618	0.079	0.697	N/A	N/A
	Back Side	0.798	0.130	0.929	N/A	N/A
	Left Side	0.623	N/A	0.623	N/A	N/A
	Right Side	0.383	0.031	0.414	N/A	N/A
	Top Side	N/A	0.045	0.045	N/A	N/A
	Bottom Side	0.287	N/A	0.287	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 7 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 12	WLAN 2.4G			
Head	Left Cheek	0.541	0.403	0.944	N/A	N/A
	Left Tilt 15 Degree	0.309	0.285	0.594	N/A	N/A
	Right Cheek	0.513	0.326	0.839	N/A	N/A
	Right Tilt 15 Degree	0.260	0.211	0.471	N/A	N/A
Body-Worn	Front Side	0.595	0.079	0.675	N/A	N/A
	Back Side	0.786	0.130	0.916	N/A	N/A
Hotspot	Front Side	0.595	0.079	0.675	N/A	N/A
	Back Side	0.786	0.130	0.916	N/A	N/A

	Left Side	0.573	N/A	0.573	N/A	N/A
	Right Side	0.348	0.031	0.379	N/A	N/A
	Top Side	N/A	0.045	0.045	N/A	N/A
	Bottom Side	0.298	N/A	0.298	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 12 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 17	WLAN 2.4G			
Head	Left Cheek	0.421	0.403	0.824	N/A	N/A
	Left Tilt 15 Degree	0.242	0.285	0.526	N/A	N/A
	Right Cheek	0.390	0.326	0.716	N/A	N/A
	Right Tilt 15 Degree	0.192	0.211	0.403	N/A	N/A
Body-Worn	Front Side	0.544	0.079	0.624	N/A	N/A
	Back Side	0.672	0.130	0.803	N/A	N/A
Hotspot	Front Side	0.544	0.079	0.624	N/A	N/A
	Back Side	0.672	0.130	0.803	N/A	N/A
	Left Side	0.531	N/A	0.531	N/A	N/A
	Right Side	0.294	0.031	0.325	N/A	N/A
	Top Side	N/A	0.045	0.045	N/A	N/A
	Bottom Side	0.266	N/A	0.266	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 17 and WLAN 2.4G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 850	Bluetooth			
Head	Left Cheek	1.129	0.265	1.394	N/A	N/A
	Left Tilt 15 Degree	0.548	0.265	0.813	N/A	N/A
	Right Cheek	0.783	0.265	1.048	N/A	N/A
	Right Tilt 15 Degree	0.532	0.265	0.797	N/A	N/A
Body-Worn	Front Side	0.714	0.132	0.846	N/A	N/A
	Back Side	1.121	0.132	1.253	N/A	N/A
Hotspot	Front Side	0.714	0.132	0.846	N/A	N/A
	Back Side	1.121	0.132	1.253	N/A	N/A
	Left Side	0.783	N/A	0.783	N/A	N/A
	Right Side	0.499	0.132	0.632	N/A	N/A
	Top Side	N/A	0.132	0.132	N/A	N/A
	Bottom Side	0.406	N/A	0.406	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM850 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 1900	Bluetooth			
Head	Left Cheek	1.183	0.265	1.448	N/A	N/A
	Left Tilt 15 Degree	0.702	0.265	0.967	N/A	N/A
	Right Cheek	0.798	0.265	1.063	N/A	N/A
	Right Tilt 15 Degree	0.583	0.265	0.848	N/A	N/A
Body-Worn	Front Side	0.607	0.132	0.739	N/A	N/A
	Back Side	0.748	0.132	0.880	N/A	N/A
Hotspot	Front Side	0.607	0.132	0.739	N/A	N/A
	Back Side	0.748	0.132	0.880	N/A	N/A
	Left Side	0.530	N/A	0.530	N/A	N/A
	Right Side	0.357	0.132	0.490	N/A	N/A
	Top Side	N/A	0.132	0.132	N/A	N/A
	Bottom Side	0.273	N/A	0.273	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM1900 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 2	Bluetooth			
Head	Left Cheek	0.902	0.265	1.167	N/A	N/A
	Left Tilt 15 Degree	0.490	0.265	0.755	N/A	N/A
	Right Cheek	0.791	0.265	1.056	N/A	N/A
	Right Tilt 15 Degree	0.393	0.265	0.658	N/A	N/A
Body-Worn	Front Side	0.533	0.132	0.666	N/A	N/A
	Back Side	0.700	0.132	0.832	N/A	N/A
Hotspot	Front Side	0.533	0.132	0.666	N/A	N/A
	Back Side	0.700	0.132	0.832	N/A	N/A
	Left Side	0.560	N/A	0.560	N/A	N/A
	Right Side	0.331	0.132	0.464	N/A	N/A
	Top Side	N/A	0.132	0.132	N/A	N/A
	Bottom Side	0.266	N/A	0.266	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 2 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 4	Bluetooth			
Head	Left Cheek	0.749	0.265	1.014	N/A	N/A
	Left Tilt 15 Degree	0.394	0.265	0.659	N/A	N/A
	Right Cheek	0.684	0.265	0.949	N/A	N/A

	Right Tilt 15 Degree	0.336	0.265	0.601	N/A	N/A
Body-Worn	Front Side	0.355	0.132	0.488	N/A	N/A
	Back Side	0.465	0.132	0.597	N/A	N/A
Hotspot	Front Side	0.355	0.132	0.488	N/A	N/A
	Back Side	0.465	0.132	0.597	N/A	N/A
	Left Side	0.368	N/A	0.368	N/A	N/A
	Right Side	0.229	0.132	0.361	N/A	N/A
	Top Side	N/A	0.132	0.132	N/A	N/A
	Bottom Side	0.173	N/A	0.173	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 4 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 5	Bluetooth			
Head	Left Cheek	0.739	0.265	1.004	N/A	N/A
	Left Tilt 15 Degree	0.408	0.265	0.673	N/A	N/A
	Right Cheek	0.634	0.265	0.899	N/A	N/A
	Right Tilt 15 Degree	0.315	0.265	0.580	N/A	N/A
Body-Worn	Front Side	0.708	0.132	0.841	N/A	N/A
	Back Side	0.929	0.132	1.061	N/A	N/A
Hotspot	Front Side	0.708	0.132	0.841	N/A	N/A
	Back Side	0.929	0.132	1.061	N/A	N/A
	Left Side	0.724	N/A	0.724	N/A	N/A
	Right Side	0.410	0.132	0.543	N/A	N/A
	Top Side	N/A	0.132	0.132	N/A	N/A
	Bottom Side	0.313	N/A	0.313	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 5 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 2	Bluetooth			
Head	Left Cheek	0.797	0.265	1.062	N/A	N/A
	Left Tilt 15 Degree	0.493	0.265	0.758	N/A	N/A
	Right Cheek	0.754	0.265	1.019	N/A	N/A
	Right Tilt 15 Degree	0.353	0.265	0.618	N/A	N/A
Body-Worn	Front Side	0.770	0.132	0.903	N/A	N/A
	Back Side	1.188	0.132	1.321	N/A	N/A
Hotspot	Front Side	0.770	0.132	0.903	N/A	N/A
	Back Side	1.188	0.132	1.321	N/A	N/A
	Left Side	0.703	N/A	0.703	N/A	N/A

	Right Side	0.543	0.132	0.675	N/A	N/A
	Top Side	N/A	0.132	0.132	N/A	N/A
	Bottom Side	0.483	N/A	0.483	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 2 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 4	Bluetooth			
Head	Left Cheek	0.708	0.265	0.973	N/A	N/A
	Left Tilt 15 Degree	0.365	0.265	0.630	N/A	N/A
	Right Cheek	0.657	0.265	0.922	N/A	N/A
	Right Tilt 15 Degree	0.297	0.265	0.561	N/A	N/A
Body-Worn	Front Side	0.347	0.132	0.479	N/A	N/A
	Back Side	0.415	0.132	0.548	N/A	N/A
Hotspot	Front Side	0.347	0.132	0.479	N/A	N/A
	Back Side	0.415	0.132	0.548	N/A	N/A
	Left Side	0.298	N/A	0.298	N/A	N/A
	Right Side	0.179	0.132	0.312	N/A	N/A
	Top Side	N/A	0.132	0.132	N/A	N/A
	Bottom Side	0.141	N/A	0.141	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 4 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 5	Bluetooth			
Head	Left Cheek	0.780	0.265	1.045	N/A	N/A
	Left Tilt 15 Degree	0.400	0.265	0.665	N/A	N/A
	Right Cheek	0.687	0.265	0.952	N/A	N/A
	Right Tilt 15 Degree	0.331	0.265	0.596	N/A	N/A
Body-Worn	Front Side	0.790	0.132	0.923	N/A	N/A
	Back Side	0.979	0.132	1.112	N/A	N/A
Hotspot	Front Side	0.790	0.132	0.923	N/A	N/A
	Back Side	0.979	0.132	1.112	N/A	N/A
	Left Side	0.751	N/A	0.751	N/A	N/A
	Right Side	0.443	0.132	0.575	N/A	N/A
	Top Side	N/A	0.132	0.132	N/A	N/A
	Bottom Side	0.371	N/A	0.371	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 5 and Bluetooth.

Test Position	Scaled SAR _{MAX}		Σ 1-g SAR	SPLSR	Remark
---------------	---------------------------	--	------------------	-------	--------

		LTE Band 7	Bluetooth	(W/Kg)		
Head	Left Cheek	1.194	0.265	1.459	N/A	N/A
	Left Tilt 15 Degree	0.666	0.265	0.931	N/A	N/A
	Right Cheek	0.793	0.265	1.058	N/A	N/A
	Right Tilt 15 Degree	0.592	0.265	0.857	N/A	N/A
Body-Worn	Front Side	0.618	0.132	0.750	N/A	N/A
	Back Side	0.798	0.132	0.931	N/A	N/A
Hotspot	Front Side	0.618	0.132	0.750	N/A	N/A
	Back Side	0.798	0.132	0.931	N/A	N/A
	Left Side	0.623	N/A	0.623	N/A	N/A
	Right Side	0.383	0.132	0.515	N/A	N/A
	Top Side	N/A	0.132	0.132	N/A	N/A
	Bottom Side	0.287	N/A	0.287	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 7 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 12	Bluetooth			
Head	Left Cheek	0.541	0.265	0.806	N/A	N/A
	Left Tilt 15 Degree	0.309	0.265	0.574	N/A	N/A
	Right Cheek	0.513	0.265	0.777	N/A	N/A
	Right Tilt 15 Degree	0.260	0.265	0.525	N/A	N/A
Body-Worn	Front Side	0.595	0.132	0.728	N/A	N/A
	Back Side	0.786	0.132	0.918	N/A	N/A
Hotspot	Front Side	0.595	0.132	0.728	N/A	N/A
	Back Side	0.786	0.132	0.918	N/A	N/A
	Left Side	0.573	N/A	0.573	N/A	N/A
	Right Side	0.348	0.132	0.481	N/A	N/A
	Top Side	N/A	0.132	0.132	N/A	N/A
	Bottom Side	0.298	N/A	0.298	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 12 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 17	Bluetooth			
Head	Left Cheek	0.421	0.265	0.686	N/A	N/A
	Left Tilt 15 Degree	0.242	0.265	0.507	N/A	N/A
	Right Cheek	0.390	0.265	0.655	N/A	N/A
	Right Tilt 15	0.192	0.265	0.457	N/A	N/A

	Degree					
Body-Worn	Front Side	0.544	0.132	0.677	N/A	N/A
	Back Side	0.672	0.132	0.805	N/A	N/A
Hotspot	Front Side	0.544	0.132	0.677	N/A	N/A
	Back Side	0.672	0.132	0.805	N/A	N/A
	Left Side	0.531	N/A	0.531	N/A	N/A
	Right Side	0.294	0.132	0.426	N/A	N/A
	Top Side	N/A	0.132	0.132	N/A	N/A
	Bottom Side	0.266	N/A	0.266	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 17 and Bluetooth.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 850	WLAN 5.2G			
Head	Left Cheek	1.129	0.305	1.434	N/A	N/A
	Left Tilt 15 Degree	0.548	0.179	0.727	N/A	N/A
	Right Cheek	0.783	0.284	1.067	N/A	N/A
	Right Tilt 15 Degree	0.532	0.150	0.683	N/A	N/A
Body-Worn	Front Side	0.714	0.143	0.857	N/A	N/A
	Back Side	1.121	0.235	1.356	N/A	N/A
Hotspot	Front Side	0.714	0.143	0.857	N/A	N/A
	Back Side	1.121	0.235	1.356	N/A	N/A
	Left Side	0.783	N/A	0.783	N/A	N/A
	Right Side	0.499	0.048	0.547	N/A	N/A
	Top Side	N/A	0.072	0.072	N/A	N/A
	Bottom Side	0.406	N/A	0.406	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM850 and WLAN 5.2G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 1900	WLAN 5.2G			
Head	Left Cheek	1.183	0.305	1.488	N/A	N/A
	Left Tilt 15 Degree	0.702	0.179	0.881	N/A	N/A
	Right Cheek	0.798	0.284	1.082	N/A	N/A
	Right Tilt 15 Degree	0.583	0.150	0.734	N/A	N/A
Body-Worn	Front Side	0.607	0.143	0.750	N/A	N/A
	Back Side	0.748	0.235	0.983	N/A	N/A
Hotspot	Front Side	0.607	0.143	0.750	N/A	N/A
	Back Side	0.748	0.235	0.983	N/A	N/A
	Left Side	0.530	N/A	0.530	N/A	N/A
	Right Side	0.357	0.048	0.405	N/A	N/A

	Top Side	N/A	0.072	0.072	N/A	N/A
	Bottom Side	0.273	N/A	0.273	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM1900 and WLAN 5.2G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 2	WLAN 5.2G			
Head	Left Cheek	0.902	0.305	1.207	N/A	N/A
	Left Tilt 15 Degree	0.490	0.179	0.669	N/A	N/A
	Right Cheek	0.791	0.284	1.075	N/A	N/A
	Right Tilt 15 Degree	0.393	0.150	0.544	N/A	N/A
Body-Worn	Front Side	0.533	0.143	0.677	N/A	N/A
	Back Side	0.700	0.235	0.934	N/A	N/A
Hotspot	Front Side	0.533	0.143	0.677	N/A	N/A
	Back Side	0.700	0.235	0.934	N/A	N/A
	Left Side	0.560	N/A	0.560	N/A	N/A
	Right Side	0.331	0.048	0.379	N/A	N/A
	Top Side	N/A	0.072	0.072	N/A	N/A
	Bottom Side	0.266	N/A	0.266	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 2 and WLAN 5.2G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 4	WLAN 5.2G			
Head	Left Cheek	0.749	0.305	1.054	N/A	N/A
	Left Tilt 15 Degree	0.394	0.179	0.572	N/A	N/A
	Right Cheek	0.684	0.284	0.968	N/A	N/A
	Right Tilt 15 Degree	0.336	0.150	0.486	N/A	N/A
Body-Worn	Front Side	0.355	0.143	0.499	N/A	N/A
	Back Side	0.465	0.235	0.700	N/A	N/A
Hotspot	Front Side	0.355	0.143	0.499	N/A	N/A
	Back Side	0.465	0.235	0.700	N/A	N/A
	Left Side	0.368	N/A	0.368	N/A	N/A
	Right Side	0.229	0.048	0.276	N/A	N/A
	Top Side	N/A	0.072	0.072	N/A	N/A
	Bottom Side	0.173	N/A	0.173	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 4 and WLAN 5.2G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA	WLAN 5.2G			

		Band 5				
Head	Left Cheek	0.739	0.305	1.044	N/A	N/A
	Left Tilt 15 Degree	0.408	0.179	0.586	N/A	N/A
	Right Cheek	0.634	0.284	0.918	N/A	N/A
	Right Tilt 15 Degree	0.315	0.150	0.465	N/A	N/A
Body-Worn	Front Side	0.708	0.143	0.852	N/A	N/A
	Back Side	0.929	0.235	1.164	N/A	N/A
Hotspot	Front Side	0.708	0.143	0.852	N/A	N/A
	Back Side	0.929	0.235	1.164	N/A	N/A
	Left Side	0.724	N/A	0.724	N/A	N/A
	Right Side	0.410	0.048	0.458	N/A	N/A
	Top Side	N/A	0.072	0.072	N/A	N/A
	Bottom Side	0.313	N/A	0.313	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 5 and WLAN 5.2G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 2	WLAN 5.2G			
Head	Left Cheek	0.797	0.305	1.102	N/A	N/A
	Left Tilt 15 Degree	0.493	0.179	0.672	N/A	N/A
	Right Cheek	0.754	0.284	1.038	N/A	N/A
	Right Tilt 15 Degree	0.353	0.150	0.504	N/A	N/A
Body-Worn	Front Side	0.770	0.143	0.914	N/A	N/A
	Back Side	1.188	0.235	1.423	N/A	N/A
Hotspot	Front Side	0.770	0.143	0.914	N/A	N/A
	Back Side	1.188	0.235	1.423	N/A	N/A
	Left Side	0.703	N/A	0.703	N/A	N/A
	Right Side	0.543	0.048	0.591	N/A	N/A
	Top Side	N/A	0.072	0.072	N/A	N/A
	Bottom Side	0.483	N/A	0.483	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 2 and WLAN 5.2G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 4	WLAN 5.2G			
Head	Left Cheek	0.708	0.305	1.013	N/A	N/A
	Left Tilt 15 Degree	0.365	0.179	0.543	N/A	N/A
	Right Cheek	0.657	0.284	0.941	N/A	N/A
	Right Tilt 15 Degree	0.297	0.150	0.447	N/A	N/A
Body-Worn	Front Side	0.347	0.143	0.490	N/A	N/A

	Back Side	0.415	0.235	0.650	N/A	N/A
Hotspot	Front Side	0.347	0.143	0.490	N/A	N/A
	Back Side	0.415	0.235	0.650	N/A	N/A
	Left Side	0.298	N/A	0.298	N/A	N/A
	Right Side	0.179	0.048	0.227	N/A	N/A
	Top Side	N/A	0.072	0.072	N/A	N/A
	Bottom Side	0.141	N/A	0.141	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 4 and WLAN 5.2G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 5	WLAN 5.2G			
Head	Left Cheek	0.780	0.305	1.085	N/A	N/A
	Left Tilt 15 Degree	0.400	0.179	0.579	N/A	N/A
	Right Cheek	0.687	0.284	0.971	N/A	N/A
	Right Tilt 15 Degree	0.331	0.150	0.481	N/A	N/A
Body-Worn	Front Side	0.790	0.143	0.934	N/A	N/A
	Back Side	0.979	0.235	1.214	N/A	N/A
Hotspot	Front Side	0.790	0.143	0.934	N/A	N/A
	Back Side	0.979	0.235	1.214	N/A	N/A
	Left Side	0.751	N/A	0.751	N/A	N/A
	Right Side	0.443	0.048	0.491	N/A	N/A
	Top Side	N/A	0.072	0.072	N/A	N/A
	Bottom Side	0.371	N/A	0.371	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 5 and WLAN 5.2G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 7	WLAN 5.2G			
Head	Left Cheek	1.194	0.305	1.499	N/A	N/A
	Left Tilt 15 Degree	0.666	0.179	0.845	N/A	N/A
	Right Cheek	0.793	0.284	1.077	N/A	N/A
	Right Tilt 15 Degree	0.592	0.150	0.742	N/A	N/A
Body-Worn	Front Side	0.618	0.143	0.761	N/A	N/A
	Back Side	0.798	0.235	1.033	N/A	N/A
Hotspot	Front Side	0.618	0.143	0.761	N/A	N/A
	Back Side	0.798	0.235	1.033	N/A	N/A
	Left Side	0.623	N/A	0.623	N/A	N/A
	Right Side	0.383	0.048	0.431	N/A	N/A

	Top Side	N/A	0.072	0.072	N/A	N/A
	Bottom Side	0.287	N/A	0.287	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 7 and WLAN 5.2G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 12	WLAN 5.2G			
Head	Left Cheek	0.541	0.305	0.846	N/A	N/A
	Left Tilt 15 Degree	0.309	0.179	0.488	N/A	N/A
	Right Cheek	0.513	0.284	0.797	N/A	N/A
	Right Tilt 15 Degree	0.260	0.150	0.411	N/A	N/A
Body-Worn	Front Side	0.595	0.143	0.739	N/A	N/A
	Back Side	0.786	0.235	1.020	N/A	N/A
Hotspot	Front Side	0.595	0.143	0.739	N/A	N/A
	Back Side	0.786	0.235	1.020	N/A	N/A
	Left Side	0.573	N/A	0.573	N/A	N/A
	Right Side	0.348	0.048	0.396	N/A	N/A
	Top Side	N/A	0.072	0.072	N/A	N/A
	Bottom Side	0.298	N/A	0.298	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 12 and WLAN 5.2G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 17	WLAN 5.2G			
Head	Left Cheek	0.421	0.305	0.726	N/A	N/A
	Left Tilt 15 Degree	0.242	0.179	0.420	N/A	N/A
	Right Cheek	0.390	0.284	0.674	N/A	N/A
	Right Tilt 15 Degree	0.192	0.150	0.343	N/A	N/A
Body-Worn	Front Side	0.544	0.143	0.688	N/A	N/A
	Back Side	0.672	0.235	0.907	N/A	N/A
Hotspot	Front Side	0.544	0.143	0.688	N/A	N/A
	Back Side	0.672	0.235	0.907	N/A	N/A
	Left Side	0.531	N/A	0.531	N/A	N/A
	Right Side	0.294	0.048	0.342	N/A	N/A
	Top Side	N/A	0.072	0.072	N/A	N/A
	Bottom Side	0.266	N/A	0.266	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 17 and WLAN 5.2G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 850	WLAN 5.8G			
Head	Left Cheek	1.129	0.396	1.525	N/A	N/A
	Left Tilt 15 Degree	0.548	0.245	0.793	N/A	N/A
	Right Cheek	0.783	0.311	1.094	N/A	N/A
	Right Tilt 15 Degree	0.532	0.210	0.743	N/A	N/A
Body-Worn	Front Side	0.714	0.222	0.936	N/A	N/A
	Back Side	1.121	0.360	1.481	N/A	N/A
Hotspot	Front Side	0.714	0.222	0.936	N/A	N/A
	Back Side	1.121	0.360	1.481	N/A	N/A
	Left Side	0.783	N/A	0.783	N/A	N/A
	Right Side	0.499	0.086	0.585	N/A	N/A
	Top Side	N/A	0.118	0.118	N/A	N/A
	Bottom Side	0.406	N/A	0.406	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM850 and WLAN 5.8G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		GSM 1900	WLAN 5.8G			
Head	Left Cheek	1.183	0.396	1.578	N/A	N/A
	Left Tilt 15 Degree	0.702	0.245	0.947	N/A	N/A
	Right Cheek	0.798	0.311	1.109	N/A	N/A
	Right Tilt 15 Degree	0.583	0.210	0.794	N/A	N/A
Body-Worn	Front Side	0.607	0.222	0.829	N/A	N/A
	Back Side	0.748	0.360	1.107	N/A	N/A
Hotspot	Front Side	0.607	0.222	0.829	N/A	N/A
	Back Side	0.748	0.360	1.107	N/A	N/A
	Left Side	0.530	N/A	0.530	N/A	N/A
	Right Side	0.357	0.086	0.443	N/A	N/A
	Top Side	N/A	0.118	0.118	N/A	N/A
	Bottom Side	0.273	N/A	0.273	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of GSM1900 and WLAN 5.8G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 2	WLAN 5.8G			
Head	Left Cheek	0.902	0.396	1.297	N/A	N/A
	Left Tilt 15 Degree	0.490	0.245	0.735	N/A	N/A
	Right Cheek	0.791	0.311	1.102	N/A	N/A
	Right Tilt 15 Degree	0.393	0.210	0.604	N/A	N/A

Body-Worn	Front Side	0.533	0.222	0.755	N/A	N/A
	Back Side	0.700	0.360	1.059	N/A	N/A
Hotspot	Front Side	0.533	0.222	0.755	N/A	N/A
	Back Side	0.700	0.360	1.059	N/A	N/A
	Left Side	0.560	N/A	0.560	N/A	N/A
	Right Side	0.331	0.086	0.417	N/A	N/A
	Top Side	N/A	0.118	0.118	N/A	N/A
	Bottom Side	0.266	N/A	0.266	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 2 and WLAN 5.8G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 4	WLAN 5.8G			
Head	Left Cheek	0.749	0.396	1.144	N/A	N/A
	Left Tilt 15 Degree	0.394	0.245	0.639	N/A	N/A
	Right Cheek	0.684	0.311	0.995	N/A	N/A
	Right Tilt 15 Degree	0.336	0.210	0.546	N/A	N/A
Body-Worn	Front Side	0.355	0.222	0.577	N/A	N/A
	Back Side	0.465	0.360	0.824	N/A	N/A
Hotspot	Front Side	0.355	0.222	0.577	N/A	N/A
	Back Side	0.465	0.360	0.824	N/A	N/A
	Left Side	0.368	N/A	0.368	N/A	N/A
	Right Side	0.229	0.086	0.314	N/A	N/A
	Top Side	N/A	0.118	0.118	N/A	N/A
	Bottom Side	0.173	N/A	0.173	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 4 and WLAN 5.8G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		WCDMA Band 5	WLAN 5.8G			
Head	Left Cheek	0.739	0.396	1.135	N/A	N/A
	Left Tilt 15 Degree	0.408	0.245	0.653	N/A	N/A
	Right Cheek	0.634	0.311	0.945	N/A	N/A
	Right Tilt 15 Degree	0.315	0.210	0.525	N/A	N/A
Body-Worn	Front Side	0.708	0.222	0.930	N/A	N/A
	Back Side	0.929	0.360	1.288	N/A	N/A
Hotspot	Front Side	0.708	0.222	0.930	N/A	N/A
	Back Side	0.929	0.360	1.288	N/A	N/A
	Left Side	0.724	N/A	0.724	N/A	N/A
	Right Side	0.410	0.086	0.496	N/A	N/A

	Top Side	N/A	0.118	0.118	N/A	N/A
	Bottom Side	0.313	N/A	0.313	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of WCDMA Band 5 and WLAN 5.8G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 2	WLAN 5.8G			
Head	Left Cheek	0.797	0.396	1.193	N/A	N/A
	Left Tilt 15 Degree	0.493	0.245	0.739	N/A	N/A
	Right Cheek	0.754	0.311	1.065	N/A	N/A
	Right Tilt 15 Degree	0.353	0.210	0.564	N/A	N/A
Body-Worn	Front Side	0.770	0.222	0.992	N/A	N/A
	Back Side	1.188	0.360	1.548	N/A	N/A
Hotspot	Front Side	0.770	0.222	0.992	N/A	N/A
	Back Side	1.188	0.360	1.548	N/A	N/A
	Left Side	0.703	N/A	0.703	N/A	N/A
	Right Side	0.543	0.086	0.628	N/A	N/A
	Top Side	N/A	0.118	0.118	N/A	N/A
	Bottom Side	0.483	N/A	0.483	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 2 and WLAN 5.8G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 4	WLAN 5.8G			
Head	Left Cheek	0.708	0.396	1.103	N/A	N/A
	Left Tilt 15 Degree	0.365	0.245	0.610	N/A	N/A
	Right Cheek	0.657	0.311	0.968	N/A	N/A
	Right Tilt 15 Degree	0.297	0.210	0.507	N/A	N/A
Body-Worn	Front Side	0.347	0.222	0.569	N/A	N/A
	Back Side	0.415	0.360	0.775	N/A	N/A
Hotspot	Front Side	0.347	0.222	0.569	N/A	N/A
	Back Side	0.415	0.360	0.775	N/A	N/A
	Left Side	0.298	N/A	0.298	N/A	N/A
	Right Side	0.179	0.086	0.265	N/A	N/A
	Top Side	N/A	0.118	0.118	N/A	N/A
	Bottom Side	0.141	N/A	0.141	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 4 and WLAN 5.8G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 5	WLAN 5.8G			
Head	Left Cheek	0.780	0.396	1.175	N/A	N/A

	Left Tilt 15 Degree	0.400	0.245	0.645	N/A	N/A
	Right Cheek	0.687	0.311	0.998	N/A	N/A
	Right Tilt 15 Degree	0.331	0.210	0.541	N/A	N/A
Body-Worn	Front Side	0.790	0.222	1.012	N/A	N/A
	Back Side	0.979	0.360	1.339	N/A	N/A
Hotspot	Front Side	0.790	0.222	1.012	N/A	N/A
	Back Side	0.979	0.360	1.339	N/A	N/A
	Left Side	0.751	N/A	0.751	N/A	N/A
	Right Side	0.443	0.086	0.528	N/A	N/A
	Top Side	N/A	0.118	0.118	N/A	N/A
	Bottom Side	0.371	N/A	0.371	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 5 and WLAN 5.8G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 7	WLAN 5.8G			
Head	Left Cheek	1.194	0.396	1.589	N/A	N/A
	Left Tilt 15 Degree	0.666	0.245	0.911	N/A	N/A
	Right Cheek	0.793	0.311	1.104	N/A	N/A
	Right Tilt 15 Degree	0.592	0.210	0.802	N/A	N/A
Body-Worn	Front Side	0.618	0.222	0.840	N/A	N/A
	Back Side	0.798	0.360	1.158	N/A	N/A
Hotspot	Front Side	0.618	0.222	0.840	N/A	N/A
	Back Side	0.798	0.360	1.158	N/A	N/A
	Left Side	0.623	N/A	0.623	N/A	N/A
	Right Side	0.383	0.086	0.468	N/A	N/A
	Top Side	N/A	0.118	0.118	N/A	N/A
	Bottom Side	0.287	N/A	0.287	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 7 and WLAN 5.8G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 12	WLAN 5.8G			
Head	Left Cheek	0.541	0.396	0.936	N/A	N/A
	Left Tilt 15 Degree	0.309	0.245	0.554	N/A	N/A
	Right Cheek	0.513	0.311	0.823	N/A	N/A
	Right Tilt 15 Degree	0.260	0.210	0.471	N/A	N/A
Body-Worn	Front Side	0.595	0.222	0.817	N/A	N/A
	Back Side	0.786	0.360	1.145	N/A	N/A

Hotspot	Front Side	0.595	0.222	0.817	N/A	N/A
	Back Side	0.786	0.360	1.145	N/A	N/A
	Left Side	0.573	N/A	0.573	N/A	N/A
	Right Side	0.348	0.086	0.434	N/A	N/A
	Top Side	N/A	0.118	0.118	N/A	N/A
	Bottom Side	0.298	N/A	0.298	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 12 and WLAN 5.8G.

Test Position		Scaled SAR _{MAX}		Σ 1-g SAR (W/Kg)	SPLSR	Remark
		LTE Band 17	WLAN 5.8G			
Head	Left Cheek	0.421	0.396	0.817	N/A	N/A
	Left Tilt 15 Degree	0.242	0.245	0.487	N/A	N/A
	Right Cheek	0.390	0.311	0.701	N/A	N/A
	Right Tilt 15 Degree	0.192	0.210	0.403	N/A	N/A
Body-Worn	Front Side	0.544	0.222	0.766	N/A	N/A
	Back Side	0.672	0.360	1.032	N/A	N/A
Hotspot	Front Side	0.544	0.222	0.766	N/A	N/A
	Back Side	0.672	0.360	1.032	N/A	N/A
	Left Side	0.531	N/A	0.531	N/A	N/A
	Right Side	0.294	0.086	0.380	N/A	N/A
	Top Side	N/A	0.118	0.118	N/A	N/A
	Bottom Side	0.266	N/A	0.266	N/A	N/A

NOTE: 1-g SAR Simultaneous Tx Combination of LTE Band 17 and WLAN 5.8G.

11. Appendix A. Photo documentation

Refer to appendix Test Setup photo---SAR

12. Appendix B. System Check Plots

Table of contents
MEASUREMENT 1 System Performance Check - SID750 - Head
MEASUREMENT 2 System Performance Check - SID750 - Body
MEASUREMENT 3 System Performance Check - SID835 - Head
MEASUREMENT 4 System Performance Check - SID835 - Body
MEASUREMENT 5 System Performance Check - SID1800 - Head
MEASUREMENT 6 System Performance Check - SID1800 - Body
MEASUREMENT 7 System Performance Check - SID1900 - Head
MEASUREMENT 8 System Performance Check - SID1900 - Body
MEASUREMENT 9 System Performance Check - SID2450 - Head
MEASUREMENT 10 System Performance Check - SID2450 - Body
MEASUREMENT 11 System Performance Check - SID2600 - Head
MEASUREMENT 12 System Performance Check - SID2600 - Body
MEASUREMENT 13 System Performance Check - SID5200 - Head
MEASUREMENT 14 System Performance Check - SID5200 - Body
MEASUREMENT 15 System Performance Check - SID5800 - Head
MEASUREMENT 16 System Performance Check - SID5800 - Body


MEASUREMENT 1

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW750</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	750.000000
Relative permittivity (real part)	41.233162
Relative permittivity (imaginary part)	21.911263
Conductivity (S/m)	0.912262
Variation (%)	-3.810000



Maximum location: X=3.00, Y=3.00

SAR Peak: 1.30 W/kg

SAR 10g (W/Kg)	0.551218
SAR 1g (W/Kg)	0.853362



MEASUREMENT 2


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW750</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	750.000000
Relative permittivity (real part)	55.300248
Relative permittivity (imaginary part)	23.313842
Conductivity (S/m)	0.970318
Variation (%)	-1.490000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=3.00

SAR Peak: 1.30 W/kg

SAR 10g (W/Kg)	0.589281
SAR 1g (W/Kg)	0.886263



MEASUREMENT 3


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW835</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative permittivity (real part)	40.533541
Relative permittivity (imaginary part)	20.159613
Conductivity (S/m)	0.940542
Variation (%)	1.870000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=3.00

SAR Peak: 1.30 W/kg

SAR 10g (W/Kg)	0.602466
SAR 1g (W/Kg)	0.945035



MEASUREMENT 4


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW835</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	835.000000
Relative permittivity (real part)	54.371111
Relative permittivity (imaginary part)	21.743359
Conductivity (S/m)	1.011236
Variation (%)	-1.200000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=2.00

SAR Peak: 1.23 W/kg

SAR 10g (W/Kg)	0.660123
SAR 1g (W/Kg)	0.970356



MEASUREMENT 5


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1800.000000
Relative permittivity (real part)	38.481237
Relative permittivity (imaginary part)	14.143229
Conductivity (S/m)	1.409367
Variation (%)	-2.110000

SURFACE SAR




VOLUME SAR




Maximum location: X=3.00, Y=2.00

SAR Peak: 6.82 W/kg


SAR 10g (W/Kg)	2.010397
SAR 1g (W/Kg)	3.806451



3D screen shot



Hot spot position



MEASUREMENT 6


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1800.000000
Relative permittivity (real part)	53.243510
Relative permittivity (imaginary part)	15.634016
Conductivity (S/m)	1.563096
Variation (%)	2.020000

SURFACE SAR





VOLUME SAR



Maximum location: X=3.00, Y=2.00

SAR Peak: 6.82 W/kg

SAR 10g (W/Kg)	2.063379
SAR 1g (W/Kg)	3.812268



MEASUREMENT 7


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1900.000000
Relative permittivity (real part)	40.961287
Relative permittivity (imaginary part)	13.843008
Conductivity (S/m)	1.460336
Variation (%)	-1.430000

SURFACE SAR





VOLUME SAR



Maximum location: X=5.00, Y=2.00

SAR Peak: 6.70 W/kg

SAR 10g (W/Kg)	2.007456
SAR 1g (W/Kg)	3.890365



MEASUREMENT 8


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1900.000000
Relative permittivity (real part)	52.573335
Relative permittivity (imaginary part)	14.903503
Conductivity (S/m)	1.569566
Variation (%)	3.460000

SURFACE SAR





VOLUME SAR



Maximum location: X=5.00, Y=2.00

SAR Peak: 6.39 W/kg

SAR 10g (W/Kg)	2.059329
SAR 1g (W/Kg)	3.910402



MEASUREMENT 9


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2450</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2450.000000
Relative permittivity (real part)	38.721421
Relative permittivity (imaginary part)	13.792631
Conductivity (S/m)	1.879663
Variation (%)	-3.350000

SURFACE SAR





VOLUME SAR



Maximum location: X=0.00, Y=1.00

SAR Peak: 8.14 W/kg

SAR 10g (W/Kg)	2.416375
SAR 1g (W/Kg)	5.369435




MEASUREMENT 10

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2450</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	2450.000000
Relative permittivity (real part)	52.091497
Relative permittivity (imaginary part)	14.883566
Conductivity (S/m)	2.032816
Variation (%)	1.420000



Maximum location: X=0.00, Y=1.00

SAR Peak: 8.46 W/kg

SAR 10g (W/Kg)	2.401285
SAR 1g (W/Kg)	5.288270



MEASUREMENT 11


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2600</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2600.000000
Relative permittivity (real part)	38.402638
Relative permittivity (imaginary part)	14.023997
Conductivity (S/m)	2.033631
Variation (%)	-0.040000

SURFACE SAR






VOLUME SAR



Maximum location: X=-1.00, Y=2.00

SAR Peak: 9.07 W/kg

SAR 10g (W/Kg)	2.419205
SAR 1g (W/Kg)	5.550267



MEASUREMENT 12


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2600</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2600.000000
Relative permittivity (real part)	52.672866
Relative permittivity (imaginary part)	15.230101
Conductivity (S/m)	2.203465
Variation (%)	-1.220000

SURFACE SAR





VOLUME SAR



Maximum location: X=0.00, Y=2.00

SAR Peak: 9.99 W/kg

SAR 10g (W/Kg)	2.463324
SAR 1g (W/Kg)	5.565188



MEASUREMENT 13


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW5200</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	5200.000000
Relative permittivity (real part)	35.832204
Relative permittivity (imaginary part)	16.043542
Conductivity (S/m)	4.632321
Variation (%)	1.660000

SURFACE SAR



VOLUME SAR




Maximum location: X=0.00, Y=6.00


SAR Peak: 40.06 W/kg

SAR 10g (W/Kg)	5.584495
SAR 1g (W/Kg)	16.077221

Z (mm)	SAR (W/kg)
0	37.84
2	22.00
4	11.00
6	5.00
8	2.50
10	1.00
12	0.50
14	0.02
16	0.02
18	0.02
20	0.02
22	0.02
24	0.02
26	0.02



Hot spot position




MEASUREMENT 14

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW5200</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>

B. SAR Measurement Results

Frequency (MHz)	5200.000000
Relative permittivity (real part)	49.662845
Relative permittivity (imaginary part)	18.301441
Conductivity (S/m)	5.293842
Variation (%)	4.490000




Maximum location: X=0.00, Y=6.00


SAR Peak: 49.61 W/kg

SAR 10g (W/Kg)	5.510184
SAR 1g (W/Kg)	15.677246


Z (m m)	0.00	2.00	4.00	6.00	8.00	10.0 0	12.0 0	14.0 0	16.0 0	18.0 0	20.0 0	22.0 0
SA R (W/ Kg)	46.6 150	27.5 644	14.0 668	7.05 91	3.59 28	1.78 02	0.89 38	0.46 70	0.24 75	0.13 53	0.06 50	0.04 000



3D screen shot



Hot spot position



MEASUREMENT 15


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW5800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	5800.000000
Relative permittivity (real part)	34.741512
Relative permittivity (imaginary part)	16.083082
Conductivity (S/m)	5.180981
Variation (%)	1.880000

SURFACE SAR






VOLUME SAR



Maximum location: X=0.00, Y=6.00

SAR Peak: 57.37 W/kg

SAR 10g (W/Kg)	6.256095
SAR 1g (W/Kg)	18.410093



MEASUREMENT 16


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW5800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	5800.000000
Relative permittivity (real part)	48.350523
Relative permittivity (imaginary part)	18.820043
Conductivity (S/m)	6.061524
Variation (%)	1.340000

SURFACE SAR





VOLUME SAR



Maximum location: X=0.00, Y=6.00

SAR Peak: 51.30 W/kg

SAR 10g (W/Kg)	5.840184
SAR 1g (W/Kg)	16.911052



13. Appendix C. Plots of High SAR Measurement

Table of contents
MEASUREMENT 1 GSM 850 Head
MEASUREMENT 2 GSM 850 Body
MEASUREMENT 3 GSM 1900 Head
MEASUREMENT 4 GSM 1900 Body
MEASUREMENT 5 WCDMA Band 2 Head
MEASUREMENT 6 WCDMA Band 2 Body
MEASUREMENT 7 WCDMA Band 4 Head
MEASUREMENT 8 WCDMA Band 4 Body
MEASUREMENT 9 WCDMA Band 5 Head
MEASUREMENT 10 WCDMA Band 5 Body
MEASUREMENT 11 WLAN 5.8G Head
MEASUREMENT 12 WLAN 5.2G Head
MEASUREMENT 13 WLAN 5.2G Body
MEASUREMENT 14 WLAN 5.8G Body
MEASUREMENT 15 WLAN 2.4G Head
MEASUREMENT 16 WLAN 2.4G Body
MEASUREMENT 17 LTE Band 2 Head
MEASUREMENT 18 LTE Band 2 Body
MEASUREMENT 19 LTE Band 4 Head
MEASUREMENT 20 LTE Band 4 Body
MEASUREMENT 21 LTE Band 5 Head
MEASUREMENT 22 LTE Band 5 Body
MEASUREMENT 23 LTE Band 7 Head
MEASUREMENT 24 LTE Band 7 Body
MEASUREMENT 25 LTE Band 12 Head
MEASUREMENT 26 LTE Band 12 Body
MEASUREMENT 27 LTE Band 17 Head
MEASUREMENT 28 LTE Band 17 Body

MEASUREMENT 1


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>GSM850</u>
<u>Channels</u>	<u>High</u>
<u>Signal</u>	<u>TDMA (Crest factor: 4.0)</u>


B. SAR Measurement Results

Frequency (MHz)	848.800000
Relative permittivity (real part)	40.284920
Relative permittivity (imaginary part)	20.227961
Conductivity (S/m)	0.953861
Variation (%)	1.020000

SURFACE SAR





VOLUME SAR



Maximum location: X=-50.00, Y=-33.00

SAR Peak: 1.55 W/kg

SAR 10g (W/Kg)	0.812759
SAR 1g (W/Kg)	1.043849



MEASUREMENT 2


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>GSM850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 4.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	54.379581
Relative permittivity (imaginary part)	21.722740
Conductivity (S/m)	1.009383
Variation (%)	-1.560000

SURFACE SAR





VOLUME SAR



Maximum location: X=-9.00, Y=32.00

SAR Peak: 1.40 W/kg

SAR 10g (W/Kg)	0.759504
SAR 1g (W/Kg)	1.050589



MEASUREMENT 3


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>GSM1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 2.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	41.018200
Relative permittivity (imaginary part)	13.744300
Conductivity (S/m)	1.435516
Variation (%)	0.600000

SURFACE SAR





VOLUME SAR



Maximum location: X=-51.00, Y=-50.00

SAR Peak: 1.54 W/kg

SAR 10g (W/Kg)	0.548766
SAR 1g (W/Kg)	0.956800



MEASUREMENT 4


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>GSM1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 2.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	52.578899
Relative permittivity (imaginary part)	14.937700
Conductivity (S/m)	1.560160
Variation (%)	0.230000

SURFACE SAR





VOLUME SAR



Maximum location: X=5.00, Y=-15.00

SAR Peak: 1.03 W/kg

SAR 10g (W/Kg)	0.311658
SAR 1g (W/Kg)	0.605025



MEASUREMENT 5


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>Band2 WCDMA1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	41.018200
Relative permittivity (imaginary part)	13.744300
Conductivity (S/m)	1.435516
Variation (%)	-1.680000

SURFACE SAR





VOLUME SAR



Maximum location: X=-52.00, Y=-49.00

SAR Peak: 1.23 W/kg

SAR 10g (W/Kg)	0.490005
SAR 1g (W/Kg)	0.830315



MEASUREMENT 6


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band2 WCDMA1900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	52.648899
Relative permittivity (imaginary part)	14.987700
Conductivity (S/m)	1.565382
Variation (%)	-0.050000

SURFACE SAR





VOLUME SAR



Maximum location: X=5.00, Y=-27.00

SAR Peak: 1.04 W/kg

SAR 10g (W/Kg)	0.341522
SAR 1g (W/Kg)	0.644242



MEASUREMENT 7


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>Band4 WCDMA1700</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1732.600000
Relative permittivity (real part)	38.937389
Relative permittivity (imaginary part)	14.095742
Conductivity (S/m)	1.356324
Variation (%)	-1.640000

SURFACE SAR





VOLUME SAR



Maximum location: X=-53.00, Y=-51.00

SAR Peak: 0.84 W/kg

SAR 10g (W/Kg)	0.362523
SAR 1g (W/Kg)	0.579524



MEASUREMENT 8


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band4 WCDMA1700</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1732.600000
Relative permittivity (real part)	53.636166
Relative permittivity (imaginary part)	15.671370
Conductivity (S/m)	1.507934
Variation (%)	0.510000

SURFACE SAR





VOLUME SAR



Maximum location: X=-20.00, Y=16.00

SAR Peak: 0.51 W/kg

SAR 10g (W/Kg)	0.233051
SAR 1g (W/Kg)	0.360076



MEASUREMENT 9


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>Band5 WCDMA850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	40.440960
Relative permittivity (imaginary part)	20.181540
Conductivity (S/m)	0.937769
Variation (%)	-0.120000

SURFACE SAR





VOLUME SAR



Maximum location: X=-50.00, Y=-21.00

SAR Peak: 0.75 W/kg

SAR 10g (W/Kg)	0.475073
SAR 1g (W/Kg)	0.629133



MEASUREMENT 10


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band5 WCDMA850</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	836.400000
Relative permittivity (real part)	54.379581
Relative permittivity (imaginary part)	21.722740
Conductivity (S/m)	1.009383
Variation (%)	-0.050000

SURFACE SAR





VOLUME SAR



Maximum location: X=0.00, Y=-8.00

SAR Peak: 1.03 W/kg

SAR 10g (W/Kg)	0.539434
SAR 1g (W/Kg)	0.780882



MEASUREMENT 11


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Right head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>IEEE 802.11a U-NII</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11a (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	5745.000000
Relative permittivity (real part)	34.869059
Relative permittivity (imaginary part)	16.119066
Conductivity (S/m)	5.144669
Variation (%)	2.630000

SURFACE SAR





VOLUME SAR



Maximum location: X=7.00, Y=-17.00

SAR Peak: 1.13 W/kg

SAR 10g (W/Kg)	0.154997
SAR 1g (W/Kg)	0.342162



MEASUREMENT 12


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Right head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>IEEE 802.11a U-NII</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11a (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	5200.000000
Relative permittivity (real part)	35.832981
Relative permittivity (imaginary part)	16.041618
Conductivity (S/m)	4.634246
Variation (%)	-0.470000

SURFACE SAR





VOLUME SAR



Maximum location: X=7.00, Y=-24.00

SAR Peak: 0.52 W/kg

SAR 10g (W/Kg)	0.100497
SAR 1g (W/Kg)	0.216975



MEASUREMENT 13


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11a U-NII</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11a (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	5200.000000
Relative permittivity (real part)	49.659538
Relative permittivity (imaginary part)	18.295509
Conductivity (S/m)	5.285369
Variation (%)	-3.930000

SURFACE SAR



VOLUME SAR






Maximum location: X=-20.00, Y=26.00

SAR Peak: 0.64 W/kg

SAR 10g (W/Kg)	0.111205
SAR 1g (W/Kg)	0.167448

Z (m m)	0.00	2.00	4.00	6.00	8.00	10.0 0	12.0 0	14.0 0	16.0 0	18.0 0	20.0 0	22.0 0
SA R (W/ Kg)	4.20 73	1.65 29	0.07 02	0.06 60	0.06 45	0.06 08	0.06 29	0.05 98	0.06 43	0.06 55	0.06 34	0.00 00



3D screen shot	Hot spot position
 A 3D rendering of a robotic arm, specifically the end effector, which is a gripper-like structure. On the bottom surface of the gripper, there is a grid of small, colored dots. The dots are primarily green, with a small cluster of blue dots on the left and a small cluster of yellow dots on the right, indicating a localized area of interest or a 'hot spot'.	 A heatmap visualization showing the spatial distribution of the 'hot spot' position. The background is a uniform green color. A large, irregularly shaped region of high intensity is visible, colored in shades of yellow and red, indicating the area of maximum concentration or 'hot spot' position. This region is centered within the frame.

MEASUREMENT 14


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11a U-NII</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11a (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	5745.000000
Relative permittivity (real part)	48.482973
Relative permittivity (imaginary part)	18.860566
Conductivity (S/m)	6.019664
Variation (%)	-1.000000

SURFACE SAR





VOLUME SAR



Maximum location: X=-19.00, Y=-16.00

SAR Peak: 0.85 W/kg

SAR 10g (W/Kg)	0.164036
SAR 1g (W/Kg)	0.310917



MEASUREMENT 15


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>IEEE 802.11b ISM</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11b (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2437.000000
Relative permittivity (real part)	38.771000
Relative permittivity (imaginary part)	13.710300
Conductivity (S/m)	1.856222
Variation (%)	-0.300000

SURFACE SAR





VOLUME SAR



Maximum location: X=-13.00, Y=25.00

SAR Peak: 0.92 W/kg

SAR 10g (W/Kg)	0.203404
SAR 1g (W/Kg)	0.340026



MEASUREMENT 16


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11b ISM</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11b (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	2437.000000
Relative permittivity (real part)	52.151600
Relative permittivity (imaginary part)	14.835620
Conductivity (S/m)	2.008578
Variation (%)	-1.910000

SURFACE SAR



VOLUME SAR




Maximum location: X=-19.00, Y=21.00


SAR Peak: 0.19 W/kg

SAR 10g (W/Kg)	0.065503
SAR 1g (W/Kg)	0.109570


Z (m m)	0.00	4.00	6.00	8.00	10.0 0	12.0 0	14.0 0	16.0 0	18.0 0	20.0 0	22.0 0	24.0 0
SA R (W/ Kg)	0.18 94	0.11 43	0.08 38	0.07 29	0.06 03	0.05 00	0.04 23	0.03 87	0.03 52	0.03 14	0.02 93	0.02 83



3D screen shot



Hot spot position



MEASUREMENT 17


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 2</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	41.063801
Relative permittivity (imaginary part)	13.738100
Conductivity (S/m)	1.434487
Variation (%)	-2.600000

SURFACE SAR





VOLUME SAR



Maximum location: X=-52.00, Y=-50.00

SAR Peak: 1.09 W/kg

SAR 10g (W/Kg)	0.430903
SAR 1g (W/Kg)	0.676565



MEASUREMENT 18


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 2</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1880.000000
Relative permittivity (real part)	52.655949
Relative permittivity (imaginary part)	14.996150
Conductivity (S/m)	1.565848
Variation (%)	-1.630000

SURFACE SAR





VOLUME SAR



Maximum location: X=5.00, Y=-25.00

SAR Peak: 1.71 W/kg

SAR 10g (W/Kg)	0.580551
SAR 1g (W/Kg)	1.008585



MEASUREMENT 19


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 4</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1732.500000
Relative permittivity (real part)	38.945290
Relative permittivity (imaginary part)	14.080592
Conductivity (S/m)	1.355257
Variation (%)	1.130000

SURFACE SAR





VOLUME SAR



Maximum location: X=-53.00, Y=-51.00

SAR Peak: 0.88 W/kg

SAR 10g (W/Kg)	0.337658
SAR 1g (W/Kg)	0.561223



MEASUREMENT 20


A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7, dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 4</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>


B. SAR Measurement Results

Frequency (MHz)	1732.500000
Relative permittivity (real part)	53.623367
Relative permittivity (imaginary part)	15.653220
Conductivity (S/m)	1.506622
Variation (%)	-1.110000

SURFACE SAR



VOLUME SAR



Maximum location: X=-21.00, Y=7.00

SAR Peak: 0.46 W/kg

SAR 10g (W/Kg)	0.215636
SAR 1g (W/Kg)	0.328907

