

FCC PART 15.247


TEST REPORT

For

TECNO MOBILE LIMITED

FLAT 39 8/F BLOCK D WAH LOK INDUSTRIAL CENTRE 31-35 SHAN MEI STREET
FOTAN NT Hong Kong

FCC ID: 2ADYY-CG8

Report Type: Original Report	Product Type: Mobile phone
Report Number: SZ1210303-05350E-00C	
Report Date: 2021-04-14	
Jimmy Xiao 	
Reviewed By: RF Engineer	
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	7
EUT EXERCISE SOFTWARE	7
DUTY CYCLE	8
SUPPORT EQUIPMENT LIST AND DETAILS	11
EXTERNAL I/O CABLE	11
BLOCK DIAGRAM OF TEST SETUP	12
SUMMARY OF TEST RESULTS	13
TEST EQUIPMENT LIST	14
FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE	15
APPLICABLE STANDARD	15
FCC §15.203 - ANTENNA REQUIREMENT.....	16
APPLICABLE STANDARD	16
ANTENNA CONNECTOR CONSTRUCTION	16
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	17
APPLICABLE STANDARD	17
EUT SETUP	17
EMI TEST RECEIVER SETUP.....	17
TEST PROCEDURE	17
CORRECTED FACTOR & MARGIN CALCULATION	18
TEST DATA	18
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	21
APPLICABLE STANDARD	21
EUT SETUP	21
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	22
TEST PROCEDURE	22
CORRECTED AMPLITUDE & MARGIN CALCULATION	22
TEST DATA	22
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	34
APPLICABLE STANDARD	34
TEST PROCEDURE	34
TEST DATA	34
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	51
APPLICABLE STANDARD	51
TEST PROCEDURE	51
TEST DATA	51

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	53
APPLICABLE STANDARD	53
TEST PROCEDURE	53
TEST DATA	53
FCC §15.247(e) - POWER SPECTRAL DENSITY	60
APPLICABLE STANDARD	60
TEST PROCEDURE	60
TEST DATA	60
APPENDIX Wi-Fi.....	65
APPENDIX A: MAXIMUM CONDUCTED OUTPUT POWER (PEAK).....	65
APPENDIX B: MAXIMUM CONDUCTED OUTPUT POWER (AVERAGE)	66
APPENDIX C: MAXIMUM POWER SPECTRAL DENSITY	67

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	Mobile phone
Tested Model	CG8
Frequency Range	BLE: 2402-2480MHz Wi-Fi: 2412-2472MHz/2422-2462MHz
Maximum Conducted Peak Power	BLE: -6.95dBm Wi-Fi: 16.72(802.11b), 16.54dBm(802.11g) 16.19dBm(802.11n-HT20), 13.64dBm(802.11n-HT40)
Modulation Technique	BLE: GFSK Wi-Fi: DSSS, OFDM
Antenna Specification*	1.2dBi(It is provided by the applicant)
Voltage Range	DC 3.87V from battery or DC 5.0V or 10.0V from adapter
Date of Test	2021-03-08 to 2021-04-14
Sample number	SZ1210303-05350E-RF-S1(RSE&CE Test), SZ1210303-05350E-RF-S2(RF Conducted Test) (Assigned by BACL, Shenzhen)
Received date	2021-03-03
Sample/EUT Status	Good condition
Adapter information	Model: U330TSA Input: AC 100-240V, 50/60Hz, 1.5A Output: DC 5.0V, 3.0A 15.0W or 10.0V, 3.3A 33.0W MAX

Objective

This report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF Output Power with Power meter		±0.73dB
RF conducted test with spectrum		±1.6dB
AC Power Lines Conducted Emissions		±1.95dB
Emissions, Radiated	Below 1GHz	±4.75dB
	Above 1GHz	±4.88dB
Temperature		±1 °C
Humidity		±6%
Supply voltages		±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 802.11b, 802.11g and 802.11n-HT20 mode, 13 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	12	2467
6	2437	13	2472
7	2442	/	/

For 802.11b, 802.11g, 802.11n-HT20 mode, EUT was tested with Channel 1, 7 and 13.

For 802.11n-HT40 mode, 9 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2422	6	2447
2	2427	7	2452
3	2432	8	2457
4	2437	9	2462
5	2442	/	/

EUT was tested with Channel 1, 5 and 9.

For BLE mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

Test in the engineer mode.


The device was tested with the worst case was performed as below:

Mode	Data rate	Power level*		
		Low channel	Middle channel	High channel
802.11b	1 Mbps	19.5	19.5	19.5
802.11g	6 Mbps	17.5	17.5	15
802.11n-HT20	MCS0	17.5	17.5	14
802.11n-HT40	MCS0	16.5	16.5	15
BLE	1Mbps & 2Mbps	Default	Default	Default

The power level was provided by the applicant.


Duty cycle

802.11b mode




Date: 10.MAR.2021 11:06:18

802.11g mode




Date: 10.MAR.2021 11:06:29

802.11n-HT20 Mode




Date: 10.MAR.2021 11:06:02

802.11n-HT40 Mode




Date: 10.MAR.2021 11:05:32

BLE 1M Mode



Date: 12.APR.2021 14:58:08

BLE 2M Mode



Date: 12.APR.2021 14:58:53

Mode	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle (%)
802.11b	--	--	100
802.11g	--	--	100
802.11n-HT20	--	--	100
802.11n-HT20	--	--	100
BLE_1M	2.16	2.50	86.40
BLE_2M	1.10	1.87	58.82

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable

Cable Description	Length (m)	From Port	To
Un-shielded Detachable Earphone Cable	1.2	EUT	Earphone
Shielded Detachable USB Cable	1.0	EUT	Adapter

Block Diagram of Test Setup

For conducted emission:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b) (1)& §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2020/08/04	2021/08/03
Rohde & Schwarz	LISN	ENV216	101613	2020/08/04	2021/08/03
Rohde & Schwarz	Transient Limitor	ESH3Z2	DE25985	2020/11/29	2021/11/28
Unknown	CE Cable	CE Cable	UF A210B-1-0720-504504	2020/11/29	2021/11/28
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
Radiated Emission Test					
R&S	EMI Test Receiver	ESR3	102455	2020/08/04	2021/08/03
Sonoma instrument	Pre-amplifier	310 N	186238	2020/08/04	2021/08/03
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2020/12/22	2023/12/21
Unknown	Cable 2	RF Cable 2	F-03-EM197	2020/11/29	2021/11/28
Unknown	Cable	Chamber Cable 1	F-03-EM236	2020/11/29	2021/11/28
Rohde & Schwarz	Auto test software	EMC 32	V9.10	NCR	NCR
Rohde & Schwarz	Spectrum Analyzer	FSV40-N	102259	2020/08/04	2021/08/03
COM-POWER	Pre-amplifier	PA-122	181919	2020/11/29	2021/11/28
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2020/11/29	2021/11/28
Sunol Sciences	Horn Antenna	3115	9107-3694	2021/01/15	2024/01/14
Insulated Wire Inc.	RF Cable	SPS-2503-3150	02222010	2020/11/29	2021/11/28
Unknown	RF Cable	W1101-EQ1 OUT	F-19-EM005	2020/11/29	2021/11/28
SNSD	Band Reject filter	BSF2402-2480MN-0898-001	2.4G filter	2020/04/20	2021/04/20
Ducommun Technologies	Horn antenna	ARH-4223-02	1007726-021304	2020/12/06	2023/12/05
RF Conducted Test					
Rohde & Schwarz	SPECTRUM ANALYZER	FSU26	200120	2021/04/02	2022/04/01
Tonscend Corporation	RF control Unit	JS0806-2	19D8060154	2020/08/04	2021/08/03
Rohde & Schwarz	Signal and Spectrum Analyzer	FSV40	101473	2020/08/04	2021/08/03
WEINSCHL	3dB Attenuator	Unknown	F-03-EM121	2020/11/29	2021/11/28
Unknown	RF Cable	Unknown	8082176/W6111	2020/11/29	2021/11/28

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Measurement Result

For worst case:

Mode	Frequency (MHz)	Max Tune-up Conducted Power (dBm)	Max Tune-up Conducted Power (mW)	Calculated Distance (mm)	Calculated value	Threshold (1-g SAR)	SAR Test Exclusion
BLE	2402-2480	-6.0	0.25	5	0.1	3.0	Yes

Result: No SAR test is required

For Wi-Fi mode:

Please refer to SAR report SZ1210303-05350E-20.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
 - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one internal antenna arrangement, which was permanently attached and the antenna gain is 1.2 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$


Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	65 %
ATM Pressure:	101.0 kPa

The testing was performed by Haiguo Li on 2021-03-08.


EUT operation mode: Transmitting & Charging (worst case is 802.11b mode, Low channel)

AC 120V/60 Hz, Line**Final Result 1**

Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
4.944170	33.9	9.000	L1	19.9	22.1	56.0
5.043270	34.3	9.000	L1	19.9	25.7	60.0
6.808990	36.6	9.000	L1	19.9	23.4	60.0
7.481590	36.8	9.000	L1	19.9	23.2	60.0
7.899230	36.3	9.000	L1	19.9	23.7	60.0
8.395370	35.7	9.000	L1	20.0	24.3	60.0

Final Result 2

Frequency (MHz)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
4.944170	25.6	9.000	L1	19.9	20.4	46.0
5.043270	25.8	9.000	L1	19.9	24.2	50.0
6.808990	29.0	9.000	L1	19.9	21.0	50.0
7.481590	29.9	9.000	L1	19.9	20.1	50.0
7.899230	29.4	9.000	L1	19.9	20.6	50.0
8.395370	29.0	9.000	L1	20.0	21.0	50.0

AC 120V/60 Hz, Neutral:**Final Result 1**

Frequency (MHz)	QuasiPeak (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.470950	32.5	9.000	N	19.8	24.0	56.5
3.977970	31.7	9.000	N	19.9	24.3	56.0
4.408090	32.4	9.000	N	19.9	23.6	56.0
4.947110	33.5	9.000	N	19.9	22.5	56.0
4.991150	33.6	9.000	N	19.9	22.4	56.0
6.185150	33.9	9.000	N	19.9	26.1	60.0

Final Result 2


Frequency (MHz)	Average (dB μ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
3.902000	23.1	9.000	N	19.9	22.9	46.0
4.398000	24.6	9.000	N	19.9	21.4	46.0
4.842000	26.1	9.000	N	19.9	19.9	46.0
4.990000	25.6	9.000	N	19.9	20.4	46.0
5.934000	26.2	9.000	N	19.9	23.8	50.0
6.462000	26.6	9.000	N	19.9	23.4	50.0

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Data


Environmental Conditions

Temperature:	24~25.8 °C
Relative Humidity:	51~56 %
ATM Pressure:	101.2 kPa

The testing was performed by Kilroy Deng on 2021-03-14 for below 1GHz and Troy Wang on 2021-04-07 for above 1GHz.

EUT operation mode: Transmitting

30 MHz~1 GHz (802.11g mode, Low channel was worst case):



Critical Freqs

Frequency (MHz)	MaxPeak (dB µ V/m)	Limit (dB µ V/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
818.367500	34.69	46.00	11.31	100.0	H	107.0	5.7
699.057500	33.37	46.00	12.63	200.0	H	0.0	4.5
174.772500	34.14	43.50	9.36	200.0	H	258.0	-6.1
173.075000	34.75	43.50	8.75	200.0	H	279.0	-6.1
947.620000	37.54	46.00	8.46	100.0	V	43.0	7.6
30.121250	27.16	40.00	12.84	100.0	V	64.0	2.4

1 GHz-25 GHz (Wi-Fi):**802.11b Mode:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2412 MHz)									
2385.85	29.43	PK	306	1.2	H	31.87	61.30	74	12.70
2385.85	14.67	Ave.	306	1.2	H	31.87	46.54	54	7.46
2486.37	29.29	PK	266	2.1	H	32.13	61.42	74	12.58
2486.37	14.63	Ave.	266	2.1	H	32.13	46.76	54	7.24
4824.00	50.17	PK	345	1.7	H	6.28	56.45	74	17.55
4824.00	44.34	Ave.	345	1.7	H	6.28	50.62	54	3.38
Middle Channel (2442MHz)									
4884.00	49.43	PK	194	1.1	H	6.76	56.19	74	17.81
4884.00	43.59	Ave.	194	1.1	H	6.76	50.35	54	3.65
High Channel (2472 MHz)									
2387.25	29.23	PK	12	2.0	H	31.87	61.10	74	12.90
2387.25	14.55	Ave.	12	2.0	H	31.87	46.42	54	7.58
2483.71	30.61	PK	181	1.4	H	32.13	62.74	74	11.26
2483.71	18.01	Ave.	181	1.4	H	32.13	50.14	54	3.86
4944.00	49.11	PK	199	1.3	H	6.76	55.87	74	18.13
4944.00	44.02	Ave.	199	1.3	H	6.76	50.78	54	3.22

802.11g Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2412 MHz)									
2389.37	31.65	PK	39	2.0	H	31.87	63.52	74	10.48
2389.37	16.42	Ave.	39	2.0	H	31.87	48.29	54	5.71
2486.45	29.76	PK	289	1.6	H	32.13	61.89	74	12.11
2486.45	15.17	Ave.	289	1.6	H	32.13	47.30	54	6.70
4824.00	44.63	PK	161	2.1	H	6.28	50.91	74	23.09
4824.00	30.72	Ave.	161	2.1	H	6.28	37.00	54	17.00
Middle Channel (2442 MHz)									
4884.00	44.43	PK	349	2.2	H	6.76	51.19	74	22.81
4884.00	30.21	Ave.	349	2.2	H	6.76	36.97	54	17.03
High Channel (2472 MHz)									
2386.72	29.69	PK	233	2.4	H	31.87	61.56	74	12.44
2386.72	15.17	Ave.	233	2.4	H	31.87	47.04	54	6.96
2483.58	37.62	PK	29	1.6	H	32.13	69.75	74	4.25
2483.58	18.06	Ave.	29	1.6	H	32.13	50.19	54	3.81
4944.00	44.12	PK	341	2.1	H	6.76	50.88	74	23.12
4944.00	30.35	Ave.	341	2.1	H	6.76	37.11	54	16.89

802.11n-HT20 Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2412 MHz)									
2389.36	35.62	PK	182	1.4	H	31.87	67.49	74	6.51
2389.36	18.81	Ave.	182	1.4	H	31.87	50.68	54	3.32
2486.45	29.47	PK	357	1.6	H	32.13	61.60	74	12.40
2486.45	15.62	Ave.	357	1.6	H	32.13	47.75	54	6.25
4824.00	44.89	PK	259	1.4	H	6.28	51.17	74	22.83
4824.00	31.76	Ave.	259	1.4	H	6.28	38.04	54	15.96
Middle Channel (2442 MHz)									
4884.00	44.65	PK	262	2.4	H	6.76	51.41	74	22.59
4884.00	30.54	Ave.	262	2.4	H	6.76	37.30	54	16.70
High Channel (2472 MHz)									
2388.18	29.77	PK	13	2.0	H	31.87	61.64	74	12.36
2388.18	15.46	Ave.	13	2.0	H	31.87	47.33	54	6.67
2484.11	37.52	PK	137	1.0	H	32.13	69.65	74	4.35
2484.11	17.58	Ave.	137	1.0	H	32.13	49.71	54	4.29
4944.00	44.34	PK	268	1.5	H	6.76	51.10	74	22.90
4944.00	30.15	Ave.	268	1.5	H	6.76	36.91	54	17.09

802.11n-HT40 Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2422 MHz)									
2389.02	33.41	PK	27	2.3	H	31.87	65.28	74	8.72
2389.02	17.48	Ave.	27	2.3	H	31.87	49.35	54	4.65
2487.53	29.92	PK	127	2.4	H	32.13	62.05	74	11.95
2487.53	15.98	Ave.	127	2.4	H	32.13	48.11	54	5.89
4844.00	44.35	PK	74	1.5	H	6.28	50.63	74	23.37
4844.00	30.94	Ave.	74	1.5	H	6.28	37.22	54	16.78
Middle Channel (2442 MHz)									
4884.00	44.07	PK	189	2.2	H	6.76	50.83	74	23.17
4884.00	30.52	Ave.	189	2.2	H	6.76	37.28	54	16.72
High Channel (2462 MHz)									
2386.18	28.87	PK	182	1.2	H	31.87	60.74	74	13.26
2386.18	15.85	Ave.	182	1.2	H	31.87	47.72	54	6.28
2483.54	35.01	PK	304	2.0	H	32.13	67.14	74	6.86
2483.54	17.78	Ave.	304	2.0	H	32.13	49.91	54	4.09
4924.00	44.15	PK	355	1.5	H	6.76	50.91	74	23.09
4924.00	30.62	Ave.	355	1.5	H	6.76	37.38	54	16.62

1 GHz-25 GHz (BLE_1M):

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2402 MHz)									
2319.54	29.53	PK	243	1.8	H	31.64	61.17	74	12.83
2319.54	17.9	Ave.	243	1.8	H	31.64	49.54	54	4.46
2496.09	28.99	PK	261	1.9	H	32.13	61.12	74	12.88
2496.09	17.64	Ave.	261	1.9	H	32.13	49.77	54	4.23
4804.00	44.09	PK	314	1.6	H	6.28	50.37	74	23.63
4804.00	32.51	Ave.	314	1.6	H	6.28	38.79	54	15.21
Middle Channel (2440 MHz)									
4880.00	44.81	PK	208	1.1	H	6.76	51.57	74	22.43
4880.00	31.61	Ave.	208	1.1	H	6.76	38.37	54	15.63
High Channel (2480 MHz)									
2317.61	29.16	PK	251	2.3	H	31.64	60.80	74	13.20
2317.61	17.93	Ave.	251	2.3	H	31.64	49.57	54	4.43
2496.09	29.4	PK	221	1.9	H	32.13	61.53	74	12.47
2496.09	17.69	Ave.	221	1.9	H	32.13	49.82	54	4.18
4960.00	44.11	PK	93	1.9	H	6.80	50.91	74	23.09
4960.00	32.71	Ave.	93	1.9	H	6.80	39.51	54	14.49

1 GHz-25 GHz (BLE_2M):

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2402 MHz)									
2319.25	29.21	PK	175	2.3	H	31.64	60.85	74	13.15
2319.25	18.79	Ave.	175	2.3	H	31.64	50.43	54	3.57
2487.62	29.76	PK	185	1.4	H	32.13	61.89	74	12.11
2487.62	18.81	Ave.	185	1.4	H	32.13	50.94	54	3.06
4804.00	44.97	PK	187	2.5	H	6.28	51.25	74	22.75
4804.00	33.43	Ave.	187	2.5	H	6.28	39.71	54	14.29
Middle Channel (2440 MHz)									
4880.00	43.76	PK	172	2.4	H	6.76	50.52	74	23.48
4880.00	33.65	Ave.	172	2.4	H	6.76	40.41	54	13.59
High Channel (2480 MHz)									
2311.32	28.35	PK	98	1.0	H	31.64	59.99	74	14.01
2311.32	18.87	Ave.	98	1.0	H	31.64	50.51	54	3.49
2487.62	28.8	PK	226	2.2	H	32.13	60.93	74	13.07
2487.62	18.85	Ave.	226	2.2	H	32.13	50.98	54	3.02
4960.00	43.65	PK	360	1.5	H	6.80	50.45	74	23.55
4960.00	33.44	Ave.	360	1.5	H	6.80	40.24	54	13.76


Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor


Corrected Amplitude = Corrected Factor + Reading

Margin = Limit - Corrected. Amplitude

The other spurious emission which is 20dB to the limit was not recorded.



**Pre-scan with 802.11b Mode, High channel
Horizontal**

Date: 7.APR.2021 16:37:04





Date: 7.APR.2021 17:26:34



Vertical



Average Horizontal



Vertical




FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH**Applicable Standard**

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

**Test Data****Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	51 %
ATM Pressure:	101.0 kPa

The testing was performed by Black Chen on 2021-03-09 and 2021-03-10.

EUT operation mode: Transmitting

Test Result: Pass.


Please refer to the following table and plots.

EUT operation mode: Transmitting

Channel	Frequency (MHz)	6dB bandwidth (MHz)	99% OBW (MHz)	Limit (kHz)
802.11b mode				
Low	2412	9.057	13.68	≥ 500
Middle	2442	7.648	11.68	≥ 500
High	2472	8.604	13.44	≥ 500
802.11g mode				
Low	2412	15.843	17.52	≥ 500
Middle	2442	10.161	16.48	≥ 500
High	2472	13.192	16.96	≥ 500
802.11n-HT20 mode				
Low	2412	16.509	18.40	≥ 500
Middle	2442	10.161	17.36	≥ 500
High	2472	13.826	17.84	≥ 500
802.11n-HT40 mode				
Low	2422	36.579	40.64	≥ 500
Middle	2442	11.294	35.36	≥ 500
High	2462	35.807	39.36	≥ 500
BLE_1M mode				
Low	2402	0.669	/	≥ 500
Middle	2440	0.669	/	≥ 500
High	2480	0.674	/	≥ 500
BLE_2M mode				
Low	2402	1.200	/	≥ 500
Middle	2440	1.185	/	≥ 500
High	2480	1.183	/	≥ 500


6dB Bandwidth:

802.11b Low Channel




Date: 10.MAR.2021 09:40:29

802.11b Middle Channel




Date: 10.MAR.2021 09:42:00

802.11b High Channel




Date: 10.MAR.2021 09:43:37

802.11g Low Channel




Date: 10.MAR.2021 09:38:17

802.11g Middle Channel




Date: 10.MAR.2021 09:37:04

802.11g High Channel




Date: 10.MAR.2021 09:33:56

802.11n-HT20 Low Channel




Date: 10.MAR.2021 09:45:43

802.11n-HT20 Middle Channel




Date: 10.MAR.2021 09:49:30

802.11n-HT20 High Channel




Date: 10.MAR.2021 09:51:00

802.11n-HT40 Low Channel




Date: 10.MAR.2021 09:52:20

802.11n-HT40 Middle Channel



Date: 10.MAR.2021 09:53:35


802.11n-HT40 High Channel



Date: 10.MAR.2021 09:54:56


99% Occupied Bandwidth:

802.11b Low Channel




Date: 10.MAR.2021 09:31:19

802.11b Middle Channel




Date: 10.MAR.2021 09:31:35

802.11b High Channel




Date: 10.MAR.2021 09:31:47

802.11g Low Channel




Date: 10.MAR.2021 09:32:10

802.11g Middle Channel




Date: 10.MAR.2021 09:32:24

802.11g High Channel




Date: 10.MAR.2021 09:32:39

802.11n-HT20 Low Channel




Date: 10.MAR.2021 09:30:16

802.11n-HT20 Middle Channel




Date: 10.MAR.2021 09:30:31

802.11n-HT20 High Channel




Date: 10.MAR.2021 09:30:45

802.11n-HT40 Low Channel




Date: 10.MAR.2021 09:29:56

802.11n-HT40 Middle Channel




Date: 10.MAR.2021 09:29:42

802.11n-HT40 High Channel




Date: 10.MAR.2021 09:29:10

BLE 1M Low Channel




Date: 9.MAR.2021 11:08:42

BLE 1M Middle Channel




Date: 9.MAR.2021 11:09:36

BLE 1M High Channel




Date: 9.MAR.2021 11:10:30

BLE 2M Low Channel




Date: 9.MAR.2021 11:06:52

BLE 2M Middle Channel



Date: 9.MAR.2021 11:06:09

BLE 2M High Channel



Date: 9.MAR.2021 11:05:02


FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	51 %
ATM Pressure:	101.0 kPa

The testing was performed by Black Chen on 2021-03-09.

EUT operation mode: Transmitting

Test Result Compliant. Please refer to the Appendix Wi-Fi.

BLE mode


Channel	Frequency (MHz)	Maximum Conducted Peak Output Power (dBm)	Limit (dBm)	Result
BLE_1M				
Low	2402	-7.02	30	Pass
Middle	2440	-7.85	30	Pass
High	2480	-7.45	30	Pass
BLE_2M				
Low	2402	-6.95	30	Pass
Middle	2440	-7.77	30	Pass
High	2480	-7.32	30	Pass

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

**Test Data****Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	51 %
ATM Pressure:	101.0 kPa


The testing was performed by Black Chen on 2021-03-09 and 2021-03-10.

EUT operation mode: Transmitting

Test Result: Compliance


Please refer to the following plots.

802.11b: Band Edge, Left Side




Date: 10.MAR.2021 09:19:30

802.11b: Band Edge, Right Side




Date: 10.MAR.2021 09:20:34

802.11g: Band Edge, Left Side




Date: 10.MAR.2021 09:18:47

802.11g: Band Edge, Right Side




Date: 10.MAR.2021 09:16:24

802.11n-HT20: Band Edge, Left Side




Date: 10.MAR.2021 09:12:50

802.11n-HT20: Band Edge, Right Side




Date: 10.MAR.2021 09:15:11

802.11n-HT40: Band Edge, Left Side




Date: 10.MAR.2021 09:11:52

802.11n-HT40: Band Edge, Right Side




Date: 10.MAR.2021 09:10:47

BLE 1M: Band Edge, Left Side




Date: 9.MAR.2021 11:14:41

BLE 1M: Band Edge, Right Side




Date: 9.MAR.2021 11:12:13

BLE 2M: Band Edge, Left Side



Date: 9.MAR.2021 11:13:58

BLE 2M: Band Edge, Right Side



Date: 9.MAR.2021 11:13:01


FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
3. Set the VBW $\geq 3 \times \text{RBW}$.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	51 %
ATM Pressure:	101.0 kPa


The testing was performed by Black Chen and Bravos Zhao from 2021-03-09 to 2021-04-14.

EUT operation mode: Transmitting

Test Result Compliant. Please refer to the Appendix Wi-Fi.


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
BLE_1M mode			
Low	2402	-24.42	≤ 8
Middle	2440	-25.15	≤ 8
High	2480	-24.98	≤ 8
BLE_2M mode			
Low	2402	-26.48	≤ 8
Middle	2440	-28.51	≤ 8
High	2480	-27.22	≤ 8

Power Spectral Density, BLE 1M Low Channel




Date: 9.MAR.2021 11:02:45

Power Spectral Density, BLE 1M Middle Channel




Date: 9.MAR.2021 11:02:30

Power Spectral Density, BLE 1M High Channel




Date: 9.MAR.2021 11:01:39

Power Spectral Density, BLE 2M Low Channel




Date: 9.MAR.2021 11:03:00

Power Spectral Density, BLE 2M Middle Channel



Date: 9.MAR.2021 11:03:15

Power Spectral Density, BLE 2M High Channel



Date: 9.MAR.2021 11:03:31

APPENDIX Wi-Fi**Appendix A: Maximum conducted output power (Peak)
Test Result**

Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	16.72	<=30	PASS
		2442	12.86	<=30	PASS
		2472	12.78	<=30	PASS
11G	Ant1	2412	16.54	<=30	PASS
		2442	12.64	<=30	PASS
		2472	11.88	<=30	PASS
11N20	Ant1	2412	16.19	<=30	PASS
		2442	13.20	<=30	PASS
		2472	14.40	<=30	PASS
11N40	Ant1	2422	12.37	<=30	PASS
		2442	12.52	<=30	PASS
		2462	13.64	<=30	PASS


**Appendix B: Maximum conducted output power (Average)
Test Result**

Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	13.94	<=30	PASS
		2442	9.89	<=30	PASS
		2472	9.75	<=30	PASS
11G	Ant1	2412	10.19	<=30	PASS
		2442	6.98	<=30	PASS
		2472	6.17	<=30	PASS
11N20	Ant1	2412	10.84	<=30	PASS
		2442	7.57	<=30	PASS
		2472	8.95	<=30	PASS
11N40	Ant1	2422	6.67	<=30	PASS
		2442	6.39	<=30	PASS
		2462	7.54	<=30	PASS


**Appendix C: Maximum power spectral density
Test Result**

Test Mode	Antenna	Channel	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-9.52	<=8	PASS
		2442	-9.95	<=8	PASS
		2472	-11.62	<=8	PASS
11G	Ant1	2412	-13.20	<=8	PASS
		2442	-14.39	<=8	PASS
		2472	-16.41	<=8	PASS
11N20	Ant1	2412	-13.03	<=8	PASS
		2442	-14.36	<=8	PASS
		2472	-14.73	<=8	PASS
11N40	Ant1	2422	-18.41	<=8	PASS
		2442	-16.00	<=8	PASS
		2462	-15.35	<=8	PASS


Test Graphs




11G Ant1_2412




11G Ant1_2442




11G Ant1_2472




11N20_Ant1_2412




11N20_Ant1_2442



11N20_Ant1_2472





***** END OF REPORT *****