

RF Exposure Evaluation Report

APPLICANT : Emerson Digital Cold Chain, Inc.
EQUIPMENT : Global PCBA
BRAND NAME : Emerson
MODEL NAME : NNT-TG05
FCC ID : AMH101019
STANDARD : 47 CFR Part 2.1091

The product evaluation date was started from Jul. 13, 2022 and completed on Jul. 13, 2022. We, Sporton International Inc. (Shenzhen), would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091, and pass the limit. Without written approval of Sporton International Inc. (Shenzhen), the test report shall not be reproduced except in full.



Approved by: Si Zhang

Sporton International Inc. (Shenzhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



Table of Contents

| | |
|--|----------|
| 1. ADMINISTRATION DATA | 4 |
| 1.1. Testing Laboratory | 4 |
| 2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT) | 5 |
| 3. MAXIMUM RF AVERAGE OUTPUT TUNE UP POWER AMONG PRODUCTION UNITS | 6 |
| 4. RF EXPOSURE LIMIT INTRODUCTION | 7 |
| 5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION | 9 |
| 5.1. Standalone assessment | 9 |



Revision History

| REPORT NO. | VERSION | DESCRIPTION | ISSUED DATE |
|------------|---------|--------------------------|---------------|
| FA260705 | Rev. 01 | Initial issue of report. | Aug. 03, 2022 |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |



1. Administration Data

1.1. Testing Laboratory

Sporton International Inc. (Shenzhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

| Testing Laboratory | | | |
|--------------------|--|---------------------|--------------------------------|
| Test Firm | Sporton International Inc. (Shenzhen) | | |
| Test Site Location | 1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595 | | |
| Test Site No. | Sporton Site No. | FCC Designation No. | FCC Test Firm Registration No. |
| | SAR01-SZ | CN1256 | 421272 |

| Applicant | |
|--------------|--|
| Company Name | Emerson Digital Cold Chain, Inc. |
| Address | 7121 Fairway Dr. Suite #400 Palm Beach Gardens, FL 33418 USA |

| Manufacturer | |
|--------------|---|
| Company Name | Konka Smart Technology Co. , Ltd |
| Address | No.12,West Section of Gangyuan Road, Guoxing Avenue,Lingang Economic Development Zone,Yibin City,P.R.China ZIP:511581 |

2. Description of Equipment Under Test (EUT)

| Product Feature & Specification | |
|---|--|
| EUT Type | Global PCBA |
| Brand Name | Emerson |
| Model Name | NNT-TG05 |
| FCC ID | AMH101019 |
| Wireless Technology and Frequency Range | GSM850: 824 MHz ~ 849 MHz GSM1900: 1850 MHz ~ 1910 MHz LTE Category M1: LTE Band 2 : 1850 MHz ~ 1910 MHz LTE Band 4 : 1710 MHz ~ 1755 MHz LTE Band 5 : 824 MHz ~ 849 MHz LTE Band 12 : 699 MHz ~ 716 MHz LTE Band 13 : 777 MHz ~ 787 MHz LTE Band 26 : 814 MHz ~ 849 MHz NB-IOT Category NB1 : NB-IOT Band 2 : 1850 MHz ~ 1910 MHz NB-IOT Band 4 : 1710 MHz ~ 1755 MHz NB-IOT Band 5 : 824 MHz ~ 849 MHz NB-IOT Band 12 : 699 MHz ~ 716 MHz NB-IOT Band 13 : 777 MHz ~ 787 MHz NB-IOT Band 26 : 814 MHz ~ 849 MHz |
| Mode | GPRS/EGPRS LTE Category M1: QPSK / 16QAM NB-IOT Category NB1 :BPSK / QPSK |
| Antenna Type | Fixed External Antenna |
| HW Version | BR0C |
| SW Version | Ver 1.0.a18 |
| EUT Stage | Production Unit |

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

| Comments and Explanations: |
|---|
| 1. The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification. 2. The maximum RF output tune up power, antenna gain also the safe distance used for evaluate RF exposure were declared by manufacturer. |

3. Maximum RF average output tune up power among production units

<GSM>

| Mode | Burst average power(dBm) | |
|-------------------------|--------------------------|----------|
| | GSM 850 | GSM 1900 |
| GPRS (GMSK, 1 Tx slot) | 33.00 | 30.00 |
| GPRS (GMSK, 2 Tx slots) | 33.00 | 30.00 |
| GPRS (GMSK, 3 Tx slots) | 32.00 | 30.00 |
| GPRS (GMSK, 4 Tx slots) | 31.00 | 30.00 |
| EDGE (8PSK, 1 Tx slot) | 27.00 | 26.00 |
| EDGE (8PSK, 2 Tx slots) | 27.00 | 26.00 |
| EDGE (8PSK, 3 Tx slots) | 27.00 | 26.00 |
| EDGE (8PSK, 4 Tx slots) | 27.00 | 26.00 |

<LTE>

| Mode | | Maximum Average power(dBm) |
|------------|---------|----------------------------|
| LTE Cat M1 | Band 2 | 24.00 |
| | Band 4 | 23.00 |
| | Band 5 | 24.00 |
| | Band 12 | 24.00 |
| | Band 13 | 23.00 |
| | Band 26 | 24.00 |
| NB-IOT | Band 2 | 23.00 |
| | Band 4 | 23.00 |
| | Band 5 | 24.00 |
| | Band 12 | 23.00 |
| | Band 13 | 23.00 |
| | Band 26 | 23.50 |

4. RF Exposure Limit Introduction

1. Per 1.1307(b)(3), (i) For single RF sources (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph (b)(2) of this section): A single RF source is exempt if:

- (A) The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);
- (B) Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad [1]$$

$$\text{Where } x = -\log_{10}\left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}}\right) \text{ and } f \text{ is in GHz} \quad [2]$$

$$\text{and } ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} < f \leq 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} < f \leq 6 \text{ GHz} \end{cases} \quad [3]$$

- (C) Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value)

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

| RF Source frequency (MHz) | Threshold ERP (watts) |
|---------------------------|-----------------------|
| 0.3-1.34 | $1,920 R^2$ |
| 1.34-30 | $3,450 R^2 / f^2$ |
| 30-300 | $3.83 R^2$ |
| 300-1,500 | $0.0128 R^2 f$ |
| 1,500-100,000 | $19.2 R^2$ |

2. For multiple RF sources: Multiple RF sources are exempt if:

- (A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(i)(A).
- (B) In the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

- a. a = number of fixed, mobile, or portable RF sources claiming exemption using the § 1.1307(b)(3)(i)(B) formula for P_{th} , including existing exempt transmitters and those being added.
- b. b = number of fixed, mobile, or portable RF sources claiming exemption using the applicable § 1.1307(b)(3)(i)(C) Table 1 formula for Threshold ERP, including existing exempt transmitters and those being added.
- c. c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance.
- d. P_i , the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive)
- e. $P_{th,i}$ the exemption threshold power (P_{th}) according to the § 1.1307(b)(3)(i)(B) formula for fixed, mobile, or portable RF source i .
- f. ERP_j the available maximum time-averaged power or the ERP, whichever is greater, of fixed, mobile, or portable RF source j .
- g. $ERP_{th,j}$ exemption threshold ERP for fixed, mobile, or portable RF source j , at a distance of at least $\lambda/2\pi$, according to the applicable § 1.1307(b)(3)(i)(C) Table 1 formula at the location in question.
- h. $Evaluated_k$ the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation.
- i. $Exposure\ Limit_k$ either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable sources RF source k , as applicable from § 1.1310 of this chapter.
- j. *The relationship between EIRP and ERP is: $ERP\ (dBm) = EIRP - 2.15$, Where $EIRP$ is the sum of the conducted power (dBm) and the antenna gain (dBi)*

The sum of the ratios of the applicable terms for SAR-based, MPE-based and measured SAR or MPE shall be less than 1, to determine simultaneous transmission exposure compliance



5. Radio Frequency Radiation Exposure Evaluation

5.1. Standalone assessment

| Band | Antenna Gain (dBi) | Maximum Conducted Power (dBm) | Maximum EIRP (dBm) | Maximum ERP (dBm) | Maximum ERP (mW) | Separation Distance (cm) | Part1.1307 option(b) Threshold (mW) |
|-------------------------|--------------------|-------------------------------|--------------------|-------------------|------------------|--------------------------|-------------------------------------|
| GPRS 850 (1 Tx slot) | -5.51 | 33.00 | 18.49 | 16.34 | 43.05 | 20 | 1681.368 |
| GPRS 850 (2 Tx slots) | -5.51 | 33.00 | 21.49 | 19.34 | 85.90 | 20 | 1680.960 |
| GPRS 850 (3 Tx slots) | -5.51 | 32.00 | 22.23 | 20.08 | 101.86 | 20 | 1681.368 |
| GPRS 850 (4 Tx slots) | -5.51 | 31.00 | 22.49 | 20.34 | 108.14 | 20 | 1681.368 |
| EGPRS 850 (1 Tx slot) | -5.51 | 27.00 | 12.49 | 10.34 | 10.81 | 20 | 1681.368 |
| EGPRS 850 (2 Tx slots) | -5.51 | 27.00 | 15.49 | 13.34 | 21.58 | 20 | 1680.960 |
| EGPRS 850 (3 Tx slots) | -5.51 | 27.00 | 17.23 | 15.08 | 32.21 | 20 | 1680.960 |
| EGPRS 850 (4 Tx slots) | -5.51 | 27.00 | 18.49 | 16.34 | 43.05 | 20 | 1680.960 |
| GPRS 1900 (1 Tx slot) | -4.12 | 30.00 | 16.88 | 14.73 | 29.72 | 20 | 3060.000 |
| GPRS 1900 (2 Tx slots) | -4.12 | 30.00 | 19.88 | 17.73 | 59.29 | 20 | 3060.000 |
| GPRS 1900 (3 Tx slots) | -4.12 | 30.00 | 21.62 | 19.47 | 88.51 | 20 | 3060.000 |
| GPRS 1900 (4 Tx slots) | -4.12 | 30.00 | 22.88 | 20.73 | 118.30 | 20 | 3060.000 |
| EGPRS 1900 (1 Tx slot) | -4.12 | 26.00 | 12.88 | 10.73 | 11.83 | 20 | 3060.000 |
| EGPRS 1900 (2 Tx slots) | -4.12 | 26.00 | 15.88 | 13.73 | 23.60 | 20 | 3060.000 |
| EGPRS 1900 (3 Tx slots) | -4.12 | 26.00 | 17.62 | 15.47 | 35.24 | 20 | 3060.000 |
| EGPRS 1900 (4 Tx slots) | -4.12 | 26.00 | 18.88 | 16.73 | 47.10 | 20 | 3060.000 |
| LTE Band 2 | -4.12 | 24.00 | 19.88 | 17.73 | 59.29 | 20 | 3060.000 |
| LTE Band 4 | -4.11 | 23.00 | 18.89 | 16.74 | 47.21 | 20 | 3060.000 |
| LTE Band 5 | -5.51 | 24.00 | 18.49 | 16.34 | 43.05 | 20 | 1680.960 |
| LTE Band 12 | -7.41 | 24.00 | 16.59 | 14.44 | 27.80 | 20 | 1425.960 |
| LTE Band 13 | -10.34 | 23.00 | 12.66 | 10.51 | 11.25 | 20 | 1585.080 |
| LTE Band 26 | -5.51 | 24.00 | 18.49 | 16.34 | 43.05 | 20 | 1660.560 |
| NB-IOT LTE Band 2 | -4.12 | 23.00 | 18.88 | 16.73 | 47.10 | 20 | 3060.000 |
| NB-IOT LTE Band 4 | -4.11 | 23.00 | 18.89 | 16.74 | 47.21 | 20 | 3060.000 |
| NB-IOT LTE Band 5 | -5.51 | 24.00 | 18.49 | 16.34 | 43.05 | 20 | 1680.960 |
| NB-IOT LTE Band 12 | -7.41 | 23.00 | 15.59 | 13.44 | 22.08 | 20 | 1425.960 |
| NB-IOT LTE Band 13 | -10.34 | 23.00 | 12.66 | 10.51 | 11.25 | 20 | 1585.080 |
| NB-IOT LTE Band 26 | -5.51 | 23.50 | 17.99 | 15.84 | 38.37 | 20 | 1660.560 |

Conclusion:

According to 47 CFR §1.1307 (b), the RF exposure analysis concludes that the RF Exposure is FCC compliant.

-----THE END-----