Applicant/Grantee Fibocom Wireless Inc./ZMO						
FCC ID: ZMOL831						
Section 15.212 Modular Transmitters						
Request		uest for Limited Modular Approval				
	Requirements	EUT Conditions	Comply (Y/N)			
Single Modular Approval Requirements						
1	The radio elements of the modular	The radio portion of this module has	Y			
	transmitter must have their own	been shielded, please see exhibition				
	shielding. The physical crystal and	external photos.				
	tuning capacitors may be located					
	external to the shielded radio elements.					
2	The modular transmitter must have	Buffered data inputs stage has been	Y			
	buffered modulation/data inputs (if such	integrated in chip PMB5740+PMB9920				
	inputs are provided) to ensure that the					
	module will comply with Part 15					
	requirements under conditions of					
	excessive data rates or over-modulation.					
3	The modular transmitter must have its	The part number of the power regulator	Y			
	own power supply regulation.	is RF8081. Please see the schem.pdf				
4	The modular transmitter must comply	The requirements of antenna connector	Y			
	with the antenna and transmission	and spurious emission have been				
	system requirements of Sections 15.203,	fulfilled, please refer to the Test Report				
	15.204(b) and 15.204(c). The antenna	exhibition.				
	must either be permanently attached or					
	employ a "unique" antenna coupler (at					
	all connections between the module and					
	the antenna, including the cable). The					
	"professional installation" provision of					
	Section 15.203 is not applicable to					
	modules but can apply to limited					
	modular approvals under paragraph (b)					
~	of this section.	Di C + d C + Di +	<b>T</b> 7			
5	The modular transmitter must be tested	Please refer to the Setup Photo	Y			
	in a stand-alone configuration, <i>i.e.</i> , the	exhibition for the stand-alone test				
	module must not be inside another	configuration.				
	device during testing for compliance					
	with Part 15 requirements. Unless the transmitter module will be battery					
	powered, it must comply with the AC					
	line conducted requirements found in					
	Section 15.207. AC or DC power lines					
	and data input/output lines connected to					
	the module must not contain ferrites,					
	unless they will be marketed with the					
	module (see Section 15.27(a)). The					
	length of these lines shall be the length					
	typical of actual use or, if that length is					
	unknown, at least 10 centimeters to					
	insure that there is no coupling between					
	the case of the module and supporting					

or support equipment connected to the	
module during testing shall be	
unmodified and commercially available	
(see Section 15.31(i)).	7
The modular transmitter must be The GSM/GPRS/EGPRS+WCDMA+ Y	(
equipped with either a permanently  LTE Module will be labeled with its	
affixed label or must be capable of own FCC ID, and the instruction on the	
electronically displaying its FCC  labeling rule of the end product has been	
identification number. stated in the User Manual of this	
(A) If using a permanently affixed label, the modular transmitter must be labeled with its own	
modular transmitter must be labeled with its own FCC identification number, and, if the FCC  User Manual exhibition.	
identification number is not visible when the	
module is installed inside another device, then	
the outside of the device into which the module is	
installed must also display a label referring to	
the enclosed module. This exterior label can use wording such as the following: "Contains	
Transmitter Module	
FCC ID: XYZMODEL1" or "Contains FCC ID:	
XYZMODEL1." Any similar wording	
that expresses the same meaning may be used.	
The Grantee may either provide such a label, an example of which must be included in the	
application for equipment	
authorization, or, must provide adequate	
instructions along with the module which explain	
this requirement. In the latter case, a copy of	
these instructions must be included in the application for equipment authorization.	
(B) If the modular transmitter uses an electronic	
display of the FCC identification number, the	
information must be readily accessible and	
visible on the modular transmitter or on the	
device in which it is installed. If the module is installed inside another device, then the outside	
of the device into which the module is installed	
must display a label referring to the enclosed	
module. This exterior label can use wording such	
as the following: "Contains FCC certified transmitter module(s)."	
Any similar wording that expresses the same	
meaning may be used. The user manual must	
include instructions on how to access the	
electronic display. A copy of these instructions	
must be included in the application for equipment authorization.	
7 The modular transmitter must comply The required FCC rule has been fulfilled Y	7
with any specific rules or operating and all the instructions for maintaining	
requirements that compliance have been clearly stated in	
ordinarily apply to a complete the User Manual.	
transmitter and the manufacturer must	
provide adequate instructions along with	
the module to explain any such	
requirements. A copy of these	
instructions must be included in the	
application for equipment authorization.	

8	The modular transmitter must comply	Please refer exhibition RF Exposure for	Y
	with any applicable RF exposure	the compliance of MPE RF exposure	
	requirements in its final configuration.	rule.	

Tao Zhu

Tao Zhu