

Test Report

Report No.: MTi240822017-01E1

Date of issue: 2024-11-08

Applicant: Spigen Korea Co., Ltd.

Product name: OneTap Pro 3 Cryomax Wireless Charging Stand,
OneTap Pro 3 Cryomax Wireless Charger with
Kickstand

Model(s): S310WC, S310WCK

FCC ID: 2AFKNS310WC

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.cn>

The test report is only used for customer scientific research, teaching, internal quality control and other purposes, and is for internal reference only.







Instructions

1. This test report shall not be partially reproduced without the written consent of the laboratory.
2. The test results in this test report are only responsible for the samples submitted
3. This test report is invalid without the seal and signature of the laboratory.
4. This test report is invalid if transferred, altered, or tampered with in any form without authorization.
5. Any objection to this test report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

Table of contents

1	General Description	5
1.1	Description of the EUT	5
1.2	Description of test modes	5
1.3	Environmental Conditions	6
1.4	Description of support units	6
1.5	Measurement uncertainty	6
2	Summary of Test Result	7
3	Test Facilities and accreditations	8
3.1	Test laboratory	8
4	List of test equipment.....	9
5	Evaluation Results (Evaluation).....	10
5.1	Antenna requirement	10
6	Radio Spectrum Matter Test Results (RF)	11
6.1	Conducted Emission at AC power line	11
6.2	20dB Occupied Bandwidth	16
6.3	Emissions in frequency bands (below 30MHz).....	20
6.4	Emissions in frequency bands (30MHz - 1GHz).....	29
	Photographs of the test setup.....	34
	Photographs of the EUT.....	35

Test Result Certification	
Applicant:	Spigen Korea Co., Ltd.
Address:	Spigen HQ-A, 446, Bongeunsa-ro, Gangnam-gu, Seoul, 06153, South Korea
Manufacturer:	Shenzhen Powerqi Technology Co.,Ltd
Address:	2nd Floor,Building A4,Block A,Fangxing Science &Tech.Park,No.13 of BaoNan Road,Longgang District,Shengzhen,China.
Factory 1:	Shenzhen Powerqi Technology Co.,Ltd.
Address:	Room 201, 302, 401 of A4 Building, Block A, Fangxing Science and Technology Park, No. 13 of Baonan Road, Longgang District, Shenzhen, China.
Factory 2:	SEOSIN ELECTRONICS VINA CO., LTD
Address:	Chau Son industrial Park, Le Chan Road, Le Hong Phong Ward, Phu Ly City.Ha Nam Province, Viet Nam
Product description	
Product name:	OneTap Pro 3 Cryomax Wireless Charging Stand, OneTap Pro 3 Cryomax Wireless Charger with Kickstand
Trademark:	
Model name:	S310WC
Series Model(s):	S310WCK
Standards:	47 CFR Part 15C
Test Method:	ANSI C63.10-2013
Date of Test	
Date of test:	2024-10-18 to 2024-11-06
Test result:	Pass

Test Engineer	:	
		(Yanice.Xie)
Reviewed By	:	
		(David Lee)
Approved By	:	
		(Leon Chen)

1 General Description

1.1 Description of the EUT

Product name:	OneTap Pro 3 Cryomax Wireless Charging Stand, OneTap Pro 3 Cryomax Wireless Charger with Kickstand
Model name:	S310WC
Series Model(s):	S310WCK
Model difference:	All the models are the same circuit and module, except the product name,model name and stand base. OneTap Pro 3 Cryomax Wireless Charging Stand is S310WC, OneTap Pro 3 Cryomax Wireless Charger with Kickstand is S310WCK.
Electrical rating:	Input:DC 5V/3A, 9V/2.77A, 12V/1.67A Output:15W Max
Accessories:	Cable:Type-C to type-C 1m
Hardware version:	V10
Software version:	V1.0
Test sample(s) number:	MTi240822017-01S1001 MTi240822017-01S1002
RF specification	
Operating frequency range:	115-205kHz(5W-10W) & 360kHz(15W)
Modulation type:	ASK
Antenna(s) type:	Coil

1.2 Description of test modes

No.	Emission test modes
Mode1	Wireless Output(5W)
Mode2	Wireless Output(7.5W)
Mode3	Wireless Output(10W)
Mode4	Wireless Output(15W)
Mode5	Standby

1.3 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15°C ~ 35°C
Humidity:	20% RH ~ 75% RH
Atmospheric pressure:	98 kPa ~ 101 kPa

1.4 Description of support units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Support equipment list			
Description	Model	Serial No.	Manufacturer
wireless charging load	YBZ1.1	/	YBZ
wireless charging load	YBZ3.0	/	YBZ
HUAWEI QUICK CHARGE(65W)	HW-200200ZP1	JN67LSN7N03451	HUAWEI
Support cable list			
Description	Length (m)	From	To
/	/	/	/

1.5 Measurement uncertainty

Measurement	Uncertainty
Conducted emissions (AMN 150kHz~30MHz)	±3.1dB
Occupied channel bandwidth	±3 %
Radiated spurious emissions (9kHz~30MHz)	±4.3dB
Radiated spurious emissions (30MHz~1GHz)	±4.7dB
Temperature	±1 °C
Humidity	± 5 %

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2 Summary of Test Result

No.	Item	Standard	Requirement	Result
1	Antenna requirement	47 CFR Part 15C	47 CFR Part 15.203	Pass
2	Conducted Emission at AC power line	47 CFR Part 15C	47 CFR Part 15.207(a)	Pass
3	20dB Occupied Bandwidth	47 CFR Part 15C	47 CFR Part 15.215(c)	Pass
4	Emissions in frequency bands (below 30MHz)	47 CFR Part 15C	47 CFR Part 15.209	Pass
5	Emissions in frequency bands (30MHz - 1GHz)	47 CFR Part 15C	47 CFR Part 15.209	Pass

3 Test Facilities and accreditations

3.1 Test laboratory

Test laboratory:	Shenzhen Microtest Co., Ltd.
Test site location:	101, No.7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China
Telephone:	(86-755)88850135
Fax:	(86-755)88850136
CNAS Registration No.:	CNAS L5868
FCC Registration No.:	448573
IC Registration No.:	21760
CABID:	CN0093

4 List of test equipment

No.	Equipment	Manufacturer	Model	Serial No.	Cal. date	Cal. Due
Conducted Emission at AC power line						
1	EMI Test Receiver	Rohde&schwarz	ESCI3	101368	2024-03-20	2025-03-19
2	Artificial mains network	Schwarzbeck	NSLK 8127	183	2024-03-21	2025-03-20
3	Artificial Mains Network	Rohde & Schwarz	ESH2-Z5	100263	2024-03-20	2025-03-19
20dB Occupied Bandwidth						
1	Wideband Radio Communication Tester	Rohde&schwarz	CMW500	149155	2024-03-20	2025-03-19
2	ESG Series Analog Ssignal Generator	Agilent	E4421B	GB40051240	2024-03-21	2025-03-20
3	PXA Signal Analyzer	Agilent	N9030A	MY51350296	2024-03-21	2025-03-20
4	Synthesized Sweeper	Agilent	83752A	3610A01957	2024-03-21	2025-03-20
5	MXA Signal Analyzer	Agilent	N9020A	MY50143483	2024-03-21	2025-03-20
6	RF Control Unit	Tonscend	JS0806-1	19D8060152	2024-03-21	2025-03-20
7	Band Reject Filter Group	Tonscend	JS0806-F	19D8060160	2024-03-21	2025-03-20
8	ESG Vector Signal Generator	Agilent	N5182A	MY50143762	2024-03-20	2025-03-19
9	DC Power Supply	Agilent	E3632A	MY40027695	2024-03-21	2025-03-20
Emissions in frequency bands (below 30MHz)						
1	EMI Test Receiver	Rohde&schwarz	ESCI7	101166	2024-03-20	2025-03-19
2	Active Loop Antenna	Schwarzbeck	FMZB 1519 B	00066	2024-03-23	2025-03-22
3	Amplifier	Hewlett-Packard	8447F	3113A06184	2024-03-20	2025-03-19
Emissions in frequency bands (30MHz - 1GHz)						
1	EMI Test Receiver	Rohde&schwarz	ESCI7	101166	2024-03-20	2025-03-19
2	TRILOG Broadband Antenna	schwarabeck	VULB 9163	9163-1338	2023-06-11	2025-06-10
3	Active Loop Antenna	Schwarzbeck	FMZB 1519 B	00066	2024-03-23	2025-03-22
4	Amplifier	Hewlett-Packard	8447F	3113A06184	2024-03-20	2025-03-19

5 Evaluation Results (Evaluation)

5.1 Antenna requirement

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
-------------------	---

5.1.1 Conclusion:

The antenna of the EUT is permanently attached.
The EUT complies with the requirement of FCC PART 15.203.

6 Radio Spectrum Matter Test Results (RF)


6.1 Conducted Emission at AC power line

Test Requirement:	Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).		
Test Limit:	Frequency of emission (MHz)	Conducted limit (dB μ V)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
	*Decreases with the logarithm of the frequency.		
Test Method:	ANSI C63.10-2013 section 6.2		
Procedure:	Refer to ANSI C63.10-2013 section 6.2, standard test method for ac power-line conducted emissions from unlicensed wireless devices		

6.1.1 E.U.T. Operation:

Operating Environment:			
Temperature:	25.9 °C	Humidity:	44 %
Pre test mode:	Mode1, Mode2, Mode3, Mode4, Mode5		
Final test mode:	All of the listed pre-test mode were tested, only the data of the worst mode (Mode4) is recorded in the report		


6.1.2 Test Setup Diagram:



6.1.3 Test Data:


S310WC:

Mode4 / Line: Line



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1539	44.75	10.30	55.05	65.79	-10.74	QP	
2		0.1539	28.82	10.30	39.12	55.79	-16.67	AVG	
3		0.2420	36.42	10.32	46.74	62.03	-15.29	QP	
4		0.3620	33.77	10.38	44.15	58.68	-14.53	QP	
5		0.3620	30.82	10.38	41.20	48.68	-7.48	AVG	
6		1.7980	19.39	10.55	29.94	46.00	-16.06	AVG	
7		2.5140	28.77	10.56	39.33	56.00	-16.67	QP	
8		2.5140	25.64	10.56	36.20	46.00	-9.80	AVG	
9	*	3.2328	30.98	10.56	41.54	46.00	-4.46	AVG	
10		3.2380	34.75	10.56	45.31	56.00	-10.69	QP	
11		8.6300	27.79	10.65	38.44	60.00	-21.56	QP	
12		14.3820	23.79	10.93	34.72	50.00	-15.28	AVG	


Mode4 / Line: Neutral



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1580	44.98	10.30	55.28	65.57	-10.29	QP	
2		0.1580	26.23	10.30	36.53	55.57	-19.04	AVG	
3		0.3620	34.59	10.38	44.97	58.68	-13.71	QP	
4		0.3620	32.36	10.38	42.74	48.68	-5.94	AVG	
5		1.7980	21.11	10.55	31.66	56.00	-24.34	QP	
6		2.5180	30.73	10.56	41.29	56.00	-14.71	QP	
7		2.5180	28.25	10.56	38.81	46.00	-7.19	AVG	
8		3.2340	34.89	10.56	45.45	56.00	-10.55	QP	
9	*	3.2340	32.20	10.56	42.76	46.00	-3.24	AVG	
10		3.9540	26.71	10.57	37.28	46.00	-8.72	AVG	
11		5.1300	29.22	10.57	39.79	60.00	-20.21	QP	
12		25.8860	24.22	10.94	35.16	50.00	-14.84	AVG	


S310WCK:

Mode4 / Line: Line



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1580	42.63	10.30	52.93	65.57	-12.64	QP	
2		0.1660	24.50	10.30	34.80	55.16	-20.36	AVG	
3		0.3580	35.15	10.38	45.53	58.77	-13.24	QP	
4		0.3620	32.02	10.38	42.40	48.68	-6.28	AVG	
5		2.5180	28.32	10.56	38.88	56.00	-17.12	QP	
6		2.5180	27.55	10.56	38.11	46.00	-7.89	AVG	
7		3.2340	33.80	10.56	44.36	56.00	-11.64	QP	
8	*	3.2340	30.37	10.56	40.93	46.00	-5.07	AVG	
9		3.9540	27.47	10.57	38.04	46.00	-7.96	AVG	
10		10.0659	28.85	10.67	39.52	60.00	-20.48	QP	
11		29.4820	27.68	10.85	38.53	60.00	-21.47	QP	
12		29.4820	26.34	10.85	37.19	50.00	-12.81	AVG	

Mode4 / Line: Neutral



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1580	44.38	10.30	54.68	65.57	-10.89	QP	
2		0.1580	25.30	10.30	35.60	55.57	-19.97	AVG	
3		0.3620	34.43	10.38	44.81	58.68	-13.87	QP	
4	*	0.3620	33.18	10.38	43.56	48.68	-5.12	AVG	
5		2.5180	28.22	10.56	38.78	56.00	-17.22	QP	
6		2.5180	27.47	10.56	38.03	46.00	-7.97	AVG	
7		3.2328	29.89	10.56	40.45	46.00	-5.55	AVG	
8		3.2380	33.85	10.56	44.41	56.00	-11.59	QP	
9		3.9540	28.06	10.57	38.63	46.00	-7.37	AVG	
10		5.8619	28.83	10.59	39.42	60.00	-20.58	QP	
11		27.3260	26.31	10.91	37.22	50.00	-12.78	AVG	
12		28.7620	27.83	10.87	38.70	60.00	-21.30	QP	


6.2 20dB Occupied Bandwidth

Test Requirement:	47 CFR Part 15.215(c)
Test Limit:	Refer to 47 CFR 15.215(c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.
Test Method:	ANSI C63.10-2013, section 6.9.2
Procedure:	<p>a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.</p> <p>b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.</p> <p>c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (OBW/RBW)]$ below the reference level. Specific guidance is given in 4.1.5.2.</p> <p>d) Steps a) through c) might require iteration to adjust within the specified tolerances.</p> <p>e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.</p> <p>f) Set detection mode to peak and trace mode to max hold.</p> <p>g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).</p> <p>h) Determine the “-xx dB down amplitude” using $[(\text{reference value}) - xx]$. Alternatively, this calculation may be made by using the marker-delta function of the instrument.</p> <p>i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).</p> <p>j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.</p> <p>k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).</p>

6.2.1 E.U.T. Operation:


Operating Environment:					
Temperature:	24 °C	Humidity:	54 %	Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4, Mode5				
Final test mode:	All of the listed pre-test mode were tested, only the data of the worst mode (Mode3-4) is recorded in the report				

6.2.2 Test Setup Diagram:




6.2.3 Test Data:

Note: Because the measured signal is CW-like, adjusting the RBW per C63.10 would not be practical since measurement bandwidth will always follow the RBW. The RBW is set to 300 Hz to perform the occupied bandwidth test.



Note: Because the measured signal is CW-like, adjusting the RBW per C63.10 would not be practical since measurement bandwidth will always follow the RBW. The RBW is set to 300 Hz to perform the occupied bandwidth test.

Frequency kHz	20 dB occupied bandwidth Hz	99% occupied bandwidth Hz
360	820	702




6.3 Emissions in frequency bands (below 30MHz)

Test Requirement:	47 CFR Part 15.209		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector. As shown in § 15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation under paragraph (b) of this section, the peak field strength shall not exceed 2500 millivolts/meter at 3 meters along the antenna azimuth.			
Test Method:	ANSI C63.10-2013 section 6.4		
Procedure:	ANSI C63.10-2013 section 6.4		

6.3.1 E.U.T. Operation:

Operating Environment:			
Temperature:	22.5 °C	Humidity:	43 %
		Atmospheric Pressure:	101 kPa
Pre test mode:	Mode1, Mode2, Mode3, Mode4, Mode5		
Final test mode:	All of the listed pre-test mode were tested, only the data of the worst mode (Mode3, Mode4) is recorded in the report		


6.3.2 Test Setup Diagram:




6.3.3 Test Data:

S310WC:

Mode3 / Polarization: Coplanar




Mode3 / Polarization: Coplanar




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		0.4349	32.64	21.24	53.88	114.84	-60.96	peak	
2		0.4351	30.64	21.26	51.90	94.83	-42.93	AVG	
3	*	0.7235	23.06	21.93	44.99	70.42	-25.43	QP	
4		1.0156	15.32	22.64	37.96	67.49	-29.53	QP	
5		1.3029	12.64	23.22	35.86	65.33	-29.47	QP	
6		1.9386	7.76	24.53	32.29	69.50	-37.21	QP	
7		2.5535	3.62	25.79	29.41	69.50	-40.09	QP	

Mode4 / Polarization: Coplanar



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		0.0350	26.90	20.95	47.85	136.62	-88.77	peak	
2	*	0.0350	24.18	20.95	45.13	116.62	-71.49	AVG	


Mode4 / Polarization: Coplanar



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		0.3596	34.15	21.08	55.23	116.49	-61.26	peak	
2		0.3596	32.22	21.08	53.30	96.49	-43.19	AVG	
3		0.4837	15.16	21.36	36.52	113.91	-77.39	QP	
4		0.8664	12.58	22.29	34.87	68.86	-33.99	QP	
5	*	1.0824	13.26	22.76	36.02	66.94	-30.92	QP	
6		2.1213	6.26	24.91	31.17	69.50	-38.33	QP	
7		2.9463	3.11	26.61	29.72	69.50	-39.78	QP	


S310WCK:

Mode3 / Polarization: Coplanar




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		0.1454	52.87	20.58	73.45	124.37	-50.92	peak	
2	*	0.1454	50.32	20.58	70.90	104.37	-33.47	AVG	

Mode3 / Polarization: Coplanar




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over		
		MHz	Level	Factor	ment			Detector	Comment
			dBuV	dB	dBuV/m	dBuV/m	dB		
1		0.4351	41.08	21.26	62.34	114.83	-52.49	peak	
2		0.4351	38.04	21.26	59.30	94.83	-35.53	AVG	
3	*	0.7236	30.74	21.93	52.67	70.42	-17.75	QP	
4		1.0157	24.08	22.64	46.72	67.49	-20.77	QP	
5		1.3029	17.99	23.22	41.21	65.33	-24.12	QP	
6		1.5935	13.23	23.81	37.04	63.59	-26.55	QP	
7		2.1783	7.56	25.03	32.59	69.50	-36.91	QP	

Mode4 / Polarization: Coplanar



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		0.1300	24.30	20.46	44.76	125.35	-80.59	peak	
2	*	0.1300	24.30	20.46	44.76	105.35	-60.59	AVG	

Mode4 / Polarization: Coplanar



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		0.3596	39.73	21.08	60.81	116.49	-55.68	peak	
2		0.3596	39.73	21.08	60.81	96.49	-35.68	AVG	
3		0.6613	19.20	21.78	40.98	71.20	-30.22	QP	
4	*	1.0824	18.91	22.76	41.67	66.94	-25.27	QP	
5		2.5266	7.59	25.75	33.34	69.50	-36.16	QP	
6		6.4882	17.20	20.68	37.88	69.50	-31.62	QP	
7		25.1876	17.32	20.91	38.23	69.50	-31.27	QP	


6.4 Emissions in frequency bands (30MHz - 1GHz)

Test Requirement:	47 CFR Part 15.209		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241. In the emission table above, the tighter limit applies at the band edges. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector. As shown in § 15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation under paragraph (b) of this section, the peak field strength shall not exceed 2500 millivolts/meter at 3 meters along the antenna azimuth.			
Test Method:	ANSI C63.10-2013 section 6.5		
Procedure:	ANSI C63.10-2013 section 6.5		

6.4.1 E.U.T. Operation:

Operating Environment:					
Temperature:	22.5 °C	Humidity:	43 %	Atmospheric Pressure:	101 kPa
Pre test mode:		Mode1, Mode2, Mode3, Mode4, Mode5			
Final test mode:		All of the listed pre-test mode were tested, only the data of the worst mode (Mode2/ Mode3) is recorded in the report			


6.4.2 Test Setup Diagram:



6.4.3 Test Data:


S310WC:

Mode2 / Polarization: Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		50.2324	26.70	-6.62	20.08	40.00	-19.92	QP	
2		128.1130	42.97	-11.02	31.95	43.50	-11.55	QP	
3		204.2377	29.33	-6.77	22.56	43.50	-20.94	QP	
4		280.0237	44.23	-5.46	38.77	46.00	-7.23	QP	
5	*	322.1886	43.65	-4.43	39.22	46.00	-6.78	QP	
6		392.0951	34.84	-3.57	31.27	46.00	-14.73	QP	


Mode2 / Polarization: Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	40.9881	42.92	-7.53	35.39	40.00	-4.61	QP	
2		128.1130	47.07	-11.02	36.05	43.50	-7.45	QP	
3		211.5265	35.83	-7.73	28.10	43.50	-15.40	QP	
4		298.2681	43.10	-4.68	38.42	46.00	-7.58	QP	
5		327.8873	42.34	-4.22	38.12	46.00	-7.88	QP	
6		422.0577	35.75	-3.26	32.49	46.00	-13.51	QP	


S310WCK:

Mode3 / Polarization: Horizontal



No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1	99.8777	40.63	-12.38	28.25	43.50	-15.25	QP	
2 *	140.3421	44.94	-8.89	36.05	43.50	-7.45	QP	
3	291.0360	41.35	-8.13	33.22	46.00	-12.78	QP	
4	387.9920	34.92	-6.57	28.35	46.00	-17.65	QP	
5	463.9696	33.44	-5.10	28.34	46.00	-17.66	QP	
6	785.0935	28.86	1.53	30.39	46.00	-15.61	QP	

Mode3 / Polarization: Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	48.6719	39.55	-8.99	30.56	40.00	-9.44	QP	
2		99.8777	40.76	-12.38	28.38	43.50	-15.12	QP	
3		142.3243	37.51	-8.72	28.79	43.50	-14.71	QP	
4		195.8220	34.71	-11.56	23.15	43.50	-20.35	QP	
5		290.0172	43.14	-8.14	35.00	46.00	-11.00	QP	
6		463.9696	34.15	-5.10	29.05	46.00	-16.95	QP	

Photographs of the test setup

Refer to Appendix - Test Setup Photos

Photographs of the EUT

Refer to Appendix - EUT Photos

----End of Report----