

April 27, 2005

Timco Engineering, Inc. **Telecommunication Certification Body** 849 NW State Road 45 Newberry, FL 32669

> SUBJECT: **ITRONIX CORPORATION**

> > FCC ID: KBCIX260PNLA580BT Part 15C - Certification **Composite Application (DTS)**

On behalf of Itronix Corporation is an application for Part 15 Subpart C Certification of the Model: IX260PNLA580BT Rugged Laptop PC with internal Senao NL-3054MP 802.11b/g WLAN Mini-PCI Card (Senao International Co., Ltd. FCC ID: NI3-AT30V216, originally granted February 5, 2004) and internal surface-mount antenna installed in the upper right side rear of the LCD display. The DUT also incorporates a co-located internal Cirronet BT2022 Bluetooth transmitter (FCC ID: HSW-BT2022M, originally granted June 28, 2004) with internal surface-mount antenna installed in the upper left side rear of the LCD display. The DUT also incorporates a co-located internal Dual-Band PCS/Cellular CDMA PCMCIA Modern Model: AirCard 580 manufactured by Sierra Wireless, Inc. (FCC ID: PNF-PC3220P, originally granted March 27, 2003), utilizing an external swivel dipole antenna mounted on the upper right side edge of the LCD display, and a vehicle-mount antenna with vehicle cradle. A Part 15C certification application for the Cirronet BT2022 Bluetooth and a Part 24E certification application for the Sierra Wireless AirCard 580 CDMA portions of the DUT under the same FCC ID: KBCIX260PNLA580BT are also submitted simultaneously with this application. The Senao NL-3054MP 802.11b/g WLAN and Sierra Wireless AirCard 580 CDMA Modem do not transmit simultaneously. The Senao NL-3054MP 802.11b/g WLAN can transmit simultaneously with the Cirronet BT2022 Bluetooth. Please refer to the Supplementary EMC test report submitted within this application for the co-located simultaneous transmit measurement data.

Model(s): IX260PNLA580BT

Device Classification: Digital Transmission System (DTS)

Device Description: Rugged Laptop PC

Internal Transmitter: Senao NL-3054MP 802.11b/g WLAN Mini-PCI Card

Co-located Transmitter(s): **Cirronet BT2022 Bluetooth**

Sierra Wireless AirCard 580 Dual-Band CDMA PCMCIA Modem

Mode(s) of Operation: **Direct Sequence Spread Spectrum (DSSS)**

Tx Frequency Range(s): 2412 - 2462 MHz

Max. RF Output Power Tested: 0.110 Watts - Peak Conducted (802.11b)

RangeStar Internal Surface-Mount - Upper Right Side Rear of LCD Display (WLAN) Antenna Type(s):

RangeStar Internal Surface-Mount - Upper Left Side Rear of LCD Display (Bluetooth)

Itronix External Swivel Dipole (Dual-Band CDMA)

Submitted within this application is the TCB Form 731, applicant's confidentiality request, Part 15C EMC measurement report data and test setup photographs (Celltech Labs Inc. and ADT Corp.), Supplementary EMC measurement report data and test setup photographs for co-located simultaneous transmit operation (Celltech Labs Inc.), MPE RF exposure evaluation report data (Celltech Labs Inc.), FCC ID label and location, internal and external device photographs, block diagram (confidential), schematic diagrams (confidential), antenna specifications (confidential), operational description. user manual (provided to the user in the built-in software on the Laptop PC), and Radio-Specific Safety Information (provided to the user in hard copy format).

If you have any questions or comments concerning the above, please contact the undersigned.

Sincerely,

Jonathan Hughes General Manager Celltech Labs Inc. cc: Itronix Corporation