

PCTEST

7185 Oakland Mills Road, Columbia, MD 21046 USA Tel. 410.290.6652 / Fax 410.290.6654 http://www.pctest.com



HEARING AID COMPATIBILITY

Applicant Name:

LG Electronics U.S.A, Inc. 1000 Sylvan Avenue Englewood Cliffs, NJ 07632 United States Date of Testing: 03/16/2020 - 03/26/2020 Test Site/Location: PCTEST, Columbia, MD, USA Test Report Serial No.: 1M2003020032-03.ZNF

Date of Issue: 04/02/2020

FCC ID: ZNFK400AM

APPLICANT: LG ELECTRONICS U.S.A, INC.

Scope of Test: Audio Band Magnetic Testing (T-Coil)

Application Type: Certification
FCC Rule Part(s): CFR §20.19(b)
HAC Standard: ANSI C63.19-2011

285076 D01 HAC Guidance v05

285076 D02 T-Coil testing for CMRS IP v03

DUT Type: Portable Handset **Model:** LM-K400AKR

Additional Model(s): LMK400AKR, K400AKR, LM-K400AM, LMK400AM, K400AM

Test Device Serial No.: Pre-Production Sample [S/N: 10575]

C63.19-2011 HAC Category: T3 (SIGNAL TO NOISE CATEGORY)

This wireless portable device has been shown to be hearing-aid compatible under the above rated category, specified in ANSI/IEEE Std. C63.19-2011 and has been tested in accordance with the specified measurement procedures. Test results reported herein relate only to the item(s) tested. Hearing-Aid Compatibility is based on the assumption that all production units will be designed electrically identical to the device tested in this report. North American Bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.







FCC ID: ZNFK400AM	PCTEST Thou to be part of the receiver	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 1 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		rage 101/1

TABLE OF CONTENTS

1.	INTRODUCTION	3
2.	DUT DESCRIPTION	4
3.	ANSI C63.19-2011 PERFORMANCE CATEGORIES	5
4.	METHOD OF MEASUREMENT	7
5.	VOLTE TEST SYSTEM SETUP AND DUT CONFIGURATION	17
6.	VOWIFI TEST SYSTEM SETUP AND DUT CONFIGURATION	19
7.	OTT VOIP TEST SYSTEM AND DUT CONFIGURATION	22
8.	FCC 3G MEASUREMENTS	25
9.	T-COIL TEST SUMMARY	26
10.	MEASUREMENT UNCERTAINTY	34
11.	EQUIPMENT LIST	35
12.	TEST DATA	36
13.	CALIBRATION CERTIFICATES	56
14.	CONCLUSION	66
15.	REFERENCES	67
16.	TEST SETUP PHOTOGRAPHS	69

FCC ID: ZNFK400AM	PCTEST Thou to be post of 6 sements	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo 2 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Page 2 of 71

1. INTRODUCTION

On July 10, 2003, the Federal Communications Commission (FCC) adopted new rules requiring wireless manufacturers and service providers to provide digital wireless phones that are compatible with hearing aids. The FCC has modified the exemption for wireless phones under the Hearing Aid Compatibility Act of 1998 (HAC Act) in WT Docket 01-309 RM-8658¹ to extend the benefits of wireless telecommunications to individuals with hearing disabilities. These benefits encompass business, social and emergency communications, which increase the value of the wireless network for everyone. An estimated more than 10% of the population in the United States show signs of hearing impairment and of that fraction, almost 80% use hearing aids. Approximately 500 million people worldwide and 30 million people in the United States suffer from hearing loss.

Compatibility Tests Involved:

The standard calls for wireless communications devices to be measured for:

- RF Electric-field emissions
- T-coil mode, magnetic-signal strength in the audio band
- T-coil mode, magnetic-signal frequency response through the audio band
- T-coil mode, magnetic-signal and noise articulation index

The hearing aid must be measured for:

- RF immunity in microphone mode
- RF immunity in T-coil mode

In the following tests and results, this report includes the evaluation for a wireless communications device.



Figure 1-1 Hearing Aid in-vitu

¹ FCC Rule & Order, WT Docket 01-309 RM-8658

FCC ID: ZNFK400AM	PCTEST'	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 3 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Page 3 01 7 1

2. **DUT DESCRIPTION**



FCC ID: ZNFK400AM

Applicant: LG Electronics U.S.A, Inc.

1000 Sylvan Avenue

Englewood Cliffs, NJ 07632

United States

Model: LM-K400AKR

Additional Model(s): LMK400AKR, K400AKR, LM-K400AM, LMK400AM, K400AM

Serial Number: 10575 HW Version: Rev.1.0 SW Version: K400AM07c Antenna: Internal Antenna Portable Handset DUT Type:

Table 2-1 7NFK400AM HAC Air Interfaces

			Z1V	FK400AM HAC AIR INTERTAC	.03	
Air-Interface	Band (MHz)	Type Transport	HAC Tested	Simultaneous But Not Tested	Name of Voice Service	Audio Codec Evaluated
	850	vo	Yes	Yes: WIFI or BT	CMRS Voice ¹	EFR
GSM	1900			163. 1411 6. 21	civillo volice	E. II.
	GPRS/EDGE	VD	Yes	Yes: WIFI or BT	Google Duo²	OPUS
	850					
UMTS	1700	VD	Yes	Yes: WIFI or BT	Yes: WIFI or BT CMRS Voice ¹ NB	NB AMR
UIVITS	1900					
	HSPA	VD	Yes	Yes: WIFI or BT	Google Duo²	OPUS
	700 (B12)				Ves: WIFLor RT Vol TE1 Google Duo2	Volte: NB AMR, WB AMR
	790 (B14)					
	850 (B5)					
LTE (FDD)	1700 (B4)	VD	Yes	Yes: WIFI or BT VoLTE ¹ , Google Duo ²		
•	1700 (B66)	1				Google Duo: OPUS
•	1900 (B2)	1				
	2300 (B30)					
WIFI	2450	VD	Yes	Yes: GSM, UMTS, or LTE	VoWIFI², Google Duo²	VoWIFI: NB AMR, WB AMR Google Duo: OPUS
BT	2450	DT	No	Yes: GSM, UMTS, or LTE	N/A	N/A
ype Transport		_	Notes:	avial in accordance with 7.4.2.4 of ANEL CC2.40.20	11 and luk 2012 CC2 Val TE Interpret	otion
/O = Voice Only OT = Digital Dat	, a - Not intended for	Voice Services		evel in accordance with 7.4.2.1 of ANSI C63.19-20 evel is -20dBm0 in accordance with FCC KDB 2850	· · ·	ation.

VD = CMRS and/or IP Voice over Data Transport

I. LTE Band Selection

This device supports the following pair of LTE bands with similar frequencies: LTE B4 & B66. This pair of LTE bands has the same target power and shares the same transmission path. Since the supported frequency span for the smaller LTE band is completely covered by the larger LTE band, only the larger LTE band (LTE B66) was evaluated for hearing-aid compliance.

FCC ID: ZNFK400AM	PCTEST hood to be part of \$ servers	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 4 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		rage 4 01 / 1

© 2020 PCTEST

3. ANSI C63.19-2011 PERFORMANCE CATEGORIES

I. MAGNETIC COUPLING

Axial and Radial Field Intensity

All orientations of the magnetic field, in the axial and radial position along the measurement plane shall be \geq -18 dB(A/m) at 1 kHz in a 1/3 octave band filter per §8.3.1.

Frequency Response

The frequency response of the axial component of the magnetic field shall follow the response curve specified in EIA RS-504-1983, over the frequency range 300 Hz – 3000 Hz per §8.3.2.





Figure 3-1
Magnetic field frequency response for Wireless Devices with an axial field ≤-15 dB(A/m) at 1 kHz



Magnetic Field frequency response for wireless devices with an axial field that exceeds
-15 dB(A/m) at 1 kHz

FCC ID: ZNFK400AM	PCTEST Hood to be part of the second	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 5 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Page 5 01 / 1

Signal Quality

The table below provides the signal quality requirement for the intended audio magnetic signal from a wireless device. Only the RF immunity of the hearing aid is measured in T-coil mode. It is assumed that a hearing aid can have no immunity to an interference signal in the audio band, which is the intended reception band for this mode. The only criterion that can be measured is the RF immunity in T-coil mode. This is measured using the same procedure as the audio coupling mode at the same levels.

The signal quality of the axial and radial components of the magnetic field was used to determine the T-coil mode category.

Category	Telephone RF Parameters			
Category	Wireless Device Signal Quality [(Signal + Noise)-to-noise ratio in dB]			
T1	0 to 10 dB			
T2	10 to 20 dB			
Т3	20 to 30 dB			
T4	> 30 dB			
Table 3-1 Magnetic Coupling Parameters				

Note: The FCC limit for SNNR is 20dB and the test data margins will indicate a margin from the FCC limit for compliance.

FCC ID: ZNFK400AM	PCTEST* Houd to be post of § secure	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Daga 6 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Page 6 of 71

METHOD OF MEASUREMENT

Test Setup I.

The equipment was connected as shown in an acoustic/RF hemi-anechoic chamber:




Figure 4-1 Validation Setup with Helmholtz Coil




Figure 4-2 T-Coil Test Setup

FCC ID: ZNFK400AM	PCTEST	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 7 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		rage / 01 / 1

II. Scanning Mechanism

Manufacturer: TEM

Accuracy: ± 0.83 cm/meter

Minimum Step Size: 0.1 mm

Maximum speed 6.1 cm/sec

Line Voltage: 115 VAC

Line Frequency: 60 Hz

Material Composite: Delrin (Acetal)

Data Control: Parallel Port

Dynamic Range (X-Y-Z): 45 x 31.75 x 47 cm

Dimensions: 36" x 25" x 38" Operating Area: 36" x 49" x 55"

Reflections: < -20 dB (in anechoic chamber)




Figure 4-3 RF Near-Field Scanner

III. ITU-T P.50 Artificial Voice

Manufacturer: ITU-T

Active Frequency Range: 100 Hz – 8 kHz

Stimulus Type: Male and Female, no spaces

Single Sample Duration: 20.96 seconds

Activity Level: 100%




Figure 4-4
Spectral Characteristic of full P.50





Figure 4-5
Temporal Characteristic of full P.50

FCC ID: ZNFK400AM	PCTEST hours to be port of the formatter	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo 9 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Page 8 of 71



ABM2 Measurement Block Diagram:



Figure 4-6 Magnetic Measurement Processing Steps

IV. **Test Procedure**

- 1. Ambient Noise Check per C63.19 §7.3.1
 - a. Ambient interference was monitored using a Real-Time Analyzer between 100-10,000 Hz with 1/3 octave filtering.
 - b. "A-weighting" and Half-Band Integration was applied to the measurements.
 - Since this measurement was measured in the same method as ABM2 measurements, this level was verified to be more than 10 dB below the lowest measurement signal (which is the highest ABM2 measurement for a T4 WD). Therefore the maximum noise level for a T4 WD with an ABM1 = -18 dBA/m is:

- 2. Measurement System Validation (See Figure 4-1)
 - The measurement system including the probe, pre-amplifier and acquisition system were validated as an entire system to ensure the reliability of test measurements.
 - b. ABM1 Validation The magnetic field at the center of the Helmholtz coil is given by the equation (per C63.19 Annex D.10.1):

$$H_c = \frac{NI}{r\sqrt{1.25^3}} = \frac{N(\frac{V}{R})}{r\sqrt{1.25^3}}$$

Where H_c = magnetic field strength in amperes per meter N = number of turns per coil

For the Helmholtz Coil (SN: 925), N=20; r=0.08m; R=10.2Ω and using V=18mV:

$$H_{c,925} = \frac{20 \cdot (\frac{0.018}{10.2})}{0.08 \cdot \sqrt{1.25^3}} = 0.316A/m \approx -10dB(A/m)$$


For the Helmholtz Coil (SN: SBI 1052), N=20; r=0.13m; R=10.193 Ω and using V=29mV:

$$H_{c,SBI~1052} = \frac{20 \cdot (\frac{0.029}{10.193})}{0.13 \cdot \sqrt{1.25^3}} = 0.316A/m \approx -10dB(A/m)$$

FCC ID: ZNFK400AM	PCTEST hood to be part of \$ servers	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 9 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		rage 9 01 / 1

Therefore a pure tone of 1kHz was applied into the coils such that 18mV was observed across the resistor in Helmholtz coil SN: 925 and 29mV was observed across the resistor in Helmholtz coil SN: SBI 1052. The voltmeter used for measurement was verified to be capable of measurements in the audio band range. This theoretically generates an expected field of -10 dB(A/m) in the center of the Helmholtz coil which was used to validate the probe measurement at -10dB(A/m). This was verified to be within ± 0.5 dB of the -10dB(A/m) value (see Page 32).

c. Frequency Response Validation The frequency response through the Helmholtz Coil was verified to be within 0.5 dB relative to 1kHz, between 300 – 3000 Hz using the P.50 signal as shown below:



d. ABM2 Measurement Validation WD noise measurements are filtered with A-weighting and Half-Band Integration over a frequency range of 100Hz - 10kHz to process ABM2 measurements. Below is the verification of the system processing A-weighting and Half-Band integration between system input to output within 0.5 dB of the theoretical result:

> Table 4-1 **ABM2 Frequency Response Validation**

	HBI, A -	HBI, A -	
f (Hz)	Measured	Theoretical	dB Var.
	(dB re 1kHz)	(dB re 1kHz)	
100	-16.180	-16.170	-0.010
125	-13.257	-13.250	-0.007
160	-10.347	-10.340	-0.007
200	-8.017	-8.010	-0.007
250	-5.925	-5.920	-0.005
315	-4.045	-4.040	-0.005
400	-2.405	-2.400	-0.005
500	-1.212	-1.210	-0.002
630	-0.349	-0.350	0.001
800	0.071	0.070	0.001
1000	0.000	0.000	0.000
1250	-0.503	-0.500	-0.003
1600	-1.513	-1.510	-0.003
2000	-2.778	-2.780	0.002
2500	-4.316	-4.320	0.004
3150	-6.166	-6.170	0.004
4000	-8.322	-8.330	0.008
5000	-10.573	-10.590	0.017
6300	-13.178	-13.200	0.022
8000	-16.241	-16.270	0.029
10000	-19.495	-19.520	0.025

FCC ID: ZNFK400AM	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 10 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		rage 10 01 / 1







Figure 4-8
ABM2 Frequency Response Validation

The ABM2 result is a power sum from 100Hz to 10kHz with half-band integration and A-weighting. To verify the power sum measurement, a power sum over the full band was measured and verified to track with the source level (See Figure 4-9). Therefore the setup in this step was used to verify the power sum post-processing for ABM2 measurements. See below block diagram:



The power summed output results for a known input were compared to the multi-meter results to verify any deviation in the post-processing implemented with the power-sum.

Table 4-2
ABM2 Power Sum Validation

WN Input (dBV)	Power Sum (dBV)	Multimeter-Full (dBV)	Dev (dB)
-60	-60.36	-60.2	0.16
-50	-50.19	-50.13	0.06
-40	-40.14	-40.03	0.11
-30	-30.13	-30.01	0.12
-20	-20.12	-20	0.12
-10	-10.14	-10	0.14

FCC ID: ZNFK400AM	FOOTEST. Float to be part of the senses	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dog 11 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Page 11 of 71
© 2020 PCTEST		•		REV 3.5.M

© 2020 PCTEST REV 3.5.M 3/2/2020





Figure 4-10 **ABM2 Power Sum Validation**

- 3. Measurement Test Setup
 - a. Fine scan above the WD (TEM)
 - i. A multitone signal was applied to the handset such that the phone acoustic output was stable within 1dB over the probe settling time and with the acoustic output level at the C63.19 specified levels (below). The measurement step size was in 2 mm increments at a distance of 10 mm between the surface of the wireless device as shown below (note that in Figure 4-12, the grid is not to scale but merely a graphical representation of the coordinate system in use):



- ii. After scanning, the planar field maximum point was determined. The position of the probe was moved to this location to setup the test using the SoundCheck system.
- iii. These steps were repeated for all T-coil orientations (axial and radial) per Figure 4-14 after a T-coil orientation was fully measured with the SoundCheck system.
- b. Speech Signal Setup to Base Station Simulator
 - i. C63.19 Table 7-1 states audio reference input levels for various technologies:

Standard	Technology	Input Level (dBm0)
TIA/EIA/IS-2000	CDMA	-18
J-STD-007	GSM (217)	-16
T1/T1P1/3GPP	UMTS (WCDMA)	-16
iDEN TM	TDMA (22 and 11 Hz)	-18

FCC ID: ZNFK400AM	PCTEST Hood to be part of the second	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 12 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Page 12 01 / 1

- ii. See Section 5 and 6 for more information regarding CMW500 audio level settings for Voice Over LTE (VoLTE), and Voice Over WIFI (VoWIFI) testing.
- iii. See Section 7 for more information regarding audio level settings for Over-The-Top (OTT) Voice Over IP (VoIP) Testing.
- c. Real-Time Analyzer (RTA)
 - i. The Real-Time Analyzer was configured to analyze measurements using 1/3 Octave band weighted filtering.
- d. WD Radio Configuration Selection
 - i. The device was chosen to be tested in the worst-case ABM2 condition (See Section 8 for more information regarding worst-case configurations for UMTS. LTE configuration information can be found in Section 5 and 7. WIFI configuration information can be found in Section 6 and 7.)
 - ii. Supported GSM vocoders were investigated for the worst-case ABM2 condition. GSM-EFR was deemed the worst-case condition for the GSM air interface.
- 4. Signal Quality Data Analysis
 - a. Narrow-band Magnetic Intensity
 - i. The standard specifies a 1kHz 1/3 octave band minimum field intensity for a sine tone. The ABM1 measurements were evaluated at 1kHz with 1/3 octave band filtering over an averaged period of 10 seconds.
 - b. Frequency Response
 - i. The appropriate frequency response curve was measured to curves in Figure 3-1 or Figure 3-2 between 300 3000 Hz using digital linear averaging (limit lines chosen according to measurement found in step 4a). A linear average over 3x the length of the artificial voice signal (3x sampling) was performed. A 10 second delay was configured in the measurement process of the stimulus to ensure handset vocoder latency effects and echo cancellation devices (if any) were appropriately stabilized during measurements.
 - ii. The appropriate post-processing was applied according to the system processing chain illustrated in Figure 4-7. All R10 frequencies were plotted with respect to 0dB at 1kHz value and aligned with respect to the EIA-504 mask.
 - iii. The margin is represented by the closest measured data point on the curve to the EIA-504 limit lines, in dB.
 - c. Signal Quality Index
 - i. Ensuring the WD was at maximum RF power, maximum volume, backlight off, display on, maximum contrast setting, keypad lights on (when possible) with no audio signal through the vocoder, the WD was measured over at least 100 Hz 10,000 Hz, maximized over 5 seconds with a 50ms sample time for the ABM2 measurement (5 second time period is used in noise measurements under standards such as IEEE 269, etc.).
 - ii. After applying half-band integration and A-weighting to the result, a power sum was applied over each 1/3 octave bandwidth frequency for an ABM2 value.
 - iii. This result was subtracted from the ABM1 result in step a, to obtain the Signal Quality.

FCC ID: ZNFK400AM	PCTEST	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 13 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		rage 13 01 / 1

V. **Test Setup**




Figure 4-13 **Audio Magnetic Field Test Setup**

Environmental conditions such as temperature and relative humidity are monitored to ensure there are no impacts on system specifications. Proper voltage and power line frequency conditions are maintained with three phase power sources. Environmental noise and reflections are monitored through system checks.

VI. **Deviation from C63.19 Test Procedure**

Non-conducted RF connection due to inaccessible RF ports.

VII. Air Interface Technologies Tested

All air interfaces which support voice capabilities over a managed CMRS or pre-installed OTT VoIP applications were tested for T-coil unless otherwise noted. See Table 2-1 for more details regarding which modes were tested.

FCC ID: ZNFK400AM	PCTEST: Houd to be port of @ secured	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 14 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Page 14 01 7 1

VIII. Wireless Device Channels and Frequencies

1. 2G/3G Modes

The frequencies listed in the table below are those that lie in the center of the bands used for cellular telephony. Low, middle and high channels were tested in each band for FCC compliance evaluation to ensure the maximum emission is captured across the entire band. Only middle channels were evaluated for data modes.

Table 4-3
Center Channels and Frequencies

Ochter Orianneis and Frequencies					
Test frequencies & associated channels					
Channel	Frequency (MHz)				
Cellular 850					
190 (GSM)	836.60				
4183 (UMTS)	836.60				
AWS 1750	AWS 1750				
1412 (UMTS)	1730.40				
PCS 1900					
661 (GSM)	1880				
9400 (UMTS)	1880				

2. 4G (LTE) Modes

The middle channel for every band and bandwidth combination was tested for each probe orientation. The band and bandwidth combination from each probe orientation resulting in the worst-case SNNR was additionally tested using low and high channels for that band and bandwidth combination. The middle channel and supported bandwidths from the worst-case band according to Table 7-5 was additionally evaluated with OTT VoIP for each probe orientation. See Tables 9-4 to 9-9 as well as 9-13 for LTE bandwidths and channels.

3. WIFI

The middle channel for each IEEE 802.11 standard was tested for each probe orientation. The 2.4GHz IEEE 802.11 standard from each probe orientation resulting in the worst-case SNNR was additionally tested using low and high channels. See Tables 9-10 as well as 9-14 for WIFI standards and channels.

FCC ID: ZNFK400AM	PCTEST* Houd to be post of § secure	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 15 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Page 15 01 7 1

IX. **Test Flow**

The flow diagram below was followed (From C63.19):




Figure 4-14 C63.19 T-Coil Signal Test Process

FCC ID: ZNFK400AM	PCTEST	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 16 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		rage 10 01 / 1

© 2020 PCTEST **REV 3.5.M**

5. VOLTE TEST SYSTEM SETUP AND DUT CONFIGURATION

I. Test System Setup for VoLTE over IMS T-coil Testing

1. Equipment Setup

The general test setup used for VoLTE over IMS is shown below. The callbox used when performing VoLTE over IMS T-coil measurements is a CMW500. The Data Application Unit (DAU) of the CMW500 was used to simulate the IP Multimedia Subsystem (IMS) server.




Figure 5-1
Test Setup for VoLTE over IMS T-Coil Measurements

2. Audio Level Settings

According to the July 2012 interpretations by the C63 Committee regarding the appropriate audio levels to be used for VoLTE over IMS T-coil testing, -16dBm0 shall be used for the normal speech input level*. The CMW500 base station simulator was manually configured to ensure that the settings for speech input and full scale levels resulted in the -16dBm0 speech input level to the DUT for the VoLTE over IMS connection.

FCC ID: ZNFK400AM	PCTEST:	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 17 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Page 17 0171

© 2020 PCTEST REV 3.5.M

^{*} http://c63.org/documents/misc/posting/new_interpretations.htm

II. **DUT Configuration for VoLTE over IMS T-coil Testing**

1. Radio Configuration

An investigation was performed to determine the modulation and RB configuration to be used for testing. The effects of modulation and RB configuration were found to be independent of band and bandwidth; therefore, only one band and bandwidth were used for this investigation. 16QAM, 1RB, 0RB offset was used for the testing as the worst-case configuration for the handset. See below table for SNNR comparison between different radio configurations:

> Table 5-1 VoLTE over IMS SNNR by Radio Configuration

	TOTAL OVER INIC CIVILLED TRACES COMINGUISME								
Band	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
30	2310.0	27710	10	QPSK	1	0	4.93	-38.55	43.48
30	2310.0	27710	10	QPSK	1	25	4.92	-35.85	40.77
30	2310.0	27710	10	QPSK	1	49	4.87	-36.88	41.75
30	2310.0	27710	10	QPSK	25	0	4.88	-38.80	43.68
30	2310.0	27710	10	QPSK	25	12	4.92	-39.04	43.96
30	2310.0	27710	10	QPSK	25	25	4.87	-37.48	42.35
30	2310.0	27710	10	QPSK	50	0	4.87	-37.24	42.11
30	2310.0	27710	10	16QAM	1	0	4.94	-30.52	35.46
30	2310.0	27710	10	16QAM	1	25	4.86	-31.91	36.77
30	2310.0	27710	10	16QAM	1	49	4.87	-32.09	36.96
30	2310.0	27710	10	16QAM	25	0	4.89	-37.53	42.42
30	2310.0	27710	10	16QAM	25	12	4.93	-37.10	42.03
30	2310.0	27710	10	16QAM	25	25	4.93	-37.28	42.21
30	2310.0	27710	10	16QAM	50	0	4.88	-37.25	42.13


2. Codec Configuration

An investigation was performed to determine the audio codec configuration to be used for testing. The effects of codec configuration were found to be independent of radio configuration; therefore, only one radio configuration was used for this investigation. The NB AMR 12.2kbps setting was used for the audio codec on the CMW500 for VoLTE over IMS T-coil testing. See below table for comparisons between different codecs and codec data rates:

> Table 5-2 **AMR Codec Investigation – VoLTE over IMS**

Codec Setting:	WB AMR 23.85kbps	WB AMR 6.60kbps	NB AMR 12.2kbps	NB AMR 4.75kbps	Orientation	Band / BW	Channel
ABM1 (dBA/m)	11.85	12.12	4.82	4.87			27710
ABM2 (dBA/m)	-30.85	-30.67	-30.73	-31.07	Asial	xial Band 30 10MHz	
Frequency Response	Pass	Pass	Pass	Pass	Axiai		
S+N/N (dB)	42.70	42.79	35.55	35.94			

- Mute on; Backlight off; Max Volume; Max Contrast
- TPC = "Max Power"



Audio Band Magnetic Curve Measurement Block Diagram

FCC ID: ZNFK400AM	PCTEST Proof to be part of \$ memory	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 18 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		rage 10 01 / 1

6. VOWIFI TEST SYSTEM SETUP AND DUT CONFIGURATION

I. Test System Setup for VoWIFI over IMS T-coil Testing

1. Equipment Setup

The general test setup used for VoWIFI over IMS, or CMRS WIFI Calling, is shown below. The callbox used when performing VoWIFI over IMS T-coil measurements is a CMW500. The Data Application Unit (DAU) of the CMW500 was used to simulate the IP Multimedia Subsystem (IMS) server.




Figure 6-1
Test Setup for VoWIFI over IMS T-Coil Measurements

2. Audio Level Settings

According to KDB 285076 D02 released by the FCC OET regarding the appropriate audio levels to be used for VoWIFI over IMS T-Coil testing, -20dBm0 shall be used for the normal speech input level². The CMW500 base station simulator was manually configured to ensure that the settings for speech input and full scale levels resulted in the -20dBm0 speech input level to the DUT for the VoWIFI over IMS connection.

² FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v03," September 13, 2017

Too office of Engineering and reciniology RBB, 2000/0 Bb2 1-0611 resting for office it voo, deptember 19, 2017						
FCC ID: ZNFK400AM	PCTEST:	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager		
Filename:	Test Dates:	DUT Type:		Page 19 of 71		
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		rage 19 01 / 1		

© 2020 PCTEST REV 3.5.M

II. DUT Configuration for VoWIFI over IMS T-coil Testing

1. Radio Configuration

An investigation was performed on all applicable data rates and modulations to determine the radio configuration to be used for testing. See tables below for SNNR comparison between radio configurations in each IEEE 802.11 standard:

Table 6-1
IEEE 802.11b SNNR by Radio Configuration

Mode	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
IEEE 802.11b	6	DSSS	1	2.18	-36.54	38.72
IEEE 802.11b	6	DSSS	2	2.19	-36.65	38.84
IEEE 802.11b	6	CCK	5.5	2.20	-36.97	39.17
IEEE 802.11b	6	CCK	11	2.20	-36.86	39.06

Table 6-2
IEEE 802.11g SNNR by Radio Configuration

Mode	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
IEEE 802.11g	6	BPSK	6	2.21	-40.06	42.27
IEEE 802.11g	6	BPSK	9	2.19	-39.86	42.05
IEEE 802.11g	6	QPSK	12	2.19	-40.80	42.99
IEEE 802.11g	6	QPSK	18	2.20	-40.90	43.10
IEEE 802.11g	6	16QAM	24	2.21	-41.42	43.63
IEEE 802.11g	6	16QAM	36	2.20	-41.17	43.37
IEEE 802.11g	6	64QAM	48	2.20	-41.63	43.83
IEEE 802.11g	6	64QAM	54	2.20	-42.09	44.29

Table 6-3
IEEE 802.11n SNNR by Radio Configuration

in the state of th								
Mode	Channel	Modulation	MCS Index	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]		
IEEE 802.11n	6	BPSK	0	2.19	-38.51	40.70		
IEEE 802.11n	6	QPSK	1	2.19	-38.05	40.24		
IEEE 802.11n	6	QPSK	2	2.19	-38.07	40.26		
IEEE 802.11n	6	16QAM	3	2.04	-38.69	40.73		
IEEE 802.11n	6	16QAM	4	2.35	-38.40	40.75		
IEEE 802.11n	6	64QAM	5	2.18	-38.68	40.86		
IEEE 802.11n	6	64QAM	6	2.22	-38.92	41.14		
IEEE 802.11n	6	64QAM	7	2.20	-38.89	41.09		

FCC ID: ZNFK400AM	PCTEST	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 20 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		rage 20 01 / 1

2. Codec Configuration

An investigation was performed to determine the audio codec configuration to be used for testing. The effects of codec configuration were found to be independent of radio configuration; therefore, only one radio configuration was used for this investigation. The NB AMR 12.2kbps setting was used for the audio codec on the CMW500 for VoWIFI over IMS T-coil testing. See below table for comparisons between different codecs and codec data rates:

> Table 6-4 **AMR Codec Investigation – VoWIFI over IMS**

Codec Setting:	WB AMR 23.85kbps	WB AMR 6.60kbps	NB AMR 12.2kbps	NB AMR 4.75kbps	Orientation	Band	Standard	Channel	
ABM1 (dBA/m)	11.90	11.76	2.18	2.18					
ABM2 (dBA/m)	-36.71	-36.53	-36.65	-36.70	Axial	2.4GHz	IEEE 802.11b		
Frequency Response	Pass	Pass	Pass	Pass	AXII 2.4GHZ	2.4012 122 002.115	6		
S+N/N (dB)	48.61	48.29	38.83	38.88					

Mute on; Backlight off; Max Volume; Max Contrast




Figure 6-2 **Audio Band Magnetic Curve Measurement Block Diagram**

FCC ID: ZNFK400AM	PCTEST:	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo 21 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Page 21 of 71

7. OTT VOIP TEST SYSTEM AND DUT CONFIGURATION

I. Test System Setup for OTT VoIP T-Coil Testing

1. OTT VoIP Application

Google Duo is a pre-installed application on the DUT which allows for VoIP calls in a held-to-ear scenario. Duo uses the OPUS audio codec and supports a bitrate range of 6kb/s to 75kb/s. All air interfaces capable of a data connection were evaluated with Google Duo.

2. Equipment Setup

A CMW500 callbox was used to perform OTT VoIP T-coil measurements. The Data Application Unit (DAU) of the CMW500 was connected to the internet and allowed for an IP data connection on the DUT. An auxiliary VoIP unit was used to initiate an OTT VoIP call to the DUT. The auxiliary VoIP unit allowed for the configuration and monitoring of the OTT VoIP codec bitrate during a call. Both high and low bitrate settings were evaluated in to determine the worst-case configuration.

3. Audio Level Settings

According to KDB 285076 D02, the average speech level of -20dBm0 shall be used for protocols not specifically listed in Table 7.1 of ANSI C63.19-2011 or the ANSI C63.19-2011 VoLTE interpretation³. The auxiliary VoIP unit allowed for monitoring the signal input level to ensure that the settings for speech input and full scale levels resulted in the -20dBm0 speech input level to the DUT for the OTT VoIP call.

Note: The green highlighted text is approved by FCC under the TCB PAG Re-Use Policy 388624 D01 IV. D. for T-Coil Testing for WI-FI calling and Google Duo.

II. DUT Configuration for OTT VoIP T-Coil Testing

1. Codec Configuration

An investigation was performed for each applicable data mode to determine the audio codec configuration to be used for testing. The effects of codec configuration were found to be independent of radio configuration; therefore, only one radio configuration for each applicable data mode was used for these investigations. The 75kbps codec setting was used for the audio codec on the auxiliary VoIP unit for OTT VoIP T-Coil testing. See the following tables for comparisons between codec data rates on all applicable data modes:

³ FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v03," September 13, 2017

T CC Office of Engineer	ing and recimology RDB, 20	03070 D02 1-Coll resultg for Civilto II	voo, oeptember 15, 2	2017
FCC ID: ZNFK400AM	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 22 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Fage 22 01 / 1

Table 7-1 Codec Investigation - OTT VoIP (EDGE)

O O O O O	OII (EDGE	.,		
Codec Setting:	75kbps	6kbps	Orientation	Channel
ABM1 (dBA/m)	9.77	9.65		
ABM2 (dBA/m)	-14.31	-14.49	Asial	661
Frequency Response	Pass	Pass	- Axial	
S+N/N (dB)	24.08	24.14		

Table 7-2 Codec Investigation - OTT VolP (HSPA)

Codec Setting:	75kbps	6kbps	Orientation	Channel								
ABM1 (dBA/m)	9.73	9.58										
ABM2 (dBA/m)	-38.54	-38.78	Avial	9400								
Frequency Response	Pass	Pass	Axial									
S+N/N (dB)	48.27	48.36										

Table 7-3 Codec Investigation - OTT VoIP (LTE)

Codec investigation – OTT voir (LTL)											
Codec Setting:	75kbps	6kbps	Orientation	Band / BW	Channel						
ABM1 (dBA/m)	9.52	9.64									
ABM2 (dBA/m)	-31.41	-31.59	Axial	Band 30	27710						
Frequency Response	Pass	Pass	Axiai	10MHz							
S+N/N (dB)	40.93	41.23									

Table 7-4 Codec Investigation - OTT VoIP (WIFI)

Codec Setting:	75kbps	6kbps	Orientation	Band	Standard	Channel	
Codec Setting.	7360095	υκυμο	Orientation	Danu	Standard	Onamici	
ABM1 (dBA/m)	9.89	9.77			IEEE 802.11b	6	
ABM2 (dBA/m)	-33.77	-33.99	Axial	0.401 -			
Frequency Response	Pass	Pass	Axiai	2.4GHz			
S+N/N (dB)	43.66	43.76					

- Mute on; Backlight off; Max Volume; Max Contrast
- Radio Configurations can be found in Section 9.II.F




Figure 7-1 **Audio Band Magnetic Curve Measurement Block Diagram**

FCC ID: ZNFK400AM	PCTEST hood to be part of \$ servers	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 23 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		rage 23 01 7 1

2. Radio Configuration for OTT VoIP (LTE)

An investigation was performed to determine the worst-case LTE FDD band to be used for OTT VoIP testing. LTE FDD Band 2 was used for the testing as the worst-case configuration for the handset. See below table for SNNR comparison between different LTE bands:

Table 7-5
OTT VoIP (LTE FDD) SNNR by LTE Band

Band	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
12	707.5	23095	10	16QAM	1	0	9.63	-31.95	41.58
14	793.0	23330	10	16QAM	1	0	9.61	-32.04	41.65
5	836.5	20525	10	16QAM	1	0	9.66	-30.04	39.70
66	1745.0	132322	20	16QAM	1	0	9.65	-29.43	39.08
2	1880.0	18900	20	16QAM	1	0	9.61	-29.15	38.76
30	2310.0	27710	10	16QAM	1	0	9.61	-31.06	40.67

FCC ID: ZNFK400AM	PCTEST:	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 24 of 74
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Page 24 of 71

FCC 3G MEASUREMENTS 8.

I. **UMTS Test Configurations**

AMR at 12.2kbps, 13.6kbps SRB (thick, purple data curve) was used for the testing as the worst-case configuration for the handset. See below plot for ABM noise comparison between vocoder rates:




Figure 8-1 **UMTS Audio Band Magnetic Noise**

Table 8-1 **Codec Investigation - UMTS**

Codec Setting:	AMR 12.2kbps	AMR 7.95kbps	AMR 4.75kbps	Orientation	Channel
ABM1 (dBA/m)	5.73	5.76	5.48		9400
ABM2 (dBA/m)	-41.71	-43.35	-43.32	Axial	
Frequency Response	Pass	Pass	Pass	Axiai	
S+N/N (dB)	47.44	49.11	48.80		

- Mute on; Backlight off; Max Volume; Max Contrast
- TPC="All 1s"



Audio Band Magnetic Curve Measurement Block Diagram

FCC ID: ZNFK400AM	PCTEST Proof to be part of \$ memory	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 25 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Page 25 01 / 1

© 2020 PCTEST **REV 3.5.M**

T-COIL TEST SUMMARY

Table 9-1 **Consolidated Tabled Results**

			00113011	dated 1	abieu Ke	Juito				
			esponse rgin	•	Magnetic Intensity Verdict		SNNR dict	Margin from FCC Limit	C63.19-2011	
C63 10) Section	8.3	3.2	8.3	3.1	8.3	3.4	(dB)	Rating	
C63. 18	Section	Axial	Radial	Axial	Radial	Axial	Radial			
GSM	Cellular	PASS	NA	PASS	PASS	PASS	PASS	-5.81	Т3	
COM	PCS	PASS	NA	PASS	PASS	PASS	PASS	0.01	10	
EDGE	Cellular	PASS	NA	PASS	PASS	PASS	PASS	-3.17	Т3	
(OTT VoIP)	PCS	PASS	NA	PASS	PASS	PASS	PASS	-5.17	13	
	Cellular	PASS	NA	PASS	PASS	PASS	PASS			
UMTS	AWS	PASS	NA	PASS	PASS	PASS	PASS	-19.34	T4	
	PCS	PASS	NA	PASS	PASS	PASS	PASS			
	Cellular	PASS	NA	PASS	PASS	PASS	PASS			
HSPA (OTT VoIP)	AWS	PASS	NA	PASS	PASS	PASS	PASS	-19.04	T4	
(011110111)	PCS	PASS	NA	PASS	PASS	PASS	PASS			
	B12	PASS	NA	PASS	PASS	PASS	PASS			
	B14	PASS	NA	PASS	PASS	PASS	PASS			
LTE FDD	B5	PASS	NA	PASS	PASS	PASS	PASS	-9.97	Т3	
LIE FUU	B66	PASS	NA	PASS	PASS	PASS	PASS	-9.97	13	
	B2	PASS	NA	PASS	PASS	PASS	PASS			
	B30	PASS	NA	PASS	PASS	PASS	PASS			
LTE FDD (OTT VoIP)	B2	PASS	NA	PASS	PASS	PASS	PASS	-12.91	T4	
	IEEE 802.11b	PASS	NA	PASS	PASS	PASS	PASS			
WLAN	IEEE 802.11g	PASS	NA	PASS	PASS	PASS	PASS	-8.41	Т3	
	IEEE 802.11n	PASS	NA	PASS	PASS	PASS	PASS			
	IEEE 802.11b	PASS	NA	PASS	PASS	PASS	PASS			
WLAN (OTT VoIP)	IEEE 802.11g	PASS	NA	PASS	PASS	PASS	PASS	-12.81	T4	
(311 13.1)	IEEE 802.11n	PASS	NA	PASS	PASS	PASS	PASS			

FCC ID: ZNFK400AM	PCTEST: Houd to be post of @ secured	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 06 of 74
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Page 26 of 71

I. **Raw Handset Data**

Table 9-2 **Raw Data Results for GSM**

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		128	17.49	-9.69		1.55	27.18	20.00	-7.18	T3	
	Axial	190	17.38	-11.37	-60.56	1.52	28.75	20.00	-8.75	Т3	2.0, 4.0
GSM850		251	17.45	-12.46		1.51	29.91	20.00	-9.91	Т3	
GSWIOSU		128	8.17	-17.64	-62.79		25.81	20.00	-5.81	Т3	
Radial	190	8.22	-19.30	-62.79		N/A	27.52	20.00	-7.52	Т3	2.0, 3.2
		251	8.22	-20.43				28.65	20.00	-8.65	Т3
		512	17.47	-13.01		1.53	30.48	20.00	-10.48	T4	
	Axial	661	17.44	-12.56	-60.56	1.48	30.00	20.00	-10.00	T4	2.0, 4.0
GSM1900		810	17.27	-12.82		1.53	30.09	20.00	-10.09	T4	
G3W1900		512	8.23	-21.17			29.40	20.00	-9.40	Т3	
Radial	661	8.17	-20.64	-62.79	N/A	28.81	20.00	-8.81	Т3	2.0, 3.2	
		810	8.30	-20.97			29.27	20.00	-9.27	Т3	

Table 9-3 **Raw Data Results for UMTS**

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates	
		4132	5.64	-42.92		1.39	48.56	20.00	-28.56	T4		
	Axial	4183	5.65	-41.26	-63.16	1.34	46.91	20.00	-26.91	T4	2.0, 4.0	
UMTS V		4233	5.66	-41.58		1.38	47.24	20.00	-27.24	T4		
UNITSV		4132	-3.81	-45.68	-62.79		41.87	20.00	-21.87	T4		
	Radial	4183	-3.81	-45.57		-62.79	N/A	41.76	20.00	-21.76	T4	2.0, 3.2
		4233	-3.83	-45.01			41.18	20.00	-21.18	T4		
Axial Axial	1312	5.67	-43.10	-63.16	1.38	48.77	20.00	-28.77	T4			
	1412	5.66	-43.19		1.34	48.85	20.00	-28.85	T4	2.0, 4.0		
	1513	5.65	-41.94		1.38	47.59	20.00	-27.59	T4			
UNITSIV		1312	-3.78	-45.22	-62.79			41.44	20.00	-21.44	T4	
	Radial	1412	-3.80	-45.14		N/A	41.34	20.00	-21.34	T4	2.0, 3.2	
		1513	-3.79	-45.21	1		41.42	20.00	-21.42	T4		
		9262	5.69	-41.31		1.35	47.00	20.00	-27.00	T4		
	Axial	9400	5.73	-41.23	-63.16	1.36	46.96	20.00	-26.96	T4	2.0, 4.0	
LIMTO II		9538	5.67	-41.71		1.36	47.38	20.00	-27.38	T4		
UMTS II		9262	-3.78	-43.12			39.34	20.00	-19.34	T4		
Radial	9400	-3.80	-45.49	-62.79	N/A	41.69	20.00	-21.69	T4	2.0, 3.2		
	Raulai	9538	-3.79	-43.46			39.67	20.00	-19.67	T4		

Table 9-4 **Raw Data Results for LTE B12**

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		10MHz	23095	5.05	-34.07		1.33	39.12	20.00	-19.12	T4	
	Axial	5MHz	23095	5.08	-32.83	-63.16	1.35	37.91	20.00	-17.91	T4	2.0, 4.0
	Axiai	3MHz	23095	5.09	-33.01	-63.16	1.37	38.10	20.00	-18.10	T4	2.0, 4.0
LTE Band 12		1.4MHz	23095	5.05	-33.15		1.37	38.20	20.00	-18.20	T4	
LIE Ballu 12		10MHz	23095	-3.92	-36.65			32.73	20.00	-12.73	T4	
	Radial	5MHz	23095	-3.97	-35.46	60.70	NVA	31.49	20.00	-11.49	T4	2.0, 3.2
	radiai	3MHz	23095	-3.98	-37.62	-62.79 N/A	IWA	33.64	20.00	-13.64	T4	2.0, 3.2
		1.4MHz	23095	-3.88	-35.98			32.10	20.00	-12.10	T4	

FCC ID: ZNFK400AM	FCC ID: ZNFK400AM		① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 27 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Page 27 of 71

Table 9-5 **Raw Data Results for LTE B14**

	Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		Axial	10MHz	23330	4.88	-33.92	-63.16	1.40	38.80	20.00	-18.80	T4	20.40
	Band 14		5MHz	23330	5.03	-32.78	-03.10	1.37	37.81	20.00	-17.81	T4	2.0, 4.0
LIE	Dana 14		10MHz	23330	-3.96	-36.74	62.70	NVA	32.78	20.00	-12.78	T4	2.0. 3.2
	Radial	5MHz	23330	-3.61	-37.06	-62.79 N	N/A	33.45	20.00	-13.45	T4	2.0, 3.2	

Table 9-6 **Raw Data Results for LTE B5**

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		10MHz	20525	4.94	-32.36		1.27	37.30	20.00	-17.30	T4	
	Axial	5MHz	20525	4.94	-33.18	-63.16	1.29	38.12	20.00	-18.12	T4	2.0, 4.0
	Axiai	3MHz	20525	4.94	-34.50	-03.10	1.35	39.44	20.00	-19.44	T4	2.0, 4.0
LTE Band 5		1.4MHz	20525	4.92	-34.70		1.36	39.62	20.00	-19.62	T4	
LIE Ballu 5		10MHz	20525	-3.75	-36.44			32.69	20.00	-12.69	T4	
	Radial	5MHz	20525	-4.03	-37.39	-62.79	N/A	33.36	20.00	-13.36	T4	2.0. 3.2
	Naulai	3MHz	20525	-3.99	-38.36		INA	34.37	20.00	-14.37	T4	2.0, 3.2
		1.4MHz	20525	-3.94	-38.33			34.39	20.00	-14.39	T4	

Table 9-7 Raw Data Results for LTF B66

				IVAII	Dutu IN	zouito io		-				
Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		20MHz	132322	4.90	-30.93		1.36	35.83	20.00	-15.83	T4	
		15MHz	132322	4.93	-30.66		1.43	35.59	20.00	-15.59	T4	
		10MHz	132322	4.77	-30.63		1.39	35.40	20.00	-15.40	T4	
	Axial	5MHz	132647	4.69	-30.95	-63.16	1.36	35.64	20.00	-15.64	T4	2.0, 4.0
	Axiai	5MHz	132322	4.79	-29.16	-03.10	1.40	33.95	20.00	-13.95	T4	2.0, 4.0
		5MHz	131997	4.73	-30.12		1.45	34.85	20.00	-14.85	T4	
		3MHz	132322	4.76	-30.21		1.42	34.97	20.00	-14.97	T4	
LTE Band 66		1.4MHz	132322	4.70	-31.21		1.40	35.91	20.00	-15.91	T4	
LIE Ballu 66		20MHz	132322	-4.04	-34.62			30.58	20.00	-10.58	T4	
		15MHz	132322	-3.98	-34.92			30.94	20.00	-10.94	T4	
		10MHz	132322	-3.68	-34.23			30.55	20.00	-10.55	T4	
	Radial	5MHz	132647	-3.93	-35.64	-62.79	N/A	31.71	20.00	-11.71	T4	2.0, 3.2
	radiai	5MHz	132322	-3.96	-33.93	-02.79	IWA	29.97	20.00	-9.97	Т3	2.0, 3.2
		5MHz	131997	-4.00	-35.42			31.42	20.00	-11.42	T4	
		3MHz	132322	-4.04	-34.49			30.45	20.00	-10.45	T4	
		1.4MHz	132322	-4.00	-34.73			30.73	20.00	-10.73	T4	

Table 9-8 Raw Data Results for LTE B2

					Dutait	counts it		_				_
Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		20MHz	18900	4.78	-30.48		1.41	35.26	20.00	-15.26	T4	
		15MHz	18900	4.73	-31.59		1.37	36.32	20.00	-16.32	T4	
Axial	10MHz	18900	4.73	-31.65	-63.16	1.40	36.38	20.00	-16.38	T4	2.0, 4.0	
	Axiai	5MHz	18900	4.75	-30.18	-03.10	1.40	34.93	20.00	-14.93	T4	2.0, 4.0
		3MHz	18900	4.74	-31.53		1.36	36.27	20.00	-16.27	T4	
LTE Band 2		1.4MHz	18900	4.71	-31.40		1.44	36.11	20.00	-16.11	T4	
LIE Ballu 2		20MHz	18900	-3.87	-36.00			32.13	20.00	-12.13	T4	
		15MHz	18900	-3.97	-36.08			32.11	20.00	-12.11	T4	
	Radial	10MHz	18900	-3.84	-35.92	-62.79	NI/A	32.08	20.00	-12.08	T4	20.22
	Radiai	5MHz	18900	-4.03	-35.92	-02.79	N/A	31.89	20.00	-11.89	T4	2.0, 3.2
		3MHz	18900	-4.01	-36.45			32.44	20.00	-12.44	T4	
		1.4MHz	18900	-4.01	-36.05			32.04	20.00	-12.04	T4	

FCC ID: ZNFK400AM	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dags 20 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Page 28 of 71

Table 9-9 Raw Data Results for LTE B30

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
Avial	10MHz	27710	4.74	-30.57	-63.16	1.38	35.31	20.00	-15.31	T4	20.40	
LTE Band 20	Axial	5MHz	27710	4.70	-31.40	-03.10	1.41	36.10	20.00	-16.10	T4	2.0, 4.0
Radial	10MHz	27710	-4.07	-36.61	00.70	-62.79	NI/A	32.54	20.00	-12.54	T4	2.0. 3.2
	Radiai	5MHz	27710	-3.93	-35.87		-62.79 N/A	31.94	20.00	-11.94	T4	2.0, 3.2

Table 9-10 Raw Data Results for 2.4GHz WIFI

				all Bata	rtoounto	101 2.701	<u> </u>				
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		1	2.19	-37.16		1.30	39.35	20.00	-19.35	T4	
	Axial	6	2.19	-36.49	-63.16	1.35	38.68	20.00	-18.68	T4	2.0, 4.0
IEEE		11	2.17	-37.11		1.34	39.28	20.00	-19.28	T4	
802.11b		1	-8.00	-37.01			29.01	20.00	-9.01	Т3	
	Radial	6	-7.93	-37.67	-62.79	N/A	29.74	20.00	-9.74	Т3	2.0, 3.2
		11	-8.04	-36.45			28.41	20.00	-8.41	Т3	
IEEE	Axial	6	2.18	-39.88	-63.16	1.35	42.06	20.00	-22.06	T4	2.0, 4.0
802.11g	Radial	6	-7.96	-38.67	-62.79	N/A	30.71	20.00	-10.71	T4	2.0, 3.2
IEEE	Axial	6	2.19	-37.92	-63.16	1.28	40.11	20.00	-20.11	T4	2.0, 4.0
802.11n	Radial	6	-8.00	-40.14	-62.79	N/A	32.14	20.00	-12.14	T4	2.0, 3.2

Table 9-11 Raw Data Results for EDGE (OTT VoIP)

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
EDGE850	Axial	190	9.75	-13.42	-63.16	1.99	23.17	20.00	-3.17	Т3	2.0, 4.0
EDGE030	Radial	190	-0.62	-24.21	-62.79	N/A	23.59	20.00	-3.59	Т3	2.0, 3.2
EDGE1900	Axial	661	9.76	-14.02	-63.16	1.99	23.78	20.00	-3.78	Т3	2.0, 4.0
LDGE 1900	Radial	661	-0.62	-25.20	-62.79	N/A	24.58	20.00	-4.58	Т3	2.0, 3.2

Table 9-12 Raw Data Results for HSPA (OTT VoIP)

					counto ioi		011 4011	,			
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
HSPA V	Axial	4183	9.73	-38.63	-63.16	2.00	48.36	20.00	-28.36	T4	2.0, 4.0
nora v	Radial	4183	-0.73	-42.11	-62.79	N/A	41.38	20.00	-21.38	T4	2.0, 3.2
HSPA IV	Axial	1412	9.62	-38.28	-63.16	2.00	47.90	20.00	-27.90	T4	2.0, 4.0
HOPA IV	Radial	1412	-0.66	-40.57	-62.79	N/A	39.91	20.00	-19.91	T4	2.0, 3.2
HSPA II	Axial	9400	9.74	-38.40	-63.16	2.00	48.14	20.00	-28.14	T4	2.0, 4.0
HOPAII	Radial	9400	-0.69	-39.73	-62.79	N/A	39.04	20.00	-19.04	T4	2.0, 3.2

FCC ID: ZNFK400AM	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 29 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Fage 29 01 / 1

Table 9-13 Raw Data Results for LTE FDD B2 (OTT VoIP)

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		20MHz	19100	9.62	-29.78		2.00	39.40	20.00	-19.40	T4	
		20MHz	18900	9.62	-28.82		1.82	38.44	20.00	-18.44	T4	
		20MHz	18700	9.60	-29.23		2.00	38.83	20.00	-18.83	T4	
	Axial	15MHz	18900	9.70	-29.63	-63.16	2.00	39.33	20.00	-19.33	T4	2.0, 4.0
	Axidi	10MHz	18900	9.57	-29.95	-63.16	2.00	39.52	20.00	-19.52	T4	2.0, 4.0
		5MHz	18900	9.64	-29.28		2.00	38.92	20.00	-18.92	T4	
		3MHz	18900	9.59	-30.05		1.98	39.64	20.00	-19.64	T4	
LTE Band 2		1.4MHz	18900	9.64	-29.79		1.94	39.43	20.00	-19.43	T4	
LIE Ballu Z		20MHz	18900	-0.57	-35.40			34.83	20.00	-14.83	T4	
		15MHz	18900	-0.62	-35.61			34.99	20.00	-14.99	T4	
		10MHz	18900	-0.60	-35.93			35.33	20.00	-15.33	T4	
	Radial	5MHz	19175	-0.67	-33.58	-62.79	N/A	32.91	20.00	-12.91	T4	2.0, 3.2
	Naulai	5MHz	18900	-0.65	-35.31	-02.79	INA	34.66	20.00	-14.66	T4	2.0, 3.2
		5MHz	18625	-0.68	-35.66			34.98	20.00	-14.98	T4	
		3MHz	18900	-0.69	-35.70			35.01	20.00	-15.01	T4	
		1.4MHz	18900	-0.63	-36.27			35.64	20.00	-15.64	T4	

Table 9-14 Raw Data Results for 2.4GHz WIFI (OTT VoIP)

						· O : : : · · · · ·	. (0	· · · ·			
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		1	9.87	-33.66		2.00	43.53	20.00	-23.53	T4	
	Axial	6	9.90	-33.41	-63.16	2.00	43.31	20.00	-23.31	T4	2.0, 4.0
IEEE		11	9.90	-33.90		2.00	43.80	20.00	-23.80	T4	
802.11b		1	-0.65	-35.20			34.55	20.00	-14.55	T4	
	Radial	6	-0.64	-34.49	-62.79	N/A	33.85	20.00	-13.85	T4	2.0, 3.2
		11	-0.59	-33.40			32.81	20.00	-12.81	T4	
IEEE	Axial	6	9.88	-36.97	-63.16	2.00	46.85	20.00	-26.85	T4	2.0, 4.0
802.11g	Radial	6	-0.86	-35.36	-62.79	N/A	34.50	20.00	-14.50	T4	2.0, 3.2
IEEE	Axial	6	9.90	-36.22	-63.16	2.00	46.12	20.00	-26.12	T4	2.0, 4.0
802.11n	Radial	6	-0.69	-37.07	-62.79	N/A	36.38	20.00	-16.38	T4	2.0, 3.2

II. **Test Notes**

A. General

- 1. Phone Condition: Mute on; Backlight off; Max Volume; Max Contrast
- 2. 'Radial' orientation refers to radial transverse.
- 3. Hearing Aid Mode (Phone→Call settings→Additional settings→Hearing aids) was set to ON for Frequency Response compliance
- 4. Speech Signal: ITU-T P.50 Artificial Voice
- 5. Bluetooth and WIFI were disabled while testing 2G/3G/4G modes.
- 6. Licensed data modes and Bluetooth were disabled while testing WIFI modes.
- 7. The Margin from FCC limit column indicates a margin from the FCC limit for compliance (T3).

B. GSM

- 1. Power Configuration: GSM850: PCL=5, GSM1900: PCL=0;
- 2. Vocoder Configuration: EFR (GSM);

FCC ID: ZNFK400AM	PCTEST Proof to be part of \$ memory	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 30 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		rage 30 01 7 1

C. UMTS

- 1. Power Configuration: TPC= "All 1s";
- 2. Vocoder Configuration: AMR 12.2 kbps (UMTS);

D. LTE FDD

- 1. Power Configuration: TPC = "Max Power"
- 2. Radio Configuration: 16QAM, 1RB, 0RB offset
- 3. Vocoder Configuration: NB AMR 12.2kbps
- 4. The worst-case band and bandwidth combination for each probe orientation is additionally tested on the low and high channels for those combinations. LTE Band 66 at 5MHz is the worst-case for both the Axial and Radial probe orientations.

E. WIFI


- 1. Radio Configuration
 - a. IEEE 802.11b: DSSS, 1Mbps
 - b. IEEE 802.11g: BPSK, 9Mbps
 - c. IEEE 802.11n: QPSK, MCS 1
- 2. Vocoder Configuration: NB AMR 12.2kbps
- The worst-case standard for 2.4GHz WIFI in each probe orientation is additionally tested on the low and high channels. IEEE 802.11b is the worst-case for both the Axial and Radial probe orientations.

F. OTT VolP


- 1. Vocoder Configuration: 75kbps
- 2. EDGE Configuration
 - a. MCS Index: 7
 - b. Number of TX slots: 2
- 3. HSPA Configuration:
 - a. Release: 6
 - b. 3GPP 34.121 Subtest 1
- 4. LTE FDD Configuration:
 - a. Power Configuration: TPC = "Max Power"
 - b. Radio Configuration: 16QAM, 1RB, 0RB offset
 - c. LTE Band 2 was the worst-case band from Table 7-5 and was used to test both Axial and Radial probe orientations.
 - d. The worst-case band and bandwidth combination for each probe orientation is additionally tested on the low and high channels for those combinations. LTE Band 2 at 20MHz is the worst-case for the Axial probe orientation. LTE Band 2 at 5MHz bandwidth is the worst-case for the Radial probe orientation.
- 5. WIFI Configuration:
 - a. Radio Configuration
 - i. IEEE 802.11b: DSSS, 1Mbps
 - ii. IEEE 802.11a: BPSK. 9Mbps
 - iii. IEEE 802.11n: QPSK, MCS 1
 - b. The worst-case standard for 2.4GHz WIFI in each probe orientation is additionally tested on the low and high channels. IEEE 802.11b is the worst-case for both the Axial and Radial probe orientations.

FCC ID: ZNFK400AM	PCTEST	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 31 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		rage 31 01 / 1

III. 1 kHz Vocoder Application Check



This model was verified to be within the linear region for ABM1 measurements at -16 dBm0 for GSM, UMTS, and VoLTE over IMS. This measurement was taken in the axial configuration above the maximum location.



This model was verified to be within the linear region for ABM1 measurements at -20 dBm0 for VoWIFI over IMS and OTT VoIP. This measurement was taken in the axial configuration above the maximum location.

IV. T-Coil Validation Test Results

Table 9-15
Helmholtz Coil Validation Table of Results – 03/16/2020

ltem	Target	Result	Verdict
Axial		_	_
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.296	PASS
Environmental Noise	< -58 dBA/m	-63.16	PASS
Frequency Response, from limits	> 0 dB	0.80	PASS
Radial			
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.347	PASS
Environmental Noise	< -58 dBA/m	-62.79	PASS
Frequency Response, from limits	> 0 dB	0.80	PASS

Table 9-16
Helmholtz Coil Validation Table of Results – 03/25/2020

Item	Target	Result	Verdict
Axial			
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-9.908	PASS
Environmental Noise	< -58 dBA/m	-60.56	PASS
Frequency Response, from limits	> 0 dB	0.70	PASS

FCC ID: ZNFK400AM	PCTEST: Houd to be part of @ secure	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 20 of 74
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Page 32 of 71

V. ABM1 Magnetic Field Distribution Scan Overlays




Figure 9-1
T-Coil Scan Overlay Magnetic Field Distributions

Notes:

- 1. Final measurement locations are indicated by a cursor on the contour plots.
- 2. See Test Setup Photographs for actual WD overlay.

FCC ID: ZNFK400AM	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 33 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		rage 33 of 7 f

MEASUREMENT UNCERTAINTY 10.

Table 10-1 Uncertainty Estimation Table

Contribution	Data +/- %	Data +/- dB	Data Type	Probability distribution	Divisor	Standard uncertainty	Standard Uncertainty (dB)
ABM Noise	7.0%	0.29	Std. Dev.	Normal k=1	1.00	7.0%	
RF Reflections	4.7%	0.20	Specification	Rectangular	1.73	2.7%	
Reference Signal Level	12.2%	0.50	Specification	Rectangular	1.73	7.0%	
Positioning Accuracy	10.0%	0.41	Uncertainty	Rectangular	1.73	5.8%	
Probe Coil Sensitivity	12.2%	0.50	Specification	Rectangular	1.73	7.0%	
Probe Linearity	2.4%	0.10	Std. Dev.	Normal k=1	1.00	2.4%	
Cable Loss	2.8%	0.12	Specification	Rectangular	1.73	1.6%	
Frequency Analyzer	5.0%	0.21	Specification	Rectangular	1.73	2.9%	
System Repeatability	5.0%	0.21	Std. Dev.	Normal k=1	1.00	5.0%	
WD Repeatability	9.0%	0.37	Std. Dev.	Normal k=1	1.00	9.0%	
Positioner Accuracy	1.0%	0.04	Specification	Rectangular	1.73	0.6%	
Combined standard uncertainty, uc (k=1) 17.7% 0.71						0.71	
							1.31

Notes:

- Test equipments are calibrated according to techniques outlined in NIS81, NIS3003 and NIST Tech Note 1297.
- All equipments have traceability according to NIST. Measurement Uncertainties are defined in further detail in NIS 81 and NIST Tech Note 1297 and UKAS M3003.

Measurement uncertainty reflects the quality and accuracy of a measured result as compared to the true value. Such statements are generally required when stating results of measurements so that it is clear to the intended audience that the results may differ when reproduced by different facilities. Measurement results vary due to the measurement uncertainty of the instrumentation, measurement technique, and test engineer. Most uncertainties are calculated using the tolerances of the instrumentation used in the measurement, the measurement setup variability, and the technique used in performing the test. While not generally included, the variability of the equipment under test also figures into the overall measurement uncertainty. Another component of the overall uncertainty is based on the variability of repeated measurements (so-called Type A uncertainty). This may mean that the Hearing Aid compatibility tests may have to be repeated by taking down the test setup and resetting it up so that there are a statistically significant number of repeat measurements to identify the measurement uncertainty. By combining the repeat measurement results with that of the instrumentation chain using the technique contained in NIS 81 and NIS 3003, the overall measurement uncertainty was estimated.

FCC ID: ZNFK400AM	PCTEST* Houd to be port of @ secured	HAC (T-COIL) TEST REPORT	€ LG	Approved by: Quality Manager
Filename: Test Dates:		DUT Type:		Page 34 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		rage 34 Ol 7 I

11. EQUIPMENT LIST

Table 11-1 Equipment List

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Control Company	4040	Therm./Clock/Humidity Monitor	6/29/2019	Biennial	6/29/2021	192291463
Dell	Latitude E6540	SoundCheck Acoustic Analyzer Laptop	4/24/2019	Biennial	4/24/2021	7BFNM32
Dell	Latitude E6540	SoundCheck Acoustic Analyzer Laptop	9/6/2018	Biennial	9/6/2020	2655082910
Listen	SoundConnect	Microphone Power Supply	4/22/2019	Biennial	4/22/2021	PS2612
Listen	SoundConnect	Microphone Power Supply	9/6/2018	Biennial	9/6/2020	0899-PS150
RME	Fireface UC	Soundcheck Acoustic Analyzer External Audio Interface	4/24/2019	Biennial	4/24/2021	23528889
RME	Fireface UC	Soundcheck Acoustic Analyzer External Audio Interface	9/6/2018	Biennial	9/6/2020	23792992
Rohde & Schwarz	CMW500	Radio Communication tester	8/14/2019	Annual	8/14/2020	140144
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	2/4/2020	Annual	2/4/2021	162125
Seekonk	NC-100	Torque Wrench (8" lb)	5/10/2018	Biennial	5/10/2020	21053
TEM	Axial T-Coil Probe	Axial T-Coil Probe	5/17/2019	Biennial	5/17/2021	TEM-1124
TEM	Axial T-Coil Probe	Axial T-Coil Probe	9/19/2018	Biennial	9/19/2020	TEM-1123
TEM		HAC Positioner	N/A		N/A	N/A
TEM		HAC System Controller with Software	N/A		N/A	N/A
TEM	C63.19	Helmholtz Coil	5/20/2019	Biennial	5/20/2021	925
TEM	Helmholtz Coil	Helmholtz Coil	10/10/2018	Biennial	10/10/2020	SBI 1052
TEM	Radial T-Coil Probe	Radial T-Coil Probe	5/17/2019	Biennial	5/17/2021	TEM-1130

FCC ID: ZNFK400AM	PCTEST* Houd to be port of @ secured	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager	
Filename: Test Dates:		DUT Type:		Page 35 of 71	
1M2003020032-03.ZNF 03/16/2020 - 03/26/2020		Portable Handset		Page 35 01 / 1	

12. TEST DATA

FCC ID: ZNFK400AM	PCTEST:	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 36 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		



PCTEST Hearing-Aid Compatibility Facility

DUT: HH Coil - SN: SBI 1052


Type: HH Coil Serial: SBI 1052

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Axial T-Coil Probe SN: TEM-1123; Calibrated: 09/19/2018
- Helmholtz Coil SN: SBI 1052; Calibrated: 10/10/2018

Noise Spectrum



Frequency Response



Results

Verification 1kHz Intensity	-9.908 dB	~	Max/Min	-9.5/-10.5
Verification ABM2	-60.56 dB	~	Maximum	-58.0
Frequency Response Margin	700m dB	•	Tolerance curves	Aligned Data

FCC ID: ZNFK400AM	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 37 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		rage 37 01 7 1



DUT: HH Coil – SN: 925


Type: HH Coil Serial: 925

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Axial T-Coil Probe SN: TEM-1124; Calibrated: 05/17/2019
- Helmholtz Coil SN: 925; Calibrated: 05/20/2019

Noise Spectrum



Frequency Response



Results

Verification 1kHz Intensity	-10.296	dB	9	Max/Min	-9.5/-10.5
Verification ABM2	-63.16	dB	•	Maximum	-58.0
Frequency Response Margin	800m	dB	•	Tolerance curves	Aligned Data

FCC ID: ZNFK400AM	PCTEST*	HAC (1-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 38 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		rage 30 01 / 1



DUT: HH Coil - SN: 925


Type: HH Coil Serial: 925

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Radial T-Coil Probe SN: TEM-1130; Calibrated: 05/17/2019
- Helmholtz Coil SN: 925; Calibrated: 05/20/2019

Noise Spectrum



Frequency Response



Results

Verification 1kHz Intensity	-10.347	dB	•	Max/Min	-9.5/-10.5
Verification ABM2	-62.79	dB	•	Maximum	-58.0
Frequency Response Margin	800m	dB	•	Tolerance curves	Aligned Data

FCC ID: ZNFK400AM	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 39 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		rage 39 01 / 1



Type: Portable Handset Serial: 10575


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1123; Calibrated: 09/19/2018

Test Configuration:

- Mode: GSM850 Channel: 128
- Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFK400AM	PCTEST Hood to be part of the second	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dags 40 of 74
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Page 40 of 71



Type: Portable Handset Serial: 10575


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1123; Calibrated: 09/19/2018

Test Configuration:

- Mode: GSM1900
- Channel: 661
- Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFK400AM	PCTEST* Road to be part of ® executed.	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 41 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		rage 41 01 / 1



Type: Portable Handset Serial: 10575

Measurement Standard: ANSI C63.19-2011


Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 05/17/2019

Test Configuration:

Mode: UMTS VChannel: 4183

Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFK400AM	PCTEST*	HAC (I-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 42 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Fage 42 01 / 1



Type: Portable Handset Serial: 10575

Measurement Standard: ANSI C63.19-2011


Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 05/17/2019

Test Configuration:

Mode: UMTS IVChannel: 1513

. Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFK400AM	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 43 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		raye 43 01 / 1



Type: Portable Handset Serial: 10575

Measurement Standard: ANSI C63.19-2011


Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 05/17/2019

Test Configuration:

Mode: UMTS IIChannel: 9400

· Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFK400AM	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 44 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		raye 44 01 / 1



Type: Portable Handset Serial: 10575

Measurement Standard: ANSI C63.19-2011


Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 05/17/2019

Test Configuration:

 Mode: LTE Band 66 Bandwidth: 5MHz Channel: 132322

Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFK400AM	PCTEST Hood to be part of the second	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dags 45 of 74
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Page 45 of 71



Type: Portable Handset Serial: 10575

Measurement Standard: ANSI C63.19-2011

Equipment:


Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 05/17/2019

Test Configuration:

Mode: 2.4GHz WIFIStandard: IEEE 802.11b

· Channel: 6

. Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFK400AM	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo 46 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Page 46 of 71



Type: Portable Handset Serial: 10575

Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 05/17/2019


Test Configuration:

VolP Application: Google Duo

Mode: EDGE850

· Channel: 190

. Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFK400AM	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 47 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		rage 47 of 71



Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 05/17/2019

Test Configuration:

 Mode: GSM850 Channel: 128



FCC ID: ZNFK400AM	PCTEST:	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dags 40 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Page 48 of 71




Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 05/17/2019

Test Configuration:

 Mode: GSM1900 Channel: 661



FCC ID: ZNFK400AM	PCTEST	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 49 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		rage 49 01 / 1




Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 05/17/2019

Test Configuration:

Mode: UMTS VChannel: 4233



FCC ID: ZNFK400AM	PCTEST	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 50 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Fage 50 01 7 1




Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 05/17/2019

Test Configuration:

 Mode: UMTS IV Channel: 1412



FCC ID: ZNFK400AM	PCTEST . Thought to be post of @ second	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogg 51 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Page 51 of 71




Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 05/17/2019

Test Configuration:

 Mode: UMTS II Channel: 9262



FCC ID: ZNFK400AM	PCTEST	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 52 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Fage 52 01 / 1




Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 05/17/2019

Test Configuration:

Mode: LTE Band 66 Bandwidth: 5MHz Channel: 132322



FCC ID: ZNFK400AM	PCTEST Total to be part of \$ servers	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 53 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		rage 55 01 / 1



Measurement Standard: ANSI C63.19-2011


Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 05/17/2019

Test Configuration:

Mode: 2.4GHz WIFI Standard: IEEE 802.11b

Channel: 11



FCC ID: ZNFK400AM	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 54 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		rage 34 01 / 1



Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 05/17/2019

Test Configuration:

· VolP Application: Google Duo

Mode: EDGE850Channel: 190



FCC ID: ZNFK400AM	PCTEST* Houd to be post of § secure	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo FF of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Page 55 of 71

CALIBRATION CERTIFICATES 13.

FCC ID: ZNFK400AM	PCTEST Board of & sement	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 56 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		rage 50 of 7 i

© 2020 PCTEST **REV 3.5.M**



Certificate of Calibration

for

AXIAL T COIL PROBE

Manufactured by:

TEM CONSULTING AXIAL T COIL PROBE

Model No: Serial No:

TEM-1124 29973

Calibration Recall No:

Submitted By:

Customer:

ANDREW HARWELL

Company:

PCTEST ENGINEERING LAB 6660-B DOBBIN ROAD

Address: 6660-B DOBI COLUMBIA

MD 21045

The subject instrument was calibrated to the indicated specification using standards traceable to the National Institute of Standards and Technology or to accepted values of natural physical constants. This document certifies that the instrument met the following specification upon its return to the submitter.

West Caldwell Calibration Laboratories Procedure No.

AXIAL T C TEM C

6/4/2019

Upon receipt for Calibration, the instrument was found to be:

Within (X)

tolerance of the indicated specification. See attached Report of Calibration.
The information supplied relates to the calibrated item listed above.
West Caldwell Calibration Laboratories' calibration control system meets the requirements, ISO 10012-1 MIL-STD-45662A, ANSI/NCSL Z540-1, IEC Guide 25, ISO 9001:2015 and ISO 17025.

Note: With this Certificate, Report of Calibration is included.

Approved by:

Calibration Date:

17-May-19

James Zhu

Certificate No:

29973 -1

Quality Manager ISO/IEC 17025:2005

QA Doc. #1051 Rev. 2.0 10/1/01 Cer

Certificate Page 1 of 1

ACCREDITED

Calibration
uncompromised calibration Laboratories, Inc.

1575 State Route 96, Victor, NY 14564, U.S.A.

Calibration Lab. Cert. # 1533.01

FCC ID: ZNFK400AM

PCTEST

HAC (T-COIL) TEST REPORT

Quality Manager

Filename:

1M2003020032-03.ZNF

03/16/2020 - 03/26/2020

Portable Handset

Approved by:
Quality Manager

Page 57 of 71

© 2020 PCTEST

REV 3.5.M



ACCREDITED

Calibration Lab. Cert. # 1533.01

ISO/IEC 17025: 2005

1575 State Route 96, Victor NY 14564

REPORT OF CALIBRATION

for

TEM Consulting LP Axial T Coil Probe Company: PCTest Engineering Labs

Model No.: Axial T Coil Probe

Serial No.: TEM-1124

I. D. No.: XXXX

Probe Sensitivity measured wit	h Helmhol	tz Coil			
Helmholtz Coil;			Before & after data same:X		
the number of turns on each coil;	10	No.			
the radius of each coil, in meters;	0.204	m	Laboratory Environment:		
the current in the coils, in amperes.;	0.09	Α	Ambient Temperature:	20.7	°C
Helmholtz Coil Constant;	7.09	A/m/V	Ambient Humidity:	42.7	% RH
Helmholtz Coil magnetic field;	5.96	A/m	Ambient Pressure:	98.256	kPa
			Calibration Date:	17-May-2019	
Probe Sensitivity at	1000	Hz.	Calibration Due:	17-May-2020	
was	-60.41	dBV/A/m	Report Number:	29973	-1
	0.954	mV/A/m	Control Number:	29973	
Probe resistance	903	Ohms			


The above listed instrument meets or exceeds the tested manufacturer's specifications.

This Calibration is traceable through NIST test numbers:

683/290345-18

The expanded uncertainty of calibration: 0.30dB at 95% confidence level with a coverage factor of k=2.

Graph represents Probes Frequency Response.



The above listed instrument was checked using calibration procedure documented in West Caldwell

Calibration Laboratories Inc. procedure :

Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCATEMC

Calibration was performed by West Caldwell Calibration Laboratories Inc. under Operating Procedures

intended to implement the requirements of ISO10012-1, IEC Guide 25, ANSI/NCSL Z540-1, (MIL-STD-45662A) and ISO 17025

Cal. Date: 17-May-2019

Measurements performed by:

James Zhu

Calibrated on WCCL system type 9700

This document shall not be reproduced, except in full, without the written approval from West Caldwell Cal. Labs. Inc.

Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCATEMC

Page 1 of 2

FCC ID: ZNFK400AM	PCTEST:	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 58 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		3

HCATEMC_TEM-1124_May-17-2019

West Caldwell Calibration Laboratories Inc.

1575 State Route 96, Victor NY 14564 Tel. (585) 586-3900 FAX (585) 586-4327

Calibration Data Record

Model No.: Axial T Coil Probe

Serial No.: TEM-1124

TEM Consulting LP Axial T Coil Probe Company: PCTest Engineering Labs

Test	Function	Tolerance		Measured values		
				Before	Out	Remarks
1.0	Probe Sensitivity at	1000 Hz.	dBV/A/m	-60.41		
			dB			
2.0	Probe Level Linearity		6	6.10		
		Ref. (0 dB)	0	0.00		
			-6	-6.00		i
			-12	-12.00		
			Hz			
3.0	Probe Frequency Response		100	-19.9		
			126	-17.9		
			158	-16.0		
			200	-14.0		
			251	-12.0		
			316	-10.0		
			398	-8.0		
			<i>i</i> 501	-6.0		
			631	-3.9		
			794	-2.0		
		Ref. (0 dB)	1000	0.0		1
			1259	2.0		
			1585	4.0		
			1995	5.9		
			2512	7.9		
			3162	9.9		
			3981	11.9		
			5012	13.9		
			6310	15.9		
			7943	18.0		
			10000	20.2		
				l		

Instruments used for o	alibration:		Date of Cal.	Traceability No.	Due Date
HP	34401A	S/N US360641	25-Jul-2018	,1010733	26-Jul-2019
HP	34401A	S/N US361024	25-Jul-2018	,1010733	26-Jul-2019
HP	33120A	S/N US360437	25-Jul-2018	,1010733	26-Jul-2019
B&K	2133	S/N 1583254	25-Jul-2018	683/290345-18	26-Jul-2019
1					

Cal. Date: 17-May-2019

Calibrated on WCCL system type 9700

This document shall not be reproduced, except in full, without the written approval from West Caldwell Cal. Labs. Inc.

Tested by: James Zhu

Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCATEMC

Page 2 of 2

FCC ID: ZNFK400AM	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 59 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		rage 59 01 / 1



Certificate of Calibration

for

RADIAL T COIL PROBE

Manufactured by:

TEM CONSULTING

Model No:

RADIAL T COIL PROBE

Serial No: Calibration Recall No: TEM-1130 29973

Submitted By:

Customer:

ANDREW HARWELL

Company: Address: PCTEST ENGINEERING LAB 6660-B DOBBIN ROAD

COLUMBIA

MD 21045

The subject instrument was calibrated to the indicated specification using standards traceable to the National Institute of Standards and Technology or to accepted values of natural physical constants. This document certifies that the instrument met the following specification upon its return to the submitter.

West Caldwell Calibration Laboratories Procedure No.

RADIAL T TEM C

Upon receipt for Calibration, the instrument was found to be:

6/4/2019

Within (X)

tolerance of the indicated specification. See attached Report of Calibration.

The information supplied relates to the calibrated item listed above.

West Caldwell Calibration Laboratories' calibration control system meets the requirements, ISO 10012-1 MIL-STD-45662A, ANSI/NCSL Z540-1, IEC Guide 25, ISO 9001:2015 and ISO 17025.

Certificate Page 1 of 1

Note: With this Certificate, Report of Calibration is Included.

Approved by:

opioved by.

Calibration Date:

17-May-19

James Zhu

Certificate No:

29973 -2

Quality Manager ISO/IEC 17025:2005

QA Doc. #1051 Rev. 2.0 10/1/01

West Caldwell Calibration

ACCREDITED

uncompromised calibration Laboratories, Inc.

Calibration Lab. Cert. # 1533.01

1575 State Route 96, Victor, NY 14564, U.S.A.

FCC ID: ZNFK400AM

Filename:

1M2003020032-03.ZNF

O3/16/2020 - 03/26/2020

HAC (T-COIL) TEST REPORT

DUT Type:

Page 60 of 71

© 2020 PCTEST



 Laboratories, Inc. Calibration Lab. Cert. # 1533.01

1575 State Route 96, Victor NY 14564

REPORT OF CALIBRATION

TEM Consulting LP Radial T Coil Probe Company: PCTest Engineering Labs

Model No.: Radial T Coil Probe

Serial No.: TEM-1130

I. D. No.: XXXX

ISO/IEC 17025: 2005


Probe Sensitivity measured wit	h Helmholi	z Coil			
Helmholtz Coil:			Before & after data same:	Y	
the number of turns on each coil:	10	No.	before & arter data same.		
the radius of each coil, in meters;	0.204	m	Laboratory Environment:		
the current in the coils, in amperes.;	0.08	Α	Ambient Temperature:	20.7	°C
Helmholtz Coil Constant;	7.09	A/m/V	Ambient Humidity:	42.7	% RH
Helmholtz Coil magnetic field;	5.94	A/m	Ambient Pressure:	98.256	kPa
			Calibration Date:	17-May-2019	
Probe Sensitivity at	1000	Hz.	Calibration Due:	17-May-2020	
was	-60.37	dBV/A/m	Report Number:	29973	-2
	0.958	mV/A/m	Control Number:	29973	
Probe resistance	895	Ohms			

This Calibration is traceable through NIST test numbers:

683/290345-18

The expanded uncertainty of calibration: 0.30dB at 95% confidence level with a coverage factor of k=2.

Graph represents Probes Frequency Response.



The above listed instrument was checked using calibration procedure documented in West Caldwell

Calibration Laboratories Inc. procedure :

Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCRTEMC

Calibration was performed by West Caldwell Calibration Laboratories Inc. under Operating Procedures

intended to implement the requirements of ISO10012-1, IEC Guide 25, ANSI/NCSL Z540-1, (MIL-STD-45662A) and ISO 17025

Cal. Date: 17-May-2019

Calibrated on WCCL system type 9700

Measurements performed by:

James Zhu

This document shall not be reproduced, except in full, without the written approval from West Caldwell Cal. Labs. Inc.

Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCRTEMC

Page 1 of 2

FCC ID: ZNFK400AM	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 61 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		rage 0101/1

HCRTEMC_TEM-1130_May-17-2019

West Caldwell Calibration Laboratories Inc.

1575 State Route 96, Victor NY 14564 Tel. (585) 586-3900 FAX (585) 586-4327

Calibration Data Record

for

TEM Consulting LP Radial T Coil Probe Company: PCTest Engineering Labs

Model No.: Radial T Coil Probe

Serial No.: TEM-1130

Function	Tolerance		Measured values		
			Before	Out	Remarks
Probe Sensitivity at	1000 Hz.	dBV/A/m	-60.37		
		dB			
Probe Level Linearity		6	6.00		
	Ref. (0 dB)	0	0.00		
		-6	-6.10		
		-12	-12.10		ŀ
		Hz			
3.0 Probe Frequency Response		100	-20.0		
		126	-17.9		
		158	-16.0		
		200	-14.0		
		251	-12.0		
		316	-10.0		
		398			1
		501	-6.0		
		631	-4.0		
		794	-2.0		
	Ref. (0 dB)	1000	0.0		
		1259	1.9		
		1585	3.9		
		1995			
		2512	7.9		
		3162	9.9		
		3981	11.9		
		5012	13.9		
		6310	15.9		
		7943	18.0		
		10000	20.1		
	Probe Level Linearity	Probe Sensitivity at 1000 Hz. Probe Level Linearity Ref. (0 dB) Probe Frequency Response	Probe Sensitivity at 1000 Hz. dBV/A/m Probe Level Linearity 6 Ref. (0 dB) 0 -6 -12 Probe Frequency Response 100 126 158 200 251 316 398 501 631 794 Ref. (0 dB) 1000 1259 1585 1995 2512 3162 3981 5012 6310 7943	Probe Sensitivity at 1000 Hz. dBV/A/m -60.37 Probe Level Linearity Ref. (0 dB) 0 0.00 -6 -6.10 -12 -12.10 Probe Frequency Response Hz Probe Frequency Response 100 -20.0 126 -17.9 158 -16.0 200 -14.0 251 -12.0 316 -10.0 398 -8.0 501 -6.0 631 -4.0 794 -2.0 Ref. (0 dB) 1000 0.0 1259 1.9 1585 3.9 1995 5.9 2512 7.9 3162 9.9 3981 11.9 5012 13.9 6310 15.9 7943 18.0	Probe Sensitivity at 1000 Hz. dBV/A/m -60.37 Probe Level Linearity Ref. (0 dB) Ref. (0 dB)

Instruments used for o	alibration:		Date of Cal.	Traceability No.	Due Date
HP	34401A	S/N US360641	25-Jul-2018	,1010733	26-Jul-2019
HP	34401A	S/N US361024	25-Jul-2018	,1010733	26-Jul-2019
HP	33120A	S/N US360437	25-Jul-2018	,1010733	26-Jul-2019
B&K	2133	S/N 1583254	25-Jul-2018	683/290345-18	26-Jul-2019

Cal. Date: 17-May-2019

Calibrated on WCCL system type 9700

This document shall not be reproduced, except in full, without the written approval from West Caldwell Cal. Labs. Inc.

Tested by: James Zhu

Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCRTEMC

Page 2 of 2

FCC ID: ZNFK400AM	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 62 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Page 02 01 / 1



Certificate of Calibration

for

AXIAL T COIL PROBE

Manufactured by:

TEM CONSULTING LP

Model No:

AXIAL T COIL PROBE

Serial No: Calibration Recall No: TEM-1123 29156

Submitted By:

Customer:

Andrew Harwell

Company:

PCTest Engineering Lab

Address:

6660-B Dobbin Road

Columbia

MD 21045

The subject instrument was calibrated to the indicated specification using standards traceable to the National Institute of Standards and Technology or to accepted values of natural physical constants. This document certifies that the instrument met the following specification upon its return to the submitter.

West Caldwell Calibration Laboratories Procedure No.

AXIAL T C TEM C

Upon receipt for Calibration, the instrument was found to be:

12/4/2019

Within (X)

tolerance of the indicated specification. See attached Report of Calibration.
The information supplied relates to the calibrated item listed above.
West Caldwell Calibration Laboratories' calibration control system meets the requirements, ISO 10012-1 MIL-STD-45662A, ANSI/NCSL Z540-1, IEC Guide 25, ISO 9001:2008 and ISO 17025.

Note: With this Certificate, Report of Calibration is included.

Approved by: Fc

Calibration Date:

19-Sep-18

Felix Christopher (QA Mgr.)

Certificate No:

29156 -2

West Caldwell Calibration

ISO/IEC 17025:2005

QA Doc. #1051 Rev. 2.0 10/1/01

Certificate Page 1 of 1

ACCREDITED

uncompromised calibration Laboratories, Inc.

1575 State Route 96, Victor, NY 14564, U.S.A.

Calibration Lab. Cert. # 1533.01

© 2020 PCTEST

REV 3.5.M



1575 State Route 96, Victor NY 14564



REPORT OF CALIBRATION

TEM Consulting LP Axial T Coil Probe Company: PCTest Enginering Lab

Model No.: Axial T Coil Probe

Serial No.: TEM-1123 I. D. No.: XXXX


Calibration results: Probe Sensitivity measured with Helmholtz Coil Helmholtz Coil; Before & after data same: ... X ... the number of turns on each coil; 10 No. 0.204 Laboratory Environment: the radius of each coil, in meters; m Ambient Temperature: °C 0.08 22.7 Α the current in the coils, in amperes.; 7.09 A/m/V Ambient Humidity: % RH Helmholtz Coil Constant; Helmholtz Coil magnetic field; 5.95 A/m Ambient Pressure: 99.326 Calibration Date: 19-Sep-2018 Calibration Due: Probe Sensitivity at 1000 Hz. dBV/A/m. Report Number: 29156 -2 -59 89 was 1.013 mV/A/m Control Number: 29156 903 Ohms Probe resistance The above listed instrument meets or exceeds the tested manufacturer's specifications.

683/284413-14

This Calibration is traceable through NIST test numbers:

The expanded uncertainty of calibration: 0.30dB at 95% confidence level with a coverage factor of k=2.

Graph represents Probes Frequency Response.



The above listed instrument was checked using calibration procedure documented in West Caldwell

Calibration Laboratories Inc. procedure :

Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCATEMC

Calibration was performed by West Caldwell Calibration Laboratories Inc. under Operating Procedures

intended to implement the requirements of ISO10012-1, IEC Guide 25, ANSI/NCSL Z540-1, (MIL-STD-45662A) and ISO 9001:2008, ISØ)17025

Cal. Date: 19-Sep-2018

Measurements performed by:

James Zhu

Calibrated on WCCL system type 9700

This document shall not be reproduced, except in full, without the written approval from West Caldwell Cal. Labs. Inc.

Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCATEMC

Page 1 of 2

FCC ID: ZNFK400AM	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 64 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		rage 04 01 / 1

HCATEMC_TEM-1123_Sep-19-2018

West Caldwell Calibration Laboratories Inc.

1575 State Route 96, Victor NY 14564 Tel. (585) 586-3900 FAX (585) 586-4327

Calibration Data Record

TEM Consulting LP Axial T Coil Probe Company: PCTest Enginering Lab

Model No.: Axial T Coil Probe

Serial No.: TEM-1123

Test	Function	Tolera	Tolerance		Measured values		
				Before	Out	Remarks	
1.0	Probe Sensitivity at	1000 Hz.	dBV/A/m	-59.89			
		···	dB				
2.0	Probe Level Linearity		6	6.03			
		Ref. (0 dB)	0	0.00			
•			-6	-6.03			
			-12	-12.05			
		***************************************	Hz				
3.0	Probe Frequency Response		100	-19.9			
			126	-17.9			
			158	-15.9			
			200	-13.9			
			251	-11.9			
			316	-9.9			
			398	-7.9			
			501	-6.0			
			631	-4.0			
			794	-2.0			
		Ref. (0 dB)	1000	0.0			
			1259	2.0			
			1585	4.0			
			1995	5.9			
			2512	7.9			
			3162	9.9			
			3981	11.9			
			5012	13.9			
•			6310	15.9			
			7943	18.0			
			10000	20.1			
						<u> </u>	

Instruments used for o	calibration:		Date of Cal.	Traceablity No.	Due Date
HP	34401A	S/N US360641	25-Jul-2018	,287708	25-Jul-2019
HP	34401A	S/N US361024	25-Jul-2018	,287708	25-Jul-2019
HP	33120A	S/N US360437	25-Jul-2018	,287708	25-Jul-2019
B&K	2133	S/N 1583254	25-Jul-2018	683/284413-14	25-Jul-2019

Cal. Date: 19-Sep-2018

Calibrated on WCCL system type 9700

This document shall not be reproduced, except in full, without the written approval from West Caldwell Cal. Labs. Inc.

Tested by: James Zhu

Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCATEMC

Page 2 of 2

FCC ID: ZNFK400AM	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 65 of 71
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		rage 05 01 / 1

14. CONCLUSION

The measurements indicate that the wireless communications device complies with the HAC limits specified in accordance with the ANSI C63.19 Standard and FCC WT Docket No. 01-309 RM-8658. Precise laboratory measures were taken to assure repeatability of the tests. The tested device complies with the requirements in respect to all parameters specific to the test. The test results and statements relate only to the item(s) tested.

The measurement system and techniques presented in this evaluation are proposed in the ANSI standard as a means of best approximating wireless device compatibility with a hearing-aid. The literature is under continual re-construction.

FCC ID: ZNFK400AM	PCTEST:	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager	
Filename:	Test Dates:	DUT Type:		Dogg 66 of 71	
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Page 66 of 71	

15. REFERENCES

- ANSI C63.19-2011, American National Standard for Methods of Measurement of Compatibility between Wireless communication devices and Hearing Aids.", New York, NY, IEEE, May 2011
- FCC Office of Engineering and Technology KDB, "285076 D01 HAC Guidance v05," September 13, 2017
- FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v03," September 13, 2017
- 4. FCC Public Notice DA 06-1215, Wireless Telecommunications Bureau and Office of Engineering and Technology Clarify Use of Revised Wireless Phone Hearing Aid Compatibility Standard, June 6, 2006
- 5. FCC 3G Review Guidance, Laboratory Division OET FCC, May/June 2006
- Berger, H. S., "Compatibility Between Hearing Aids and Wireless Devices," Electronic Industries Forum, Boston, MA, May, 1997
- 7. Berger, H. S., "Hearing Aid and Cellular Phone Compatibility: Working Toward Solutions," Wireless Telephones and Hearing Aids: New Challenges for Audiology, Gallaudet University, Washington, D.C., May, 1997 (To be reprinted in the American Journal of Audiology).
- 8. Berger, H. S., "Hearing Aid Compatibility with Wireless Communications Devices, " IEEE International Symposium on Electromagnetic Compatibility, Austin, TX, August, 1997.
- Bronaugh, E. L., "Simplifying EMI Immunity (Susceptibility) Tests in TEM Cells," in the 1990 IEEE International Symposium on Electromagnetic Compatibility Symposium Record, Washington, D.C., August 1990, pp. 488-491
- 10. Byme, D. and Dillon, H., The National Acoustics Laboratory (NAL) New Procedure for Selecting the Gain and Frequency Response of a Hearing Aid, Ear and Hearing 7:257-265, 1986.
- Crawford, M. L., "Measurement of Electromagnetic Radiation from Electronic Equipment using TEM Transmission Cells, "U.S. Department of Commerce, National Bureau of Standards, NBSIR 73-306, Feb. 1973.
- Crawford, M. L., and Workman, J. L., "Using a TEM Cell for EMC Measurements of Electronic Equipment," U.S. Department of Commerce, National Bureau of Standards. Technical Note 1013, July 1981.
- 13. EHIMA GSM Project, Development phase, Project Report (1st part) Revision A. Technical-Audiological Laboratory and Telecom Denmark, October 1993.
- 14. EHIMA GSM Project, Development phase, Part II Project Report. Technical-Audiological Laboratory and Telecom Denmark, June 1994.
- EHIMA GSM Project Final Report, Hearing Aids and GSM Mobile Telephones: Interference Problems, Methods of Measurement and Levels of Immunity. Technical-Audiological Laboratory and Telecom Denmark, 1995.
- 16. HAMPIS Report, Comparison of Mobile phone electromagnetic near field with an upscaled electromagnetic far field, using hearing aid as reference, 21 October 1999.

FCC ID: ZNFK400AM	PCTEST* Houd to be port of @ secured	HAC (T-COIL) TEST REPORT	€ LG	Approved by: Quality Manager	
Filename:	Test Dates:	DUT Type:		Page 67 of 71	
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		Page 07 01 7 1	

- 17. Hearing Aids/GSM, Report from OTWIDAM, Technical-Audiological Laboratory and Telecom Denmark, April 1993.
- 18. IEEE 100, The Authoritative Dictionary of IEEE Standards Terms, Seventh Edition.
- Joyner, K. H, et. al., Interference to Hearing Aids by the New Digital Mobile Telephone System, Global System for Mobile (GSM) Communication Standard, National Acoustic Laboratory, Australian Hearing Series, Sydney 1993.
- Joyner, K. H., et. al., Interference to Hearing Aids by the Digital Mobile Telephone System, Global System for Mobile Communications (GSM), NAL Report #131, National Acoustic Laboratory, Australian Hearing Series, Sydney, 1995.
- 21. Kecker, W. T., Crawford, M. L., and Wilson, W. A., "Contruction of a Transverse Electromagnetic Cell", U.S. Department of Commerce, National Bureau of Standards, Technical Note 1011, Nov. 1978.
- 22. Konigstein, D., and Hansen, D., "A New Family of TEM Cells with enlarged bandwidth and Optimized working Volume," in the Proceedings of the 7th International Symposium on EMC, Zurich, Switzerland, March 1987; 50:9, pp. 127-132.
- 23. Kuk, F., and Hjorstgaard, N. K., "Factors affecting interference from digital cellular telephones," Hearing Journal, 1997; 50:9, pp 32-34.
- 24. Ma, M. A., and Kanda, M., "Electromagnetic Compatibility and Interference Metrology," U.S. Department of Commerce, National Bureau of Standards, Technical Note 1099, July 1986, pp. 17-43.
- 25. Ma, M. A., Sreenivashiah, I., and Chang, D. C., "A Method of Determining the Emission and Susceptibility Levels of Electrically Small Objects Using a TEM Cell," U.S. Department of Commerce, National Bureau of Standards, Technial Note 1040, July 1981.
- 26. McCandless, G. A., and Lyregaard, P. E., Prescription of Gain/Output (POGO) for Hearing Aids, Hearing Instruments 1:16-21, 1983
- 27. Skopec, M., "Hearing Aid Electromagnetic Interference from Digital Wireless Telephones, "IEEE Transactions on Rehabilitation Engineering, vol. 6, no. 2, pp. 235-239, June 1998.
- 28. Technical Report, GSM 05.90, GSM EMC Considerations, European Telecommunications Standards Institute, January 1993.
- 29. Victorian, T. A., "Digital Cellular Telephone Interference and Hearing Aid Compatibility—an Update," Hearing Journal 1998; 51:10, pp. 53-60
- 30. Wong, G. S. K., and Embleton, T. F. W., eds., AIP Handbook of Condenser Microphones: Theory, Calibration and Measurements, AIP Press.

FCC ID: ZNFK400AM	PCTEST:	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager	
Filename:	Test Dates:	DUT Type:		Page 68 of 71	
1M2003020032-03.ZNF	03/16/2020 - 03/26/2020	Portable Handset		1 age 00 01 7 1	