

[illegible]

2. **Power** button may also be used to stop the device.
3. **Power** button may also be used to stop the device.
4. **Mode** button may also be used to stop the device.
5. **Mode** button may also be used to stop the device.
6. **Mode** button may also be used to stop the device.
7. **Mode** button may also be used to stop the device.
8. **Mode** button may also be used to stop the device.
9. **Mode** button may also be used to stop the device.
10. **Mode** button may also be used to stop the device.

7. Charging issue: The recharge tank overcharge protection circuit, which is connected to a computer or charger for a long time, about 2 hours, to *MAI* charger. Any battery charging time will be different due to the size of different acid or the valve.

8. Unconnected state Automatic shutdown after 15 minutes.

9. The connections wire of the charging station can only be connected to 12VDC, when you need to connect the charging station to 24VDC, you can connect a **10A blade fuse holder** in the 12VDC position wire, which can prevent the equipment from being damaged in case of short circuit.

10. The Power Indicator lights up when there is 12VDC input from the charging station.

3. Connect the "USB to FireWire" cables into the ports on the back of the hard drive.

4. Insert the FireWire into the FireWire port on the hard drive.

INSTALLATION TO THE DESKTOP

1. Connect the "USB to FireWire" cables into the ports on the back of the hard drive.

2. Insert the FireWire into the FireWire port on the hard drive.

1. Remove the 4 screws (M2.0x8mm); separate the Speaker and Changing Station.
2. Slide the Speaker out of the Changing Station.

[illegible]