Host Label and Label location

TropOS 2420
PRODUCT NO:
24203060D

INPUT: 7-32VDC, 10W ====



NOTE: Installer must be a trained technical professional.
















IC: 4751A-642401 m/n: Bluefin 2G IC: 4751A-645801 m/n: Bluefin 5G Class I, Division 2, Groups A, B, C, and D; Ex nA IIA T4A Gc Class I, Zone 2; AEx nA IIA T4 Gc

Ambient range: Tamb = -40°C to +75°C

WARNING - EXPLOSION HAZARD. DO NOT CONNECT OR DISCONNECT WHEN ENERGIZED.

AVERTISSEMENT - RISQUE D'EXPLOSION. NE PAS BRANCHER OU DÉBRANCHER LORSQUE LE CIRCUIT EST SOUS TENSION.

WARNING – EXPLOSION HAZARD. DO NOT REMOVE OR REPLACE WHILE CIRCUIT IS LIVE UNLESS THE AREA IS FREE OF IGNITIBLE CONCENTRATIONS.

AVERTISSEMENT — RISQUE D'EXPLOSION. NE PAS RETIRER OU REMPLACER LORSQUE LE CIRCUIT EST SOUS TENSION, À MOINS QUE LE MILIEU SOIT LIBRE DE SUBSTANCES INFLAMMABLES CONCENTRÉES.

Model: KD3 Label P/N: 152705-00_A3 PROTECTED BY U.S. PATENTS

Label Location

