

Test Method:	FCC Part 15 Subpart C, Spurious Case Radiated Emissions, Paragraph 15.209(a)						
Customer:	X-10 (USA)				Job No.	R-8468-1	
Test Sample:	2.4GHz Transceiver				FCC ID:	B4SVT32A	
Model No.:	VT32A				Serial No.	N/A	
Operating Mode:	2.4GHz Transmitter, Continuous						
Technician:	P. Lananna				Date:	March 28, 2000	
Notes:	Test Distance: 3 Meters Temp:18C Humidity:33% Detector: Quasi-Peak Below 1 GHz, Peak above 1 GHz						
Test Freq.	Antenna Position	EUT Orientation	Meter Readings	Correction Factor	Corrected Reading	Converted Reading	LIMIT
MHz	(V/H) / Meters	Degrees	dBuV	dB	dBuV/m	uV/m	UV/m
30.00							100
88.00							100
88.00							150
110.2	V/1.0	270	37	-10.5	26.5	21.1	
216.00							150
216.00							200
310.0	V/1.0	180	48	-3.9	44.1	160.3	
960.00							200
960.00							500
1000.0							500
25000.0							500
The EUT was scanned from 30 MHz to 25 GHz							
The emissions observed from the EUT do not exceed the specified limits. Emissions not recorded							
were more than 10dB under the specified limit							



Retlif Testing Laboratories

Retlif Job Number R-8468-1