

LTE Band 13 (ANT A+B)

5 MHz

QPSK

UL Verification Services, Inc.

Above 1GHz High Frequency Substitution Measurement

Company:

Project #:

Date:

Test Engineer:

Configuration:

Location:

Mode:

Test Votage:

Samsung

4790841160

2023-06-14

51078

EUT / AC Adapter, X-Position, HF

Chamber 1

LTE_QPSK Band 13 Harmonics, 5MHz Bandwidth

AC 120 V, 60 Hz

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 779.5MHz									
1558.40	-19.5	V	3.0	46.3	1.0	-64.9	-40.0	-24.9	
2337.60	-11.0	V	3.0	46.8	1.0	-56.8	-13.0	-43.8	
3116.80	-11.4	V	3.0	46.9	1.0	-57.3	-13.0	-44.3	
1558.40	-20.0	H	3.0	46.3	1.0	-65.4	-40.0	-25.4	
2337.60	-11.9	H	3.0	46.8	1.0	-57.7	-13.0	-44.7	
3116.80	-9.9	H	3.0	46.9	1.0	-55.8	-13.0	-42.8	
Mid Ch, 782MHz									
1564.00	-18.3	V	3.0	46.4	1.0	-63.7	-40.0	-23.7	
2346.00	-6.7	V	3.0	46.8	1.0	-52.5	-13.0	-39.5	
3128.00	-9.9	V	3.0	46.9	1.0	-55.8	-13.0	-42.8	
1564.00	-19.1	H	3.0	46.4	1.0	-64.5	-40.0	-24.5	
2346.00	-6.9	H	3.0	46.8	1.0	-52.7	-13.0	-39.7	
3128.00	-9.8	H	3.0	46.9	1.0	-55.7	-13.0	-42.7	
High Ch, 784.5MHz									
1569.00	-18.8	V	3.0	46.4	1.0	-64.2	-40.0	-40.0	
2353.50	-11.4	V	3.0	46.8	1.0	-57.3	-13.0	-44.3	
3138.00	-9.9	V	3.0	46.9	1.0	-55.8	-13.0	-42.8	
1569.00	-20.2	H	3.0	46.4	1.0	-65.6	-40.0	-25.6	
2353.50	-11.4	H	3.0	46.8	1.0	-57.3	-13.0	-44.3	
3138.00	-9.9	H	3.0	46.9	1.0	-55.7	-13.0	-42.7	

LTE Band 13 (ANT A)

5 MHz

QPSK

UL Verification Services, Inc.

Above 1GHz High Frequency Substitution Measurement

Company: Samsung

Project #: 4790841160

Date: 2023-06-15

Test Engineer: 51078

Configuration: EUT / AC Adapter, Z-Position, FF

Location: Chamber 2

Mode: LTE_QPSK Band 13 Harmonics, 5MHz Bandwidth

Test Votage: AC 120 V, 60 Hz

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 779.5MHz									
1559.00	-26.5	V	3.0	40.7	1.0	-66.2	-40.0	-26.2	
2338.50	-12.6	V	3.0	41.1	1.0	-52.7	-13.0	-39.7	
3118.00	-10.3	V	3.0	42.0	1.0	-51.3	-13.0	-38.3	
1559.00	-26.7	H	3.0	40.7	1.0	-66.4	-40.0	-26.4	
2338.50	-12.7	H	3.0	41.1	1.0	-52.8	-13.0	-39.8	
3118.00	-10.4	H	3.0	42.0	1.0	-51.5	-13.0	-38.5	
Mid Ch, 782MHz									
1564.00	-25.4	V	3.0	40.7	1.0	-65.1	-40.0	-25.1	
2346.00	-12.5	V	3.0	41.1	1.0	-52.6	-13.0	-39.6	
3128.00	-10.1	V	3.0	42.0	1.0	-51.1	-13.0	-38.1	
1564.00	-25.9	H	3.0	40.7	1.0	-65.6	-40.0	-25.6	
2346.00	-12.6	H	3.0	41.1	1.0	-52.7	-13.0	-39.7	
3128.00	-10.4	H	3.0	42.0	1.0	-51.4	-13.0	-38.4	
High Ch, 784.5MHz									
1569.00	-27.0	V	3.0	40.7	1.0	-66.7	-40.0	-26.7	
2353.50	-12.5	V	3.0	41.1	1.0	-52.6	-13.0	-39.6	
3138.00	-9.9	V	3.0	42.0	1.0	-50.9	-13.0	-37.9	
1569.00	-27.1	H	3.0	40.7	1.0	-66.8	-40.0	-26.8	
2353.50	-12.5	H	3.0	41.1	1.0	-52.6	-13.0	-39.6	
3138.00	-10.2	H	3.0	42.0	1.0	-51.2	-13.0	-38.2	

LTE Band 41(UL CA, ANT B)

20+20 MHz	QPSK	UL Verification Services, Inc. Above 1GHz High Frequency Substitution Measurement									
		Company: Samsung Project #: 4790841160 Date: 2023-06-19 Test Engineer: 24542 Configuration: EUT / AC Adapter, Z-Position, Open Location: Chamber 2 Mode: LTE_QPSK Band 41 Harmonics, 20+20MHz Bandwidth Test Votage: AC 120 V, 60 Hz									
		f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
		Low Ch, PCC : 2506MHz SCC : 2525.8MHz									
		5031.80	-18.7	V	3.0	42.8	1.0	-60.4	-25.0	-35.4	
		7547.70	-13.6	V	3.0	42.4	1.0	-55.0	-25.0	-30.0	
		10063.60	-13.6	V	3.0	40.9	1.0	-53.5	-25.0	-28.5	
		5031.80	-18.0	H	3.0	42.8	1.0	-59.8	-25.0	-34.8	
		7547.70	-9.6	H	3.0	42.4	1.0	-51.0	-25.0	-26.0	
		10063.60	-13.0	H	3.0	40.9	1.0	-52.9	-25.0	-27.9	
		Mid Ch, PCC : 2583.1MHz SCC : 2602.9MHz									
		5186.00	-18.8	V	3.0	42.8	1.0	-60.6	-25.0	-35.6	
		7779.00	-16.7	V	3.0	42.3	1.0	-57.9	-25.0	-32.9	
		10372.00	-12.3	V	3.0	41.0	1.0	-52.3	-25.0	-27.3	
		5186.00	-18.7	H	3.0	42.8	1.0	-60.5	-25.0	-35.5	
		7779.00	-14.5	H	3.0	42.3	1.0	-55.8	-25.0	-30.8	
		10372.00	-11.7	H	3.0	41.0	1.0	-51.7	-25.0	-26.7	
		High Ch, PCC : 2660.2MHz SCC : 2680MHz									
		5340.20	-18.9	V	3.0	42.8	1.0	-60.8	-25.0	-35.8	
		8010.30	-15.6	V	3.0	42.2	1.0	-56.7	-25.0	-31.7	
		10680.40	-12.3	V	3.0	41.1	1.0	-52.4	-25.0	-27.4	
		5340.20	-18.7	H	3.0	42.8	1.0	-60.6	-25.0	-35.6	
		8010.30	-14.1	H	3.0	42.2	1.0	-55.3	-25.0	-30.3	
		10680.40	-11.9	H	3.0	41.1	1.0	-52.0	-25.0	-27.0	

LTE Band 41(UL CA, ANT F)

20+20 MHz	QPSK	UL Verification Services, Inc. Above 1GHz High Frequency Substitution Measurement									
		Company: Samsung Project #: 4790841160 Date: 2023-06-20 Test Engineer: 19568 Configuration: EUT / AC Adapter, Z-Position, HF Location: Chamber 2 Mode: LTE_QPSK Band 41 Harmonics, 20+20MHz Bandwidth Test Votage: AC 120 V, 60 Hz									
		f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
		Low Ch, PCC : 2506MHz SCC : 2525.8MHz									
		5031.80	-16.4	V	3.0	42.8	1.0	-58.2	-25.0	-33.2	
		7547.70	-16.3	V	3.0	42.4	1.0	-57.8	-25.0	-32.8	
		10063.60	-13.3	V	3.0	40.9	1.0	-53.2	-25.0	-25.0	
		5031.80	-17.5	H	3.0	42.8	1.0	-59.2	-25.0	-34.2	
		7547.70	-16.3	H	3.0	42.4	1.0	-57.7	-25.0	-32.7	
		10063.60	-13.2	H	3.0	40.9	1.0	-53.1	-25.0	-28.1	
		Mid Ch, PCC : 2583.1MHz SCC : 2602.9MHz									
		5186.00	-14.0	V	3.0	42.8	1.0	-55.8	-25.0	-30.8	
		7779.00	-16.2	V	3.0	42.3	1.0	-57.5	-25.0	-32.5	
		15558.00	-5.6	V	3.0	43.5	1.0	-48.1	-25.0	-23.1	
		5186.00	-16.7	H	3.0	42.8	1.0	-58.5	-25.0	-33.5	
		7779.00	-16.2	H	3.0	42.3	1.0	-57.5	-25.0	-32.5	
		10372.00	-12.7	H	3.0	41.0	1.0	-52.7	-25.0	-27.7	
		High Ch, PCC : 2660.2MHz SCC : 2680MHz									
		5340.20	-14.4	V	3.0	42.8	1.0	-56.2	-25.0	-31.2	
		8010.30	-16.1	V	3.0	42.2	1.0	-57.3	-25.0	-32.3	
		10680.40	-11.9	V	3.0	41.1	1.0	-52.1	-25.0	-27.1	
		5340.20	-14.3	H	3.0	42.8	1.0	-56.1	-25.0	-31.1	
		8010.30	-16.2	H	3.0	42.2	1.0	-57.4	-25.0	-32.4	
		10680.40	-11.8	H	3.0	41.1	1.0	-51.9	-25.0	-26.9	

LTE Band 66 (ANT B)

15 MHz

QPSK

UL Verification Services, Inc.
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4790841160
Date: 2023-06-20
Test Engineer: 24542
Configuration: EUT / AC Adapter, Y-Position, Open
Location: Chamber 1
Mode: LTE_QPSK Band 66 Harmonics, 15MHz Bandwidth
Test Votage: AC 120 V, 60 Hz

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1717.5MHz									
3435.00	-8.9	V	3.0	46.4	1.0	-54.3	-13.0	-41.3	
5152.50	-7.6	V	3.0	46.1	1.0	-52.7	-13.0	-39.7	
6870.00	-4.1	V	3.0	45.5	1.0	-48.6	-13.0	-35.6	
8587.50	-3.1	V	3.0	45.6	1.0	-47.6	-13.0	-34.6	
10305.00	-0.6	V	3.0	45.8	1.0	-45.4	-13.0	-32.4	
3435.00	-8.4	H	3.0	46.4	1.0	-53.8	-13.0	-40.8	
5152.50	-7.4	H	3.0	46.1	1.0	-52.5	-13.0	-39.5	
6870.00	-4.6	H	3.0	45.5	1.0	-49.1	-13.0	-36.1	
8587.50	-2.7	H	3.0	45.6	1.0	-47.3	-13.0	-34.3	
10305.00	-0.5	H	3.0	45.8	1.0	-45.4	-13.0	-32.4	
Mid Ch, 1745MHz									
3490.00	-8.5	V	3.0	46.3	1.0	-53.8	-13.0	-40.8	
5235.00	-7.4	V	3.0	46.0	1.0	-52.4	-13.0	-39.4	
6980.00	-3.9	V	3.0	45.5	1.0	-48.4	-13.0	-35.4	
8725.00	-2.8	V	3.0	45.5	1.0	-47.4	-13.0	-34.4	
10470.00	-0.4	V	3.0	46.0	1.0	-45.3	-13.0	-32.3	
3490.00	-8.3	H	3.0	46.3	1.0	-53.7	-13.0	-40.7	
5235.00	-5.4	H	3.0	46.0	1.0	-50.5	-13.0	-37.5	
6980.00	-4.1	H	3.0	45.5	1.0	-48.6	-13.0	-35.6	
8725.00	-3.0	H	3.0	45.5	1.0	-47.5	-13.0	-34.5	
10470.00	-0.1	H	3.0	46.0	1.0	-45.1	-13.0	-32.1	
High Ch, 1772.5MHz									
3545.00	-8.2	V	3.0	46.3	1.0	-53.4	-13.0	-40.4	
5317.50	-7.1	V	3.0	46.0	1.0	-52.1	-13.0	-39.1	
7090.00	-3.8	V	3.0	45.5	1.0	-48.3	-13.0	-35.3	
8862.50	-2.8	V	3.0	45.5	1.0	-47.3	-13.0	-34.3	
10635.00	-0.2	V	3.0	46.1	1.0	-45.3	-13.0	-32.3	
3545.00	-7.9	H	3.0	46.3	1.0	-53.2	-13.0	-40.2	
5317.50	-6.6	H	3.0	46.0	1.0	-51.6	-13.0	-38.6	
7090.00	-3.9	H	3.0	45.5	1.0	-48.4	-13.0	-35.4	
8862.50	-2.9	H	3.0	45.5	1.0	-47.4	-13.0	-34.4	
10635.00	-0.1	H	3.0	46.1	1.0	-45.2	-13.0	-32.2	

NR Band n41 (ANT B)

90 MHz

DFT-s_OFDM

UL Verification Services, Inc.

Above 1GHz High Frequency Substitution Measurement

Company: Samsung

Project #: 4790841160

Date: 2023-06-19

Test Engineer: 19568

Configuration: EUT / AC Adapter, Z-Position, HF

Location: Chamber 2

Mode: 5G NR_QPSK NR n41 Harmonics, 90MHz Bandwidth

Test Votage: AC 120 V, 60 Hz

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 2541.01MHz									
5082.02	-18.4	V	3.0	42.8	1.0	-60.1	-25.0	-35.1	
7623.03	-14.3	V	3.0	42.4	1.0	-55.7	-25.0	-30.7	
10164.04	-13.2	V	3.0	40.9	1.0	-53.1	-25.0	-28.1	
5082.02	-17.9	H	3.0	42.8	1.0	-59.7	-25.0	-34.7	
7623.03	-15.6	H	3.0	42.4	1.0	-57.0	-25.0	-32.0	
10164.04	-12.9	H	3.0	40.9	1.0	-52.9	-25.0	-27.9	
Mid Ch, 2592.99MHz									
5185.98	-16.5	V	3.0	42.8	1.0	-58.3	-25.0	-33.3	
7778.97	-14.7	V	3.0	42.3	1.0	-56.0	-25.0	-31.0	
10371.96	-12.7	V	3.0	41.0	1.0	-52.7	-25.0	-27.7	
5185.98	-16.8	H	3.0	42.8	1.0	-58.6	-25.0	-33.6	
7778.97	-15.4	H	3.0	42.3	1.0	-56.7	-25.0	-31.7	
10371.96	-12.5	H	3.0	41.0	1.0	-52.5	-25.0	-27.5	
High Ch, 2645MHz									
5290.00	-16.1	V	3.0	42.8	1.0	-57.9	-25.0	-32.9	
7935.00	-14.9	V	3.0	42.2	1.0	-56.1	-25.0	-31.1	
10580.00	-12.3	V	3.0	41.1	1.0	-52.4	-25.0	-27.4	
5290.00	-16.2	H	3.0	42.8	1.0	-58.1	-25.0	-33.1	
7935.00	-14.8	H	3.0	42.2	1.0	-56.1	-25.0	-31.1	
10580.00	-12.0	H	3.0	41.1	1.0	-52.1	-25.0	-27.1	

NR Band n41 (ANT F)

40 MHz
DFT-s_OFDM

UL Verification Services, Inc.

Above 1GHz High Frequency Substitution Measurement

Company: Samsung

Project #: 4790841160

Date: 2023-06-22

Test Engineer: 19568

Configuration: EUT / AC Adapter, Z-Position, HF

Location: Chamber 2

Mode: 5G NR_QPSK NR n41 Harmonics, 40MHz Bandwidth

Test Votage: AC 120 V, 60 Hz

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 2516.01MHz									
5032.02	-18.2	V	3.0	42.8	1.0	-60.0	-25.0	-35.0	
7548.03	-18.1	V	3.0	42.4	1.0	-59.5	-25.0	-34.5	
10064.04	-14.8	V	3.0	40.9	1.0	-54.7	-25.0	-29.7	
5032.02	-19.7	H	3.0	42.8	1.0	-61.4	-25.0	-36.4	
7548.03	-18.2	H	3.0	42.4	1.0	-59.6	-25.0	-34.6	
10064.04	-14.9	H	3.0	40.9	1.0	-54.7	-25.0	-29.7	
Mid Ch, 2592.99MHz									
5185.98	-17.3	V	3.0	42.8	1.0	-59.1	-25.0	-34.1	
7778.97	-18.2	V	3.0	42.3	1.0	-59.5	-25.0	-34.5	
10371.96	-14.6	V	3.0	41.0	1.0	-54.6	-25.0	-29.6	
5185.98	-15.6	H	3.0	42.8	1.0	-57.4	-25.0	-32.4	
7778.97	-18.2	H	3.0	42.3	1.0	-59.5	-25.0	-34.5	
10371.96	-14.4	H	3.0	41.0	1.0	-54.4	-25.0	-29.4	
High Ch, 2670MHz									
5340.00	-18.3	V	3.0	42.8	1.0	-60.1	-25.0	-35.1	
8010.00	-18.5	V	3.0	42.2	1.0	-59.7	-25.0	-34.7	
10680.00	-13.9	V	3.0	41.1	1.0	-54.1	-25.0	-29.1	
5340.00	-17.5	H	3.0	42.8	1.0	-59.4	-25.0	-34.4	
8010.00	-17.5	H	3.0	42.2	1.0	-58.7	-25.0	-33.7	
10680.00	-13.8	H	3.0	41.1	1.0	-53.9	-25.0	-28.9	

NR Band n66 (ANT B)

		UL Verification Services, Inc. Above 1GHz High Frequency Substitution Measurement									
		Company: Samsung Project #: 4790841160 Date: 2023-06-21 Test Engineer: 24542 Configuration: EUT / AC Adapter, Y-Position, Open Location: Chamber 2 Mode: 5G NR_QPSK NR n66 Harmonics, 30MHz Bandwidth Test Votage: AC 120 V, 60 Hz									
		f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
30 MHz DFT-s_OFDM		Low Ch, 1725MHz									
		3450.00	-8.8	V	3.0	42.1	1.0	-49.9	-13.0	-36.9	
		5175.00	-8.7	V	3.0	42.8	1.0	-50.5	-13.0	-37.5	
		6900.00	-5.9	V	3.0	42.7	1.0	-47.7	-13.0	-34.7	
		8625.00	-4.6	V	3.0	41.9	1.0	-45.5	-13.0	-32.5	
		10350.00	-1.6	V	3.0	41.0	1.0	-41.6	-13.0	-28.6	
		3450.00	-9.0	H	3.0	42.1	1.0	-50.1	-13.0	-37.1	
		5175.00	-8.5	H	3.0	42.8	1.0	-50.4	-13.0	-37.4	
		6900.00	-6.0	H	3.0	42.7	1.0	-47.7	-13.0	-34.7	
		8625.00	-4.5	H	3.0	41.9	1.0	-45.5	-13.0	-32.5	
		10350.00	-1.4	H	3.0	41.0	1.0	-41.4	-13.0	-28.4	
		Mid Ch, 1745MHz									
		3490.00	-8.8	V	3.0	42.1	1.0	-49.8	-13.0	-36.8	
		5235.00	-8.8	V	3.0	42.8	1.0	-50.6	-13.0	-37.6	
		6980.00	-5.9	V	3.0	42.7	1.0	-47.5	-13.0	-34.5	
		8725.00	-4.4	V	3.0	41.9	1.0	-45.3	-13.0	-32.3	
		10470.00	-1.1	V	3.0	41.1	1.0	-41.1	-13.0	-28.1	
		3490.00	-9.0	H	3.0	42.1	1.0	-50.0	-13.0	-37.0	
		5235.00	-8.6	H	3.0	42.8	1.0	-50.4	-13.0	-37.4	
		6980.00	-5.7	H	3.0	42.7	1.0	-47.4	-13.0	-34.4	
		8725.00	-4.3	H	3.0	41.9	1.0	-45.2	-13.0	-32.2	
		10470.00	-0.9	H	3.0	41.1	1.0	-40.9	-13.0	-27.9	
		High Ch, 1765MHz									
		3530.00	-8.3	V	3.0	42.1	1.0	-49.4	-13.0	-36.4	
		5295.00	-8.4	V	3.0	42.8	1.0	-50.3	-13.0	-37.3	
		7060.00	-5.7	V	3.0	42.7	1.0	-47.4	-13.0	-34.4	
		8825.00	-3.9	V	3.0	41.8	1.0	-44.8	-13.0	-31.8	
		10590.00	-0.8	V	3.0	41.1	1.0	-40.9	-13.0	-27.9	
		3530.00	-8.6	H	3.0	42.1	1.0	-49.7	-13.0	-36.7	
		5295.00	-8.3	H	3.0	42.8	1.0	-50.2	-13.0	-37.2	
		7060.00	-5.7	H	3.0	42.7	1.0	-47.4	-13.0	-34.4	
		8825.00	-3.9	H	3.0	41.8	1.0	-44.7	-13.0	-31.7	
		10590.00	-0.6	H	3.0	41.1	1.0	-40.7	-13.0	-27.7	

END OF REPORT