

TEST REPORT

Applicant	GN Audio USA Inc.
Address	900 Chelmsfort St, Tower 2, Floor 8 Lowell, Massachusetts United States 01851

Manufacturer or Supplier	GN Audio A/S
Address	Lautrupbjerg 7, 2750 Ballerup, Denmark
Product	Bluetooth Headset
Brand Name	Jabra
Model	OTE160R (Right Earbud); OTE160L (Left Earbud)
Additional Model & Model Difference	N/A
Date of tests	Aug. 02, 2021 ~ Sep. 04, 2021

The tests have been carried out according to the requirements of the following standards:

☒ **FCC Part 15, Subpart C, Section 15.247**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Lucas Chen Project Engineer / EMC Department	Approved by Glyn He Assistant Manager / EMC Department
	 Date: Oct. 09, 2021

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <https://www.cps-bureauveritas.com/terms-conditions> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1 SUMMARY OF TEST RESULTS.....	5
2 MEASUREMENT UNCERTAINTY	5
3 GENERAL INFORMATION	6
3.1 GENERAL DESCRIPTION OF EUT.....	6
3.2 DESCRIPTION OF TEST MODES.....	7
3.2.1. CONFIGURATION OF SYSTEM UNDER TEST	8
3.2.2. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	8
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS.....	10
3.4 DESCRIPTION OF SUPPORT UNITS.....	10
4 TEST TYPES AND RESULTS.....	11
4.1. RADIATED EMISSION AND BANDEDGE MEASUREMENT	11
4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT	11
4.1.2 TEST INSTRUMENTS.....	12
4.1.3 TEST PROCEDURES	13
4.1.4 DEVIATION FROM TEST STANDARD	14
4.1.5 TEST SETUP.....	14
4.1.6 EUT OPERATING CONDITIONS	15
4.1.7 TEST RESULTS.....	16
4.2 NUMBER OF HOPPING FREQUENCY USED.....	32
4.2.1 LIMIT OF HOPPING FREQUENCY USED	32
4.2.2 TEST SETUP.....	32
4.2.3 TEST INSTRUMENTS.....	32
4.2.4 TEST PROCEDURES	33
4.2.5 DEVIATION FROM TEST STANDARD	33
4.2.6 TEST RESULTS.....	33
4.3 DWELL TIME ON EACH CHANNEL	36
4.3.1 LIMIT OF DWELL TIME USED	36
4.3.2 TEST SETUP.....	36
4.3.3 TEST INSTRUMENTS.....	36
4.3.4 TEST PROCEDURES	36
4.3.5 DEVIATION FROM TEST STANDARD	37
4.3.6 TEST RESULTS.....	37

4.4	CHANNEL BANDWIDTH.....	40
4.4.1	LIMITS OF CHANNEL BANDWIDTH	40
4.4.2	TEST SETUP.....	40
4.4.3	TEST INSTRUMENTS.....	40
4.4.4	TEST PROCEDURE.....	40
4.4.5	DEVIATION FROM TEST STANDARD	40
4.4.6	EUT OPERATING CONDITION.....	40
4.4.7	TEST RESULTS.....	41
4.5	HOPPING CHANNEL SEPARATION	45
4.5.1	LIMIT OF HOPPING CHANNEL SEPARATION	45
4.5.2	TEST SETUP.....	45
4.5.3	TEST INSTRUMENTS.....	45
4.5.4	TEST PROCEDURES	45
4.5.5	DEVIATION FROM TEST STANDARD	45
4.5.6	TEST RESULTS.....	46
4.6	CONDUCTED OUTPUT POWER	50
4.6.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT.....	50
4.6.2	TEST SETUP.....	50
4.6.3	TEST INSTRUMENTS.....	50
4.6.4	TEST PROCEDURES	50
4.6.5	DEVIATION FROM TEST STANDARD	50
4.6.6	EUT OPERATING CONDITION.....	51
4.6.7	TEST RESULTS.....	51
4.7	OUT OF BAND EMISSION MEASUREMENT	54
4.7.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT	54
4.7.2	TEST INSTRUMENTS.....	54
4.7.3	TEST PROCEDURE.....	54
4.7.4	DEVIATION FROM TEST STANDARD	54
4.7.5	EUT OPERATING CONDITION.....	54
4.7.6	TEST RESULTS.....	54
5	PHOTOGRAPHS OF THE TEST CONFIGURATION	59
6	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING	
	CHANGES TO THE EUT BY THE LAB	60



Test Report No.: RF2107WDG0484-1

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF2107WDG0484-1	Original release	Oct. 09, 2021

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	N/A	Powered by battery
15.247(a)(1)(iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Conducted Output Power	PASS	Meet the requirement of limit.
15.247(d)&15.209	Transmitter Radiated Emission	PASS	Meet the requirement of limit.
15.247(d)	Out of band Emission Measurement	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Radiated emissions	9KHz ~ 30MHz	2.16dB
	30MHz ~ 1GMHz	3.82dB
	1GHz ~ 18GHz	4.94dB
	18GHz ~ 40GHz	5.07dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Bluetooth Headset
MODEL NO.	OTE160R (Right Earbud); OTE160L (Left Earbud)
ADDITIONAL MODEL	N/A
FCC ID	BCE-OTE160
POWER SUPPLY	Earbuds: DC 3.85V from Li-ion Battery or DC 5V from Charging Case Charging Case: DC 3.7V from Li-ion Battery or DC 5V from USB Host Unit
MODULATION TECHNOLOGY	FHSS
MODULATION TYPE	GFSK, $\pi/4$ DQPSK, 8DPSK
OPERATING FREQUENCY	2402MHz~2480MHz
NUMBER OF CHANNEL	79
PEAK OUTPUT POWER	Left Earbud: 18.750mW (Max. Measured) Right Earbud: 15.996mW (Max. Measured)
ANTENNA TYPE	Left Earbud: FPCB Antenna, -2.27dBi Gain Right Earbud: FPCB Antenna, -2.58dBi Gain
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	USB Line: Unshielded Detachable 15cm

NOTES:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
3. Please refer to the EUT photo document (Reference No.: 2107WDG0484-1) for detailed product photo.
4. When the EUT charging that BT function can't working, the charging mode was tested in the FCC Part 15B(sDOC) report.(report no.: FS2107WDG0484).
5. This product has two Bluetooth Chips (distribute left earbud and right earbud), they are identical in RF circuitry except the antenna gain and Layout of partial components, all test items are carried out on the maximum power "Right earbud" except Conducted Output power, Power Spectral Density and Radiated Emission tests.

6. The batteries for earplugs and charging cases are provided by different manufacturers (see notes 7). They are evaluated in FCC 15B(sDoC) report, but the worst case and full test was performed for the earplugs which batteries provided by "VDL".
7. The battery manufacturer's supply information is as follows:

BATTERY	MANUFACTURERS	BATTERY INFORMATION
Battery cell (for Earbuds)	Chongqing VDL Electronics Co., Ltd.	3.85V, 70mAh, Lithium ion cell type
Battery cell (for Earbuds)	Guangdong Mic. power New Energy Co., Ltd.	3.85V, 70mAh, Lithium ion cell type

3.2 DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

3.2.1. CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photograph of the test configuration for reference.

3.2.2. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned on X axis for radiated emission. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE<1G	RE≥1G	PLC	APCM	
A	√	√	-	√	Powered by Fully Battery with Bluetooth link

Where **RE<1G**: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission

RE≥1G: Radiated Emission above 1GHz
APCM: Antenna Port Conducted Measurement

NOTE: No need to concern of Conducted Emission due to the EUT is powered by battery.

RADIATED EMISSION TEST (BELOW 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	39	FHSS	GFSK	DH5

For the test results, only the worst case was shown in test report.

RADIATED EMISSION TEST (ABOVE 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

ANTENNA PORT CONDUCTED MEASUREMENT:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE (SYSTEM)	TESTED BY
RE<1G	27deg. C, 58%RH	DC 3.85V From Fully Battery	Jelly
RE≥1G	27deg. C, 58%RH	DC 3.85V From Fully Battery	Jelly
PLC	N/A	N/A	N/A
APCM	25deg. C, 60%RH	DC 3.85V From Fully Battery	Vincent

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247

KDB 558074 D01 15.247 Meas Guidance v05r02

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit without any other necessary accessory or support units.

4 TEST TYPES AND RESULTS

4.1. RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a). Other emissions shall be at least 20dB below the highest level of the desired power.

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTES:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESU40	100449	Mar. 07,22
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV7	102331	May 09, 22
Active Loop Antenna (9KHz -30MHz)	SCHWARZBECK	FMZB 1519B	1519B-045	May 29,22
Amplifier (9KHz -1GHz)	Burgeon	BPA-530	100210	Mar. 13,22
Bilog Antenna (20MHz -2GHz)	Teseq	CBL 6111D	30643	May 29,22
Horn Antenna (1GHz -18GHz)	ETS -Lindgren	3117	00062558	May 29,22
Horn Antenna (18GHz -40GHz)	SCHWARZBECK	BBHA 9170	BBHA9170147	May 09, 22
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	May 22,22
Test Software	ADT	ADT_Radiated_V 7.6.15.9.2	N/A	N/A
Broadband Preamplifier (1GHz~18GHz)	SCHWARZBECK	BBV9718	305	May 08,22
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Mar. 13,22
Test Software	ADT	ADT_Radiated_V 7.6.15.9.2	N/A	N/A
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	N/A

NOTES:

1. The test was performed in 966 Chamber.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
4. Test Firm Registration Number: 749762.
5. Designation Number: CN1174

4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 1.5 meters(above 1GHz) and 0.8 meters(below 1GHz) above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. For below 1GHz was used bilog antenna, and above 1GHz was used horn antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the center of the loop shall be 1m above the ground.
- g. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

NOTES:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz(Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The testing of the EUT was performed on all 3 orthogonal axes; the worst-case test configuration was reported on the file test setup photo.

4.1.4 DEVIATION FROM TEST STANDARD


No deviation.

4.1.5 TEST SETUP

Below 30MHz test setup




Below 1GHz test setup



Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).

Above 1GHz test setup



Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.

4.1.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA:

Left Earbud:


GFSK DH5

CHANNEL	Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTIO N FACTOR (dB/m)
1	30.00	14.39 QP	40.00	-25.61	1.00 H	233	27.39	-13.00
2	141.92	10.95 QP	43.50	-32.55	1.00 H	245	29.14	-18.19
3	353.33	13.34 QP	46.00	-32.66	1.00 H	217	28.38	-15.04
4	468.37	16.76 QP	46.00	-29.24	1.00 H	183	28.60	-11.84
5	552.31	20.40 QP	46.00	-25.60	1.00 H	193	28.94	-8.54
6	645.58	20.47 QP	46.00	-25.53	1.00 H	207	28.39	-7.92

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. 9KHz~30MHz have been test and test data more than 20dB margin.
5. Margin value = Emission level – Limit value




CHANNEL	Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTIO N FACTOR (dB/m)
1	30.00	15.34 QP	40.00	-24.66	1.00 V	316	28.34	-13.00
2	132.60	18.77 QP	43.50	-24.73	1.00 V	304	37.77	-19.00
3	261.62	12.65 QP	46.00	-33.35	1.00 V	278	29.18	-16.53
4	399.97	15.10 QP	46.00	-30.90	1.00 V	266	28.48	-13.38
5	549.20	19.25 QP	46.00	-26.75	1.00 V	294	27.94	-8.69
6	631.59	20.17 QP	46.00	-25.83	1.00 V	256	28.08	-7.91

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. 9KHz~30MHz have been test and test data more than 20dB margin.
5. Margin value = Emission level – Limit value



Right Earbud:


GFSK DH5

CHANNEL	Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTIO N FACTOR (dB/m)
1	31.55	17.01 QP	40.00	-22.99	1.00 H	263	30.52	-13.51
2	141.92	11.71 QP	43.50	-31.79	1.00 H	276	29.90	-18.19
3	333.12	13.89 QP	46.00	-32.11	1.00 H	286	29.61	-15.72
4	468.37	18.73 QP	46.00	-27.27	1.00 H	295	30.57	-11.84
5	588.06	20.14 QP	46.00	-25.86	1.00 H	304	29.19	-9.05
6	696.88	21.57 QP	46.00	-24.43	1.00 H	314	29.72	-8.15

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. 9KHz~30MHz have been test and test data more than 20dB margin.
5. Margin value = Emission level – Limit value




CHANNEL	Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTIO N FACTOR (dB/m)
1	31.55	17.01 QP	40.00	-22.99	1.00 V	180	30.52	-13.51
2	141.92	11.76 QP	43.50	-31.74	1.00 V	180	29.95	-18.19
3	294.26	12.85 QP	46.00	-33.15	1.00 V	180	29.40	-16.55
4	468.37	18.73 QP	46.00	-27.27	1.00 V	180	30.57	-11.84
5	552.31	21.25 QP	46.00	-24.75	1.00 V	180	29.79	-8.54
6	626.92	20.91 QP	46.00	-25.09	1.00 V	180	29.08	-8.17

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. 9KHz~30MHz have been test and test data more than 20dB margin.
5. Margin value = Emission level – Limit value



ABOVE 1GHz DATA

Left Earbud:

BT_GFSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	51.24 PK	74.00	-22.76	1.00 H	158	45.67	5.57
2	2390.00	40.16 AV	54.00	-13.84	1.00 H	158	34.59	5.57
3	*2402.00	104.36 PK			1.00 H	158	98.77	5.59
4	*2402.00	103.32 AV			1.00 H	158	97.73	5.59
5	4804.00	58.64 PK	74.00	-15.36	1.00 H	0	47.71	10.93
6	4804.00	43.29 AV	54.00	-10.71	1.00 H	0	32.36	10.93
7	#7206.00	59.32 PK	74.00	-14.68	1.00 H	0	41.54	17.78
8	#7206.00	44.55 AV	54.00	-9.45	1.00 H	0	26.77	17.78
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	48.92 PK	74.00	-25.08	1.00 V	17	43.35	5.57
2	2390.00	37.94 AV	54.00	-16.06	1.00 V	17	32.37	5.57
3	*2402.00	99.65 PK			1.00 V	17	94.06	5.59
4	*2402.00	98.93 AV			1.00 V	17	93.34	5.59
5	4804.00	57.36 PK	74.00	-16.64	1.00 V	0	46.43	10.93
6	4804.00	42.15 AV	54.00	-11.85	1.00 V	0	31.22	10.93
7	#7206.00	58.33 PK	74.00	-15.67	1.00 V	0	40.55	17.78
8	#7206.00	43.26 AV	54.00	-10.74	1.00 V	0	25.48	17.78

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	100.75 PK			1.00 H	163	95.10	5.65
2	*2441.00	100.02 AV			1.00 H	163	94.37	5.65
3	4882.00	60.25 PK	74.00	-13.75	1.00 H	0	48.99	11.26
4	4882.00	45.63 AV	54.00	-8.37	1.00 H	0	34.37	11.26
5	7323.00	61.34 PK	74.00	-12.66	1.00 H	0	43.14	18.20
6	7323.00	45.93 AV	54.00	-8.07	1.00 H	0	27.73	18.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	100.25 PK			1.00 V	25	94.60	5.65
2	*2441.00	99.74 AV			1.00 V	25	94.09	5.65
3	4882.00	59.81 PK	74.00	-14.19	1.00 V	0	48.55	11.26
4	4882.00	44.51 AV	54.00	-9.49	1.00 V	0	33.25	11.26
5	7323.00	59.84 PK	74.00	-14.16	1.00 V	0	41.64	18.20
6	7323.00	44.53 AV	54.00	-9.47	1.00 V	0	26.33	18.20

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	102.43 PK			1.00 H	90	96.71	5.72
2	*2480.00	101.51 AV			1.00 H	90	95.79	5.72
3	2483.50	51.13 PK	74.00	-22.87	1.00 H	90	45.39	5.74
4	2483.50	39.92 AV	54.00	-14.08	1.00 H	90	34.18	5.74
5	4960.00	59.05 PK	74.00	-14.95	1.00 H	0	47.45	11.60
6	4960.00	43.58 AV	54.00	-10.42	1.00 H	0	31.98	11.60
7	7440.00	60.26 PK	74.00	-13.74	1.00 H	0	41.65	18.61
8	7440.00	45.39 AV	54.00	-8.61	1.00 H	0	26.78	18.61
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	99.79 PK			1.00 V	183	94.07	5.72
2	*2480.00	99.22 AV			1.00 V	183	93.50	5.72
3	2483.50	50.16 PK	74.00	-23.84	1.00 V	183	44.42	5.74
4	2483.50	39.27 AV	54.00	-14.73	1.00 V	183	33.53	5.74
5	4960.00	58.13 PK	74.00	-15.87	1.00 V	0	46.53	11.60
6	4960.00	42.55 AV	54.00	-11.45	1.00 V	0	30.95	11.60
7	7440.00	59.36 PK	74.00	-14.64	1.00 V	0	40.75	18.61
8	7440.00	44.25 AV	54.00	-9.75	1.00 V	0	25.64	18.61

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

BT_8DPSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	51.16 PK	74.00	-22.84	1.00 H	55	45.59	5.57
2	2390.00	40.05 AV	54.00	-13.95	1.00 H	55	34.48	5.57
3	*2402.00	104.29 PK			1.00 H	55	98.70	5.59
4	*2402.00	103.22 AV			1.00 H	55	97.63	5.59
5	4804.00	58.63 PK	74.00	-15.37	1.00 H	0	47.70	10.93
6	4804.00	43.15 AV	54.00	-10.85	1.00 H	0	32.22	10.93
7	#7206.00	59.14 PK	74.00	-14.86	1.00 H	0	41.36	17.78
8	#7206.00	44.26 AV	54.00	-9.74	1.00 H	0	26.48	17.78
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	48.57 PK	74.00	-25.43	1.00 V	177	43.00	5.57
2	2390.00	37.25 AV	54.00	-16.75	1.00 V	177	31.68	5.57
3	*2402.00	99.28 PK			1.00 V	177	93.69	5.59
4	*2402.00	98.64 AV			1.00 V	177	93.05	5.59
5	4804.00	57.15 PK	74.00	-16.85	1.00 V	0	46.22	10.93
6	4804.00	41.98 AV	54.00	-12.02	1.00 V	0	31.05	10.93
7	#7206.00	58.11 PK	74.00	-15.89	1.00 V	0	40.33	17.78
8	#7206.00	42.89 AV	54.00	-11.11	1.00 V	0	25.11	17.78

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	100.12 PK			1.00 H	66	94.47	5.65
2	*2441.00	99.84 AV			1.00 H	66	94.19	5.65
3	4882.00	58.35 PK	74.00	-15.65	1.00 H	0	47.09	11.26
4	4882.00	44.27 AV	54.00	-9.73	1.00 H	0	33.01	11.26
5	7323.00	60.25 PK	74.00	-13.75	1.00 H	0	42.05	18.20
6	7323.00	45.94 AV	54.00	-8.06	1.00 H	0	27.74	18.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	99.89 PK			1.00 V	18	94.24	5.65
2	*2441.00	99.36 AV			1.00 V	18	93.71	5.65
3	4882.00	57.69 PK	74.00	-16.31	1.00 V	0	46.43	11.26
4	4882.00	43.26 AV	54.00	-10.74	1.00 V	0	32.00	11.26
5	7323.00	59.28 PK	74.00	-14.72	1.00 V	0	41.08	18.20
6	7323.00	45.69 AV	54.00	-8.31	1.00 V	0	27.49	18.20

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	102.25 PK			1.00 H	255	96.53	5.72
2	*2480.00	101.34 AV			1.00 H	255	95.62	5.72
3	2483.50	50.93 PK	74.00	-23.07	1.00 H	255	45.19	5.74
4	2483.50	39.36 AV	54.00	-14.64	1.00 H	255	33.62	5.74
5	4960.00	59.84 PK	74.00	-14.16	1.00 H	0	48.24	11.60
6	4960.00	44.28 AV	54.00	-9.72	1.00 H	0	32.68	11.60
7	7440.00	60.25 PK	74.00	-13.75	1.00 H	0	41.64	18.61
8	7440.00	45.33 AV	54.00	-8.67	1.00 H	0	26.72	18.61
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	100.16 PK			1.00 V	135	94.44	5.72
2	*2480.00	99.27 AV			1.00 V	135	93.55	5.72
3	2483.50	49.69 PK	74.00	-24.31	1.00 V	135	43.95	5.74
4	2483.50	39.15 AV	54.00	-14.85	1.00 V	135	33.41	5.74
5	4960.00	58.22 PK	74.00	-15.78	1.00 V	0	46.62	11.60
6	4960.00	43.69 AV	54.00	-10.31	1.00 V	0	32.09	11.60
7	7440.00	59.58 PK	74.00	-14.42	1.00 V	0	40.97	18.61
8	7440.00	44.28 AV	54.00	-9.72	1.00 V	0	25.67	18.61

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

Right Earbud:

BT_GFSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	52.38 PK	74.00	-21.62	1.00 H	298	46.81	5.57
2	2390.00	37.24 AV	54.00	-16.76	1.00 H	298	31.67	5.57
3	*2402.00	103.68 PK			1.00 H	298	98.09	5.59
4	*2402.00	102.89 AV			1.00 H	298	97.30	5.59
5	4804.00	57.35 PK	74.00	-16.65	1.00 H	0	46.42	10.93
6	4804.00	42.69 AV	54.00	-11.31	1.00 H	0	31.76	10.93
7	#7206.00	58.39 PK	74.00	-15.61	1.00 H	0	40.61	17.78
8	#7206.00	43.25 AV	54.00	-10.75	1.00 H	0	25.47	17.78
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	52.99 PK	74.00	-21.01	1.00 V	159	47.42	5.57
2	2390.00	37.72 AV	54.00	-16.28	1.00 V	159	32.15	5.57
3	*2402.00	105.86 PK			1.00 V	159	100.27	5.59
4	*2402.00	105.20 AV			1.00 V	159	99.61	5.59
5	4804.00	58.35 PK	74.00	-15.65	1.00 V	0	47.42	10.93
6	4804.00	43.19 AV	54.00	-10.81	1.00 V	0	32.26	10.93
7	#7206.00	59.63 PK	74.00	-14.37	1.00 V	0	41.85	17.78
8	#7206.00	44.19 AV	54.00	-9.81	1.00 V	0	26.41	17.78

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	103.34 PK			1.00 H	199	97.69	5.65
2	*2441.00	103.05 AV			1.00 H	199	97.40	5.65
3	4882.00	56.25 PK	74.00	-17.75	1.00 H	0	44.99	11.26
4	4882.00	42.74 AV	54.00	-11.26	1.00 H	0	31.48	11.26
5	7323.00	57.53 PK	74.00	-16.47	1.00 H	0	39.33	18.20
6	7323.00	43.57 AV	54.00	-10.43	1.00 H	0	25.37	18.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	105.11 PK			1.00 V	54	99.46	5.65
2	*2441.00	104.68 AV			1.00 V	54	99.03	5.65
3	4882.00	57.65 PK	74.00	-16.35	1.00 V	0	46.39	11.26
4	4882.00	43.59 AV	54.00	-10.41	1.00 V	0	32.33	11.26
5	7323.00	58.39 PK	74.00	-15.61	1.00 V	0	40.19	18.20
6	7323.00	44.06 AV	54.00	-9.94	1.00 V	0	25.86	18.20

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	102.14 PK			1.00 H	205	96.42	5.72
2	*2480.00	101.93 AV			1.00 H	205	96.21	5.72
3	2483.50	51.59 PK	74.00	-22.41	1.00 H	205	45.85	5.74
4	2483.50	36.84 AV	54.00	-17.16	1.00 H	205	31.10	5.74
5	4960.00	56.58 PK	74.00	-17.42	1.00 H	0	44.98	11.60
6	4960.00	42.64 AV	54.00	-11.36	1.00 H	0	31.04	11.60
7	7440.00	57.85 PK	74.00	-16.15	1.00 H	0	39.24	18.61
8	7440.00	43.05 AV	54.00	-10.95	1.00 H	0	24.44	18.61
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	104.25 PK			1.00 V	154	98.53	5.72
2	*2480.00	103.78 AV			1.00 V	154	98.06	5.72
3	2483.50	52.36 PK	74.00	-21.64	1.00 V	154	46.62	5.74
4	2483.50	37.25 AV	54.00	-16.75	1.00 V	154	31.51	5.74
5	4960.00	57.36 PK	74.00	-16.64	1.00 V	0	45.76	11.60
6	4960.00	43.59 AV	54.00	-10.41	1.00 V	0	31.99	11.60
7	7440.00	58.39 PK	74.00	-15.61	1.00 V	0	39.78	18.61
8	7440.00	43.59 AV	54.00	-10.41	1.00 V	0	24.98	18.61

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

BT_8DPSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	51.69 PK	74.00	-22.31	1.00 H	188	46.12	5.57
2	2390.00	36.58 AV	54.00	-17.42	1.00 H	188	31.01	5.57
3	*2402.00	102.59 PK			1.00 H	188	97.00	5.59
4	*2402.00	101.47 AV			1.00 H	188	95.88	5.59
5	4804.00	57.59 PK	74.00	-16.41	1.00 H	0	46.66	10.93
6	4804.00	43.19 AV	54.00	-10.81	1.00 H	0	32.26	10.93
7	#7206.00	58.64 PK	74.00	-15.36	1.00 H	0	40.86	17.78
8	#7206.00	44.16 AV	54.00	-9.84	1.00 H	0	26.38	17.78
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	52.34 PK	74.00	-21.66	1.00 V	58	46.77	5.57
2	2390.00	37.05 AV	54.00	-16.95	1.00 V	58	31.48	5.57
3	*2402.00	103.47 PK			1.00 V	58	97.88	5.59
4	*2402.00	103.05 AV			1.00 V	58	97.46	5.59
5	4804.00	58.44 PK	74.00	-15.56	1.00 V	0	47.51	10.93
6	4804.00	44.36 AV	54.00	-9.64	1.00 V	0	33.43	10.93
7	#7206.00	59.35 PK	74.00	-14.65	1.00 V	0	41.57	17.78
8	#7206.00	45.26 AV	54.00	-8.74	1.00 V	0	27.48	17.78

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	103.25 PK			1.00 H	15	97.60	5.65
2	*2441.00	102.87 AV			1.00 H	15	97.22	5.65
3	4882.00	57.18 PK	74.00	-16.82	1.00 H	0	45.92	11.26
4	4882.00	43.65 AV	54.00	-10.35	1.00 H	0	32.39	11.26
5	7323.00	58.74 PK	74.00	-15.26	1.00 H	0	40.54	18.20
6	7323.00	44.06 AV	54.00	-9.94	1.00 H	0	25.86	18.20
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	105.13 PK			1.00 V	293	99.48	5.65
2	*2441.00	104.75 AV			1.00 V	293	99.10	5.65
3	4882.00	58.59 PK	74.00	-15.41	1.00 V	0	47.33	11.26
4	4882.00	44.18 AV	54.00	-9.82	1.00 V	0	32.92	11.26
5	7323.00	59.64 PK	74.00	-14.36	1.00 V	0	41.44	18.20
6	7323.00	45.18 AV	54.00	-8.82	1.00 V	0	26.98	18.20

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	101.59 PK			1.00 H	29	95.87	5.72
2	*2480.00	101.24 AV			1.00 H	29	95.52	5.72
3	2483.50	51.26 PK	74.00	-22.74	1.00 H	29	45.52	5.74
4	2483.50	36.45 AV	54.00	-17.55	1.00 H	29	30.71	5.74
5	4960.00	57.24 PK	74.00	-16.76	1.00 H	0	45.64	11.60
6	4960.00	43.02 AV	54.00	-10.98	1.00 H	0	31.42	11.60
7	7440.00	58.35 PK	74.00	-15.65	1.00 H	0	39.74	18.61
8	7440.00	43.93 AV	54.00	-10.07	1.00 H	0	25.32	18.61
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	104.36 PK			1.00 V	213	98.64	5.72
2	*2480.00	103.58 AV			1.00 V	213	97.86	5.72
3	2483.50	52.36 PK	74.00	-21.64	1.00 V	213	46.62	5.74
4	2483.50	37.24 AV	54.00	-16.76	1.00 V	213	31.50	5.74
5	4960.00	58.63 PK	74.00	-15.37	1.00 V	0	47.03	11.60
6	4960.00	44.51 AV	54.00	-9.49	1.00 V	0	32.91	11.60
7	7440.00	59.81 PK	74.00	-14.19	1.00 V	0	41.20	18.61
8	7440.00	45.03 AV	54.00	-8.97	1.00 V	0	26.42	18.61

REMARKS:


1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

4.2 NUMBER OF HOPPING FREQUENCY USED

4.2.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 channels frequencies, and should be equally spaced.

4.2.2 TEST SETUP



4.2.3 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
Power Meter	Anritsu	ML2495A	1139001	Feb. 24,22
Power Sensor	Anritsu	MA2411B	1531155	Feb. 24,22
Digital Multimeter	FLUKE	15B	A1220010DG	N/A
Humid & Temp Programmable Tester	Haida	HD-225T	110807201	Nov. 03,21
Oscilloscope	Agilent	DSO9254A	MY51260160	Aug. 10,22
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV40	101094	Feb. 24,22
Signal Generator	Agilent	N5183A	MY50140980	Aug. 10,22
MXG-B RF Vector Signal Generator	Keysight	N5182B	MY56200288	Sep. 04,21
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	N/A
Attenuator	MINI	BW-S10W2+	S130129FGE2	N/A
DC Source	Keysight	E3642A	MY56146098	N/A

NOTES:

1. The test was performed in RF Oven room.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

4.2.4 TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Set the SA on Max Hold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- d. Set the SA on View mode and then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were completed.



4.2.5 DEVIATION FROM TEST STANDARD

No deviation.



4.2.6 TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.

GFSK



8DPSK




4.3 DWELL TIME ON EACH CHANNEL

4.3.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.3.2 TEST SETUP



4.3.3 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.3.4 TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- e. Repeat above procedures until all different time-slot modes have been completed.

4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

4.3.6 TEST RESULTS

GFSK


Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
DH1	79	31.6	5	50	316.00	0.45	142.20	400	PASS
DH3	79	31.6	5	25	158.00	1.73	273.34	400	PASS
DH5	79	31.6	5	17	107.44	3.02	324.47	400	PASS

8DPSK


Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
3DH1	79	31.6	5	51	322.32	0.52	167.61	400	PASS
3DH3	79	31.6	5	27	170.64	1.73	295.21	400	PASS
3DH5	79	31.6	5	17	107.44	2.96	318.02	400	PASS

NOTE: Test plots of the transmitting time slot are shown on next page.

GFSK



8DPSK




4.4 CHANNEL BANDWIDTH

4.4.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.4.4 TEST PROCEDURE

- Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- Repeat above procedures until all frequencies measured were complete.

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 EUT OPERATING CONDITION


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.4.7 TEST RESULTS


GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	0.957
39	2441	0.960
78	2480	0.958


CH 0



CH 39




CH 78




8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.30
39	2441	1.30
78	2480	1.30


CH 0



CH 39



CH 78




4.5 HOPPING CHANNEL SEPARATION

4.5.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.5.4 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.


4.5.6 TEST RESULTS

GFSK


CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.00	0.957	0.638	PASS
39	2441	1.00	0.960	0.640	PASS
78	2480	1.00	0.958	0.639	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.


CH 0



CH 39



CH 78




8DPSK


CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.00	1.30	0.867	PASS
39	2441	1.00	1.30	0.867	PASS
78	2480	1.00	1.30	0.867	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.


CH 0



CH 39



CH 78




4.6 CONDUCTED OUTPUT POWER

4.6.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

The Maximum Output Power Measurement is 0.125W.

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.6.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor and set the detector to PEAK. Record the power level.

An average power sensor was used on the output port of the EUT. A power meter was used to read the response of the average power sensor and set the detector to AVERAGE. Record the power level.

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

4.6.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.6.7 TEST RESULTS

MAXIMUM PEAK OUTPUT POWER

Left Earbud:

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (W)	PASS/FAIL
0	2402	11.94	15.631	0.125	PASS
39	2441	12.54	17.947	0.125	PASS
78	2480	12.73	18.750	0.125	PASS

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (W)	PASS/FAIL
0	2402	11.75	14.962	0.125	PASS
39	2441	12.13	16.331	0.125	PASS
78	2480	12.40	17.378	0.125	PASS

Right Earbud:

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (W)	PASS/FAIL
0	2402	11.46	13.996	0.125	PASS
39	2441	11.82	15.205	0.125	PASS
78	2480	12.04	15.996	0.125	PASS

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (W)	PASS/FAIL
0	2402	11.03	12.677	0.125	PASS
39	2441	11.44	13.932	0.125	PASS
78	2480	11.65	14.622	0.125	PASS

AVERAGE OUTPUT POWER(FOR REFERENCE)

Left Earbud:

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)
0	2402	10.92	12.359
39	2441	11.40	13.804
78	2480	11.61	14.488

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)
0	2402	8.22	6.637
39	2441	8.54	7.145
78	2480	8.93	7.816

Right Earbud:

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)
0	2402	10.57	11.402
39	2441	10.70	11.749
78	2480	10.92	12.359

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)
0	2402	7.01	5.023
39	2441	7.41	5.508
78	2480	7.70	5.888

4.7 OUT OF BAND EMISSION MEASUREMENT

4.7.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz RBW).

4.7.2 TEST INSTRUMENTS

Refer to section 4.2.3 to get information of above instrument.

4.7.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. of Spectrum Analyzer was set RBW to 100 kHz and VBW to 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. Detector = PEAK and Trace mode = Max Hold. The band edges was measured and recorded.

4.7.4 DEVIATION FROM TEST STANDARD

No deviation.

4.7.5 EUT OPERATING CONDITION


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.7.6 TEST RESULTS


The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.

GFSK


Low Channel



High Channel




8DPSK




GFSK

Hopping on Low Channel




Hopping on High Channel




8DPSK

Hopping on Low Channel



Hopping on High Channel



5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---