




Test plot as follows:





802.11n(HT40)

802.11ac(HT20)




CH38

CH36







CH46

CH40



CH48



4.6 Minimum Emission Bandwidth (6dB Bandwidth)

Limit

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Test Procedure

1. Set resolution bandwidth (RBW) = 100 kHz
2. Set the video bandwidth 3 x RBW.
3. Detector = Peak.
4. Trace mode = Max hold.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Test Configuration



Test Results


Type	Bands	Channel	6dB Bandwidth (MHz)	Limit (KHz)	Result
802.11a	U-NII 3	149	16.28	≥500KHz	Pass
		157	16.00		
		165	16.44		
802.11n(HT20)	U-NII 3	149	17.28		
		157	16.92		
		165	17.56		
802.11n(HT40)	U-NII 3	151	35.04		
		159	32.64		
802.11ac(HT20)	U-NII 3	149	17.60		
		157	17.32		
		165	17.72		
802.11ac(HT40)	U-NII 3	151	36.24		
		159	34.40		
802.11ac(HT80)	U-NII 3	155	75.04		

Test plot as follows:





802.11n(HT40)

802.11ac(HT20)




CH151

CH149



CH159



CH157



CH165


802.11ac(HT40)

802.11ac(HT80)



CH151

CH155




CH159

4.7 Frequency Stability

LIMIT

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.

TEST CONFIGURATION



TEST PROCEDURE

Frequency Stability under Temperature Variations:

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -30°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.

Frequency Stability under Voltage Variations:

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ($\pm 15\%$) and endpoint, record the maximum frequency change.



TEST RESULTS

Record worst case as below:

Reference Frequency: 802.11ac channel=36 frequency=5180MHz					
Voltage (V)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
12.00	-30	126.54	0.0244	Within the band of operation	Pass
	-20	133.82	0.0258		
	-10	127.96	0.0247		
	0	124.35	0.0240		
	10	136.27	0.0263		
	20	135.84	0.0262		
	30	130.42	0.0252		
	40	141.68	0.0274		
	50	137.95	0.0266		
13.2	25	129.43	0.0250	Within the band of operation	Pass
10.8	25	135.82	0.0262		

Reference Frequency: 802.11ac channel=149 frequency=5745MHz					
Voltage (V)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		Hz	ppm		
12.00	-30	137.29	0.0239	Within the band of operation	Pass
	-20	142.08	0.0247		
	-10	136.42	0.0237		
	0	129.76	0.0226		
	10	133.81	0.0233		
	20	137.65	0.0240		
	30	128.36	0.0223		
	40	139.43	0.0243		
	50	144.57	0.0252		
13.2	25	137.42	0.0239	Within the band of operation	Pass
10.8	25	135.88	0.0237		

5 Test Setup Photos of the EUT



6 Photos of the EUT

Reference to the test report No. GRCTR230802008-01.

***** End of Report *****